

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE DEPENDENT RESURVEY

OF A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 13, 14, 23, 25 and 26

AND

THE METES-AND-BOUNDS SURVEYS, OF THE

ADMINISTRATIVE BOUNDARY OF THE GILA BEND AIR FORCE AUXILLARY FIELD

TOWNSHIP 6 SOUTH, RANGE 5 WEST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Gordon R. Bubel, Cadastral Surveyor

Under Special Instructions dated September 21, 2020, approved September 21, 2020, which provided for the surveys included under Group No. 1210, and assignment instructions dated September 21, 2020.

Survey commenced September 22, 2020

Survey completed October 21, 2020

INDEX DIAGRAM

TOWNSHIP 6 SOUTH RANGE 5 WEST
GILA & SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14 7	13
19	20	21	22	23	24
30	29	28	27 5	6 26 4	25
31	32	33	34	35	36

Subdivision of Section 13	Pages 8-9
Subdivision of Section 14	Pages 9-13
Subdivision of Section 23	Pages 13-14
Subdivision of Section 25	Pages 14-15
Subdivision of Section 26	Pages 16-17
Metes-and-Bounds Survey	Pages 18-23
Composite Description Administrative Boundary	Pages 24-25

T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe: The dependent resurvey of a portion of the subdivisional lines. The subdivision of sections 13, 14, 23, 25 and 26. The metes-and-bounds surveys of the administrative boundary of the Gila Bend Air Force Auxiliary Field, Township 6 South, Range 5 West, Gila and Salt River Meridian, Arizona.

The survey history is as follows: Daniel Drummond, U.S. Deputy Surveyor, surveyed the subdivisional lines in 1891.

The land status history is as follows: On Nov. 4, 1941, section 24 was leased to private parties as a municipal airfield. Executive Order No. 9104, issued on March 18, 1942, withdrew all the unpatented lands in the south 24 sections of the township, with the exception of section 24, for an aerial gunnery range. On August 6, 1942, via Executive Order No. 9215, section 24 was withdrawn for military purposes. Public Land Order No. 512, issued on August 6, 1948, revoked Executive Order No. 9104. Public Land Order No. 652, issued on June 26, 1950, withdrew for Air Force military purposes, the same lands withdrawn under Executive Order No. 9104. Public Law 99-606, effective November 6, 1986, established the Barry M. Goldwater Air Force Range. In this township it included all the lands in Public Land Order No. 652, plus section 24.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated September 21, 2020 for Group Number 1210, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R10-2 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from first order U.S. Coast and Geodetic Survey control station RUBY 1977, as published by the National Geodetic Survey, NAD 83 (1992).

The horizontal position of the corner of sections 25, 26, 35 and 36, is as follows:

Latitude: 32°52'08.611" N. Longitude: 112°43'58.989" W

T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

The horizontal position of the 1/4 section corner of sections 14 and 15, is as follows:

Latitude: 32°54'19.299" N. Longitude: 112°45'00.218" W.

The mean magnetic declination is 10 1/4° E.

**Dependent Resurvey of Portions of the Subdivisional Lines,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Daniel Drummond, in 1891

Beginning at the cor. of secs. 25, 26, 35 and 36, reestablished by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011. Monumented with a rebar, 3/4 in. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 2 ft. base, to top. An attached 3 1/4 ins. diam., aluminum cap is mkd. T6N R5W S26 S25 S35 S36 2011 RLS 47302. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.

A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1.5 lks. N of the cor.

N. 0°55' E., bet. secs. 25 and 26.

Within the Barry M. Goldwater Air Force Range, (BMGAFR).

Through creosote, with many northerly draining washes.

40.14

Point accepted for the 1/4 sec. cor. of secs. 25 and 26, on the administrative boundary bet. BMGAFR and Gila Bend Air Force Auxiliary Field, (GBAFAP), origin unknown. Monumented with a rusted iron pipe, 1 1/2 ins. diam., firmly set, projecting 3 ins. above ground. Accepted as the best available evidence of the orig. cor.

Hammer a 2 ins. diam. brass tablet, with 1 1/2 ins. x 1 1/4 ins. long stem, within the iron pipe. Brass tablet is mkd.

T 6 S R 5 W
1/4
S 26 | S 25

2020

Set a steel fence post 1 lk. S. of the cor.

Dependent Resurvey of Portions of the Subdivisional Lines,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in a rusted 4 strand barbed wire fence.</p> <p>From this cor. point, a rebar 3/4 in. diam., firmly set, projecting 5 in. above ground, bears N. 88°35' E., 21.3 lks. dist. An attached 3 1/4 ins. diam. aluminum cap is mkd. T6S R5W 1/4 S26 S25 2011 RLS 47302. According to the record of survey, filed in the Maricopa County Recorder's Office in book 1088, page 49, executed by Vernen Kalani Lee in 2011, a 1/2 in. diam., rebar was found at this location and remonumented as described above. No record of this monument was found, and it is not harmoniously related to found orig. monuments. Not utilized in the course of this resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Within the GBAFAF.</p>
40.15	<p>The cor. of secs. 23, 24, 25 and 26, reestablished by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011. Monumented with a brass disk, 3 ins. diam., cemented in the sidewalk of 4th St. Brass disk is mkd. T6S R5W S23 S24 S26 S25 2011 RLS 47302. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 26, 27, 34 and 35. Monumented with a granite stone, 8 x 6 ins., firmly set, projecting 5 ins. above ground, with 2 grooves on the E. face and 1 groove on the S. face.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>N. 0°11' E., bet. secs. 26 and 27.</p> <p>Within the BMGAFR.</p> <p>Through creosote, with many northerly draining washes.</p>
40.15	<p>Point accepted for the 1/4 sec. cor. of secs. 26 and 27. Monumented with a granite stone, 12 x 7 ins., firmly set, projecting 5 ins. above ground, with an inverted 4 on the W. face, origin unknown. The original monument was a palo verde tree. Accepted as a the best available evidence of the orig. cor. position.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1.5 lks. N of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°11' E., beginning new measurement.</p>

Dependent Resurvey of Portions of the Subdivisional Lines,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.10	<p>The cor. of secs. 22, 23, 26 and 27. Monumented with a volcanic stone, 10 x 5 ins., firmly set, projecting 5 ins. above ground, in a collar of stone, with 2 grooves on the E. face and 2 groove on the S. face.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1 lk. N. of the cor.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°33' W., bet. secs. 23 and 26.</p> <p>Within the GBAFAF.</p>
39.87	<p>The 1/4 sec. cor. of secs. 23 and 26, reestablished by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011. Monumented with a rebar, 3/4 in. diam., firmly set, projecting 6 ins. above ground. An attached 3 1/4 ins. diam., aluminum cap is mkd. T6N R5W 1/4 S23 S26 2011 RLS 47302. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 5 W</p> <p>S 23</p> <p>1/4 ———</p> <p>S 26</p> <p>2020</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the aluminum cap at the base of the stainless steel post, bury the rebar alongside.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1 lks. E. of the cor.</p> <p>Cor. is located within a 4 strand barbed wire fence, and beneath a single wire power line, bearing E. and W.</p> <hr/> <p>S. 89°33' E., beginning new measurement.</p> <p>Exit GBAFAF, enter BMGAFR.</p>

Dependent Resurvey of Portions of the Subdivisional Lines,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.34	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24, reestablished by Scott T. Burden, Arizona R.L.S. No. 13554 in 1995. Monumented with a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above ground, with attached metal wafer mkd. LS 13554. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 452, page 40.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1.5 lks. N. of the cor.</p> <p>S. 89°37' W., bet. secs. 14 and 23.</p> <p>Within the GBAFAF.</p>
39.98	<p>The 1/4 sec. cor. of secs. 14 and 23, reestablished by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011. Monumented with a rebar, 3/4 in. diam., firmly set, 4 ins. below ground. Attached 3 1/4 ins. diam., aluminum cap is mkd. T6N R5W 1/4 S14 S23 2011 RLS 47302. Accepted as a careful and faithful reestablishment of the orig. cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <p>Cor. is located beneath graveled road, 20 ft. wide, bears N. 35° E., curving westerly and S. 60° W.</p> <hr/> <p>S. 89°37' W., beginning new measurement.</p>
2.88	<p>Intersect a 4 strand barbed wire fence, on the administrative bdy. bet. GBAFAF and BMGAFR.</p> <p>From this point, an angle point in the metes-and-bounds survey of the administrative bdy. bet. GBAFAF and BMGAFR, bears N. 13°35' E., 6.30 chs. dist., hereinafter described.</p> <p>Continuing measurement within BMGAFR.</p>
12.20	<p>Intersect a 4 strand barbed wire fence, on the easterly right-of-way of Az. State Highway No. 85, bears N. 25° E. and S. 25° W.</p> <p>From this point, highway station number 2083+00, bears N. 25°14' E., 2.21 chs. dist. Monumented with a 2 x 1 in. wood hub, set flush, within the 4 strand barbed wire fence. A 4 in. angle iron, mkd. 2083+00 on a face and HWY R. of W. on opposite face, is located 2.1 ft. SSW of the hub.</p>

**Dependent Resurvey of Portions of the Subdivisional Lines,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same point, highway station number 1983+00, bears S. 25°14' W., 28.10 chs. dist. Monumented with a 2 x 1 in. wood hub, set flush, within the 4 strand barbed wire fence. A 4 in. angle iron, mkd. 1983+00 on a face and HWY R. of W. on opposite face, is located 2.2 ft. SSW of the hub.</p> <p>Continuing measurement, across Az. State Highway No. 85.</p>
17.24	<p>Intersect a 4 strand barbed wire fence, on the westerly right-of-way of Az. State Highway No. 85, bears N. 25° E. and S. 25° W.</p> <p>From this point, highway station number 2083+00, bears N. 25°14' E., 4.38 chs. dist. Monumented with a 2 x 1 in. wood hub, set flush, within the 4 strand barbed wire fence. A 4 in. angle iron, mkd. 2083+00 on a face and HWY R. of W. on opposite face, is located 1.8 ft. SSW of the hub.</p> <p>From this same point, highway station number 1983+00, bears S. 25°14' W., 25.99 chs. dist. Monumented with a 1 x 2 ins. wood hub, set flush, within a 4 strand barbed wire fence. A 4 in. angle iron, mkd. 1983+00 on a face and HWY R. of W. on opposite face, is located 2.4 ft. NNE of the hub.</p>
39.98	<p>The cor. of secs. 14, 15, 22 and 23. Monumented with a granite stone, 8 x 6 ins., firmly set, projecting 10 ins. above ground. Mkd. with 2 grooves on the E. face and 3 grooves on the S. face.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1 lks. N. of the cor.</p> <hr/> <p style="text-align: center;">Subdivision of Section 13, T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp. As described in the dependent resurvey of the W. bdy. of T. 6 S., R. 4 W., executed concurrently under this same group.</p> <p>From this cor. point, 1st order, U.S. Coast and Geodetic Survey triangulation station RUBY 1971, bears S. 9°57' E., 24.47 chs. dist. Monumented with a brass disk, 3 1/2 ins. diam., set in a 12 ins. diam. concrete cylinder, projecting 3 ins. above ground. Top is marked U.S. COAST & GEODETIC SURVEY RUBY 1971 TRIANGULATION STATION and a triangle.</p> <p>S. 89°40' W., on the E. and W. center line of sec. 13, identical with the administrative bdy. bet. BMGAFR and GBFAF.</p> <p>In and along a 4 strand barbed wire fence.</p>
26.72	<p>Point selected for a witness point.</p>

Subdivision of Section 13,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
53.44	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">W P T 6 S R 5 W S 13 C———C</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located within a 4 strand barbed wire fence, bears E. and W.</p> <p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
80.16	<p style="text-align: center;">W P T 6 S R 5 W C———C S 13</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located within a 4 strand barbed wire fence, bears E. and W.</p> <p>Point accepted for the 1/4 sec. cor. of secs. 13 and 14. Monumented with a capped iron pipe, 2 ins. diam., firmly set, projecting 18 ins. above ground, unknown origin. An aluminum washer, 1 1/2 ins. diam., mkd. LS 47302, is wired to the iron pipe.</p> <p>Wire to the pipe, a brass washer, 1 1/2 ins. diam., mkd. BLM 2020.</p> <p>Cor. is located in a 4 strand barbed wire fence, bearing E. and a woven wire fence, topped with 2 strands of barbed wire, bearing W.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">Subdivision of Section 14, T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 14 and 23, hereinbefore described.</p>

Subdivision of Section 14,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°13' W., on the N. and S. center line of sec. 14. Within the GBAFAF.
11.41	Intersect a slump block fence, 8 ft. high, on the administrative bdy. bet. GBAFAF and BMGAFR. From this point, an angle point in the metes-and-bounds survey of the administrative bdy. bet. GBAFAF and BMGAFR, bears S. 64°37' W., 7.3 lks. dist., hereinafter described. Continuing measurement within BMGAFR.
18.53	A rebar, 3/4 in. diam., firmly set, projecting 1 ins. above ground, with attached 3 1/4 ins. diam., alum. cap mkd. GBAF 2011 RLS 47302. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the railroad right-of-way. Not utilized in the course of this resurvey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.
18.55	Intersect the easterly right-of-way of Tucson, Cornelia and Gila Bend Railroad. From this point, an angle point at the intersection of fences and on the administrative boundary bet. GBAFAF and BMGAFR, bears N. 25°14' E., 13.9 lks. dist., hereinafter described. The railroad, is no longer in operation and the right-of-way fence in this portion has been removed to accommodate the main entrance to GBAFAF. Continuing measurement, within the R.O.W. of the Tucson, Cornelia and Gila Bend Railroad.
22.06	Single track railroad, bears N. 25° E. and S. 25° W.
25.59	Intersect a 4 strand barbed wire fence, on the easterly right-of-way of Az. State Highway No. 85, identical with the westerly right-of-way of Tucson, Cornelia and Gila Bend Railroad. From this point, highway station number 2030+00, bears N. 25°13' E., 14.72 chs. dist. Monumented with a 3 ins. diam., brass disk, set in a 6 ins. diam. concrete cylinder, projecting 1 ins. above ground. Disk is marked ARIZONA HIGHWAY DEPT. + ELEV. 798-16 STA 19. A 4 in. angle iron, mkd. 2030+00 on a face and HWY R. of W. on opposite face, is located 2.0 ft. SSW. Both located within the highway R.O.W. fence. From this same point, highway station number 2012+00, bears S. 25°13' W., 12.61 chs. dist. Monumented with a 3 ins. diam., brass disk, set in a 6 ins. diam. concrete cylinder, projecting 2 ins. above ground. Disk is marked ARIZONA HIGHWAY DEPT. ELEV. +

Subdivision of Section 14,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>STA 19. A 4 in. angle iron, leaning 16 ins. to the S., mkd. 2012+00 on a face and HWY R. of W. on opposite face, is located 2.0 ft. SSW. Both located within the highway R.O.W. fence. Continuing measurement, across Az. State Highway No. 85.</p>
36.17	<p>Intersect a 4 strand barbed wire fence, on the westerly right-of-way of Az. State Highway No. 85.</p> <p>From this point, highway station number 2030+00, bears N. 25°15' E., 5.15 chs. dist. Monumented with a 3 ins. diam., brass disk, set in a 6 ins. diam. concrete cylinder, projecting 2 ins. above ground. Disk is marked ARIZONA HIGHWAY DEPT. + ELEV. 794-93 STA 19. A 4 in. angle iron, mkd. 2030+00 on a face and HWY R. of W. on opposite face, is located 2.0 ft. NNE. Both located within the highway R.O.W. fence.</p> <p>From this same point, highway station number 2012+00, bears S. 25°15' W., 22.14 chs. dist. Monumented with a 3 ins. diam., brass disk, set in a 6 ins. diam. concrete cylinder, projecting 2 ins. above ground. Disk is marked ARIZONA HIGHWAY DEPT. ELEV. + STA 19. A 4 in. angle iron, mkd. 2012+00 on a face and HWY R. of W. on opposite face, is located 2.0 ft. SSW. Both located within the highway R.O.W. fence.</p>
40.08	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14.</p> <p>Not monumented.</p>
59.82	<p>The center N. 1/16 sec. cor. of sec. 14, established by Scott T. Burden, Arizona R.L.S. No. 13554. Monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with attached metal tag mkd. LS 13554. Accepted as a careful and faithful establishment of the cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 452, page 40.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located alongside and SE of the cor.</p> <p>Cor. is located alongside of a fence cor., with barbed wire fences extending N. and W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14, hereinbefore described.</p> <p>S. 89°40' W., on the E. and W. center line of sec. 13, identical with the administrative bdy. bet. BMGAFR and GBFAF.</p> <p>In and along a woven wire fence, topped with 2 strands of barbed wire.</p>

Subdivision of Section 14,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
29.93	<p>Point for an Angle Point on the administrative bdy. bet. BMGAFR and GBFAF, at the intersection of fences. Identical with the easterly right-of-way of Tucson, Cornelia and Gila Bend Railroad. Witnessed by an off plumb, 2 ins. angle iron, fence cor., cemented in place, leaning to the NW. With woven wire fences, topped with 2 strands of barbed wire, bearing E. and S. 25° W.</p> <p>Wire to the fence cor., a brass washer, 1 1/2 ins. diam., mkd. BLM 2020.</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 in. diam., set 21 ins. in the ground for a reference monument, bears N. 89°43' E., 15.0 ft. dist. with attached 2 ins. diam. brass cap mkd. RM T6S R5W S14 15.0 FT TO COR. AP 2020 and an arrow pointing to the cor. Located in a woven wire fence, topped with 2 strands of barbed wire, fence extends E. and W.</p> <p style="padding-left: 40px;">A rebar, 24 ins. long, 5/8 in. diam., set 20 ins. in the ground for a reference monument, bears S. 25°14' W., 15.0 ft. dist. with attached 2 ins. diam. brass cap mkd. RM T6S R5W S14 15.0 FT TO COR. AP 2020 and an arrow pointing to the cor. Located in a woven wire fence, topped with 2 strands of barbed wire, fence extends N. 25° E., and S. 25° W.</p> <p>From this cor. point, a rebar, 3/4 in. diam., firmly set, projecting 1 ins. above ground, bears S. 61 1/4° E., 1.0 lks. dist. An attached 3 1/4 ins. diam., aluminum cap is mkd. GBAF 2011 RLS 47302. Witnessed by fiberglass survey marker sign, 2 ins. wide, projecting 50 ins. above ground, set 1 lks. SE of the rebar. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the GBFAF bdy. Not utilized in the course of this survey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°39' W., beginning new measurement, exit GBFAF, enter BMGAFR.</p> <p>Within the R.O.W. of the Tucson, Cornelia and Gila Bend Railroad.</p>
1.68	Single track railroad, bears N. 25° E. and S. 25° W.
3.36	<p>Intersect a 4 strand barbed wire fence, on the easterly right-of-way of Az. State Highway No. 85, identical with the westerly right-of-way of Tucson, Cornelia and Gila Bend Railroad.</p> <p>From this point, highway station number 2044+97.80, bears N. 25°17' E., 21.34 chs. dist. Monumented with a 3 ins. diam.,</p>

Subdivision of Section 14,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>brass disk, set in a 6 ins. diam. concrete cylinder, projecting 2 ins. above ground. Disk is marked ARIZONA HIGHWAY DEPT. + ELEV. 794 66 STA 19. A 4 in. angle iron, mkd. 2044+97.80 on a face and HWY R. of W. on opposite face, is located 2.0 ft. SSW. Both located within the highway R.O.W. fence.</p> <p>From this same point, highway station number 2030+00, bears S. 25°17' W., 1.32 chs. dist., hereinbefore described.</p>
8.40	<p>Intersect a 4 strand barbed wire fence, on the westerly right-of-way of Az. State Highway No. 85.</p> <p>From this point, highway station number 2030+00, bears N. 25°14' E., 0.83 chs. dist., hereinbefore described.</p> <p>From this same point, highway station number 2012+00, bears S. 25°14' W., 26.47 chs. dist., hereinbefore described.</p>
10.26	<p>The point for the C 1/4 sec. cor. of sec. 14.</p>
49.96	<p>The 1/4 sec. cor. of secs. 14 and 15. Monumented with a granite stone, 12 x 9 ins., firmly set, projecting 7 ins. above ground, no marks visible.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 1 lks. N. of the cor.</p>
<hr/> <p>Subdivision of Section 23, T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 23 and 26, hereinbefore described.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 23.</p> <p>In and along a 4 strand barbed wire fence, on the administrative boundary bet. GBAFAF and BMGAFR.</p>
32.45	<p>Point for an Angle Point on the administrative bdy. bet. GBAFAF and BMGAFR, identical with a break in bearing of a barbed wire fence.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 20 ins. in the ground, seated in cement. Attach a 2 1/2 ins. diam. brass tablet, with a 1 1/2 ins. long stem, with tablet mkd.</p>
<p>T 6 S R 5 W</p> <p>S 23 AP</p> <p>2020</p>	

Subdivision of Section 23,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on the N. side of a fencepost, with 4 strand barbed wire fences extending S. and N. 9° W.</p> <p>Continuing measurement, within GBAFAF.</p>
39.60	Southerly terminus of dilapidated barbed wire fence, extends north.
80.34	The 1/4 sec. cor. of secs. 14 and 23, hereinbefore described.
<hr/> <p style="text-align: center;">Subdivision of Section 25, T. 6 N., R. 5 W., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp. As described in the dependent resurvey of the W. bdy of T. 6 S., R. 4 W., executed concurrently under this same group.</p> <p>S. 89°45' W. on the E. and W. center line of sec. 25.</p> <p>Across main runway, with GBAFAF.</p>
33.77	<p>Point for an Angle Point on the administrative bdy. bet. GBAFAF and BMGAFR, identical with the intersection of fences. Witnessed by an off plumb, 2 ins. angle iron, fence cor., cemented in place, leaning to the SW, with barbed wire fences extending E., S. and W.</p> <p>Wire a brass washer, 1 1/2 ins. diam., mkd BLM 2020 to the angle iron fence corner.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground for a reference monument, bears S. 0°06' W., 10.0 ft. dist. with brass cap mkd. RM T6S R5W S25 10.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends N. and S.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears S. 89°52' W., 10.0 ft. dist. with brass cap mkd. RM T6S R5W 10.0 FT TO COR. S25 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends E. and W.</p> <p>From this cor. point, a rebar, 3/4 in. diam., firmly set, projecting 1 ins. above ground, bears N. 48 1/4° W., 1.8 lks. dist. An attached 3 1/4 ins. diam., aluminum cap is mkd. GBAF 2011</p>

Subdivision of Section 25,
T. 6 N., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>RLS 47302. Witnessed by a fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, set 1 lks. NE. of the rebar. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the GBAFAF bdy. Not utilized in the course of this survey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°52' W., beginning new measurement.</p> <p>On the administrative bdy. bet. GBAFAF and BMGAFR, in and along a barbed wire fence.</p>
6.32	<p>The center 1/4 sec. cor. of sec. 25, established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011. Monumented with a rebar, 30 ins. long, 3/4 in. diam., firmly set, 25 ins. in the ground. An attached 3 1/4 ins. diam. aluminum cap is mkd. C 1/4 S25 2011 RLS 47302. Accepted as a careful and faithful establishment of the cor. position. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <p>Cor. is located on the N. side of a 4 strand barbed wire fence. Witnessed by a fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, located 1 lk. N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°46' W., beginning new measurement.</p> <p>On the administrative bdy. bet. GBAFAF and BMGAFR, in and along a 4 strand barbed wire fence.</p>
18.90	Graded road, 13 ft. wide, bears N. and S.
28.24	End of 4 strand barbed wire fence, begin woven wire fence, topped with 2 strands of barbed wire.
29.90	Quilotosa Wash, 40 ft. wide, 6 ft. deep, drains N. 10° W.
39.90	The 1/4 sec. cor. of secs. 25 and 26, hereinbefore described.
	<hr style="width: 20%; margin: 10px auto;"/>

Subdivision of Section 26,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Preliminary Statement: An internal document obtained from the USAF, entitled R/E OUT GRANT MAP, GILA BEND A.F. AUXILLARY FIELD, dated 30 SEP 85, contains a topographic survey and a resurvey of the GBAFAF boundary fence. The survey was executed by the 832 Engineering Squadron of Luke Air Force Base. Within the document, it can be demonstrated the center 1/4 sec. cor. of sec. 26, was established by extending the east and west center line of sec. 25, to the intersection with the extension of the north and south center line of sec. 23. The establishment of the center 1/4 sec. cor. of sec. 26, was prior to the 1985 resurvey. This is evidenced by the old fence lines and remnants of a prior fence, both erected prior to 1985. The fence line is also depicted within the USGS 7.5 min. quadrangle map entitled GILA BEND, ARIZ. 1973. In compliance with section 6-36, of the <u>Manual of Instructions for the Survey of the Public Lands of the United States, 2009</u>, the fence cor. representing the center 1/4 section cor. of sec. 26 is accepted.</p> <p>From the 1/4 sec. cor. of secs. 26 and 35. Monumented with a volcanic stone, 8 x 6 ins., firmly set, in a collar of stone, projecting 7 ins. above ground, mkd, 1/4 on the N. face. Remove the collar of stone, and raise a mound of stone 2 1/2 ft. base, 1 1/2 ft. high, N. of the cor.</p> <p>A fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, is located 3 lks. N. of the cor.</p> <p>N. 1°42' E., on the N. and S. center line of sec. 26, within BMGAFR.</p>
40.23	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection of woven wire fences, on the administrative bdy. bet. GBAFAF and BMGAFR. Witnessed by an off plumb, 2 ins. angle iron, fence cor., cemented in place, leaning to the SW. Accepted as a good faith location.</p> <p>Wire a brass washer, 1 1/2 ins. diam., mkd BLM 2020 to the angle iron fence corner.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 89°46' E., 15.0 ft. dist. with brass cap mkd. RM T6S R5W S26 15.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a woven wire fence, extends E. and W.</p>

Subdivision of Section 26,
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 0°04' W., 15.0 ft. dist. with brass cap mkd. RM T6S R5W S26 15.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a woven wire fence, extends N. and S.</p> <p>From this cor. point, a rebar, 3/4 in. diam., firmly set, projecting 5 ins. above ground, bears S. 50 1/2° W., 1.9 lks. dist. An attached 2 ins. diam., aluminum cap is mkd. T6S R5W C1/4 S26 RLS 47302 2011. Witnessed by a fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, set 1 lks. N. of the rebar. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the GBAFAF bdy. Not utilized in the course of this survey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p> <p>In and along a woven wire fence, topped with 2 strands of barbed wire.</p> <p>On the administrative boundary bet. GBAFAF and BMGAFR.</p>
39.99	<p>The 1/4 sec. cor. of secs. 23 and 26, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, hereinbefore described.</p> <p>S. 89°46' W., on the E. and W. center line of sec. 26.</p> <p>In and along a woven wire fence, topped with 2 strands of barbed wire.</p> <p>On the administrative boundary bet. GBAFAF and BMGAFR.</p>
39.78	<p>The center 1/4 sec. cor. of sec. 26.</p> <hr/> <p>S. 89°24' W., beginning new measurement.</p> <p>Within the BMGAFR.</p>
40.52	<p>The 1/4 sec. cor. of secs. 26 and 27, hereinbefore described.</p> <hr/>

Metes-and-Bounds Survey's in Sections 14, 23 and 25
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

Preliminary Statement: The following metes-and-bounds surveys, identify three distinct portions of the administrative bdy. between GBFAF and BMGAFR. (1) The easterly right-of-way of the Tucson, Cornelia and Gila Bend Railroad, in the S. 1/2 of sec. 14. (2) That portion of the fence that deviates from the N. and S. center lines of sec. 14 and 23. (3) A tract of land in the SE 1/4 of sec. 25, containing a portion of the active runway and clear zone.

In Sections 14 & 23

From the Angle Point at the intersection of the E. and W. center line of sec. 14, with the easterly right-of-way of Tucson, Cornelia and Gila Bend Railroad, hereinbefore described.

S. 25°14' W., on the administrative bdy. bet. GBFAF and BMGAFR, identical with easterly right-of-way of Tucson, Cornelia and Gila Bend Railroad.

In and along a 4 strand barbed wire fence.

23.73

Point for an Angle Point.

Set a rebar, 24 ins. long, 5/8 in. diam., 20 ins. in the ground. Wire a brass washer, 1 1/2 ins. diam., mkd BLM S14 AP 2020 to the rebar.

Cor. is located at the intersection of 4 strand barbed wire fences, adjacent and W. of a wood fence cor., off plumb and leaning to the E.

S. 5°16' E., on the administrative bdy. bet. GBFAF and BMGAFR.

Departing from the easterly right-of-way of Tucson, Cornelia and Gila Bend Railroad.

In and along a 4 strand barbed wire fence.

0.61

Point for an Angle Point.

Set a rebar, 24 ins. long, 5/8 in. diam., 20 ins. in the ground, attach a brass cap, 2 ins. diam. x 1 3/4 ins. long stem, mkd.

T 6 S R 5 W

S 14 | AP

2020

Metes-and-Bounds Survey's in Sections 14, 23 and 25
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on the NW side of a 4 ins. x 4 ins. wood fence post, at the northerly terminus of a split rail fence.</p> <hr/>
	<p>S. 6°28' E., on the administrative bdy. bet. GBAFAF and BMGAFR. In and along a split rail fence, 1 lk. westerly and parallel with a 4 strand barbed wire fence.</p>
5.34	<p>Point for an Angle Point. Set a rebar, 24 ins. long, 5/8 in. diam., 22 ins. in the ground, attach a brass cap, 2 ins. diam. x 1 3/4 ins. long stem, mkd.</p>
	<p style="text-align: center;">T 6 S R 5 W S 14 AP 2020</p>
	<p>Cor. is located on the SW side of a 4 ins. x 4 ins. wood fence post, at the southerly terminus of a split rail fence.</p> <hr/> <p>S. 10°27' E., on the administrative bdy. bet. GBAFAF and BMGAFR. In and along a 4 strand barbed wire fence.</p>
0.22	<p>An Angle Point at the intersection of a barbed wire fence, with a slump block fence, 8 ft, high.</p> <hr/>
	<p>S. 5°39' E., on the administrative bdy. bet. GBAFAF and BMGAFR.</p>
0.75	<p>Point for an Angle Point, at intersection of slump block fence with 4 rail iron fence. Wire a brass washer, 1 1/2 ins. diam., mkd BLM S14 AP 2020 to the iron fence cor.</p> <hr/>
	<p>S. 64°37' W., on the administrative bdy. bet. GBAFAF and BMGAFR. Along a 4 rail iron fence.</p>
0.18	<p>End of iron rail fence at intersection with the easterly edge of pavement, of main entrance road to GBAFAF. Road extends S. 28° E. and N. 28° W.</p>
0.78	<p>Begin iron rail fence at intersection with the westerly edge of pavement, of main entrance road to GBAFAF. Road extends S. 28° E. and N. 28° W.</p>

Metes-and-Bounds Survey's in Sections 14, 23 and 25
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
0.89	<p>Intersect the N. and S. center line of sec. 14.</p> <p>From this point, the 1/4 sec. cor. of secs. 14 and 23, bears S. 0°13' E., 11.41 chs. dist., hereinbefore described.</p>
0.96	<p>Point for an Angle Point, at intersection of slump block fence with iron rail fence.</p> <p>Wire a brass washer, 1 1/2 ins. diam., mkd BLM S14 AP 2020 to the iron fence cor.</p> <hr/> <p>S. 13°25' W., on the administrative bdy. bet. GBAFAF and BMGAFR.</p> <p>In and along a slump block fence.</p>
0.73	<p>An Angle Point at the intersection of a barbed wire fence, with a slump block fence, 8 ft, high.</p> <hr/> <p>S. 22°43' W.,</p>
0.10	<p>Point for an Angle Point.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 20 ins. in the ground, attach a brass cap, 2 ins. diam. x 1 3/4 ins. long stem, mkd.</p> <p style="text-align: center;">T 6 S R 5 W</p> <p style="text-align: center;">S 14 AP</p> <p style="text-align: center;">2020</p> <p>Cor. is located on the NW side of a 4 ins. x 4 ins. wood fence post, at the northerly terminus of a split rail fence.</p> <hr/> <p>S. 13°38' W., on the administrative bdy. bet. GBAFAF and BMGAFR.</p> <p>In and along a split rail fence, 1 lk. W. and parallel with barbed wire fence.</p>
4.60	<p>Point for an Angle Point.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 20 ins. in the ground, attach a brass cap, 2 ins. diam. x 1 3/4 ins. long stem, mkd.</p> <p style="text-align: center;">T 6 S R 5 W</p> <p style="text-align: center;">S 14 AP</p> <p style="text-align: center;">2020</p>

Metes-and-Bounds Survey's in Sections 14, 23 and 25
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located on the SW side of a 4 ins. x 4 ins. wood fence post, at the southerly terminus of a split rail fence.</p> <hr/>
	<p>S. 13°35' W., on the administrative bdy. bet. GBAFAF and BMGAFR. In and along a barbed wire fence.</p>
4.90	<p>Quilotosa Wash, 25 ft. wide, drains NW.</p>
6.30	<p>Intersect the line bet. secs. 14 and 23. From this point, the 1/4 sec. cor. of secs. 14 and 23, bears N. 89°37' E., 2.88 chs. dist., hereinbefore described. Continuing measurement in sec. 23.</p>
8.20	<p>Point for an Angle Point, at intersection of barbed wire fences. Wire a brass washer, 1 1/2 ins. diam., mkd BLM S23 AP 2020 to a 9 ins. diam. wood fence cor. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 13°35' E., 10.0 ft. dist. with brass cap mkd. RM T6S R5W S23 10.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends N. 13 1/2° E. and S. 13 1/2° W. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears S. 1°40' E., 10.0 ft. dist. with brass cap mkd. RM T6S R5W S23 10.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends S. 1 3/4° E. and N. 1 3/4° W.</p> <hr/>
	<p>S. 1°40' E., on the administrative bdy. bet. GBAFAF and BMGAFR. In and along a barbed wire fence.</p>
8.57	<p>Point for an Angle Point, at intersection of barbed wire fences. Wire a brass washer, 1 1/2 ins. diam., mkd BLM S23 AP 2020 to a 9 ins. diam. wood fence cor. from which</p>

Metes-and-Bounds Survey's in Sections 14, 23 and 25
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 4°43' E., 7.0 ft. dist. with brass cap mkd. RM T6S R5W S23 7.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends S. 4 3/4° E. and N. 4 3/4° W.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 1°40' W., 7.0 ft. dist. with brass cap mkd. RM T6S R5W S23 7.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends S. 1 3/4° E. and N. 1 3/4° W.</p>
	<p>S. 4°43' E., on the administrative bdy. bet. GBAFAP and BMGAFR. In and along a barbed wire fence.</p>
37.20	<p>Point for an Angle Point, at intersection of barbed wire fences. Wire a brass washer, 1 1/2 ins. diam., mkd BLM S23 AP 2020 to a 2 ins. diam. iron fence cor.</p>
	<p>S. 9°12' E., on the administrative bdy. bet. GBAFAP and BMGAFR. In and along a barbed wire fence.</p>
0.40	<p>The Angle Point, at intersection with the N. and S. center line of sec. 23, hereinbefore described.</p>
<p>In Section 25</p>	
	<p>From the Angle Point on the of the E. and W. center line of sec. 25, hereinbefore described.</p>
	<p>S. 0°06' W., on the administrative bdy. bet. GBAFAP and BMGAFR. In and along a barbed wire fence.</p>
25.43	<p>Point for an Angle Point, at the intersection of fences, witnessed by an off plumb, 2 ins. angle iron, fence cor., cemented in place, leaning to the SE. Wire a brass washer, 1 1/2 ins. diam., mkd BLM 2020 to the angle iron fence cor.</p>

Metes-and-Bounds Survey's in Sections 14, 23 and 25
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 0°06' E., 35.0 ft. dist. with brass cap mkd. RM T6S R5W S25 35.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends N. and S.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 89°45' E., 10.0 ft. dist. with brass cap mkd. RM T6S R5W S25 10.0 FT TO COR. 2020 and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Cor. is located in a 4 strand barbed wire fence, extends E. and W.

From this cor. point, a rebar, 3/4 in. diam., firmly set, projecting 3 ins. above ground, bears S. 58 1/4° W., 8.9 lks. dist. An attached 3 1/4 ins. diam., aluminum cap is mkd. GBAF 2011 RLS 47302. Witnessed by fiberglass survey marker sign, 2 ins. wide, projecting 48 ins. above ground, set 1.5 lks. N. of the rebar. Cor. was established by Vernen Kalani Lee, Arizona R.L.S. No. 47302 in 2011 and disregarded the long established fence, as evidence of the GBAFAF bdy. Not utilized in the course of this survey. The record of survey that includes this cor., is recorded in the Maricopa County Recorder's Office in book 1088, page 49.

N. 89°45' E., on the administrative bdy. bet. GBAFAF and BMGAFR.

In and along a barbed wire fence.

33.76

The angle point on the administrative bdy. bet GBAFAF and BMGAFR, at intersection with the E. bdy. of the Tp. As described in the dependent resurvey of the W. bdy. of the T. 6 S., R. 4 W., executed concurrently under this same group.

GENERAL DESCRIPTION

The area surveyed is located about 5 miles SSE from the Town of Gila Bend, Municipal Building. Access is provided by Az. State Highway No. 85, to Gila Bend. Thence to Martin Road, a graveled and improved road, within the corporate boundaries of the Town of Gila Bend.

The terrain is nearly level, cut with many, small northerly draining washes. Vegetation is predominantly creosote. Palo verde

T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

and ironwood timber is found in and near the washes. The soils are alluvial deposits of loam and sandy loam.

The bounds of GBAFAF are enclosed by fences. A security perimeter road inside the GBAFAF, runs parallel with the fences. The security entrance station for GBAFAF is located in the SE 1/4 of sec. 14. The lone active runway is located in sections 13, 24 and 25, traversing in a N. and S. direction.

The mean magnetic declination of 10 1/4° E. was derived from National Oceanic and Atmospheric Administration, on line Magnetic Field Calculator program, utilizing the World Magnetic Model (2019-2024), for the dates of the survey.

**Composite Description of the Administrative Boundary
of the Gila Bend Air Force Auxiliary Field
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona**

Beginning at the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.

thence S. 89°40' W., on the E. and W. center line of sec. 13, at 26.72 chs. dist. a witness point, at 53.44 chs. dist. a witness point, at 80.16 chs. the 1/4 sec. cor. of secs. 13 and 14.

thence S. 89°40' W., on the E. and W. center line of sec. 14, at 29.93 chs. dist., an Angle Point at the intersect with the Tucson, Cornelia and Gila Bend Railroad.

thence S. 25°14' W., 23.73 chs. dist. in sec. 14, on the easterly right-of-way of the Tucson, Cornelia and Gila Bend Railroad, to an Angle Point.

thence S. 5°16' E., 0.61 chs. dist., in sec. 14, to an Angle Point.

thence S. 6°28' E., 5.34 chs. dist., in sec. 14, to an Angle Point.

thence S. 10°27' E., 0.22 chs. dist., in sec. 14, to an Angle Point.

thence S. 5°39' E., 0.75 chs. dist., in sec. 14, to an Angle Point.

thence S. 64°37' W., in sec. 14, at 0.89 chs. dist., intersect the N. and S. center line of sec. 14, at 0.96 chs. dist. to an Angle Point.

thence S. 13°25' W., 0.73 chs. dist., in sec. 14, to an Angle Point.

thence S. 22°43' W., 0.10 chs. dist., in sec. 14, to an Angle Point.

Composite Description of the Administrative Boundary
of the Gila Bend Air Force Auxiliary Field
T. 6 S., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	thence S. 13°38' W., 4.60 chs. dist., in sec. 14, to an Angle Point.
	thence S. 13°35' W., in sec. 14, at 6.30 chs. dist., intersect the line bet. secs. 14 and 23.
	continuing S. 13°35' W., 1.90 chs. dist., in sec. 23, to an Angle Point.
	thence S. 1°40' E., 8.57 chs. dist., in sec. 23, to an Angle Point.
	thence S. 4°43' E., 37.20 chs. dist., in sec. 23, to an Angle Point.
	thence S. 9°12' E., 0.40 chs. dist., in sec. 23, to an Angle Point, on the N. and S. center line of sec. 23.
	thence S. 0°03' E., on the N. and S. center line of sec. 23, 32.45 chs. dist., to the 1/4 sec. cor. of secs. 23 and 26.
	thence S. 0°04' E., on the N. and S. center line of sec. 26, at 39.99 chs. dist., the center 1/4 sec. cor. of sec. 26.
	thence N. 89°46' E., on the E. and W. center line of sec. 26, at 39.78 chs. dist., the 1/4 sec. cor. of secs. 25 and 26.
	thence N. 89°46' E., on the E. and W. center line of sec. 25, at 39.90 chs. dist., the center 1/4 sec. cor. of sec. 25.
	thence N. 89°52' E., on the E. and W. center line of sec. 25, at 6.32 chs. dist., an Angle Point.
	thence S. 0°06' W., 25.43 chs. dist., in sec. 25, to an Angle Point.
	thence N. 89°45' E., 33.76 chs. dist., in sec. 25, to an Angle Point on the E. bdy. of the Tp.
	thence N. 0°08' E., 25.43 chs. dist., on the E. bdy. of the Tp., to the 1/4 sec. cor. of secs. 25 and 30.
	thence N. 0°07' E., 40.15 chs. dist., on the E. bdy of the Tp., to the cor. of secs. 19, 24, 25 and 30.
	thence N. 0°08' E., 40.15 chs. dist., on the E. bdy. of the Tp., to the 1/4 sec. cor. of secs. 19 and 24.
	thence N. 0°07' E., 40.15 chs. dist., on the E. bdy of the Tp., to the cor. of secs. 13, 18, 19 and 24.
	thence N. 0°06' E., 40.15 chs. dist., on the E. bdy. of the Tp., to the 1/4 sec. cor. of secs. 13 and 18, and point of beginning.

CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 21st day of September, 2020. I have dependently resurveyed a portion of the subdivisional lines. Subdivided sections 13, 14, 23, 25 and 26. Executed the metes-and-bounds surveys of the administrative boundary of the Gila Bend Air Force Auxiliary Field, in Township 6 South, Range 5 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

APRIL 8, 2021
(Date)

Gordon R. Bubel
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines. The subdivision of sections 13, 14, 23, 25 and 26. The metes-and-bounds surveys of the administrative boundary of the Gila Bend Air Force Auxiliary Field, T. 6 S., R. 5 W., Gila and Salt River Meridian, in the State of Arizona. Executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/14/2021
(Date)

Mark Mark
(Chief Cadastral Surveyor of)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 6 S., R. 5 W., Gila and Salt River Meridian, in the state of Arizona, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor of)~~