

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE EAST BOUNDARY,
PORTIONS OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTIONS 23 AND 24,
AND METES-AND-BOUNDS SURVEYS
TOWNSHIP 6 SOUTH, RANGE 19 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Rosendo Ramos Serrano, Cadastral Surveyor

Under Special Instructions dated October 22, 2020, approved January 4, 2021, which provided for the surveys included under Group No. 1208, and assignment instructions dated December 21, 2020.

Survey commenced January 4, 2021

Survey completed April 8, 2021

INDEX DIAGRAM

TOWNSHIP 6 SOUTH RANGE 19 EAST
GILA & SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	11 12 23 6 9	8 24 4 5
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 23 Pages 13-15
 Subdivision of Section 24 Pages 15-17
 Metes-and-Bounds in Section 23 Pages 18-21
 Metes-and-Bounds in Section 24 Pages 21-21

T.6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary, portions of the subdivisional lines, the subdivision of sections 23 and 24 and Metes-and-Bounds surveys in Township 6 South, Range 19 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey and survey is as follows:

In 1877, a portion of the south and east boundary, was surveyed by Theo. F. White, Deputy Surveyor.

In 1877, a portion of the subdivisional lines, was surveyed by John L. Harris, Deputy Surveyor, under Group No. 125, Arizona.

In 1924, Glenn F. Sawyer, U.S. Surveyor and Theodore Vander Meer, U.S. Transitman, resurveyed portions of the subdivisional lines, portions of the south boundary, survey the north and west, completion of the south and east boundary and subdivisional lines, executed by, under Group No. 773, Arizona.

In 1928, a resurvey of the east boundary, was executed by William E. Hiester, U.S. Surveyor and Charles E. Hunter, U.S. Transitman, Group No. 141, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated October 22, 2020, for Group Number 1208, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R10-2 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Navigation Satellite System (GNSS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DF7063 COT2 CITY OF TUCSON 2 CORS ARP, DK7569 AZSF SAFFORD CORS ARP DF5763 AZGB GILA COUNTY CORS ARP.

The NAD 83 (CORS2011) (EPOCH 2010.0000), geographic position of the corner sections 24 and 25 only on the east boundary of the township, is as follows:

T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS

Latitude: 32°53'26.053" N. Longitude: 110°21'00.343" W.

The NAD 83 (CORS2011) (EPOCH 2010.0000), geographic position of the corner of sections 14, 15, 22 and 23, is as follows:

Latitude: 32°54'16.878" N. Longitude: 110°23'02.744" W.

The mean magnetic declination is 9 1/2 ° E.

**Dependent Resurvey of a Portion of the East Boundary,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
William E. Hiester, in 1928.

Beginning at the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented with an iron post 2 ins. diam., firmly set, flush with the ground, with brass cap mkd. T6SR19E S24 S25 T6S S19 R20E 1928.

Add the marks 2021 to the brass cap.

Cor. is located S. 38° E., 4.85 lks. dist., of a cor. of barbed wire fences, 4 strand, extending N., S. and W.

From this cor., the closing cor. of secs. 19 and 30 only, Tp. 6 S. R. 20 E., bears S. 0°20' W., 1.03 chs. dist., monumented with an iron post 2 ins. diam., firmly set projecting 9 ins. above ground in a collar of stone 1 ft. base to top, with brass cap mkd. T6S S25 R19E R20E S19 C S30 C 1928.

Add the marks 2021 to the brass cap.

Cor. is located E. 1 lk. dist of a barbed wire fence, 7 strand, bears N. and S.

N. 01°46' W., bet. secs. 19 and 24 on the east bdy. of the Tp.

38.90

The 1/4 sec. cor. of sec. 19 only, Tp. 6 S., R. 20 E., monumented with a 1 in. diam. iron post, firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S19 1928.

Add the marks 2021 to the brass cap.

From this same point a mound of stone of unknown origin, 3 ft. base, 1/2 ft. high, bears N. 52°16' E., 5.16 chs. dist.

39.08

The 1/4 sec. cor. of sec. 24 only, monumented with a 1 in. diam. iron post, firmly, set projecting 18 ins. above ground, with brass cap mkd. 1/4 S24 1928.


**Dependent Resurvey of a Portion of the East Boundary,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Raise a supporting mound of stone 2 1/2 ft. base, 2 1/2 ft. high.</p> <p>Add the marks T6SR19E and 2021, to the brass cap.</p> <p>Cor. is located approx. 45 lks. above the foot of a steep WNW facing slope, bears N. and S. 25° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°00' W., beginning new measurement.</p>
39.12	<p>The cor. of secs. 13 and 24 only, on the E. bdy of the Tp., monumented with an iron post, 2 ins. diam., firmly set projecting 11 ins. above ground, with brass cap mkd. T6S R19E S13 S24 T6S S19 R20E 1928.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 6 strand, bears N. and S.</p> <p>From this cor., the closing cor. of secs. 18 and 19 only, Tp. 6 S., R. 20 E., bears N. 0°49' E., 0.66 chs. dist., monumented with an iron post 2 ins. diam., firmly set projecting 10 ins. above ground, with brass cap mkd. T6S S13 R19E T6S R20E S18 S19 1928, Scattered remains of accessory mound of stone 3 1/2 ft. base.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located in a barbed wire fence, 6 strand, bears N. and S.</p> <hr style="width: 50%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°56' W., bet. secs. 24 and 25.</p>
40.19	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 6 S R 19 E</p> <p> S 24</p> <p> 1/4 ———</p> <p> S 25</p> <p> 2021</p> </div>



**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Drive a "T" steel fence post, N. of the cor.</p> <p>Cor. is located 11 ft. north of barbed wire fence, 4 strand, bears E. and W.</p>						
44.55	Barbed wire fence, 5 strand, 15 lks., N. 11° W. of the cor. of fences extending E., W. and N. 11° W.						
80.38	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a gabion 4 1/2 ft. high, 3 ft. diam., filled with rocks, this position is been utilized by previous surveys, accepted by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 1 of 2. This position is harmoniously related to identified original corners, and is accepted as a faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Drive a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in top of the gabion, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 6 S</td> <td>R 19 E</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> </table> <p>2021</p> </div> <p>Cor. functions as the cor. of fences, extending N. and E.</p> <p>This area is subject to flooding.</p> <hr/> <p>N. 0°06' W., bet. secs. 23 and 24.</p>	T 6 S	R 19 E	S 23	S 24	S 26	S 25
T 6 S	R 19 E						
S 23	S 24						
S 26	S 25						
39.91	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a gabion 4 ft. high, 3 ft. diam., filled with rocks, this position is been utilized by previous surveys, accepted by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 1 of 2. This position is harmoniously related to identified original corners, and is accepted as a faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Drive a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in top of the gabion, with brass cap mkd.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 6 S R 19 E 1/4 S 23 S 24 2021</p> <p>Cor. functions as the cor. of fences, extending N., S. and W.</p> <p>This area is subject to flooding.</p> <p>From this cor. point, the SE corner of an old trailer house bears N. 62°20' W., 6.30 chs. dist.</p> <p>From this same cor. point, the SE corner of a storage shed bears N. 50°51' W., 6.26 chs. dist.</p> <p>From this same cor. point, a power pole, bears N. 59°19' W., 7.94 chs. dist.</p> <p>From this same cor. point, the SE corner of a storage shed, bears N. 46°27' W., 8.98 chs. dist.</p> <p>From this same cor. point, a water well in use, bears N. 46°08' W., 9.11 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°08' E., beginning new measurement.</p>
5.19	<p>Point for angle point No. 5, sec. 23, identical with angle point No. 3, sec. 24, on the sec. line between secs. 23 and 24.</p> <p>Set a rebar 24 ins. long, 5/8 in. diam., 22 ins. in the ground, with a 2 ins. diam. brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E</p> <div style="text-align: center;">  <p>AP 5 AP 3 S 23 S 24</p> </div> <p style="text-align: center;">2021</p> <p>Cor. is located 10 lks. east of a barbed wire fence, 5 strand, bears N. and S.</p>
18.83	Corral fence of pipe and windmill sucker rod.
19.42	The N 1/16 sec. cor. of secs. 23 and 24, monumented with a rebar, 1/2 in. diam., firmly set 9 ins. below corral detritus, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2, and is accepted as careful and faithful determination of the corner point.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p>  <p>Cor. is located in eastern portion of an irregular corral.</p> <hr/> <p>N. 0°08' E., beginning new measurement.</p>
1.21	Corral fence of pipe and windmill sucker rod.
18.33	<p>The angle point No. 1 sec. 23, monumented with a rebar 1/2 in. diam. firmly set, projecting 2 ins. above ground, in a collar stone, 16 ins. diam., with a damaged plastic cap, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p>  <p>Drive a "T" steel fence post, N. of the cor.</p> <hr/> <p>N. 0°08' E., beginning new measurement.</p>
1.09	<p>The cor. of secs. 13, 14, 23 and 24, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with an aluminum cap mkd. T6S R19E 14 13 23 24 2020 RLS 19315, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2, and is accepted as careful and faithful determination of the corner point.</p> <p>From this point, a wood post, 3 1/2 X 4 1/2 wide X 51 ins. long, laying loose, bears N., 70 lks. dist.</p> <hr/> <p>From the cor. of secs. 13, and 24, on the E. bdy. of the Tp. hereinbefore described.</p> <p>N. 89°38' W., bet. secs. 13 and 24.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

<p>CHAINS 38.89</p>	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Drive a "T" steel fence post, N. of the cor.</p> <p>Cor. is located on the NW face of slope, bears N. 45° E. and S. 45° W.</p> <p>Cor. is located 74 lks. south of wash, 5 ft. wide, 2 ft. deep, drains S. 60° W.</p>
<p>58.34</p>	<p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Drive a rebar 24 ins. long, 5/8 in. diam., 23 ins. in the ground, with a 2 ins. diam. brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E S 13 W 1/16 ——— S 24</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Drive a "T" steel fence post, N. of the cor.</p> <p>Cor. is located 12 lks. north of a wash, 1 ft. wide, 1 ft. deep, drains N. 80° W.</p> <p>Cor. is located in cove between 2 ridges, northerly ridge bears N. 70° E. and W., southerly ridge bears N. 70° E. and W.</p>
<p>77.79</p>	<p>The cor. of secs. 13, 14, 23 and 23.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 88°44' W., bet. secs. 23 and 26.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.51	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionated dist., there is no remaining evidence of the original corner</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor. point, a scattered mound of stone 2 1/2 ft. base, 1 ft. high, bears N. 17°16' E., 1.65 chs. dist.</p>
77.13	<p>Barbed wire fence, 4 strand, bears N. and S.</p>
79.02	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a granite stone, 10 X 8 ins., firmly set, projecting 15 ins. above ground, with no visible marks.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A living juniper, 12 ins. diam., with forked, blazed and visible marks TVIS RXIXE XXIII, bears N. 66°32' E., 79 lks. dist.</p> <p style="padding-left: 40px;">A living juniper, 15 ins. diam., with blazed and scribed marks TVIS RXIXE XXVII, bears S. 32°34' W., 47 lks. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E S 22 S 23 ————— S 27 S 26</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Raise an accessory mound of stone on the N. side of the cor.</p> <p>Drive a "T" steel fence post, W. of the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Cor. is located 42 lks. south of a wash 8 ft. wide, 4 ft. deep, drains S. 70° W.</p> <p>From this point the cor. of secs. 21, 22, 27 and 28, monumented with the a juniper wood post 4 ins. diam., firmly set, projecting 33 ins. above ground, with an iron post 2 ins. diam., firmly set alongside to the east, projecting 13 ins. above ground, with brass cap mkd. T6S R19E S21 S22 28 S27 2001 1924, with a collar stone 2 ft. base, 1/2 ft. high, bears S. 89°38' W., 79.03 chs. dist.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 0°52' E., bet. secs. 22 and 23.</p> <p>39.84 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E 1/4 S 22 S 23 2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Drive a "T" steel fence post, N. of the cor.</p> <p>Cor. is located 62 lks. west of a reconstructed fence line 5 strand barbed wire fence, extending N. and S.</p> <p>79.69 The cor. of secs. 14, 15, 22 and 23, occupied by an old wood fence post, cor. of fences extending N., E. and S. and has been accepted by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 1 of 2. This position is harmoniously related to identified original cor. It is accepted as a careful and faithful determination of the corner point.</p> <p>From which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears S. 41° W., 12ft. dist. with brass cap mkd. RM T6S R19E 12.0FT TO COR S22 2021 and an arrow pointing to the cor. Raise a mound of stone 3 ft. base to top. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
---------------	---


Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground for a reference monument, bears N. 49°15' W., 12 ft. dist. with brass cap mkd. RM T6S R19E 12FT TO COR. S15 2021 and an arrow pointing to the cor. Raise a mound of stone 3 ft. base to top. Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>From this cor., the cor. of secs. 15, 16, 21 and 22, monumented with an iron post 2 ins. diam., firmly set, projecting 12 ins. above ground in a mound of stone, 3 ft. base, 1 ft. high, with a brass cap mkd. T6S R19E S16 S15 S21 S22 2001 1924, bears S. 88°47' W., 80.16 chs. dist.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24. S. 89°24' W., bet. secs. 14 and 23.</p> <p>19.45 The E 1/16 sec. cor. of secs. 14 and 23, monumented with a rebar, 1/2 in. diam., firmly set, projecting 11 ins. above ground, with pink plastic cap mkd. AMOX RLS 19315, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2, and is accepted as a careful and faithful determination of the corner point.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div data-bbox="812 1123 1015 1312" data-label="Diagram"> </div> <p>Drive a "T" steel fence post, N. of the cor. Cor. is located in a cluster of mesquite trees.</p> <p>38.90 Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E S 14 1/4 ——— S 23 2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
---------------	--

Subdivision of Section 23,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Drive a "T" steel fence post, W. of the cor.</p> <p>From this point a mound of stone 3 ft. base, 1 ft. high, bears N. 41°16' W., 85 lks. dist.</p> <p>Cor. is located, 1.99 chs. south of a barbed wire fence, 4 strand, bears N. 85° E. and S. 85° W.</p>
77.80	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p style="text-align: center;">Subdivision of Section 23, T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0°27' E., on the N. and S. center line of sec. 23.</p>
39.88	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E C 1/4 S 23</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
79.22	<p>Drive a "T" steel fence post, W. of the cor.</p> <p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S.88°40' W., on the E. and W. center line of sec. 23.</p>
7.04	<p>Point for angle point No. 6 in sec. 23, described in the legal description in Graham County Recorder's Office in Document Deed No. 2001-03533, point is located on centerline of Arivaipa Town Road, graded dirt, 20 ft. wide. Impractical to establish a permanent monument.</p> <p>Point is located 16 lks., south, of a gate across Arivaipa Town Road.</p>
9.77	<p>Power line, 4 strand, bears S. 10° E. and N. 10° W.</p>


Subdivision of Section 23,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.56	<p>Point for the CE 1/16 sec. cor. of sec. 23, Described Document Deed No. 2001-03533. Set a rebar 24 ins. long, 5/8 in. diam., 17 ins. in a rock crevice, with a 2 ins. diam. brass cap, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 19 E E 1/16 C———C S 23 2021</p> </div> <p>Drive a "T" steel fence post, E. of the cor.</p> <p>Cor. is located on a steep east facing slope, bears N. and S.</p> <p>From this point a decomposing wood post, 5 X 4 ins., firmly set, projecting 44 ins. above the ground, in a mound of stone 1 1/2 ft. base, 1 ft. high, bears N.14°45' W., 49 lks. dist.</p> <p>From this same point a gabion fence corner 4 1/2 ft. high, 3 1/2 ft. diam., bears N.89°51' E., 6.17 chs. dist., fence line extends E. and N.31°W.</p>
39.12	The center 1/4 sec. cor. of sec. 23.
78.34	The 1/4 sec. cor. of secs. 22 and 23.
	<hr/> <p>NE 1/4</p> <hr/>
20.87	<p>Point for the angle point No. 16, described in the legal description in Graham County Recorder's Office in Document Deed No. 2001-03533 determined by record distance from the CE 1/16.</p> <p>Set a rebar 24 ins. long, 5/8 in. diam., 21 ins. in the ground, with a 2 ins. diam. brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 19 E AP 16 S 23  2021</p> </div> <p>Drive a "T" steel fence post, NW of the cor.</p>

Subdivision of Section 23,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located 10 lks. west of a barbed wire fence, 5 strand, bearing N. and S.</p> <p>Cor. is located 24 lks., S. 28° W., of a an iron pipe, 4 1/2 ins. diam. corner of barbed wire fences, 5 strand, fences extend N., N. 85° E., and S.</p> <p>From this point a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with pink plastic cap mkd. AMOX, bears N. 50°02' W., 65 lks. dist. This monument was established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2, was not placed on the N. and S. center line of the NE1/4 of sec. 23, and is not utilized in this survey.</p>
39.09	<p>The E 1/16 sec. cor. of secs. 14 and 23.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p style="text-align: center;">Subdivision of Section 24, T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°56' W., on the N. and S. center line of sec. 24.</p>
39.50	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E C 1/4 S 24</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Drive a "T" steel fence post, N. of the cor.</p>
58.98	<p>Point for the center N. 1/6 sec. cor. of sec. 24.</p> <p>Set a rebar 24 ins. long, 5/8 in. diam., 21 ins. in the ground, with a 2 ins. diam. brass cap mkd.</p> <p style="text-align: center;">T 6 S R 19 E C N 1/16 S 24 C</p> <p style="text-align: center;">2021</p>



Subdivision of Section 24,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Raised an accessory mound of stone 1 1/2 ft base, 1 1/2 ft high, W. of the cor. Drive a "T" steel fence post, W. of the cor.</p>
78.47	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 24 only, on the E. bdy. N.89°27' W., on the E. and W. center line of sec. 24.</p>
39.63	<p>The center 1/4 sec. cor. of sec. 24.</p>
59.44	<p>The center W. 1/16 sec. cor. of sec. 24, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground, with pink plastic cap mkd. AMOX RLS 19315, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2. The private surveyor has proportioned the position correctly and used proper controlling corners. It is accepted as careful and faithful determination of the corner point.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div style="text-align: center; margin: 10px 0;">  </div> <p>Drive a "T" steel fence post, N. of the cor.</p> <p>Cor. is located 45 lks. E. of an old barbed wire fence, 5 strand, bears S. 47° E., and N. 47° W.</p> <hr/> <p>N. 89°28' W., beginning new measurement.</p>
19.81	<p>The 1/4 sec. cor. of sec. 23 and 24.</p> <hr/> <p style="text-align: center;">NW1/4</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 24. N. 0°24' W., on the N. and S. center line of the NW1/4 of sec. 24.</p>
16.38	<p>The angle point No. 1 sec. 24, monumented with a rebar 1/2 in. diam. firmly set, projecting 1 1/2 ins. above ground, with a damaged pink plastic cap, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2.</p>


Subdivision of Section 24,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div data-bbox="808 359 1008 548" style="text-align: center;"> <p>BLM T6S R19E AP1 S24 2021</p> </div> <p>Drive a "T" steel fence post, SW of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°24' W., beginning new measurement.</p>
<p>3.07</p>	<p>The NW 1/16 sec. cor. of sec. 24, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 in. above ground, with a damaged pink plastic cap, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2, and is accepted as careful and faithful determination of the corner point.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div data-bbox="808 989 1008 1178" style="text-align: center;"> <p>BLM T6S R19E NW 1/16 S24 2021</p> </div> <p>Drive a "T" steel fence post, N. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°24' W., beginning new measurement.</p>
<p>19.45</p>	<p>The W 1/16 sec. cor. of secs. 13 and 24.</p> <hr style="width: 80%; margin: auto;"/> <p>From the center N. 1/16 sec. cor. of sec. 24.</p> <p>N. 89°32' W., on the E. and W. center line of the NW1/4 of sec. 24.</p>
<p>19.63</p>	<p>The NW 1/16 sec. cor. of sec. 24.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°33' W., beginning new measurement.</p>
	<p>19.63</p> <p>The N 1/16 sec. cor. of secs. 23 and 24.</p> <hr style="width: 80%; margin: auto;"/>

Metes-and-Bounds Survey in Section 23,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From angle point 1, sec. 23, on the line bet. secs. 23 and 24, hereinbefore described.</p> <p>S. 89°24' W., on line 1-2.</p> <p>2.22 Barbed wire fence, 5 strand, with old wood posts, bears N. and S.</p> <p>7.82 Angle point No. 2, sec. 23, monumented with a rebar 3/8 in. diam. firmly set, projecting 2 ins. above ground, with a collar stone 2 ft. base, 1/2 ft. high, with pink plastic cap mkd. AMOX RLS 19315, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div style="text-align: center;">  </div> <p>Drive a "T" steel fence post, SW of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 21°06' W., on line 2-3.</p> <p>5.53 Angle point No. 3, in sec. 23, monumented with a rebar 1/2 in. diam. firmly set, projecting 3 ins. above ground, with pink plastic cap mkd. AMOX RLS 19315, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div style="text-align: center;">  </div> <p>Drive a "T" steel fence post, alongside.</p> <p>From this point, a cor. of barbed wire fences, 5 strand, bears S. 87°33' E., 82 lks. dist., fences extend N. 17° E. and S. 44° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 14°24' E., on line 3-4.</p> <p>29.27 Angle point No. 4, sec. 23, monumented with a rebar 1/2 in. diam. firmly set, projecting 2 ins. above ground, with a collar stone</p>
--------	--


**Metes-and-Bounds Survey in Section 23,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>2 ft. base, 1/2 ft. high, with pink plastic cap mkd. AMOX RLS 19315, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div style="text-align: center;">  </div> <p>Drive a "T" steel fence post, W of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 67°15' E., on line 4-5.</p>
.17	Barbed wire fence, 5 strand, bears S. 1° E. and N. 1° W
2.55	Barbed wire fence, 5 strand, bears N. and S.
2.66	Angle point No. 5 sec. 23, identical with angle point 3 sec. 24, on the line bet. secs. 23 and 24, hereinbefore described.
	<hr/> <p>Note: The following courses are best fit curves to the centerline of Arivaipa Town Road as it was observed at the time of survey. Aravaipa Town Road is subject to flooding and frequent grading, making it impractical to establish permanent monuments.</p> <hr/> <p>From angle point No. 6, sec. 23, on the E. and W. centerline of the sec., hereinbefore described.</p> <p>N. 03°34' W., on line 6-7, along the centerline of Arivaipa Town Road.</p>
1.24	Point for AP 7, sec. 23, identical with the Point of Curvature. Not monumented.
	<hr/> <p>Thence, on line 7-8 along a circular curve concave southwesterly, having a central angle of 5°30'08", a radius of 300.00 ft., the chord of said arc bears N. 6°19' W., 0.44 chs. dist.</p>
0.44	Point for AP 8, sec. 23, identical with the Point of Tangency, . Not monumented.
	<hr/> <p>Thence, N. 9°04' W., on line 8-9, on the center line of Arivaipa Town Road.</p>

**Metes-and-Bounds Survey in Section 23,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
2.14	Power line, 1 strand, bears N. 57° E. and S. 57° W.
3.13	Angle point No. 9, sec. 23, identical with the Point of Curvature. Not monumented. _____
	Thence, on line 9-10 along a circular curve concave southwesterly, having a central angle of 21°36'19", a radius of 300.00 ft., the chord of said arc bears N. 19°52' W., 1.70 chs. dist.
1.71	Point for AP 10, sec. 23, identical with the Point of Tangency,. Not monumented. _____
	Thence, N. 30°40' W., on line 10-11, on the center line of Arivaipa Town Road.
2.26	Angle point No. 11, sec. 23, identical with the Point of Curvature. Not monumented. _____
	Thence, on line 11-12 along a circular curve concave southwesterly, having a central angle of 3°51'22", a radius of 300.00 ft., the chord of said arc bears N. 32°36' W., 0.31 chs. dist.
0.31	Point for AP 12, sec. 23, identical with the Point of Tangency,. Not monumented. _____
	Thence, N. 34°31' W., on line 12-13, on the center line of Arivaipa Town Road.
4.38	Power line, 4 strand, bears S. 10° E. and N. 10° W.
6.22	Angle point No. 13, sec. 23, identical with the Point of Non Tangent Curvature. From which the radius bears N. 61°57' W., 1500.00 ft. dist. Not monumented. _____
	Thence, on line 13-14 along a circular curve concave northeasterly, having a central angle of 12°30'56", a radius of 1500.00 ft., the chord of said arc bears N. 21°47' W., 4.96 chs. dist.
4.96	Point for AP 14, sec. 23, identical with the Point of Compound Curvature. Not monumented. _____
	Thence, on line 14-15 along a compound circular curve concave northeasterly, having a central angle of 20°46'26", a radius of 450.00 ft., the chord of said arc bears N. 5°09' W., 2.46 chs. dist.
2.47	Angle point No. 15. Not monumented.

**Metes-and-Bounds Survey in Section 23,
T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this point a rebar 1/2 in. diam. firmly set, projecting 6 ins. above the ground in a collar stone 1 ft. base, bears N. 31°32' W., 53 lks. dist. there is no identification tag or cap on rebar.</p> <p>From this same point an iron pipe fence corner with 5 strand barbwire fence, bears N. 26°24' W., 51 lks. dist., fence lines extend S. 3°E., and S. 83°W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87°59' W., on line 15-16.</p>
4.32	<p>Angle Point No. 16, on the N. and S. center line of the NE1/4 of sec. 23, hereinbefore described.</p> <hr style="width: 60%; margin: 10px auto;"/> <p style="text-align: center;">Metes-and-Bounds Survey in section 24, T. 6 S., R. 19 E., Gila and Salt River Meridian, Arizona</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the angle point No. 1, on the N. and S. center line of the NW1/4 of sec. 24, hereinbefore described.</p> <p>S. 51°45' W., on line 1-2.</p>
9.49	<p>The angle point No. 2, on sec. 24, monumented with a rebar 1/2 in. diam. firmly set, projecting 2 ins. above ground, with a damaged plastic cap mkd. AMOX RLS 19315, established by Ted D. Amox R.L.S. No. 19315 in 2020, as recorded in the Graham County Recorder's Office in Map File 644-5 at page 2 of 2.</p> <p>Attach a 1 1/2 ins. diam. brass washer to the rebar, mkd.</p> <div style="text-align: center; margin: 10px 0;">  </div> <p>Drive a "T" steel fence post, N of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 67°15' W., on line 2-3.</p>
1.80	<p>Barbed wire fence, 5 strand, bears S. 32° E. and N. 32° W.</p>
13.26	<p>Angle point No. 3 sec. 24, identical with angle point No. 5 sec. 23, intersect the N. and S. sec. line between secs. 23 and 24, hereinbefore described.</p> <hr style="width: 60%; margin: 10px auto;"/>

GENERAL DESCRIPTION

CHAINS

This survey is situated approximately 38 miles northwesterly from Safford, Arizona.

The land is generally vast and open, with very little timber, with elevation ranging from approximately 3,400 ft. to 4,300 ft. above sea level in the vicinity of this survey.

No mineral deposit or activity was noted during the course of the survey.

Note: An area of state land, approximately 0.08 acres, of the NW1/4 NW1/4 sec. 24, is being utilized as a corral.

The mean magnetic declination of $9\ 1/2^\circ$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2020 for the dates of survey.

CERTIFICATE OF SURVEY

I, Rosendo Ramos Serrano, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the day of 22nd day of October, 2020, I have dependently resurveyed a portion of the east boundary, portions of the subdivisional lines, the subdivision of sections 23 and 24 and Metes-and-Bounds surveys of Township 6 South, Range 19 East, Gila and Salt River Meridian, in the State of Arizona,, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

8-16-2021

(Date)



(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east boundary, portions of the subdivisional lines, the subdivision of sections 23 and 24 and Metes-and-Bounds surveys of Township 6 South, Range 19 East, Gila and Salt River, Arizona., executed by Rosendo Ramos Serrano, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/17/2021

(Date)



(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 6 South, Range 19 East, Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)