

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTION 30,

TOWNSHIP 6 SOUTH, RANGE 26 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Blas J. Urena, Cadastral Surveyor

Under Special Instructions dated February 17, 2021, approved February 17, 2021, which provided for the surveys included under Group No. 1215, and assignment instructions dated February 17, 2021.

Survey commenced February 22, 2021

Survey completed March 25, 2021

INDEX DIAGRAM

TOWNSHIP 6 SOUTH RANGE 26 EAST
GILA & SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
10					
5 30	9 29	28	27	26	25
7					
31	32	33	34	35	36

Subdivision of Section 30 Pages 11-17

T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of section 30, Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Theodore F. White, United States Deputy Surveyor, surveyed the South and West boundaries, including a portion of the First Standard Parallel South, through Range 25 East, Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona, in 1875 (Book 1574).

Philip Contzen, Compassman, surveyed the East boundary, including a portion of the First Standard Parallel South, through Ranges 26, 27, 28, and 29 East, Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona, in 1895 (Books 1592, 1591, 1547, and 1521).

Philip Contzen, Compassman, resurveyed the South and West boundaries, and surveyed the subdivisional lines of Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona, in 1895-96 (Books 658, 659, and 660).

William H. Thorn, United States Cadastral Engineer, and Benjamin J. Kinsey, United States Transitman, resurveyed the First Standard Parallel South, through Range 26 East, Township 5 South, Range 26 East, Gila and Salt River Meridian, Arizona, in 1920-21 (Book 3581).

Dell Cazier, Cadastral Surveyor, Glen B. Hatch and Eldon W. Sibley, Survey Aids, resurveyed the East, South, and West boundaries, and the subdivisional lines of Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona, in 1960 (Book 4615).

Harry K. Smith and Paul L. Reeves, Cadastral Surveyors, resurveyed a portion of the East boundary and Subdivisional lines, and surveyed Tracts No. 37 and 38, Township 6 South, Range 26 East, Gila and Salt River Meridian, Arizona, in 1976 (Book 5020).

Paul L. Reeves, Cadastral Surveyor, resurveyed a portion of the First Standard Parallel South, through Ranges 24 and 25 East, resurvey a portion of East boundary and subdivisional lines, and subdivided sections 6, 8, 9, 15, 23, 25, and 26, Township 5 South, Range 26 East, Gila and Salt River Meridian, Arizona, in 1976-77 (Book 5040).

This survey was executed at the request of Scott Cooke, Field Manager, Safford Field Office, Bureau of Land Management.

The steel "T" posts referred to in these notes are 60 inches long.

T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated February 17, 2021, for Group Number 1215, Arizona.

The true meridian direction and length of all lines were determined by static or real time kinematic Global Navigation Satellite System observations using Trimble Navigation R10 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Navigation Satellite System (GNSS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DF5763 AZGB GILA COUNTY CORS ARP, DM4629 AZRV ROUND VALLEY CORS ARP, DM7129 AZVA SYCOMORE ELEM SCH CORS ARP.

The NAD 83 (2011) (EPOCH: 2010.0000), geographic position of the corner of sections 25, 30, 31, and 36, on the West Boundary of the Township, is as follows:

Latitude: 32°52'28.258" N. Longitude: 109°43'58.142" W.

The NAD 83 (2011) (EPOCH: 2010.0000), geographic position of the corner of sections 19, 20, 29, and 30, is as follows:

Latitude: 32°53'20.467" N. Longitude: 109°43'00.422" W.

The mean magnetic declination is 9 1/4° E.

**Resurvey of a portion of the West Boundary,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Theodore F. White, in 1875,
and the resurveys executed by
Philip Contzen, in 1895-96,
Dell Cazier, Glen B. Hatch, and Eldon W. Sibley, in 1960,
and Paul L. Reeves, in 1976-77

Resurvey of a portion of the West Boundary,
T. 6 S., R. 26 ., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. "T6S R25E R26E S25 S30 S36 S31 1960". Add the marks 2021 to the brass cap.</p> <p>The cor. is located alongside a wall corner, block, 1 1/2 ft. high, with an iron fence on top, 5 ft. high, extending S. 0°23' W. and N. 89°58' W.</p> <p>From this cor., the SE cor. of the same wall, bears S. 0°17' W., 1.095 chs. dist.</p> <p>From this same cor., the NW cor. of the same wall, bears N. 89°50' W., 1.705 chs. dist.</p> <p>This cor. was most likely was removed and reset in place during the construction of the wall, and it is accepted as a careful and faithful perpetuation of the 1960 cor.</p> <p>N. 0°01' E., bet. secs. 25 and 30, on the W. bdy. of the Tp.</p> <p>Over rolling terrain, across public lands.</p>
9.80	<p>From this point, a rebar of unknown origin, 1/4 in. diam., firmly set, projecting 4 ins. above ground, bears East, 6.0 lks. dist., and it is not utilized in the course of this resurvey.</p> <p>This rebar is located on a northerly facing steep slope.</p>
19.91	<p>The S. 1/16 sec. cor. of secs. 25 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a scattered mound of stone, with brass cap mkd. "T6S R25E R26E S 1/16 S25 S30 1976". Add the marks 2021 to the brass cap.</p> <p>Rebuilt the mound of stone, 2 ft. base, to top of brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p>
19.91	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, in a scattered mound of stone, with brass cap mkd. "T6S R25E R26E S 1/4 S25 S30 1960". Add the marks 2021 to the brass cap.</p> <p>Rebuilt the mound of stone, 3 ft. base, to top of brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°14' E., beginning new measurement.</p>
19.835	<p>Point for the N. 1/16 sec. cor. of secs. 25 and 30.</p>

**Resurvey of a portion of the West Boundary,
T. 6 S., R. 26 ., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 25 E R 26 E N 1/16</p> <p style="text-align: center;">S 25 S 30</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post W. of cor.</p> <p>39.67 The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. "T6S R25E R26E S24 S19 S25 S30 1960", witnessed by a scattered mound of stone. Add the marks 2021 to the brass cap.</p> <p>Rebuilt the mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>From this cor., a fence corner, bears S. 79°38' W., 2.4 lks. dist., barbed wire, 4 strand, extending N. 50°21' E. and S. 42°41' W.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the survey executed by Philip Contzen, in 1895-96, and the resurvey executed by Dell Cazier, Glen B. Hatch, and Eldon W. Sibley, in 1960</p> <hr/> <p>From the point for the cor. of secs. 29, 30, 31, and 32, determined at proportionate dist., utilizing the 1/4 sec. cor. of secs. 29 and 30, the 1/4 sec. cor. of secs. 31 and 32, the 1/4 sec. cor. of secs. 29 and 32, and the 1/4 sec. cor. of secs. 30 and 31, there is no remaining evidence of the original cor., or the 1960 cor., falls within the existing City of Safford Landfill, within private lands. Not monumented.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS

From this cor. point, the 1/4 sec. cor. of secs. 29 and 32, bears S. 89°53' E., 40.09 chs. dist., monumented with an iron post 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. "T6S R26E 1/4 S29 S32 1960". Witnessed by a scattered mound of stone to the North, and by 2 galvanized iron pipe, 2 1/4 ins. diam., in concrete, projecting 4 1/2 ft. above concrete, North, 4 ft., and projecting 4.7 ft. above ground, South, 4.8 ft. dist. Add the marks 2021 to the brass cap.

Enclose in a collar of stone, 2 ft. base to top of brass cap.

Rebuilt the mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

From this same cor. point, the 1/4 sec. cor. of secs. 31 and 32, bears S. 2°01' E., 40.05 chs. dist., reestablished by David Howard Woodruff, Registered Professional Engineer (civil), circa 1973, monumented with an open ended galvanized iron pipe, 2 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap, 2 ins. diam., cemented on top, mkd. "WOODRUFF ENGINEERING RCE - 6820 T6SR26E 1/4 S31 S32 1973", found and accepted by Ray E. Thiessen, Arizona R.L.S. No. 16296, in 1993, according to Reception Number 1993-02370, on file at Graham County Recorder's Office.

This is accepted as a careful and faithful reestablishment of the 1960 cor. position.

There is no remaining evidence of the original cor., or the 1960 witness cor.

Witnessed by a galvanized iron pipe, 2 1/4 ins. diam., cemented in concrete, and projecting 5.3 ft. and approximately 4 ft. North of cor.

The cor. is located on top of the right bank of the main channel of the Cottonwood Wash, approximately 75 ft. wide, drains S. 30° W.

From this 1/4 sec. cor. of secs. 31 and 32, a disturbed iron pipe of unknown origin, 2 1/2 ins. diam., cemented in concrete and stone cylinder, 18 ins. diam., leaning E., approximately 5 ins. above concrete, with a punched iron cap, 3 ins. diam., mkd. "31 32 1/4", bears N. 0°05' E., 40 lks. dist., and it is not utilized in the course of this resurvey.

N. 89°50' W., bet. secs. 30 and 31.

Over the existing City of Safford Landfill, within private lands.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.05	<p>The E. 1/16 sec. cor. of secs. 30 and 31, monumented with an open ended iron pipe, 2 ins. diam., cemented in concrete cylinder, 12 ins. diam., projecting 2 ins. above ground, iron pipe projecting 1 in. above concrete, with an aluminum cap, 2 ins. diam., stamped "THEISSEN SURVEYING RLS 16296" and mkd. "T6S R26E S30 E----1/16 S31 1993", established by Ray E. Thiessen, Arizona R.L.S. No. 16296, in 1993, according to Reception Number 1993-02370, on file at Graham County Recorder's Office. This is accepted as a careful and faithful establishment of the corner point.</p> <p>The cor. is located alongside a fence, barbed wire, 4 strand, and woven, 6 ft. high, extending S. 0°39' E. and N. 0°39' W.</p> <hr/> <p>N. 89°50' W., beginning new measurement.</p> <p>Thence within public lands.</p>
20.04	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a scattered collar of stone, with brass cap mkd. "T6S R26E 1/4 S30 S31 1960", witnessed by a wood post, 1 1/2 ins. sq. with a 3 ft. wood lath attach in top. Add the marks 2021 to the brass cap.</p> <p>Rebuilt the collar of stone.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p>
20.05	<p>Point for the W. 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">S 30</p> <p style="text-align: center;">W 1/16 ———</p> <p style="text-align: center;">S 31</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post N. of cor.</p>
34.74	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.04	<p>N. 0°22' W., bet. secs. 29 and 30.</p> <p>Over the existing City of Safford Landfill, within private lands.</p> <p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. "T6S R26E 1/4 S30 S29 1960". Add the marks 2021 to the brass cap.</p> <p>The cor. is located alongside a fence, barbed wire, 4 strand, extending N. 89°32' E. and S. 89°32' W.</p> <p>From this cor., a fence corner on the same fence, bears S. 78°58' E., 2 lks. dist., barbed wire, 4 strand, extending N. 0°48' E., S. 89°19' E., and S. 89°32' W.</p> <p>Enclose in a collar of stone, 1 1/2 ft. base, to top of brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Thence within public lands.</p>
20.06	<p>Point for the N. 16 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E N 1/16</p> <p style="text-align: center;">S 30 S 29</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post W. of cor.</p> <p>The cor. is located alongside a down barbed wire fence, 4 strand, extending northerly and southerly.</p>
40.12	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a scattered collar of stone, with brass cap mkd. "T6S R26E S19 S20 S30 S29 1960". Add the marks 2021 to the brass cap.</p> <p>Rebuilt the collar of stone, 2 ft. base, to top of brass cap.</p> <p>The cor. is located alongside a down barbed wire fence, 4 strand, extending S. 0°02' E. and N. 0°02' W.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°40' W., bet. secs. 19 and 30.</p> <p>Over gently rolling terrain, within public lands.</p>
20.07	<p>Point for the E. 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">S 19 E 1/16 ——— S 30</p> <p style="text-align: center;">2021</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post N. of cor.</p>
40.14	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. "T6S R26E 1/4 S19 S30 1960". Add the marks 2021 to the brass cap.</p>
	<p style="text-align: center;">—————</p> <p>S. 89°35' W., beginning new measurement.</p>
20.02	<p>Point for the W. 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">S 19 W 1/16 ——— S 30</p> <p style="text-align: center;">2021</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post N. of cor.</p>
34.27	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <p style="text-align: center;">—————</p>

Subdivision of Section 30,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°12' W., on the N. and S. center line of sec. 30.</p> <p>Over gently rolling terrain, within public lands.</p> <p>39.91 The center 1/4 sec. cor. of sec. 30, established by persons unknown, monumented with an open ended iron pipe, totaling 17 ins. long, 1 in. diam., firmly set, projecting 6 ins. above ground, in a scattered mound of stone, and at the center of an old aerial target. This is accepted as a careful and faithful establishment of the corner point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">C 1/4 S 30</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Deposit the pieces of the iron pipe inside the stainless steel post.</p> <p>Set a steel "T" post W. of cor.</p> <p>From this cor., a rebar, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, with an "X" cut on top, in a small collar of stone, bears N. 45°35' W., 79.2 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°12' W., beginning new measurement.</p> <p>19.954 Point for the center N. 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">C N 1/16 S 30 C</p> <p style="text-align: center;">2021</p>
---------------	---

Subdivision of Section 30,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post W. of cor.</p>
29.93	<p>Point for the center N-N 1/64 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">S 30 C-N-N 1/64</p> <p style="text-align: center;">2021</p>
39.907	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post W. of cor.</p> <p>The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/>
19.99	<p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>S. 89°59' W., on the E. and W. center line of sec. 30.</p> <p>Over gently rolling terrain, on a portion of public lands bdy.</p> <p>The center E. 1/16 sec. cor. of sec. 30, established by persons unknown, monumented with an open ended iron pipe, 24 ins. long, 1 in. diam., loosely set, projecting 12 ins. above ground, and bent to the E. This is accepted as a careful and faithful establishment of the corner point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">E 1/16 C———C S 30</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Subdivision of Section 30,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Bury the iron pipe horizontally, alongside and N. of stainless steel post.</p> <p>Set a steel "T" post N. of cor.</p> <p>From this cor., an open ended iron pipe, 2 ins. diam., cemented in concrete cylinder, 12 ins. diam., projecting 4 ins. above ground, iron pipe projecting 1/2 in. above concrete, with an aluminum cap, 2 ins. diam., stamped "THEISSEN SURVEYING RLS 16296" and mkd. "T6S R26E C-E 1/16 --- S30 1993", established by Ray E. Thiessen, Arizona R.L.S. No. 16296, in 1993, according to Reception Number 1993-02370, on file at Graham County Recorder's Office, bears N. 87°48' W., 3.1 lks. dist., and it is not utilized in the course of this resurvey.</p> <p>From this same cor., a rebar of unknown origin, 1/2 in. diam., firmly set, flush with the surface of the ground, and at the center of an old aerial target, bears N. 12°25' W., 30.6 lks. dist., and it is not utilized in the course of this resurvey.</p> <p>From this same cor., a fence corner, bears S. 89°12' E., 3 lks. dist., barbed wire, 4 strand, extending S. 89°34' E. and S. 46°34' W.</p> <p>From this same cor., another fence corner on the same fence, bears S. 26°50' W., 7 lks. dist., barbed wire, 4 strand, extending N. 46°34' E. and S. 1°19' E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>Thence within public lands.</p> <p>19.99 The center 1/4 sec. cor. of sec. 30.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p> <p>20.08 Point for the center W. 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">W 1/16</p> <p style="text-align: center;">C ——— C</p> <p style="text-align: center;">S 30</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
--------	--

Subdivision of Section 30,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.58	<p>Set a steel "T" post N. of cor.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.</p> <hr/>
	<p style="text-align: center;">NE 1/4</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 30.</p> <p>N. 0°05' W., on the N. and S. center line of the NE 1/4 of sec. 30.</p> <p>Over gently rolling terrain, within public lands.</p>
20.01	<p>Point for the NE 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">NE 1/16 S 30</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post W. of cor.</p>
30.01	<p>Point for the center N-NE 1/64 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 26 E</p> <p style="text-align: center;">S 30</p> <p style="text-align: center;">C-N-NE</p> <p style="text-align: center;">1/64</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post W. of cor.</p>
40.02	<p>The E. 1/16 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 29 and 30.</p>

Subdivision of Section 30,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°50' W., on the E. and W. center line of the NE 1/4 of sec. 30.</p> <p>Over gently rolling terrain, within public lands.</p>
20.03	The NE 1/16 sec. cor. of sec. 30.
40.06	The center N. 1/16 sec. cor. of sec. 30.
<hr/> NW 1/4 of NE 1/4 <hr/>	
	<p>From the center N-NE 1/64 sec. cor. of sec. 30.</p> <p>S. 89°45' W., on the E. and W. center line of the NW 1/4 of the NE 1/4 of sec. 30.</p> <p>Over gently rolling terrain, within public lands.</p>
20.05	The center N-N 1/64 sec. cor. of sec. 30.
<hr/> SE 1/4 <hr/>	
	<p>From the E. 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°17' W., on the N. and S. center line of the SE 1/4 of sec. 30.</p> <p>Over gently rolling terrain, on a portion of public lands bdy.</p>
39.97	The center E. 1/16 sec. cor. of sec. 30.
<hr/> SW 1/4 <hr/>	
	<p>From the W. 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°15' W., on the N. and S. center line of the SW 1/4 of sec. 30.</p> <p>Over gently rolling terrain, within public lands.</p>
39.86	The center W. 1/16 sec. cor. of sec. 30.
<hr/> NW 1/4 <hr/>	
	<p>From the center W. 1/16 sec. cor. of sec. 30.</p> <p>N. 0°07' W., on the N. and S. center line of the NW 1/4 of sec. 30.</p>

Subdivision of Section 30,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling terrain, within public lands.
19.885	Point for the NW 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NW 1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T 6 S R 26 E NW 1/16 S 30 2021 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post W. of cor.
29.827	Point for the center N-NW 1/16 sec. cor. of sec. 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 6 S R 26 E S 30 C-N-NW 1/64 2021 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post W. of cor.
39.77	The W. 1/16 sec. cor. of secs. 19 and 30. <hr/> From the center N. 1/16 sec. cor. of sec. 30. S. 89°47' W., on the E. and W. center line of the NW 1/4 of sec. 30. Over gently rolling terrain, within public lands.
20.05	The NW 1/16 sec. cor. of sec. 30.
34.43	The N. 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp. <hr/>

Subdivision of Section 30,
T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>NE 1/4 of the NW 1/4</p> <hr style="width: 20%; margin: auto;"/>
20.03	<p>From the center N-N 1/64 sec. cor. of sec. 30.</p> <p>S. 89°41' W., on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 30.</p> <p>Over gently rolling terrain, within public lands.</p> <p>The center N-NW 1/64 sec. cor. of sec. 30.</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr style="width: 20%; margin: auto;"/> <p>The area surveyed and resurveyed is located approximately 3.3 miles N. 10° E., of the intersection of Interstate Highway No. 70 and S. 8th Street, Safford, Arizona.</p> <p>The terrain is predominately gently rolling. The elevation ranges from about 3005 to 3080 feet above sea level. City of Safford Landfill is partly situated in sec. 30.</p> <p>The mean magnetic declination of 9 1/4° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2020 for the dates of survey.</p> <hr style="width: 20%; margin: auto;"/>

CERTIFICATE OF SURVEY

I, Blas J. Urena, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 17th day of February, 2021, I have dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines, and subdivided section 30, T. 6 S., R. 26 E., Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

9/16/2021
(Date)

Blas J. Urena
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of section 30, T. 6 S., R. 26 E., Gila and Salt River Meridian, in the State of Arizona, executed by Blas J. Urena, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

8/17/2021
(Date)

Mark Mabe
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~