

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF PORTIONS OF
THE HOPI AND NAVAJO PARTITION LINE,
THE COMPLETION SURVEYS OF THE NORTH AND WEST BOUNDARIES,
THE SURVEY OF THE SOUTH BOUNDARY,
THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF CERTAINS SECTIONS
TOWNSHIP 30 NORTH, RANGE 12 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Rosendo Ramos Serrano, Cadastral Surveyor

Under Special Instructions dated April 23, 2021 approved April 23, 2021 which provided for the surveys included under Group No. 1209, and assignment instructions dated June 8, 2021.

Survey commenced June 7, 2021

Survey completed July 15, 2021

INDEX DIAGRAM

TOWNSHIP 30 NORTH RANGE 12 EAST
 GILA & SALT RIVER MERIDIAN, ARIZONA

| | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|
| | | | 18 | | 17 | | 16 | | 15 | | 14 |
| 6 | 55 | 7 | 5 | 47 | 4 | 40 | 3 | 33 | 2 | 26 | 1 |
| 55 | | | 54 | | 46 | | 39 | | 32 | | 25 |
| 7 | 54 | 7 | 8 | 45 | 9 | 38 | 10 | 31 | 11 | 24 | 12 |
| 54 | | | 53 | | 45 | | 38 | | 31 | | 24 |
| 18 | 52 | 6 | 17 | 44 | 16 | 37 | 15 | 30 | 14 | 23 | 13 |
| 52 | | | 51 | | 43 | | 37 | | 30 | | 22 |
| 19 | 50 | 6 | 20 | 43 | 21 | 36 | 22 | 29 | 23 | 22 | 24 |
| 4 | | | | | | | | | | | |
| 14 | 50 | | 49 | | 42 | | 35 | | 28 | | 21 |
| 13 | 30 | 48 | 29 | 41 | 28 | 35 | 27 | 28 | 26 | 20 | 25 |
| | 48 | | 48 | | 41 | | 34 | | 27 | | 20 |
| 13 | 31 | 47 | 32 | 40 | 33 | 33 | 34 | 27 | 35 | 19 | 36 |
| | 12 | | 11 | | 10 | | 9 | | 9 | | 8 |

Subdivision of Section 1 Pages 56-57
 Subdivision of Section 2 Pages 57-58
 Subdivision of Section 3 Pages 58-59

T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of portions of the Hopi and Navajo Partition line, the completion surveys of the North and West boundaries, the survey of the South boundary, the subdivisional lines and the subdivision of certain sections, T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

In 1996-97, a portion of the Hopi and Navajo Partition line, was surveyed by Steven K. Hansen and Joe R. Salazar Cadastral Surveyors, under Group No. 804.

In 2003, portions of the N and W. boundaries, were surveyed by Gordon R. Bubel, Cadastral Surveyor, under Group Nos. 906 and 909.

In 2009, the dependent resurvey and survey of Township 29 North, Range 9 East, executed by Leonard R. Sandoval, Cadastral Surveyor, under Group No. 1057.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated April 23, 2021 for Group No. 1209, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R10-2 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Navigation Satellite System (GNSS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8820 FERN FERNO MESA CORS ARP, DL1882 AZFL NAU FLAGSTAFF CORS ARP, DP9946 P008 TUBA_CITY_AZ2007 CORS ARP.

The NAD 83 (CORS2011) (EPOCH 2010.0000), geographic position of the corner of Townships 29 and 30 North, Ranges 12 and 12 1/2 East is as follows:

Latitude: 35°55'53.058" N. Longitude: 111°03'06.132" W.

The NAD 83 (CORS2011) (EPOCH 2010.0000), geographic position of the corner sections 5, 6, 31 and 32 on the north boundary of the township.

T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

Latitude: 36°01'01.156" N. Longitude: 111°08'27.400" W.

The mean magnetic declination is 10° E.

Dependent Resurvey of portions of the Hopi and Navajo Partition Line, T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by
Steven K. Hansen and Joe R. Salazar, in 1996-97

Beginning at the closing cor. of the Hopi and Navajo Partition Line on the W. bdy. of the tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground with brass cap mkd. T30N CC R11E R12E S24 S19 HOPI NAVAJO 2003.

This cor. now functions as a crossing closing corner.

Remarks the brass cap to read:

| | |
|--------|--------|
| T 30 N | |
| CCC | |
| R 11 E | R 12 E |
| S 24 | S 19 |
| HOPI | |
| ----- | |
| NAV | AJO |
| 2021 | |
| 2003 | |

Cor. is located in a barbwire fence, 5 strands, bears E. and W.

From this point the 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T30N R11E R12E 1/4 S24 S19 2003, bears N., 13.77 chs. dist.

Add the marks 2021 to the brass cap.

Set a steel fence post 5 ft. long, W. of the cor.

East, along the Hopi and Navajo Partition Line.

22.05

Witness point 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. WP11 HOPI NAVAJO 1997 2003.

Add the marks 2021 to the brass cap.

Dependent Resurvey of portions of the Hopi and Navajo Partition Line,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | East, beginning new measurement. |
| 42.87 | <p>True point for witness point 12 at proportionate dist., find the orig. stainless steel post, 28 ins. long, 2 1/2 ins. diam., with brass cap mkd. WP12 HOPI NAVAJO 1997, laying loose and leaning against the Hopi and Navajo bdy. fence.</p> <p>Reset the stainless steel post, 26 ins. in the ground,</p> <p>Add the marks 2021 to the brass cap.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | Cor. is located in a barbwire fence, 5 strands, bears E. and W. |
| 48.54 | <p>Witness point 13, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. WP13 HOPI NAVAJO 1997, with a steel fence post set E. of the cor.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears E. and W.</p> <hr/> |
| | East, beginning new measurement. |
| 10.75 | <p>True point for witness point 14 at proportionate dist, find the original magnet in a white plastic case in depression in ground and the accessory steel fence post alongside.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">WP 14 HOPI ——— NAVAJO</p> <p style="text-align: center;">2021</p> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Cor. is located in a barbwire fence, 5 strands, bears E. and W. |
| 10.88 | Point for the crossing closing cor. bet. secs. 19 and 20, hereinafter described. |
| 14.99 | Angle point 39, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. AP39 HOPI NAVAJO 1997. |

Dependent Resurvey of portions of the Hopi and Navajo Partition Line,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located at the cor. of fences, barb wire fence, 5 strands, bears N. and W.</p> <hr/> <p>Note: Witness point 15 is not needed to control this survey, and has not been recovered.</p> <hr/> <p>North, beginning new measurement.</p> |
| 43.52 | <p>Witness point 16, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. WP16 HOPI NAVAJO 1997.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> |
| 53.79 | <p>Point for the crossing closing cor. bet. secs. 17 and 20, hereinafter described.</p> |
| 55.39 | <p>Witness point 17, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. WP17 HOPI NAVAJO 1997.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Reset the stainless steel post 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground.</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> <hr/> <p>North, beginning new measurement.</p> |
| 42.58 | <p>Witness point 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. WP18 HOPI NAVAJO 1997.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> |
| 78.40 | <p>Point for the crossing closing cor. bet. secs. 8 and 17, hereinafter described.</p> |

Dependent Resurvey of portions of the Hopi and Navajo Partition Line,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 86.89 | <p>At proportionated dist. for witness point 19, find the accessory steel fence post, there is no other remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP 19 HOPI —— NAVAJO</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set steel fence post, 6 ft. long, W. of the cor.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> |
| 123.40 | <p>Witness point 20, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. WP20 HOPI NAVAJO 1997.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> <hr/> <p>Note: Witness point 21 is not needed to control this survey, and has not been recovered.</p> <hr/> <p>From witness point 22, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. WP22 HOPI NAVAJO 1997.</p> <p>Add the marks 2021 to the brass cap.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> <p>North, along the Hopi and Navajo Partition Line.</p> |
| 5.21 | <p>Point for the crossing closing cor. bet. secs. 5 and 8, hereinafter described.</p> |
| 14.63 | <p>Witness point 23, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. WP23 HOPI NAVAJO 1997.</p> <p>Add the marks 2021 to the brass cap.</p> |

Dependent Resurvey of portions of the Hopi and Navajo Partition Line,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Cor. is located at intersection of fences, barbwire fence, 5 strands, bears N., S. and S. 52° W.</p> |
| | <p style="text-align: center;">Survey of the South Boundary, T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> |
| | <p>From the corner of Townships 29 and 30 North, Ranges 12 and 12 1/2 East, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with a brass cap mkd. T30N R12E R12 1/2E S36 S35 S1 S4 T29N 2021, with a steel fence post to the W. of the cor.</p> |
| | <p>West, bet. secs. 1 and 36, on the S. bdy. of the Tp.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 30 N R 12 E S 36 1/4 ——— S 1 T 29 N 2021</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 40.10 | <p>Trail road, bears N. 35° E. and S. 35° W.</p> |
| 80.00 | <p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 30 N R 12 E S 35 S 36 S 2 S 1 T 29 N 2021</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |

Survey of the South Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | West, bet. secs. 2 and 35. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 2 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 30 N R 12 E S 35 1/4 ——— S 2 T 29 N 2021 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, N. of the cor. |
| 80.00 | Point for the cor. of secs. 2, 3, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 30 N R 12 E S 34 S 35 ——— ——— S 3 S 2 T 29 N 2021 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, N. of the cor. |
| | _____ |
| | West, bet secs. 3 and 34. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 30 N R 12 E S 34 1/4 ——— S 3 T 29 N 2021 </div> |

Survey of the South Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|--|--------|--------|------|------|-----|-----|--------|--|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> | | | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 30 N</td><td>R 12 E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T 29 N</td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <p>From which</p> <p style="padding-left: 40px;">A point at base of sandstone, 30 ft. high, bears N. 84°38' W., 10.91 lks. dist., mkd. XBO.</p> <hr/> | T 30 N | R 12 E | S 33 | S 34 | S 4 | S 3 | T 29 N | | | |
| T 30 N | R 12 E | | | | | | | | | | |
| S 33 | S 34 | | | | | | | | | | |
| S 4 | S 3 | | | | | | | | | | |
| T 29 N | | | | | | | | | | | |
| | <p>West, bet. secs. 4 and 33.</p> | | | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 30 N</td><td>R 12 E</td></tr> <tr><td>S 33</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td colspan="2">T 29 N</td></tr> </table> <p>2021</p> </div> | T 30 N | R 12 E | S 33 | | 1/4 | — | S 4 | | T 29 N | |
| T 30 N | R 12 E | | | | | | | | | | |
| S 33 | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| S 4 | | | | | | | | | | | |
| T 29 N | | | | | | | | | | | |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> | | | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> | | | | | | | | | | |

Survey of the South Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 30 N R 12 E S 32 S 33 S 5 S 4 T 29 N 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, N. of the cor. Cor. is located in the southerly gutter of a graded dirt road, 35 ft. wide, bears N. 72° E. and S. 62° W. |
| | <hr/> West, bet. secs. 5 and 32. |
| 0.35 | Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 65° E. and S. 61° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 5 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E S 32 1/4 ——— S 5 T 29 N 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, N. of the cor. |
| 80.00 | Point for the cor. of secs. 5, 6, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E S 31 S 32 S 6 S 5 T 29 N 2021 |

Survey of the South Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 31 1/4 ——— S 6 T 29 N</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 81.67 | <p>Point for the cor. of Tps. 29 and 30 N., Rs. 11 and 12 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 11 E R 12 E S 36 S 31 S 1 S 6 T 29 N</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <p>From this cor. point, the cor. of Tps. 29 and 30 N., Rs. 9 and 10 E., bears W. 958.67 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap mkd. T30N R9E R10E S36 S31 S1 S6 T29N 2009 2021.</p> <hr/> |

The completion Survey of the West Boundary,
T. 30 N, R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From the cor. of Tps. 29 and 30 N., Rs. 11 and 12 E, hereinbefore described.</p> <p>North, bet. secs. 31 and 36, on the W. bdy. of the Tp.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 N 1/4 R 11 E R 12 E S 36 S 31</p> </div> <p>2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| | <p>80.00 Point for the cor. of secs. 25, 30, 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 N R 11 E R 12 E S 25 S 30 S 36 S 31</p> </div> <p>2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> |
| | <p>North, bet. secs. 25 and 30.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 N 1/4 R 11 E R 12 E S 25 S 30</p> </div> <p>2021</p> |

**The completion Survey of the West Boundary,
T. 30 N, R. 12 E., Gila and Salt River Meridian, Arizona**

| CHAINS | | | | | | | | | | | |
|--------|--|--------|--------|--------|--------|------|------|---|-----|--------|------|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> | | | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 30 N</td></tr> <tr><td>R 11 E</td><td>R 12 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2">—</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> | T 30 N | | R 11 E | R 12 E | S 24 | S 19 | — | | S 25 | S 30 |
| T 30 N | | | | | | | | | | | |
| R 11 E | R 12 E | | | | | | | | | | |
| S 24 | S 19 | | | | | | | | | | |
| — | | | | | | | | | | | |
| S 25 | S 30 | | | | | | | | | | |
| 26.21 | <p>The crossing closing cor. at the Hopi and Navajo Partition Line, on the W. bdy. of the tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">The completion Survey of the North Boundary, T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 30 and 31 N., Rs. 12 and 12 1/2 E, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground with a brass cap mkd. T31N R12E R12 1/2E S36 S33 S1 S4 T30N 2021, with a steel fence post to the W. of the cor.</p> <p>West, bet. secs. 1 and 36, on the N. bdy. of the Tp.</p> | | | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 31 N</td><td>R 12 E</td></tr> <tr><td></td><td>S 36</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td></td><td>S 1</td></tr> <tr><td>T 30 N</td><td></td></tr> </table> <p>2021</p> </div> | T 31 N | R 12 E | | S 36 | 1/4 | — | | S 1 | T 30 N | |
| T 31 N | R 12 E | | | | | | | | | | |
| | S 36 | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| | S 1 | | | | | | | | | | |
| T 30 N | | | | | | | | | | | |

The completion Survey of the North Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|---|--------|--------|------|------|-----|-----|--------|--|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> | | | | | | | | | | |
| 71.97 | <p>Power line, bears S. 9° E. and N. 9° W.</p> | | | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 31 N</td> <td>R 12 E</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td colspan="2">T 30 N</td> </tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <hr/> <p>West, bet. secs. 2 and 35.</p> | T 31 N | R 12 E | S 35 | S 36 | S 2 | S 1 | T 30 N | | | |
| T 31 N | R 12 E | | | | | | | | | | |
| S 35 | S 36 | | | | | | | | | | |
| S 2 | S 1 | | | | | | | | | | |
| T 30 N | | | | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 31 N</td> <td>R 12 E</td> </tr> <tr> <td>S 35</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 2</td> <td></td> </tr> <tr> <td colspan="2">T 30 N</td> </tr> </table> <p>2021</p> </div> | T 31 N | R 12 E | S 35 | | 1/4 | — | S 2 | | T 30 N | |
| T 31 N | R 12 E | | | | | | | | | | |
| S 35 | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| S 2 | | | | | | | | | | | |
| T 30 N | | | | | | | | | | | |
| 80.00 | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <p>Point for the cor. of secs. 2, 3, 24 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> | | | | | | | | | | |

The completion Survey of the North Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T 31 N R 12 E S 34 S 35 S 3 S 2 T 30 N</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <hr/> <p>West, bet. secs. 3 and 34.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 34 1/4 ——— S 3 T 30 N</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 59.07 | <p>Intersect the easterly right-of-way fence of the Arizona State Route No. 264, parallel to the highway.</p> |
| 65.60 | <p>Intersect Arizona State Route No. 264, asphalt surfaced, 29 ft. wide, bears S. 77° E. and N. 77° W.</p> |
| 72.14 | <p>Intersect the westerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway.</p> |
| 80.00 | <p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |

The completion Survey of the North Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | |
|--------|---|--------|--------|------|------|-----|-----|--------|--|--------|--|
| | <div style="text-align: center;"> <table border="1"> <tr><td>T 31 N</td><td>R 12 E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T 30 N</td></tr> </table> <p>2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <hr/> </div> | T 31 N | R 12 E | S 33 | S 34 | S 4 | S 3 | T 30 N | | | |
| T 31 N | R 12 E | | | | | | | | | | |
| S 33 | S 34 | | | | | | | | | | |
| S 4 | S 3 | | | | | | | | | | |
| T 30 N | | | | | | | | | | | |
| 40.00 | <p>West, bet. secs. 4 and 33.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> | | | | | | | | | | |
| 41.80 | <div style="text-align: center;"> <table border="1"> <tr><td>T 31 N</td><td>R 12 E</td></tr> <tr><td>S 33</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td colspan="2">T 30 N</td></tr> </table> <p>2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> </div> | T 31 N | R 12 E | S 33 | | 1/4 | — | S 4 | | T 30 N | |
| T 31 N | R 12 E | | | | | | | | | | |
| S 33 | | | | | | | | | | | |
| 1/4 | — | | | | | | | | | | |
| S 4 | | | | | | | | | | | |
| T 30 N | | | | | | | | | | | |
| 48.55 | <p>Underground water line, bears N. 12° E. and S. 12° W.</p> <p>Power line, bears N. 16° E. and S. 16° W.</p> | | | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel rod, 9/16 ins. diam., 18 ins. long, cemented in a 5/8 in. drill hole in sandstone, with 3 1/4 ins. diam. brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 31 N</td><td>R 12 E</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T 30 N</td></tr> </table> <p>2021</p> <p>Deposit a crush magnet, at the base of the stainless steel rod.</p> </div> | T 31 N | R 12 E | S 32 | S 33 | S 5 | S 4 | T 30 N | | | |
| T 31 N | R 12 E | | | | | | | | | | |
| S 32 | S 33 | | | | | | | | | | |
| S 5 | S 4 | | | | | | | | | | |
| T 30 N | | | | | | | | | | | |

The completion Survey of the North Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a steel fence post in a 1 in. diam., drill hole, 5 ft. long, N. of the cor.</p> <hr/> <p>West, bet. secs. 5 and 33.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 32 1/4 ——— S 5 T 30 N</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <hr/> <p>West, beginning new measurement.</p> |
| 35.62 | <p>The closing cor. of secs. 5 and 32, on the N. bdy. of the tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground with brass cap mkd. T31N R12E S32 CC S5 HOPI NAVAJO T30N R12E 2003.</p> <p>This cor. now functions as the crossing closing corner.</p> <p>Remarks the brass cap to read:</p> <p style="text-align: center;">T 31 N R 12 E N C S 32 H A C O V C ——— P A S 5 I J O T 30 N R 12 E 2021 2003</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> <hr/> <p>N. 89°57' W., beginning new measurement.</p> |

The completion Survey of the North Boundary,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

4.38

The cor. of secs. 5, 6, 31 and 32, on the N. bdy of the Tp.,
monumented with a stainless steel post, 2 1/2 ins. diam., firmly
set, projecting 4 ins. above the ground, with a brass cap
erroneously mkd. T31N R12E S6 S5 S31 S32 T30N R12E 2003.

Remark the brass cap to read:

| | |
|--------|--------|
| T 31 N | R 12 E |
| S 31 | S 32 |
| S 6 | S 5 |
| T 30 N | R 12 E |
| | 2021 |
| | 2003 |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.,
hereinbefore described.

N. 0°01' W., bet. secs. 35 and 36.

40.00

Point for the 1/4 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins.
in the ground, with brass cap mkd.

| | |
|--------|--------|
| T 30 N | R 12 E |
| | 1/4 |
| S 35 | S 36 |
| | 2021 |

Deposit a magnet, in a white plastic case, at the base of the
stainless steel post.

Set a steel fence post 5 ft. long, W. of the cor.

80.00

Point for the cor. of secs. 25, 26, 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins.
in the ground, with brass cap mkd.

| | |
|--------|--------|
| T 30 N | R 12 E |
| S 26 | S 25 |
| S 35 | S 36 |
| | 2021 |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 25, 28, 33 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a brass cap mkd. T30N R12E R12 1/2E S25 S28 S36 S33 2021, with a steel fence post to the W. of the cor.</p> <p>West, bet. secs. 25 and 36.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 25 1/4 ——— S 36 2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 80.00 | <p>The cor. of secs. 25, 26, 35 and 36, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 25 and 26.</p> |
| 20.90 | <p>Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 66° E. and S. 66° W.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 26 S 25 2021</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|------|------|------|------|--|------|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <p>From this cor. point, center of windmill well casing 6 ins. diam., projecting 16 ins. above the ground, bears S. 18°45' E., 19.49 chs. dist., windmill base 8 ft. x 8 ft. x 36 ft. high.</p> | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 30 N</td> <td style="padding: 0 10px;">R 12 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 26</td> <td style="padding: 0 10px;">S 25</td> </tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 21, 24, 25 and 28, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground with a brass cap mkd. T30N R12E R12 1/2E S24 S21 S25 S28 2021, with a steel fence post to the W. of the cor.</p> <p>West, bet. secs. 24 and 25.</p> | T 30 N | R 12 E | S 23 | S 24 | S 26 | S 25 | | |
| T 30 N | R 12 E | | | | | | | | |
| S 23 | S 24 | | | | | | | | |
| S 26 | S 25 | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 31 N</td> <td style="padding: 0 10px;">R 12 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 25</td> </tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> | T 31 N | R 12 E | | S 24 | 1/4 | — | | S 25 |
| T 31 N | R 12 E | | | | | | | | |
| | S 24 | | | | | | | | |
| 1/4 | — | | | | | | | | |
| | S 25 | | | | | | | | |
| 58.50 | <p>Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 15° E. and S. 15° W.</p> | | | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.00 | <p>The cor. of secs. 23, 24, 25 and 26, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26, hereinbefore described. N. 0°01' W., bet. secs. 23 and 24.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 N R 12 E 1/4 S 23 S 24</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 N R 12 E S 14 S 13 S 23 S 24</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 13, 16, 21 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground with a brass cap mkd. T30N R12E R12 1/2E S13 S16 S24 S21 2021, with a steel fence post to the W. of the cor.</p> <p>West, bet. secs. 13 and 24.</p> |
| 37.30 | <p>Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 15° E. and S. 15° W.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 80.00 | <p>The cor. of secs. 13, 14, 23 and 24, hereinbefore described.</p> <hr style="border: 0.5px solid black;"/> <p>From the cor. of secs. 13, 14, 23 and 24, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 13 and 14.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 14 S 13</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|---------|---|
| | Set a steel fence post 5 ft. long, W. of the cor. |
| | <hr/> |
| | From the cor. of secs. 9, 12, 13 and 16 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground with a brass cap mkd. T30N R12E R12 1/2E S12 S9 S13 S16 2021, with a steel fence post to the W. of the cor. |
| | West, bet. secs. 12 and 13. |
| 23.63 | Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 6° E. and S. 6° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 12 and 13. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 31 N R 12 E S 12 1/4 ——— S 13 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, N. of the cor. |
| 80.00 | The cor. of secs. 11, 12, 13 and 14, hereinbefore described. |
| | <hr/> |
| | From the cor. of secs. 11, 12, 13 and 14, hereinbefore described. |
| | N. 0°01' W., bet. secs. 11 and 12. |
| 36.55 | Power line, bears N. 89° E. and S. 89° W. |
| | From this point, a power pole, bears S. 89°46' W., 1.15 chs. dist., extends S. 89° W. and N. 65° W. |
| ..40.00 | Point for the 1/4 sec. cor. of secs. 11 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E 1/4 S 11 S 12 2021 |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | |
|---------|---|--------|--------|-----|-----|------|------|
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | |
| | Set a steel fence post 5 ft. long, westerly of the cor. | | | | | | |
| ..40.84 | Property woven wire fence and single strand barbwire fence, bears N. 73° E. and S. 73° W. | | | | | | |
| | From this point, a corner of fence, bears N. 73° E., 1.62 chs. dist., extending S. 73° W. and N. 17° W. | | | | | | |
| ..46.45 | Property woven wire fence and single strand barbwire fence, bears S. 17° E. and N. 17° W. | | | | | | |
| ..48.85 | Underground water line, bears N. 83° E. and S. 83° W. | | | | | | |
| 80.00 | Point for the cor. of secs. 1, 2, 11 and 12. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. | | | | | | |
| | <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 30 N</td> <td>R 12 E</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> </table> | T 30 N | R 12 E | S 2 | S 1 | S 11 | S 12 |
| T 30 N | R 12 E | | | | | | |
| S 2 | S 1 | | | | | | |
| S 11 | S 12 | | | | | | |
| | 2021 | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | |
| | Set a steel fence post 5 ft. long, westerly of the cor. | | | | | | |
| | <hr/> | | | | | | |
| | From the cor. of secs. 1, 4, 9 and 12 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground with a brass cap mkd. T30N R12E R12 1/2E S1 S4 S12 S9 2021, with a steel fence post to the W. of the cor. | | | | | | |
| | West, bet. secs. 1 and 12. | | | | | | |
| 5.95 | Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 11° E. and S. 11° W. | | | | | | |
| 9.90 | Power line, bears N. 83° E. and S. 38° W. | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 1 and 12. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd. | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 31 N R 12 E S 1 1/4 ——— S 12 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, N. of the cor. |
| 40.17 | Trail road, bears N. 36° E. and S. 35° W. |
| 80.00 | The cor. of secs. 1, 2, 11 and 12, hereinbefore described. |
| | ————— |
| | From the cor. of secs. 1, 2, 11 and 12, hereinbefore described. |
| | N. 0°01' W., bet. secs. 1 and 2. |
| 36.02 | Intersect the southerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 37.55 | Intersect Arizona State Route No. 264, asphalt surfaced, 29 ft. wide, bears S. 77° E. and N. 77° W. |
| 39.12 | Intersect the northerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 1 and 2. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E 1/4 S 2 S 1 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| 72.18 | The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. |
| | ————— |
| | From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described. |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>N. $0^{\circ}01'$ W., bet. secs. 34 and 35. 40.00 Point for the $1/4$ sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 34 S 35</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 27 S 26 S 34 S 35</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, hereinbefore described.</p> <p>West, bet. secs. 26 and 35.</p> |
| 38.15 | <p>Trail road, bears N. 65° E. and S. 65° W.</p> |
| 40.00 | <p>Point for the $1/4$ sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 26 1/4 ——— S 35</p> <p style="text-align: center;">2021</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, N. of the cor. |
| 80.00 | The cor. of secs. 26, 27, 34 and 35, hereinbefore described. <hr/> |
| | From the cor. of secs. 26, 27, 34 and 35, hereinbefore described. N. 0°01' W., bet. secs. 26 and 27. |
| 2.00 | Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 72° E. and S. 75° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 30 N R 12 E 1/4 S 26 S 27 2021 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, W. of the cor. |
| 80.00 | Point for the cor. of secs. 22, 23, 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 30 N R 12 E S 22 S 23 S 27 S 26 2021 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, W. of the cor. <hr/> |
| | From the cor. of secs. 23, 24, 25 and 26, hereinbefore described. West, bet. secs. 23 and 26. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 23 and 26. |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 23 1/4 ——— S 26</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 80.00 | <p>The cor. of secs. 22, 23, 26 and 27, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27, hereinbefore described.</p> <p>N. 0°01' W., bet. secs. 22 and 23.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 22 S 23</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 79.83 | <p>Property fence line, bears N. 55° E., S. 55° W.</p> |
| 80.00 | <p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 15 S 14 S 22 S 23</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a steel fence post 5 ft. long, W. of the cor. Cor. is located inside enclosed fence property.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24, hereinbefore described. West, bet. secs. 14 and 23.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 14 1/4 ——— S 23</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 40.24 | Trail road, bears N. 69° E. and S. 69° W. |
| 79.75 | Property fence line, bears N. 55° E., S. 55° W. |
| 80.00 | <p>The cor. of secs. 14, 15, 22 and 23, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23, hereinbefore described. N. 0°01' W., bet. secs. 14 and 15.</p> |
| 4.11 | Property fence line, bears N. 55° E., S. 55° W. |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 15 S 14</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, westerly of the cor.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|--|--------|--------|------|------|------|------|------|--|
| 80.00 | <p>Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 30 N</td> <td>R 12 E</td> </tr> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, westerly of the cor.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14, hereinbefore described. West, bet. secs. 11 and 14.</p> | T 30 N | R 12 E | S 10 | S 11 | S 15 | S 14 | | |
| T 30 N | R 12 E | | | | | | | | |
| S 10 | S 11 | | | | | | | | |
| S 15 | S 14 | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 31 N</td> <td>R 12 E</td> </tr> <tr> <td>S 11</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 14</td> <td></td> </tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, westerly of the cor.</p> | T 31 N | R 12 E | S 11 | | 1/4 | — | S 14 | |
| T 31 N | R 12 E | | | | | | | | |
| S 11 | | | | | | | | | |
| 1/4 | — | | | | | | | | |
| S 14 | | | | | | | | | |
| 80.00 | <p>The cor. of secs. 10, 11, 14 and 15, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15, hereinbefore described. N. 0°01' W., bet. secs. 10 and 11.</p> | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> | | | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 30 N R 12 E 1/4 S 10 S 11 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, westerly of the cor. |
| 74.00 | Power line, bears S. 65° E. and N. 65° W. |
| 80.00 | Point for the cor. of secs. 2, 3, 10 and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E S 3 S 2 ———— S 10 S 11 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, westerly of the cor. |
| | From this cor. point, a rebar 1/2 in. diam., firmly set, projecting 1 in. above the ground, with a orange plastic cap mkd. GPS RLS 12048, bears S. 69°23' W., 11.34 chs. dist., with a steel fence post nearby. |
| | From the cor. of secs. 1, 2, 11 and 12, hereinbefore described. |
| | West, bet. secs. 2 and 11. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 2 and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 31 N R 12 E S 2 1/4 ——— S 11 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Set a steel fence post 5 ft. long, N. of the cor. |
| 60.82 | Underground water line, bears S. 61° E. and N. 61° W. |
| 80.00 | The cor. of secs. 2, 3, 10 and 11, hereinbefore described. |
| | <hr/> |
| | From the cor. of secs. 2, 3, 10 and 11, hereinbefore described. |
| | N. 0°01' W., bet. secs. 2 and 3. |
| 10.72 | Underground water line, bears S. 61° E. and N. 61° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 2 and 3. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E 1/4 S 3 S 2 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| 55.02 | Intersect the southerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 56.57 | Intersect Arizona State Route No. 264, asphalt surfaced, 29 ft. wide, bears S. 77° E. and N. 77° W. |
| 58.14 | Intersect the northerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 72.18 | The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described. |
| | <hr/> |
| | From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described. |
| | N. 0°02' W., bet. secs. 33 and 34. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 33 and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 30 N R 12 E 1/4 S 33 S 34 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| 58.60 | Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 59° E. and S. 56° W. |
| 80.00 | Point for the cor. of secs. 27, 28, 33 and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E S 28 S 27 S 33 S 34 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| | <hr/> From the cor. of secs. 26, 27, 34 and 35, hereinbefore described. West, bet secs. 27 and 34. |
| 8.66 | Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 77° E. and S. 77° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 27 and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
| | T 31 N R 12 E S 27 1/4 ——— S 34 2021 |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 80.00 | <p>The cor. of secs. 27, 28, 33 and 34, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 27 and 28.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 28 S 27</p> <p style="text-align: center;">2021</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 21 S 22 S 28 S 27</p> <p style="text-align: center;">2021</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27, hereinbefore described.</p> <p>West, bet. secs. 22 and 27.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 80.00 | <p>The cor. of secs. 21, 22, 27 and 28, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28, hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 21 and 22.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 21 S 22</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 16 S 15 S 21 S 22</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> |
| | <p>From the cor. of secs. 14, 15, 22 and 23, hereinbefore described. West, bet. secs. 15 and 22.</p> |
| 2.66 | <p>Property fence line, bears S. 35° E. and N. 35° W.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 15 and 22.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 31 N R 12 E S 15 1/4 ——— S 22 2021</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 80.00 | <p>The cor. of secs. 15, 16, 21 and 22, hereinbefore described.</p> <hr/> |
| | <p>From the cor. of secs. 15, 16, 21 and 22, hereinbefore described. N. 0°02' W., bet. secs. 15 and 16.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 30 N R 12 E 1/4 S 16 S 15 2021</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |
| | <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

| | |
|--------|--------|
| T 30 N | R 12 E |
| S 09 | S 10 |
| S 16 | S 15 |

2021

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post 5 ft. long, westerly of the cor.

Cor. is located 18 lks. S., of a narrow drainage 4 ft. wide, 1 ft. deep, drains S. 80° E. and N. 72° W.

From the cor. of secs. 10, 11, 14 and 15, hereinbefore described.

West, bet. secs. 10 and 15.

40.00 Point for the 1/4 sec. cor. of secs. 10 and 15.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

| | |
|--------|---------|
| T 31 N | R 12 E |
| | S 10 |
| | 1/4 ——— |
| | S 15 |

2021

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post 5 ft. long, westerly of the cor.

80.00 The cor. of secs. 9, 10, 15 and 16, hereinbefore described.

From the cor. of secs. 9, 10, 15 and 16, hereinbefore described.

N. 0°02' W., bet. secs. 9 and 10.

40.00 Point for the 1/4 sec. cor. of secs. 9 and 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| | |
|--------|---|
| CHAINS | <p style="text-align: center;">T 30 N R 12 E 1/4 S 9 S 10</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <p>Cor. is located N. 31°43' E., 29.5 lks. dist., center of intersection, 2 track road, 8 ft. wide, bears N. 71° E., S. 26° W. and N. 56° W.</p> |
| 80.00 | <p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 4 S 3 ----- S 9 S 10</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11, hereinbefore described.</p> <p>West, bet. secs. 3 and 10.</p> |
| 12.63 | <p>Power line, bears S. 65° E. and N. 65° W.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 3 1/4 ----- S 10</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | Set a steel fence post 5 ft. long, N. of the cor. |
| 80.00 | The cor. of secs. 3, 4, 9 and 10, hereinbefore described. |
| | <hr/> |
| | From the cor. of secs. 3, 4, 9 and 10, hereinbefore described. |
| | N. 0°02' W., bet. secs. 3 and 4. |
| 32.00 | Power line, bears S. 65° E. and N. 65° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 3 and 4. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E 1/4 S 4 S 3 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| 42.27 | Underground water line, bears S. 66° E. and N. 66° W. |
| 72.18 | The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described. |
| | <hr/> |
| | From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described. |
| | N. 0°03' W., bet. secs. 32 and 33. |
| 0.15 | Intersect graded Navajo Road No. 6710, 25 ft. wide, bears N. 66° E. and S. 62° W. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 32 and 33. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E 1/4 S 32 S 33 2021 |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|---|--------|--------|------|------|------|------|------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> | | | | | | | | |
| 80.00 | <p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 30 N</td><td>R 12 E</td></tr> <tr><td>S 29</td><td>S 28</td></tr> <tr><td>S 32</td><td>S 33</td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, hereinbefore described.</p> <p>West, bet. secs. 28 and 33.</p> | T 30 N | R 12 E | S 29 | S 28 | S 32 | S 33 | | |
| T 30 N | R 12 E | | | | | | | | |
| S 29 | S 28 | | | | | | | | |
| S 32 | S 33 | | | | | | | | |
| 39.37 | Trail road, bears N. 70° E. and N. 80° W. | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 31 N</td><td>R 12 E</td></tr> <tr><td>S 28</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 33</td><td></td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> | T 31 N | R 12 E | S 28 | | 1/4 | — | S 33 | |
| T 31 N | R 12 E | | | | | | | | |
| S 28 | | | | | | | | | |
| 1/4 | — | | | | | | | | |
| S 33 | | | | | | | | | |
| 80.00 | <p>The cor. of secs. 28, 29, 32 and 33, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 28 and 29.</p> | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 28 and 29. | | | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 29 S 28</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 20 S 21 ----- S 29 S 28</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28, hereinbefore described. West, bet. secs. 21 and 28.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 N R 12 E S 21 1/4 ——— S 28</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 80.00 | <p>The cor. of secs. 20, 21, 28 and 29, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29, hereinbefore described. N. 0°03' W., bet. secs. 20 and 21.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E 1/4 S 20 S 21</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E S 17 S 16 S 20 S 21</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22, hereinbefore described. West, bet. secs. 16 and 21.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | T 31 N R 12 E S 16 1/4 ——— S 21 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, N. of the cor. |
| 80.00 | The cor. of secs. 16, 17, 20 and 21, hereinbefore described. |
| | <hr/> From the cor. of secs. 16, 17, 20 and 21, hereinbefore described. |
| | N. 0°03' W., bet. secs. 16 and 17. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 16 and 17. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E 1/4 S 17 S 16 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| 80.00 | Point for the cor. of secs. 8, 9, 16 and 17. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E S 8 S 9 — — S 17 S 16 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| | <hr/> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | From the cor. of secs. 9, 10, 15 and 16, hereinbefore described. West, bet. secs. 9 and 16. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 31 N R 12 E S 9 1/4 ——— S 16 2021 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, N. of the cor. |
| 80.00 | The cor. of secs. 8, 9, 16 and 17, hereinbefore described. <hr/> |
| | From the cor. of secs. 8, 9, 16 and 17, hereinbefore described. N. 0°03' W., bet. secs. 8 and 9. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 30 N R 12 E 1/4 S 8 S 9 2021 </div> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, W. of the cor. |
| 80.00 | Point for the cor. of secs. 4, 5, 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | |
|--------|--|--------|--------|-----|-----|-----|-----|
| | <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 30 N</td> <td style="padding: 0 10px;">R 12 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> </table> | T 30 N | R 12 E | S 5 | S 4 | S 8 | S 9 |
| T 30 N | R 12 E | | | | | | |
| S 5 | S 4 | | | | | | |
| S 8 | S 9 | | | | | | |
| | 2021 | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | |
| | Set a steel fence post 5 ft. long, W. of the cor. | | | | | | |
| | Cor. is located S., 31 lks. dist., of a dirt road 8 ft. wide, bears N. 56° E. and S. 56° W. | | | | | | |
| | _____ | | | | | | |
| | From the cor. of secs. 3, 4, 9 and 10, hereinbefore described. | | | | | | |
| | West, bet. secs. 4 and 9. | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 4 and 9. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. | | | | | | |
| | <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 31 N</td> <td style="padding: 0 10px;">R 12 E</td> </tr> <tr> <td style="padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 9</td> </tr> </table> | T 31 N | R 12 E | S 4 | S 4 | 1/4 | S 9 |
| T 31 N | R 12 E | | | | | | |
| S 4 | S 4 | | | | | | |
| 1/4 | S 9 | | | | | | |
| | 2021 | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | |
| | Set a steel fence post 5 ft. long, N. of the cor. | | | | | | |
| 80.00 | The cor. of secs. 4, 5, 8 and 9, hereinbefore described. | | | | | | |
| | _____ | | | | | | |
| | From the cor. of secs. 4, 5, 8 and 9, hereinbefore described. | | | | | | |
| | N. 0°03' W., bet. secs. 4 and 5. | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 4 and 5. | | | | | | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | T 30 N R 12 E 1/4 S 5 S 4 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, W. of the cor. |
| 72.18 | The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described. <hr/> From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0°03' W., bet. secs. 31 and 32. |
| 40.00 | Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E 1/4 S 31 S 32 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, W. of the cor. |
| 80.00 | Point for the cor. of secs. 29, 30, 31 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E S 30 S 29 S 31 S 32 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post 5 ft. long, N. of the cor. |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From the cor. of secs. 28, 29, 32 and 33, hereinbefore described.</p> <p>West, bet. secs. 29 and 32.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E</p> <p>S 29</p> <p>1/4 ———</p> <p>S 32</p> </div> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 80.00 | <p>The cor. of secs. 29, 30, 31 and 32, hereinbefore described.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 29, 30, 31 and 32, hereinbefore described.</p> <p>West, bet. secs. 30 and 31.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E</p> <p>S 30</p> <p>1/4 ———</p> <p>S 31</p> </div> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 81.59 | <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 29, 30, 31 and 32, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E 1/4 S 30 S 29</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 80.00 | <p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> <p>Cor. is located, E., 31 ft. top of ridge, 15 ft. wide, 30 ft. high bears N. and S. 60° W.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29, hereinbefore described. West, bet. secs. 20 and 29.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2021</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | |
|--------|--|----|----|-----|-----|------|-----|-----|--|
| 80.00 | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <p>The cor. of secs. 19, 20, 29 and 30, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 19, 20, 29 and 30, hereinbefore described.</p> <p>West, bet. secs. 19 and 30.</p> | | | | | | | | |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E</p> <p>S 19</p> <p>1/4 ———</p> <p>S 30</p> </div> <p style="text-align: center; margin: 10px 0;">2021</p> | | | | | | | | |
| 81.50 | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 19, 20, 29 and 30, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> | | | | | | | | |
| 26.21 | <p>Intersect the Hopi and Navajo Partition Line.</p> <p>Point for the crossing closing corner</p> <p>Set a stainless steel post 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">HO</td> <td style="padding: 0 5px;">PI</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">NAV</td> <td style="padding: 0 5px;">AJO</td> </tr> <tr> <td style="padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">CCC</td> </tr> </table> <p style="text-align: center; margin: 10px 0;">2021</p> </div> | HO | PI | NAV | AJO | S 19 | S20 | CCC | |
| HO | PI | | | | | | | | |
| NAV | AJO | | | | | | | | |
| S 19 | S20 | | | | | | | | |
| CCC | | | | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears E. and W.</p> <p>From this cor. point, the angle point 39, bears E., 4.11 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the witness point 14, bears W., 13 chs. dist., hereinbefore described.</p> <p>Along the Hopi Reservation</p> |
| 40.00 | Point for the 1/4 sec. cor. of secs. 19 and 20, not monumented. |
| 80.00 | Point for the cor. of secs. 17, 18, 19 and 20, not monumented. |
| | <p>From the cor. of secs. 16, 17, 20 and 21, hereinbefore described.</p> <p>West, bet. secs. 17 and 20.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E</p> <p>S 17</p> <p>1/4 ———</p> <p>S 20</p> <p>2021</p> </div> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 75.84 | <p>Intersect the Hopi and Navajo Partition Line.</p> <p>Point for the crossing closing corner</p> <p>Set a stainless steel post 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | | | | | | | | | | | | |
|--------|--|--------|--------|--|--|---|--|---|---|------|---|---|---|---|---|---|---|---|------|--|---|---|
| | <table border="0"> <tr> <td>T 30 N</td> <td>R 12 E</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black;">N</td> <td></td> </tr> <tr> <td>H</td> <td style="border-left: 1px solid black; border-right: 1px solid black;">A</td> <td>S 17</td> </tr> <tr> <td>O</td> <td style="border-left: 1px solid black; border-right: 1px solid black;">V</td> <td>C</td> </tr> <tr> <td style="border-top: 1px solid black;">P</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-top: 1px solid black;">A</td> <td style="border-top: 1px solid black;">C</td> </tr> <tr> <td>I</td> <td style="border-left: 1px solid black; border-right: 1px solid black;">J</td> <td>S 20</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black;">O</td> <td>C</td> </tr> </table> | T 30 N | R 12 E | | | N | | H | A | S 17 | O | V | C | P | A | C | I | J | S 20 | | O | C |
| T 30 N | R 12 E | | | | | | | | | | | | | | | | | | | | | |
| | N | | | | | | | | | | | | | | | | | | | | | |
| H | A | S 17 | | | | | | | | | | | | | | | | | | | | |
| O | V | C | | | | | | | | | | | | | | | | | | | | |
| P | A | C | | | | | | | | | | | | | | | | | | | | |
| I | J | S 20 | | | | | | | | | | | | | | | | | | | | |
| | O | C | | | | | | | | | | | | | | | | | | | | |
| | 2021 | | | | | | | | | | | | | | | | | | | | | |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. | | | | | | | | | | | | | | | | | | | | | |
| | Cor. is located in a barbwire fence, 5 strands, bears N. and S. | | | | | | | | | | | | | | | | | | | | | |
| | From this cor. point, the witness point 16, bears S. 0°01' E., 10.27 chs. dist., hereinbefore described. | | | | | | | | | | | | | | | | | | | | | |
| | From this same cor. point, the witness point 17, bears N. 0°02' W., 1.60 chs. dist., hereinbefore described. | | | | | | | | | | | | | | | | | | | | | |
| | Along the Hopi Reservation | | | | | | | | | | | | | | | | | | | | | |
| 80.00 | Point for the cor. of secs. 17, 18, 19 and 20, not monumented. | | | | | | | | | | | | | | | | | | | | | |
| | <hr/> From the cor. of secs. 17, 18, 19 and 20, hereinbefore described. S. 89°59' W., bet. secs. 18 and 19. Within the Hopi Reservation. | | | | | | | | | | | | | | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 18 and 19, not monumented. | | | | | | | | | | | | | | | | | | | | | |
| 81.41 | The cor. of secs. 13, 18, 19 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with bass cap mkd. T30N R11E R12E S13 S18 S24 S19 2003. | | | | | | | | | | | | | | | | | | | | | |
| | Add the marks 2021 to the brass cap. | | | | | | | | | | | | | | | | | | | | | |
| | <hr/> From the cor. of secs. 17, 18, 19 and 20, hereinbefore described. N. 0°03' W., bet. secs. 17 and 18. Within the Hopi Reservation. | | | | | | | | | | | | | | | | | | | | | |
| 40.00 | Point for the 1/4 sec. cor. of secs. 17 and 18, not monumented. | | | | | | | | | | | | | | | | | | | | | |
| 80.00 | Point for the cor. of secs. 7, 8, 17 and 18, not monumented. | | | | | | | | | | | | | | | | | | | | | |
| | <hr/> | | | | | | | | | | | | | | | | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------|---|---|----|--|--|---|---|---|---|---|---|--|---|---|---|--|---|---|---|---|----|---|--|--|--|
| 40.00 | <p>From the cor. of secs. 8, 9, 16 and 17, hereinbefore described.</p> <p>West, bet. secs. 8 and 17.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> </div> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> | | | | | | | | | | | | | | | | | | | | | | | | |
| 75.76 | <p>Intersect the Hopi and Navajo Partition Line.</p> <p>Point for the crossing closing corner</p> <p>Set a stainless steel post 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 N R 12 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">N</td> <td></td> <td></td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">H</td> <td style="padding: 0 5px;">A</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">O</td> <td style="padding: 0 5px;">V</td> <td style="border-bottom: 1px solid black;"></td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">P</td> <td style="padding: 0 5px;">A</td> <td></td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">I</td> <td style="padding: 0 5px;">J</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">17</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">O</td> <td></td> <td></td> <td></td> </tr> </table> </div> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located in a barbwire fence, 5 strands, bears N. and S.</p> <p>From this cor. point, the witness point 18, bears S., 35.82 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the witness point 19, bears N., 8.49 chs. dist., hereinbefore described.</p> <p>Within the Hopi Reservation.</p> | N | | | | H | A | S | 8 | O | V | | C | P | A | | C | I | J | S | 17 | O | | | |
| N | | | | | | | | | | | | | | | | | | | | | | | | | |
| H | A | S | 8 | | | | | | | | | | | | | | | | | | | | | | |
| O | V | | C | | | | | | | | | | | | | | | | | | | | | | |
| P | A | | C | | | | | | | | | | | | | | | | | | | | | | |
| I | J | S | 17 | | | | | | | | | | | | | | | | | | | | | | |
| O | | | | | | | | | | | | | | | | | | | | | | | | | |
| 80.00 | <p>The cor. of secs. 7, 8, 17 and 18, hereinbefore described.</p> <hr style="width: 80%; margin-left: 0;"/> | | | | | | | | | | | | | | | | | | | | | | | | |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From the cor. of secs. 7, 8, 17 and 18, hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 7 and 18.</p> <p>Along the Hopi Reservation.</p> |
| 40.00 | Point for the 1/4 sec. cor. of secs. 7 and 18, not monumented. |
| 81.32 | <p>The cor. of secs. 7, 12, 13 and 18, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T30N R11E R12E S12 S7 S13 S18 2003.</p> <p>Add the marks 2021 to the brass cap.</p> <hr/> |
| | <p>From the cor. of secs. 7, 8, 17 and 18, hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Within the Hopi Reservation.</p> |
| 40.00 | Point for the 1/4 sec. cor. of secs. 7 and 8, not monumented. |
| 80.00 | Point for the cor. of secs. 5, 6, 7 and 8, not monumented. |
| | <hr/> <p>From the cor. of secs. 4, 5, 8 and 9, hereinbefore described.</p> <p>West, bet. secs. 5 and 8.</p> |
| 40.00 | <p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E S 5 1/4 ——— S 8</p> <p style="text-align: center;">2021</p> |
| | <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, N. of the cor.</p> |
| 75.69 | <p>Intersect the Hopi and Navajo Partition Line.</p> <p>Point for the crossing closing corner</p> <p>Set a stainless steel post 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> |

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

CHAINS

| | | | | | | |
|---|----|---|---|----|---|---|
| T | 30 | N | R | 12 | E | |
| | | N | | | | |
| | | H | A | S | 5 | |
| | | O | V | | | C |
| | | P | A | | | C |
| | | I | J | S | 8 | C |
| | | O | | | | |

2021

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Cor. is located in a barbwire fence, 5 strands, bears N. and S.

From this cor. point, the witness point 22, bears S., 5.21 chs. dist., hereinbefore described.

From this same cor. point, the witness point 23, bears N., 9.42 chs. dist., hereinbefore described.

Within the Hopi Reservation.

80.00 The cor. of secs. 5, 6, 7 and 8, hereinbefore described.

From the cor. of secs. 5, 6, 7 and 8, hereinbefore described.

West, bet. secs. 6 and 7.

Within the Hopi Reservation.

40.00 Point for the 1/4 sec. cor. of secs. 6 and 7, not monumented.

81.23 The cor. of secs. 1, 6, 7 and 12, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with bass cap mkd. T30N R11E R12E S1 S6 S12 S7 2003.

Add the marks 2021 to the brass cap.

From the cor. of secs. 5, 6, 7 and 8, hereinbefore described.

N. 0°03' W., bet. secs. 5 and 6.

Within the Hopi Reservation.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 6, not monumented.

Survey of the Subdivisional Lines,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 72.17 | <p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 1, T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>North, on the N. and S. centerline of sec. 1.</p> |
| 0.23 | Trail road, bears N. 36° E. and S. 36° W. |
| 25.34 | Intersect the southerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 26.91 | Intersect Arizona State Route No. 264, asphalt surfaced, 29 ft. wide, bears S. 73° E. and N. 73° W. |
| 28.50 | Intersect the northerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 29.09 | Power line, bears S. 72° E. and N. 74° W. |
| 40.00 | <p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 N R 12 E C 1/4 S 1</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post 5 ft. long, W. of the cor.</p> |
| 72.18 | <p>The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 4, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam. firmly set, projecting 2 ins. above the ground, with brass cap mkd. T30N R12E R12 1/2E 1/4 S1 S4 2021, with a steel fence post to the W. of the cor.</p> <p>West, on the E. and W. centerline of sec. 1.</p> |

Subdivision of Section 1,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--|---|
| 8.32 | Graded road, 28 ft. wide, bears N. 44° E. and S. 44° W. |
| 20.40 | Power line, bears N. 32° E. and S. 32° W. |
| 40.00 | The center 1/4 sec. cor. of sec. 1. |
| 66.98 | Power line, bears S. 9° E. and N. 9° W. |
| 80.00 | The 1/4 sec. cor. of secs. 1 and 2. |
| <hr/> <p>Subdivision of Section 2, T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona</p> <hr/> | |
| | From the 1/4 sec. cor. of secs. 2 and 11. |
| | N. 0°01' W., on the N. and S. centerline of sec. 2. |
| 40.00 | Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 30 N R 12 E C 1/4 S 2 |
| | 2021 |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| 45.53 | Intersect the southerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 47.06 | Intersect Arizona State Route No. 264, asphalt surfaced, 29 ft. wide, bears S. 77° E. and N. 77° W. |
| 48.63 | Intersect the northerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 72.18 | The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp. |
| <hr/> | |
| | From the 1/4 sec. cor. of secs. 1 and 2. |
| | West, on the E. and W. centerline of sec. 2. |
| 3.69 | Intersect the easterly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |

**Subdivision of Section 2,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona**

| CHAINS | |
|--|--|
| 10.29 | Intersect Arizona State Route No. 264, asphalt surfaced, 29 ft. wide, bears S. 77° E. and N. 77° W. |
| 16.73 | Intersect the westerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 40.00 | The center 1/4 sec. cor. of sec. 2. |
| 80.00 | The 1/4 sec. cor. of secs. 2 and 3. |
| <hr/> <p>Subdivision of Section 3, T. 30 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> | |
| | From the 1/4 sec. cor. of secs. 3 and 10. |
| | N. 0°02' W., on the N. and S. centerline of sec. 3. |
| 12.99 | Power line, bears S. 65° E. and N. 65° W. |
| 27.32 | Underground water line, bears S. 72° E. and N. 71° W. |
| 40.00 | Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. |
| | <p>T 30 N R 12 E C 1/4 S 3</p> <p>2021</p> |
| | Deposit a magnet, in a white plastic case, at the base of the stainless steel post. |
| | Set a steel fence post 5 ft. long, W. of the cor. |
| 64.53 | Intersect the easterly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 66.08 | Intersect Arizona State Route No. 264, asphalt surfaced, 29 ft. wide, bears S. 77° E. and N. 77° W. |
| 67.65 | Intersect the westerly right-of-way fence of the Arizona State Route No. 264, parallel to the highway. |
| 72.18 | The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp. |


Subdivision of Section 3,
T. 30 N., R. 12 E., Gila and Salt River Meridian, Arizona

| | |
|--------|--|
| CHAINS | <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>West, on the E. and W. centerline of sec. 3.</p> <p>40.00 The center 1/4 sec. cor. of sec. 3.</p> <p>74.91 Underground water line, bears S. 66° E. and N. 66° W.</p> <p>80.00 The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is situated approximately 13 miles southeasterly from Tuba City, Arizona</p> <p>The land is generally vast and open, with very little timber, with elevation ranging from approximately 5,300 ft. to 5,950 ft. above sea level in the vicinity of this survey.</p> <p>No mineral deposit or activity was noted during the course of the survey.</p> <p>The mean magnetic declination of 10° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2020 for the dates of survey.</p> <hr/> |
|--------|--|

CERTIFICATE OF SURVEY

I, Rosendo Ramos Serrano, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the day of 23rd day of April, 2021, I have dependently resurveyed portions of the Hopi and Navajo Partition line, the completion surveys of the North and West boundaries, the survey of the South boundary, the subdivisional lines and the subdivision of certain sections of Township 30 North, Range 12 East, Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

12/02/2021
(Date)


(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions of the Hopi and Navajo Partition line, the completion surveys of the North and West boundaries, the survey of the South boundary, the subdivisional lines and the subdivision of certain sections of Township 30 North, Range 12 East, Gila and Salt River, Arizona., executed by Rosendo Ramos Serrano, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

12/8/2021
(Date)


(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 30 North, Range 12 East, Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor of Arizona)~~