

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE DEPENDENT RESURVEY OF  
A PORTION OF THE WEST BOUNDARY,  
A PORTION OF THE SUBDIVISION LINES,  
THE SUBDIVISION OF 4, 8, 9, AND 17,

AND

A METES-AND-BOUNDS SURVEY THROUGH SECTIONS 4, 8, 9, AND 17,

**PARTIALLY SURVEYED TOWNSHIP 2 SOUTH, RANGE 19 WEST**

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA

**EXECUTED BY**

**Marshall Steele Wixom, Cadastral Surveyor**

Under Special Instructions dated July 31, 2020, approved August 3, 2020, which provided for the surveys included under Group No. 1201, and assignment instructions dated October 13, 2020.

**Survey commenced October 19, 2020**

**Survey completed April 27, 2021**

## INDEX DIAGRAM

TOWNSHIP 2 SOUTH                      RANGE 19 WEST  
GILA & SALT RIVER MERIDIAN, ARIZONA

7							
7	6	5	12 4	8 3	2	1	
		18	11				
6	7	18 8	10 9	8 10	11	12	
		17	10				
6	18	16 17	9 16	15	14	13	
		16					
5	19	14 20	21	22	23	24	
		14					
5	30	13 29	28	27	26	25	
		13					
	31	32	33	34	35	36	

Subdivision of Section 4 ..... Pages 19-20  
 Subdivision of Section 8 ..... Pages 20-27  
 Subdivision of Section 9 ..... Pages 27-28  
 Subdivision of Section 17 ..... Pages 28-30  
 Subdivision of Section 19 ..... Pages 30-32  
 Subdivision of Section 30 ..... Pages 32-35  
 Metes-and Bounds ..... Pages 35-38

## T.2 S., R.19 W., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary, a portion of the subdivision lines, the subdivision of 4, 8, 9, and 17, and a metes-and-bounds survey through sections 4, 8, 9, and 17, partially surveyed Township 2 South, Range 19 West, Gila and Salt River Meridian, Arizona.

This survey was executed concurrently along with other surveys in Township 1 North, Township 2 North, and Township 1 South, Range 19 West, all of which are also included under Group No. 1201.

These surveys were requested by Ross C. Poppenberger, Colonel, Commanding, Department of the Army, in an interagency agreement for survey, dated April 04, 2020. The purpose is to identify the boundary of a portion of the lands currently managed by the Bureau of Land Management that have been proposed for withdrawal for the expansion of the existing Yuma Proving Ground facility. Hereinafter referred to as YPGE.

The history of surveys pertaining to this survey is as follows:

Ty White, U.S. Surveyor, surveyed the a portion of the south boundary, Township 2 South, Range 19 West, in 1940 (Book 4223). He and William E. Hiester, U.S. Cadastral Engineer, also surveyed the east and north boundaries of the same township, as well as portion of the subdivisional lines, in 1941 (Book 4279). Ty White returned and surveyed the remainder of the south boundary, the west boundary, and another portion of the subdivisional lines, Township 2 South, Range 19 West, in 1952 (Book 4398).

The Arizona State Highway Department, surveyed a portion of U.S. Route 95, in Townships 1 and 2 South, Range 19 West, from station 4129+99.60 to station 4460+00.00, in 1967. Monuments where established along the right-of-way and ties where made to corners of the PLSS. The record of survey is filed electronically on ADOT's website as Right Of Way Map No. D-14-T-338, and is associated with Project No. S-264-704.

Fred William O'Bannon, Arizona Registered Land Surveyor No. 2993, subdivided section 8, Township 2 South, Range 19 West. In the course of this unrecorded survey, O'Bannon monumented the center 1/4 corner, and the subdivisional corners which define the boundary of the aliquot lands described in U. S. Patent Nos. 1146299, 1146725, and 1207693.

James G. Spring, Arizona Registered Land Surveyor No. 22282, surveyed a portion of the KOFA Wildlife Refuge Boundary, on behalf of the U.S. Department of the Interior Fish and Wildlife Services, in Township 2 South, Range 19 West. Spring's plat of survey is recorded at the Yuma County Recorder's Office in Book of Surveys No. 2, pages 12 through 22. His Arizona Land Survey Corner Record Form is also recorded at the same location in Docket No. 1818, pages 407 through 452.

## T.2 S., R.19 W., Gila and Salt River Meridian, Arizona

## CHAINS

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated July 31, 2020, for Group Number 1201, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R10-2 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DL1884 AZYU CITY OF YUMA CORS ARP, AF9486 BLYT BLYTHE PGGGA STA CORS ARP, and DN7584 GMPK\_SCGN\_CS2000 CORS ARP.

The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of sections 25, 30, 31, and 36, on the W. bdy. of the Tp., is as follows:

Latitude: 33°13'06.915" N.                      Longitude: 114°16'07.614" W.

The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of sections 3, 4, 33, and 34, on the N. bdy. of the Tp. is as follows:

Latitude: 33°17'28.132" N.                      Longitude: 114°13'02.481" W.

The mean magnetic declination is 10 3/4° E.

---

**Dependent Resurvey of a Portion of the West Boundary  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona**

---

Restoring a portion of the survey  
executed by Ty White, in 1952

---

Beginning at the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T2S R20W R19W S25 S30 S36 S31 1952.

Add the marks 2020 to the brass cap. Set a steel fence post alongside, to the W.

**Dependent Resurvey of a Portion of the West Boundary  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 0°01' W., bet. secs. 25 and 30, along the W. bdy. of the Tp.</p> <p>Over rolling land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. 1/4 S25 S30 1952. A cairn shaped accessory mound-of-stone, 2 ft. base, 2 ft. high, alongside, to the W.</p> <p>Add the marks T2S R20W R19W 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0°01' W., beginning new measurement.</p>
19.99	<p>True point for the N 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., falls near the midpoint of a wash, 65 ft. wide, 6 ft. deep, drains S. 15° W. Point not monumented.</p> <p>From this point, the witness corner for the N 1/16 sec. cor. of secs. 25 and 30, bears S. 89°58' E., 1.20 chs. dist., hereinafter described.</p>
39.98	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with galvanized post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T2S R20W R19W S24 S19 S25 S30 1952. A cairn shaped accessory mound-of-stone, 3 ft. base, 3 1/2 ft. high, to the N.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post alongside, to the N.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>North, bet. secs. 19 and 24, along the W. bdy. of the Tp.</p> <p>Over mountainous land.</p>
39.99	<p>The 1/4 sec. cor. of sec. 19 and 24, on the W. bdy. of the Tp., monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/4 S24 S19 1952. An accessory mound-of-stone, 2 1/2 ft. base, 1 1/2 ft. high, to the W.</p> <p>Add the marks T2S R20W R19W 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>North, beginning new measurement.</p>
39.96	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. T2S R20W</p>

Dependent Resurvey of a Portion of the West Boundary  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>R19W S13 S18 S24 S19 1952. Fallen accessory mound-of-stone to the S.</p> <p>Add the marks 2020 to the brass cap. Incorporate the fallen accessory mound into a supporting mound-of-stone, 3 ft. base, to top. Set a steel fence post alongside, to the E.</p> <hr/> <p>North, bet. secs. 13 and 18, along the W. bdy. of the Tp.</p> <p>Over rolling land.</p>
40.07	<p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S13 S18 1952. An accessory mound-of-stone, 2 1/2 ft. base, 1 ft. high, alongside, to the W.</p> <p>Add the marks T2S R20W R19W 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p>
39.96	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T2S R20W R19W S12 S7 S13 S18 1952. An accessory mound-of-stone, 2 1/2 ft. base, 2 ft. high, to the W.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr/> <p>North, bet. secs. 7 and 12, along the W. bdy. of the Tp.</p> <p>Over mountainous land.</p>
40.03	<p>The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/4 S12 S7 1952. An accessory mound-of-stone, 2 ft. base, 1 ft. high, alongside, to the W.</p> <p>Add the marks T2S R20W R19W 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p>
40.03	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., falls in wash, 3 ft. wide, 3 ft. deep, drains N 50° E. Point not monumented.</p>

Dependent Resurvey of a Portion of the West Boundary  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.73	<p>The witness cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T2S R20W R19W WC S1 S6 S12 S7 1952. An accessory mound-of-stone, 3 ft. base, 1 ft. high, to the N.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post alongside, to the NE.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 6, along the W. bdy. of the Tp.</p> <p>Over mountainous land.</p>
39.32	<p>The 1/4 sec. cor. of sec. 1 and 6, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S1 S6 1952. An accessory mound-of-stone, 2 1/2 ft. base, 2 ft. high, to the W.</p> <p>Add the marks T2S R20W R19W 2020 to the brass cap. Set a steel fence post to the E.</p> <hr/> <p>North, beginning new measurement.</p>
28.95	<p>The closing cor. of secs. 1 and 6 only, on the W. bdy. of the Tp., at intersection with the S. bdy. of sec. 36, T. 1 S., R. 19 W. Monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above top of supporting mound-of-stone, 3 ft. base, 2 ft. high, with brass cap mkd. T1S R19W S36 S1 S6 R20W R19W T2S CC 1952.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post, alongside in the supporting mound.</p> <hr/> <p>N. 89°56' E., bet. secs. 1 and 36, along the W. bdy. of the Tp.</p> <p>Over mountainous land.</p>
3.73	<p>The cor. of T. 1 S., R. 20 W. only, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above top of supporting mound-of-stone, 3 ft. base, 3 ft. high, with brass cap mkd. T1S R20W S36 T2S S6 R19W 1941.</p> <p>Add the marks 2020 to the brass cap.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
11.07	<p>The closing cor. of secs. 6 and 31 only, on the N. bdy. of the Tp., at intersection with the E. bdy. of sec. 36, T. 1 S., R.20 W. Monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above top of supporting mound-of-stone, 4 ft.</p>

**Dependent Resurvey of a Portion of the West Boundary  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona**

CHAINS	<p>base, 3 ft. high, with brass cap mkd. T1S S36 R20W T1S R19W S31 S6 T2S 1941.</p> <p>Add the marks 2020 to the brass cap.</p> <p>Cor. located along a steep hill, sloped down to the S.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring a portion of the survey executed by William E. Hiester and Ty White, in 1941</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T2S R19W S9 S10 S16 S15 1941. An accessory mound-of-stone, 2 1/2 ft. base, 2 1/2 ft. high, alongside, to the W. A pair of steel fence posts, to the NE and S.</p> <p>Add the marks 2020 to the brass cap.</p> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land.</p>
40.01	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. ground, with brass cap mkd. 1/4 S9 S10 1941. An accessory mound-of-stone, 2 1/2 ft. base, 1 ft. high, alongside, to the W. A pair of steel fence posts, to the N. and S.</p> <p>Add the marks T2S R19W 2020 to the brass cap.</p> <hr/> <p>North, beginning new measurement.</p>
40.02	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T2S R19W S4 S3 S9 S10 1941. A pair of steel fence posts, to the N. and S.</p> <p>Add the marks 2020 to the brass cap.</p> <hr/> <p>N. 0°09' E., bet. secs. 3 and 4.</p> <p>Over nearly level land.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. 1/4 S4 S3 1941. A pair of steel fence posts to the S.</p> <p>Add the marks T2S R19W 2020 to the brass cap.</p> <hr/> <p>N. 0°06' E., beginning new measurement.</p>
40.11	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. T1S R19W S33 S34 S4 S3 T2S 1941. A pair of steel fence posts, with signs mkd. National Wilderness Area, to the E. and SE.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post to the W.</p> <hr/> <p style="text-align: center;">Restoring a portion of the survey executed by Ty White, in 1952</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T2S R19W S17 S16 S20 S21 1952. A cairn shaped accessory mound-of-stone, 2 1/2 ft. base, 2 1/2 ft. high, alongside, to the W. Small piles of stone to the N., SE, and SW.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over gently rolling land.</p>
16.46	<p>A rebar, 5/8 in. diam., firmly set, projecting 1 in. above ground, with aluminum cap, 3 1/4 ins. diam., mkd. U.S. Dept. of Interior Fish &amp; Wildlife Service KOFA K12 1992. A steel fence post, with sign mkd. National Wilderness Area Boundary, alongside, to the SE.</p> <p>From this point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, bears S. 89°07' W., 19.97 chs. dist., with aluminum cap, 3 1/4 ins. diam., mkd. U.S. Dept. of Interior Fish &amp; Wildlife Service KOFA K14 1992.</p>
40.01	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. 1/4 S17 S16 1952.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr/>
	<p>N. 0°03' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 8, 9, 16, and 17, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. T2S R19W S8 S9 S17 S16 1952. A steel fence post to the NE.</p> <p>Add the marks 2020 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 89°51' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/4 S9 S16 1952. Fallen accessory mound-of-stone alongside, to the N.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr/>
	<p>N. 89°52' W., beginning new measurement.</p>
39.95	<p>The cor. of secs. 8, 9, 16, and 17.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p>
19.95	<p>Trail road, 10 ft. wide, bears N. 30° E. and S. 30° W.</p>
20.005	<p>The S 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 25 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T 2 S R 19 W S 1/16 S 8   S 9  2021</p>
40.01	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, encircled in collar-of-stone, 2 1/2 ft. diam., with brass</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>cap mkd. 1/4 S8 S9 1952. An iron pipe, 1 1/4 ins. diam., projecting 8 ft. above ground, alongside, to the NE.</p> <p>Add the marks T2S R19W 2020 to the brass cap.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
25.81	<p>A concrete cylinder, 24 ins. long, 6 ins. diam., at the top, rough poured into metal bucket, 14 ins. diam., loose and disturbed above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT 19 . An angle iron also loose and disturbed, to the N.</p>
29.70	<p>Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.</p>
30.95	<p>Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W..</p>
39.75	<p>WP, on the YPGE bdy., identical with station 4273+05.31, of the westerly right-of-way, U.S. Route 95, bears N. 25°42' E. and N. 25°42' E., hereinafter described.</p>
40.00	<p>The cor. of secs. 4, 5, 8, and 9, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, among a scattered mound-of-stone, with brass cap mkd. T2S R19W S5 S4 S8 S9 1952.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post alongside, to the W.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°52' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p>
39.99	<p>The 1/4 sec. cor. of secs. 4 and 9, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd 1/4 S4 S9 1952. Remains of fallen accessory mound-of-stone to the N.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the N.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p>
33.12	<p>A concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. Arizona Highway Dept 19 . An angle iron to the N.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS									
35.00	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.								
35.60	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.								
39.84	<p>WP, at intersection with the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <table style="margin: auto;"> <tr> <td>T 2 S</td> <td>R 19 W</td> </tr> <tr> <td>S 4</td> <td>/</td> </tr> <tr> <td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td>S 9</td> <td>/ROW</td> </tr> </table> <p>2021</p> </div> <p>Set a steel fence post alongside, to the W.</p>	T 2 S	R 19 W	S 4	/	<hr style="width: 50%; margin: 0 auto;"/>		S 9	/ROW
T 2 S	R 19 W								
S 4	/								
<hr style="width: 50%; margin: 0 auto;"/>									
S 9	/ROW								
39.96	<p>The cor. of secs. 4, 5, 8, and 9.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°02' E., bet. secs. 4 and 5.</p> <p>Over gently rolling land.</p>								
40.01	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. 1/4 S5 S4 1952.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the N.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p>								
39.92	<p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T1S R19W S32 S33 S5 S4 T2S 1941. Accessory mound-of-stone, 2 1/2 ft. base, 1 1/2 ft. high, alongside, to the W.</p> <p>Add the marks 2020 to the brass cap. Incorporate the accessory mound into a supporting mound-of-stone, 3 ft. base, to top. Set a steel fence post alongside, to the W.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting, 15 ins. above ground, with brass cap mkd T2S R19W S30 S29 S31 S32 1941. An accessory mound-of-stone, 3 ft. base, 2 ft. high, alongside, to the W.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks 2020 to the brass cap. Incorporate the accessory mound into a supporting mound-of-stone, 3 ft. base, to top. Set a steel fence post alongside, to the E.</p> <p>N. 89°55' W., bet. secs. 30 and 31.</p>
36.35	Easterly edge of pavement, U.S Route 95, bears N. 20° E. and S. 20° W.
36.90	Westerly edge of pavement, U.S Route 95, bears N. 20° E. and S. 20° W.
39.99	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, among a scattered mound-of-stone, with brass cap mkd. 1/4 S30 S31 1952.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the E. Raise an accessory mound-of-stone, 3 ft. base, 1 ft. high, to the N., utilizing materials from the scattered mound.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
38.51	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
40.00	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting, 2 ins. above top of supporting mound-of-stone, 2 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd 1/4 S30 S29 1952.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the E of the supporting mound.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
38.60	Easterly edge of pavement, U.S. Route 95, bears N 30° E and S 30° W.
39.70	Westerly edge of pavement, U.S. Route 95, bears N 30° E and S 30° W.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>The cor. of secs. 19, 20, 29, and 30, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, 6 ins. below ground, with brass cap mkd. T2S R19W S19 S20 S30 S29 1952. Add the marks 2021 to the brass cap.</p> <p>From this corner, the 1/4 sec. cor. of secs. 20 and 29, bears N. 89°55' E., 39.92 chs. dist. Monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above top of supporting mound-of-stone, 3 1/2 ft. base, 2 1/2 ft. high, with brass cap mkd. 1/4 S20 S29 1952. Add the marks T2S R19W 2020 to the brass cap.</p> <hr/> <p>N. 89°53' W., bet. secs. 19 and 30.</p> <p>Over mountainous land.</p>
39.93	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above top of supporting mound-of-stone, 2 1/2 ft. base, 2 ft. high, with brass cap mkd. 1/4 S19 S30 1952.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the NW of the supporting mound.</p> <p>Cor. falls along a steep hill, sloped down to the NW.</p> <hr/> <p>S. 89°59' W., beginning new measurement.</p>
20.06	<p>Point for the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T 2 S R 19 W S 19 W 1/16 ——— S 30</p> <p style="text-align: center;">2021</p> <p>Set a steel fence post, alongside, to the N.</p>
38.50	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over mountainous land.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
39.97	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a galvanized steel post, 2 1/2 ins. diam. firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/4 S19 S20 1952. An accessory mound-of-stone, 2 1/2 ft. base, 2 ft. high, to the W.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, in the accessory mound.</p> <hr/> <p>N. 0°03' W., beginning new measurement.</p>
15.40	<p>Graded road, 14 ft. wide, bears S 85° E and N 85° W.</p>
20.00	<p>Point for the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T 2 S R 19 W N 1/16 S 19   S 20</p> <p style="text-align: center;">2020</p> <p>Set a steel fence post alongside, to the N.</p>
40.00	<p>The cor. of secs. 17, 18, 19, and 20, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T2S R19W S18 S17 S19 S20 1952. Fallen accessory mound-of-stone to the S. A steel fence post alongside, to the NW.</p> <p>Add the marks 2020 to the brass cap.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 89°50' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p>
19.97	<p>Point accepted for the E 1/16 sec. cor. of secs. 17 and 20, occupied with a rebar, 5/8 in. diam, firmly set, projecting 1 in. above ground, with aluminum cap, 3 1/4 ins. diam., mkd. U.S. Dept. of Interior Fish &amp; Wildlife Service KOFA 1992. This is accepted as the best available evidence of the cor. position. A steel fence post, with sign mkd. National Wilderness Area Boundary, alongside, to the E.</p>
39.96	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. 1/4 S17 S20 1952. Fallen accessory mound-of-stone alongside, to the N. A steel fence post to the NE.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>Add the marks T2S R19W 2020 to the brass cap.</p> <hr/> <p>S. 89°51' W., beginning new measurement.</p>
19.55	Easterly edge of pavement, U.S Route 95, bears N. 5° E. and S. 5° W.
20.10	Westerly edge of pavement, U.S Route 95, bears N. 5° E. and S. 5° W.
39.94	The cor. of secs. 17, 18, 19, and 20.
	<hr/> <p>N. 89°58' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
20.01	<p>Point for the E 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>T 2 S R 19 W</p> <p>S 18</p> <p>E 1/16 ———</p> <p>S 19</p> <p>2020</p> </div>
	<p>Set a steel fence post alongside, to the N.</p>
40.02	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/4 S18 S19 1952. An accessory mound-of-stone, 2 1/2 ft. base, 2 1/2 ft. high, alongside, to the N.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the S.</p> <hr/>
	<p>N. 89°59' W., beginning new measurement.</p>
38.34	The cor. of secs. 13, 18, 19, and 24.
	<hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p>
20.01	Point for the S 1/16 sec. cor. of secs. 17 and 18.



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T 2 S R 19 W S 1/16 S 18   S 17</p> <p style="text-align: center;">2021</p> <p>Set a steel fence post alongside, to the N.</p>
40.02	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. 1/4 S18 S17 1952. Fallen accessory mound-of-stone alongside, to the W.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p>
40.01	<p>The cor. of secs. 7, 8, 17, and 18, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T2S R19W S7 S8 S18 S17 1952. An accessory mound-of-stone, 2 1/2 ft. base, 1 ft. high, alongside, to the W.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post alongside, to the E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>S. 89°51' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land.</p>
19.95	<p>Point for the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T 2 S R 19 W S 8 E 1/16 ——— S 17</p> <p style="text-align: center;">2021</p> <p>Set a steel fence post alongside, to the W.</p>
29.93	<p>Point for the W-E 1/64 sec. cor. of secs. 8 and 17. Point not monumented.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
31.75	A concrete cylinder, 6 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap, 3 ins. diam., mkd. Arizona Highway Dept. STA. 4216+48.48 1967. An angle iron to the N.
33.65	Easterly edge of pavement, U.S Route 95, bears N. 25° E and S. 25° W.
34.25	Westerly edge of pavement, U.S Route 95, bears N. 25° E and S. 25° W.
38.48	WP, on the YPGE bdy., identical with station 4214+54.68, of the westerly right-of-way, U.S. Route 95, bears N. 25°41' E. and S. 25°42' W., hereinafter described.
39.90	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/4 S8 S17 1952. Fallen accessory mound-of-stone to the N.</p> <p>Add the marks T2S R19W 2020 to the brass cap. Set a steel fence post alongside, to the N.</p> <hr/> <p>S. 89°50' W., beginning new measurement.</p>
39.98	<p>The cor. of secs. 7, 8, 17, and 18.</p> <hr/> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
40.02	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, flush with the top of supporting mound-of-stone, 3 1/2 ft. base, 2 1/2 ft. high, with brass cap mkd. 1/4 S7 S8 1952.</p> <p>Add the marks T2S R19W 2020 to the brass cap.</p> <hr/> <p>N. 0°04' W., beginning new measurement.</p>
39.99	<p>The cor. of secs. 5, 6, 7, and 8, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T2S R19W S6 S5 S7 S8 1952. An accessory mound-of-stone, 2 1/2 ft. base, 1 ft. high, alongside, to the W.</p> <p>Add the marks 2020 to the brass cap. Set a steel fence post alongside, in the accessory mound.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S. 89°52' W., bet. secs. 5 and 8.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2. S, R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	Over gently rolling land.
39.93	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a galvanized steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, among a fallen mound-of-stone, with brass cap mkd. 1/4 S5 S8 1952. A wood post, 4 x 6 ins., projecting 5 ft. above ground, alongside, to the N.</p> <p>Add the marks T2S R19W 2020 to the brass cap.</p> <hr/> <p>S. 89°50' W., beginning new measurement.</p>
39.96	<p>The cor. of secs. 5, 6, 7, and 8.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 4, T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona</b></p> <hr/>
40.01	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°06' E., on the N. and S. center line of sec. 4.</p> <p>Over nearly level land.</p> <p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 2 S R 19 W C 1/4 S 4 2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside, to the N.</p>
73.05	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
74.30	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
80.03	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp, monumented with an iron post, 1 in. daim., firmly set, projecting, 11 ins. above ground, with brass cap mkd. 1/4 S33 S4 1941. An accessory mound-of-stone, 3 ft. base, 1 1/2 ft. high, to the N. A steel fence post, to the SE.</p>

Subdivision of Section 4,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks T1S R19W T2S 2020 to the brass cap.</p> <p>From this cor., the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., bears East, 40.02 chs. dist., hereinbefore described.</p> <p>From this same cor., the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears S. 89°59' W., 40.02 chs. dist., hereinbefore described.</p> <p>From this same cor., WP, identical to Station 4331+75.69, of the westerly right-of-way, U.S. Route 95, identical to the YPGE bdy. bears S. 89°59' W., 1.49 chs. dist. Monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4331+75.69 1967. An angle iron to the N.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89°52' W., on the E. and W. center line of sec. 4.</p>
40.03	The center 1/4 sec. cor. of sec. 4.
55.85	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
56.45	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
60.69	<p>WP, at intersection with the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 20 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;">WP T 2 S R 19 W S 4 C ——— C     / ROW</p> </div> <p style="text-align: center;">2021</p>
80.03	<p>Set a steel fence post alongside, to the W.</p> <p>The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;">Subdivision of Section 8, T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17.</p>

Subdivision of Section 8,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°04' W., on the N. and S. center line of sec. 8.  Over gently rolling land.
10.00	Point for the C-S-S 1/64 sec. cor. of sec. 8. Point not monumented.
20.005	Point for the C-S 1/16 sec. cor. of sec. 8.  Set a rebar, 24 ins. long, 5/8 ins. diam., 21 ins. in the ground, with brass cap, 2 ins. diam., mkd.
	T 2 S R 19 W C S 1/16   S 8 C 2021
	Set a steel fence post alongside, to the E.
25.01	Point for the C-S-N-S 1/256 sec. cor. of sec. 8. Point not monumented.
30.01	Point for the C-N-S 1/64 sec. cor. of sec. 8. Point not monumented.
40.01	The center 1/4 sec. cor. of sec. 33, monumented with a galvanized steel pipe, 1 in. diam., firmly set, projecting 5 ins. above ground, hollow and filled with concrete, with brass washer, 3/4 ins. diam., tacked atop, mkd. LS 2993.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 2 S R 19 W C 1/4 S 8 2020
	Deposit a magnet, in a white plastic case, and the recovered pipe, 22 ins. long, inside of the stainless steel post.  Set a steel fence post alongside, to the W.
80.02	The 1/4 sec. cor. of secs. 5 and 8. <hr/>
	From the 1/4 sec. cor. of secs. 8 and 9.  S. 89°51' W., on the E. and W. center line of sec. 8.

Subdivision of Section 8,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
12.45	A concrete monument, 6 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. Arizona Highway Dept STA. 4245+82.44 1967. An angle iron to the N.
14.35	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
14.95	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
19.18	WP on the YPGE bdy., identical with station 4243+88.63, of the westerly right-of-way, U.S. Route 95, bears N. 25°41' E. and S. 25°41' W., hereinafter described.
19.96	Point for the E 1/16 sec. cor. of sec. 8.  Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.  <div style="text-align: center;">           T 2 S R 19 W            E 1/16            C ——— C            S 8             2021         </div> Se a steel fence post alongside, to the W.
29.94	Point for the W-E 1/64 sec. cor. of sec. 8. Point not monumented.
39.92	The center 1/4 sec. cor. of sec. 8.
79.88	The 1/4 sec. cor. of secs. 7 and 8.  <hr/> From the E 1/16 sec. cor. of secs. 8 and 17.  N. 0°03' W., on the E 1/16 line of sec. 8.
10.005	Point for the C-S-SE 1/64 sec. cor. of sec. 8. Point not monumented.
15.005	Point for the C-N-S-SE 1/256 sec. cor. of sec. 8. Point not monumented.
20.005	Point for the SE 1/16 sec. cor. of sec. 8, at intersection with the S. 1/16 line of sec. 8.  Set a rebar, 24 ins. long, 5/8 ins. diam., 26 ins. in the ground, with brass cap, 2 ins. diam., mkd.

Subdivision of Section 8,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	T 2 S R 19 W SE 1/16 S 8  2021
28.35	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
29.60	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
30.01	Point for the C-N-SE 1/64 sec. cor. of sec. 8. Point not monumented.
40.01	The E 1/16 sec. cor. of sec. 8.
	<hr/>
	From the S 1/16 sec. cor. of secs. 8 and 9. S. 89°51' W., on the S 1/16 line of sec. 8.
19.96	The SE 1/16 sec. cor. of sec. 8.
24.00	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
24.60	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
24.95	Point for the C-E-W-SE 1/256 sec. cor. of sec. 8. Point not monumented.
29.94	Point for the C-W-SE 1/64 sec. cor. of sec. 8. Point not monumented.
34.92	Point for the C-W-W-SE 1/256 sec. cor. of sec. 8. Point not monumented.
39.92	The C-S 1/16 sec. cor. of sec. 8.
	<hr/>
	From the point for the C-W-SE 1/64 sec. cor. of sec. 8. N. 0°04' W., on the W-E 1/64 line of sec. 8.
5.00	The C-S-NW-SE 1/256 sec. cor. of sec. 8, monumented with a galvanized steel pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground, hollow and filled with concrete, with brass washer, 3/4 ins. diam., tacked atop, mkd. LS 2993.  A second galvanized steel pipe, 2 1/2 ins. diam., projecting 6 feet above ground, and a third galvanized steel pipe, 1 1/2 ins. diam., projecting 2 ft. above ground, with an elbow joint, both located alongside, to the W. of the corner monument.

Subdivision of Section 8,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Affix a brass washer mkd. BLM C-S-NW-SE S8 1/256 2021, to the hollow concrete filled pipe.
10.00	Point for the NW-SE 1/64 sec. cor. of sec. 8, at intersection with the N-S and W-E 1/64 lines of sec. 8. Point not monumented.
20.01	The point for the C-W-E 1/64 sec. cor. of sec. 8.
	-----
	From the point for the C-N-SE 1/64 sec. cor. of sec. 8.
	S. 89°51' W., on the N-S 1/64 line of sec. 8.
4.99	The C-E-NW-SE 1/256 sec. cor. of sec. 8, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground. A steel fence post alongside, to the N.
	Affix a brass washer mkd. BLM C-E-NW-SE S8 1/256 2021.
9.98	The point for the NW-SE 1/64 sec. cor. of sec. 8.
14.97	The C-W-NW-SE 1/256 sec. cor. of sec. 8, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground.
	Affix a brass washer mkd. BLM C-W-NW-SE S8 1/256 2021. Set a steel fence post alongside, to the W.
19.96	The point for the C-N-S 1/64 sec. cor. of sec. 8.
	-----
	From the point for the C-W-W-SE 1/256 sec. cor. of sec. 8.
	N. 0°03' W., on the W-W-E 1/256 line of sec. 8.
5.00	The SW-NW-SE 1/256 sec. cor. of sec. 8, monumented with an X mark, 5 x 5 ins., cut in rock outcrop, with traces of orange paint.
	At the corner point
	Drill hole and drive rebar, 24 ins. long, 5/8 in. diam., 6 ins. into rock outcrop, with brass cap, 2 ins. diam., mkd.
	T 2 S R 19 W S 8 SW-NW-SE 1/256  2021
	Raise supporting mound-of-stone, 2 1/2 ft. base, to top.
10.00	The C-W-NW-SE 1/256 sec. cor. of sec 8.
	-----



Subdivision of Section 8,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	From the C-S-NW-SE 1/256 sec. cor. of sec. 8.
	S. 89°51' W., on the S-N-S 1/256 line of sec. 8.
4.99	The SW-NW-SE 1/256 sec. cor. of sec. 8.
9.98	The point for the C-S-N-S 1/256 sec. cor. of sec 8.
<hr/>	
	From the point for the C-E-W-SE 1/256 sec. cor. of sec. 8.
	N. 0°03' W., on the E-W-E 1/256 line of sec. 8.
2.12	WP, at the intersection of the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95, monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground.
	Affix brass washer mkd. BLM WP E-W-E ROW S8 2021.
	Barbed wire fence bears northeasterly and southwesterly, substantially along the westerly right-of-way.
5.00	The SE-NW-SE 1/256 sec. cor. of sec. 8, monumented with a galvanized steel pipe, 2 ins. diam., firmly set, projecting 8 ins. above ground, hollow and filled with concrete, with brass washer, 3/4 in. diam., tacked atop, mkd. LS2993. A steel fence post alongside, to the N.
	Affix brass washer mkd. BLM SE-NW-SE S8 1/256 2021.
10.00	The C-E-NW-SE 1/256 sec. cor. of sec 8.
<hr/>	
	From the point for the W-E 1/64 sec. cor. of secs. 8 and 17.
	N. 0°04' W., on the W-E 1/64 line of sec. 8.
7.70	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
8.95	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
10.00	Point for the SW-SE 1/64 sec. cor. of sec. 8, at intersection with the W-E and S-S 1/64 lines of sec. 8. Point not monumented.
13.44	Intersect the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95.
15.00	The C-N-SW-SE 1/256 sec. cor. of sec. 8, monumented with a galvanized steel pipe, 2 ins. diam., firmly set, projecting 4 ins. above ground, hollow and filled with concrete, with brass washer, 3/4 in. diam., tacked atop, mkd. LS 2993. A steel fence post alongside, to the SW, with a PVC tube, 4 ft. long, 4 ins. diam.

Subdivision of Section 8,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Affix brass washer mkd. BLM C-N-SW-SE S8 1/256 2021. Set another steel fence post alongside, to the E.
20.01	The point for the C-W-SE 1/64 sec. cor. of sec 8.
	-----
	From the C-S-SE 1/64 sec. cor. of sec. 8.
	S. 89°51' W., on the S-S 1/64 line of sec. 8.
4.99	Point for the C-E-SW-SE 1/256 sec. cor. of sec. 8. Point not monumented.
8.85	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
9.45	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
9.98	The point for the SW-SE 1/64 sec. cor. of sec. 8.
13.70	Intersect the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95.
19.96	The point for the C-S-S 1/64 sec. cor. of sec 8.
	-----
	From the point for the C-E-SW-SE 1/256 sec. cor. of sec. 8.
	N. 0°03' W., on the E-W-E 1/256 line of sec. 8.
5.00	The NE-SW-SE 1/256 sec. cor. of sec. 8, monumented with a galvanized steel pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, hollow and filled with concrete, with brass washer, 3/4 in. diam., tacked atop, mkd. LS 2993.
	Affix brass washer mkd. BLM NE-SW-SE S8 1/256 2021. Set a steel fence post alongside, to the SE.
8.05	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
9.30	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
10.00	The point for the C-E-W-SE 1/256 sec. cor. of sec 8.
	-----
	From the C-N-S-SE 1/256 sec. cor. of sec. 8.
	S. 89°50' W., on the N-S-S 1/256 line of sec. 8.
4.99	The NE-SW-SE 1/256 sec. cor. of sec. 8.

Subdivision of Section 8,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
6.45	Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
7.05	Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.
8.43	<p>WP, at the intersection of the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95, monumented with a rebar, 1/2 in. diam., firmly set, projecting 1 in. above ground.</p> <p>Affix brass washer mkd. BLM WP N-S-S ROW S8 2021. Set a steel fence post alongside, to the E.</p> <p>Barbed wire fence bears northeasterly and southwesterly, substantially along the westerly right-of-way.</p>
9.98	The C-N-SW-SE 1/256 sec. cor. of sec 8.
<hr/> <p style="text-align: center;">Subdivision of Section 9, T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 9.</p> <p>Over nearly level land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 2 S R 19 W C 1/4 S 9</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside, to the N.</p>
80.01	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>N. 89°51' W., on the E. and W. center line of sec. 9.</p>
39.98	The center 1/4 sec. cor. of sec. 9.

Subdivision of Section 9,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS 79.93	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;">Subdivision of Section 17, T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N. 0°01' W., on the N. and S. center line of sec. 17.</p> <p>Over nearly level land.</p>
20.015	<p>Point for the S 1/16 sec. cor. of sec. 17. Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T 2 S R 19 W C S 1/16   S 17 C 2020</p> <p>Set a steel fence post alongside, to the N.</p>
40.03	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 2 S R 19 W C 1/4 S 17 2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside, to the N.</p>
67.05	<p>Easterly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.</p>
68.30	<p>Westerly edge of pavement, U.S Route 95, bears N. 25° E. and S. 25° W.</p>
77.09	<p>WP, at intersection with the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 17,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;"> <p>WP T 2 S R 19 W S 17 C / ROW C</p> <p>2021</p> </div> <p>Set a steel fence post alongside, to the W.</p>
80.04	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 16 and 17. S. 89°51' W., on the E. and W. center line of sec. 17.</p>
39.93	<p>The center 1/4 sec. cor. of sec. 17.</p>
52.40	<p>Easterly edge of pavement, U.S Route 95, bears northeasterly along a curve to the right and southwesterly along a curve to the left.</p>
53.00	<p>Westerly edge of pavement, U.S Route 95, bears northeasterly along a curve to the right and southwesterly along a curve to the left.</p>
57.80	<p>WP, at intersection with the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95.</p> <p>Set a rebar, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p>
	<div style="text-align: center;"> <p>WP T 2 S R 19 W S 17 C — C / ROW</p> <p>2021</p> </div> <p>Set a steel fence post alongside, to the W.</p>
79.89	<p>The 1/4 sec. cor. of secs. 17 and 18.</p> <hr/>
	<p>From the C-S 1/16 sec. cor. of sec. 17. S. 89°51' W., on the S 1/16 line of sec. 17.</p>
17.10	<p>Easterly edge of pavement, U.S Route 95, bears N. 20° E. and S. 20° W.</p>
17.60	<p>Westerly edge of pavement, U.S Route 95, bears N. 20° E. and S. 20° W.</p>

Subdivision of Section 17,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS 27.52	<p>WP, at intersection with the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T 2 S R 19 W</p> <p>S 17 /</p> <p>S ——— S</p> <p>      / ROW</p> </div> <p style="text-align: center;">2021</p> <p>Set a steel fence post alongside, to the N.</p>
39.95	<p>The S 1/16 sec. cor. of secs. 17 and 18.</p> <hr/> <p style="text-align: center;">Subdivision of Section 19, T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0°07' W., on the N. and S. center line of sec. 19.</p> <p>Over mountainous land.</p>
17.50	<p>Wash, 30 ft. wide, 5 ft. deep, drains East.</p>
39.94	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 2 S R 19 W</p> <p>C 1/4 S 19</p> </div> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post alongside, to the E. Raise a supporting mound-of-stone, 5 ft. base, to top of cap.</p>
59.93	<p>Point for the N 1/16 sec. cor. of sec. 19.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 22 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p>

Subdivision of Section 19,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	T 2 S R 19 W C N 1/16   S 19 C 2020
	Set a steel fence post alongside, to the E.
79.92	The 1/4 sec. cor. of secs. 18 and 19.
	<hr/> From the 1/4 sec. cor. of secs. 19 and 20. N. 89°56' W., on the E. and W. center line of sec. 19.
19.985	Point for the E 1/16 sec. cor. of sec. 19.
	Set a rebar, 24 ins. long, 5/8 ins. diam., in supporting mound-of-stone, 3 ft. base, 2 ft. high, with brass cap, 2 ins. diam., flush with the top and mkd.
	T 2 S R 19 W E 1/16 C ——— C S 19 2020
	Set a steel fence post alongside, to the NW, in the supporting mound.
26.40	Graded road, 14 ft. wide, bears N 50° E and S 50° W.
39.97	The center 1/4 sec. cor. of sec. 19.
59.99	Point for the W 1/16 sec. cor. of sec. 19.
	Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.
	T 2 S R 19 W W 1/16 C ——— C S 19 2020
	Set a steel fence post alongside, to the S.

Subdivision of Section 19,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
78.39	The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.
	From the C-E 1/16 sec. cor. of sec. 19.
	N. 0°05' W., on the E. 1/16 line of sec. 19.
5.65	Graded road, 14 ft. wide, bears N 50° E and S 50° W.
19.995	Point for the NE 1/16 sec. cor. of sec. 30, at intersection with the N. 1/16 line of sec. 19.
	Set a rebar, 24 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap, 2 ins. diam., mkd.
	T 2 S R 19 W NE 1/16 S 19
	2020
	Set a steel fence post alongside, to the S.
39.99	The E 1/16 sec. cor. of secs. 18 and 19.
	From the N 1/16 sec. cor. of secs. 19 and 20.
	N. 89°57' W., on the N 1/16 line of sec. 19.
20.00	The NE 1/16 sec. cor. of sec. 19.
40.00	The N 1/16 sec. cor. of sec. 19.
	From the W 1/16 sec. cor. of secs. 19 and 30.
	N. 0°04' W., on the W 1/16 line of sec. 19.
39.96	The C-W 1/16 sec. cor. of sec. 19.
	Subdivision of Section 30, T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0°01' W., on the N. and S. center line of sec. 30.
	Over rolling land.
32.60	Wash, 40 ft. wide, 3 ft. deep, drains S. 35° W.



Subdivision of Section 30,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
39.99	<p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 2 S R 19 W C 1/4 S 30</p> <p style="text-align: center;">2020</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Encircle cap in collar-of-stone, 3 ft. diam. Set a steel fence post alongside collar, to the N.</p>
60.01	<p>Point for the N 1/16 sec. cor. of sec. 30.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T 2 S R 19 W C N 1/16   S 30 C</p> <p style="text-align: center;">2021</p> <p>Set a steel fence post alongside, to the E.</p>
80.03	<p>The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 89°55' W., on the E. and W. center line of sec. 30.</p>
19.75	Easterly edge of pavement, U.S Route 95, bears N. 20° E. and S. 20° W.
20.50	Westerly edge of pavement, U.S Route 95, bears N. 20° E. and S. 20° W.
32.10	Wash, 40 ft. wide, 3 ft. deep, drains S. 50° W.
39.96	The center 1/4 sec. cor. of sec. 30.
59.99	<p>Point for the W 1/16 sec. cor. of sec. 30.</p> <p>Set a rebar, 24 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap, 2 ins. diam., mkd.</p>

Subdivision of Section 30,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	T 2 S R 19 W W 1/16 C ——— C S 30  2021 Set a steel fence post alongside, to the N.
78.46	The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.  <hr/> From the C-W 1/16 sec. cor. of sec. 30.  N. 0°03' W., on the W. 1/16 line of sec. 30.
20.005	Point for the NW 1/16 sec. cor. of sec. 30, at intersection with the N. 1/16 line of sec. 30.  Set a rebar, 24 ins. long, 5/8 ins. diam., 12 ins. in the ground, with brass cap, 2 ins. diam., mkd.
	T 2 S R 19 W NW 1/16 S 30  2021 Raise supporting mound-of-stone, 2 ft. base, to top. Set rebar electrical post, 1/4 ins. diam., alongside, to the N.
40.01	The W 1/16 sec. cor. of secs. 19 and 30.  <hr/> From the C-N 1/16 sec. cor. of sec. 30.  N. 89°58' W., on the N 1/16 line of sec. 30.
20.04	The NW 1/16 sec. cor. of sec. 30.
37.30	Point for the witness corner of the N 1/16 sec. cor. of secs. 25 and 30.  Set a rebar, 24 ins. long, 5/8 ins. diam., 22 ins. in the ground, with brass cap, 2 ins. diam., mkd.
	WC T 2 S R 20 W R 19 W ← N 1/16 S 25   S 30  2021

Subdivision of Section 30,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel fence post alongside, to the E.
38.00	Left bank of wash, 65 ft. wide, 6 feet deep, drains S 15° E.
38.50	True point for the N 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., falls in the wash.
<hr/> <b>Metes-and Bounds Survey through Sections 4, 8, 9, and 17, T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona</b> <hr/>	
<p>Note: The following is the metes-and-bounds survey of YPGE bdy., coincident with the westerly right-of-way, U.S. Route 95, through sections 4, 8, 9, and 17. The retracement data is based upon Arizona State Highway Department, Right Of Way Map, No. D-14-T-338, approved December 02, 1967. Station numbering on said map is referenced to the survey center line.</p> <hr/>	
<p>From WP, on the N. bdy. of the Tp., at intersection of the YPGE bdy., hereinbefore described, located S. 89°59' W., 1.49 chs. dist., from the 1/4 sec. cor. of secs. 4 and 33, also hereinbefore described.</p>	
<p>S. 25°42' W., on the YPGE bdy., through sec. 4.</p>	
17.81	AP1, sec. 4, identical with station 4320+00.00, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4320+00 1967. An angle iron to the N.
<hr/>	
<p>Thence, S. 25°42' W., on the YPGE bdy., through sec. 4.</p>	
21.22	AP2, sec. 4, identical with station 4306+00.00, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4306+00 1967. An angle iron to the N.
<hr/>	
<p>Thence, S. 25°42' W., on the YPGE bdy., through sec. 4.</p>	
5.33	WP, on the E. and W. center line of sec. 4, hereinbefore described.
<p>From this point, the 1/4 sec. cor. of secs. 4 and 5, bears N. 89°52' W., 19.33 chs. dist. hereinbefore described.</p> <hr/>	
<p>Thence, S. 25°42' W., on the YPGE bdy., through sec. 4.</p>	
44.36	WP, on the line bet. secs. 4 and 9, hereinbefore described.

Metes-and Bounds Survey through Sections 4, 8, 9, and 17,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point, the cor. of secs. 4, 5, 8, and 8, bears N. 89°53' W., 12 lks. dist., hereinbefore described.</p> <hr/>
	<p>S. 25°42' W., on the YPGE bdy., through sec. 9.</p>
0.27	<p>WP, identical with station 4273+05.31, on the line bet. secs. 8 and 9, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4273+05.31 1967. An angle iron to the N.</p>
	<p>From this point, the cor. of secs. 4, 5, 8, and 8, bears N. 0°03' W., 25 lks. dist., hereinbefore described.</p> <hr/>
	<p>S. 25°42' W., on the YPGE bdy., through sec. 8.</p>
44.17	<p>WP, identical with station 4243+88.63, on the E. and W. center line of sec. 8, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4243+88.63 1967. An angle iron to the N.</p>
	<p>From this point, the 1/4 sec. cor. of secs. 8 and 9, bears N. 89°51' E., 19.18 chs. dist., hereinbefore described.</p> <hr/>
	<p>S. 25°41' W., on the YPGE bdy., through sec. 8.</p>
1.80	<p>Intersect the E 1/16 line of sec. 8. From this point, the E 1/16 sec. cor. of sec. 8, bears N. 0°03' W., 1.62 chs. dist., hereinbefore described.</p>
8.92	<p>AP1, sec. 8. identical with station 4238+00.00, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4238+00 1967. An angle iron to the N.</p>
	<p>Right-of-way width decreases from 200 ft. to 30 ft. from the survey centerline.</p> <hr/>
	<p>S. 64°19' E., on the YPGE bdy., through sec. 8.</p>
2.57	<p>AP2, sec. 8, identical with station 4238+00.00, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4238+00 1967. An angle iron to the N.</p> <hr/>
	<p>S. 25°41' W., on the YPGE bdy., through sec. 8.</p>
0.95	<p>Intersect the N-S 1/64 line of sec. 8.</p>

Metes-and Bounds Survey through Sections 4, 8, 9, and 17,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
9.13	Beginning of barbed wire fence, which runs substantially along the westerly right-of-way, U.S. Route 95.
9.71	<p>WP, at the intersection of the E-W-E 1/256 line of sec. 8, monument hereinbefore described.</p> <p>Barbed wire fence continues southwesterly, substantially along the right-of-way.</p> <p>From this point, the SE-NW-SE 1/256 sec. cor. of sec. 8, bears N. 0°04' W., 2.89 chs. dist., hereinbefore described.</p> <hr/>
	<p>From WP, at the intersection of the YPGE bdy., identical with the westerly right-of-way, U.S. Route 95 with the N-S-S 1/256 line of sec. 8, hereinbefore described.</p> <p>From this point, the C-N-SW-SE 1/256 sec. cor. of sec. 8, bears S. 89°50' W., 1.55 chs. dist., hereinbefore described.</p> <p>S. 25°43' W., on the YPGE bdy., through sec. 8.</p>
2.08	<p>AP3, sec. 8, identical with station 4225+00.00, monumented with a concrete cylinder, 5 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4225+00 1967. An angle iron to the N.</p> <p>Right-of-way width increases from 30 ft. to 200 ft. from the survey centerline.</p> <hr/>
	<p>N. 64°19' W., on the YPGE bdy., through sec. 8.</p>
0.72	Intersect the W-E 1/64 line of sec. 8. From this point, the C-N-SW-SE 1/256 sec. cor. of sec. 8, bears N. 0°01' W., 1.56 chs. dist., hereinbefore described.
2.58	<p>AP4, sec. 8, identical with station 4225+00.00, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4225+00 1967. An angle iron to the N.</p> <hr/>
	<p>S. 25°41' W., on the YPGE bdy., through sec. 8.</p>
4.72	Intersect the S-S 1/64 line of sec. 8, bears N. 89°51' E. and S. 89°51' W.
15.84	<p>WP, identical with station 4214+54.68, on the line bet. secs. 8 and 17, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4214+54.68 1967. An angle iron to the N.</p>

Metes-and Bounds Survey through Sections 4, 8, 9, and 17,  
T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point, the 1/4 sec. cor. of secs. 8 and 17, bears S. 89°51' W., 1.42 chs. dist., hereinbefore described.</p> <hr/>
	<p>S. 25°42' W., on the YPGE bdy., through sec. 17.</p>
3.28	<p>WP, on the N. and S. center line of sec. 17, hereinbefore described.</p>
	<p>From this point, the 1/4 sec. cor. of secs. 8 and 17, bears N. 0°01' W., 2.95 chs. dist., hereinbefore described.</p> <hr/>
	<p>S. 25°42' W., on the YPGE bdy., through sec. 17.</p>
14.22	<p>AP1, sec. 17, identical with station 4203+00.00, monumented with a concrete cylinder, 6 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 ins. diam., mkd. ARIZONA HIGHWAY DEPT. STA. 4203+00 1967. An angle iron to the N.</p> <hr/>
	<p>S. 25°42' W., on the YPGE bdy., through sec. 17.</p>
26.96	<p>WP, on the E. and W. center line of sec. 17, hereinbefore described.</p>
	<p>From this point, the 1/4 sec. cor. of secs. 17 and 18, bears S. 89°51' W., 22.09 chs. dist. hereinbefore described.</p> <hr/>
	<p>S. 25°42' W., on the YPGE bdy., through sec. 17.</p>
22.24	<p>WP, on the S. 1/16 line of sec. 17, hereinbefore described.</p>
	<p>From this point, the S 1/16 sec. cor. of sec. 17 and 18, bears S. 89°51' W., 12.43 chs. dist., hereinbefore described.</p>
	<p>From this same point, an angle iron, 4 x 4 ins., firmly set, projecting 3 ft. above ground, bears S. 25°42' W., 4.14 chs. dist., mkd. HWY. R. OF W. P.T. 4167+80 3, with white paint.</p> <hr/>

## GENERAL DESCRIPTION

## CHAINS

The land encompassed in this survey is located in Yuma County, along U.S. Route 95, approximately 26 miles south of the town of Quartzsite, Arizona, and immediately east of the Yuma Proving Ground. Elevations range from about 1,300 ft. to 1,900 ft. above sea level.

Access is provided via U.S. Route 95 as well as unmarked secondary trail roads.

The terrain is gently rolling for the most part and broken in places by narrow but distinct washes. The landscape is considerably more rugged along portions of the west boundary of the township. Timber is scarce and limited to an occasional Palo Verde or Ironwood tree. Some Saguaro and Cholla cacti are present. Undergrowth is plentiful consisting mostly of Creosote.

The mean magnetic declination of  $10 \frac{3}{4}^{\circ}$  E. was derived from the National Oceanic and Atmospheric Administration computer program GEOMAG, utilizing the World Magnetic Model 2020 for the dates of survey.

---





CERTIFICATE OF SURVEY

I, Marshall Steele Wixom, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 31st day of July, 2020. I have dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines, the subdivision of 4, 8, 9, and 17, and surveyed a metes-and-bounds survey through sections 4, 8, 9, and 17, partially surveyed Township 2 South, Range 19 West, of the Gila and Salt River Meridian, in the State of Arizona. Which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

4/12/2022  
(Date)

Marshall S. Wixom  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, the subdivision of 4, 8, 9, and 17, and a metes-and-bounds survey through sections 4, 8, 9, and 17, partially surveyed Township 2 South, Range 19 West, Gila and Salt River Meridian, in the State of Arizona, executed by Marshall Steele Wixom, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

4/12/2022  
(Date)

[Signature]  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in partially surveyed T. 2 S., R. 19 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor of Arizona)~~