

ORIGINAL

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
SURVEY OF A PORTION OF THE SOUTH BOUNDARY OF
TOWNSHIP 40 NORTH, RANGE 26 EAST,
THE SURVEY OF THE SIXTH GUIDE MERIDIAN EAST, (WEST BOUNDARY),
THE EAST BOUNDARY AND
THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 39 NORTH, RANGE 25 EAST,
OF THE GILA AND SALT RIVER MERIDIAN,
IN THE STATE OF ARIZONA.

EXECUTED BY

Blas J. Urena, Cadastral Surveyor

Under Special Instructions dated April 5, 2021, approved April 5, 2021, which provided for the surveys included under Group No. 1213, and assignment instructions dated April 5, 2021.

Survey commenced April 12, 2021

Survey completed May 26, 2021

INDEX DIAGRAM

TOWNSHIP 39 NORTH RANGE 25 EAST GILA & SALT RIVER MERIDIAN, ARIZONA

79	78	63	49	37	5
11 6 77	5 61	4 48	3 36	2 26	1 17
76	75	60	48	35	25
10 7 75	8 59	9 47	10 34	11 24	12 16
74	73	58	46	34	24
9 18 72	17 58	16 45	15 33	14 22	13 16
71	70	57	43	32	22
8 19 69	20 55	21 42	22 31	23 21	24 15
68	68	54	42	30	20
7 30 66	29 52	28 40	27 29	26 20	25 14
65	64	51	39	29	19
7 31 63	32 50	33 38	34 27	35 18	36 13

A Portion of the S. Bdy. of T. 40 N., R. 26 E Pages 4- 7
 Subdivision of Section 4 Pages 79-80
 Subdivision of Section 9 Pages 80-82
 Subdivision of Section 16 Pages 82-84
 Subdivision of Section 20 Pages 84-85
 Subdivision of Section 21 Pages 85-86
 Subdivision of Section 28 Pages 86-88
 Subdivision of Section 33 Pages 89-91
 Subdivision of Section 34 Pages 91-93

T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of a portion of the south boundary of Township 40 North, Range 26 East, the survey of the sixth guide meridian east, (west boundary), the east boundary and the subdivisional lines, and the subdivision of certain sections, Township 39 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Leonard R. Sandoval, Cadastral Surveyor, surveyed the north boundary of Township 38 North, Range 25 East, in 2000 (Book 5647).

Leonard R. Sandoval, Cadastral Surveyor, surveyed the south boundary of Township 40 North, Range 27 East, in 2000 (Book 5642).

Rosendo Ramos Serrano, Cadastral Surveyor, surveyed the south boundary of Township 40 North, Range 25 East, in 2017 (Book 6093).

The plan for Township 39 North, Range 25 East, to close on a portion of the South Boundaries of Townships 40 North, Ranges 25 and 26 East, is found in the Bureau of Land Management, Arizona Protraction Diagram No. 37, signed February 11, 1960.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated April 5, 2021, for Group Number 1213, Arizona.

The true meridian direction and length of all lines were determined by static or real time kinematic Global Navigation Satellite System observations using Trimble Navigation R10-2 model receivers.

This survey was executed at the request of Lena M. Yazzie, Realty Specialist, Cadastral Survey Coordinator, Navajo Region, Bureau of Indian Affairs.

The steel "T" posts referred to in these notes are 60 inches long.

Geodetic control was derived from Global Navigation Satellite System (GNSS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DI2245 P011 SPIDERROCKAZ2005 CORS ARP, DI3419 P012 MONTICELLOUT2006 CORS ARP, DH6916 MC04 MESA CNTY 04 COOP CORS ARP.

The NAD 83 (2011) (EPOCH: 2010.0000), geographic position of the corner of Townships 38 and 39 North, Ranges 25 and 26 East, is as follows:

Latitude: 36°44'15.190" N.

Longitude: 109°35'19.898" W.

T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

The NAD 83 (2011) (EPOCH: 2010.0000), geographic position of the closing corner of Townships 39 North, Ranges 24 and 25 East, on the South Boundary of Section 32, Township 40 North, Range 25 East, is as follows:

Latitude: 36°49'26.914" N. Longitude: 109°41'48.116" W.

The mean magnetic declination is 9 3/4° E.

**Survey of a Portion of the South Boundary,
T. 40 N., R. 26 E., Gila and Salt River Meridian, Arizona**

Beginning at the point for the 1/4 sec. cor. of sec. 32 only, T. 40 N., R. 26 E., determined West, 360.00 chs. dist., from the cor. of Tps. 40 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. "T40N R26E R27E S36 S31 2017 2011 2000". Add the marks 2021 to the brass cap.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 40 N R 26 E
1/4 S 32

2021

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel "T" post alongside and N. of cor.

West, on the S. bdy. of sec. 32.

Over rolling terrain.

- 1.47 Barbed wire fence, 5 strand, bears S. 38° E. and N. 38° W.
- 37.86 Point for the closing cor. of Tps. 39 N., Rs. 25 and 26 E.

Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.

Survey of a portion of the South Boundary,
T. 40 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 40 N R 26 E S 32 <hr style="width: 50px; margin: 0 auto;"/> S 1 S 6 R 25 E R 26 E T 39 N CC 2021
	Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.
	Set a steel "T" post in a drill hole, alongside and S. of cor.
40.00	Point for the cor. of secs. 31 and 32 only. Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.
	T 40 N R 26 E S 31 S 32 <hr style="width: 50px; margin: 0 auto;"/> 2021
	Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.
	Set a steel "T" post in a drill hole, alongside and N. of cor.
	<hr style="width: 80%; margin: 0 auto;"/> West, on the S. bdy. of sec. 31. Over rolling terrain.
37.86	Point for the 1/4 sec. cor. of sec. 1 only, T. 39 N., R. 25 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 40 N R 26 E <hr style="width: 50px; margin: 0 auto;"/> 1/4 S 1 T 39 N R 25 E 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and S. of cor.

Survey of a portion of the South Boundary,
T. 40 N., R. 26 E., Gila and Salt River Meridian, Arizona

CHAINS 40.00	<p>Point for the 1/4 sec. cor. of sec. 31 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 26 E 1/4 S 31</p> <hr style="width: 10%; margin: auto;"/> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>		
77.86	<p>Point for the closing cor. of secs. 1 and 2, T. 39 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 26 E S 31</p> <hr style="width: 10%; margin: auto;"/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> </table> <p>T 39 N R 25 E CC</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and S. of cor.</p>	S 2	S 1
S 2	S 1		
79.85	<p>The cor. of Tps. 40 N., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. "T40N R25E R26E S36 S31 2017". Add the marks 2021 to the brass cap.</p> <p>Found the steel "T" post laying loose W. and alongside the cor., reset it alongside and N. of cor.</p> <p>From this cor., an iron pipe, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, mkd. on the S. face, "T40N R25E R26E 36 31 1 6 T39N", with a brass cap, approximately 3 ins. diam., cemented on top and mkd. "T40N S36 S31 R25E R26E S1 S6 T39N G.& S.R.M. 1961 F.S.O.S.", bears S. 51°03' E., 1.344 chs. dist. This iron pipe is typical as the monuments set by Ernest V. Echohawk, Arizona R.L.S. No. 2311, in 1958, in or near T. 40 N., R. 27 E., found by Leonard R. Sandoval, Cadastral Surveyor, while originally surveying T. 40 N., R. 27 E., in 2000, according to Book 5642.</p> <hr style="width: 80%; margin-left: 0;"/>		

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of Tps. 38 and 39 N., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. "T39N R24E R25E S36 S31 S1 S6 T38N 2000". Add the marks 2021 to the brass cap.</p>
	<p>North, bet. secs. 31 and 36, on the W. bdy. of the Tp.</p>
	<p>Over gently rolling terrain.</p>
18.02	<p>Navajo Route 8014, a graded road, 24 ft. wide, bears S. 85° E. and N. 85° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 36.</p>
	<p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p>
	<p style="text-align: center;"> T 39 N R 24 E R 25 E 1/4 S 36 S 31 2021 </p>
	<p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p>
	<p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p>
78.10	<p>Trail road, bears S. 40° E. and N. 40° W.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T 39 N R 24 E R 25 E S 25 S 30 ----- S 36 S 31 2021 </p>
	<p>Deposit a magnet, in a white plastic case, and an empty white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel "T" post alongside and W. of cor.</p>
	<hr/> <p>North, bet. secs. 25 and 30.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Over rolling terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N</p> <p>R 24 E R 25 E</p> <p>1/4</p> <p>S 25 S 30</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, an empty white plastic case, and a bundle of white flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>
80.00	<p>Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N</p> <p>R 24 E R 25 E</p> <p>S 24 S 19</p> <p>S 25 S 30</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, and an empty white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 39 N R 24 E R 25 E 1/4 S 24 S 19 2021</p> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 24 E R 25 E S 13 S 18 S 24 S 19 2021</p> <p>Deposit a magnet, in a white plastic case, and 2 empty white plastic cases, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling, broken, and gently rolling terrain.</p>
5.20	<p>Top of descent, slopes northerly.</p>
37.08	<p>Bottom of descent, approximately 320 vertical ft.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 24 E R 25 E 1/4 S 13 S 18 2021</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.								
	Set a steel "T" post alongside and W. of cor.								
70.90	Trail road, bears S. 55° E. and N. 55° W.								
75.95	Wash, approximately 50 ft. wide, approximately 3 ft. deep, drains S. 85° W.								
80.00	Point for the cor. of secs. 7, 12, 13, and 18.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.								
	<table border="0" style="margin: auto;"> <tr> <td colspan="2" style="text-align: center;">T 39 N</td> </tr> <tr> <td style="text-align: center;">R 24 E</td> <td style="text-align: center;">R 25 E</td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td style="text-align: center;">S 13</td> <td style="text-align: center;">S 18</td> </tr> </table>	T 39 N		R 24 E	R 25 E	S 12	S 7	S 13	S 18
T 39 N									
R 24 E	R 25 E								
S 12	S 7								
S 13	S 18								
	2021								
	Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.								
	Set a steel "T" post alongside and W. of cor.								

	North, bet. secs. 7 and 12.								
	Over gently rolling, broken, and rolling terrain.								
15.25	Left bank of the Chinle Wash, approximately 20 ft. high, bears N. 75° E. and N. 85° W.								
25.40	Main channel of the Chinle Wash, approximately 20 ft. wide, approximately 5 ft. deep, drains N. 75° W.								
37.75	Right bank of the Chinle Wash, approximately 25 ft. high, bears East. and S. 85° W.								
40.00	Point for the 1/4 sec. cor. of secs. 7 and 12.								
	Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 13 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.								

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 39 N R 24 E R 25 E 1/4 S 12 S 7 2021</p> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 33 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 24 E R 25 E S 1 S 6 S 12 S 7 2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling, broken, and gently rolling terrain.</p>
36.85	<p>Dirt road, 10 ft. wide, bears N. 52° E. and S. 52° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 24 E R 25 E 1/4 S 1 S 6 2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>

Survey of the Sixth Guide Meridian East, (West Boundary),
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel "T" post alongside and W. of cor.
40.70	Trail road, bears N. 40° E. and S. 40° W.
43.85	Enter inhabited area.
46.20	A fence enclosing a cultivated field, woven wire, approximately 6 ft. high, bears East and West.
47.67	The same fence enclosing the cultivated field, woven wire, approximately 6 ft. high, bears East and West.
50.65	Trail road, bears N. 80° E. and S. 80° W.
64.90	Trail road, bears S. 55° E. and N. 55° W.
67.35	Trail road, bears S. 85° E. and N. 85° W.
70.30	Leave inhabited area.
74.55	Dirt road, 10 ft. wide, bears S. 80° E. and N. 75° W.
77.80	Point for the closing cor. of Tps. 39 N., Rs. 24 and 25 E., at intersection with the S. bdy. of sec. 32, T. 40 N., R. 25 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a supported mound of stone, 4 ft. base, to top, with brass cap mkd.
	<pre> T 40 N R 25 E S 32 ----- S 1 S 6 R 24 E R 25 E T 39 N CC 2021 </pre>
	Deposit a magnet, in a white plastic case, and a bundle of pink and white flagging, at the base of the stainless steel post.
	From this closing cor., the 1/4 sec. cor. of sec. 32 only, T. 40 N., R. 25 E., bears East, 36.49 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. "T40N R25E 1/4 S32 2017", witnessed by a steel "T" post, N. of cor. Add the marks 2021 to the brass cap.

**Survey of the Sixth Guide Meridian East, (West Boundary),
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same closing cor., the cor. of secs. 31 and 32 only, T. 40 N., R. 25., bears West, 3.49 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. "T40N R25E S31 S32 2017". Add the marks 2021 to the brass cap. There is not remaining evidence of the 2017 steel "T" post that was set nearby the cor.</p> <hr/> <p align="center">Survey of the East Boundary, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of Tps. 38 and 39 N., Rs. 25 and 26 E., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, cemented in sandstone bedrock, in a scattered collar of stone, with top mkd. "T39N R25E R26E S36 S31 S1 S6 T38N 2000". Add the marks 2021 to the brass tablet. Rebuilt the collar of stone over the top of tablet to protect the cement. The cor. is located on the SE slope, near the top of a sandstone butte.</p> <p>North, bet. secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>Over rugged, broken, and rolling terrain.</p>
40.00	The true point for the 1/4 sec. cor. of secs. 31 and 36, falls in an area surround by sheer walls, where it is impracticable to establish a permanent monument. Not monumented.
49.48	<p>The point selected for the witness cor. to the 1/4 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <div style="text-align: center;"> <p>WC T 39 N R 25 E R 26 E 1/4 ↓ S 36 S 31 ↓ 2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p> <p>The witness cor. is located on top edge of a ridge, approximately 80 ft. high, extending N. 25° E. and N. 40° W.</p>
80.00	Point for the cor. of secs. 25, 30, 31, and 36.

**Survey of the East Boundary,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 39 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr style="border-top: 1px solid black;"><td>S 36</td><td>S 31</td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>North, bet. secs. 25 and 30.</p> <p>Over gently rolling terrain.</p>	T 39 N		R 25 E	R 26 E	S 25	S 30	S 36	S 31
T 39 N									
R 25 E	R 26 E								
S 25	S 30								
S 36	S 31								
17.35	Apache County Road C485, a graded road, 24 ft. wide, bears S. 50° E. and N. 50° W.								
22.05	Trail road, bears N. 85° E. and S. 85° W.								
22.75	Power line, 2 strand, bears S. 45° E. and N. 45° W.								
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 39 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>	T 39 N		R 25 E	R 26 E	1/4		S 25	S 30
T 39 N									
R 25 E	R 26 E								
1/4									
S 25	S 30								
52.50	From this point, a steel water tank, approximately 24 ft. diam., enclosed in by a fence, bears West, 8.28 chs. dist.								
68.45	Apache County Road C484, a graded road, 24 ft. wide, bears S. 55° E. and N. 55° W.								
80.00	Point for the cor. of secs. 19, 24, 25, and 30.								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>								

Survey of the East Boundary,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<table style="margin: auto;"> <tr><td colspan="2">T 39 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table>	T 39 N		R 25 E	R 26 E	S 24	S 19	S 25	S 30
T 39 N									
R 25 E	R 26 E								
S 24	S 19								
S 25	S 30								
	2021								
	Deposit a magnet, in a white plastic case, and 4 empty white plastic cases, at the base of the stainless steel post.								
	North, bet. secs. 19 and 24.								
	Over gently rolling terrain.								
9.65	Apache County Road C484, a graded road, 24 ft. wide, bears N. 20° E. and S. 20° W.								
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.								
	Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 39 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 39 N		R 25 E	R 26 E	1/4		S 24	S 19
T 39 N									
R 25 E	R 26 E								
1/4									
S 24	S 19								
	2021								
	Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.								
	Set a steel "T" post in a drill hole, alongside and W. of cor.								
53.60	Trail road, bears S. 70° E. and N. 70° W.								
80.00	Point for the cor. of secs. 13, 18, 19, and 24.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T 39 N</td></tr> <tr><td>R 25 E</td><td>R 26 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table>	T 39 N		R 25 E	R 26 E	S 13	S 18	S 24	S 19
T 39 N									
R 25 E	R 26 E								
S 13	S 18								
S 24	S 19								
	2021								
	Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.								

Survey of the East Boundary,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E R 26 E 1/4 S 13 S 18</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Set a steel "T" post alongside and W. of cor.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E R 26 E S 12 S 7 S 13 S 18</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over gently rolling terrain.</p>
39.30	<p>Upgraded portion of Apache County Rd. C484, 8 ft. wide, bears N. 88° E. and S. 88° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Survey of the East Boundary,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E R 26 E 1/4 S 12 S 7 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.
55.75	Trail road, bears N. 70° E. and S. 70° W.
80.00	Point for the cor. of secs. 1, 6, 7, and 12.
	Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole in sandstone bedrock, with top mkd.
	T 39 N R 25 E R 26 E S 1 S 6 S 12 S 7 2021
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.
	Set a steel "T" post in a drill hole, alongside and W. of cor.
	<hr/> North, bet. secs. 1 and 6.
	Over rolling terrain.
21.47	Barbed wire fence, 5 strand, bears N. 85° E. and S. 85° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.
	T 39 N R 25 E R 26 E 1/4 S 1 S 6 2021

**Survey of the East Boundary,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p>
77.79	<p>The closing cor. of Tps. 39 N., Rs. 25 and 26 E., at intersection with the S. bdy. of sec. 32, T. 40 N., R. 26 E., hereinbefore described.</p> <p>From this closing cor., the 1/4 sec. cor. of sec. 32 only, T. 40 N., R. 26 E., bears East, 37.86 chs. dist., hereinbefore described.</p> <p>From this same closing cor., the cor. of secs. 31 and 32 only, T. 40 N., R. 26., bears West, 2.14 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Survey of the Subdivisional Lines, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 16 ins. below blow sand, with brass cap mkd. "T39N R25E S35 S36 S2 S1 T38N 2000". Remove surrounding sand, the stainless steel post is projecting 3 ins. above ground. Add the marks 2021 to the brass cap.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Over rugged, broken, and rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <p style="text-align: center;">T 39 N R 25 E 1/4 S 35 S 36</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and N. of cor.</p> <p>The cor. is located at the toe of slope, approximately 15 ft. above canyon floor, of easterly canyon wall, approximately 80 ft. high, bears N. 30° W. and S. 30° W.</p>

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS 80.00	<p>The true point for the cor. of secs. 25, 26, 35, and 36, falls on a steep ESE facing slope, where it is impracticable to establish a permanent monument. Not monumented.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 25, 26, 35, and 36, bears N. 2°56' W., 44 lks. dist.</p> <p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <div style="text-align: center;"> <p>WC</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="border-left: 1px solid black; padding: 0 10px;"></td> <td style="padding: 0 10px;">R 25 E</td> </tr> <tr> <td style="padding: 0 10px;">S 26</td> <td style="border-left: 1px solid black; padding: 0 10px;"></td> <td style="padding: 0 10px;">S 25</td> </tr> <tr> <td style="padding: 0 10px;">S 35</td> <td style="border-left: 1px solid black; padding: 0 10px;"></td> <td style="padding: 0 10px;">S 36</td> </tr> </table> <p style="margin-top: 10px;">↓</p> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p> <p>The cor. is located on an ESE facing sandstone slope, bears N. 30° E. and S. 30° W.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling, rugged, and broken terrain.</p>	T 39 N		R 25 E	S 26		S 25	S 35		S 36			
T 39 N		R 25 E											
S 26		S 25											
S 35		S 36											
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">R 25 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 25</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">—</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 36</td> </tr> </table> <p style="margin-top: 10px;">2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>	T 39 N		R 25 E			S 25		1/4	—			S 36
T 39 N		R 25 E											
		S 25											
	1/4	—											
		S 36											

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <hr/> <p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rugged, broken, and rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 13 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E 1/4 S 26 S 25</p> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E S 23 S 24 S 26 S 25</p> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p> <p>The cor. is located on a NW facing sandstone slope, approximately 50 ft. high, bears N. 40° E. and S. 40° W.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling and broken terrain.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
5.20	Apache County Road C484, a graded road, 24 ft. wide, bears N. 30° E. and S. 30° W.
16.67	Power line, 2 strand, bears S. 30° E. and N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 39 N R 25 E S 24 1/4 ——— S 25</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>
80.00	The cor. of secs. 23, 24, 25, and 26. <hr/> N. 0°01' W., bet. secs. 23 and 24. Over rugged, broken, and rolling terrain.
40.00	The true point for the 1/4 sec. cor. of secs. 23 and 24, falls at the bottom of a canyon with sheer vertical cliffs, where it is impracticable to establish a permanent monument. Not monumented.
47.55	The point selected for the witness cor. to the 1/4 sec. cor. of secs. 23 and 24. Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd. <div style="text-align: center;"> <p>WC T 39 N R 25 E 1/4 ↓ S 23 S 24 ↓ 2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and N. of cor.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 13 and 24.</p> <p>Over rolling terrain.</p>	T 39 N	R 25 E	S 14	S 13	S 23	S 24		
T 39 N	R 25 E								
S 14	S 13								
S 23	S 24								
33.68	<p>Approximate location of underground water line, extending N. 7° E. and S. 7° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supported mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 13</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 24</td> <td></td> </tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, and an empty white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>	T 39 N	R 25 E	S 13		1/4	—	S 24	
T 39 N	R 25 E								
S 13									
1/4	—								
S 24									
60.88	<p>Power line, 2 strand, bears S. 30° E. and N. 30° W.</p>								
80.00	<p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling, broken, and gently rolling terrain.</p>								

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
34.40	Power line, 2 strand, bears S. 35° E. and N. 35° W.
38.77	Trail road, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 25 E 1/4 S 14 S 13 2021 </div>
	Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor.
55.68	Trail road, bears N. 30° E. and S. 30° W.
61.33	The same trail road, bears S. 35° E. and N. 35° W.
63.65	Approximate location of underground water line, extending N. 88° E. and S. 88° W.
66.18	Trail road, bears S. 75° E. and N. 85° W.
74.88	Trail road, bears N. 65° E. and S. 65° W.
80.00	Point for the cor. of secs. 11, 12, 13, and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 25 E S 11 S 12 S 14 S 13 2021 </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor. From this cor. point, the SE corner of a fence, bears N. 64° W., 5.45 chs. dist., woven wire, 6 ft. high, enclosing an open pit septic tank, and extending N. 45° E. and N. 45° W.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this same cor. point, the NE corner of the same fence, bears N. 39° W., 5.09 chs. dist., woven wire, 6 ft. high, extending S. 45° W. and N. 45° W.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 25 E</p> <p>S 12</p> <p>1/4 ———</p> <p>S 13</p> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p> <p>Set a steel "T" post in a drill hole, alongside and N. of cor.</p>
69.67	<p>Trail road, bears N. 30° E. and S. 30° W.</p>
70.35	<p>Trail road, bears N. 50° E. and S. 50° W.</p>
80.00	<p>The cor. of secs. 11, 12, 13, and 14.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling terrain.</p>
20.75	<p>Upgraded portion of Apache County Rd. C484, bears N. 75° E. and S. 75° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 25 E</p> <p>1/4</p> <p>S 11 S 12</p> <p>2021</p> </div>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>								
68.35	Barbed wire fence, 5 strand, bears N. 65° E. and S. 65° W.								
80.00	Point for the cor. of secs. 1, 2, 11, and 12.								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 39 N</td><td>R 25 E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>S 11</td><td>S 12</td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling terrain.</p>	T 39 N	R 25 E	S 2	S 1	S 11	S 12		
T 39 N	R 25 E								
S 2	S 1								
S 11	S 12								
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.								
	<p>Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 39 N</td><td>R 25 E</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td>S 12</td><td></td></tr> </table> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p> <p>Set a steel "T" post in a drill hole, alongside and N. of cor.</p>	T 39 N	R 25 E	S 1		1/4	_____	S 12	
T 39 N	R 25 E								
S 1									
1/4	_____								
S 12									
58.94	Barbed wire fence, 5 strand, bears N. 60° E. and S. 60° W.								
80.00	The cor. of secs. 1, 2, 11, and 12.								

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 25 E 1/4 S 2 S 1 2021</p> <p>Deposit a magnet, in a white plastic case, and a bundle of pink and white flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>
77.79	<p>The closing cor. of secs. 1 and 2, T. 39 N., R. 25 E., at intersection with the S. bdy. of sec. 31, T. 40 N., R. 26 E., hereinbefore described.</p> <p>From this closing cor., the 1/4 sec. cor. of sec. 31 only, T. 40 N., R. 26 E., bears East, 37.86 chs. dist., hereinbefore described.</p> <p>From this same closing cor., the cor. of Tps. 40 N., Rs. 25 and 26 E., bears West, 1.99 chs. dist., hereinbefore described.</p> <hr/> <p>The 1/4 sec. cor. of sec. 1 only, T. 39 N., R. 25 E., at midpoint on the N. bdy. of sec. 1, on the S. bdy. of sec. 31, T. 40 N., R. 26 E., hereinbefore described.</p> <p>From this cor. point, the cor. of secs. 31 and 32 only, T. 40 N., R. 26 E., bears East, 37.86 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 31 only, T. 40 N., R. 26 E., bears West, 2.14 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins., firmly set, 6 ins. below the surface of the ground, with brass cap mkd. "T39N R25E S34 S35 S3 S2 T38N 2000". Add the marks 2021 to the brass cap.</p> <p>The cor. is located on an abandoned cultivated field.</p> <p>from which the remains of the original reference monuments</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A magnet, in a white plastic case, 26 ins. below the surface of the ground, bears S. 45°02' E., 330.2 ft. dist. (Record: S. 45°00' E., 330.0 ft.), from which both reference offset nails in their original 2 ft. offset distances: one nail set 2 ft. to the North and the other nail set 2 ft. to the West. There is no remaining evidence of the original stainless steel post or the steel fence post that was set nearby.</p> <p>Reset the RM utilizing the 2 found original offset nails, set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 32 ins. in the ground for a reference monument, bears S. 45°02' E., 330.2 ft. dist. with brass cap mkd. "RM T38N R25E 330.2 FT. TO COR S2 2021" and an arrow pointing to the cor. Bury the magnet, in the white plastic case, at the base of the stainless steel post. The RM is located in a dirt road, 8 ft. wide, bears N. 31° E. and S. 31° W., and West, 26 lks. dist., from a dirt irrigation canal, 4 ft. wide, 2 ft. deep, parallels the dirt road.</p> <p>A stainless steel post, 2 1/2 ins. diam., firmly set, 22 ins. below the surface of an agricultural dirt berm, bears S. 44°58' W., 296.9 ft. dist. (Record: S. 45°00' W., 297.0 ft.), with brass cap mkd. "RM T38N R25E S3 297.0 FT. TO COR. 2000" and an arrow pointing to the cor. Add the marks 2021 to the brass cap. The RM is located in an agricultural dirt berm, 15 ft. wide, 2 ft. high, bears S. 10° E. and N. 10° W., and East, 1.4 lks. dist., from a woven wire fence, parallels the berm.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over nearly level terrain, within abandoned cultivated fields, and within the Chinle Valley.</p>
29.40	Power line, 2 strand, bears S. 30° E. and N. 30° W.
30.25	Leave abandoned cultivated fields, bears S. 10° E. and N. 10° W.
34.50	Navajo Route 353, 24 ft. wide, bears S. 10° E. and N. 10° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 39 N R 25 E</p> <p>1/4</p> <p>S 34 S 35</p> <p>2021</p> </div>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
	Deposit a magnet, in a white plastic case, an empty white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.						
	Set a steel "T" post alongside and W. of cor.						
43.70	Trail road, bears N. 25° E. and S. 25° W.						
44.25	Enter inhabited area.						
46.05	Trail road, bears S. 80° E. and N. 80° W.						
60.95	Power line, 2 strand, bears N. 70° E. and S. 70° W.						
64.70	Power line, 2 strand, bears S. 13° E. and N. 13° W.						
69.62	Woven wire fence, approximately 6 ft. high, bears S. 85° E. and N. 85° W.						
71.90	Southerly edge of a hogan, bears East and West.						
72.14	Northerly edge of the same hogan, bears East and West.						
73.10	Southerly edge of a house, irregular shape, short side bears S. 80° E. and N. 80° W., long side bears N. 10° E. and S. 10° W.						
74.20	Northeasterly edge of the same house, bears S. 50° E. and N. 50° W.						
75.21	Woven wire fence, approximately 6 ft. high, bears S. 85° E. and N. 85° W.						
80.00	Point for the cor. of secs. 26, 27, 34, and 35.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table>	T 39 N	R 25 E	S 27	S 26	S 34	S 35
T 39 N	R 25 E						
S 27	S 26						
S 34	S 35						
	2021						
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.						
	Set a steel "T" post alongside and W. of cor.						
	From this cor. point, the NW corner of a fence, bears N. 70° E., 1.67 chs. dist., woven wire, 6 ft. high, enclosing an open pit septic tank, and extending S. 75° E. and S. 15° W.						

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, the SW corner of the same fence, bears S. 54° E., 1.41 chs. dist., woven wire, 6 ft. high, extending N. 15° E. and S. 75° E.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over rugged, broken, rolling, and gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 13 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E</p> <p>S 26</p> <p>1/4 ———</p> <p>S 35</p> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and N. of cor.</p>
59.75	<p>Descend into the Chinle Valley.</p>
68.20	<p>Trail road, bears N. 60° E. and S. 40° W.</p>
75.00	<p>Enter inhabited area.</p>
77.06	<p>The easterly fence that enclose an open pit septic tank, woven wire, 6 ft. high, extending N. 15° E. and S. 15° W.</p>
78.59	<p>The westerly fence of the same open pit septic tank, woven wire, 6 ft. high, extending N. 15° E. and S. 15° W.</p>
80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over nearly level, rolling, rugged, and broken terrain, within the Chinle Valley.</p>
26.00	<p>Leave inhabited area.</p>
39.00	<p>Leave the Chinle Valley.</p>

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**


CHAINS

40.00

The true point for the 1/4 sec. cor. of secs. 26 and 27, falls on the south face of a cliff, approximately 80 ft. high, bears N. 55° E. and N. 65° W., where it is impracticable to establish a permanent monument. Not monumented.

From this true point, the point selected for a witness cor. to the 1/4 cor. of secs. 26 and 27, bears S. 17°53' W., 1.70 chs. dist.

Set a brass tablet, 3 1/2 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.



2021


Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.

Set a steel "T" post in a drill hole, alongside and S. 20° W. of cor.

80.00

Point for the cor. of secs. 22, 23, 26, and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.



2021

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel "T" post alongside and W. of cor.

The cor. is located West, 42 lks. dist., from the base of the canyon wall, approximately 75 ft. high, bears S. 30° E. and N. 30° W.

From the cor. of secs. 23, 24, 25, and 26.

West, bet. secs. 23 and 26.

Over rugged, broken, and rolling terrain.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/4 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E</p> <p>S 23</p> <p>1/4 ———</p> <p>S 26</p> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p> <p>Set a steel "T" post in a drill hole, alongside and N. of cor.</p>
80.00	<p>The cor. of secs. 22, 23, 26, and 27.</p> <hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over rugged, broken, rolling, and gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E</p> <p>1/4</p> <p>S 22 S 23</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <p>The cor. is located East, 88 lks., from the base of a sandstone cliff, approximately 60 ft. high, bears N. 40° E. and S. 10° E.</p>
73.20	<p>Apache County Road C484, a graded road, 24 ft. wide, bears N. 40° E. and S. 40° W.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 25 E</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 15</td> <td style="padding: 0 10px;">S 14</td> </tr> <tr> <td style="padding: 0 10px; border-right: 1px solid black;">S 22</td> <td style="padding: 0 10px;">S 23</td> </tr> </table>	T 39 N	R 25 E	S 15	S 14	S 22	S 23				
T 39 N	R 25 E										
S 15	S 14										
S 22	S 23										
	2021										
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <p>From this cor. point, a fence corner, bears S. 85° E., 4.64 chs. dist., barbed wire, extending N. 30° E. and N. 60° W.</p> <p>From this same cor. point, a fence corner on the same fence, bears N. 45° W., 4.92 chs. dist., extending N. 30° E. and S. 60° E.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling, rugged, broken, and gently rolling terrain.</p>										
40.00	<p>The true point for the 1/4 sec. cor. of secs. 14 and 23, falls on a sheer vertical south face of a sandstone cliff, approximately 100 ft. high, bears S. 65° E. and N. 80° W., where it is impracticable to establish a permanent monument. Not monumented.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 14 and 23, bears N. 54°59' E., 50 lks. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 2 1/4 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p>										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">WC</td> </tr> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 25 E</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">S 14</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px; border-top: 1px solid black;">S 23</td> </tr> <tr> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">↙</td> </tr> </table>	WC		T 39 N	R 25 E		S 14	1/4	S 23		↙
WC											
T 39 N	R 25 E										
	S 14										
1/4	S 23										
	↙										
	2021										
	<p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p> <p>Set a steel "T" post in a drill hole, alongside and N. 55° E. of cor.</p>										
74.57	<p>Apache County Road C484, a graded road, 24 ft. wide, bears N. 34° E. and S. 34° W.</p>										

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
75.10	Barbed wire fence, bears N. 30° E. and S. 30° W., enter inhabited area.
76.25	The same barbed wire fence, bears S. 60° E. and N. 60° W.
80.00	The cor. of secs. 14, 15, 22, and 23.
	N. 0°01' W., bet. secs. 14 and 15.
	Over gently rolling terrain.
1.83	Barbed wire fence, bears S. 60° E. and N. 60° W.
3.53	Approximate location of underground water line, extending S. 85° E. and N. 85° W.
4.27	Power line, 2 strand, bears East and west.
9.50	Barbed wire fence, bears N. 30° E. and S. 30° W.
13.10	Trail road, bears N. 50° E. and S. 50° W., leave inhabited area.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E 1/4 S 15 S 14
	2021
	Deposit a magnet, in a white plastic case, and an empty white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.
51.20	Approximate location of underground water line, extending N. 85° E. and S. 85° W.
61.32	Power line, 2 strand, bears East and west.
62.15	Apache County Road C484, a graded road, 24 ft. wide, along a curve to the right, bears southeasterly and northwesterly.
80.00	Point for the cor. of secs. 10, 11, 14, and 15.
	Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E S 10 S 11 S 15 S 14 2021
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet. Set a steel "T" post in a drill hole, alongside and W. of cor. The cor. is located on the southerly edge of a sandstone drainage, 5 ft. wide, 1 ft. deep, drains S. 45° W.
	<hr/> From the cor. of secs. 11, 12, 13, and 14. West, bet. secs. 11 and 14. Over gently rolling, rugged, and rolling terrain.
3.29	Enter inhabited area.
16.56	Leave inhabited area.
24.85	Upgraded portion of Apache County Rd. C484, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.
	T 39 N R 25 E S 11 1/4 ——— S 14 2021
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet. Set a steel "T" post in a drill hole, alongside and N. of cor.
80.00	The cor. of secs. 10, 11, 14, and 15. <hr/> N. 0°01' W., bet. secs. 10 and 11. Over rolling terrain.
27.95	Barbed wire fence, 5 strand, bears N. 65° E. and S. 65° W.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 25 E 1/4 S 10 S 11</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 25 E S 3 S 2 S 10 S 11</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>West, bet. secs. 2 and 11.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 25 E S 2 1/4 ——— S 11</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, and a bundle of pink and white flagging, at the base of the stainless steel post.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>Set a steel "T" post alongside and N. of cor.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p> <hr/> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over gently rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 25 E 1/4 S 3 S 2</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>
49.20	<p>Trail road, bears N. 70° E. and S. 25° W.</p>
77.79	<p>Point for the closing cor. of secs. 2 and 3, T. 39 N., R. 25 E., at intersection with the S. bdy. of sec. 36, T. 40 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 36 ----- S 3 S 2 T 39 N R 25 E CC</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, and 3 empty white plastic cases, and a bundle of pink and white flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and S. of cor.</p> <p>From this closing cor., the 1/4 sec. cor. of sec. 36 only, T. 40 N., R. 25 E., bears East, 38.03 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins above ground, with brass cap mkd. "T40N R25E 1/4 S36 2017", witnessed by a steel "T" post, N. of cor. Add the marks 2021 to the brass cap.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

From this same closing cor., the cor. of secs. 35 and 36 only, T. 40 N., R. 25., bears West, 1.96 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins above ground, with brass cap mkd. "T40N R25E S35 S36 2017". Add the marks 2021 to the brass cap. Found the steel "T" post laying loose approximately 18 lks. West of cor. Reset the steel "T" post alongside and N. of cor.

From this cor. of secs. 35 and 36 only, T. 40 N., R. 25., an iron pipe, 2 1/2 ins. diam., filled with concrete, firmly set, projecting 14 ins. above ground, mkd. on the S. face, "T40N R25E R26E 35 36 2 1 T39N", witnessed by a scattered mound of stone, 2 ft. base, 1/2 ft. high, W. of cor., bears S. 50°30' E., 1.335 chs. dist. This iron pipe is typical as the monuments set by Ernest V. Echhawk, Arizona R.L.S. No. 2311, in 1958, in or near T. 40 N., R. 27 E., found by Leonard R. Sandoval, Cadastral Surveyor, while originally surveying T. 40 N., R. 27 E., in 2000, according to Book 5642.

Point for the 1/4 sec. cor. of sec. 2 only, T. 39 N., R. 25 E., at midpoint on the N. bdy. of sec. 2, on the S. bdy. of sec. 36, T. 40 N., R. 25 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 40 N R 25 E

—————
1/4 S 2
T 39 N R 25 E

2021

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel "T" post alongside and S. of cor.

From this cor. point, the cor. of Tps. 40 N., Rs. 25 and 26 E., bears East, 38.01 chs. dist., hereinbefore described.

From this same cor. point, the 1/4 sec. cor. of sec. 36 only, T. 40 N., R. 25 E., bears West, 1.98 chs. dist.

From this same cor. point, a wing mill/water well, bears approximately S. 55° E., 20.05 chs. dist.

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. "T39N R25E S33 S34 S4 S3 T38N 2000". Add the marks 2021 to the brass cap.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over gently rolling and broken terrain, within the Chinle Valley.</p>
8.20	Left bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 55° E. and N. 55° W.
20.80	Left bank of the Chinle Wash, approximately 10 ft. high, bears S. 65° E. and N. 55° W.
22.25	Main channel of the Chinle Wash, approximately 30 ft. wide, approximately 5 ft. deep, drains N. 40° W.
23.05	Right bank of the Chinle Wash, approximately 10 ft. high, bears S. 50° E. and N. 55° W.
28.65	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 55° E. and N. 55° W.
36.58	Trail road, bears N. 65° E. and S. 65° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E</p> <p>1/4</p> <p>S 33 S 34</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>
42.15	Enter inhabited area.
45.30	Southerly fence of a corral, barbed wire, bears N. 80° E. and S. 80° W.
46.10	Northerly fence of the same corral, barbed wire, bears S. 10° E. and N. 10° W.
46.48	Power line, 2 strand, bears S. 35° E. and N. 35° W.
47.00	Power line, 2 strand, bears S. 35° E. and N. 35° W.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
48.40	Approximate location of underground water line, extending N. 60° E. and S. 60° W.						
50.15	Leave inhabited area.						
51.95	Graded road, 24 ft. wide, bears N. 35° E. and S. 35° W., approximate location of underground water line, extending S. 30° E. and N. 30° W.						
57.45	Graded road, 24 ft. wide, bears N. 85° E. and S. 85° W.						
65.01	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.						
68.26	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears S. 28° E. and N. 28° W.						
71.52	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.						
80.00	Point for the cor. of secs. 27, 28, 33, and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> <p>2021</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor. <hr style="width: 50%; margin-left: 0;"/> From the cor. of secs. 26, 27, 34, and 35. West, bet. secs. 27 and 34. Over gently rolling, broken, and rolling terrain, within the Chinle Valley.	T 39 N	R 25 E	S 28	S 27	S 33	S 34
T 39 N	R 25 E						
S 28	S 27						
S 33	S 34						
3.60	Power line, 2 strand, bears S. 13° E. and N. 13° W.						
19.65	Dirt road, 20 ft. wide, bears N. 30° E. and S. 50° W.						
30.83	Barbed wire fence, bears S. 25° E. and N. 25° W.						
35.68	Trail road, bears S. 50° E. and N. 50° W.						
36.65	Power line, 2 strand, bears S. 48° E. and N. 48° W.						

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 32 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E</p> <p>S 27</p> <p>1/4 ———</p> <p>S 34</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>
48.55	Irrigation canal, approximately 6 ft. wide, approximately 4 ft. deep, bears S. 45° E. and N. 45° W.
62.90	Enter inhabited area.
67.50	Power line, 2 strand, bears North and S. 45° E.
71.00	Leave inhabited area.
72.15	Dirt road, 20 ft. wide, bears S. 10° E. and N. 10° W.
80.00	The cor. of secs. 27, 28, 33, and 34.
	<hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over gently rolling, rugged, broken and rolling terrain, within the Chinle Valley.</p>
4.80	Graded road, 24 ft. wide, bears S. 10° E. and N. 10° W.
5.50	Graded road, 24 ft. wide, bears S. 5° E. and N. 5° W.
15.15	Graded road, 24 ft. wide, bears N. 45° E. and S. 45° W.
29.05	Barbed wire fence, bears N. 85° E. and S. 85° W.
30.00	Enter abandoned cultivated fields.
37.15	Barbed wire fence, bears N. 85° E. and S. 85° W.
39.27	Power line, 2 strand, bears S. 45° E. and N. 45° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E 1/4 S 28 S 27 2021
	Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.
	From this cor. point, a fence corner, bears S. 60° E., 4.63 chs. dist., barbed wire, extending North and East.
	From this same cor. point, another fence corner, bears S. 42° W., 4.94 chs. dist., extending N. 85° E., S. 85° W. and N. 10° W.
	The cor. is located in an abandoned cultivated field.
47.38	Barbed wire fence, bears N. 85° E. and S. 85° W., leave abandoned cultivated fields.
47.67	Graded road, 24 ft. wide, bears N. 85° E. and S. 85° W.
48.02	Barbed wire fence, bears N. 85° E. and S. 85° W., enter abandoned cultivated fields.
55.95	Leave abandoned cultivated fields.
58.30	Leave the Chinle Valley.
80.00	The true point for the cor. of secs. 21, 22, 27, and 28, falls on a steep 50° westerly facing sandstone slope, where it is impracticable to establish a permanent monument. Not monumented.
	From this true point, the point selected for a witness cor. to the cor. of secs. 21, 22, 27, and 28, bears N. 22°01' E., 1.40 chs. dist.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/4 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.
	WC T 39 N R 25 E S 21 S 22 S 28 S 27 ↓ 2021
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a steel "T" post in a drill hole, alongside and NNE of cor.</p> <p>The witness cor. is located on top of a sandstone finger ridge, approximately 20 ft. wide, 40 ft. high, bears North and S. 30° E.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over gently rolling, rugged, broken and rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/4 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 39 N R 25 E S 22 1/4 ——— S 27</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p> <p>Set a steel "T" post in a drill hole, alongside and N. of cor.</p> <p>The cor. is located approximately N. 45° E., 98 lks. dist., from the top edge of an amphitheater shape sandstone cove, 25 ft. deep, extending N. 50° E. and S. 15° W.</p>
80.00	<p>The cor. of secs. 21, 22, 27, and 28.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling, rugged, and broken terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <p style="text-align: center;">T 39 N R 25 E 1/4 S 21 S 22</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
	Set a steel "T" post in a drill hole, alongside and W. of cor.						
80.00	Point for the cor. of secs. 15, 16, 21, and 22.						
	Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table>	T 39 N	R 25 E	S 16	S 15	S 21	S 22
T 39 N	R 25 E						
S 16	S 15						
S 21	S 22						
	2021						
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.						
	Set a steel "T" post in a drill hole, alongside and W. of cor.						
	The cor. is located on a gentle south facing sandstone slope, bears N. 60° E. and N. 80° W.						
	<hr/>						
	From the cor. of secs. 14, 15, 22, and 23.						
	West, bet. secs. 15 and 22.						
	Over gently rolling, broken, and rolling terrain.						
18.00	Enter inhabited area.						
19.79	Barbed wire fence, bears N. 25° E. and S. 25° W.						
20.30	The easterly edge of a house, 32 x 24 ft., bears N. 25° E., 2 ft. to the NE cor., and S. 25° W., 30 ft. to the SE cor.						
20.68	The westerly edge of the same house, bears N. 25° E., 11 ft. to the NW cor., and S. 25° W., 21 ft. to the SW cor.						
23.23	Trail road, bears S. 20° E. and N. 20° W.						
26.14	Trail road, bears N. 65° E. and S. 65° W.						
30.08	The easterly fence that enclose an open pit septic tank, woven wire, 6 ft. high, extending S. 10° E. and N. 10° W.						
32.45	The westerly fence of the same open pit septic tank, woven wire, 6 ft. high, extending S. 10° E. and N. 10° W.						
32.85	Leave inhabited area.						
38.48	Enter inhabited area.						

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
38.88	The easterly fence that enclose an open pit septic tank, woven wire, 6 ft. high, extending S. 5° E. and N. 5° W.
40.00	<p>The true point for the 1/4 sec. cor. of secs. 15 and 22, falls in an open pit septic tank, where it is impracticable to establish a permanent monument. Not monumented.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 15 and 22, bears N. 55°00' W., 1.80 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 39 N R 25 E</p> <p>S 15</p> <p>1/4 ———</p> <p>S 22 ↘</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and NW of cor.</p> <p>From this witness cor., the NE corner of a fence, bears N. 84°11' E., 2.493 chs. dist., woven wire, 6 ft. high, enclosing an open pit septic tank, and extending S. 5° E. and S. 83° W.</p> <p>From this same witness cor., the SE corner of the same fence, bears S. 53°02' E., 3.350 chs. dist., woven wire, 6 ft. high, enclosing the open pit septic tank, and extending S. 87° W. and N. 5° W.</p> <p>From this same witness cor., the SW corner of the same fence, bears S. 17°52' E., 2.222 chs. dist., woven wire, 6 ft. high, enclosing the open pit septic tank, and extending N. 87° E. and N. 9° W.</p> <p>From this same witness cor., the NW corner of the same fence, bears S. 88°45' E., 34.2 lks. dist., woven wire, 6 ft. high, enclosing the open pit septic tank, and extending N. 83° E. and S. 9° E.</p>
40.97	The westerly fence that enclose the open pit septic tank, woven wire, 6 ft. high, extending S. 9° E. and N. 9° W., with a sign stamped "CAUTION WARNING CONTAMATED WATER".
41.40	From this point, a sewer clean out, set in concrete, bears South, 5.1 lks. dist.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
42.62	From this point, another sewer clean out, set in concrete, bears South, 11.5 lks. dist.
46.05	Leave inhabited area.
48.97	Power line, 2 strand, bears North and South.
49.62	Approximate location of underground water line, extending North and South.
54.50	Trail road, bears S. 42° E. and N. 42° W.
59.38	Apache County Road C484, a graded road, 24 ft. wide, bears S. 11° E. and N. 11° W.
63.23	Trail road, bears N. 15° E. and S. 15° W.
80.00	The cor. of secs. 15, 16, 21, and 22.

	N. 0°02' W., bet. secs. 15 and 16.
	Over rolling and gently rolling terrain.
5.85	Trail road, bears N. 35° E. and S. 35° W.
6.21	Trail road, bears N. 60° E. and S. 75° W.
16.62	Trail road, bears S. 25° E. and N. 25° W.
32.58	Trail road, bears N. 60° E. and S. 60° W.
37.22	Apache County Road C484, a graded road, 24 ft. wide, bears S. 47° E. and N. 47° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E 1/4 S 16 S 15
	2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.
48.60	Trail road, bears N. 40° E. and S. 40° W.

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS							
49.78	Apache County Road C484, a graded road, 24 ft. wide, along a curve to the left, bears northeasterly and southwesterly.						
51.94	Approximate location of underground water line, extending S. 45° E. and N. 45° W.						
53.02	Power line, 2 strand, bears S. 45° E. and N. 45° W.						
53.45	Enter inhabited area.						
57.43	Steel fence, bears N. 25° E. and S. 25° W.						
57.76	The same steel fence, bears S. 35° E. and N. 35° W.						
59.70	Approximate location of underground water line, extending East and West.						
67.18	Power line, 2 strand, bears East and West.						
69.92	A fence corner, barbed wire, 5 strands, bears N. 65° E. and West, leave inhabited area.						
80.00	Point for the cor. of secs. 9, 10, 15, and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> </table> <p>2021</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor. <hr style="width: 50%; margin-left: 0;"/> From the cor. of secs. 10, 11, 14, and 15. West, bet. secs. 10 and 15. Over rolling and broken terrain.	T 39 N	R 25 E	S 9	S 10	S 16	S 15
T 39 N	R 25 E						
S 9	S 10						
S 16	S 15						
33.20	Power line, 2 strand, bears N. 6° E. and S. 6° W.						
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.						

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E S 10 1/4 ——— S 15 2021
	Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.
	Set a steel "T" post alongside and N. of cor.
60.35	Barbed wire fence, 5 strands, bears N. 65° E. and S. 65° W.
80.00	The cor. of secs. 9, 10, 15, and 16.
	N. 0°02' W., bet. secs. 9 and 10.
	Over gently rolling and rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E 1/4 S 9 S 10 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.
80.00	Point for the cor. of secs. 3, 4, 9, and 10.
	Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.
	T 39 N R 25 E S 4 S 3 S 9 S 10 2021
	Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over gently rolling terrain.</p>
25.35	Power line, 2 strand, bears N. 6° E. and S. 6° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 25 E</p> <p style="margin-left: 100px;">S 3</p> <p style="margin-left: 100px;">1/4 ———</p> <p style="margin-left: 100px;">S 10</p> <p style="margin-left: 100px;">2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Set a steel "T" post alongside and N. of cor.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over gently rolling terrain.</p>
11.44	Dirt road, 18 ft. wide, bears N. 62° E. and S. 62° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 25 E</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 100px;">S 4 S 3</p> <p style="margin-left: 100px;">2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS

77.79

Point for the closing cor. of secs. 3 and 4, T. 39 N., R. 25 E., at intersection with the S. bdy. of sec. 35, T. 40 N., R. 25 E.

Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.

T	40	N	R	25	E
			S	35	
	S	4	S	3	
		T	39	N	R
			25		E
					CC

2021

Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.

Set a steel "T" post in a drill hole, alongside and S. of cor.

From this closing cor., the 1/4 sec. cor. of sec. 35 only, T. 40 N., R. 25 E., bears East, 38.04 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins above ground, with brass cap mkd. "T40N R25E 1/4 S35 2017", witnessed by a steel "T" post, N. of cor. Add the marks 2021 to the brass cap.

From this same closing cor., the cor. of secs. 34 and 35 only, T. 40 N., R. 25., bears West, 1.94 chs. dist., monumented with a with a brass tablet, 3 1/2 ins. diam., firmly set, cemented in sandstone bedrock, with top mkd. "T40N R25E S34 S35 2017", witnessed by a mound of stone, 2 1/2 ft. base, 2 ft. high, S. of cor. Add the marks 2021 to the brass tablet.

From this cor. of secs. 34 and 35 only, T. 40 N., R. 25., an iron pipe, 2 1/2 ins. diam., filled with concrete, firmly set, projecting 18 ins. above ground, mkd. on the S. face, "T40N R25E 34 35 3 2 T39N", bears S. 50°19' E., 1.365 chs. dist. This iron pipe is typical as the monuments set by Ernest V. Echohawk, Arizona R.L.S. No. 2311, in 1958, in or near T. 40 N., R. 27 E., found by Leonard R. Sandoval, Cadastral Surveyor, while originally surveying T. 40 N., R. 27 E., in 2000, according to Book 5642.

From this same closing cor., power line, 2 strand, extending N. 8° E. and S. 8° W., bears West, 11.14 chs. dist.

Point for the 1/4 sec. cor. of sec. 3 only, T. 39 N., R. 25 E., at midpoint on the N. bdy. of sec. 3, on the S. bdy. of sec. 35, T. 40 N., R. 25 E.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T 40 N R 25 E
	<hr style="width: 10%; margin: auto;"/> 1/4 S 3 T 39 N R 25 E
	2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and S. of cor.
	From this cor. point, the cor. of secs. 35 and 36 only, T. 40 N., R. 25 E., bears East, 38.04 chs. dist.
	From this same cor. point, the 1/4 sec. cor. of sec. 35 only, T. 40 N., R. 25 E., bears West, 1.95 chs. dist.
	<hr style="width: 80%; margin: 10px auto;"/> From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3, ins. above ground, in a scattered collar of stone, with brass cap mkd. "T39N R25E S32 S33 S5 S4 T38N 2000". Add the marks 2021 to the brass cap.
	Rebuilt the collar of stone to top of brass cap.
	N. 0°03' W., bet. secs. 32 and 33.
	Over gently rolling and broken terrain, within the Chinle Valley.
7.68	Graded road, 24 ft. wide, bears S. 60° E. and N. 60° W.
9.05	Barbed wire fence, bears S. 55° E. and N. 55° W.
13.18	The same barbed wire fence, bears N. 20° E. and S. 20° W.
17.85	Dirt road, 10 ft. wide, bears N. 55° E. and S. 55° W.
21.00	Enter inhabited area.
26.75	Barbed wire fence enclosing a circular shape corral, bears northeasterly and southwesterly.
27.75	The same barbed wire fence enclosing the circular shape corral, bears southeasterly and northwesterly.
30.30	Power line, 2 strand, bears S. 77° E. and N. 77° W.
39.10	Leave inhabited area.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E 1/4 S 32 S 33</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The cor. is located approximately 1.14 chs. from a burial site.</p>
47.55	Trail road, bears N. 15° E. and S. 20° W.
52.56	Navajo Route 8014, a graded road, 24 ft. wide, along a curve to the right, bears southeasterly and northwesterly.
53.55	Left bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 65° E. and N. 65° W.
67.35	Left bank of the Chinle Wash, approximately 5 ft. high, bears N. 65° E. and S. 55° W.
75.75	Main channel of the Chinle Wash, approximately 45 ft. wide, approximately 5 ft. deep, drains S. 65° W.
78.50	Right bank of the Chinle Wash, approximately 10 ft. high, bears S. 75° E. and N. 80° W.
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E S 29 S 28 S 32 S 33</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>West, bet. secs. 28 and 33.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling and broken terrain, within the Chinle Valley.
4.48	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
6.18	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears S. 28° E. and N. 28° W.
7.89	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
13.30	Graded road, 24 ft. wide, bears N. 40° E. and S. 40° W.
15.25	Graded road, 24 ft. wide, bears N. 55° E. and S. 55° W.
15.94	Approximate location of underground water line, extending S. 30° E. and N. 30° W.
23.39	Power line, 2 strand, bears S. 35° E. and N. 35° W.
23.76	Power line, 2 strand, bears S. 35° E. and N. 35° W.
35.05	Trail road, bears N. 20° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 32 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 25 E S 28 1/4 ——— S 33 2021 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and N. of cor.
42.25	Trail road, bears S. 25° E. and N. 25° W.
43.05	Trail road, bears N. 80° E. and S. 80° W.
49.20	Trail road, bears S. 50° E. and N. 50° W.
61.95	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears N. 15° E. and S. 25° W.
80.00	The cor. of secs. 28, 29, 32, and 33. <hr style="width: 80%; margin-left: 0;"/> N. 0°03' W., bet. secs. 28 and 29.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling and broken terrain, within the Chinle Valley.
1.10	Right bank of the Chinle Wash, approximately 10 ft. high, bears N. 75° E. and S. 80° W.
1.75	Main channel of the Chinle Wash, approximately 45 ft. wide, approximately 5 ft. deep, drains N. 75° E.
6.90	Main channel of the Chinle Wash, approximately 40 ft. wide, approximately 5 ft. deep, drains S. 40° W.
9.30	Right bank of the Chinle Wash, approximately 10 ft. high, bears N. 65° E. and S. 70° W.
21.15	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 55° E. and N. 40° W.
21.55	Trail road, bears S. 55° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 39 N R 25 E 1/4 S 29 S 28 2021 </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor.
45.45	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears N. 35° E. and S. 50° W.
57.25	Right bank of the Chinle Wash, approximately 6 ft. high, bears N. 70° E. and S. 70° W.
59.90	Main channel of the Chinle Wash, approximately 40 ft. wide, approximately 5 ft. deep, drains N. 75° E.
65.75	Main channel of the Chinle Wash, approximately 30 ft. wide, approximately 5 ft. deep, drains S. 45° W.
67.40	Right bank of the Chinle Wash, approximately 6 ft. high, bears S. 10° E. and N. 20° W.
77.40	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 65° E. and N. 55° W.
79.24	Power line, 2 strand, bears S. 35° E. and N. 35° W.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS									
80.00	<p>Point for the cor. of secs. 20, 21, 28, and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> </table> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p> <p>The cor. is located on top of the left bank of a wash, 8 ft. wide, 5 ft. deep, drains N. 25° W.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>West, bet. secs. 21 and 28.</p> <p>Over rugged, broken, rolling, and gently rolling terrain.</p>	T 39 N	R 25 E	S 20	S 21	S 29	S 28		
T 39 N	R 25 E								
S 20	S 21								
S 29	S 28								
21.40	Descent abruptly into the Chinle Valley.								
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 31 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 25 E</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 21</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="border-bottom: 1px solid black; padding: 0 10px;">—</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">S 28</td> </tr> </table> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>	T 39 N	R 25 E		S 21	1/4	—		S 28
T 39 N	R 25 E								
	S 21								
1/4	—								
	S 28								
49.59	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.								
51.26	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears S. 48° E. and N. 48° W.								
53.56	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.								

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
60.85	Trail road, bears N. 45° E. and S. 35° W.
77.85	Barbed wire fence, bears S. 60° E. and N. 60° W.
80.00	The cor. of secs. 20, 21, 28, and 29.

	N. 0°03' W., bet. secs. 20 and 21.
	Over gently rolling, broken, and rolling terrain, within the Chinle Valley.
29.14	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, along a curve to the right, bears southeasterly and northwesterly.
	Note: There is not a westerly right-of-way fence in this area, the Highway is located easterly of the bottom of a southwesterly facing sandstone cliff.
34.55	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E 1/4 S 20 S 21 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor.
44.79	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
50.15	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, along a curve to the right, bears northeasterly and southwesterly.
50.41	Approximate location of underground water line, extending S. 70° E. and N. 70° W.
51.25	From this point, approximate location of underground water line, extending S. 70° E. and N. 78° W., bears West, 2.86 chs. dist.
53.82	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
54.15	From this point, power line, 2 strand, extending N. 27° E. and S. 18° W., bears West, 1.64 chs. dist.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
55.02	From this point, approximate location of underground water line, extending S. 78° E. and N. 84° W., bears West, 20.23 chs. dist.						
55.12	From this point, approximate location of underground water line, extending S. 84° E. and West, bears West, 21.24 chs. dist.						
57.47	Power line, 2 strand, bears N. 27° E. and S. 27° W.						
62.00	From this point, approximate location of underground water line, extending N. 20° E. and S. 41° W., bears East, 12.73 chs. dist. From this location, the NE cor. of a fence, enclosing a water pumping station, bears approximately N. 35° E., 1.22 chs. dist., chain link, 6 ft. high, extending S. 20° W. and N. 70° W. From this same location, the SE cor. of the same fence, enclosing the water pumping station, bears approximately N. 50° E., 50 lks. dist., chain link, 6 ft. high, extending N. 20° E. and N. 70° W. From this same location, the SW cor. of the same fence, enclosing the water pumping station, bears approximately N. 30° W., 65 lks. dist., chain link, 6 ft. high, extending N. 20° E. and S. 70° E. From this same location, the NW cor. of the same fence, enclosing the water pumping station, bears approximately N. 2° W., 1.28 chs. dist., chain link, 6 ft. high, extending S. 70° E. and S. 20° W.						
68.75	Power line, 2 strand, bears N. 70° E. and S. 70° W.						
69.60	Trail road, bears N. 60° E. and S. 60° W.						
73.40	Leave the Chinle Valley.						
80.00	Point for the cor. of secs. 16, 17, 20, and 21. Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd. <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> <p style="text-align: center;">2021</p> Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.	T 39 N	R 25 E	S 17	S 16	S 20	S 21
T 39 N	R 25 E						
S 17	S 16						
S 20	S 21						

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel "T" post in a drill hole, alongside and W. of cor.
	From the cor. of secs. 15, 16, 21, and 22.
	West, bet. secs. 16 and 21.
	Over rugged, broken, rolling, and gently rolling terrain.
39.00	Descent abruptly into the Chinle Valley.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E S 16 1/4 ——— S 21 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and N. of cor.
42.27	Barbed wire fence, enclosing an abandoned cultivated field, bears North and South.
43.79	The same barbed wire fence, bears N. 65° E. and S. 65° W., leave the abandoned cultivated field.
48.35	Leave the Chinle Valley.
52.80	Enter the Chinle Valley.
54.00	Enter inhabited area.
61.60	Power line, 2 strand, bears N. 27° E. and S. 27° W.
62.70	Leave inhabited area, leave the Chinle Valley.
63.02	Approximate location of underground water line, extending N. 27° E. and S. 27° W.
63.53	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
65.21	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears N. 26° E. and S. 26° W.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
66.92	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
68.73	Power line, 2 strand, bears N. 27° E. and S. 27° W.
80.00	The cor. of secs. 16, 17, 20, and 21. <hr/>
	N. 0°03' W., bet. secs. 16 and 17. Over rugged, broken, and rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17. Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd. <div style="text-align: center;">T 39 N R 25 E 1/4 S 17 S 16 2021</div>
	Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod. Set a steel "T" post in a drill hole, alongside and W. of cor.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd. <div style="text-align: center;">T 39 N R 25 E S 8 S 9 S 17 S 16 2021</div>
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet. Set a steel "T" post in a drill hole, alongside and W. of cor. <hr/>
	From the cor. of secs. 9, 10, 15, and 16. West, bet. secs. 9 and 16. Over gently rolling, rugged, and rolling terrain.
23.10	Trail road, bears S. 20° E. and N. 20° W.

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
26.64	Power line, 2 strand, bears S. 45° E. and N. 45° W.
28.17	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
29.71	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears N. 8° E. and S. 8° W.
31.22	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
32.79	Power line, 2 strand, bears N. 8° E. and S. 8° W.
34.26	Approximate location of underground water line, extending S. 14° E. and N. 14° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 25 E S 9 1/4 ——— S 16</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, an empty white plastic case, and a bundle of white flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>
80.00	<p>The cor. of secs. 8, 9, 16, and 17.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rugged, broken, and rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 39 N R 25 E 1/4 S 8 S 9</p> <p>2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
	Set a steel "T" post in a drill hole, alongside and W. of cor.												
68.70	Trail road, bears N. 55° E. and S. 55° W.												
69.45	Trail road, bears S. 80° E. and N. 80° W.												
80.00	Point for the cor. of secs. 4, 5, 8, and 9.												
	Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.												
	<table style="margin: auto;"> <tr> <td colspan="2">T 39 N</td> <td colspan="2">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 5</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 4</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black;">S 8</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 9</td> <td></td> </tr> </table>	T 39 N		R 25 E		S 5		S 4		S 8		S 9	
T 39 N		R 25 E											
S 5		S 4											
S 8		S 9											
	2021												
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.												
	Set a steel "T" post in a drill hole, alongside and W. of cor.												
	<hr/>												
	From the cor. of secs. 3, 4, 9, and 10.												
	West, bet. secs. 4 and 9.												
	Over gently rolling and rolling terrain.												
12.00	Trail road, bears North, and S. 5° E.												
17.16	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.												
18.70	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears N. 8° E. and S. 8° W.												
20.21	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.												
21.82	Power line, 2 strand, bears N. 8° E. and S. 8° W.												
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.												

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E S 4 1/4 ——— S 9 2021
	Deposit a magnet, in a white plastic case, and a bundle of white flagging, at the base of the stainless steel post.
	Set a steel "T" post alongside and N. of cor.
58.40	Enter inhabited area.
63.38	A fence enclosing a corral, steel, approximately 6 ft. high, bears N. 15° E. and S. 15° W.
64.24	The same fence enclosing the corral, steel, approximately 6 ft. high, bears S. 35° E. and N. 35° W.
64.35	Approximate location of underground water line, extending S. 41° E. and N. 41° W.
65.03	Power line, 2 strand, bears N. 43° E. and S. 43° W.
65.25	Power line, 2 strand, bears S. 40° E. and N. 40° W.
68.15	Dirt road, 12 ft. wide, bears N. 45° E. and S. 45° W.
70.32	Graded road, 24 ft. wide, bears N. 20° E. and S. 20° W.
73.45	Leave inhabited area.
80.00	The cor. of secs. 4, 5, 8, and 9.
	<hr/>
	N. 0°03' W., bet. secs. 4 and 5.
	Over rugged, rolling, and gently rolling terrain.
6.50	Enter inhabited area.
17.35	Leave inhabited area.
25.00	Power line, 2 strand, bears S. 70° E. and N. 70° W.
25.76	Approximate location of underground water line, extending S. 70° E. and N. 70° W.
32.05	Trail road, bears S. 70° E. and N. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <p style="text-align: center;">T 39 N R 25 E 1/4 S 5 S 4 2021</p> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p> <p>Set a steel "T" post in a drill hole, alongside and W. of cor.</p> <p>The cor. is located halfway up of the south face a sandstone slope, 20 ft. high, bears N. 60° E. and S. 60° W.</p>
49.90	Trail road, bears N. 60° E. and S. 60° W.
50.27	Trail road, bears S. 30° E. and N. 30° W.
77.79	<p>Point for the closing cor. of secs. 4 and 5, T. 39 N., R. 25 E., at intersection with the S. bdy. of sec. 34, T. 40 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E S 34 ----- S 5 S 4 T 39 N R 25 E CC 2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and S. of cor.</p> <p>From this closing cor., the 1/4 sec. cor. of sec. 34 only, T. 40 N., R. 25 E., bears East, 38.075 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins above ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd. "T40N R25E 1/4 S34 2017". Add the marks 2021 to the brass cap.</p>

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same closing cor., the cor. of secs. 33 and 34 only, T. 40 N., R. 25., bears West, 1.915 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins above ground, with brass cap mkd. "T40N R25E S33 S34 2017", witnessed by a steel "T" post, N. of cor. Add the marks 2021 to the brass cap.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 4 only, T. 39 N., R. 25 E., at midpoint on the N. bdy. of sec. 4, on the S. bdy. of sec. 34, T. 40 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 33 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 4 T 39 N R 25 E</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and S. of cor.</p> <p>From this cor. point, the cor. of secs. 34 and 35 only, T. 40 N., R. 25 E., bears East, 38.06 chs. dist.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 34 only, T. 40 N., R. 25 E., bears West, 1.93 chs.</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., firmly set, cemented in sandstone bedrock, with top mkd. "T39N R25E S31 S32 S6 S5 T38N 2000". The sandstone bedrock has been eroding away, patch up the holes with concrete. Add the marks 2021 to the brass tablet.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over rolling, rugged, and broken terrain.</p>
10.25	Navajo Route 8014, a graded road, 24 ft. wide, bears N. 65° E. and S. 65° W.
17.15	Power line, 2 strand, bears N. 84° E. and S. 84° W.
18.55	Enter inhabited area.
23.30	Trail road, bears S. 60° E. and N. 60° W.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
27.85	Leave inhabited area.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32. Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 11 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd. <div style="text-align: center;"> T 39 N R 25 E 1/4 S 31 S 32 2021 </div> Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod. Set a steel "T" post in a drill hole, alongside and W. of cor.
80.00	Point for the cor. of secs. 29, 30, 31, and 32. Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd. <div style="text-align: center;"> T 39 N R 25 E S 30 S 29 S 31 S 32 2021 </div> Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod. Set a steel "T" post in a drill hole, alongside and W. of cor. The cor. is located on an easterly facing sandstone slope, 20 ft. high, bears N. 10° E. and S. 10° E. <hr/> From the cor. of secs. 28, 29, 32, and 33. West, bet. secs. 29 and 32. Over gently rolling, broken, rolling and rugged terrain, within the Chinle Valley.
3.45	Right bank of the Chinle Wash, approximately 10 ft. high, bears N. 75° E. and S. 70° W.
4.15	Main channel of the Chinle Wash, approximately 40 ft. wide, approximately 5 ft. deep, drains N. 70° E.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
6.90	Left bank of the Chinle Wash, approximately 10 ft. high, bears N. 60° E. and S. 20° E.
22.60	Left bank of the Chinle Wash flood plain, approximately 2 ft. high, bears N. 15° E. and S. 20° E.
24.18	Apache County Road C487, a graded road, 24 ft. wide, bears S. 27° E. and N. 27° W.
29.23	Barbed wire fence, 4 strand, bears S. 25° E. and N. 25° W.
39.50	Leave the Chinle Valley.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32. Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.
	T 39 N R 25 E S 29 1/4 ——— S 32 2021
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.
	Set a steel "T" post in a drill hole, alongside and N. of cor.
	The cor. is located approximately 10 vertical ft. above the desert floor, on the easterly face of a 32° sandstone slope, bears S. 10° E. and N. 10° W.
80.00	The cor. of secs. 29, 30, 31, and 32.

	West, bet. secs. 30 and 31.
	Over rugged and rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E S 30 1/4 ——— S 31 2021

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, an empty white plastic case, and a bundle of white flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>
78.82	<p>The cor. of secs. 25, 30, 31, and 36, on the Sixth Guide Meridian East, (West Boundary of the Tp.), hereinbefore described.</p> <hr/> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rugged, broken, rolling, and gently rolling terrain.</p>
30.50	<p>Top of descent, slopes northerly.</p>
35.80	<p>Bottom of descent, approximately 100 vertical ft., enter the Chinle Valley.</p>
39.00	<p>Trail road, bears S. 45° E. and N. 45° W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E 1/4 S 30 S 29</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, an empty white plastic case, and a bundle of white flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>
41.05	<p>Trail road, bears N. 50° E. and S. 50° W.</p>
41.75	<p>Trail road, bears N. 25° E. and S. 35° W.</p>
44.35	<p>Trail road, bears S. 30° E. and N. 65° W.</p>
45.95	<p>Trail road, bears S. 60° E. and N. 60° W.</p>
54.35	<p>Trail road, bears N. 35° E. and S. 50° W.</p>
55.00	<p>Enter inhabited area.</p>
56.65	<p>Leave inhabited area.</p>
57.40	<p>Trail road, bears S. 30° E. and N. 30° W.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS													
59.90	Trail road, bears N. 55° E. and S. 55° W.												
64.00	Enter inhabited area.												
64.30	Trail road, bears N. 15° E. and S. 15° W.												
66.88	Power line, 2 strand, bears S. 80° E. and N. 80° W.												
68.30	Southerly edge of a hogan, bears N. 80° E. and S. 80° W.												
68.72	Northerly edge of the same hogan, bears S. 65° E. and N. 65° W.												
71.00	Leave inhabited area.												
73.50	Trail road, bears S. 65° E. and N. 5° W.												
73.85	Trail road, bears S. 30° E. and N. 30° W.												
75.25	Trail road, bears S. 25° E. and N. 25° W.												
80.00	Point for the cor. of secs. 19, 20, 29, and 30.												
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 39 N</td> <td colspan="2">R 25 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 19</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 20</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black;">S 30</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 29</td> <td></td> </tr> </table>	T 39 N		R 25 E		S 19		S 20		S 30		S 29	
T 39 N		R 25 E											
S 19		S 20											
S 30		S 29											
	2021												
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.												
	Set a steel "T" post West, approximately 3 ft. of cor.												
	The cor. is located on the westerly edge of a 2 track road, 8 ft. wide, bears North and South.												
	from which												
	A galvanized nail, 2 ins. long, stamped "PK", set in the NE face of a wooden power pole, 9 ins. diam., approximately 30 ft. high, number "3 D 1 08", nail set 12 ins. above ground, for a reference monument, bears S. 24°26' W., 152.5 ft. dist. with brass washer, 1 1/2 ins. diam. mkd. "BLM 2021". The power line bears North and South.												
	From this cor. point, a wooden power pole on the same power line, bears approximately N. 15° W., approximately 3.36 chs. dist.												
	From the cor. of secs. 20, 21, 28, and 29.												

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, bet. secs. 20 and 29.
	Over gently rolling and broken terrain, within the Chinle Valley.
0.53	Power line, 2 strand, bears S. 35° E. and N. 35° W.
5.95	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 60° E. and N. 50° W.
17.55	Right bank of the Chinle Wash, approximately 6 ft. high, bears S. 10° E. and N. 15° W.
21.55	Main channel of the Chinle Wash, approximately 30 ft. wide, approximately 5 ft. deep, drains N. 25° W.
22.30	Left bank of the Chinle Wash, approximately 6 ft. high, bears S. 25° E. and N. 15° W.
26.65	Left bank of the Chinle Wash flood plain, approximately 2 ft. high, bears N. 10° E. and S. 15° E.
28.30	Trail road, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E S 20 1/4 ——— S 29 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and N. of cor.
69.34	Apache County Road C487, a graded road, 24 ft. wide, bears S. 26° E. and N. 26° W.
75.75	Trail road, bears N. 5° E. and S. 5° W.
78.79	Approximate location of underground water line, extending North and South.
80.00	The cor. of secs. 19, 20, 29, and 30.

	West, bet. secs. 19 and 30.
	Over gently rolling, rugged and rolling terrain, within the Chinle Valley.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
1.00	Power line, 2 strand, bears North and South.
3.18	Trail road, bears S. 30° E. and N. 30° W.
7.15	Trail road, bears N. 15° E. and South.
15.55	Trail road, bears S. 25° E. and N. 25° W.
17.15	Bottom of ascent, slopes westerly, leave the Chinle Valley.
28.80	Top of ascent, approximately 120 vertical ft.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.
	T 39 N R 25 E S 19 1/4 ——— S 30 2021
	Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.
	Set a steel "T" post in a drill hole, alongside and N. of cor.
78.73	The cor. of secs. 19, 24, 25, and 30, on the Sixth Guide Meridian East, (West Boundary of the Tp.), hereinbefore described.

	N. 0°03' W., bet. secs. 19 and 20.
	Over gently rolling and broken terrain, within the Chinle Valley.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E 1/4 S 19 S 20 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
40.31	From this point, power line, 4 strand, extending North, N. 70° E. and South, bears West, 23 lks. dist.						
40.39	Power line, 2 strand, bears N. 70° E. and S. 70° W.						
50.43	Approximate location of underground water line, extending S. 25° E. and N. 25° W.						
55.37	Apache County Road C487, a graded road, 24 ft. wide, along a curve to the left, bears southeasterly and northwesterly.						
80.00	Point for the cor. of secs. 17, 18, 19, and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T 39 N</td> <td>R 25 E</td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> </table> <p>2021</p> </div> Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor. <hr/> From the cor. of secs. 16, 17, 20, and 21. West, bet. secs. 17 and 20. Over rolling, broken, and gently rolling terrain.	T 39 N	R 25 E	S 18	S 17	S 19	S 20
T 39 N	R 25 E						
S 18	S 17						
S 19	S 20						
3.00	Descent into the Chinle valley.						
16.65	Trail road, bears S. 15° E. and N. 15° W.						
24.25	Right bank of the Chinle Wash, approximately 10 ft. high, bears S. 40° E. and N. 55° W.						
25.00	Main channel of the Chinle Wash, approximately 40 ft. wide, approximately 5 ft. deep, drains N. 50° W.						
31.30	Left bank of the Chinle Wash, approximately 6 ft. high, bears N. 30° E. and S. 20° E.						
39.40	Left bank of the Chinle Wash flood plain, approximately 4 ft. high, bears S. 30° E. and N. 25° W.						
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.						

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 25 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and N. of cor.</p>
41.60	Trail road, bears S. 5° E. and N. 5° W.
66.25	Trail road, bears N. 35° E. and S. 35° W.
73.10	Trail road, bears N. 15° E. and S. 15° W.
80.00	The cor. of secs. 17, 18, 19, and 20.
	<hr/> <p>West, bet. secs. 18 and 19.</p> <p>Over gently rolling, rugged, broken, and rolling terrain, within the Chinle Valley.</p>
14.20	Apache County Road C487, a graded road, 24 ft. wide, bears S. 34° E. and N. 34° W.
15.80	Power line, 2 strand, bears S. 28° E. and N. 28° W.
17.60	Approximate location of underground water line, extending S. 31° E. and N. 31° W.
34.90	Bottom of ascent, slopes westerly, leave the Chinle Valley.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	<p>Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.</p> <p style="text-align: center;">T 39 N R 25 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.</p>

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a steel "T" post in a drill hole, alongside and N. of cor. The cor. is located on the south face of a sandstone ridge, bears East and S. 80° W., and approximately 80 vertical ft. above the desert floor.
68.00	Top of ascent, approximately 330 vertical ft.
78.64	The cor. of secs. 13, 18, 19, and 24, on the Sixth Guide Meridian East, (West Boundary of the Tp.), hereinbefore described.

	N. 0°03' W., bet. secs. 17 and 18. Over gently rolling, broken, and rolling terrain, within the Chinle Valley.
36.75	Trail road, bears S. 50° E. and N. 50° W.
39.10	Trail road, bears S. 40° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E 1/4 S 18 S 17 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor.
48.65	Trail road, bears N. 30° E. and S. 30° W.
65.20	Trail road, bears N. 65° E. and S. 65° W.
72.80	Left bank of the Chinle Wash, approximately 15 ft. high, bears S. 75° E. and N. 80° W.
74.05	Main channel of the Chinle Wash, approximately 30 ft. wide, approximately 5 ft. deep, drains N. 70° W.
76.35	Right bank of the Chinle Wash, approximately 15 ft. high, bears N. 70° E. and S. 60° W.
79.50	Leave the Chinle Valley.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS							
80.00	<p>The true point for the cor. of secs. 7, 8, 17 and 18, falls on the south face of a sandstone cliff, approximately 20 ft. high, bears S. 80° E. and N. 80° W., where it is impracticable to establish a permanent monument. Not monumented.</p> <p>From this true point, the point selected for a witness cor. to the cor. of secs. 7, 8, 17 and 18, bears N. 7°10' E., 59 lks. dist.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd.</p> <div style="text-align: center;"> <p>WC</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 39 N</td> <td style="padding: 0 10px;">R 25 E</td> </tr> <tr> <td style="padding: 0 5px;">S 7</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 8</td> </tr> <tr> <td style="padding: 0 5px;">S 18</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 17</td> </tr> </table> <p style="margin: 0 auto;">↓ 2021</p> </div> <p>Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet.</p> <p>Set a steel "T" post in a drill hole, alongside and N. 7° E. of cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, bet. secs. 8 and 17.</p> <p>Over rugged, broken, and rolling terrain.</p>	T 39 N	R 25 E	S 7	S 8	S 18	S 17
T 39 N	R 25 E						
S 7	S 8						
S 18	S 17						
17.85	Trail road, bears N. 35° E. and S. 40° W.						
21.65	Top of descent, slopes easterly.						
24.05	Bottom of descent, approximately 40 vertical ft., enter the Chinle Valley.						
25.80	Trail road, bears S. 10° E. and N. 20° W.						
31.40	Trail road, bears North and South.						
40.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> <p>2021</p> </div>						

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and N. of cor.
41.60	Trail road, bears N. 40° E. and S. 45° W.
51.50	Leave the Chinle Valley.
80.00	The cor. of secs. 7, 8, 17 and 18.
<hr/>	
	West, bet. secs. 7 and 18.
	Over rugged, broken, and rolling terrain.
7.40	Enter the Chinle Valley.
20.50	Right bank of the Chinle Wash, approximately 25 ft. high, bears S. 20° E. and N. 25° W.
27.70	Main channel of the Chinle Wash, approximately 60 ft. wide, approximately 5 ft. deep, drains N. 25° E.
33.15	Left bank of the Chinle Wash, approximately 15 ft. high, bears S. 45° E. and S. 75° W.
38.20	Trail road, bears S. 35° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E S 7 1/4 ——— S 18 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and N. of cor.
51.65	Left bank of the Chinle Wash, approximately 10 ft. high, bears N. 45° E. and S. 65° W.
61.00	Left bank of the Chinle Wash, approximately 10 ft. high, bears S. 50° E. and N. 40° W.
62.85	Trail road, bears S. 10° W. and N. 5° W.

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
66.20	Trail road, bears S. 30° E. and N. 15° W.
78.55	The cor. of secs. 7, 12, 13, and 18, on the Sixth Guide Meridian East, (West Boundary of the Tp.), hereinbefore described. <hr/>
	N. 0°03' W., bet. secs. 7 and 8. Over rugged, broken, and rolling terrain.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8. Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd. <div style="text-align: center;">T 39 N R 25 E 1/4 S 7 S 8 2021</div>
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet. Set a steel "T" post in a drill hole, alongside and W. of cor.
80.00	Point for the cor. of secs. 5, 6, 7, and 8. Set a brass tablet, 3 1/4 ins. diam., 3 ins. stem, cemented in a drill hole, in sandstone bedrock, with top mkd. <div style="text-align: center;">T 39 N R 25 E S 6 S 5 S 7 S 8 2021</div>
	Deposit a magnet, without the white plastic case, at the base of the stem of the brass tablet. Set a steel "T" post in a drill hole, alongside and N. of cor. The cor. is located on top of the southerly edge of a sandstone cove, approximately 30 ft. wide, approximately 30 ft. deep, and approximately 8 ft. up from the bottom. <hr/>
	From the cor. of secs. 4, 5, 8, and 9. West, bet. secs. 5 and 8. Over rugged, broken, and rolling terrain.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
37.00	Trail road, bears S. 15° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 39 N R 25 E S 5 1/4 ——— S 8 2021</div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and N. of cor.
41.25	Trail road, bears N. 35° E. and S. 35° W.
41.95	Approximate location of underground water line, extending N. 16° E. and S. 16° W.
42.67	Power line, 2 strand, bears N. 16° E. and S. 16° W.
80.00	The cor. of secs. 5, 6, 7, and 8. <hr style="width: 60%; margin-left: 0;"/>
	West, bet. secs. 6 and 7. Over rugged, broken, and rolling terrain.
33.00	Trail road, bears N. 15° E. and S. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 39 N R 25 E S 6 1/4 ——— S 7 2021</div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and N. of cor.
48.15	Trail road, bears S. 50° E. and N. 40° W.
48.75	Trail road, bears North and South.

Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
78.46	<p>The cor. of secs. 1, 6, 7, and 12, on the Sixth Guide Meridian East, (West Boundary of the Tp.), hereinbefore described.</p> <hr/> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over rugged, broken, and rolling terrain.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 39 N R 25 E 1/4 S 6 S 5</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, and a bundle of pink flagging, at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
53.75	Trail road, bears N. 80° E. and S. 80° W.
53.86	Power line, 2 strand, bears S. 70° E. and N. 70° W.
54.65	Approximate location of underground water line, extending S. 70° E. and N. 70° W.
77.80	<p>Point for the closing cor. of secs. 5 and 6, T. 39 N., R. 25 E., at intersection with the S. bdy. of sec. 33, T. 40 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 40 N R 25 E S 33 ----- S 6 S 5 T 39 N R 25 E CC</p> <p>2021</p> </div> <p>Deposit a magnet, in a white plastic case, and an empty white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and S. of cor.</p>

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this closing cor., the 1/4 sec. cor. of sec. 33 only, T. 40 N., R. 25 E., bears East, 38.09 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins above ground, with brass cap mkd. "T40N R25E 1/4 S33 2017", witnessed by a steel "T" post, N. of cor. Add the marks 2021 to the brass cap.

From this same closing cor., the cor. of secs. 32 and 33 only, T. 40 N., R. 25., bears West, 1.89 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 7 ins below the surface of BIA Road No. 5023, with brass cap mkd. "T40N R25E S32 S33 2017". BIA Road No. 5023, a graded road, 33 ft. wide, bears N. 73° E. and S. 66° W. Add the marks 2021 to the brass cap.

From this cor. of secs. 32 and 33 only, T. 40 N., R. 25., the original reference monuments

A stainless steel post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, bears S. 45°00' E., 75.0 ft. dist. with brass cap mkd. "RM T39N R25E 75.0 FT TO COR. S6 2017" and an arrow pointing to the cor., witnessed by a steel "T" post NW of RM. Remove surrounding dirt, stainless steel post is projecting 1 in. above ground. Add the marks 2021 to the brass cap.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears N. 45°00' W., 75.0 ft. dist. with brass cap mkd. "RM T40N R25E 75.0 FT TO COR. S32 2017" and an arrow pointing to the cor., witnessed by a steel "T" post SE of RM. Add the marks 2021 to the brass cap.

Point for the 1/4 sec. cor. of sec. 5 only, T. 39 N., R. 25 E., at midpoint on the N. bdy. of sec. 5, on the S. bdy. of sec. 33, T. 40 N., R. 25 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 40 N R 25 E

—————
1/4 S 5
T 39 N R 25 E

2021

Deposit a magnet, in a white plastic case, and a small bundle of pink flagging, at the base of the stainless steel post.

Set a steel "T" post alongside and S. of cor.

**Survey of the Subdivisional Lines,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this cor. point, the cor. of secs. 33 and 34 only, T. 40 N., R. 25 E., bears East, 38.09 chs. dist.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 33 only, T. 40 N., R. 25 E., bears West, 1.90 chs. dist.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 6 only, T. 39 N., R. 25 E., at 40.00 chs. dist. from the closing cor. of secs. 5 and 6, on the N. bdy. of sec. 6, on the S. bdy. of sec. 32, T. 40 N., R. 25 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 40 N R 25 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 6 T 39 N R 25 E</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, and an empty white plastic case, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and S. of cor.</p> <p>From this cor. point, the cor. of secs. 32 and 33 only, T. 40 N., R. 25 E., bears East, 38.11 chs. dist.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 32 only, T. 40 N., R. 25 E., bears West, 1.88 chs. dist.</p> <hr/> <p style="text-align: center;">Subdivision of Section 4, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 4.</p> <p>Over rolling terrain.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 4,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E C 1/4 . S 4 2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.
77.79	The 1/4 sec. cor. of sec. 4 only, on the N. bdy of the Tp., on the S. bdy. of sec. 34, T. 40 N., R. 25 E.
	From the 1/4 sec. cor. of secs. 3 and 4. West, on the E. and W. center line of sec. 4 Over gently rolling and rolling terrain.
11.67	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
13.21	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears N. 8° E. and S. 8° W.
14.71	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
16.32	Power line, 2 strand, bears N. 8° E. and S. 8° W.
40.00	The center 1/4 sec. cor. of sec. 4.
76.15	Trail road, bears N. 3° E. and S. 3° W.
80.00	The 1/4 sec. cor. of secs. 4 and 5.
	Subdivision of Section 9, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 9 and 16. N. 0°02' W., on the N. and S. center line of sec. 9. Over gently rolling terrain.
12.58	Approximate location of underground water line, extending S. 45° E. and N. 45° W.
13.50	Power line, 2 strand, bears S. 45° E. and N. 45° W.

Subdivision of Section 9,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
14.90	Trail road, bears S. 20° E. and N. 30° W.
17.00	Trail road, bears S. 65° E. and N. 65° W.
20.30	Trail road, bears S. 30° E. and N. 30° W.
21.70	Dirt road, 16 ft. wide, bears S. 48° E. and N. 48° W.
40.00	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. T 39 N R 25 E C 1/4 . S 9 2021 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor.
42.65	Trail road, bears N. 35° E. and S. 35° W.
59.20	From this point, a steel water tank, approximately 20 ft. diam., approximately 20 ft. high, bears East, 6.20 chs. dist.
59.60	From this point, a windmill, bears East, 6.24 chs. dist.
60.05	Graded road, 30 ft. wide, bears N. 83° E. and S. 83° W.
80.00	The 1/4 sec. cor. secs. 4 and 9. <hr/>
	From the 1/4 sec. cor. of secs. 9 and 10. West, on the E. and W. center line of sec. 9. Over rolling terrain.
22.67	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
24.21	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears N. 8° E. and S. 8° W.
25.73	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
27.33	Power line, 2 strand, bears N. 8° E. and S. 8° W.

**Subdivision of Section 9,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
33.45	Graded road, 24 ft. wide, bears N. 20° E. and S. 10° W.
40.00	The center 1/4 sec. cor. of sec. 9.
41.60	Trail road, bears N. 35° E. and S. 35° W.
52.47	Power line, 2 strand, bears S. 14° E. and N. 14° W.
53.13	Approximate location of underground water line, extending S. 14° E. and N. 14° W.
80.00	The 1/4 sec. cor. of secs. 8 and 9.
<hr/> <p>Subdivision of Section 16, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 16 and 21.
	N. 0°02' W., on the N. and S. center line of sec. 16.
	Over gently rolling, rugged, broken, and rolling terrain.
5.00	Leave the Chinle Valley.
38.52	Approximate location of underground water line, extending N. 27° E. and S. 27° W.
40.00	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line.
	Set a stainless steel drive rod, 14 ins. long, 9/16 in. diam., cemented in a drill hole, 14 ins. in sandstone bedrock, with brass tablet, 3 1/2 ins. diam. mkd.
	T 39 N R 25 E
	C 1/4 . S 16
	2021
	Deposit a magnet, without the white plastic case, at the base of the stainless steel drive rod.
	Set a steel "T" post in a drill hole, alongside and W. of cor.
	From this cor. point, a rebar, 1/2 in. diam., firmly set, flush with the surface of the ground, with an aluminum cap, approximately 2 ins. diam., mkd. "T & D SVCS, LLC + NMPS 5211 AZPS 39243", bears N. 25°38' E., 5.31 chs. dist., established by James Botsford, Arizona R.L.S. No. 39243, date unknown.

Subdivision of Section 16,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From this same cor. point, a fence corner on the easterly right-of-way fence of U. S. Highway 191, bears N. 70°29' W., 4.04 chs. dist., barbed wire, 5 strand, with fences extending S. 65° E. and S. 26° E.
	From this same cor. point, another fence corner on the same easterly right-of-way fence of U. S. Highway 191, bears N. 71°50' W., 3.21 chs. dist., barbed wire, 5 strand, with fences extending N. 26° E. and N. 65° W.
43.23	Power line, 2 strand, bears N. 27° E. and S. 27° W.
47.12	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
50.54	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears N. 27° E. and S. 27° W.
53.12	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
57.45	Power line, 2 strand, bears N. 27° E. and S. 27° W.
80.00	The 1/4 sec. cor. of secs. 9 and 16.
	<hr/>
	From the 1/4 sec. cor. of secs. 15 and 16.
	West, on the E. and W. center line of sec. 16.
	Over rolling and rugged terrain.
2.38	Apache County Road C484, a graded road, 24 ft. wide, along a curve to the left, bears southeasterly and northwesterly.
39.29	Approximate location of underground water line, extending N. 27° E. and S. 27° W.
40.00	The center 1/4 sec. cor. of sec. 16.
41.57	Power line, 2 strand, bears N. 27° E. and S. 27° W.
44.48	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
45.22	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears N. 27° E. and S. 27° W.
46.94	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
48.74	Power line, 2 strand, bears N. 27° E. and S. 27° W.


Subdivision of Section 16,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	The 1/4 sec. cor. of secs. 16 and 17.
<hr/> <p>Subdivision of Section 20, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 20 and 29.
	N. 0°03' W., on the N. and S. center line of sec. 20.
	Over gently rolling terrain, within the Chinle Valley.
40.00	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T 39 N R 25 E
	C 1/4 . S 20
	2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor.
54.58	Power line, 2 strand, bears N. 70° E. and S. 70° W.
54.80	Approximate location of underground water line, extending East and West.
57.95	Trail road, bears N. 85° E. and S. 85° W.
73.85	Trail road, bears S. 10° E. and N. 10° W.
80.00	The 1/4 sec. cor. of secs. 17 and 20.
<hr/>	
	From the 1/4 sec. cor. of secs. 20 and 21.
	West, on the E. and W. center line of sec. 20.
	Over gently rolling, broken, and rolling terrain, within the Chinle Valley.
0.47	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
1.96	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, along a curve to the left, bears northeasterly and southwesterly.

**Subdivision of Section 20,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
3.48	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
6.28	Power line, 2 strand, bears N. 18° E. and S. 18° W.
9.50	Right bank of the Chinle Wash, approximately 10 ft. high, bears N. 20° E. and S. 15° W.
12.30	Main channel of the Chinle Wash, approximately 50 ft. wide, approximately 5 ft. deep, drains N. 45° E.
15.40	Left bank of the Chinle Wash, approximately 6 ft. high, bears N. 35° E. and S. 45° W.
33.25	Trail road, bears S. 10° E. and N. 10° W.
40.00	The center 1/4 sec. cor. of sec. 20.
75.52	Apache County Road C487, a graded road, 24 ft. wide, bears S. 27° E. and N. 27° W.
76.35	Approximate location of underground water line, extending S. 17° E. and N. 17° W.
80.00	The 1/4 sec. cor. of secs. 19 and 20.
<hr/> <p>Subdivision of Section 21, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 21 and 28.
	N. 0°02' W., on the N. and S. center line of sec. 21.
	Over gently rolling, rugged, broken, and rolling terrain, within the Chinle Valley.
6.05	Leave the Chinle Valley.
40.00	The true point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line, falls in an area surrounded by sandstone cliffs, where it is impracticable to establish a permanent monument. Not monumented.
	From this true point, the point selected for a witness cor. to the center 1/4 sec. cor. of sec. 21, bears N. 67°14' W., 4.55 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.

Subdivision of Section 21,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E
	C 1/4 . S 21
	2021 
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and N. 67° W. of cor.
71.55	Descent into the Chinle Valley.
80.00	The 1/4 sec. cor. of secs. 16 and 21.
<hr/>	
	From the 1/4 sec. cor. of secs. 21 and 22.
	West, on the E. and W. center line of sec. 21.
	Over rolling, rugged, broken, and gently rolling terrain.
40.00	The center 1/4 sec. cor. of sec. 21.
42.65	Descent abruptly into the Chinle Valley.
63.85	Trail road, bears N. 5° E. and S. 5° W.
64.35	Trail road, bears S. 30° E. and N. 30° W.
67.10	Trail road, bears N. 30° E. and S. 30° W.
73.90	Trail road, bears N. 5° E. and S. 5° E.
76.28	Approximate location of underground water line, extending S. 14° E. and N. 14° W.
80.00	The 1/4 sec. cor. of secs. 20 and 21.
<hr/>	
<p>Subdivision of Section 28, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p>	
<hr/>	
	From the 1/4 sec. cor. of secs. 28 and 33.
	N. 0°02' W., on the N. and S. center line of sec. 28.
	Over gently rolling, broken, and rolling terrain, within the Chinle Valley.
0.65	Trail road, bears N. 55° E. and S. 55° W.
1.10	Trail road, bears N. 45° E. and S. 45° W.

**Subdivision of Section 28,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
22.79	Power line, 2 strand, bears S. 35° E. and N. 35° W.
23.33	Power line, 2 strand, bears S. 35° E. and N. 35° W.
34.75	Trail road, bears S. 20° E. and N. 20° W.
37.78	Approximate location of underground water line, extending N. 57° E. and S. 57° W.
38.21	Power line, 2 strand, bears N. 13° E. and S. 13° W.
40.00	Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. T 39 N R 25 E C 1/4 . S 28 2021 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel "T" post alongside and W. of cor. The cor. is located on top of a dirt berm, 5 ft. wide, 2 1/2 ft. high, bears S. 80° E. and N. 70° W.
41.73	A fence enclosing a steel water tank, approximately 12 ft. diam., approximately 50 ft. high, and a block building, approximately 20 x 10 ft., housing a pumping station, chain link, 6 ft. high, with 3 strands of barbed wire on top, extending N. 59° E. and S. 59° W.
42.84	The same chain link fence, extending N. 60° E. and S. 60° W.
43.10	Trail road, bears S. 40° E. and N. 45° W.
46.55	Trail road, bears N. 60° E. and S. 60° W.
50.05	Trail road, bears N. 85° E. and S. 75° W.
61.01	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
64.17	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears S. 28° E. and N. 28° W.
66.63	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.

Subdivision of Section 28,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
72.90	Trail road, bears S. 70° E. and N. 70° W.
75.85	Trail road, bears S. 25° E. and N. 25° W.
80.00	The 1/4 sec. cor. of secs. 21 and 28.
	<hr/>
	From the 1/4 sec. cor. of secs. 27 and 28.
	West, on the E. and W. center line of sec. 28.
	Over gently rolling terrain, within abandoned cultivated fields, and within the Chinle Valley.
0.80	Power line, 2 strand, bears S. 45° E. and N. 45° W.
10.60	Leave the abandoned cultivated fields.
10.75	Trail road, bears S. 15° E. and N. 15° W.
20.45	Trail road, bears S. 35° E. and N. 55° W.
25.50	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
27.27	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears S. 28° E. and N. 28° W.
28.97	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
36.62	Approximate location of underground water line, extending S. 30° E. and N. 30° W.
39.59	Power line, 2 strand, bears N. 13° E. and S. 13° W.
40.00	The center 1/4 sec. cor. of sec. 28.
44.00	Trail road, bears S. 5° E. and N. 5° W.
51.26	Approximate location of underground water line, extending S. 35° E. and N. 35° W.
52.14	Power line, 2 strand, bears S. 35° E. and N. 35° W.
80.00	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/>

Subdivision of Section 33,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, 3 ins. below blow sand, with brass cap mkd. "T39N R25E 1/4 S33 S4 T38N 2000". Remove blow sand, stainless steel post is projecting 1 in. above ground. Add the marks 2021 to the brass cap.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 33.</p> <p>Over gently rolling and broken terrain, within the Chinle Valley.</p>
2.75	Enter inhabited area.
14.00	Leave inhabited area.
19.03	Navajo Route 8014, a graded road, 24 ft. wide, bears S. 61° E. and N. 61° W.
20.41	Power line, 2 strand, bears S. 43° E. and N. 43° W.
23.40	Enter inhabited area.
26.18	Power line, 2 strand, bears East and West.
31.53	Power line, 2 strand, bears S. 78° E. and N. 78° W.
32.74	Trail road, bears N. 35° E. and S. 35° W.
33.41	Trail road, bears S. 30° E. and N. 30° W.
33.50	Leave inhabited area.
36.00	Trail road, bears N. 20° E. and S. 20° W.
38.60	Left bank of the Chinle Wash flood plain, approximately 2 ft. high, bears N. 50° E. and S. 50° W.
40.00	<p>Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 39 N R 25 E</p> <p style="text-align: center;">C 1/4 . S 33</p> <p style="text-align: center;">2021</p> <p>Deposit a magnet, in a white plastic case, an empty white plastic case, and a bundle of white flagging, at the base of the stainless steel post.</p> <p>Set a steel "T" post alongside and W. of cor.</p>

Subdivision of Section 33,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
50.75	Left bank of the Chinle Wash, approximately 5 ft. high, bears S. 80° E. and N. 70° W.
51.15	Main channel of the Chinle Wash, approximately 30 ft. wide, approximately 5 ft. deep, drains N. 75° W.
52.47	From this point, power line, 2 strand, extending N. 35° E. and S. 45° W., bears East, 11.45 chs. dist.
56.90	Right bank of the Chinle Wash, approximately 5 ft. high, bears S. 70° E. and N. 60° W.
58.00	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 55° E. and N. 55° W.
58.30	Enter inhabited area.
72.00	Leave inhabited area.
73.05	Trail road, bears S. 65° E. and N. 65° W.
77.15	Trail road, bears S. 30° E. and N. 30° W.
80.00	The 1/4 sec. cor. of secs. 28. and 33.
	<hr/>
	From the 1/4 sec. cor. of secs. 33 and 34.
	West, on the E. and W. center line of sec. 33.
	Over gently rolling and broken terrain, within the Chinle Valley.
5.80	Trail road, bears S. 15° E. and N. 15° W.
11.50	Right bank of the Chinle Wash flood plain, approximately 2 ft. high, bears S. 10° E. and N. 20° W.
15.10	Right bank of the Chinle Wash, approximately 5 ft. high, bears S. 10° E. and N. 15° W.
23.30	Main channel of the Chinle Wash, approximately 40 ft. wide, approximately 5 ft. deep, drains N. 15° W.
30.15	Left bank of the Chinle Wash, approximately 5 ft. high, bears S. 65° E. and N. 55° W.
37.10	Power line, 2 strand, bears N. 35° E., and S. 35° W.
40.00	The center 1/4 sec. cor. of sec. 33.
41.55	Left bank of the Chinle Wash flood plain, approximately 2 ft. high, bears N. 45° E. and S. 40° W.
59.00	Trail road, bears S. 65° E. and N. 65° W.

**Subdivision of Section 33,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona**

CHAINS	
70.69	Navajo Route 8014, a graded road, 24 ft. wide, bears S. 30° E. and N. 30° W.
80.00	The 1/4 sec. cor. of secs. 32 and 33.
<hr/> <p>Subdivision of Section 34, T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, 13 ins. below the surface of the ground, with brass cap mkd. "T39N R25E 1/4 S34 S3 T38N 2000". Add the marks 2021 to the brass cap.</p> <p>The cor. is located on an abandoned cultivated field.</p> <p>from which the original reference monuments</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, bears S. 45°06' E., 125.0 ft. dist. (Record: S. 45°00' E., 124.9 ft.) with brass cap mkd. "RM T38N R25E 124.9 FT. TO COR. 1/4 S3 2000" and an arrow pointing to the cor. Add the marks 2021 to the brass cap. The RM is located alongside a woven wire fence, approximately 6 ft. high, bears N. 75° E. and S. 75° W.</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, bears S. 45°00' W., 179.9 ft. dist. (Record: 180.0 ft.) with brass cap mkd. "RM T38N R25E 180.0 FT. TO COR. 1/4 S3 2000" and an arrow pointing to the cor. Add the marks 2021 to the brass cap. The RM is located East, 3.8 lks., from the easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, bears S. 24° E. and N. 24° W.</p> <p>N. 0°02' W., on the N. and S. center line of sec. 34.</p> <p>Over nearly level terrain, within abandoned cultivated fields, and within the Chinle Valley.</p>
18.65	Barbed wire fence, 4 strand, bears N. 50° E. and S. 50° W.
20.17	Barbed wire fence, 4 strand, bears S. 35° E. and N. 35° W.
31.94	Barbed wire fence, 4 strand, bears East and West.
40.00	Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 34,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 39 N R 25 E
	C 1/4 S 34
	2021
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel "T" post alongside and W. of cor. The cor. is located in an abandoned cultivated field.
42.06	Barbed wire fence, 4 strand, bears N. 80° E. and S. 80° W.
70.00	Barbed wire fence, 4 strand, bears N. 58° E. and S. 58° W., leave the abandoned cultivated fields.
70.30	Graded road, 24 ft. wide, bears N. 58° E. and S. 58° W.
74.23	Irrigation canal, approximately 6 ft. wide, approximately 4 ft. deep, bears S. 67° E. and N. 67° W.
80.00	The 1/4 sec. cor. of secs. 27 and 34.
	<hr/>
	From the 1/4 sec. cor. of secs. 34 and 35.
	West, on the E. and W. center line of sec. 34.
	Over nearly level terrain, within the Chinle Valley.
1.25	Graded road, 24 ft. wide, bears S. 10° E. and N. 10° W.
1.80	Enter abandoned cultivated fields, bears S. 10° E. and N. 10° W.
6.88	Power line, 2 strand, bears S. 30° E. and N. 30° W.
40.00	The center 1/4 sec. cor. of sec. 34.
63.40	The easterly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway, leave abandoned cultivated fields.
65.11	The U.S. Highway 191, asphalt surfaced, 26 ft. wide, bears S. 28° E. and N. 28° W.
66.81	The westerly right-of-way fence of U. S. Highway 191, barbed wire, 5 strand, parallels the highway.
75.04	Power line, 2 strand, bears S. 35° E. and N. 35° W.
75.39	Power line, 2 strand, bears S. 35° E. and N. 35° W.
77.85	Trail road, bears N. 5° E. and S. 5° W.

Subdivision of Section 34,
T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS 80.00	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is located within the Navajo Nation and is approximately N. 12° W., approximately 4 1/4 miles from the Rock Point Chapter House, and approximately S. 9° W., approximately 10 miles from the intersection of the U. S. Highway 160 and the U. S. Highway 191.</p> <p>Access to the township is provided by U. S. Highway 191, which runs northerly and southerly through portion of the township, entering in section 34 and running through sections 33, 28, 21, 20, 16, 9 and exiting in section 4. Further access to the township is provided by a series of graded roads including Apache County Roads C484, C487, and Navajo Route 8014, and a series of bladed roads and trails roads. ATV's were required to access the majority of the township.</p> <p>The terrain is predominately rolling, with sandy soil, and scattered sandstone outcropping. Drainage is to the north with the Chinle Wash as the main drainage, along the western portion of the township, entering the township in section 34 and running through sections 33, 29, 28, 20, 17, 18, and exiting in the west boundary of section 7. The elevation ranges from 4900 to 5400 ft. above sea level. There is scattered housing throughout the NE 1/4 of section 3; SW 1/4 of section 4; N 1/2 of section 6; NW 1/4 of section 8; SW 1/4 and NW 1/4 of section 9; N 1/2 of section 14; section 15; NE 1/4 of section 16; SE 1/4 of section 18; NW 1/4 of section 21; section 22; E 1/2 of section 25; S 1/2 and NW 1/4 of section 27; NE 1/4 of section 28; S 1/2 of section 31; SW 1/4 of section 32; NE 1/4 and S 1/2 of section 33; N 1/2 of section 34; and S 1/2 of section 35.</p> <p>The mean magnetic declination of 9 3/4° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2020 for the dates of survey.</p> <hr/>
-----------------	--

CERTIFICATE OF SURVEY

I, Blas J. Urena, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 5th day of April, 2021, I have surveyed of a portion of the south boundary of T. 40 N., R. 26 E., surveyed of the sixth guide meridian east, (west boundary), the east boundary and the subdivisional lines, and the subdivision of certain sections, T. 39 N., R. 25 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

5/17/2022

(Date)

Blas J. Urena

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the survey a portion of the south boundary of T 40 N., R. 26 E., the survey of the sixth guide meridian east, (west boundary), the east boundary and the subdivisional lines, and the subdivision of certain sections, T. 39 N., R. 25 E., Gila and Salt River Meridian, in the State of Arizona, executed by Blas J. Urena, having been critically examined and found correct, are hereby approved.

5/24/2022

(Date)

M. A. Mh

(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 40 N., R. 25 E., T. 40 N., R. 26 E. and T. 39 N., R. 25 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~