## U. S. DEPARTMENT OF AGRICULTURE

FOREST SERVICE

Jan. 3 - 1814

JUL3-1916

DEC 5-1917

# FIELD NOTES

OF

HOMESTEAD ENTRY SURVEY NO. 278

SITUATED IN THE CHIRICAHUA

NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

In Section 7 , unsurveyed, Township 17 5., Range 30 E. In Section 8 , unsurveyed, Township 17 S., Range 30 E. In Section 17 , unsurveyed, Township 17 S., Range 30 E.

of the

Gila and Salt River Base and Meridian.

State of Arizona.

Applicant for listing E. J. Hands,

Residence

Light, Arizona,

7 \*

Application No. 23 V Supp'l. List 3-798, List No. 3-798 List No.

, dated dated , dated

December 8 , 1907 August 15, 1916. November 2, 1910

Applicant for survey Edward J. Hands,

Residence

0

Light, Arizona.

H. E. No. 014891, dated

July 17 , 1911 /

Office Land District

Phoenix, Arizona.

Survey executed by . C. A. Long,

Surveyor, Forest Service. [Forest Service Title.]

Under special instructions dated

October 1, 19 14

Survey commenced

July 16 , 19 15

Survey completed

July 20, 19 15

Under Acts of 8-2349

June 11, 1906 and March 4, 1915.

We hereby certify that we assisted C. A. Long

Surveyor, Forest Service Title.]

in surveying all those

parts or portions of Homestead Entry Survey No. 278 , in the State , which are represented in the following field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the United States Surveyor General for Arizona ...

Note: It would have been very expensive and inconvenient to appear before an officer to administer the oaths to assistants; hence they were taken by the Surveyor.

Subscribed and sworn to before me this

twentieth

July

OATH OF SURVEYOR

I, C. A. Long,

Surveyor, Forest Service [Forest Service Title.]

do solemnly swear that, in strict conformity with the special instructions of the United States Surveyor General for Arizona , dated October 1 , 19 14 , and the laws of the United States, I have well, faithfully, and truly, in my own proper person, surveyed a tract of land embraced in

Supp'l. List 3-798, dated August 15, 1916, and hovember 2, 19 10, for , No. 3-798 List , under the Act of June 11 , 19 06 , Patent the same to be known as Homestead Entry Survey No. 278 National Forest, in Chiricahua situated within the , Range 30 E. , Township 17 S., Township 17 S. unsurveyed Section 7 , Range 30 E. Township 17 S. Township 17 S. unsurveyed Section unsurveyed Section 17

G. & S. R. B. & meridian, Arizona related retracements and resurveys and section subdivisions, which are represented in the following field notes as having been surveyed by me; and I further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the stated special instructions, and in the specific manner described in the field notes, and that the following are the original field notes of such survey.

day of

Subscribed and sworn to before me this

\*\*\*\*\*\*\*

, 19/6.

149

### CHIRICAHUA NATIONAL FOREST

#### STATE OF ARIZONA

Chains Applicant for listing, E. J. Hands; Application No. 23, dated December 8, 1907; List No. 3-798, dated November 2, 1910; H. E. 014891 made in the Phoenix Land Office on July 17, 1911 by Edward J. Hands.

. Also a strip of land excepted from the original listing was included in this survey, since the exception is no longer required for the protection of Government interests. The area has been opened to entry upon supplemental list 3,798, dated August 15, 1916.

Surveyed under special instructions from the Surveyor General for Arizona, dated October 1, 1914 and designated as Homestead Entry Survey No. 278.

Situated in what will probably be, when surveyed, secs. 7 8, and 17, T. 17 S., R. 30 E., Gila and Salt River Base and Meridian, Chiricahua National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and March 4,1915.

Survey commenced July 16, 1915 and executed with a Buff and Buff transit No. 9699.

I test the adjustments of the transit and make necessary corrections.

The stadia is adjusted to read 1:132.

All measurements were made directly on the slope with a 500 link steel tape and the slope angles were determined with a clinometer. July 17, 1916.

July 16, 1915.

At cor. H-5 of List No. 1497, and what will be cor. No. 1 of this survey, which is identical with cor. No. 4 of H. E. S. 277, hereinafter described, Lat. 31° 58' N., Long. 109° 18' 30" W., taken from Surveyor General's special instructions, and later verified, I clamp the horizontal limb at zero and with telescope direct, I sight to an old snag about 30 chs. dist. and at 6h. 30.4m.

#### STATE OF ARIZONA

Chains

is no

-Telur

p.m. l.m.t., I unclamp the upper motion and turn to the E. until the vertical hair bisects Polaris. The resulting angle between Polaris and reference mark, is 25° 29'. Greenwich m.t. U.C. Pol., July 16, 1915. 5h. 57.3m.a.m. Sidereal correction, reexe has to direch. 56.1m.

Astron. 1.m.t. U.C. Pol., July 15, 1915, 17h. 56.lm. Astron. 1.m.t. of obsn., July 15, 1915, 30h. 30.4m. Hour Angle. 12h. 34.3m. 23h. 56.lm. -old warine argument, benego meed and ser ser ·11h. 21.8m.

Azimuth of Polaris at obsn., 180° 12' 42" 25° 291 00" Subtract, Azimuth of reference mark, 154° 43' 42" or a bearing of, N. 25° 16' 18" W.

At 6h. 35.6m. p.m., l.m.t., I again observe Polaris as above described, with telescope reversed. The resulting angle between reference mark and Polaris is 25° 31'

Astron. 1.m.t. U.C. Pol., July 15, 1915, Astron. 1.m.t. of obsn., July 15, 1915, 17h. 56.1m. 30h. 35.6m. 12h. 39.5m. Hour Angle, enst to stea eff rebne 23h. 56.1m. 11h. 16.6m. Time Argument.

Azimuth of Polaris at obsn., 180° 14' 30"

Subtract, 25° 31' 00"

Azimuth of reference mark, 154° 43' 30"

or a bearing of, N. 25° 16' 30" W.

The mean of which is N. 25° 16' 24" W., and to the corresponding meridian all the courses of this survey are Deer of between at athere our .SEI:I referred.

measurements were made direct

. rejemonijo g ojiw benim

July 16, 1915.

#### BOUNDARIES OF CLAIM

July 17, 1915.

#### TRACT A.

-TO

Beginning at cor. No. 1.

Identical with beginning cor. of the list survey, which was cor. H-5 of List 1497, a limestone 6 x 8 x 16 ins. above ground, marked and witnessed as described by the Forest Service. I destroyed all trace of the List cor. in connection with the survey of H. E. S. 277. At this point I previously established cor. No. 4 of H. E. S.

151

#### CHIRICAHUA NATIONAL FOREST

#### STATE OF ARIZONA

Chains

277, which is a porphyry stone 5 x 14 x 10 ins. above ground, chiseled cross (+) for the point and 4 - H E S 277 on NW. face; with a mound of stone 4 ft. base, 3 ft. high NW. of cor. I chisel same stone 1 - H E S 278 on E. face for cor. No. 1 of this survey, and raise a mound of stone 4 ft. base, 3 ft. high E. of cor., whence:

A nail in a white oak, 14 ins. dia., bears
S. 40° 51' E., 63 lks. dist.

A nail in a white oak, 20 ins. dia., bears
N. 58° 02' E., 71 lks. dist.

Each blazed and scribed 1 H E S 278 B T.

The 1/4 sec. cor. on E. bdy. of sec. 12,

T. 17 S., Rs. 29 and 30 E., which is a lime
stone 6 x 8 x 8 ins. above ground, firmly

set and marked 1/4 on W. face, with a mound

of stone West of cor., bears N. 81° 38' W.,

78.43 chs. dist., by traverse which appears

at the end of these notes.

Note: This 1/4 sec. cor. was evidently restored by the

U. S. G. S. when this Forest boundary was established

in 1906 as the original description furnished by the

Surveyor General calls for a wooden post.

The observed magnetic declination at 7h. 00m. a.m., is

14° 15' E., which corrected for dirunal change gives
a mean magnetic variation of 14° 11' E.

Lat. 31° 58' N., Long. 109° 18' 30" W., from special instructions of the Surveyor General and later verified.

Thence N. 0° 40' W.

Along line 4-3 of H. E. S. 277. Over open level bottom land.

0.08 Cor. of wire fence, from which fences bear N. 0° 40' W. and N. 54° 20' W. Thence along W. side of fence.

3.17 Wire fence bears E. and W.

#### STATE OF ARIZONA

Chains

Deposit a limestone 2 x 2 x 3 ins. marked with a +, 14 ins. in the ground, over which set a limestone 7 x 16 x 24 ins., chiseled cross for the point and 2 - H E S 278 on SE. face; raise a mound of stone 4 ft. base, 3 ft. high, SE. of cor., whence:

A nail in a black oak, 6 ins. dia., bears

A nail in a juniper, 8 ins. dia., bears
. S. 76° 30' E., 46 lks. dist.

Each blazed and scribed 2 H M S 278 B T.

- Cor. No. 3 of H. E. S. 277, a granite stone
- at the point and 3 H & S 277 on the SW.
- face, with mound of stone 4 ft. base, 3 ft.

  high, SW. of cor., bears N. 0° 40' W., 15.68

  chs. dist.

Thence S. 57° 11' E. event to be ent ta

Along 5W. side of road exception over level bottom land through dense undergrowth, oak and juniper timber.

- 0.50 Wire fence around yard bears E. and W. Thence across yard.
- 3.20 Wire fence around yard bears N. and S. Leave yard.

78.45 chs. dist., by traverse which appears

- 15.20 Wire fence bears N. and S.
- 15.24 To cor. No. 3.

Deposit a limestone 2 x 3 x 3 ins. marked with a +, 14

ins. in the ground, over which set a limestone 6 x 14 x

24 ins., chiseled cross for the point and 3 - H = 5 278

on W. face; raise a mound of stone 4 ft. base, 3 ft.

high W. of cor., whence:

a mean magnetic variation of 14°

. A nail in a white oak, 14 ins. dia., bears

A nail in a juniper, 5 ins. dia., bears

S. 54° 13' W., 25 lks. dist.

#### STATE OF ARIZONA

Chains

Each blazed and scribed 3 H E S 278 B T

Thence S. O° 15' W.

Over level bottom land through dense undergrowth, oak, denticel with cor. H-4 of and juniper trees

- porphyry stone 6 x Wire fence bears NW. and SE. 0.07
- Dim road bears NW. and SE. 0.60
- To cor. No. 4. 1.58

Identical with cor. H-3 of the list survey which is a rhyolite stone 5 x 16 x 18 ins. above ground marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. Deposit a porphyry stone 2 x 2 x 3 ins. marked with a cross 17 ins. in the ground over which set a schist stone 7 x 12 x 27 ins. chiseled cross for the point and 4 - H E S 278 on W.face raise a mound of stone 4 ft. base, 3 ft. high, W. of cor. whence

A nail in a white oak 14 ins. dia. bears N. 81° 26' W., 47 lks. dist.

A nail in a white oak 28 ins. dia. bears

N. 46° 55' E., 24 lks. dist.

Each blazed and scribed 4 H E S 278 B T

July 17, 1915. steep secent, thence over graduel ascent to cor.

To cor. No. 6.

etone I x 5 x 4 ins.

July 19, 1915.

Thence S. 29° 20' E.

Over level bottom land through dense undergrowth oak juniper and sycamore timber.

- 3.50 S. Fork of Pinery Creek. 25 1ks. wide, course NW.
- S. Fork of Pinery Creek, 25 lks. wide, course N. 7.50
- 13.75 Dim road bears N. and S.
- Enter bed of S. Fork of Pinery Creek. 18.00
- Leave bed of S. Fork of Pinery Creek. 21.20
- S. Fork of Pinery Creek, 20 lks. wide, course NW. 31.00

8 ft, base, 34 ft. high, N. of cor. whence

#### STATE OF ARIZONA

		DIWIT	OT	ANLAUN

Chains 51.25

.6.

S. Fork Pinery Creek, 20 lks. wide, course N. 10° 00' W.

54.50

S. Fork Pinery Creek, 20 lks. wide, course N. 70° 00' W.

56.16

To cor. No. 5.

Identical with cor. H-4 of the list survey which is a porphyry stone 6 x 12 x 20 ins. above ground marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. Deposit a sandstone 2 x 3 x 4 ins. marked with a cross 16 ins. in the ground over which set a limestone 12 x 12 x 26 ins. chiseled cross for the point and 5 - H E S 278 on W. face; raise a mound of stone 4 ft. base, 3 ft. high, W. of cor. whence

A nail in a sycamore 12 ins. dia. bears
N. 41° 50' E., 27 lks. dist.

A nail in a white oak 14 ins. dia. bears
N. 83° 20' W., 74 lks. dist.

Each blazed and scribed 5 H E S 278 B T

Thence S. 48° Ol W.

Ascend 95 ft. to cor. through dense undergrowth along

NW. side of wire fence, 5 lks. dist.

1.60 Dim wood road bears NW. and SE.

Top of steep ascent, thence over gradual ascent to cor.

July 19, 1915.

11.00 Enter cleared land.

14.94 To cor. No. 6.

2.75

Identical with cor. H-5 of the list survey which is a quartzite stone 6 x 8 x 16 ins. above ground marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. Deposit a lime-stone 1 x 3 x 4 ins. marked with a cross 12 ins. in the ground over which set a sandstone 7 x 14 x 20 ins. (no longer stone available) chiseled cross for the cor. and 6 - H E S 278 on N. face; raise a mound of stone 3 ft. base,  $3\frac{1}{2}$  ft. high, N. of cor. whence

#### STATE OF ARIZONA

Chains

A nail in a blackjack pine 10 ins. dia. bears S. 82° 05' E., 46 lks. dist. A nail in a blackjack pine 6 ins. dia. bears N. 30° 40' W., 104 lks. dist. Each blazed and scribed 6 H E S 278 B T

Thence N. 29° 27' W.

Descend 70 ft. to cor. over rolling land along edge of clearing and along NE. side of wire fence 5 lks. dist. which bears with line.

4.00 Leave edge of clearing bearing NE. Enter dense oak brush. 9.25

Arroyo 25 lks. wide, 10 ft. deep, course N. 30° 00' E. Arroyo 50 lks. wide, 10 ft. deep, course NE. 18.00

20.00 Arroyo 100 lks. wide, 30 ft. deep, course NE.

29.98 Cor. wire fence, fence bears N. and SE. along line.

30.02 To cor. No. 7.

> Identical with cor. H-6 of the list survey which is a quartzite stone 5 x 6 x 14 ins. above ground marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. Deposit a limestone 2 x 3 x 4 ins. marked with a cross 12 ins. in the ground over which set a limestone 10 x 12 x 20 ins. (No longer stone available) chiseled cross for the point and 7 - H E S 278 on E. face; raise a mound of stone 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor. from which

A nail in a black oak 16 ins. dia. bears N. 28° 30' E., 17 lks. dist.

A nail in a juniper 6 ins. dia. bears S. 62° 00' E., 29 lks. dist.

Each blazed and scribed 7 H E S 278 B T

It was impracticable to place mound inside Thence N. 48° 32' E. E. WE exsed exact exist

.arer

Ascend 6 ft. through dense oak brush and oak timber.

00.8

#### STATE OF ARIZONA

1	
Chains 0.05	Wire fence bears N. and S. Thence along S. side of
0.00	wire fence 10 lks. dist.
1.25	Mon of ascent, and descend 60 ft. to cor.
7.50	Wire fence bears N. 49° 00! E. and S. 49° 00' W. thence
7.50	along N. side of fence.
70 80	
10.70	Identical with cor. H-7 of the list survey which is
ege	a red anderite stone 5 x 12 x 18 ins. above ground
. and	
	vice. I destroy all trace of this list cor. Deposit
Housed a	En Askas water com one thad one rants to agon grass will be
.0	a porphyry stone 1 x 3 x 5 ins. marked with a cross
	15 ins. in the ground over which set a porphyry
	stone 6 x 10 x 25 ins. chiseled cross for the point
	and 8 - H E S 278 on E. Tace; raise a mound of stone
	4 ft. base, 3 ft. high, E. of cor. whence
aei	A nail in a black cak 6 ins. dia. bears
ber	N. 40° 55' E., 14 lks. dist.
1	A nail in a blackjack pine 12 ins. dia. bears
- enti	S. 52° 45' E., 26 lks. dist.
ai	Each blazed and scribed 8 H E S 278 B T
08	x 21 2 Of enoteentl a sea delaw leve boung ent
To	Thence N. 34° 51' W.
Bruo:	Descend 120 ft. along NE. slope through dense under
	growth, oak, juniper, and sycamore timber.
0.60	which
	side of wire fence 5 lks. dist.
3.00	Wire fence bears N. 34° W. and S. 34° E.
25.50	
35.25	- WAA - 1 / 17/0 TA
36.00	A ASSE
36.40	
min	and the same will one of the
36.50	Wire fence bears NW. and Sh. 198 98 .W. ashed?

.9.

# CHIRICAHUA NATIONAL FOREST STATE OF ARIZONA

Chains

July 20, 1915, at al promeeye s at lish A

Tract B. . Jaid . ext GS .. . 183 877 .8 Beginning at point for cor. No. 9

On line 4-3 of H.E.S. 277, deposit a limestone 1 x 3 x 5 ins. marked with a cross 17 in. in the ground over which set a porphyry stone 4 x .8 x .27 ins. chiseled cross for the point and 9 - H E S 278 on NE. face; and raise a mound of stone 4 ft. base, 3 ft. high, NE. of car. whence 10.9 ... 101 00 .0 sreed

A nail in a white oak 18 ins. dia. bears S. 13° 30' E., 75 lks. dist.

A nail in a white oak 24 ins. dia. bears

N. 87° 10' E., 133 lks. dist.

Each blazed and scribed 9 H E S 278 B T

Cor. No. 2 bears S. 0° 40' E., 55 lks. dist.

Cor. No. 3 H.E.S. 277 heretofore described bears

N. 0° 40' W., 15.13 chs. dist.

Cor. No. 4. H.E.S. 277 heretofore described bears bind beatsm bad S. 0° 40' E., 3.84 chs. 31 saddlemin

- 85 I Thence N. 0° 40' W., of Deciroses as Descentive

Over level bottom land, along line 4-3 of H.E.S. 277

0.04 . Wire fence bears E. and W. Enter alfalfa field. 1.94

Wire fence bears E. and W. Leave alfalfa field. Enter scattering sycamore timber.

2.17 To cor. No. 10. to basem a eafar ; soul . do Identical with cor. H-1 of the list survey which is a rhyolite stone 7 x 7 x 15 ins. above ground marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. Deposit a limestone 2 x 2 x 5 ins. marked with a cross 14 ins. in the ground over which set a sandstone 7 x 16 x 24 ins. chiseled cross for the point and 10 - H E S 278 on SE. face; raise a mound of stone 4 ft. base, 3 ft. high, SE. of cor. whence

# CHIRICAHUA NATIONAL FOREST STATE OF ARIZONA

Chains

A nail in a sycamore 16 ins. dia. bears 

A nail in a juniper 24 ins. dia. bears

Z z enorganii N. 33° 50° E., 160 lks. dist. enii no

Each blazed and scribed 10 H E S 278 B T

Delegation, and Cor. No. 3 of H.E.S. 277 heretofore described

bears N. 0° 40' W., 12.96 chs. dist.

. Cor. No. 4 of H.E.S. 277 heretofore described bears S. 0° 40' E., 6.01 chs. dist. . sib . eni 81 nao etinw a ni lisa A

Thence East. wib . and 57 . a 108 °81 Over level bottom land, through dense undergrowth juniper, and oak timber. Along N. side of wire fence.

Road bears NE. and SW. on bas besseld nosal 9.65

Ascend 10 ft. to cor. . a stand S .OM .TOO 10.00

11.75

To cor. No. 11. and SI. 31, . 100 00 . H Identical with cor. H-2 of the list survey which is a limestone 12 x 17 x 17 ins. above ground marked and witnessed as described by the Forest Service. I de-. . . stroy all trace of this list cor. Deposit a porphyry . stone 2 x 3 x 4 ins. marked with a cross 16 ins. in . the ground over which set a porphyry stone 6 x 8 x 26 ins. chiseled cross for the point and 11 - H E S 278 on SW. face; raise a mound of stone 4 ft. base, 3 ft. s at sinhigh, SW. of cor. whence . Too hall a factoreal

A nail in a juniper 40 ins. dia. bears .solves S. 5° 47' E., 119 1ks. dist. essentiw

A nail in a yellow pine 16 ins. dia. bears

of thi . and S. 82° 50' W., 139 lks. dist. x 3 x 3

. Each blazed and scribed 11 H E S 278 B T

There : seaso" A to boom a salar : sosi.

SE. of cor. whence

# STATE OF ARIZONA

Chains	Thence S. 0° 15' W.
o.t	Ascend 70 ft. over steep NW. slope through dense under-
	growth, oak and juniper timber.
0.90	Fence cor., from which fence bears NW. and S. 0° 30' W.
0.00	Thence along E. side of wire fence.
6.00	Top of divide between N. and S. Forks of Pinery Creek.
	. 20 on Top morr . Tail . and OS. 3
70.44	Descend 75 ft. to cor. over steep SW. slope.
10.44	To cor. No. 12.
	Deposit a sandstone 1 x 2 x 3 ins. marked with a +, 14
	ins. in the ground, over which set a porphyry stone 8
07	x 12 x 24 ins., chiseled cross for the point and 12 -
	HES 278 on NW. face; raise a mound of stone 4 ft. base
	3 ft. high, NW. of cor., whence:
	A nail in a black oak, 6 ins. dia., bears
	N. 47° 28' E. 32 lks. dist.
00	A nail in a juniper, 4 ins. dia., bears
sides	N. 68° 05' W., 40 lks. dist.
	Each blazed and scribed 12 H E S 278 B T.
	Cor. No. 3, heretofore described, bears
	S. 0° 15' W., 54 lks. dist.
	and sail of the bodard to softm own though
O(	Thence -N. 57°-11'-W 00 58
00	. Along NE. side of road exception, through dense under-
•	growth, oak and juniper timber, over level bottom land.
12.00	Wire fence bears N. and S. Enter yard.
12.75	Wire fence bears E. and W. Leave yard.
	o cor. No. 9, the place of beginning.
elfe.	Con an inverse thank of balance Class are a principal
	need evan seres of thook seldstesev bus mist
	area of fract A
	Area of Tract B 8.11 acres
	Total Area 73.68 acres
The state of the s	disted Area 71.59 acres
eau oi	Inlisted Area 2011 2 - 1 - 2.09 acres
redew A	lotal Area 73.68 acres
	for stock is citained from deeps along for theery Gr

#### HOMESTEAD ENTRY SURVEY NO. 278

#### CHIRICAHUA NATIONAL FOREST

#### STATE OF ARIZONA

#### Chains

#### IMPROVEMENTS

The improvements made upon this claim and belonging to the claimant herein, consist of the following:

A tarred felt house, 24 x 28 ft., course of long sides E. and W., the SE. cor. of which bears N. 28° 45' E., 2.20 chs. dist. from cor. No. 1.

Value ----- \$300.00

A windmill over a dug well, 25 ft. deep, the center of which bears N. 1° 06' W., 3.89 chs. dist. from cor.

No. 1. This well is on H. E. S. 277.

Value ----- \$250.00

A red wood tank, 9 ft. high, 10 ft. dia., the center of which bears N. 5° 25' E., 3.05 chs. dist. from cor. No. 1.

A frame chicken house, 8 x 10 ft., course of long sides

E. and W., the NW. cor. of which bears S. 66° 31' E.,

65 lks. dist. from cor. No. 1.

Value ----- \$ 25.00

About two miles of barbed wire fencing.

Value ----- \$200.00

Total value of improvements ----- \$925.00

#### . BILL TO DESCRIPTION . BYREE CONDICTIVE OD. SI

This claim is located along the narrow valley of the S.

Fork of Pinery Creek. The soil is a light sandy loam

first rate, and well suited to fruit growing, alfalfa,

grain and vegetables. About 15 acres have been

cleared of brush and timber and put in cultivation.

The uncleared portion is covered with a dense growth

of oak brush, oak, juniper and sycamore timber; about

75% of the area can be farmed. Water for domestic use

is obtained from a dug well about 25 ft. deep, and water

for stock is obtained from seeps along Pinery Creek.

13.

#### CHIRICAHUA NATIONAL FOREST

#### STATE OF ARIZONA

Chains

Light is the nearest postoffice and trading place. It is about 16 miles in a SW. direction, and is reached by a fair wagon road.

Conflicts and Adjoining Claims.

There are no conflicts. H. E. S. 277 Frank Hands, claimant, joins this claim on the west, lines 1-2 and 9-10 of this claim being on line 4-3 of H. E. S. 277.

	Traver	SAS.			
Tract A.	110101				
	Dist.	N.	S.	E.	W.
2-3 S. 57° 11' E. 3-4 S. 0° 15' W. 4-5 S. 29° 20' E. 5-6 S. 48° 01' W. 6-7 N. 29° 27' W. 7-8 N. 48° 32' E. 8-1 N. 34° 51' W.	3.29 15.24 1.58 56.16 14.94 30.02 10.70 39.26 71.19	26.14 7.09 32.22 68.74		27.51	11.11
Tract B. Course	Dist.	N.	s.	E.	W.
10-11 East 11-12 S. 0° 15' W. 12-9 N. 57° 11' W.	2.17 12.90 10.44 15.25 40.76	2.17  8.26  10.43	10.44 10.44 10.43 .01	12.90 12.90 12.90 00	.C3 .05 12.82 12.90

Traverse for Tie from Cor. No. 1 to 1/4 bet. secs.

			, am	Tr.		
Course		Dist.	N.	S.	E.	W.
N. 54° 20	· W.	8.15	4.75			6.62V
N. 85° 06	' W.	30.00	2.56			29.89
S. 88° 20	· W.	41.10		1.19/		41.08
North		5.30	5.30			
			12.61	1.19		77.59
	-	1000	1.19			
N. 81º 3	81 11.	78-43	11.42			

Survey completed July 20, 1915.

Surveyor Forest Service.

### HOMESTEAD ENTRY SURVEY NO.

## NATIONAL FOREST

STATE OF THE HO SHATE

	or-6 P	ne S-f	Trepl	E. S. E?	s. R.	d all	lhop			
	or-6 P	ne S-f	Trepl	E. S. 27	s. R.	d all	lhop			
	or-6 P	me S-f		.deswed.	im on t					
								eni	TO PART	
		8. 877	.H .E	to 5-4 e						Ins
A					HIE NO	ante	d mi	cla	einj	10
A	183			.ess	Teveri					tost?
		. 8	.8	.H	.delu	•				.000
	10.			88.6	99.0				• 11	1-8
	10.	IB.SI	83.8		48.6I 88.E	.II.		57°	. 0	2-2
		18.51	0.8 . 84		56.15		108	966	.8	4-5
	11.11		66.6	26.14	16.94		170			8-8
		80.8		90.7	TO.VE		198		. 103	9-8-5
	24.38		OR 05	88.88	88.98			54.0		· 1-8
	48.08	40.04	68.79	21.00	61.141					
			60.74							Error
						60%		TOTAL		deofo
									.8	descri
	• 17	•			.jalC					.100
	BD.	00.81		8.17	2.17			°O ts	· VI	11-0
	a0.	14 14 14 14 14 14 14 14 14 14 14 14 14 1	10.44		10.44	. W	*8.5	00	. 0	81-1
	12.96	09.83	10.44	9.86 10.48	15.85	• 1	144	976	• 4	8-9
		00.81	10.43							t Tota
						9	404:	LTO		gnieol
	secs.	. bod a		or. No.	from O	piq			ever!	
		.W	.2	8.	7 snd 7				ear	
		\$30.0			4.75		30.0	• 11	108	°88.
		80.1		1.19	000		41.1	. 19	108	°88.
					08.8		S.G.			nitt
		69.1		1.1	8.61					
					1.19	Ī. S	1.87	+ 1	183	-10 ·
					o, isi	ly 2	ar þ	isto		Yaali
		. estvae								

20/1311.33 20/162.24 S. AREAS. DIRECTIONS.—1. Carry out calculation to two decimals only.

2. In balancing Latitud and Departures do not obliterate or change the original figures.

Put the corrected figures above in red ink. Do not change the footing of the original figures, but put below them the corrected figures above in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner. 261.76 725.50 2129,10 106.52 1141.77 04 N. AREAS. Arizona DOUBLE M. D. 04 53.12 25.61 36.98 43,66 12.81 69.53 22.51 12.90 03 12,88 25.75 STATE OF 04 22,43 14.76 35 0 48,35 03 12.82 12.90 05 WEST. DEPARTURES. 278 35 12.90 12.90 8 12.81 2 48.34 EAST. 27 NO TABLING AND CALCULATIONS OF HOMESTEAD ENTRY SURVEY Closing error 1:3363 Closing error 1:4076 8.26 1.58 48.96 68.79 10,44 10.44 SOUTH. 0 LATITUDES. 8.26 2.17 29 10.43 7.09 26.14 32.22 68.74 NORTH. 53 DISTANCE 3.29 1.58 30.08 15.24 56,16 39.86 171.19 14.94 10.70 2.17 40.76 12.90 15.25 10.44 田 570 11 臣 田 W M 401 110 275 BEARING. 00 15 290 201 51 401 325 15: ô 290 480 480 340 00 ° East N. Form 85. Sheet Mo. 3.—Revised Feb., 1915. Treet A. Tract B CORNERS.

acres

65.57

3440,43 2129.10

40,46 105,68

2599.69 694.60 8.11acres

106.59

268.83

268.83

#### APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, June 14 , 1917.

The foregoing field notes of Homestead Entry Survey No.

278

executed by C. A. Long, Surveyor Forest Service

[Forest Service Title.]

under his special instructions, dated October 1 , 1914, having

been critically examined, and the necessary corrections and explanations

made, the said field notes, and the surveys they describe, are hereby

approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described survey in the State of Arizona , has been correctly copied from the original notes on file in this office.

Frank P. Trott

U. S. Surveyor General.