U. S. DEPARTMENT OF AGRICULTURE

FOREST SERVICE

FIELD NOTES

HOMESTEAD ENTRY SURVEY NO. 353

SITUATED IN THE PRESCOTT NATIONAL FOREST

hinn , 4 1 8

ADMINISTRATIVE DISTRICT NO. 3

In Section 18 , unsurveyed, Township 18 N. Range 4 W.

of the

Gila and Salt River Base and Meridian.

State of

ARIZONA

Applicant for listing Joseph A. Harris,

Residence

Simmons, Arizona.

Application No. 178 , dated

May 23

, 19 13

List No. 3-2718

, dated

August 7

, 19 13

Applicant for survey Joseph A. Harris,

Residence

Simmons, Arizona.

H. E. No. 024670 , dated

April 25

, 1914

Office Land District

Phoenix, Arizona.

Survey executed by Charles D. Hodson, Surveyor - Draftsman

Under special instructions dated

April 20

, 1915 V

Survey commenced

July 27

, 1915

Survey completed

July 28

, 1915

Under Acts of June 11, 1906 and March 4, 1915

OATH OF ASSISTANTS

We hereby certify that we assisted

Surveyor - Draftsman

[Forest Service Title.]

Charles D. Hodson,

in surveying all those

parts or portions of Homestead Entry Survey No. 353 , in the State of Arizona , which are represented in the following field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the United States Surveyor General for Arizona.

Note: It would have been very expensive and inconvenient to appear before an officer to administer oaths to Assistants; hence, they were taken by the Surveyor.

les	Bacc	ht,	Chainma	n
D		nois	1	

Subscribed and sworn to before me this

28th

day of

July

, 19 15 .

was hiroanoa

Surveyor - Draftsman

OATH OF SURVEYOR

I. Charles D. Hodson,

Surveyor - Draftsman

[Forest Service Title.]

do solemnly swear that, in strict conformity with the special instructions of the United States Surveyor General for Arizona, dated April 20, 1915, and the laws of the United States, I have well, faithfully, and truly, in my own proper person, surveyed a tract of land embraced in

List , No.3-2718 , dated August 7 , 1913 , for Patent , under the Act of June 11 , 1906 , the same to be known as Homestead Entry Survey No. 353 , situated within the PRESCOTT National Forest, in unsurveyed Section 18 , Township 18 N. , Range 4 W. / , and -surveyed Section - - - , Township - - - - , Range - - - - ,

of the **G. and S. R. B. and** meridian, **Arizona**, and the related retracements and resurveys and section subdivisions, which are represented in the following field notes as having been surveyed by me; and I further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the stated special instructions, and in the specific manner described in the field notes, and that the following are the original field notes of such survey.

Charles DHodson

Surveyor - Draftsman

[Forest Service Title.]

Subscribed and sworn to before me this

ight

day of

, 19 / .

in Chang tublic

My Commission empires April 20, 1918

STATE OF ARIZONA

Chains

Applicant for listing, Joseph A. Harris, Application No. 178, dated May 23, 1913; List No. 3-2718, dated August 7. 1913: H. E. 024670, made in the Phoenix Land Office on April 25, 1914 by Joseph A. Harris.

Surveyed under special instructions from the Surveyor General for Arizona, dated April 20, 1915 and designated as Homestead Entry Survey No. 353.

Situated in what will probably be, when surveyed, sec. 18. T. 18 N., R. 4 W., Gila and Salt River Base and Meridian, Prescott National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and March 4, 1915. lean of two obens. M. 58° 28' Oll E.

Survey commenced July 27, 1915 and executed with a Buff and Buff transit No. 9700-6, equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary

All distances are horizontal and were reduced from measurements made directly on the slope with a 500 link steel tape. The slope angles were determined with a clinometer.

July 27, 1915.

At 7h. 20m. 09s. p.m., at cor. H-9, near what will be cor. No. 1 of this survey, I observe polaris with telescope direct. The reading on the reference object, a nail in a stump 10.00 chs. from my station, is set at zero. My watch is set for local mean time. Lat. 34° 57' 55" . N. Long. 112° 43' 38" W. from Special instructions from Surveyor General and later verified. Horizontal Angle, Left, ... 37° 43' 30".

> Greenwich m.t. U.C. Pol., July 28, 1915, 5h. 10.3m.a.m. 1.3m. Correction for Long., l.m.t. U.C. Pol., July 28, 1915, 12h. - 7h. 20m. 09s. = 5h. 09.0m. 4h. 39.65m. 9h. 48.65m.

Hour Angle and Time Argument,

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains

Azimuth of Pol. at obsn., 0° 44' 38" E. 100 . 100 . 20 . 1918: Mat No. 2-2718, date

Bearing of reference object, N.38° 28' 08" E.

At 7h. 21m. 12s. p.m., 1.m.t., I again observe Polaris at same station with telescope reversed.

Horizontal Angle, Left, 37° 43' 00"

Ho. 9700-6, comisped with Smith

Greenwich m.t. U.C. Pol., July 28, 1915, 5h. 10.3m.a.m. Correction for Long., 1.3m.

l.m.t. U.C. Pol., July 28, 1915, 5h. 09m. 12h. - 7h. 2lm. 12s. = 4h. 38.8m Hour Angle and Time Argument, 9h. 47.8m.

4h. 38.8m.

Azimuth of Pol. at obsn., 0° 44' 55" E. 37° 43' 00"

Bearing of Reference Object, N. 38° 27' 55" E. Mean of two obsns., N. 38° 28' Ol' E., and from the corresponding meridian all the courses of this survey are deflected.

July 27, 1915.

Takes July 28, 1915. spart and to sthematerine and they

At 7h. 00m. a.m., 1.m.t., I set off 34° 58' N. on the lat. arc, 19° 11' N. on the decl. arc, and determine a meridian with the solar. My line of sight falls 0° 00' 30" to the right of the azimuth determined by obsn. on Pol. with a dlinometer.

RETRACEMENT

At 7h. 30m. a.m., 1.m.t., I set off 34° 58' N. on the lat. arc, 19° 10-1/2' N. on the decl. arc and determine a meridian with the solar at the 1/4 cor. bet. secs. 13 and 18, T. 18 N., Rs. 4 and 5, W., which is a granite stone 8 x 8 x 4 ins. above ground, marked and witnessed as described by the Surveyor General. Thence North tow redel bas levered revevue mout

1.c.t. U.1. 201., July 88, 1915,

Hour Angle and Time Argument,

12h. - 7h. 20m. 09a.

On a random line bet. secs. 13 and 18.

. 40.00 After careful and diligent search . I am unable to find

3.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains any trace of the cor. to secs. 7, 12, 13 and 18.

80.00. After careful and diligent search I am unable to find any trace of the 1/4 sec. cor. bet. secs. 7 and 12.

118.93 Fall 7 lks. W. of the cor. to secs. 1, 6, 7 and 12, a lime-coated malpais stone 10 x 6 x 6 ins. above ground, marked and witnessed as described by the Surveyor General, whence:

A pinon tree, 8 ins. dia., bears N. 59° 30' E.,

175 lks. dist. I mark this tree T 18 N

R 4 W S 6 B T.

A pinon tree, 10 ins. dia., bears S. 76° 08' E.,
79 lks. dist. I mark this tree T 18 N
. R 4 W S 7 B T.

Thence S. O'. 02' W. As a base attempth ; some

On true line bet. secs. 7 and 12.

39.6341/2Thel/4 sec. cor. bet. secs. 7 and 12. Set a granite stone 18 x 10 x 10 ins., 12 ins. in the ground over a small stone marked with a cross. I chisel 1/4 s on the W. face, and raise a mound of stone 2 ft. base, 1-1/2 ft. high, W. of cor. No suitable bearings 'available, pits impracticable.

79.29 The cor. to secs. 7, 12, 13 and 18. Set a granite stone 30 x 12 x 10 ins., 20 ins. in the ground, over a small stone marked with a cross. I chisel 4 grooves on S. face and 2 grooves on N. face, and raise a mound

of stone 3 ft. base, 2 ft. high, W. of cor., whence:

A juniper, 10 ins. dia., blazed and scribed ... T 18 N R 4 W S.7 B T, bears N. 4° 41'. E.,

A pinon, 12 ins. dia., blazed and scribed

T 18 N R 4 W S18 B T, bears S. 83° 40' E.,

114 lks. dist.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains . A juniper, 12 ins. dia., blazed and scribed T 18 N R 5 W S 13 B T, bears S. 43° 33' W., . DAS T . 013 lks. dist. Loss by loss to spart yas

> A pinon, 10 ins. dia., blazed and scribed . T 18 N R 5 W S 12 B T, bears N. 25° 22' W.,

vevus o 87 lks. dist. or bearen w has believe

118.93

The 1/4 sec. cor. bet. secs. 13 and 18, heretofore ... described. od . sib . sal 8 . oout monly

BOUNDARIES OF CLAIM

Beginning at cor. No. . 1. 01, out model

Set a malpais stone 24 x 10 x 8 ins., 14 ins. in the ground, over a small stone marked with a cross. chisel a cross at the point and 1 - H E S 353 on the SE. face; dig pits 24 x 24 x .12 ins. crosswise on line S. and ENE. 7 ft. dist.; and raise a mound of stone covered with earth 5 ft. base, 2-1/2 ft. high SE. of revo fcor., whence: . and Min. . and Of x Of x 81 enote

The cor. to secs. 7, 12, 13 and 18, previously described, bears N. 14° ,11' W., 10.94 chs. dist. entroed by direct measurement. , did . Jr S/1-1

Fence, 5 lks. W. of cor., bears N. 9° 41' E. 79.29 The cor. to seen. 7, 12, .W '14 '9 .2 and s. eranite

cor. H-9 of the list survey, a malpais stone 28 TO x 8 x 8 ins. above ground, marked and witnessed as described by the Forest Service, bears N. 9° 41' E., 4.80 chs. dist.

I destroy all trace of this list cor.

Lat. 34° 57' 55" N., Long. 112° 43' 38" W., obtained

from the special instructions of the Surveyor General. and later verified. Mag. decl. at 12h. QQm. 1.m.t., 14° 50' E. Mean mag.

decl. 14° 52.8' E. T. 8 812 T. A. M. M. M. T.

At 12h., noon apparent time, I set off 19° 07-1/2' N.

STATE OF ARIZONA

Chains

s of on the decl. arc and observe the sun on the meridian. Resultant lat. is 34° 58' N.

Thence N. 73° 24' E.

Over open land with gentle \$. slope.

- 7.15 Wash, 20 lks. wide, 4.ft. deep, course SE.
- 8.60 Irrigation ditch, 4.1ks. wide, 1 ft. deep, course NE.
- 13.26 To cor. No. 2.

boulder 24 x 20 x 6 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of the list cor. and at this point set a limestone 26 x 10 x 6 ins., 16 ins. in the ground, over a small stone marked with a cross. I chisel a cross at the point, and 2.- H E.S 353 on the SW. face; and raise a mound of stone 2 ft. base, 1-1/2 ft. high, SW. of cor., whence:

. ds ib . ext &I

A juniper, 12 ins. dia., blazed and scribed

2 H E S 353 + B T, bears N. 10° 02' E.,

78 lks. dist.

A juniper, 10 ins. dia., blazed and scribed

2.H E S 353 + B T, bears S, 75° 38' E.,

82 lks. dist.

- 4.40 Left bank Walnut Creek, 2 ft. high, course SE.
 - 6.40 Right bank Walnut Creek, 2 ft. high, course SE.
- 14.87 To cor. No. 3. of the day of bed and bed moses as

Identical with cor. H-7. of the list survey, a malpais
stone 10 x 10.x 6 ins, above ground, marked and witnessed as described by the Forest Service. I destroy
all trace of the list cor. and at this point set a

2349

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains malpais stone 24 x 18 x 12 ins., .14 ins. in the ground, over a small stone marked with a cross. I chisel a cross, at the point, and 3 - H E S 353 on the S. face; dig pits 24 x 24 x 12 ins. crosswise on this and the succeeding course, 3-1/2 ft. dist.; and raise a mound of earth 4 ft. base, 2 ft. high, S. of cor., whence:

> A juniper, 12 ins. dia., blazed and scribed ... 3 H E S 353 + B T, bears N. 85° 30; W., 13 lks. dist.

ed to a . . A juniper, 6 ins. dia., blazed and scribed 3 H E S 353 + B T, bears S. 70° 00' E., worded in .es 12901ks.edist.dd wd bedraesb as beseen

Thence N. 55° 32' E.

0.80 Right bank Walnut Creek, 1 ft. high, course SE.

Jaior side Je bas . You Jeil on

- Left bank Walnut Creek, 1 ft. high, course SE. 1.80 . Ma . d MAsc. 25 ft. essa . dr 2 enove to baron s ester
- Irrigation ditch, 4 lks. wide, 1 ft. deep, course SE. 2.50
- Road, bears N. and SE., top of asc., thence over flat topped ridge.
- Edge of ridge, bears N. and S., desc. 15 ft. over 6.40 solope. Detail . . air . air of . Tolling .
- Foot of desc.; thence along foot of SE. slope at edge 12.10
- Wash. 15 lks. wide, 2 ft. deep, course S. 17.70
- Fence cor., fences bear SW. and S. 300 8 900 8 19.15
- 19.22

Identical with cor. H-6 of the list survey, a limestone 12 x 10 x 10 ins. above ground, marked and witnessed as described by the Forest Service. . I destroy all. trace of the list cor. and at this point set a malpais stone 24 x 10 x 10 ins., 14 ins. in the ground, over a small stone marked with a cross. I chisel a cross at the point and 4 - H E S 353 on the SSW. face; and

STATE OF ARIZONA

Chains

raise a mound of stone 2 ft. base, 1-1/2 ft. high, . sull a SSW. of cor., whence: Dro favor to eabo enot

. A juniper, 16 ins. dia., blazed and scribed 4 H E S 353 + B T, bears N. 17° 45' E., ofinal s . vev 71 lks. dist. . A-H . roe ditw Issifuent

- A juniper, 8 ins. dia., blazed and scribed 4 H E S 353 + B T, bears N. 71° 22' W., fee taken 131 lks. dist. of take and to sound the

Thence S. 5° 27' W. W. Berran enote Ifamera

Desc. 15 ft. over S. slope. Fence along line inside

5.00 Foot of desc., wash 20 lks. wide, 2 ft. deep, course E. Right bank Walnut Creek is 30 lks. left, thence parallel to creek bank.

10.74 To cor. No. 5, at cor. fence. Fence bears N. and SSE. halong claim lines. . Ath . 201 A , 1941 May A

,Identical with cor. H-5 of the list survey, a malpais stone 10 x 4 x 12 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of the list cor. and at this point set a malpais stone 24 x 8 x 8 ins., 14 ins. in the ground. over a small stone marked with a cross. I chisel a cross at the point and 5 - H E S 353 on the W. face: and raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.,

A juniper, 16 ins. dia., blazed and scribed 5 H E S 353 + B T, bears N. 18° 39' E., some see 18 lks. dist. one . care a rear of shows

. A juniper, 8 ins. dia., blazed and scribed 5 H E S 353 + B T, bears S. 18° 45' W., , busons and ma .201 lks. .dist. x 21 x 83 anote alegien

HOMESTEAD ENTRY SURVEY NO. 353 PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

Chains

7.43

Thence S. 31° 26' W. and a manual property

Along edge of level cultivated land. Fence on line. To cor. No. 6 at cor. of fence. Fence NNE. and West elong line. . arsed . 2 8 + 668 8 8 8 9

Identical with cor. H-4 of the list survey, a granite stone 10 x 4 x 6 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of the list cor. and at this point set a malpais stone 24 x 8 x 8 ins., 14 ins. in the ground, over a small stone marked with a cross. I chisel a cross at the point and 6 - H E S 353 on the NNW. face; and raise a mound of stone 2 ft. base, 1-1/2 ft. high, . NNW. of cor., whence: Sal OS BEEN .. SEED TO SOUT 90.3

A juniper, 5 ins. dia., blazed and scribed 6 H E S 353 + B T, bears S. 79° 37' W., .222 bus . a 209 lks. distant . Too ds . d . of . Too of AV.OI

A juniper, 4 ins. dia., blazed and scribed olad | 8 . . . 6 H E S 353 + B T, bears S. 65° 05' E., Bas bear 70 .lks. dist. ds .ank SI x A x OI enote

Thence N. 89° 59' W. . 100 Jeil and to spart its

Along S. edge of cultivated field. Fence on line. 5.50 Left bank Walnut Creek, bank 1 ft. high, course SE. 7.00 Right bank Walnut Creek, 1 ft. high, course SE.

Thence over level land. . I so shows to show a

To cor. No. 7 at cor. of fence. Fence bears E. along line and NW. ald . . all of . roginul A

> ·Identical with cor. H-3 of the list survey, a malpais stone 10 x 6 x 8 ins. above ground, marked and witnessed as described by the Forest Service. I destroy · all trace of the list cor. and at this point set a malpais stone 26 x 12 x 6 ins., 16 ins. in the ground, over a small stone marked with a cross. I chisel a

STATE OF ARIZONA

Chains

cross at the point and 7 - H E S 353 on the NE. face; and raise a mound of stone 2 ft. base, 1-1/2 ft. high, Medaut dreek, be NE. of cor., whence:

A juniper, 12 ins. dia., blazed and scribed 7 H E S 353 + B T, bears N. 49° 07' W. 150 lks. dist. 10 . 100 fs 2 . 01 . 100 01 00.31

A juniper, 18 ins. dia., blazed and scribed 7 H E S 353 + B T, bears S. 62° 41' W., 2 4 2 3 aniword 70 lks. dist. wod sisalem a ha beleated

Asc. 15 ft. at foot of ME. slope.

I ft. shove ground, marked and witnessed as described

10.39 To cor. No. 8. ends emes to got no dds 2 1 3 9 +

Set a malpais stone 24 x 12 x 10 ins., 14 ins. in the ground, over a small stone marked with a cross. chisel a cross at the point and 8 - H E S 353 on the N. face; and raise a mound of stone 2 ft. base, 1-1/2 ft. high, N. of cor., whence:

> A juniper, 16 ins. dia., blazed and scribed 8 H E S 353 + B T, bears S. 77° 08' W., 167 lks. dist.

> > A juniper, 8 ins. dia., blazed and scribed 8 H E S 353 + B T, bears S. 5° 25' W., 106 lks. dist. . Waw bas . SVA ersed , beoff 02.0

Thence S. 62° 54' W.

Asc. 20 ft. over NE. slope.

Fence bears SE. and SW. along line. 3.00 Cor. fence. cor. H-2 of the list survey, a malpais stone 8 x 4 x 16 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this

Desc. 25 ft. over W. slope of ridge.

PRESCOTT NATIONAL FOREST

STATE OF ARTZONA

STATE OF ARIZONA					
Chains 3.60	Irrigation ditch, 5 lks. wide, lift. deep, course N.				
3.65	Right bank Walnut Creek, bank 1 ft. high, course N.				
5.10	Left bank Walnut Creek, course N. and proceed over level				
	land, parallel to bank of creek, and along fence.				
16.99	To cor. No. 9 at cor. of fence. Fence bears NE. and				
	NNE. along lines.				
	Identical with cor. H-1 of the list survey, a cross				
	chiseled on a malpais boulder in place showing 6 x 4 x				
Kape Dijamen in Sileman	1 ft. above ground, marked and witnessed as described				
	by the Forest Service. I destroy the marks on stone				
	and witnesses pertaining to the list cor. and chisel				
	+ 9 H E S 353 on top of same stone; and raise a mound				
the	of stone 3 ft. base, 2 ft. high, NE. of cor., whence:				
I	A juniper, 24 ins. dia., blazed and scribed				
the D.	9 H E S 353 + B T, bears S. 9° 50' E.,				
.71 8	1-1 . ess 307 lks. dist.				
,	A juniper, 6 ins. dia., blazed and scribed				
	9 H E S 353 + B T, bears S. 16 ° 04' E.,				
	303 lks. dist.				
	Jow Iks. dat.				
	beautoc bur bessle sin .ani 8 . Touthout A				

Thence N. 9° 41' E. Along fence.

- Road, bears ENE. and WSW. 0.20
- Irrigation ditch, 8 1ks. wide, 1 ft. deep, course 0.40 N. 70° E.
- Asc. 20 ft. over SE. slope of ridge. 5.00
- Irrigation ditch, 5 lks. wide, 1 ft. deep, course NE. 6.20
- Top of ridge, and desc. 15 ft. over N. slope. 8.00
- Foot of slope. Thence over level ground. 12.00
- Fence cor., fences bear N. and S. along line and E. 13.80
- To cor. No. 1, and place of beginning. 15.06

.11.

PRESCOTT NATIONAL FOREST

STATE OF ARIZONA

DESCRIPTION

This claim is situated in the bottom of the canyon formed by Walnut Creek. The soil is a rich sandy loam and produces good crops of corn, alfalfa, beans and potatoes.

Value ----- \$225.00

Water for domestic purposes is obtained from a spring 1/4 mile W. of cor. No. 9.

Water for irrigation and stock purposes is obtained from the creek.

There is a small fringe of juniper timber included on lines 3-4 and 8-9. This timber has no commercial value.

This is not a mineralized section and I saw no indication of mineral on the claim.

PRESCOTT NATIONAL FOREST

	STATE OF	ARIZONA				
Chains	CONFLICTS	AND ADJOINING CI	AIMS	Chains		
sers	There are no conflicts	or adjoining cl	aims. A fator			
manufic are applied to the supplied	H. E. No. 026808, Char	cles L. Alvis, H.	E. S. No. 3	54 un-		
	surveyed, lies appro	eximately 1/2 mil	e NE. of thi	s claim.		
chis	Simmons, the nearest p	ost office, is a	pproximately	18		
	miles in a Southeast	erly direction a	nd is reache	d by		
bns .	fair wagon road.	Prescott, the nes	rest railroa	d and		
. market point, is approximately 45 miles in a Southeast-						
	erly direction and	is reached by 18	miles of fai	r wagon		
,00	and 27 miles of good	automobile road	1.			
	irrigation diven.	y 1-1/2 miles of	Arreckimatel			
Any discrepancy between these field notes and those of						
the listing survey is due to error in the latter.						
00	0.8888	oulsy				
TRAVERSE						
	Course Dist	s DASC N FOLO	E W			
formed	N. 73° 24' E. 13.2	61 3.79 Jantie 8	12.71 sint			
	S. 30° 02' E. 14.8' N. 55° 32' E. 19.2	7 12.87	7.44			
	S. 5° 27' W. 10.74	10.69	1.08			
-sto	S. 31° 26. W. 7.4	3 00 10 20 6.34 0	12.03	1		
	N. 89° 59' W. 12.0	1 0.00	TH. 01			

N. 38° 40' W. S. 62° 54' W. 10.39 8.11 . = 6.49/ gni q N. 9° 41' E. 37.64 38.53

37.62 . 38.51

mora for Error in Lat. and Dep. bas not .02 Tel. 02 Closing error 1:4241. the creek.

no be Survey completed July 28, 1915. If and a si ereal

miner lized section and I saw no indication

lines 5-4 and 8-9. This timber has no commercial .eulsv

Surveyor - Draftsman

Form 85. Sheet No. 3.—Revised Feb., 1915.

DIRECTIONS.—1. Carry out calculation to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

2. In balancing Latitudes above in red ink. Do not change the footing of the original figures, but put below them the corrected figure or figures above in red ink. Do not change the lengths of the lines.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O. 4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, April 30 , 1918

The foregoing field notes of Homestead Entry Survey No.

353

executed by Charles D. Hodson, Surveyor-Draftsman

[Forest Service Title.]

under his special instructions, dated April 20 , 1915 having

been critically examined, and the necessary corrections and explanations

made, the said field notes, and the surveys they describe, are hereby

approved.

U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described survey in the State of Arizona, has been correctly copied from the original notes on file in this office.

Frank P. Trott
U. S. Surveyor General.

-2349