0

ORIGINAL

U. S. DEPARTMENT OF AGRICULTURE

FOREST SERVICE

FIELD NOTES

HOMESTEAD ENTRY SURVEY NO. 548

SITUATED IN THE SITGREAVES NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

In Section 35 , ursurveyed, Township 12 N., Range 17 E.

of the

GILA AND SALT RIVER BASE & Meridian.

State of

ARIZONA

Applicant for listing L. B. Turley

Residence

Heber, Arizona

Application No. 633

, dated

December 20 , 1916

List No.

3-3968

, dated

February 16 , 1917

Applicant for survey Lowell Barr Turley,

Residence

Heber, Arizona.

H. E. No. 035923

, dated August 3 , 19 17

Land Rickinkx Office,

Phoenix. Arizona.

Survey executed by Frank D. Yost, Surveyor - Forest Service, [Forest Service Title.]

Under special instructions dated

February 15, , 19 18.

Survey commenced

July 13 , 19 19

Survey completed

, 19 19. July 15

Under Acts of June 11, 1906, and July 24, , 1919 Over

OATH OF ASSISTANTS

We hereby certify that we assisted Surveyor - Forest Service, [Forest Service Title.]

Frank D. Yost, in surveying all those

parts or portions of Homestead Entry Survey No. 548, in the State of ARIZONA which are represented in the following field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the United States Surveyor General for ARIZONA.

Note: It would have been very expensive and inconvenient to appear before an officer to administer oaths to Assistants; hence, they were taken by the Surveyor.

HE Branchbury
Chairman

H. H. Long Sellow

Chainman

Subscribed and sworn to before me this

Sixth

day of

August , 1919.

Surveyor - Forest Service.

OATH OF SURVEYOR

I, Frank D. Yost, Surveyor - Forest Service, [Forest Service Title.]

do solemnly swear that, in strict conformity with the special instructions of the United States Surveyor General for ARIZONA, dated February 15, 1918, and the laws of the United States, I have well, faithfully, and truly, in my own proper person, surveyed a tract of land embraced in List No. 3-3968, dated February 16, 1917, and a tract of unlisted land upon the application of L. B. Turley,

, dated December 20,1916 , for Application , No. 633 Listing and Patent , under the Act of June 11 , 1906 the same to be known as Homestead Entry Survey No. 548 National Forest, in situated within the SITGREAVES , Township 12 N., Range 17 E., and unsurveyed Section 35 surveyed Section ---, Township --- , Range

of the GILA AND SALT RIVER BASE & meridian, ARIZONA, and the related retracements and resurveys and section subdivisions, which are represented in the following field notes as having been surveyed by me; and I further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the stated special instructions, and in the specific manner described in the field notes, and that the following are the original field notes of such survey.

Surveyor - Forest Service.

[Forest Service Title.]

Subscribed and sworn to before me this

Fifth

day of

November , 1919.

SEAL.

8-2349

Notary Public,

My commission expires March 17, 1921.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Applicant for listing, L. B. Turley; Application No. 633, dated December 20, 1916; List No. 3-3968, dated February 16, 1917; H. E. 035923 made in the Phoenix Land Office on August 3, 1917, by Lowell Barr Turley. Also a tract of unlisted land adjoining claimant's entry was included in this survey; the land is agricultural in character, was desired by entryman and will be listed as a basis for amendment of his entry. This is therefore a composite survey.

Surveyed under special instructions from the Surveyor General for Arizona, dated February 15, 1918, and designated as Homestead Entry Survey No. 548.

Situated in what will probably be when surveyed Sec. 35, T. 12 N., R. 17 E., Gila and Salt River Base and Meridian, Sitgreaves National Forest, Arizona.

Surveyed under the Acts of June 11, 1906 and July 24,

Survey commenced July 13, 1919, and executed with a Buff and Buff transit No. 10019, equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary corrections.

All distances are horizontal, and were reduced from measurements made directly on the slope with a 500 link steel tape. The slope angles were determined with a clinometer.

All courses of this survey were deflected from the meridian established by me at Cor. No. 5 of H.E.S.549 by direct solar obsn. on July 12, 1919, in connection with the survey of H.E.S. 549.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

RETRACEMENTS

July 14, 1919.

From the Cor. of Ts. 11 and 12 N., Rs. 17 and 18 E., a sandstone 8 x 4 x 9 ins. above ground, marked with 6 notches on N., S., E. and W. edges, with mound of stone 3 ft. base, 2 ft. high, N. of cor., whence from cor.:

A yellow pine 12 ins. dia., brs. N. 32° 15' E., 67 lks. dist., blazed and scribed T 12 N R 18 E S 31 B T

A yellow pine 8 ins. dia., brs. S. 58° 30' E., 28 lks. dist., blazed and scribed T. 11 N R 18 E S 6 B T

A yellow pine 8 ins. dia., brs. S. 86° W., 37 lks. dist., blazed and scribed T 11 N. R 17 E S 1 B T

A yellow pine 22 ins. dia., brs. N. 50° W.. 84 lks. dist., blazed and scribed

(Note: This cor. was restored by Forest Service Surveyor R.P.A.Johnson on August 3, 1916, in connection with the survey of H. E. S. 452.)

Thence North,

Retracing line bet. Secs. 31 and 36, S/2.

T 12 N R 17 E S 36 B T

Fall 23 lks. E. of 1/4 Sec. cor. bet. Secs. 31 and 36. a porphyry stone 12 x 4 x 7 ins. above ground. mkd. 1/4 on W. face, with mound of stone West of cor., witnessed as described by the Surveyor General. True line is N. 0° 20' W., 40.04 chs.

Thence North,

Retracing line bet. Secs. 31 and 36, N/2.

40.04

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA.

Chains 41.21

Fall 73 lks. E. of cor. of Secs. 25, 30, 31 and 36, a sandstone 8 x 6 x 8 ins. above ground, marked and witnessed as described by the Surveyor General.

True line is N. 1° 01' W., 41.22 chs.

July 14, 1919.

BOUNDARIES OF CLAIM

July 13, 1919.

Beginning at Cor. No. 1, which is also Cor. No. 3 of H. E. S. 549.

Identical with Cor. H-1 of List 3-3968 and Cor. H-4 of List 3-4023, which is a cobble rock 10 x 7 x 3 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor. Deposit a sandstone 5 x 4 x 2 ins. marked with a + 18 ins. in the ground, on solid rock, over which set an iron post 36 ins. long, 2 ins. dia., with brass cap marked 1919 on S. rim, 1 H E S 548 in SW. quadrant, and 3 H E S 549 in East half, surrounded by a mound of stone 2-1/2 ft. base, 18 ins. high, whence:

A cedar 12 ins. dia., brs. N. 7° 47' E., 575 lks.dist.

A cedar 14 ins. dia., brs. N. 20° 10' W., 422 lks. dist.

Each blazed and scribed 1 H E S 548 - 4 H E S 549 + B T

The 1/4 cor. bet. Secs. 31 and 36, T. 12 N.,

Rs. 17 and 18 E., heretofore described,

brs. S. 81° 16' 40" E., 101.95 chs. dist.

by traverse which appears at the end of

these notes.

Lat. 34° 23' 53" N., Long. 110° 31' 12" W., from special instructions of Surveyor General and later verified.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains	Magnetic declination at 8 a.m. is 14° 30' E. Mean
	Magnetic declination, 14° 26' E.
- 4 3	Thence S. 12° 05' W.
	Along line 3-2 of H. E. S. 549, over level bottom land, fence on line.
12.37	Cor. wire fence, fence bears NW., N. 12° 05' E. and
	S. 12° 05' W. along line. Cultivated land on West.
49.82	Cor. H-5 of the list survey, which is a cobble rock 10 x
1	8 x 6 ins. above ground, marked and witnessed as de-
	scribed by the Forest Service. I destroy all trace of
	this list cor. Cor. of wire fence; fence brs. NW.,
	N. 12° 05' E. and S. 12° 05' W. along line. Leave
	cultivated land on West.
54.23	To Cor. No. 2, which is also Cor. No. 2 of H. E. S. 549.
	Identical with Cor. H-3 of List 3-4023, which is a
	cobble rock 6 x 5 x 4 ins. above ground, marked and
	witnessed as described by the Forest Service. I de-
	stroy all trace of this list cor.
o red - M	Deposit a sandstone 4 x 3 x 2 ins. marked with a + 24
0.1001	ins. in the ground, over which set an iron post 36 ins.
	long, 2 ins. dia., with brass cap marked 1919 on S. rim.
	2 H E S 548 in NW. quadrant and 2 H E S 549 in NE.
	quadrant; raise mounds of stone 3 ft. base, 2 ft. high,
	NW. and NE. of cor., whence:
	A juniper 7 ins. dia., brs. N. 87° 09' E.,
	90 lks. dist.
7	A juniper 12 ins. dia., brs. S. 4° Ol' W., 77 lks. dist.
	Each blazed and scribed 2 H E S 548 - 2 H E S
	549 + B T

Cor. No. 4 of H.E.S. 452, a sandstone 16 x 8 x

10 ins. above ground, marked + on top and

4 H E S 452 on SE. face, with mound of stone

4

-2349

SITGREAVESNATIONAL FOREST

STATE OF ARIZONA

Chains

SE., brs. S. 85° 07' 35" E., 26.84 chs. dist. by traverse, which appears at the end of these notes. .

July 13, 1919.

July 15, 1919. Thence W. 51° 04' W.

Ascend 10 ft., over grassy NE. slope, thru juniper, cedar and oak, over unlisted land.

40.99 To Cor. No. 3.

Deposit a sandstone 3 x 2 x 2 ins. marked with a + 26 ins. in the ground, over which set an iron post 36 ins. long, 2 ins. dia., marked 1919 on S. rim and 3 H E S 548 in portion of circle facing claim; raise a mound of stone 3 ft. base, 2 ft. high, NE. of cor. whence:

.A cedar 8 ins. dia., brs. N. 70° 10' E. 292 lks. dist.

A cedar 4 ins. dia., brs. N. 40° 07' W., 205 1ks. dist. 9000

Each blazed and scribed 5 H E S 548 + B T Cor. H-4 of the list survey, which is a cobble rock 8 x 5 x 2 ins. above ground, marked and witnessed as described by the Forest Service, brs. N. 77° 41' E., 14.07 chs. dist. I destroy all trace of this list cor.

Thence N. 0° 42' W.

Over level grassy land,

3.02

Cor. H-3 of the list survey, which is a cobble rock 9 x 8 x 3 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor.

Leave unlisted and enter listed land.

Cor. wire fence brs. East, 7 lks. dist., fences bear

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

East and North.

27.08

To Cor. No. 4.

Identical with Cor. H-2 of the list survey, which is a cobble rock 8 x 7 x 6 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list cor.

Deposit a sandstone 4 x 2 x 2 ins. marked with a + 24 ins. in the ground, over which set an iron post 36 ins. long, 2 ins. dia., marked 1919 on S. rim and 4 H E S 548 in SE. quadrant; raise a mound of stone 3 ft. base, 2 ft. high, SE. of cor., whence:

A cedar 14 ins. dia., brs. S. 89° 02' E.,

822 lks. dist.

A pine 20 ins. dia., brs. N. 31° 15' E.,

Each blazed and scribed 4. HES 548 * BT Corner of wire fence bears S. 35° 07' E., 68 lks. dist., from which fences bear South and East.

Thence N. 89° 47' E.

Over level grassy land, thru juniper, cedar and oak. To Cor. No. 1, the place of beginning.

43.59

AREA

IMPROVEMENTS

The improvements made upon and for the benefit of this claim and belonging to the claimant herein, consist of the following:

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

A frame house 16 x 16 ft., the long sides extending N. and S., the NE. cor. of which
brs. S. 31° 30' W., 11.91 chs. dist. from
Cor. No. 1.

Value - - - - - - - \$ 200.00

A frame barn 20 x 30 ft., the long sides extending N. 20° E. and S. 20° W., the E. cor. of which bears S. 14° 30' W., 9.17

chs. dist. from Cor. No. 1.

Value - - - - - - - - - \$ 150.00

Approximately 1-3/4 miles of wire fencing,

Value - - - - - - \$ 250.00

An earth dam 6 ft. wide, 3 ft. high, 80 ft. long, extending in a semicircle from SE. to NW., the SE. end of which brs. S. 12°36'W., 12.40 chs. from Cor. No. 1.

Value -- - - - - - - - \$ 50.00

DESCRIPTION

The claim consists mainly of open level land, lying on the West side of a wide shallow draw, which drains North.

The soil is a rich dark loam, generally free from rocks, about 3 ft. deep with a red clay subsoil. Approximately 80 percent of the claim is suitable for agricultural purposes, of which about 60 acres were under cultivation at the time of survey. Dry farming methods are necessary to grow crops. The claimant has endeavored to conserve the surface water in an earth dam for stock watering purposes, but is unable to store enough for the whole year.

Water for domestic use is hauled from Pierce Seeps, which lie about one mile to the West.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA.

Level .. Mark con the

Ċ	ha	ai	n	S
		~~		~

There is no timber of commercial value on the claim.

I saw no indications of mineral on the claim.

CONFLICTS AND ADJOINING CLAIMS

There are no conflicts. H.E.S. 549 adjoins on the East; line 2-3 thereof being identical with line 1-2 of this survey.

H.E.S. No. 452 lies about 1/4 mile distant in a South-easterly direction, and H.E.S. No. 550 lies about 1/4 mile distant in a south-wall direction.

Heber, Arizona, the nearest settlement and postoffice,
·lies about six miles distant in a Northwesterly direc· tion.

*Holbrook, Arizona, the nearest railroad point lies about 50 miles distant in a Northeasterly direction and is reached by fair wagon road.

T	RA	VEL	RS:	ES

00.00

Course	Dist.	N.	S.	E.	W.
S. 12° 05' E. N. 51° 04' W. N. 0° 42! W. N. 89° 47' E.	54.23 40.99 27.08 43.59	25.76 27.08	53.03	43.59	11.35 31.89 .33
Error in Lat.	and Dep.	53.00		43,59 43.57 .02	43.57

Closing Error, 1:4601

TIE FROM COR. NO. 1 TO THE 1/4 COR. BET. SECS. 31 AND 36, T. 12 N. Rs. 17 and 18 E.

ı				re The Ties	Troe TI alla	TO TO		
1	THE R	Course		Dist.	N. I.	S.	E.	W.
-	N.	12° 21'	E.	4.85	4.74		1.04	
	N.	89° 061	E.	20.72	.33	o de la c	20.72	
	N.	84° 331	E.	42.32	4.02		42.13	
	N.	15° 05'	W.	16.430	15.86		La transition	4.28
	S.	66° 471	E.	9.78		3.86	8.99	
	N.	69° 051	E.	15.01	5.36		14.02	
-	N.	80° 481	E.	11.37	1.82		11.22	
	S.	67° 531	E.	6.69	who had the	2.52	6.20	
	S.	1, 01,	E.	41.22		41.21	.73	
-				7 2 12	32.13,	47.59	105.05	4.28
			.,			32.13	4.28	
-	GRY	TOTAL .	14.		L BOW CLUB	15.46	100.77	

Resultant course, S. 81° 16' 40" E., 101.95 chs.

-2349

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

TIE FROM COR. NO. 2 TO COR. NO. 4 OF H. E. S. NO. 452. Chains Course Dist. N. 89° 51' E. 33.55 .09 .09 ... S. 70° 51' W. 7.21 S. E. 33.55 2.37 6.81 .09 6.81 2.37 33.55 2.28 $\frac{6.81}{26.74}$ Resultant course S.85°07'35"E. 26.84 chs.

26.84 chs.
Survey completed July 15,1919.

Surveyor - Forest Service,

8--2319

Form 85. Sheet No. 3.—Revised Feb., 1915.

Directions.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

CORNERS. BEARING.		DISTANCE.	LATI	TUDES.	DEPART	URES.	DOUBLE M.	D. N. AREAS	š.	S. AREA	S.	
			North.	South.	East.	West.						
		TRAVERSE	OF LISTED	And the second control of the second control		-77-6						
	S. 12-05 W.	49.82		48 72		10 43		2		373	7 03	
	N. 37-56 W.	31.00	24 45			19 8	47 2	2 1155	00			
	N. 89-55 W.	13.79	02			13 79	14 3	7	29			
	N. 0-42 W.	24.06	24 06			29	2	9 6	98			
	N. 89-47 E.	43.59	16		43 59		43 5		41			
		162.26	48 69	48 72 48 69	43 59 43 56	43 56		1169	68	3737	03	
			48 71	48 69	43 56	4337				1169		
	Error in	Lat. and De	p. 13827	03	03					20/2567	35	
			3 -1							128	37	Acres.
	Closurge	rior 1/	3827									
				-								
				-								
				-								
				-								
				-								
				-								

Directions.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

TABLING AND CALCULATIONS OF			THE RESIDENCE OF THE PARTY OF T							
CORNERS.	BEARING.	DISTANCE.	LATITU		DEPART		DOUBLE M. D.	N. AREAS.	S. AREAS.	
			North.	South.	EAST.	West.				
1 - 2	S. 12-05 E.	54.23		53 03		11 35	75 80		4018 92	
2 - 3	N. 51-04 W.	40.99	25 76			31 89	32 55	838 81	**	
, 3 - 4	N. 0-42 W.	27.08	27 08		58	33	33	8 94		
4 - 1	N. 89-47 E.	43.59	16		43 59	14 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	43 58	7 41		
		165.89	53 00	53 03 53 002	43 59 43 57	43 57	100 X44 F.	855 16	4018 92	
			53 02	53 00	743 57	4238			855 16	
	Error in La	t. and Dep.		03	02				20/ 3163 76	
									158 19	Acres.
	Closing Err	or, 1:4601								三丁
)

July 15, 1919.

I, Lowell Barr Turley, hereby agree to the survey of my homestead, number 548, as made on 15th day of July, 1919, by Forest Service Surveyor Frank D. Yost, and further agree that when notified that the survey has been approved and before attempting to make final proof on my entry, I will apply for amendment of the same to conform with said survey.

addition o	n the South	and Wast		
		1 alla West	or Agricu	ltural
land, desi	red by me.			

(Sgd.) L.B. Turley,

Claimant.

APPROVAL

Office of the United States Surveyor General,

Phoenix, Arizona, Opril 26, 1920

The foregoing field notes of Homestead Entry Survey No.

548

executed by Frank D. Yost, Lurueyor [Forest Service Title.] under his special instructions, dated February 15, 1918, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General

I certify that the foregoing transcript of the field notes of the above-described survey in the State of Arizona, has been correctly copied from the original notes on file in this office.

FRANK P. TROTT

1-**2**349

U. S. Surveyor General.