#### U. S. DEPARTMENT OF AGRICULTURE

FOREST SERVICE

HOMESTEAD ENTRY SURVEY NO. 594

SITUATED IN THE APACHE . NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3.

In Section 13 , un-surveyed, Township 4N , Range 30 E. In Section 14 , un-surveyed, Township 4N , Range 30 E. and

Establishment of U.S.L.M. No. 594 H.E.S.

of the

GILA AND SALT RIVER BASE AND Meridian.

State of ARIZONA.

Applicant for listing J. A. Townsend,

Residence.

Espero, Arizona

Application No. 338

, dated September 26

, 19 14

List No. 3-3659

, dated September 25

Applicant for survey Jesse L. Burke,

Residence

Espero, Arizona

H. E. No. 035656

, dated July 11

, 19 17.

Land Office Phoenix, Arizona

Survey executed by Thomas F. Myers, Surveyor-Forest Service

[Forest Service Title.]

Under special instructions dated

May 14

.... , 19 19

Survey commenced

June 12

, 19 21 .

Survey completed

June 16

, 19 21

We hereby certify that we assisted Surveyor - Forest Service

Thomas F. Myers,

in surveying all those

[Forest Service Title.]

, in the State parts or portions of Homestead Entry Survey No. 594 which are represented in the following field notes of ARIZONA as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furmished by the United States

Surveyor General for ARIZONA. Note: It would have been very expensive and incomvenient to appear before an officer to administer Oaths to Assistants; hence they were taken by the Surveyor.

Subscribed and sworn to before me this

16th

day of

June

, 19 21

Surveyor - Forest Service.

OATH OF SURVEYOR

Thomas F. Myers,

Surveyor - Forest Service, [Forest Service Title.]

do solemnly swear that, in strict conformity with the special instructions of the United States Surveyor General for ARIZONA , dated May 14 , 1919 , and the laws of the United States, I have well, faithfully, and truly, in my own proper person, surveyed a tract of land embraced in List No. 3-3659, dated September 25, 1915, and a tract of land upon the application of J. A. Townsend.

, dated September 261914 Application , No. 338 June 11 , 19 06 , , under the Act of listing and patent the same to be known as Homestead Entry Survey No. 594 National Forest, in situated within the APACHE , Township 4 N. , Range 30 E. , Township 4 N. , Range 30 E. 13 un-surveyed Section 14 un-surveyed Section

ARIZONA of the GILA AND SALT RIVER BASE & meridian, , and the related retracements and resurveys and section subdivisions, which are represented in the following field notes as having been surveyed by me; and I further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the stated special instructions, and in the specific manner described in the field notes, and that the following are the original field notes of such

> Surveyor - Forest Service. [Ferest Service Title.]

Subscribed and sworn to before me this

fifth

day of

April

. 1922.

Notary Public

Exhel G. m

\*\*\*\* SEAL. STREET, STREET

1112770

My comm. expires April 12, 1925.

1.

#### HOMESTEAD ENTRY SURVEY NO. 594

#### APACHE NATIONAL FOREST

STATE OF Arizona

Chains

Applicant for listing, J. A. Townsend; Application No. 338, dated September 26, 1914; List No. 3-3659, dated September 25, 1915; H. E. 035656, made in the Phoenix Land Office on July 11, 1917, by Jesse L. Burke. Also a tract of unlisted land adjoining claimant's entry was included in this survey. The land is agricultural in character, was desired by entryman and will be listed as a basis for amendment of his entry. This is therefore a composite survey. Surveyed under special instructions from the Surveyor General for Arizona, dated May 14, 1919, and designated as Homestead Entry Survey No. 594. Situated in what will probably be when surveyed Secs. 13 and 14, T. 4 N., R. 30 E., Gila and Salt River Base and Meridian, Apache National Forest, Arizona. Surveyed under the Acts of June 11, 1906, and May 31, 1920.

Survey commenced June 12, 1921, and executed with a Buff and Buff transit No. 10530, equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary corrections.

All distances are horizontal, and were reduced from measurements made directly on the slope with a 500 link steel tape. The slope angles were determined with a clinometer.

All the courses of claim lines of this survey were deflected by sustained angulation from the meridian established by me by Polaris obsn. at Cor. No. 1 of H.E.S. 595 on June 14, 1921, in connection with the

Form 85. Sheet No. 2.

#### APACHE NATIONAL FOREST

#### STATE OF ARIZONA

Chains

survey thereof.

ESTABLISHMENT OF U. S. L. M. 594 H. E. S.

on the first of the contract of

June 12, 1921.

There being no public land corner or U. S. Location

Monument within the prescribed limits to which this

survey could be tied, in accordance with the special
instructions, I establish U.S.L.M. 594 HES. as follows:

On top of a low flat ridge about 3/8 of a mile westerly
from Tutts Gienega, I select an embedded Malpais
boulder showing 55x46x22 ins. above ground. I chisel
this boulder + on top for the point and USLM 594 HES
on NE. face and raise a mound of stone 9 ft. base 7 ft.
high NE. of U.S.L.M., whence:

A pine 20 ins. dia. brs. N. 49°04' E. 16 lks.

A pine 9 ins. dia. brs. S. 81°08' E. 55 lks.

A pine 16 ins. dia. brs. S. 13°12' W. 41 lks.

A pine 19 ins. dia. brs. N. 85°12' W. 38 lks.

Each blazed and scribed USIM 594 HES + BT.

U.S.L.M. 504 HES., a lava bluff 6x6x8 ft.

above ground, marked + USIM 504 HES on top

with mound of stone 11 ft. base 9 ft. high

W. of monument, bears N. 60°36'01" W. 207.09

chains distant by traverse which appears at

the end of these notes.

cor. No. 1 of HES. 597 (established by me on June 12, 1921), a malpais stone 12x8x10 ins above ground, chiseled + on top and 1 HES 597 on SW. face, with mound of stone 2 ft. base 1-1/2 ft. high SW. of Cor., bears S. 47.03'06" W. 38.51 chs. dist. by traverse which appears at the end of these notes.

3. .

#### HOMESTEAD ENTRY SURVEY NO. 594

#### APACHE NATIONAL FOREST

#### STATE OF ARIZONA

Chains

Note: The azimuth of the lines of the traverses for ties in connection with the establishment of U.S.L.M. 594 HES. was brought forward by sustained angulation from the meridian established by me by Polaris observation near Cor. No. 1 of HES. 592 on June 8, 1921.

Rain in afternoon.

June 12, 1921.

June 13, 1921, worked on HES. 597.

June 14, 1921, worked on HES. 595.

June 15, 1921, Rain.

#### BOUNDARIES OF CLAIM

- June 16, 1921.

Beginning at Cor. No. 1.

. Identical with Cor. H/5 of the list survey, which is a malpais stone 12x3x10 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list Cor.

Deposit a malpais stone 6x6x6 ins., marked with a + 16 ins. in the ground, over which set a malpais stone 26x12x6 ins., chiseled.+ for the point and 1 HES 594 on SE. face; raise.a mound of stone 2 ft. base 1-1/2 ft. high SE. of Cor., whence:

A pine 34 ins. dia. brs. N. 53°30' W. 35 lks.

A pine 14 ins. dia. brs. N. 38°00' W. 51 lks.

Each blazed and scribed 1 HES 594 + BT.

U.S.L.M. 594 HES., previously described, bears

N. 56°47'48", 30.37 chs. distant by traverse

which appears at the end of these notes.

8--2349

4.

#### HOMESTEAD ENTRY SURVEY NO. 594

#### APACHE NATIONAL FOREST

#### STATE OF ARIZONA

Chains

Lat. 33°41'05" N., Long. 109°12'40" W. from: Forest Service Base Map.

Mag. decl. at 10:30 a.m. 13°30 E., mean mag. decl.

· Thence N. 56°48' E.

Along NW. edge of meadow through scattering pine.
Fence on line.

18.02

To Cor. No. 2.

Identical with Cor. H/4 of the list survey, which is a malpais stone 8x4x8 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list Cor.

Deposit a malpais stone, 6x5x3 ins., marked with a + 16 ins. in the ground, over which set a malpais stone 24x16x8 ins. chiseled + for the point and 2 HES. 594 on SE. face; raise a mound of stone 2 ft. base 1-1/2 ft. high SE. of Cor., whence:

Cor. No. 1 of HES. 595 (established by me on June 14, 1921), a malpais stone 12x8x10 ins. above ground, marked + on top and 1 HES. 595 on NW. face, with mound of stone 2 ft. base 1-1/2 ft. high NW. of Cor., bears N. 38°57'17"

W. 16.38 chs. dist. by traverse which appears at the end of these notes.

Thence N. 35°26! E.

Along foot of gentle SE. slope, through edge of scattering pine and reproduction.

Fence inside of line.

14.80 Beaver Creek-Blue River Trail, bears E. and W.

15.30 Fence Cor. Fences bear S. 35°30' W. and ESE.

#### APACHE NATIONAL FOREST

#### STATE OF ARIZONA

5. . .

#### Chains 16.42

To Cor. No. 3.

Identical with Cor. H/3 of the list survey, which is a malpais stone 8x3x12 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list Cor.

Deposit a malpais stone 3x5x6 ins., marked with a + 16 ins. in the ground, over which set a malpais stone 26x10x4 ins., chiseled + for the point and 3 HES. 594 on S. face; raise a mound of stone 2 ft. base 1-1/2 ft. high S. of Cor. whence:

A pine 40 ins. dia. brs. N.4°00' W. 90 lks.

A pine 26 ins. dia. brs. N. 73°45' W. 132 lks.

Each blazed and scribed 3 HES 594 + BT.

Thence N. 82°47' E.

Over open land along gentle S. slope.

Fence bears N. and S. Enter scattering pine and reproduction.

25.07 To Cor. No. 4.

3.40

Identical with Cor. H/2 of the list survey, which is a malpais stone 12x3x14 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list Cor.

Deposit a malpais stone 6x4x6 ins. marked with a + 18 ins. in the ground, over which set a malpais stone 28x16x5 ins. chiseled + for the point and 4 HES. 594 on S. face; raise a mound of stone 2 ft. base 1-1/2 ft. high S. of Cor., whence:

A pine 20 ins. dia. brs. S. 53°19'W. 44 lks.

A pine 24 ins. dia. brs. N. 60°37' E. 26 lks.

Each blazed and scribed 4 HES 594 + BT.

--2340

#### STATE OF ARIZONA

_		
The second second	Chains	Thence N. 69°08' E.
		Over unlisted land, along gentle S. slope through
		scattering pine.
The second second	2.40	Beaver Creek-Blue River Trail bears N. 50°E. and S.
The state of the s		50° W.
The second	3.70	Beaver Creek-Blue River Trail bears NW. and SE.
	12.20	Fence bears N. 80° W. and S. 80° E.
	17.43	To Cor. No. 5.
-		Deposit a malpais stone 4x4x7 ins., marked with a +
		14 ins in the ground, over which set a malpais stone
		24x9x5 ins., chiseled + for the point and 5 HES 594 on
	. 27	SW. face; raise a mound of stone 2 ft. base 1-1/2 ft.
-		high SW. of Cor. whence:
		A pine 8 ins. dia. brs. S. 50° W. 31 lks.
The same		A pine 12 ins. dia. brs. S. 80°34' E. 38 1ks.
		Each blazed and scribed 5 HES 594 + BT.
		Each prazed and scriped a mas ear a pre-
		Eggi blazed alu scribed 5 ms 551 , br
	- 1	Thence S. 25°03' E.
		A
	•60	Thence S. 25°03' E.
		Thence S. 25°03' E.  Over rolling land through edge of scattering pine.
		Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along
	.60	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.
	.60 2.85	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,
	.60 2.85	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.
	2.85 4.40	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,  Course E.
	2.85 4.40	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,  Course E.  To Cor. No. 6. At Cor. fence. Fences bear N. 25° W.  and S. 79° W.
	2.85 4.40	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,  Course E.  To Cor. No. 6. At Cor. fence. Fences bear N. 25° W.  and S. 79° W.
	2.85 4.40	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,  Course E.  To Cor. No. 6. At Cor. fence. Fences bear N. 25° W.  and S. 79° W.  Deposit a malpais stone 5x5x8 ins., marked with a + 20
	2.85 4.40	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,  Course E.  To Cor. No. 6. At Cor. fence. Fences bear N. 25° W. and S. 79° W.  Deposit a malpais stone 5x5x8 ins., marked with a + 20 ins. in the ground, over which set a malpais stone
	2.85 4.40	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,  Course E.  To Cor. No. 6. At Cor. fence. Fences bear N. 25° W. and S. 79° W.  Deposit a malpais stone 5x5x8 ins., marked with a + 20 ins. in the ground, over which set a malpais stone  26x12x6 ins., chiseled + for the point and 6 HES 594
	2.85 4.40	Thence S. 25°03' E.  Over rolling land through edge of scattering pine.  Fence Cor. Fences bear N. 80° W. and S. 25° E. along inside of line.  Beaver Creek-Blue River Trail bears E. and W.  Castle Creek (dry) 30 lks. wide, banks 2 ft. high,  Course E.  To Cor. No. 6. At Cor. fence. Fences bear N. 25° W.  and S. 79° W.  Deposit a malpais stone 5x5x8 ins., marked with a + 20 ins. in the ground, over which set a malpais stone  26x12x6 ins., chiseled + for the point and 6 HES 594 on NW. face; raise a mound of stone 3 ft. base 2 ft.

A pine 30 ins. dia. brs. S. 46°10' E. 66 lks.

Each blazed and scribed 6 HES. 594 + BT.

9.-2349

#### STATE OF ARIZONA

Chains

Thence S. 78°53' W.

Over rolling land through scattering pine. Fence inside of line.

21.33

To Cor. No. 7.

Deposit a malpais stone 7x7x6 ins., marked with a + 20 ins. in the ground, over which set a malpais stone 24x15x4 ins., chiseled + for the point and 7 HES 594 on N. face: raise a mound of stone 2 ft. 1-1/2 ft. high N. of Cor., whence:

A pine 38 ins. dia. brs. S. 71° W. 60 lks. A pine 15 ins. dia. brs. N. 56°27' W. 135 lks. Each blazed and scribed 7 HES. 594 + BT. Cor H/1 of the list survey, which is a malpais stone 8x3x8 ins. above ground, marked and witnessed as described by the Forest Service, brs. N. 52°30' W. 1.80 chs. I destroy all trace of this list Cor. Leave unlisted and enter list

Thence N. 85°09' W.

Over gently rolling land through edge of scattering. pine. Fence inside of line.

19.30 To Cor. No. 8.

Identical with Cor. H/8 of the list survey, which is a malpais stone 14x4x12 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list Cor.

Deposit a malpais stone 6x6x4 ins., marked with a + 16 ins. in the ground, over which set a malpais stone 26x14x8 ins. chiseled + for the point and 8 HES 594 on N. face; raise a: mound of stone 2 ft. base 1-1/2 ft. high N. of Cor., whence:

. A pine 36 ins. dia. brs. N. 84°35' W. 53 lks. A pine 36 ins. dia. brs. S. 75°10' W. 45 lks. Each blazed and scribed 8 HES 594 + BT.

Leave unlisted and enter listed land ..

#### STATE OF ARIZONA

Chains

Thence S. 43°14' W.

Through edge of scattering pine and aspen.

17.81

To Cor. No. 9.

Identical with Cor. H/7 of the list survey, which is a malpais stone 8x6x6 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list Cor.

Deposit a malpais stone 3x4x5 ins., marked with a + 14 ins. in the ground, over which set a malpais stone 24x14x8 ins., chiseled + for the point and 9 HES 594 on NW. 'face; raise a mound of stone 2 ft. base 1-1/2 ft. high NW of Cor., whence:

A pine 10 ins. dia. brs. N. 2°45' W. 199 lks.

A pine 16 ins. dia. brs. N. 29°00' E. 146 lks.

Each blazed and scribed 9 HES 594 + BT.

Thence S. 59°27' W.

Over gently rolling land through edge of scattering pine.

18.20

To Cor. No. 10.

Identical with Cor. H/6 of the list survey, which is a malpais stone 10x3x8 ins. above ground, marked and witnessed as described by the Forest Service. I destroy all trace of this list Cor.

Deposit a malpais stone 8x4x5 ins., marked with a + 18 ins. in the ground, over which set a malpais stone 24x16x12 ins., chiseled + for the point and 10 HES 594 on NE. face; raise a mound of stone 2 ft. base 1-1/2 ft. high NE. of Cor., whence:

A pine 28 ins. dia. brs. N. 22°45. W. 70 lks.

A pine 10 ins. dia. brs. N. 32°15 E. 68 lks.

Each blazed and scribed 10 HES 594 + BT.

.. onei bowete came one coveling even

9....

No set He

## HOMESTEAD ENTRY SURVEY NO. 594

#### APACHE NATIONAL FOREST

# STATE OF ARIZONA

		Chains	Thence N. 35°51' W.
		-70	Through edge of scattering aspen and pine.
1		6.00	Castle Creek (dry), 10 lks wide, banks 2 ft. high, course
		6.60	
			AREA
	,		Listed area 45.04 acres
			Unlisted area 26.29 "
			Total area 71.33 acres
	1	s day	All of the leg for the case of the first of the
		,	IMPROVEMENTS
			The improvements made upon and for the benefit of this
			claim and belonging to the claimant herein consist of
			the following:
		0	A log house 12x16 ft., the long sides extending N. and
-			S., the NE. Cor. of which bears S. 38°29' W. 1.80 chs.
0			from Cor. No. 5.
			Value \$200.00
			A log shed 10x12 ft., the long sides extending N. and
			S., the NE. cor. of which bears S. 20°37' W. 1.23 chs.
			from Cor. No. 5.
		Park I	Value \$ 25.00
		-	A log dugout 10x14 ft., the long sides extending N. and
			S., the NE. Cor. of which bears S. 31°37'. W. 1.37 chs.
			from Cor. No. 5.
			Value \$ 10.00
			A pole corral, figure 8, 40 ft. and 50 ft. dia.,
			bearing E. and W., the E. end of which bears S. 60° W.
2			2.90 chs. from Cor. No. 5.
			Value
			About 2 miles of wire fencing.
A			Value

#### APACHE NATIONAL FOREST

#### STATE OF ARIZONA

#### Chains

#### DESCRIPTION

The claim is situated on Castle Creek, a small intermittent stream which flows only during the early spring months. The claim is comprised mainly of open bottom land. About 90 per cent of the area is suitable for agricultural purposes, of which approximately 20 acres were under cultivation at the time of survey. The rainfall is depended upon to grow crops, though it is believed water might be secured at a shallow depth if a well were driven.

During ordinary years water for domestic use is obtained from a spring near the west end of the claim. However, last year being an exceptionally dry year, the spring had dried, and water for domestic use would have to be obtained from Beaver Creek, about 1-1/2 miles to NW. There is no timber of commercial value on the claim.

I saw no indications of mineral on the claim.

#### CONFLICTS AND ADJOINING CLAIMS

There are no conflicts or adjoining claims. H.E.S. 595. lies about 1/4 mile to NW., and H.E.S. 597 lies about 1/2 mile to SW.

Espero, Arizona, postoffice, lies about 4 miles to NW. Alpine, Arizona, the nearest trading point and settlement, lies about 20 miles to NE. and is reached by trail.

Springerville, Arizona, the general trading point for this section of the country, lies about 4 miles to the north and is reached by fair wagon road.

274 cass 19

### APACHE NATIONAL FOREST

### STATE OF ARIZONA

Chains		1,81,181,17,1	TRAVERSES			actary,
•	UNLISTED AREA		1 1 1 m			
	Course	Dist.	N	. S.	. E.	W.
	N. 69°08' E. S. 25°03' E. S. 78°53' W. N. 85°09' W. S. 88°18' E. N. 0°37' W.	14.59 21.33 19.30 17.81	1.63	13.22 4.11 .53		20.93
	N. 0.34. W.	10.02	10.02	17.86	40.27	40.27
	Course	Dist.	N.	o s	E.	W.
	N. 56°48' E. N. 35°26' E. N. 82°47' E. N. 69°08' E. S. 25°03' E. S. 78°53' W. N. 85°09' W. S. 43°14' W. S. 59°27' W. N. 35°51' W.	16.42 25.07 17.43 14.59 21.33 19.30 17.81 18.20	13.38 3.15 6.21	and the second of the second of	IN'S	20.93 19.23 12.20 15.67 3.87
br-	Error in Lat.	. & Dep.	23.03	03		71.90 04
90	Closing error	1/3495	al tables			
	TIE USLM 594	HES TO US	LM 504 HE	s.	of the co	
	Course	Dist	N.	s.	E.	W.
•	N. 61°55' E. S. 23°16' E. S. 14°49' W. S. 85°46' W. S. 88°45' W. N. 42°02' 27''V N. 49°16' E. N. 47°40' W.	16.64	.27 55.24 10.86 19.97	7.14 17.36 2.01	.51 3.07	4.59 27.18 51.05 49.81 21.93
	N. 44°24' W.	60.10	129.28	27.62	16.19	42.05
- 13			27.62	No ha		16.19
100000	Resultant Cou	irse N. 60		. 207.09	chs.	
n to the second	TIE USLM 594	HES TO COL	R. 1/597			
	Course	Dist.	N.	s.	E.	W.
	N. 61°55' E. S. 23°16' E. S. 14°49' W. S. 85°46' W.	.58 7.77 17.96 27.25	.27	7.14 17.36 2.01 26.51 27 26.24	3.07 3.58	4.59 27.18 31.77 3.58 28.19
	Resultant Cou	rse S. 47°	03'06" W.	. 38.51	N. T.	

12.

#### HOMESTEAD ENTRY SURVEY NO. 594

#### APACHE NATIONAL FOREST

STATE OF ARIZONA

Chains	TIE COR.	2/594 to Cor	. 1/595	denied)		
	Course	Dist.	N.	s.	E.	W.
	N. 58°59' N. 55°39' .N. 75°05' .N. 39°25'	W. 9.33 W. 4.94	2.93 5.26 1.27 3.28		4.87	7.70
		Price.I	12.74	0	4.87	15.17 4.87 10.30

Resultant Course N. 38°57'17" W. 16.38 chs.

. TIE COR. 1/594 to USLM 594 HES.

,Course	Dist.	N	Ş. 1	#.	W.
.N. 38°57'1	E. 18.02 L7"W.16.38 L5"W.30.78	9.87	5.98	15.08	10.30
60.	1.60 T	22.61 5.98 16.63	5.98	15.08	40.49 15.08 25.41

Resultant Course N. 56°47'48" W. 30.37 chs.

Note: Any discrepancy between these field notes and those of the listing survey is due to error in the latter.

Survey completed June 16, 1921.

Komas & myers
Surveyor - Forest Service.

Note: The tie from U.S.L.M. 504 HES. to Cor. of Secs. 24 and 25 on E. boundary of T. 4 N., R. 28 E., as recorded in the field notes of HES. 504, was found to be slightly in error, by reason of the ties made by me in connection with the survey of HES. 616, which ties in donnection with claim lines of subsequent surveys in this vicinity made by me afford a closed traverse. Tie from Cor. 1 HES. 504 to U.S.L.M. 504 HES. recorded in field notes of HES. 504 is in error as shown in traverse recorded in field notes of HES. 573.

Thomas 3 Myers

Surveyor 2 Forest Service.

Sheet No. 3.—Revised Feb., 1915.

Directions.—1. Carry out calculations to two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

CORNERS.	BEARING.	DISTANCE.	LATITUDES.					DEPARTURES.				DOUBLE M. D.		N. AREAS.		S. AREAS.		11/2	
0022.2		DISTANOE.	NORTH. SOUTH.			Е	East.		Wes	т.	DOUBLIS M. D.		n. muno.		b. 11111116.				
1 = 2	N.56°48'E.	18.02	9	87			]	.5	08			15	08	148	84				
2 - 3	N.35°26'E.	16.42	13	38				9 5	52			39	68	530	92			i i i i i i i i i i i i i i i i i i i	
3 - 4	N.82°47'E.	25.07	3	15			2	4 8	37			74	06	232	55				
4 - 5	N.69°08'E.	17.43	6	21		14		6.2	All of the last of the last			115	21	715	45				
5 - 6	S.25°03'E.	14.59			13	22		6 1	18		911	137	68			1820	13		
6 - 7	S.78°53'W.	21.33		1.	4	11	ARTHUR S			20	93	. 122	92			506	43	132	
7 - 8	N.85°09'W.	19.30	1	62 63	Z 1500					19	23	82	74	134	04			VARIET	
8 - 9	. S.43°14'W.	17.81			12	98				12	20	51	30	Nation 1		665	87		
9 - 10	S.59°27'W.	18.20	9	8	9	25	/			15	678		42			216	64		
10 - 1	N.35°51'W.	6.60	5	35	7					3	87	3	87	20	70				
		174,77	39	59	39	56	7	1 9	94	71	90			1782		3209	07		
	Error in I	at. & Dep.				03					04					1782	50		
Closing	error 1/3495															20/ 1426		1-1-1-1	F
	6															71	33	acres	
			Property.		UNLIST	ED A	AREA								(L.) Trici	O man			
	N.69°08'E.	17.43	6	21			]	.6 2	29			51	67	320	87				
	S.25°03'E.	14.59			13	22		6 ]	18				14			980	13		
	S.78°53'W.	21.33			4	11				20	93	59				244			
	N.85°09'W.	19,30	1	63	1-1					19		19		31	34	64-44-4			
	S.88°18'E.	17.81				53	2	.7 8	30		-6452	77			-4,1%	9	43		
	N. 0°37'W.	10.02	10	02	/						11	35		355	67	7	4:0		
			17	86	17	86		10 2	27	40	27	0.0		707		1233	65		
						19			5	±	-14-1				.0.2			Filtra	
																20/ 525			

#### APPROVAL

Office of the United States Surveyor General,

Dhoanix, Arizona, Dec. 12, 1922

The foregoing field notes of Homestead Entry Survey No.

594

executed by Thomas F. Myers, Secrety or [Forest Service Title.] under his special instructions, dated May 14, 1919, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Surveyor General

I certify that the foregoing transcript of the field notes of the above-described survey in the State of Arizona, has been correctly copied from the original notes on file in this office.

U. S. Surveyor General.

-2349