U. S. DEPARTMENT OF AGRICULTURE ORIGINAL

FOREST SERVICE

FIELD NOTES

HOMESTEAD ENTRY SURVEY NO. 634

SITUATED IN THE SITGREAVES . NATIONAL FOREST

ADMINISTRATIVE DISTRICT NO. 3

In Section 1 , - surveyed, Township 10 N , Range 20 E. In Section 12 , - surveyed, Township 10 N., Range 20 E.

of the

Gila and Salt River Base and Meridian.

State of

Arizona.

Applicant for listing George M. Myce, Linden, Arizona. Residence

, dated February 24 , 19 07 Application No. 62

, dated December 16 List No. 805 , 19 07

Applicant for survey Lewis Smauldon,

Linden, Arizona. Residence

H. E. No. 010596 , dated January 3 , 19 11.

Phoenix, Arizona. Land Office

Survey executed by Thomas F. Myers, Surveyor - Forest Service. Forest Service Titles;

Under special instructions dated March 19 , 19 23

, 19 23 Survey commenced August 15

, 1923 August 17 Survey completed

Under Acts of June 11, 1906, and February 26, 1923. NOVER

CATH OF ASSISTANTS

We hereby certify that we assisted Thomas F. Myers, Surveyor - Forest Service in survey

in surveying all those

[Forest Service Title.]

parts or portions of Homestead Entry Survey No. 634 , in the State which are represented in the following field notes of Arizona as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the United States Surveyor General for Arigona.

Note: It would have been very expensive and inconvenient to appear before an officer to administer Oaths to Assistants; hence they were taken by the Surveyor.

Chainman

Subscribed and sworn to before me this

17 th

omas Ill

August

1923.

Surveyor - Forest Service.

OATH OF SURVEYOR

Surveyor - Forest Service, Thomas F. Myers, [Forest Service Title.]

do solemnly swear that, in strict conformity with the special instructions of the United States Surveyor General for Arizona , dated March 19 , 1923 , and the laws of the United States, I have well, faithfully, and truly, in my own proper person, surveyed a tract of land embraced in

, No. 805 , dated December 16, 19 07, for under the Act of June 11 , 190 List , under the Act of June 11 , 1906 , Patent the same to be known as Homestead Entry Survey No. 634 National Forest, in situated within the Sitgreaves 1 , Township 10 N. , Range 20 E. , and 12 , Township 10 N. , Range 20 E. , - surveyed Section 12 - surveyed Section

of the Gila and Salt River Base & meridian, Arizona related retracements and resurveys and section subdivisions, which are represented in the following field notes as having been surveyed by me; and I further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the stated special instructions, and in the specific manner described in the field notes, and that the following are the original field notes of such survey.

Surveyor - Forest Service.

omas of Much

[Fcrest Service Title.]

Subscribed and sworn to before me this

7th

January

, 19 24.

Notary Public.

My Commission expires: April 12, 1925.

(4) SEAL.

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

1.

Chains

Applicant for listing, George M. Myce; Application No. 62, dated February 24, 1907; List No. 805, dated December 16, 1907; H. E. 010596, made in the Phoenix Land Office on January 3, 1911, by Lewis Smauldon. Surveyed under special instructions from the Surveyor General for Arizona, dated March 19, 1923, and designated as Homestead Entry Survey No. 634. Situated in Secs. 1 and 12, T. 10 N., R. 20 E. (Surveyed and accepted), Gila and Salt River Base and Meridian, within the Sitgreaves National Forest, Arizona. Surveyed under the Acts of June 11, 1906, and February 26, 1923.

Survey commenced August 15, 1923, and executed with a Buff and Buff transit No. 14631, equipped with Smith solar attachment.

I test the adjustments of the transit and make necessary corrections.

All distances are horizontal, and were reduced from measurements made directly on the slope with a 400 link steel tape. The slope angles were determined with a clinometer.

August 17. 1923.

At the Cor. of Secs. 6 and 7, T. 10 N., R. 21 E., which is also Cor. No. 2 of this survey and Cor. No. 1 of HES. 635, hereinafter described, in Latitude 34°16'50"

N., Longitude 110°09'36" W. from Forest Service Base Map at 6h 45m 36s p.m. 1.m.t., I observe Polaris with telescope direct, reading an angle of 0°57'30" from star to left to tack in a stake about 10 chs. northerly of my station.

2.

HOMESTEAD ENTRY SURVEY NO. 634

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

Greenwich m.t. U.C. Polaris August 18, 1923, 3h 52.5m a.m.

Corr. for Long.

1.2

1.m.t. U.C. Polaris, August 18, 1923, 3h 51.3m a.m.

1.m.t. Obsn. Polaris August 17, 1923, 6h 45.6m p.m.

Hour angle

9h 05.7m

Azimuth of Polaris 0°54'.8'. E.

Bearing of reference mark N. 0°02.7' W.

At same station at 6h 50m 36s p.m. l.m.t., I again observe Polaris with telescope reversed, reading an angle of '0°58'30" from star to left to same reference mark. .

1.m.t. U.C. Polaris August 18, 1923, 5h 51.5m a.m. l.m.t. Obsn. Polaris August 17, 1923, 6h 50.6m p.m.

9h 00.7m

Hour angle .

Azimuth of Polaris '0°56.1' E.

Bearing of reference mark N. 0°02.4' W.

The bearing of reference mark as determined from the mean of the two observations is N. '0°02'33"W. I accept bearing of reference mark as N. 0°03" W. and from the corresponding meridian all the courses of this survey were referred by sustained angulation.

Note: The courses of this survey were run on an assumed azimuth which was subsequently corrected to the above meridian.

RETRACEMENTS .

August 14, 1923:

Beginning at the Cor. of Secs. 6 and 7. T. 10 N. R. 21 E., an iron post 3 ins. in dia: 1 in. above ground, with brass cap, marked and witnessed as described by the Surveyor General.

Thence N. O'12' E.

Along line between T. 10 N., Rs. 20 and 21 E. for flag on Cor. Ts. 10 and 11 N., Rs. 20 and 21 E., which is

3.

HOMESTEAD ENTRY SURVEY NO. 634

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

| Chains | plainly visible. |
|------------|--|
| 2.97 | Cor. Secs. 1 and 12, T. 10 N., R. 20 E., an iron post |
| | 3 ins. in dia., 6 ins. above ground, with brass cap, |
| | marked and witnessed as described by the Surveyor |
| | General. |
| 40.36 | The 1/4 Cor. for Secs. 6, an iron post 1 in. in diameter, |
| - Sans | 8 ins. above ground, with brass cap, marked and |
| a | witnessed as described by the Surveyor General. |
| 42.97 ; | The 1/4 Cor. for Sec. 12, an iron post 1 in. in diameter |
| | 8 ins. above ground, with brass cap, marked and witnes- |
| | sed as described by the Surveyor General. |
| 80.72, | The Cor. of Ts. 10 and 11 N., Rs. 20 and 21 E., an iron |
| a contract | post 5 ins. in diameter, 6 ins. above ground, with |
| | brass cap, marked and witnessed as described by the |
| 10 0 | Surveyor General. |
| | Rain in afternoon. |
| | . August 14, 1923. |
| A REST | |
| | |
| | August 15, 1923. |
| | Return to Cor. Secs. 1 and 12, previously described. |
| - 15 | Return to Cor. Secs. 1 and 12, previously described. Thence West. |
| | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. |
| | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an |
| | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with |
| 38.54 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the |
| 38.54 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. |
| 38.54 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the |
| 38.54 | Return to Cor. Secs. 1 and 12, previously described. Thence West. hetracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. True line is S. 89°56! W. 38.34 chs. |
| 38.54 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. True line is S. 89°56' W. 38.34 chs. Return to Cor. of Secs. 6 and 7, previously described. |
| 38.54 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Aetracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. True line is S. 89°56' W. 38.34 chs. Return to Cor. of Secs. 6 and 7, previously described. Thence S. 0°15' W. |
| 38.34 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Attracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. True line is S. 89°56' W. 38.34 chs. Return to Cor. of Secs. 6 and 7, previously described. Thence S. 0°15' W. Retracing line between Secs. 7 and 12 N/2. |
| 38.54 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. True line is S. 89°56' W. 38.34 chs. Return to Cor. of Secs. 6 and 7, previously described. Thence S. 0°15' W. Retracing line between Secs. 7 and 12 N/2. Fall 25 lks. West of 1/4 Cor. for Sec. 12 an iron post |
| 38.34 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. True line is S. 89°56' W. 38.34 chs. Return to Cor. of Secs. 6 and 7, previously described. Thence S. 0°15' W. Retracing line between Secs. 7 and 12 N/2. Fall 25 lks. West of 1/4 Cor. for Sec. 12 an iron post 1 in. in diameter, 10 ins. above ground, with brass |
| 38.34 | Return to Cor. Secs. 1 and 12, previously described. Thence West. Retracing line between Secs. 1 and 12, E/2. Fall 4 lks. N. of 1/4 Cor. between Secs. 1 and 12, an iron post 1 in. in diameter, 12 ins. above ground, with brass cap, marked and witnessed as described by the Surveyor General. True line is S. 89°56' W. 38.34 chs. Return to Cor. of Secs. 6 and 7, previously described. Thence S. 0°15' W. Retracing line between Secs. 7 and 12 N/2. Fall 25 lks. West of 1/4 Cor. for Sec. 12 an iron post |

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

True line is S. 0°08' E. 37.06 chs.

BOUNDARIES OF CLAIM

var signed to as, is here, in all in the

August 15, 1923.

Beginning at Cor. No. 1.

Identical with Cor. of Secs. 1 and 12, previously described, I adopt same for Cor. No. 1 of this survey and alongside to West set a sandstone 24x14x12 ins.

20 ins. in ground, chiseled 1 HES 654 on W. face; raise mound of stone 2 ft. base 1-1/2 ft. high W. of Cor.

No witnesses available. Pits impracticable.

Latitude 34°16'52" N., Longitude 110°09'36" W. from

Forest Service Base Map.

Mag. decl. at 12 N. 14°40' E. Mean Mag. decl. 14°43' E. Thence S. 0°12' W.

On line between Secs. 12 and 6. Fence on line.

To Cor. No. 2 and Closing Cor. on E. boundary of Sec. 12, also Cor. No. 1 of HES. 635.

Identical with Cor. of Secs. 6 and 7, previously described. I adopt Sec. Cor. for Cor. No. 2 of the survey and Cor. No. 1 of HES. 635, and alongside to W. set a sandstone 24x18x13 ins. 14 ins. in ground, chiseled CC on W., 2 HES 634 on NW. and 1 HES 635 on SW.

No witnesses available. · Pits impracticable.

Thence S. 89°56! W.

Over open level land on N. side of lane. Fence on line.

5.00 Cross to inside of fence.

Fence bears NW. and SE. Cor. is SE. 10 1ks.

Road, bears NW. and SE.

Fence bears NW. and SE. Enter edge of pine reproduction.

Ascend NE. slope 5 ft.

2.97

0.00

17.70

17.95

18.91

9-2349

Chains

1.06

2.55

To Cor. No. 3, also Cor. No. 14 of HES. 635.

Deposit a sandstone 2x2x4 ins., marked with a + 14 ins. in the ground, over which set a sandstone 24x12x12 ins. chiseled + for the point and 3 HES 634 on NE. face; and 14 HES 635 on SW. face; raise a mound of stone 2 ft. base 1-1/2 ft. high NE. and SW. of Cor., whence:

A pine 8 ins. dia. brs. S. 52°12' E. 20 1ks.

Each blazed and scribed 3 HES. 634 + BT.

A pine 11 ins. dia. brs. N. 65°37' W. 86 lks.

A pine 10 ins. dia. brs. S. 85°30' W. 71 lks.

Each blazed and scribed 14 HES 635 + BT.

Thence N. 0°10' E.

Descend 5 ft. over NE. slope through edge of pine reproduction.

.76 Fence bears NW. and SE.

Road bears NW. and SE.

1.45 Fence bears NW. and SE.

Witness Cor. for No. 4 and Closing Cor. on line between Secs. 1 and 12, which is also witness for Cor. No. 13 of HES. 635. Point for Cor. falls in an arroyo and would not be permanent if set. Therefore at this point set witness Cor. for Cor. No. 4 of this survey and Cor. No. 13 of HES. 635 as follows:

Deposit a sandstone 1x2x3 ins., marked with a + 12 ins. in the ground, over which set a sandstone 22x8x8 ins. chiseled + for the point and CC on S., WC 4 HES 634 on E. face; and WC 13 HES 635 on W. faces; raise a mound of stone 2 ft. base, 1-1/2 ft. high S. of Cor., on Closing line, whence:

A pine 7 ins. dia. brs. S. 51°18' E. 31 lks.

A juniper 10 ins. dia. brs. S. 71°47' E. 142 lks.

Each blazed and scribed WOC 4 HES 634 + BT.

6.

HOMESTEAD ENTRY SURVEY NO. 634

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

Chains

A pine 11 ins. dia. brs. N. 89°02' W. 64 lks. An oak 8 ins. dia. brs. N. 49°10' W. 43 1ks. Each blazed and scribed WCC 13 HES 635 + BT.

2.97

Point for Cor. No. 4 and Closing Cor. on line between Secs. 1 and 12, also point for Cor. No. 13 of HES. 635 falls in an arroyo 35 lks. wide, 3 ft. deep, course East. Corner would not be permanent if set.

> Cor. Secs. 1 and 12, previously described, brs. N. 89°56' E. 20.00 chs.

1/4 Cor. between Secs. 1 and 12, previously described brs. S. 89°56' W. 18.34 chs.

August 15, 1923.

August 16. 1925.

Thence N. O'10' E.

Over open land along inside of fence.

.38

Witness Cor. to Cor. No. 4 and Closing Cor. on line between Secs. 1 and 12, which is also witness Cor. for Cor. No. 13 HES. 635.

Deposit a sandstone 1x2x3 ins., marked with a + 16 ins. in the ground, over which set a sandstone 24x14x12 ins. chiseled + for the point, CC on S., WC 4 HES 634 on E. face; and WC 13 HES 635 on W. faces, whence:

A pine 26 ins. dia. brs. S. 61°58' E. 405 lks. blazed and scribed WCC 4 HES 634 + BT. A pine 7 ins. dia. brs. S. 74°38' W. 122 1ks.

'An oak 6 ins. dia. brs. S. 32°39' W. 92 lks.

Each blazed and scribed WCC 13 HES 635 + BT.

Note: It was impracticable to set witness Cor. Hast or West on Sec. line within 3.00 chs. of point for Cor.

16.80

Fence gate, fence bears East.

17.50 22.03.

23.30

22.90

Wash, 15 lks. wide, 1 ft. deep, course NE. Cor. No. 12 of H.E.S.635.
Arroyo 30 lks. wide, 4 ft. deep, course East.

Fence Cor. bears West 15 1ks. Fences bear S. 0°10' W. and West.

SITGREAVES NATIONAL FOREST

STATE OF

| ARIZONA7 |
|----------|
|----------|

| Chains 25.40 | Fence bears East. |
|-----------------|---|
| 27.10 | Enter S. end barn at center. |
| 27.86 | Leave N. end barn at center. |
| 29.80 | Begin ascent of 20 ft. over S. slope through scattering |
| | cedar and oak. |
| 34.50 | Top of ascent. Thence over gently rolling East slope. |
| 61.30 | Wash 30 lks. wide, 2 ft. deep, course ENE. |
| 76.79 | To Cor. No. 5. |
| | Deposit a sandstone 3x5x6 ins., marked with a + 12 ins. |
| | in the ground, over which set a sandstone 22x11x8 ins., |
| | no longer stone available, chiseled + for the point and |
| | 5 HES 634 on SE. face; raise a mound of stone 3 ft. |
| | base, 2 ft. high SE. of Cor., whence: |
| | A juniper 30 ins. dia. brs. S. 5°45' W. 143 lks. |
| le lette | A pine 10 ins. dia. brs. S. 51°55' E. 146 lks. |
| | Each blazed and scribed 5 HES 634 + BT. |
| | |
| Tel best | Thence N. 89°57! E. |
| loi | Over open land. |
| 4.00 | Begin ascent of 40 ft. over rolling S. slope through |
| | heavy pinon and cedar. |

heavy pinon and cedar.

20.00 To Cor. No. 6 and Closing Cor. on line between Secs. 1 and 6.

> Deposit a sandstone 1x3x6 ins., marked with a + 24 ins. in the ground, over which set a cedar post 3 ft. long, 8 ins. dia., pointed at top, scribed CC on W. and 6 HES 634 on SW. face; raise a mound of stone 2 ft. base, 1-1/2 ft. high W. of Cor., whence:

> > A clump juniper 40 ins. dia. at base brs. S. 60°50' E. 67 lks.

A cedar 8 ins. dia. brs. N. 5°30' E. 25 1ks. Each blazed and scribed CC 6 HES 634 + BT. Cor. Ts. 10 and 11 N., Rs. 20 and 21 E., previously described, bears N. 0°12' E.

1.00 chs.

SITGREAVES NATIONAL FOREST

8.

STATE OF ARIZONA

| Chains | 1/4 Cor. for Sec. 1, previously described, |
|--------|--|
| | bears S. 0°12' W. 37.75 chs. |
| | Rain in afternoon. |
| | August 16, 1923. |
| | the distriction of the second contract of the |
| | August 17, 1923. |
| | Thence S. 0°12' W. |
| | Along line between Secs. 1 and 6. Descend 30 ft. over |
| | S. slope through scattering pinon and cedar. Fence |
| | along line inside claim. |
| 7.75 | Bottom of descent, thence over nearly level land. |
| 14.25 | Arroyo 30 lks. wide, 5 ft. deep, course ENE. |
| 15:50 | Cross fence, fence outside of line. |
| 23.90 | Fence Cor. is East 10 lks. Fences bear N. and W. |
| 24.24 | Center lane, bears E. and W. |
| 24.58 | Fence Cor. is East 10 'lks. Fences bear W. and S. along |
| | Tine. |
| 36.75 | To Cor. No. 7. |
| | Identical with 1/4 Cor. for Sec. 1, previously described |
| | I adopt same for Cor. No. 7 of this survey, and along- |
| | side to West set a juniper post 4 ft. long, 6 ins. in |
| | dia., 2 ft. in ground, scribed 7 HES 634 on W. face. |
| | |
| | Thence S. 0°12' W. |
| . 2/ 3 | Along line between Secs. 1 and 6, over open level land. |
| . 2.97 | 1/4 Cor. for Sec. 6 previously described. |
| 22.90 | Fence Cor. is East 7 lks. Fences bear W., N. and S. |
| | along line. Thence along East edge of cultivated |
| | field. : (the hir |
| 40.00 | To Cor. No. 1, the place of beginning. |
| | |
| | AREA · |
| | Area in Sec. 1 153.54 acres |
| | Area in Sec. 12 5.94 " |
| | · Total Area |
| | |

SITGREAVES NATIONAL FOREST

STATE OF ARIZONA

9.

Chains

. IMPROVEMENTS

The improvements made upon and for the benefit of this claim consist of the following:

A frame house 20x40 ft., the long sides extending N. and S., the SW. Cor. of which bears N. 0°10' E. 27.03 chs. from Cor. No. 3.

Value - - - - - - - - - - - - - - 5500.00

A frame barn 20x50 ft., the long sides extending N. and S., the SW. Cor. of which bears N. O'10' W. 30.13 chs. from Cor. No. 3.

Value - - - - - - - - - - - - - - 50.00

A frame chicken house 10x12 ft., the long sides extending E. and W., the SW. Cor. of which bears N. 1°52' E. 28.22 chs from Cor. No. 3.

Value - - - - - - - - - - \$ 10.00

A frame blacksmith shop 10x12 ft., the long sides extending N. and S., the SW. Cor. of which bears N. 4°34'

E. 28.27 chs. from Cor. No. 3.

Value - - - - - - - - - - 10.00
Approximately 2 miles of wire fencing.

Value - - - - - - - - - - - - \$200.00

DESCRIPTION

The area embraced in this homestead is comprised mainly of open valley land, with a gentle slope to the NE. The soil is a rich sandy loam of good depth and very fertile. Approximately 140 acres of the area is suitable for agricultural purposes, of which about 40 acres are under cultivation. The rainfall must be depended upon to grow crops.

Water for domestic use is hauled from a well about 3 miles distant in a southerly direction. It is probable water could be developed on the claim or could be con-

STATE OF ARIZONA

Chains

served by means of cisterns.

There was no timber of commercial value on the claim.

I saw no indication of mineral on the claim.

There are no conflicts. The claim is joined on the south and west by HES 635, covering homestead of Oliano Cordoba, and on the east by HE. 025387 of Jesse R. Jarvis, patented July 7, 1918, and HE. 024509 of J. H. Frost, patented June 2, 1919.

Linden, Arizona, the nearest postoffice, lies about 1 mile distant in a southeasterly direction.

Snowflake, Arizona, the main trading point in this vicinity, lies about 20 miles distant in a north-easterly direction and is reached by good wagon road.

Survey completed August 17, 1923.

Surveyor - Forest Sarvice.

8-234

Form 85. Sheet No. 3.—Revised Feb., 1915.

Directions.—1. Carry out calculated by the two decimals only.

2. In balancing Latitudes and Departures do not obliterate or change the original figures.

Put the corrected figure or figures above in red ink. Do not change the footing of the original figures, but put below them the corrected footing in red ink.

The corrections for balancing fallings should be proportional to the lengths of the lines.

3. In calculations of fallings take result to nearest link. In calculations of N. and S. areas drop all after second decimal. Surveyors are required to use the Standard Field Tables issued by the G. L. O.

4. Only three copies of this tabulation are necessary, for the District Office, the Surveyor General, and the Commissioner.

| CORNERS. | BEARING. | DISTANCE. | LATITUDES. | | | DEPARTURES. | | | DOUBLE M. D. | | N. AREAS. | | S. AREAS. | | | | |
|----------|------------------|----------------|------------|--------|-----------|-------------|------------|----|--------------|--------------|-----------|-----------|--------------|-----------|---------|--|-----------|
| | | | NORTH. SOU | | SOUTH. EA | | AST. WEST. | | sT. | DOUBLE M. D. | | N. AKEAS. | | S. AREAS. | | | |
| | | | | nell y | ARE | A IN | SEC. | | | | | | | | | | |
| 1 - 4 | S. 89°56' W. | 20.00 | | | | 02 | V I | | 20 | 00 | 20 | 00 | , | - | | 40 | 7 12 1 |
| 4 - 5 | N. 0°10' E. | 76.79 | 76 | 79 | , , | | | 25 | / | | | 25 | 7.9 | 19 | V | 120 | |
| 5 - 6 | N. 89°57° E. | 20.00 | | 02 | | 01 | 20 | OO | | | 20 | | / | 47 | 7 | | |
| 6 - 7 | S. 0°12' W. | 36.75 | | | 36 | 75 | / | | | 13 | | 38 | , | Stale | 1484 | 37 | / |
| 7 - 1 | S. 0°12' W. | 40.00 | | | 40 | 00 | 25 | | | 14 | | 13 | (| | 1605 | | 1 |
| | | 193.54 | 76 | 81 | 76 | 77 | 20 | 22 | 20 | 27 | | | 79 | 60 | 3090 | | 1 |
| | | | 76 | 77 | | | | | | 22 | | | | | | 60 | ~ |
| Error | in Lat. & Dep. | Water Property | | 04 | | | | | | 05 | | | | | 20/3070 | - | 7 |
| Clo | sing error 1/30 | 23 | 76 | 79 | 76 | 79 | 20 | 25 | 20 | 25 | | | | | | STATE OF THE STATE | acres |
| | | | | | ARE | IN | SEC.] | 2 | | | | | | | | | |
| 1 - 2 | S. 0°12' W. | 2.97 | | | 2 | 97 | 1 | | | 01 | 40 | 01 | | | 118 | 83 | V 44 1/32 |
| 2 - 3 | S. 89°56' W. | 20.00 | | | | 02 | 2 | | 20 | 00 | 20 | 00 | / 10 (2) (4) | | | 40 | |
| 3 - 4 | N. 0°10' E. | 2.97 | 2 | 97 | 1 | | | 01 | <i>(</i> | | | 01 | | 03 | | | |
| 4 - 1 | N. 89° 56 E. | 20.00 | | 02 | V | Linetin | 20 | 00 | 1 | | 20 | 02 | | 40 | | | |
| | | 45.94 | 2 | 99 | 2 | 99 | 20 | 01 | 20 | 01 | v | | | 43 | 119 | 23 | |
| | | | | | _ 2 | 99 | 20 | 01 | | | | | | | | 43 | |
| | in Lat. & Dep. | Name Page 1 | | | | 00 | / | 00 | | | | | | | 20/ 118 | | 2000 |
| Clos | sing error: None | | | | | | | | A Linis | | | | | | 5 | 94 8 | acres 20 |
| | | | | | | | | | | | | | | | | | T. W. S. |
| | | · | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |

| | AMORIDA | | | | | | | | |
|--|--|------------------|-------|--------|---------|--------|----------|--------------------|------------|
| | | North Additional | | | | | | | |
| | | | | | | | | | |
| | | | 00 03 | | 30 | | 00.00 | 1 000 | F1 5 2 3 3 |
| | T CA | 38 | | - 00 | | 87 | | | |
| | | da las | | | | 30 | Maria VI | | |
| 82 A3 | | ell de | | | 75 V CF | | 100.00 | | |
| 00.000 | | 40 22 | lal | | | | | 1010 | |
| A Respondence of the second | 10, 81 | | | 12 08 | 76 77 | Let an | Sa. Nes | | |
| | | | 80 0 | | | | | | |
| The State Of | | | .0 | | | | | of a sent the sent | |
| a near to the near to | | | | | | - | | | |
| | | | | SI .CH | MI WIRV | | | | |
| May ar all the | | | | | 8 | | Co | . Tage on the | 3 - 1 |
| W-1087 | | | | | | | mine . | Total . | 2 /- c |
| | STATE OF THE PARTY | | | | | 79 0 | | In Falls | 7-8 |
| | - Vir II Line | . 80 08 | | 05 08 | | 90 | na.ne | 1 0 0 m . m | 1 - 10 |
| | | | | IO 08 | 6618 | 8.8 | 27.00 | | |
| | | | | | 64 5 | | | | |
| Maria Abarra Abarra | | | | | | | | red a I he w | The same |
| | | | | | | | | Was town parties | |
| | | | | | | | | | |
| | | | | | | | | | |

APPROVAL.

Office of the United States Surveyor General,

Phoenix, Arizona, April 4 , 1924

The foregoing field notes of Homestead Entry Survey No.

634

executed by Thomas F. Myers, Surveyor,

under his special instructions, dated March 19, 1923, having
been critically examined, and the necessary corrections and explanations
made, the said field notes, and the surveys they describe, are hereby
approved.

Gearles W. Douolios.
U. S. Surveyor General.

I certify that the foregoing transcript of the field notes of the above-described survey in the State of Arizona , has been correctly copied from the original notes on file in this office.

Charles M. Donohoe

U. S. Surveyor General.

8-2349