

8

8

5

2

0

## MINERAL SURVEY NO. 2588

	M & B Desc.	Improvements	Loc. Notices
	Pg. 14	Pg. 23	Pg.
Claims			
Comet			5
Franklin	1	21	15
Franklin No. 2	2	21	16
Gold Wedge	10	23	18
Hondo	13	24	6
Lynx No. 1	11	24	7
Lynx No. 2	13	24	8
Manilla	15	25	4
Mount Davis	16	24	1
Mt. Union	17	24	2
No. 1 Gould	7	23	10
Penobscot	4	21	14
Summit	9	23	12
Spruce	18	24	3
Sure Thing Gold	6	22	0
The Last Dollar	8	23	
The Mountain View	3	21	
Winiford Gould	4	22	
Yankee Blade	11	23	

1015-191

4-683.

MINERAL SURVEY No. 2588

LOT No. \_\_\_\_\_

Arizona

Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Mount Union Consolidated Mining Co.

Mount Davis, Mt. Union, <sup>KNOWN AS THE</sup> Spruce, Manilla, Comet, Bonds, Lynx Nos. 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 689, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, 726, 727, 728, 729, 730, 731, 732, 733, 734, 735, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 762, 763, 764, 765, 766, 767, 768, 769, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 812, 813, 814, 815, 816, 817, 818, 819, 820, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846, 847, 848, 849, 850, 851, 852, 853, 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 915, 916, 917, 918, 919, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 930, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 970, 971, 972, 973, 974, 975, 976, 977, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000.

Assayumpu

Mining District,

Yavapai

County,

Arizona

Section Approx, Township 12 N, Range 1 W, Unsur.

Surveyed under instructions dated Sep. 19, 1908

by J. J. Fisher

U. S. Mineral Surveyor.

Claim located See loc. Notices, 19

Survey commenced Sep. 21, 1908

Survey completed Sep. 29, 1908

6-822

Robert E. Morrison,  
Attorney for Claimant  
Prescott  
Ariz.

# POOR QUALITY

**The following pages are scanned at the best possible quality setting. The original pages are of poor quality and this is the best possible reproduction.**

SURVEY No. 2563.

FRANKLIN.

Feet.

Beginning at corner No. 1 which is also corner No.2 of the Penobscot lode of this survey. Identical with corner of location, a monument of stone 2 ft. base, 1-1/2 ft. high.

Set a porphyry stone 30x18x8 ins. 15 ins. in ground, alongside raised a mound of stone 3x3 ft. stone marked F.1-2563, also on opposite side P.S-2563, whence

A X on a porphyry rock in place marked S.R.P.2-2563 bears N.3°W. 25.5 feet.

A X on a granite rock in place marked F.S.P.1-2563 bears N.30°45'W. 13.6 feet.

U. S. M. N. No.1 Massawaba Mining Dist. bears N.9° 13'30"W. 3278.1 ft. distant

Thence S. 15°50'W.

1168  
1500

To cor.No.3 the MOUNTAIN VIEW LODE this survey. To cor.No.2 which is also cor.No.1 FRANKLIN No.3 LODE of this survey, identical with corner of location, a monument of stone 2 ft. base 1-1/2 ft. high.

Set a granite stone 24x16x10 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked F.2-2563, also on opposite side F.No.2,1-2563

Whence a X on a granite rock in place marked F.R. F.2-2563 bears N.37°30'W. 6.9 ft. distant,

A X on a granite rock in place marked S.R.P.No.2,1-2563 bears S.64°15'E. 12.2 ft. distant,

Thence S. 74°30'E.

300

To S. center end which is also the N. center end of FRANKLIN No.3 LODE of this survey, identical with location monument,

Set a granite stone 23x10x8 ins. 14 ins. in ground, alongside raised a mound of stone 3x3 ft. stone marked S.C.E.P.2563 also on opposite side N.O.E.P.No.3,2563

600

To cor.No.3 which is also cor.No.4 FRANKLIN No.3 Lode of this survey, identical with cor. of location.

Set a granite stone 24x14x5 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked F.S-2563 also on opposite side F.No.2,4-2563,

1200

No bearings available.

1200

Thence N. 15° 30' W.

140  
1500

To cor.No.2 YANKEE BLADE LODE of this survey. To cor.No.4 which is also cor.No.5 PENOBSCOT LODE of this survey, put a X on a granite rock in place marked F.4-2563 and on opposite side P.S-2563, no bearings available, this cor. is identical with cor. of loc.

Thence N. 74° 30' W.

300

To N. center end which is also the S. center end of PENOBSCOT LODE of this survey, identical with loc.

Set a granite stone 24x10x8 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked N.C.E.P.2563 also on opposite side S.C.E.P.2563

300

REF.

Feet.

600

To cor. No. 1 the place of beginning survey of exterior boundaries.

FRANKLIN No. 3 LOBE.

Beginning at cor. No. 1 which is also cor. No. 2 of FRANKLIN LOBE this survey, corner described above, whence U.S.M.P. No. 1 Hadsayupa M.D. bears N. 5° 30' W. 9857.9 feet distant,

Thence S. 1° 45' W.

1500

To cor. No. 2 identical with cor. of loc. a monument of stone 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x10x6 ins. 12 ins. in ground, alongside raised a mound of stone 3x3 ft. stone marked F.No. 2, 2-2583, whence a X on a granite rock in place marked B.R.F. No. 2, 2-3583 bears N. 67° 30' W. 17.1 ft. A X on a granite rock in place marked B.R.F. No. 2, 2-3583 bears S. 70° W. 9.3 ft. distant,

Thence S. 74° 30' E.

300

To S.C.E. identical with loc. a monument of stone 2 ft. base 1-1/2 ft. high,

Set a granite stone 30x12x6 ins. 15 ins. in ground, alongside raised a mound of stone 3x3 ft., stone marked B.C.R.F. No. 2, 2583.

600

To cor. No. 3, identical with cor. of loc. a monument of stone 2 ft. base 1-1/2 ft. high,

Set a granite stone 30x12x6 ins. 15 ins. in ground, alongside raised a mound of stone 3x3 ft. stone marked F.No. 2, 2-2583, no bearings available.

Thence N. 1° 45' E.

1200

To cor. No. 4 which is also cor. No. 3 FRANKLIN LOBE of this survey, cor. described above.

Thence N. 74° 30' W.

300

To N.C.E. which is also the S.C.E. FRANKLIN LOBE this survey, monument described above.

600

To cor. No. 1 the place of beginning survey of exterior boundaries.

I-1/2 18 11 1/2  
corner of ...  
of the ...  
bearing of corner No. 1

See

FRANKLIN No. 3 LOBE

SURVEY No. 2588.

THE MOUNTAIN VIEW.

Beginning at cor. No. 1 which is identical with the N.C. loc. of stones 2 ft. base 1 1/2 ft. high.

Set a granite stone 24x15x10 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked M.V.1-2588,

Whence U.S.M.M.No.1 Hassayampa M.D. bears N.8°16'W. 7943.6 ft. distant, no other bearings available.

Original cor. of loc., a mon. of stones 2 ft. base, 1 1/2 ft. high, bears N. 74° 30' W. 300 ft. distant.

Thence S. 19° 55' W. 1502.1 ft. distant

To cor. No. 2 whence S.W. cor. of loc., a mon. of stones 2 ft. base 1-1/2 ft. high bears N. 74° 30' W. 300 ft. distant. Cut a X on a granite rock in place marked M.V.2-2588 alongside raised a mound of stones 3x3 ft., no bearings available.

Thence S. 74° 30' E.

To S.C.E. identical with loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked B.R.M.V.2588.

To cor. No. 3, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x8 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked M.V.3-2588,

Whence a X on a granite rock in place marked B.R.M.V.3-2588 bears N. 0° 50' W. 18.3 ft. distant,

A X on a granite rock in place marked B.R.M.V.3-2588 bears S. 14° 50' W. 16.5 ft. distant,

Thence N. 41° 15' 30" E.

To cor. No. 1 FRANKLIN and cor. No. 2 PENOBSCOT Lines of this survey,

To cor. No. 4, identical with cor. of loc., a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a porphyry stone 24x8x8 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked M.V.4-2588,

Whence a X on a granite rock in place marked B.R.M.V.4-2588 bears S. 34° 30' W. 29.9 ft. distant,

A X on a granite rock in place marked B.R.M.V.4-2588 bears N. 42° 15' W. 35.2 ft. distant.

N E 788

Thence N. 74° 30' W.

To cor. No. 1 the place of beginning survey of exterior boundaries.

\* \* \* \* \*

leaf

PENOBSCOT LODGE.

Beginning at cor.No.1 which is also cor.No.2 WINIFORD GOULD Lode of this survey, identical with cor.of loc. a mon.of stones 2 ft.base 1-1/2 ft.high,  
 Set a granite stone 24x10x3 ins. 12 ins.in ground, alongside raised a mound of stones 5x3 ft. stone marked P.1-2583 and on opposite side W.G.2-2583,  
 Whence U.S.M.M.No.1 Massachussetts M.D. bears N.14°34'37" W. 8911 ft. distant,

N                      E 192                      S

1180  
1500  
1800  
300  
600

Thence S. 15° 30' W.  
 To cor.No.4 MOUNTAIN VIEW Lode of this survey,  
 To cor.No.2 which is also cor.No.1 FRANKLIN Lode of this survey, cor. described above.  
 Thence S. 74° 30' E.  
 To S.C.E. which is also the N.C.E. the FRANKLIN Lode of this survey, cor. described above.  
 To Cor. No. 3, which is also Cor. No. 4 Franklin lode of this survey, cor. described above.

Thence N. 15° 30' E.

70  
1500

To cor.No.1 YANKIE BLADE and cor.No.2 GOLD WEDGE Lodes of this survey,  
 To cor.No.4 which is also cor.No.3 WINIFORD GOULD Lode of this survey, identical with cor.of loc. a mon.of stones 2 ft. base 1-1/2 ft.high,  
 Set a granite stone 24x18x6 ins. 12 ins.in ground, alongside raised a mound of stones 5x3 ft. stone marked P.4-2588, also on opposite side W.G.3-2588,  
 Whence a X on a granite rock in place marked: B.R.P.4-2588 bears S.1°E. 19.9 ft. distant,  
 A X on a granite rock in place marked B.R.W.G.3-2588 bears N.23°W. 7:4 ft. distant,

Thence N. 74° 30' W.

300  
600

To N.C.E. which is also the S.C.E. WINIFORD GOULD Lode of this survey, identical with loc. a mon.of stones 2ft. base 1-1/2 ft.high,  
 Set a granite stone 24x18x3 ins. 12 ins.in ground, alongside raised a mound of stones 3x3 ft. stone marked N.C.E.P.2583 and on opposite side S.C.E.W.G.2583,  
 To cor.No.1 the place of beginning the survey of exterior boundaries,

WINIFORD GOULD LODE.  
 Beginning at cor.No.1 identical with cor.of loc. a mon.of stones 2ft. base 1-1/2ft. high,  
 Set a porphyry stone 24x15x3 ins. 12 ins.in ground

THE MOUNTAIN VIEW

BRIDGE No. 2583



SURVEY No. 2588.  
WINIFORD GOULD LODE.

Feet.	
3-53 2'8"	<p>Alongside raised a mound of stones 3x3 ft. stone marked W.G.1-2588,            Whence a X on an Oak 6 ins. diam. marked B.T.W.G.1-2588 bears S. 51° 15' E. 10.3 ft. distant,            A X on an Oak 8 ins. diam. marked B.T.W.G.1-2588 bears N. 25° 39' W. 14.1 ft. distant,            U.S.M.M. No. 1 Hanyaya N.D. bears N. 51° 38' W. 57.37.3 ft. distant,</p>
	<p>Thence S. 15° 30' W.</p>
1440	<p>To cor. No. 3 which is also cor. No. 1 PENOBSCOT Lode of this survey, cor. described above,</p>
	<p>Thence S. 74° 30' E.</p>
300	<p>To S.C.E. which is also the N.C.E. PENOBSCOT Lode of this survey, monument described above,</p>
600	<p>To cor. No. 5 which is also cor. No. 4 PENOBSCOT Lode of this survey, cor. described above,</p>
	<p>Thence N. 15° 50' E.</p>
70	<p>To intersect line 1-2 No. 1 GOULD Lode of this survey at S. 3° 45' E. 318.3 ft. from cor. No. 1,</p>
738	<p>To intersect line 1-4 No. 1 GOULD and line 2-3 SURE THING GOLD Lodes of this survey at S. 26° 15' E. 154 ft. from cor. No. 1 GOULD and cor. No. 2 SURE THING GOLD Lodes of this survey,</p>
1440	<p>To cor. No. 4 identical with cor. of loc. a mon. of stone 2 ft. base 1-1/2 ft. high</p>
	<p>Set a granite stone 2x10x4 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked W.G.4-2588,</p>
	<p>Whence a X on an Oak 6 ins. diam. marked B.T.W.G.1-2588 bears N. 70° 15' E. 16.4 ft. distant,</p>
	<p>A X on an Oak 8 ins. diam. marked B.T.W.G.4-2588 bears S. 36° W. 23.7 ft. distant,</p>
	<p>Cor. No. 6 GOVERNOR Lode, Lot No. 54 bears N. 63° 26' W. 107.2 ft. distant,</p>
	<p>Thence N. 74° 30' W.</p>
234.93	<p>To intersect line 1-3 SURE THING GOLD Lode of this survey at N. 3° 45' E. 755 ft. from cor. No. 2,</p>
300	<p>To N.C.E. identical with N.C.E. of loc. a mon. of stone 2 ft. base 1-1/2 ft. high,</p>
	<p>Set a granite stone 2x10x4 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked N.C.E.W.G.2588,</p>
600	<p>To cor. No. 1 the place of beginning survey of exterior boundaries,</p>

SURE THING GOLD LODE.

Fact.

Beginning at cor.No.1 identical with cor.of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x15x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.G.1-2538,

Whence a line 3 ins. diam. marked B.T.S.G.1-2538 bears S. 10° 15' W. 20.6 ft. distant,

A line 3/4 ins. diam. marked B.T.S.G.1-2538 bears S. 26° W. 71.8 ft. distant,

U.S.L.S.No.1 4338, rampa H.D. bears N. 26° 30' W. 5489.1 ft. distant,

W E 429 S

Thence S. 3° 45' W. 34.0'

497.35

To intersect line 2-3 GOVERNOR Lode Lot No. 54, at N. 75° W. 100.26 ft. from cor.No. 6,

508

To intersect line 1-1 WINIFORD GOULD Lode of this survey at N. 74° 30' W. 1082.93 ft. from cor.No. 4,

1203

To cor.No. 2 which is also cor.No. 1 GOULD Lode of this survey, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a X on a granite rock in place marked S.G. 2-2538 also on opposite side No. 1 G. 1-2538,

Whence a X on a granite rock in place marked B.R.No. 1 G. 1-2538 bears S. 45° 30' W. 21.3 ft. distant,

Thence S. 3° 45' W. 34.0'

137

To intersect line 2-1 WINIFORD GOULD Lode of this survey at S. 15° 30' W. 712 ft. from cor.No. 4,

300

To S.C.E. which is also the N.C.E. No. 1 GOULD Lode of this survey, identical with loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 23x10x8 ins. 14 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.S. 2-2538 also on opposite side N.C.E. No. 1 G. 2538,

300

To cor.No. 3 which is also cor.No. 2 No. 1 GOULD Lode of this survey, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 20x18x8 ins. 15 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.G. 3-2538 also on opposite side No. 1 G. 4-2538,

Whence a X on a granite rock in place marked B.R.S.G. 3-2538 bears N. 17° 45' W. 20.6 ft. distant,

A X on a granite rock in place marked B.R.No. 1 G. 4-2538 bears S. 30° 30' W. 10 ft. distant,

Thence N. 3° 45' E.

126

To cor.No. 1 LIXX No. 2 and cor.No. 2 LIXX No. 1 Lodes of this survey,

To cor.No. 1 identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x18x8 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft., stone marked S.G. 4-2538,

Whence a X on a granite rock in place marked B.R.S.G. 4-2538 bears N. 34° 45' W. 20.6 ft. distant,

300'

WINIFORD GOULD LODE

SECTION No. 2538

5

SURE THING GOLD LODE.

1800  
 300 To N.C.E. identical with loc. a row of stones 3 ft. base 1-1/2 ft. high,  
 Set a granite stone 22x22 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stones marked N.C.E.N.S.1 G.2533.

317.15 To intersect line S-S G.W.L. Lode loc No.1, at 1170  
 543.53 ft. from cor.No.1.

600 To cor.No.1 the place of beginning survey of extension  
 towards N.

No.1 GOLD LODE.

Beginning at cor.No.1 which is also cor.No.2 SURE THING GOLD Lode of this survey, cor. described above,  
 Whence U.S.L.N. No.1 Hassayama N.S. bears N. 30° 58' 51" W. 6810.7 ft. distant,  
 Whence S. 50° 45' W. 11.1 ft. distant.

644.2 To loc. M 475 line S-S G.W.L. Lode of this survey  
 70 ft. from cor.No.1.

645.2 To cor.No.2 GOLD WILDER Lode of this survey.

1500 To cor.No.2 which is also cor.No.1 of THE LAST GOLD LODE of this survey, identical with loc. a row of stones 3 ft. base 1-1/2 ft. high,  
 Set a granite stone 30x30 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stones marked No.1 G.S.2533 also on opposite side L.S.1-2533.

Whence a X on a granite rock in place marked B.R.L.D.1 G.S.2533 bears N. 68° 30' W. 13.8 ft. distant,  
 A X on a granite rock in place marked B.R.L.D.1-2533 bears S. 66° 45' W. 11.1 ft. distant,

Whence S. 66° 45' W.

300 To S.C.E. which is also the N.C.E. of THE LAST GOLD LODE of this survey, identical with loc. a row of stones 3 ft. base 1-1/2 ft. high,  
 Set a granite stone 22x22 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stones marked S.C.E.N.S.1 G.2533 also on opposite side N.C.E.L.D.2533

800 To cor.No.3 which is also cor.No.4 THE LAST GOLD LODE of this survey, identical with loc. a row of stones 3 ft. base 1-1/2 ft. high,  
 Set a X on a granite rock in place marked No.1 G.S.2533 also on opposite side L.S.1-2533.

Whence a X on a granite rock in place marked B.R.L.D.1 G.S.2533 bears N. 51° 45' E. 13.8 ft. distant,  
 A X on a granite rock in place marked B.R.L.D.1-2533 bears N. 51° W. 15.1 ft. distant,

Whence N. 51° W.

500

Thence N. 3° 45' E.

To cor. No. 2 LYNN No. 2 Lode of this survey,  
To cor. No. 3 which is also cor. No. 3 SURE THING GOLD  
Lode of this survey, corner described above;

Thence N. 3° 45' E.

300 To cor. No. 4 which is also cor. No. 4 SURE THING GOLD  
Lode of this survey, corner described above;

400 To cor. No. 5 which is also cor. No. 5 SURE THING GOLD Lode of this survey,  
corner described above; also the place of beginning survey of exterior  
boundary,

\* \* \* \* \*

THE LAST DOLLAR MINE

Beginning at cor. No. 1 which is also cor. No. 2, No. 1  
GOLD Lode of this survey, corner described above,  
Thence S. 76° 30' E. 10.0 ft. to cor. No. 2,  
corner described above;

Thence N. 3° 45' E.

641.0 To cor. No. 3 GOLD MINE and cor. No. 3 HATFIELD MINE  
Lode of this survey,

1500 To cor. No. 4 which is also cor. No. 4 SURE THING GOLD Lode of this  
survey, corner described above; also the place of beginning survey of exterior  
boundary,

Along the line of the above mentioned lode 10 ins. in width,  
along the line of the above mentioned lode 10 ft. along marked  
B.R.S. 1-2533, also an opposite side B.R.S. 1-2533,

Thence a X on a granite rock in place marked B.R.S. 1-  
2533 bears S. 76° 30' E. 10.0 ft. distance, no other bear-  
ings available,

Thence S. 76° 30' E.

300 To cor. No. 5 which is also the N.C.M. MINE Lode of this  
survey, marked with loc. 2, corner of stone 10 ft. high  
1-1/2 ft. high,

Along the line of the above mentioned lode 10 ins. in width,  
along the line of the above mentioned lode 10 ft. along marked  
B.R.S. 1-2533 on opposite side B.R.S. 1-2533.

300 To cor. No. 6 which is also the N.C.M. MINE Lode of this  
survey, marked with loc. 3, corner of stone 10 ft. high  
1-1/2 ft. high,

Along the line of the above mentioned lode 10 ins. in width,  
along the line of the above mentioned lode 10 ft. along marked  
B.R.S. 1-2533 on opposite side B.R.S. 1-2533.

Thence N. 3° 45' E.

1500 To cor. No. 4 which is also cor. No. 4 No. 1 GOLD Lode of  
this survey, corner described above,

SURE THING GOLD MINE

LYNN No. 2 LODE

SURVEY No. 2588.

THE LAST DOLLAR MINE.

Foot. 300 To S.C.E. which is also the U.C.E. of this survey, monument described above,  
 400 To cor. No. 1, the place of beginning survey of exterior boundaries.

To S.C.E. which is also the U.C.E. of this survey, monument described above,  
 Thence S. 3° 45' W. 9419.2 ft. distant, 19' 12" W.

To cor. No. 3 MARKER BLADE Ledge of this survey,  
 To cor. No. 2, whence original cor. of loc. bears S. 3° 45' W. 337 ft. distant, a mon. of stone 3 ft. base 1-1/2 ft. high of a granite stone 24x10x5 ins. 12 in. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.S. 2588,  
 a X on a granite rock in place marked P.M. 2-3387 bears S. 30° 15' W. 7.8 ft. distant,  
 a X on a granite rock in place marked P.M. 2-3387 bears S. 30° 30' W. 11.4 ft. distant.

To S.C.E. whence original cor. of loc. bears S. 3° 45' W. 337 ft. distant,  
 Set a granite stone 24x8x6 ins. 12 inc. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.S. 2588,  
 To cor. No. 3 whence original cor. of loc. bears S. 3° 45' W. 337 ft. distant,  
 Set a granite stone 24x10x5 ins. 12 in. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.S. 2588, no bearings available,

To cor. No. 4 which is also cor. No. 3 THE LAST DOLLAR MINE of this survey, cor. described above,  
 Thence N. 30° 15' E.

To N.C.E. which is also the U.C.E. of THE LAST DOLLAR MINE of this survey, mon. described above,  
 To cor. No. 1 the place of beginning survey of exterior boundaries.

\* \* \* \* \*



Feet.

GOLD WEDGE LODGE.

Beginning at cor. No. 1 identical with cor. of loc. 2 mon. of side 2 ft. base 1-1/2 ft. high,

Set a granite stone 30x15x10 ins. 15 ins. in ground, stone marked X for cor. point and on N. side <sup>G.W.</sup> X. 1-2533

Whence a X on a granite rock in place marked X. 2. 1-2533 bears S. 13° 30' W. 10.2 ft. distant, <sub>G.W.</sub>

U.S.M.M. No. 1 Hassayampa I.D. bears N. 13° 0' 24" W. 10.2 ft. distant,

Thence S. 13° 30' W.

To cor. No. 3 NEWTON GOLD and cor. No. 4 PENOBSCOT Lode of this survey,

To cor. No. 2 which is also cor. No. 1 YANKEE BLADE Lode of this survey, identical with cor. of loc. 2 mon. of stones 2 ft. base 1-1/2 ft. high.

Cut a X on a granite rock in place marked G.W. 3-2533 on S. side Y. 3. 1-2533 alongside raised a mound of stones 3x3 ft. no bearings available,

Whence a X on a granite rock in place marked G.W. 3-2533 on S. side Y. 3. 1-2533 alongside raised a mound of stones 3x3 ft. no bearings available,

Thence S. 13° 30' W.

153.6 To S.C.E. which is also the N.C.E. Yankee Blade lode of this survey, mon. des. above.

To cor. No. 2 which is also cor. No. 1 YANKEE BLADE Lode of this survey, identical with cor. of loc. 2 mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 30x15x10 ins. 15 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked G.W. 3-2533 on opposite side Y. 3. 1-2533, no bearings avail-

Thence N. 5° 45' E.

644.7 To cor. No. 1 of THE EAST DOLLAR LODE and cor. No. 2 of No. 1 GOLD Lodes of this survey,

1499 To cor. No. 4 identical with cor. of loc. 2 mon. of stones 2 ft. base 1-1/2 ft. high,

Cut a X for cor. point on same stone set for cor. No. 1 on N. side of X marked G.W. 4-2533,

Whence a X on a granite rock in place marked G.W. 4-2533 bears N. 34° E. 12.3 ft. distant, no other bearings available,

Thence N. 30° 33' W.

0.5 To cor. No. 1 the place of beginning survey of branch of main lode,

\* \* \* \* \*

YANKEE BLADE LODE

Beginning at cor. No. 1 which is also cor. No. 2 of the GOLD WEDGE Lode of this survey, cor. described above,

Whence U.S.M.M. No. 1 Hassayampa I.D. bears N. 13° 6' 24" W. 8481.9 ft. distant,

THE FIRST BRANCH OF THE

YANKEE BLADE LODE

# **POOR QUALITY**

**The following pages are scanned at the best possible quality setting. The original pages are of poor quality and this is the best possible reproduction.**

SURVEY No. 2588.

YANKEE BLADE LODGE.

23 Feet.

COL. No. 1 SURE THING GOLD LODE ...  
Thence S. 15° 40' W.

70  
1700

To cor. No. 3 TELEBOGOT and cor. No. 4 FRANKLIN Lodes of  
this survey.  
To cor. No. 3 identical with cor. of loc. a mound of stones  
2 ft. base 1-1/2 ft. high.  
Set a granite stone 24x8x6 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
Y.B. 2-2588,  
Thence on Oak 5 ins. diam. marked B.T.Y.B. 2-2588 bears  
N. 89° 15' E. 14.8 ft. distant,  
On Oak 5 ins. diam. marked B.T.Y.B. 2-2588 bears N. 0° 45'  
15.0 ft. distant,

Thence S. 30° 52' E.

300

To S.C.E. identical with loc. a mound of stones 2 ft.  
base 1-1/2 ft. high,  
Set a granite stone 24x8x6 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
S.C. Y.B. 2588,

599.7

To cor. No. 3 identical with cor. of loc. a mound of stones  
2 ft. base 1-1/2 ft. high,  
Set a granite stone 24x8x6 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
Y.B. 3-2588, no bearings available,

Thence N. 3° 45' E.

574.2

To cor. No. 1 SURE THING and cor. No. 2 SURE THING GOLD LODE  
Lodes of this survey,

1450

To cor. No. 4 which is also cor. No. 5 of the GOLD WEDGE  
Lode of this survey, see description above,  
Thence N. 80° 22' W.

153.6

To N.C.E., which is also the S.C.E. Gold Wedge lode of  
this survey, identical with loc. a mon. of stones 2 ft.  
base, 1 1/2 ft. high. ~~xxxxxxxxxxxxxxxxxxxxxxxx~~ Set a granite stone  
24 x 8 x 6 ins 12 ins. in ground, alongside raised a mound  
of stones 3x3 ft., stone marked N.C.E. Y.B. 2588, and on opposite

307.2

To cor. No. 1 the place of beginning the survey of ex-  
terior boundaries,

side S.  
G.W. 2588

LYNX No. 1 LODGE.

Beginning at cor. No. 1 identical with cor. of loc. a  
mound of stones 2 ft. base 1-1/2 ft. high,  
Set a granite stone 24x8x6 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
L.Y. 1, 1-2588,

Thence on a granite rock in place marked B.T.Y. No. 1  
1-2588 bears N. 73° 15' E. 14.8 ft. distant,  
U.S.P.M. No. 1 Haggypa N.D. bears N. 82° 55' E. 14.8  
ft. distant,

Thence S. 3° 45' W.

1840

236

To cor. No. 4 SURE THING GOLD Lode of this survey,



Pest.

1440

12. To cor. No. 2 which is also cor. No. 1 LYNX No. 2 Lode of  
 this survey, identical with cor. of loc. a mon. of stones  
 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x6 ins. 15 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 L.N.E.L. No. 1, 2588, on opposite side L.N.E.L. No. 2, 2589.

Trace N. 89° 15' E. 100 ft. distant.

Set a granite stone 24x12x6 ins. 15 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 L.N.E.L. No. 1, 2588, on opposite side L.N.E.L. No. 2, 2589.

Thence N. 89° 15' E.

500

To N.C.E. which is also the N.C.E. of LYNX No. 2 Lode  
 of this survey, a mon. of stone 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x6 ins. 15 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 S.C.E.L. No. 1, 2588, on opposite side N.C.E.L. No. 2, 2588

600

To cor. No. 3 which is also cor. No. 4 LYNX No. 2 Lode of  
 this survey, identical with cor. of loc. a mon. of stones  
 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x6 ins. 15 ins. in ground,  
 alongside raised mound of stones 3x3 ft. stone marked  
 L.N.E.L. No. 1, 2588, on opposite side L.N.E.L. No. 2, 2589, no bearing

Thence N. 89° 15' E.

400

1440

To cor. No. 1 identical with cor. of loc. a mon. of stones  
 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x6 ins. 15 ins. in ground,  
 alongside raised mound of stones 3x3 ft. stone marked  
 L.N.E.L. No. 1, 2588, no bearing

Thence N. 89° 15' E.

300

To N.C.E. identical with N.C.E. of loc. a mon. of  
 stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x6 ins. 15 ins. in ground,  
 alongside raised mound of stones 3x3 ft. stone marked  
 N.C.E.L. No. 1, 2588,

600

To cor. No. 1 the place of beginning survey of interior  
 boundaries,

LYNX No. 2 LODE.

Beginning at cor. No. 1 which is also cor. No. 3 LYNX  
 No. 2 Lode of this survey, loc. described above,

Thence U. 71° 45' 17" W. 100 ft. distant.

71° 45' 17" W

Thence S. 3° 45' E.

55

To cor. No. 3 SURE THING GOLD and cor. No. 4 No. 1 GOOLD

AMERICAN PATENT

MINING

37

SURVEY No. 2568.

LYNX NO.2 LODE.

Feet.	1500
	<p>1500 To cor. No. 2 identical with cor. of loc. 2 mon. of stones 2 ft. base 1-1/2 ft. high, Set a granite stone 24x18x2 ins. 12 in. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.S. No. 2, 2568;</p> <p>Place X on a granite rock in place marked B.R.L. No. 2, 2-2568 bears S. 65° 30' E. 7.5 ft. distant,</p> <p>Place Y on a granite rock in place marked B.R.L. No. 2, 2-2568 bears N. 75° 30' W. 9. ft. distant,</p> <p>Place Z on a granite rock in place marked B.R.L. No. 2, 2-2568 bears N. 75° 30' W. 9. ft. distant,</p> <p>Place A on a granite rock in place marked B.R.L. No. 2, 2-2568 bears S. 17° E. 10.6 ft. distant,</p> <p>Place B on a granite rock in place marked B.R.L. No. 2, 2-2568 bears N. 62° E. 18.6 ft. distant,</p> <p>U.S.M.M. No. 1 Hassayampa H.D. bears N. 31° 51' 20" W. 6810 ft. distant,</p> <p>Distance S. 2° 15' E.</p>
300	<p>300 To cor. No. 3 identical with cor. of loc. 2 mon. of stones 2 ft. base 1-1/2 ft. high, Set a granite stone 24x18x2 ins. 12 in. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.S. No. 2, 2568,</p>
600	<p>600 To cor. No. 3 identical with cor. of loc. 2 mon. of stones 2 ft. base 1-1/2 ft. high, Set a granite stone 24x18x2 ins. 12 in. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.S. No. 2, 2568;</p> <p>Place X on a granite rock in place marked B.R.L. No. 2, 2-2568 bears S. 65° 30' E. 7.5 ft. distant,</p> <p>Place Y on a granite rock in place marked B.R.L. No. 2, 2-2568 bears N. 75° 30' W. 9. ft. distant,</p> <p>Place Z on a granite rock in place marked B.R.L. No. 2, 2-2568 bears N. 75° 30' W. 9. ft. distant,</p> <p>Place A on a granite rock in place marked B.R.L. No. 2, 2-2568 bears S. 17° E. 10.6 ft. distant,</p> <p>Place B on a granite rock in place marked B.R.L. No. 2, 2-2568 bears N. 62° E. 18.6 ft. distant,</p> <p>U.S.M.M. No. 1 Hassayampa H.D. bears N. 31° 51' 20" W. 6810 ft. distant,</p> <p>Distance S. 2° 15' E.</p>
410	<p>410 To cor. No. 3 under half of this survey,</p> <p>Distance N. 26° 15' W. 2500 ft.</p>
1500	<p>1500 To cor. No. 3 under half of this survey,</p> <p>Distance N. 26° 15' W. 2500 ft.</p>
300	<p>300 To N.C.E. which is also the S.C.E. of LYNX No. 1 Lode of this survey, mon. described above;</p>
600	<p>600 To cor. No. 1 the place of beginning survey of exterior boundaries. 1000 ft. distant from 300 ft. mark;</p>
1500	<p>1500 Beginning at cor. No. 1 which is also cor. No. 2 COMEY Lode of this survey, identical with cor. of loc. 2 mon. of stones 2 ft. base 1-1/2 ft. high.</p> <p>Set a granite stone 24x18x2 ins. 12 in. in ground alongside raised a mound of stones 3x3 ft. stone marked H. 1-2568, on opposite side C. 2-2568,</p> <p>Place X on a granite rock in place marked B.R.H. 1-2568 bears S. 17° E. 10.6 ft. distant,</p> <p>Place Y on a granite rock in place marked B.R.C. 2-2568 bears N. 62° E. 18.6 ft. distant,</p> <p>U.S.M.M. No. 1 Hassayampa H.D. bears N. 31° 51' 20" W. 6810 ft. distant,</p> <p>Distance S. 2° 15' E.</p>

Feet.

Thence S. 5° 45' W.

410 To cor.No.3 LYNX No.1 and cor.No.4 LYNX No.2 Lodes of  
 1500 this survey, identical with cor. of loc. a mon. of stones  
 2 ft. base, 1-1/2 ft. high.  
 Set a granite stone 24x10x8 ins. 12 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 H.3-2588, no bearings available.

Thence S. 86° 15' E.

500 To S.C.E. identical with S.C.E. of loc. a mon. of stones  
 2 ft. base 1-1/2 ft. high,  
 Set a granite stone 24x12x10 ins. 12 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 S.C.E.H.2588,

600 To cor.No.3 identical with cor. of loc. a mon. of stones  
 2 ft. base 1-1/2 ft. high,  
 Set a granite stone 30x18x8 ins. 15 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 H.3-2588,

Thence a X on a granite rock in place marked D.R.H.  
 3-2588 bears S. 86° E. 25.7 ft. distant,

A X on a granite rock in place marked P.R.H.3-2588  
 bears S. 21° E. 21 ft. distant,

Thence N. 7° 45' E.

1040 To cor.No.1 BRUCE and cor.No.2 THE UNION Lodes of  
 1500 this survey,  
 To cor.No.4 which is also cor.No.5 COMET Lode of this  
 survey, identical with cor. of loc. a mon. of stones 2 ft.  
 base 1-1/2 ft. high,  
 Set a granite stone 24x20x8 ins. 12 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 H.4-2588, on opposite side C.S-2588,  
 A X on a granite rock in place marked E.R.H.4-2588  
 bears S. 55° 15' W. 50.3 ft. distant, no other bearings  
 available,

Thence N. 86° 15' W.

1000 To N.C.E. which is also the S.C.A. COMET Lode of this  
 survey, identical with location, a mon. of stones 2 ft.  
 base, 1-1/2 ft. high.  
 Set a granite stone 24x10x8 ins. 12 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 N.C.E.H.2588 and on opposite side S.C.E.C.2588,

To cor.No.1 the place of beginning, survey of exterior  
 boundaries,

COMET LODES

Beginning at cor.No.1 which is also cor.No.2 DANIELA  
 1200 lode of this survey, identical with cor. of loc. a mon.  
 of stones 2 ft. base 1-1/2 ft. high,

1500 Set a granite stone 28x15x8 ins. 14 ins. in ground,

LYNX No. 3

LYNX No. 4

SURVEY No. 2588.

COMET LODE.

Feet.

alongside raised a mound of stones 3x3 ft. stone marked  
 P.T. 1-2588, on opposite side M. 2-2588,  
 whence a X on a granite rock in place marked P.R.C. 1-  
 2588 bears S. 19° W. 28.4 ft. distant,  
 whence a X on a granite rock in place marked B.R.M. 2-2588  
 bears S. 33° E. 10.6 ft. distant,  
 U.S.M.M. No. 1 Hassayampa H.D. bears N. 40° 44' 13" W.  
 2658.3 ft. distant,

Thence C. 3° 45' W.

470 To cor. No. 1, LYNN No. 1 Lode of this survey,  
 1500 To cor. No. 3 which is also cor. No. 1 HONDO Lode of this  
 survey, cor. described above,

Thence S. 80° 15' E.

300 To S.C.E. which is also N.C.E. of HONDO Lode of this  
 survey, mon. described above,  
 600 To cor. No. 3 which is also cor. No. 4 HONDO Lode of this  
 survey, cor. described above,

Thence H. 3° 45' E.

1040 To cor. No. 1 M.P. UNION and cor. No. 2 HONEY DAVIS Lodes of  
 this survey,

1500 To cor. No. 4 which is also cor. No. 3 MANILLA Lode of  
 this survey, identical with cor. of loc. a mon. of stones  
 3 ft. base 1-1/2 ft. high,

Set a granite stone 8x12x8 ins. 12 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 C. 4-2588, on opposite side M. 3-2588,  
 whence a X on an Oak 10 in. diam. marked B.T.C. 4-2588  
 bears S. 5° E. 21.1 ft. distant,

Thence N. 86° 15' W.

1300 300 To N.C.E. which is also the S.C.E. of Manilla Lode of  
 this survey, identical with loc. c mon. of stones 3 ft.  
 base 1-1/2 ft. high,

Set a granite stone 8x6x6 ins. 12 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 H.C.E.C. 2588, on opposite side F.C.E.M. 2588,

600 To cor. No. 1 the place of beginning survey of exterior  
 boundaries,

\* \* \* \* \*

MANILLA LODGE.

Beginning at cor. No. 1 identical with cor. of loc. a mon.  
 of stones 3 ft. base 1-1/2 ft. high,

1300 Set a granite stone 8x10x8 ins. 12 ins. in ground,  
 alongside raised a mound of stones 3x3 ft. stone marked  
 M. 1-2588,

1500 Whence a X on a granite rock in place marked B.R.M.  
 1-2588 bears S. 76° 15' W. 29 ft. distant,

U.S.M.M. No. 1 Hassayampa H.D. bears N. 49° 14' 13" W.  
 4352.4 ft. distant,

Handwritten initials or mark at the bottom left corner.

16.

Feet.

1500

To cor.No.2 which is also cor.No.1 COMET Lode of this survey, cor. described above,

Thence S. 15° 21' E.

Thence S. 86° 15' E.

300

To S.C.E. which is also the N.C.E. of COMET Lode of this survey, mon. described above,

600

To cor.No.3 which is also cor.No.4 COMET Lode of this survey, cor. described above,

Thence N. 15° 21' W.

1500

To cor.No.4 identical with cor. loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x8x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked M.4-2588, no bearings available,

Thence N. 86° 15' W.

300

To N.C.E. identical with loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Cut a X on a granite rock in place marked N.C.E.M. 2588, alongside raised a mound of stones 3x3 ft.

600

To cor.No.1 the place of beginning survey of exterior boundaries.

\* \* \* \* \*

Mount DAVIS LODE.

Beginning at cor.No.1 identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 30x15x8 ins. 15 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked Mt.D.1-2588,

Whence a X on a granite rock in place marked B.R.M. D.1-2588 bears S. 54° 30' E. 7.5 ft. distant,

U.S.M.M. No.1 Hassayampa M.D. bears N. 52° 58' W. 5460.7 ft. distant,

Thence S. 3° 45' W.

1040

To cor.No.3 MINERLA and Cor.No.4 COMET Lodes of this survey,

1500

To cor.No.2 which is also cor.No.1 Mt. UNION Lode of this survey, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x12x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked Mt.D.2-2588 and on opposite side Mt.U.1-2588,

Whence a X on a granite rock in place marked B.R.M. U.1-2588 bears S. 59° 15' E. and 2.6 ft. distant, no other bearings available,

COMET LODE

MONUMENT No. 2588

SURVEY No. 2588.

MOUNT DAVIS LODE.

Feet  
 100  
 200  
 300  
 400  
 500  
 600  
 700  
 800  
 900  
 1000  
 1100  
 1200  
 1300  
 1400  
 1500  
 1600  
 1700  
 1800  
 1900  
 2000  
 2100  
 2200  
 2300  
 2400  
 2500  
 2600  
 2700  
 2800  
 2900  
 3000

To S.C.E. which is also N.C.E. of UNION Lode of this survey, identical with loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x10x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E. Mt. D. 2588, on opposite side N.C.E. Mt. U. 2588,

To cor. No. 3 which is also cor. No. 4 of UNION Lode of this survey, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 22x12x12 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked Mt. D. 3-2588, on opposite side Mt. U. 4-2588,

Whence a X on a granite rock in place marked B.R. Mt. D. 3-2588 bears N. 62° 45' W. 39.6 ft. distant,

A X on a granite rock in place marked B.R. Mt. U. 4-2588 bears S. 4° 45' E. 31.5 ft. distant,

Thence N. 3° 45' E.

To cor. No. 4 identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x13x5 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked Mt. D. 4-2588, no bearings available,

Thence N. 36° 15' E.

To N.C.E. identical with loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Cut a X on a granite rock in place marked N.C.E. Mt. D. 2588 alongside raised a mound of stones 3x3 ft.

To cor. No. 1 the place of beginning survey of exterior boundaries.

\* \* \* \* \*

MT. UNION LODE.

Beginning at cor. No. 1 which is also cor. No. 3 MOUNT DAVIS Lode of this survey, cor. described above,

Whence U.S.M.M. No. 1 Haseycampa N.D. bears N. 41° 41' W. 3407.9 ft. distant,

Thence S. 3° 45' W.

To cor. No. 3 COMET and Cor. No. 4 HONEY Lodes of this survey,

To cor. No. 2 which is also cor. No. 1 SPRUCE Lode of this survey, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Cut a X on a granite rock in place marked Mt. U. 2-2588 and on opposite side S. 1-2588, no bearings available.

Thence S. 36° 15' E.

To S.C.E. which is also the N.C.E. SPRUCE Lode of this

18.

Thence S. 30. 38. W.

survey, identical with loc. a mon. of stones 2 ft. base, 1-1/2 ft. high,

Set a granite stone 24x14x3 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.P. 2588, on opposite side N.C.E.S. 2588,

To cor. No. 3 which is also cor. No. 4 SPRUCE Lode of this survey, identical with cor. loc. a mon. of stones 2 ft. base 1-1/2 ft. high

Set a granite stone 24x15x3 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S. 2-2588 and on opposite side S. 4-2588,

Thence a X on a granite rock in place marked B.R. N. U.S.-2588 bears N. 19° W. 12 ft. distant,

A X on a granite rock in place marked B.R. S. 4-2588 bears S. 74° 45' W. 6.7 ft. distant,

Thence N. 3° 45' E.

SPRUCE LODE

To cor. No. 4 which is also cor. No. 3 MOUNT DAVIS Lode of this survey, cor. described above,

Thence N. 30° 15' W.

To H.C.P. which is also the S.C.E. of MOUNT DAVIS Lode of this survey, mon. described above,

To cor. No. 1 the place of beginning survey of exterior boundaries,

SPRUCE LODE

Beginning at cor. No. 1 which is also cor. No. 2 MOUNT DAVIS Lode of this survey, cor. described above,

Whence U.S.M.M. No. 1 Haseyampa H.D. Bears N. 33° 31' 51" W. 7536.5 ft. distant,

Thence S. 3° 45' W.

To cor. No. 3 MONROE Lode of this survey,

To cor. No. 2, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Cut a X on a granite rock in place marked S. 2-2588, alongside raised a mound of stones 3x3 ft.

Thence S. 33° 45' E.

To S.C.E. identical with S.C.E. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 24x10x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.C.E.P. 2588,

To cor. No. 3 identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,

Set a granite stone 30x8x3 ins. 15 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked

MOUNT DAVIS LODE

Loc. No. 2587

SURVEY No. 2588.

SPRUCE LODGE

Feet  
 1. Whence a X on a granite rock in place marked B.R.S.3-2588 bears N.65°30'W. 19.4 ft. distant,  
 2. CA X on a granite rock in place marked B.R.S.3-2588 bears N.55°15'E. 18.5 ft. distant,

Thence N. 3° 45' E.

1490 To cor. No.4 which is also cor.No.3 of UNION Lode of this survey, cor. described above,

Thence N. 36° 15' W.

300 To N.C.E. which is also the S.C.E. of UNION Lode of this survey, mon. described above,

600 To cor.No.1 place of beginning survey of exterior boundaries.

Variation at all corners 14° 15' E.

\* \* \* \* \*

LOCATION.

This claim is located on unurveyed lands approximately in Township 12 North, Range 1 West, G. & S. R. B. & M., in the Massachusetts Mining District, Yavapai County, Arizona, <sup>in Prescott Forest Reserve,</sup> and is bounded on the North by COVENOR Lode, Lot No. 54; on the East by Lode Claims names unknown, Charles Knowles claimant; on the South by lode claims names unknown, R. E. Sloan and J. P. Robinson claimants; on the West by HARRISON, ALLIGATOR and BIRD TOM Patented Lode Claims, <sup>Survey No. 1588,</sup> patented to Penn American Mining Company, ~~Survey No. 1588 does not adjoin this claim, as there is vacant land intervening.~~

TRUSS VEINS.

- FRANKLIN, extends North 15° 50' E. 1200 feet and S. 159° 30' W. 300 feet from the discovery shaft,
- FRANKLIN No.2 extends N. 1° 45' E. 800 feet and S. 1° 45' W. 680 feet from the discovery cut and shaft.
- The** MOUNTAIN VIEW, extends N. 15° 30' E. 850 feet and S. 15° 30' W. 650 feet from the discovery shaft,
- PENOBSCOT, extends N. 15° 30' E. 535 feet and S. 15° 30' W. 965 feet from the discovery shaft,
- WINIFORD GOULD, extends N. 15° 30' E. 1440 feet from N.C.E. monument,
- SURE-THING GOLD, extends S. 3° 45' W. 1265 feet from the N.C.E. monument,
- No.1 GOULD, extends N. 3° 45' E. 1480 feet and S. 3° 45' W. 120 feet from the discovery shaft,
- THE LAST DOLLAR MINE, extends N. 3° 45' E. 500 feet and S. 3° 45' W. 1000 feet from the discovery shaft,

Handwritten initials or marks at the bottom left corner.



SUMMIT, extends N65°45'E. 800 feet and S.3°45'W. 163 feet from the discovery shaft;

~~YANKEE BLADE extends Northwesterly 1220 feet from the S.C.E. monument;~~

~~GOLD WEDGE extends Northerly 610 feet and Southerly 800 feet from the discovery shaft;~~

LYNX No.1, extends N.5°45'E. 500 feet and S.3°45'W. 940 feet from the discovery shaft;

LYNX No.2, extends N.5°45'E. 40 feet and S.3°45'W. 1480 feet from the discovery shaft;

HONDO, extends N.5°45'E. 450 feet and S.3°45'W. 1050 feet from discovery shaft;

COMET, extends N.5°45'E. 600 feet and S.3°45'W. 900 feet from the discovery shaft;

MANILLA, extends N.15°21'W. 800 feet and S.15°21'E. 700 feet from discovery shaft,

MOUNT DAVIS, extends N.5°45'E. 1050 feet and S.3°45'W. 450 feet from the discovery shaft,

MT. UNION, extends N.5°45'E. 750 feet and S.3°45'W. 750 feet from the discovery shaft,

SPRUCE, extends N.5°45'E. 150 feet and S. 3°45'W. 1340 feet from the discovery shaft,

30 YANKEE BLADE, extends N. 9° 37' E. 1392.5 ft., and S. 9°37' W. ft. from dis. shaft.

GOLD WEDGE, extends N. 9° 37' E. 1491.1 ft. from S.C.E. mon.

\* \* \* \* \*

AREAS.

LYNX No.1 Lode	19.035	Acres
SPRUCE, "	20.523	"
YANKEE BLADE Lode,	14.303	"
GOLD WEDGE Lode	5.263	"
FRANKLIN Lode	20.661	"
PENOBSCOT Lode	20.661	"
FRANKLIN No.2 Lode	20.669	"
THE MOUNTAIN VIEW	11.703	"
No.1 GOLD,	20.661	"
LYNX No.2	20.661	"
HONDO	20.661	"
COMET	20.661	"
MT. UNION	20.661	"
MOUNT DAVIS	20.661	"
THE LAST DOLLAR NINE Lode,	20.661	"
MANILLA Lode	19.524	"
SUMMIT	13.264	"
WINIFORD GOLD	Gross 19.354	Acres
Less conflict with		
SURE THING GOLD, No.1 GOLD,	15.355	"
Gross 17.397	Acres	
Less conflict with		
GOVERNOR, Lot 54.	2.741	"
Net Area,	340.954	"
Total Area Lode Claim,	340.954	"

-21-

Survey No. 2582.

## EXPENDITURE OF FIVE HUNDRED DOLLARS.

I hereby certify that the value of the labor and improvements upon this claim, placed thereon by the claimant and its grantors is not less than Five Hundred Dollars for each location in claim, and that said improvements consist of:

FRANKLIN LODGE, discovery shaft No. 1, which org. from C.C.F. monument N. 15° 30' E., 300 feet.  
Shaft 4 x 6 feet, 80 feet deep.  
Value, \$ 800.00

Tunnel No. 2, which org. from S.C.E. Monument N. 15° 30' E., 1048 ft.  
Tunnel 4 x 7 feet, course N. 15° 30' E., 352 ft., to connect with shaft No. 3 at the 200 ft. level.  
Value, \$3520.00

Shaft No. 3, which org. from N.C.E. Mon., S. 15° 30' W., 100 ft.,  
Shaft 4 x 8 ft. in clear, timbered, double compartment 700 feet deep.  
Value,  
Cost for first 300 feet, \$25.00 per ft., \$12500.00  
Cost for lower 300 ft., \$100 per ft., 20000.00  
Total value of shaft and tunnel No. 2 \$36020.00

Proportionate value of improvements of tunnel No. 2 and Shaft No. 3 of the Franklin Lode, together with shaft No. 2 and tunnel No. 3 of the Comet Lode of this survey, in the amount of \$ 2273.16 is to be credited to the Franklin Lode.

## FRANKLIN No. 2 LODGE:

Discovery cut and shaft No. 1 which org. from N.C.E. Mon. S. 1° 45' W., 820 ft., cut 4 x 20 ft., 10 ft. face, shaft 4 x 6 ft., 10 ft. deep,  
Value, \$ 200.00

Cut No. 2, which org. from N.C.E. Mon., S. 1° 45' W., 625 ft.  
Cut 6 x 18 ft., 10 ft. face,  
Value, \$ 100.00

Proportionate value of improvements of Tunnel No. 2 and Shaft No. 3 of the Franklin Lode, together with shaft No. 2 and tunnel No. 3 of the Comet Lode of this survey, in the amount of \$ 2273.16 is to be credited to the Franklin No. 2 Lode of this survey.

## The MOUNTAIN VIEW LODGE:

Discovery shaft No. 1, which org. from Cor. No. 3, N. 8° 30' W., 120 ft.  
Shaft 4 x 6 ft., 10 ft. deep,  
Value, \$ 100.00

Proportionate value of improvements of Tunnel No. 2 and shaft No. 3 of the Franklin Lode, together with Shaft No. 2 and Tunnel No. 3 of the Comet Lode of this survey in the amount of \$ 2273.16 is to be credited to the Mountain View Lode.

## PENOBSCOT LODGE:

Discovery shaft No. 1, ~~from~~ org. from cor. No. 4 S. 45° W., 615 ft., shaft 4 x 6 ft., 30 ft. deep,  
Value, \$ 300.00

Tunnel No. 2, on small side vein org. N. 79° 30' W., 445 ft. dist., from cor. No. 4.  
Tunnel 4 x 6 ft., course N. 16° 54' E., extending

into the Winiford Gould claim, length of tunnel, 731 ft., 40 ft. of which is to be credited to the Penobscot, Value, \$ 400.00  
 Proportionate value of improvements of Tunnel No.2 and Shaft No.3 of the Franklin Lode, together with shaft No.2 and tunnel No.3 of the Comet Lode of this survey in the amount of \$2273.16 is to be credited to the Penobscot Lode.

WINIFORD GOULD LODE:

Discovery shaft No.1, which brs. from the N.C.E.Mon. S.15°30'W., 290 ft., shaft 4 x 6 ft., 80 ft. deep, Value, \$ 800.00

Shaft No.2, which brs. from Cor.No.3, N.64° W., 450 ft. Shaft 4 x 6 ft., 60 ft. deep, Value, \$ 600.00

No.3  
 Portion of Tunnel No.2 on Penobscot Claim, 31 ft. in length, Value, \$ 810.00

Cut No.4, which brs. from the N.C.E.Mon. S. 21°E., 75 ft. Cut 4 x 20 ft., 10 ft. face, at the end of cut, tunnel 4 x 6 ft., 30 ft. long, to vein, Value, \$ 400.00

Cut No.5, which brs. from the N.C.E.Mon., S.15°30'W., 50 ft. Cut 4 x 15 ft., 10 ft. face, Value, \$ 150.00

Proportionate value of improvements of tunnel No.2 and shaft No.3 of the Franklin Lode, together with shaft No.2 and tunnel No.3 of the Comet Lode of this survey in the amount of \$2273.16 is to be credited to the Winiford Gould Lode.

SURE THING GOLD LODE:

Discovery shaft No.1, which brs. from the N.C.E.Mon., S.3°45'W., 30 ft. dist. Shaft 4 x 6 ft., 10 ft. deep, Value, \$ 100.00

Shaft No.2, which brs. from the S.C.F. Loc. N.3°45' E., 110 ft., Shaft 4 x 6 ft., 12 ft. deep, Value, \$ 120.00

Proportionate value of improvement of Tunnel No.2 and shaft No.3 of the Franklin Lode, together with shaft No.2 and tunnel No.3 of the Comet Lode of this survey in the amount of \$2273.16 is to be credited to the Sure Thing Gold Lode.

NO.1 GOLD LODE:

Discovery shaft No.1, which brs. from S.C.E. Mon. N.3°45'E., 20 ft. Shaft 4 x 6 ft., 10 ft. deep, Value, \$ 100.00

Shaft No.2, which brs. from the N.C.E.Mon., S.3°45'W., 400 ft. Shaft 4 x 6 ft., 20 ft. deep, Value, \$ 200.00

Cut No.3, which brs. from the N.C.E.Mon., S.3°45'W., 360 ft. Cut 4 x 15 ft., 10 ft. face, Value, \$ 150.00

Cut No.4, which brs. from the N.C.E. Mon., S.3°45'W., 270 ft. Cut, 4 x 20 ft. 10 ft. thick, Value, \$ 110.00

Value, \$ 110.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.16 is to be credited to the No. 1 Gould Lode.

*Mine*  
LAST DOLLAR LODE:

Discovery shaft No. 1 which brs. from the N.C.E. mon. S. 3° 45' W., 500 ft. Shaft 4 x 6 ft., 10 ft. deep.

Value, \$ 100.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of Comet lode of this survey in the amount of \$ 2273.16 is to be credited to the Last Dollar *Mine* Lode.

SUMMIT LODE:

Discovery shaft No. 1, which brs. from the S.C.E. Mon. N. 3° 45' E., 163 ft. dist. Shaft 4 x 6 ft., 10 ft. deep.

Value, \$ 100.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin Lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.16 is to be credited to the Summit Lode.

YANKEE BLADE LODE:

Discovery shaft No. 1, which brs. from the S.C.E. Mon. N. 13° E., 30 ft. Shaft 4 x 6 ft., 10 ft. deep.

Value, \$ 100.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.16 is to be credited to the Yankee Blade Lode.

GOLD WEDGE LODE:

Discovery shaft No. 1, which brs. from Cor. No. 2, No. 1 Gould Lode on line 3-4 of Gold Wedge lode, N. 3° 45' E., 644.2 ft. from Cor. No. 3, 230 ft., shaft 4 x 6 ft., 10 ft. deep.

Value, \$ 100.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey, in the amount of \$ 2273.16 is to be credited to the Gold Wedge Lode.

COMET LODE.

Discovery shaft No. 1, which brs. from the N.C.E. mon. S. 3° 45' W., 600 ft., shaft 4 x 6 ft., 50 ft. deep.

Value, \$ 500.00

Shaft No. 2, which brs. from the S.C.E. Mon. N. 15° W., 330 ft., shaft 4 x 8 ft., double compartment, timbered, 190 ft. deep. At first level, cross cut to west 4 x 6 ft. 40 ft. long; at 180 ft. level, cross cut to west 4 x 6 ft. 40 ft. long. Drift to North 4 x 6 ft., 60 ft. long, and drift to south 4 x 6 ft., 30 ft. long.

Value, \$ 5500.00

Tunnel No. 3, which brs. from the S.C.E. mon. N. 42° W., 220 ft., tunnel 4 x 6 ft., course N. 21° 42' E., to connect with shaft <sup>No. 2</sup> 167 ft. long.

Value, \$ 1670.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.16 is to be credited to the Comet Lode.

LYNX NO. 1. LODE:

Discovery shaft No. 1, which hrs. from N.C.E. Mon. S. 3°45'W., 500 ft., shaft 4 x 6 ft., 30 ft. deep.

\$800.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.18 is to be credited to the LYNX No. 1 lode.

LYNX NO. 2 LODE.

Discovery cut No. 1, which hrs. from N.C.E. Mon. S. 3°45'W., 40 ft., cut 4 x 20 ft., 10 ft. face.

Value,

\$100.00

Approach for cross cut tunnel No. 2, which hrs. from Cor. No. 4, S. 3°45'W., 500 ft., approach 4 x 20 ft., 10 ft. face.

Value,

\$100.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.18 is to be credited to the LYNX No. 2 lode.

HONDO LODE:

Discovery shaft No. 1, which hrs. from N.C.E. Mon. S. 3°45'W., 450 ft., shaft 4 x 6 ft., 10 ft. deep.

Value,

\$100.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.18 is to be credited to the Hondo lode.

SPRUCE LODE:

Discovery shaft No. 1, which hrs. from the N.C.E. Mon. S. 3°45'W., 150 ft., shaft 4 x 6 ft., 10 ft. deep,

Value,

\$100.00

Shaft No. 2, which hrs. from Cor No. 2 East 470 ft., shaft 4 x 6 ft., 50 ft. deep,

Value,

\$500.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.18 is to be credited to the Spruce lode.

MT. UNION LODE:

Discovery shaft No. 1, which hrs. from the S.C. Mon. N. 3°45'E., 750 ft., shaft 4 x 6 ft., 10 ft. deep,

Value,

\$100.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.18 is to be credited to the Mt. Union lode.

MOUNT DAVIS LODE:

Discovery shaft No. 1, which hrs. from the S.C.E. Mon. N. 3°45'E., 450 ft. shaft 4 x 6 ft., 10 ft. deep.

Value,

\$100.00

Tunnel No. 2, which hrs. from cor. No. 5 N. 25°W., 1090 ft. Approach to tunnel, 4x30 ft. 15 ft. face, tunnel 4 x 6 ft. 70 ft. 10 ft. course 35 ft.

Value,

\$850.00

Proportionate value of improvements of tunnel No. 2 and shaft No. 3 of the Franklin lode, together with shaft No. 2 and tunnel No. 3 of the Comet lode of this survey in the amount of \$ 2273.18 is to be credited to Mount Davis lode.

## MANILLA LODGE:

Discovery shaft No. 1, which hrs. from the S.C.E.  
 Mon. N. 15° 21' W., 700 ft., shaft 4 x 6 ft., 10 ft. deep.  
 Value, \$100.00

Tunnel No. 2, which hrs. from Cor. No. 1, S. 58° 15'  
 E., 370 ft.  
 Approached to tunnel 4 x 50 ft., 10 ft. face,  
 tunnel, 4 x 6 ft., 50 ft. long. At end of tunnel  
 a winze 4 x 6 ft., 10 ft. deep.  
 Value, \$800.00

Cut No. 3, which hrs. from Cor. No. 1, S. 40° 15' E.,  
 290 ft., cut 4 x 6 ft., 50 ft. long, course East  
 12 ft. face. Value, \$200.00

Proportionate value of improvements of tunnel No. 2  
 and shaft No. 3 of the Franklin lode, together with  
 Shaft No. 2 and tunnel No. 3 of the Comet lode of this  
 survey in the amount of \$ 2273.16 is to be credited to  
 the Manilla lode.

Total value of improvements, \$53270.

NOTE: Tunnel No. 2 and shaft No. 3 of the Franklin Lode  
 together with shaft No. 2 and tunnel No. 3 of the Comet  
 lode are common improvements for the benefit of the  
 entire group of claims, and 1/19 part thereof is to  
 be credited to each claim in group.

The topography of the country is such that the entire  
 group can be developed by crosscuts from the different  
 level of shafts No. 3 Franklin and shaft No. 2 Comet  
 Lodes.

-----  
 ADDITIONAL IMPROVEMENTS.

Shaft No. 3 on Franklin Lode,  
 FIRST LEVEL.  
 Running Northerly, 4x6 ft., 100 ft. and Southerly  
 4 x 6 ft., 50 ft.  
 SECOND LEVEL.  
 Running Northerly 4x6 ft., 150 ft.  
 THIRD LEVEL.  
 Running Northerly 4 x 6 ft., 275 ft. and Southerly  
 4 x 6 ft., 175 ft.  
 FOURTH LEVEL.  
 Running Northerly, 4x6 ft., 300 ft., and Southerly  
 4x6 ft., 100 ft.  
 FIFTH LEVEL.  
 Running Northerly, 4x6 ft., 740 ft. and Southerly  
 4x6 ft., 45 ft.  
 SIXTH LEVEL.  
 Running Northerly, 4x6 ft., 125 ft., and Southerly  
 4x6 ft., 275 ft.  
 SEVENTH LEVEL.  
 Running Northerly, 4x6 ft., 300 ft., and Southerly  
 4x6 ft., 175 ft.

STEAM HOIST AND BUILDING, at No. 3 shaft FRANKLIN claim,  
 the S.W. cor. of which bears S. 44° 30' E., 250 ft. from Cor.  
 No. 1.

QUARTZ HILL on PENOBSCOT lode, the E.W. cor. of which hrs.  
 S. 87° E., 310 ft. from Cor. No. 2.

## COMPANY CAMP!

House hrs. N. 51° E., 1020 ft. from cor. No. 2 of WINIFORD  
 GOULD CLAIM.

Office bears N. 46° 30' E., 1060 ft. from same cor.  
 Boarding House bears N. 42° E., 1115 ft. from same  
 corner.  
 Barn bears N. 39° E., 980 ft. from same cor.  
 STEAM HOIST AND BUILDING.  
 At Shaft No. 2 COMET.

INSTRUMENTS.

This survey was made with a transit to obtain Solar  
 Transit. The courses were deflected from the true  
 meridian as determined by solar observation.

The distances were measured with a 50 ft. and 300  
 ft. steel tape.

NOTE.

The disagreement between these field notes and the  
 location certificate of the Mondo and Gold Ledge lodes is  
 due to error in the latter.

Prescott, Arizona,  
 October 3, 1908.

*J. J. Fisher*

Mineral Surveyor.

*Handwritten notes and scribbles:*  
 - *at 10* (top right)  
 - *at 10* (middle right)  
 - *at 10* (bottom right)  
 - *at 10* (middle left)  
 - *at 10* (bottom left)  
 - *at 10* (center)

# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by J. J. Fisher

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of \_\_\_\_\_

Mount Union Consolidated Mining Company,  
known as the Lynx No. 1, Spence, Yankee Block, Gold Wedge, Franklin, Pinoboscot, Franklin No. 2, The Mountain View, No. 1 Gold, Lynx No. 2, Honddo Comet, Mt. Union, Mount Davis, The Last Dollar Mine, Manilla, Summit, Winifred Gould, Something Gold,  
and showing the respective capacities in which they acted.

- E. H. Draper ..... , Chairman.
- Wm Crocker ..... , Chairman.
- Wm Crocker ..... , Axman.
- E. H. Draper ..... , Flagman.

## FINAL OATHS OF ASSISTANTS.

We, E. H. Draper

and Wm Crocker ..... , do solemnly swear that we assisted J. J. Fisher

..... , United States Mineral Surveyor, in marking the corners and surveying

the boundaries of the mining claim of Mount Union Consolidated Mining Company

known as the Lynx No. 1, Spence, Yankee Block, Gold Wedge, Franklin, Pinoboscot, Franklin No. 2, The Mountain View, No. 1 Gold, Lynx No. 2, Honddo, Comet, Mt. Union, Mount Davis, The Last Dollar Mine, Manilla, Summit, Winifred Gould, Something Gold.

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the United States Surveyor-General for Arizona

- E. H. Draper ..... , Chairman.
- Wm. Crocker ..... , Chairman.
- Wm. Crocker ..... , Axman.
- E. H. Draper ..... , Flagman

Subscribed and sworn to by the above-named persons before me this 29<sup>th</sup>

day of September , 1908

J. J. Fisher  
Notary Public

My Commission Expires.  
Sep. 18, 1912.



FINAL OATH OF U. S. MINERAL SURVEYOR.

I, J. J. Fisher, U. S. Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the United States  
Surveyor General for Arizona, dated  
Sep. 19, 1908, I have, in strict conformity to the laws of the  
United States, the official regulations and instructions thereunder, and the instructions  
of said Surveyor General, faithfully and correctly executed the survey of the Mining  
Claim of Mount Union Consolidated Mining Co.  
known as the Lynx No. 1, Lynx No. 2, Sure thing Lead, No. 4, known as the  
The Last Dollar Mine, Summit, Winford Road, Northwest, Franklin  
Franklin No. 2, Mountain Peak, Gold Midge and Yankee Block,  
situate in Hessayampa Mining District,  
Yavapai County, Arizona, in Section  
Approximately, Township No. 12 N., Range No. 1 W. Unsur,  
and designated as Survey No. 2588, as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim  
as distinctly marked by monuments on the ground, and described in the attached copy  
of the location certificate, which was received by me from the Surveyor General with  
said instructions, and that all the corners of said survey have been established and per-  
petuated in strict accordance with the law, official regulations and instructions there-  
under; and I do further solemnly swear that the foregoing are the true and original  
field notes of said survey and my report therein, and that the labor expended and  
improvements made upon said mining claim by claimant or its grantors  
are as therein fully stated, and that the character, extent, location, and itemized value  
thereof are specified therein with particularity and full detail, and that no portion of  
said labor or improvements so credited to this claim has been included in the estimate  
of expenditures upon any other claim.

J. J. Fisher  
U. S. Mineral Surveyor.

Subscribed and sworn to by the said J. J. Fisher  
U. S. Mineral Surveyor, before me, a Notary Public

this 3<sup>rd</sup>  
day of October, 1908. My commission expires  
June 20, 1911.

Seeville  
Notary Public

Affidavit of Five Hundred Dollars Improvements.

We, Wm Crocker, and EH Draper

of lawful age, being first duly sworn according to law, depose and say: That we are acquainted with the <sup>Lynx No 1, Spruce, Yankee Blade, Gold Wedge, Franklin, Penobscot, Franklin No 2, The Mountain View, No 1 & 2</sup> mining claim, <sup>Lynx No 2, Stoneto, Comet, Mt Union, Mount Davis, The Last Dollar mine, Manilla, Summit, Winiford bank, Sure thing Gold,</sup> situate in Assayampa Mining district, Yavapai County, Arizona Territory, for which

Mount Union Consolidated Mining Company

has made application for survey prior to application for patent under the provisions of the Act of Congress, approved May 10, 1872; and that the labor done and improvements made <sup>upon or for each hole claim of this luvy</sup> ~~thereon~~ by the applicant and its grantors exceed Five Hundred Dollars in value, and further that we are not personally interested in said mine.

Wm Crocker  
EH Draper

TERRITORY OF ARIZONA,  
County of Yavapai } ss:

Sworn to and subscribed before me, this 29<sup>th</sup>  
day of September, 1908



J. J. Fisher  
Notary Public

6986500-2-03

My commission expires sep 18<sup>th</sup> 1912

Mount Davis.

Notice of Mining Location. Quartz Claim.

To all Whom it May Concern:

This Mining Claim, the name of which is the Mount Davis Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable Mineral deposits, was entered upon and located for the purpose of exploration and purchase by Theo. B. Comstock, Jeff Lefors and Amos Adams, the undersigned, on the 26th day of May, 1895.

The length of this claim is fifteen hundred feet and we claim eleven hundred feet in a Northerly direction and four hundred feet in a Southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with three hundred feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the South to the North.

The claim is situated and located in Hassayampa Mining District, in Yavapai County, in the Territory of Arizona, about half a mile in a Westerly direction from the Summit of Mount Union, on the western slope thereof.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stone at a point in a Southerly direction four hundred feet from the discovery shaft (at which this notice is posted), going in the center of the Southern end line of said claim; thence Westerly 300 feet to a monument of stone, being the Southwest corner of said claim; thence Northerly 750 feet to a monument of stone at the center of the Western side line of said claim; thence Northerly 750 feet to a monument of stone, being at the Northwest corner of said claim; thence Easterly 300 feet to a monument of stone at the center of the Northern end of said claim; thence Easterly three hundred feet to a monument of stone, being at the Northeast corner of said claim; thence Southerly 750 feet to a monument of stone, being at the center of the Eastern side line of said claim; thence Southerly 750 feet to a monument of stone, at the Southeast corner of said claim; thence Westerly 300 feet to the place of beginning.

All done under the provisions of Chapter six, of Title XXIII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines", approved March 20th 1895.

Dated and posted on the ground this 26th day of May, 1895.

Theo. B. Comstock  
Jeff Lefors  
Amos Adams

Filed and recorded at request of Theo. B. Comstock, June 25<sup>th</sup> A.D., 1895, at 3:25 o'clock P.M., in Book 44 of Mines, pages 419 et seq., records of Yavapai County, Arizona.

By H. O. Archibald (Seal) P. A. Tritle County Recorder.  
Deputy.

1895

Mt Union

## Notice of Mining Location Quartz Claim

To all whom it may concern This mining claim the name of which is the Mt Union Mining claim situate on lands belonging to the United States of America and in which there are valuable mineral deposits was entered upon and located for the purpose of exploration and purchase by W.A.Adams Jeff Lefors and Theo D Comstock the undersigned on the 25th day of May 1896

The length of this claim is Fifteen hundred feet and we claim seven hundred and fifty feet in a northerly direction and seven hundred and fifty feet in a southerly direction from the center of the discovery shaft at which this notice is posted lengthwise of the claim together with three hundred feet in width of the surface grounds on each side of the center of said claim. The general course of the lode deposit and premises is from the North to the South. The claim is located and situated in Crook Canyon Mining District in Yavapai County in the Territory of Arizona, about one mile (more or less) in an easterly direction from Flints Arastra. The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stone with stake at a point in a southerly direction 750 feet from the discovery shaft (at which this notice is posted) being in the center of the south end line of said claim; thence east 300 feet to a monument of stone at side of pine tree, being the south east corner of said claim; thence 750 (northerly) feet to a monument of stone at the center of the Eastern side line of said claim; thence 750 ft northerly to a monument of stone being at the North east corner of said claim; thence 300 ft westerly to a monument of stone at the center of the northern end of said claim; thence westerly 300 feet to a monument of stone being at the North west corner of said claim; thence 750 feet southerly to a monument of stone being at the center of the western side line of said claim thence 750 feet southerly to a monument of stone at the southwest corner of said claim, thence 300 ft easterly to the place of beginning. This is a relocation with same monuments of the Mt Union Claim located May 12 1896 by W.A.Adams and Albert Blair.

All done under the provisions of Chapter Six of Title XXIII of the Revised Statutes of the United States and of an Act of the General Assembly of Arizona entitled "An Act Concerning Mines" approved March 30th 1895

Dated and posted on the ground this 25th day of May 1896.

W.A.Adams  
Jeff. Lefors  
Theo D Comstock

Filed and recorded at request of Theo D Comstock June 6 A M 1896 at 10:05 o'clock A M in Book 44 of Mines pages 388, 389 & 390 Records of Yavapai County, Arizona

(Seal)

F A Tritle  
County Recorder.

1896

SpruceNotice of Location.  
-----

Know all Men by these Presents:

That We the undersigned have this day Located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water privileges thereon or appurtenant thereto, under and according to the United States Mining Laws, under which it is Located.

This claim commences at this Monument and Notice placed upon the ledge, and runs 100 feet in a Northerly direction and 1400 feet in a Southerly direction along the ledge, from discovery shaft.

The Exterior boundaries are as follows, viz:

Commencing at a Monument of Stone on West boundary line, distant Three Hundred (300) feet in a Westerly direction from Discovery Monument; thence in a Northerly direction parallel with the ledge 100 feet to Monument of Stone at N.W. corner of claim; thence in an Easterly direction at right angles across the ledge Six Hundred (600) feet to Monument of Stone at N.E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to Monument of Stone at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to Monument of Stone at S.W. corner of claim; thence in a Northerly direction parallel with the ledge 1400 feet to Monument on West boundary and place of beginning.

This ledge may be more generally described as situated on West side of Mount Union on East prong of Crook Canyon. Bounded on North by Mount Union Mining Claim: 1/2 mile in Westerly direction from Summit of Mount Union in Crook Canyon Mining District, Yavapai County, Arizona Territory; and shall be known as the Spruce Mining Claim.

DATED ON THE GROUND this 1<sup>st</sup> day of January 1897

Joe Hobbs  
Jeff Lefors

Filed at request of Jeff Lefors March 1<sup>st</sup> A.D. 1897, at 12.40 o'clock P.M., in Book 43 of Mines, page 431 Records of Yavapai County, Arizona.

(Seal) W.I. Johnson. County Recorder.

By P.J. Farley Deputy.

FD

"Manilla"

Notice of Location.

-----  
Know all Men by these Presents:

That We the undersigned, have this day Located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Two Hundred (200) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water privileges thereon or appurtenant thereto, under and according to the provisions of the United States Mining Laws, under which it is Located.

This claim commences at this Monument and Notice placed upon the ledge, and runs 750 feet in a Northerly direction and 750 feet in a Southerly direction along the ledge from discovery shaft

The interior boundaries are as follows, viz:

Commencing at a Monument of Stone on West boundary line, distant Three Hundred (300) feet in a Westerly direction from discovery Monument; thence in a Northerly direction parallel with the ledge 750 feet to Monument of Stone at NW. corner of claim; thence in a Northerly direction at right angles across the ledge Six Hundred (600) feet to Monument of Stone at N.E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to Monument of Stone at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to Monument of Stone at S.W. corner of claim; thence in a Northerly direction parallel with the ledge 750 feet to Monument on West boundary and place of beginning.

This ledge may be more generally described as situated on Mt Union about 1000 ft. west of the Mt. Union mine and joining the Buena Ventura mine on the west side and about 3/4 mile east of Storme Cloud mine. Bounded on the west by Flints Patented ground, in Hassayampa Mining District, Yavapai County, Arizona Territory, and shall be known as the Manilla Mining Claim.

DATED ON THE GROUND this 13 day of May 1899

Wm O:Harrell  
Jos Hobbs.

Recorded at request of Wm O. Harrell Aug 14<sup>th</sup> A.D. 1899, at 9 o'clock A.M., in Book 40 of Mines, page 436 Records of Yavapai County, Arizona.

(Seal) W.I. Johnson County Recorder.

By F.B. Walker Deputy.

Handwritten initials or marks at the bottom left corner.

"Comet"

Notice of Mining Location.  
Lode Claim.

To All Whom it May Concern:

This Mining Claim, the name of which is the "Comet" Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by George Mayer and Jeff Lefors the undersigned, on the 30 day of October, 1902.

The length of this claim is fifteen hundred (1500) feet, and we claim Seven hundred and 25 (725) feet, in a northerly direction and Seven hundred and 75 (775) feet in a southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with three hundred (300) feet in width of the surface grounds, on each side of the center of said vein. The general course of the lode deposit and premises is from the northerly to the southerly.

The claim is situated and located in the Mount Union Mining District in Yavapai County, in the Territory of Arizona, about twenty five hundred feet in a South West direction from Summit of Mount Union.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stones at a point in a northerly direction about Seven hundred and twenty five feet from the discovery shaft (at which this notice is posted), being in the center of the North end line of said claim; thence easterly 300 feet to a monument of stones being the North East corner of said claim; thence southerly 1500 feet to a monument of stones being the Southeast corner of said claim; thence westerly 300 feet to a monument of stones at the center of the South end of said claim; thence westerly 300 feet to a monument of stones being at the southwest corner of said claim; thence northerly 1500 feet to a monument of stones being at the northwest corner of said claim; thence easterly 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the revised Statutes of the United States and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines," approved March 20, 1895, and amended March 26, 1899. and March 16, 1901.

Dated and posted on the ground, this 30 day of October 1902

Witness  
A.A. Varney

George L. Mayer  
Jeff Lefors.

Recorded at request of Geo L. Mayer Nov 6 A.D. 1902, at 3:15 o'clock P.M., Book 66 of Mines, Page 210, Records of Yavapai County, Arizona.

By C.M. Dotson (Seal) P.J. Farley County Recorder.  
Deputy Recorder.

PS

"Hondo"

## Notice of Location.

Know all Men by these Presents:

That We the undersigned, have this day Located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water privileges thereon or appurtenant thereto, under and according to the provisions of the United States Mining Laws, under which it is Located.

This claim commences at this Monument and Notice placed upon the ledge, and runs 400 four hundred feet in a Northerly direction and 1100 feet in a Southerly direction along the ledge, from discovery shaft

The Exterior boundaries are as follows, viz:

Commencing at a Monument of Stone on West boundary line, distant Three Hundred (300) feet in a Westerly direction from Discovery Monument; thence in a Northerly direction parallel with the ledge 400 feet to Monument of Stone at N.W. corner of claim; thence in a Easterly direction at right angles across the ledge Six Hundred (600) feet to monument of Stone at N.E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to Monument of Stone at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to Monument of Stone at S.W. corner of claim; thence in a Northerly direction parallel with the ledge 1100 feet to Monument on West boundary and place of beginning.

This ledge may be more generally described as situated West slope of Mount Union and is bounded of the West by the Mount Union and Spruce Mining claims-

Original location dated Dec the 14 1897, in Hassayampa Mining District, Yavapai County, Arizona Territory, and shall be known as the Hondo Mining Claim.

DATED ON THE GROUND this the 9 day of March 1898

Witness:  
I.C.Ray.

Jeff Lefors  
H.P.Dryant

Recorded at request of Jos Hobbs March 11" A.D. 1898, at 4:08 o'clock P.M., in Book 49 of Mines, page 41 Records of Yavapai County, Arizona.

By E.C. Sveryt Deputy (Seal) W.I. Johnson County Recorder.

1898



"Lynx No. 1"Notice of Location.  
-----

Know all Men by these Presents:

That We the undersigned, have this day located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water Privileges thereon or appurtenant thereto, under and according to the provisions of the Mining laws of the United States, under which it is located.

This claim commences at this Monument and Notice placed upon the ledge, and runs Fifteen Hundred (1,500) feet in a Southerly direction along the ledge, from discovery shaft

The interior boundaries are as follows, viz:

Commencing at this Monument and Notice, and running Three Hundred (300) feet in an Easterly direction to monument of stone at N.E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to monument at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to monument at S.W. corner of claim; thence parallel with the lode in a Northerly direction Fifteen Hundred (1,500) feet to monument at N.W. corner of claim; thence at right angles across the ledge in an Easterly direction Three Hundred (300) feet to monument upon the ledge and place of beginning.

This ledge may be more generally described as situated and about 1/2 mile in an South Easterly directions from the old Flint Arastar in the Hasyampia Mining District, Navapai County, Arizona Territory, and shall be known as the Lynx No 1

DATED ON THE GROUND, this 15 day of October 1898

C.C. Fineout  
H.L. Sweeney

Recorded at request of H.L. Sweeney Jan. 12<sup>th</sup> A.D. 1899, at 9:00 o'clock A.M., in Book 36 of Mines, Page 334 Records of Navapai County, Arizona.

(Seal) W.I. Johnson County Recorder.

By E.C. Averett. Deputy.

"Lynx No. 2."Notice of Location.  
-----

Know all Men by these Presents:

That We the undersigned, have this day Located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limit of said claim, and all Water and Water Privileges thereon or appurtenant thereto, under and according to the provisions of the Mining Laws of the United States, under which it is located.

This claim commences at this Monument and Notice placed upon the ledge, and runs Fifteen Hundred (1,500) feet in a Southerly direction along the ledge, from discovery shaft

The Exterior boundaries are as follows, viz:

Commencing at this Monument and Notice, and running Three Hundred (300) feet in an Easterly direction to monument of stone at N.E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to monument at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to monument at S.W. corner of claim; thence parallel with the lode in a Northerly direction Fifteen Hundred (1,500) feet to monument at N.W. corner of claim; thence at right angles across the ledge in an Easterly direction Three Hundred (300) feet to monument upon the ledge and place of beginning.

This ledge may be more generally described as situated about 1/3 of a mile in a Sout\_ Easterly direction from the Old Flint Arastar in the Husayappa Mining District, Yavapai County, Arizona Territory, and shall be known as the Lynx No 2 Mining Claim.

DATED ON THE GROUND, this 15<sup>th</sup> day of October 1898

C.C. Fineout  
H.L. Swoney

Recorded at request of H.L. Swoney Jan 15<sup>th</sup> A.D. 1899, at 9:00 o'clock A.M., in Book 36 of Mines, Page 635 Records of Yavapai County, Arizona.

(Seal) W.I. Johnson County Recorder.

By H.C. Averyt. Deputy.

"Sure thing Gold"

## Notice of Location.

Know all Men by these Presents:

That I the undersigned, have this day located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations; with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim; and all Water and Water Privileges thereon or appurtenant thereto, under and according to the provisions of the Mining Laws of the United States, under which it is located.

This claim commences at this Monument and Notice placed upon the ledge, and runs Fifteen Hundred (1,500) feet in a Southerly direction along the ledge. from discovery shaft.

The Exterior boundaries are as follows, viz:

Commencing at this Monument and Notice, and running Three Hundred (300) feet in an Easterly direction to monument of stone at N.E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to monument at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to monument at S.W. corner of claim; thence parallel with the lode in a Northerly direction Fifteen Hundred (1,500) feet to monument at N.W. corner of claim; thence at right angles across the ledge in an Easterly direction Three Hundred (300) feet to monument upon the ledge and place of beginning.

This ledge may be more generally described as situated 3/4 of a mile East of the Old Crook Mine and joins on to the Flint Group of Mines. in Maricopa Mining District, Yavapai County, Arizona Territory, and shall be known as the Sure thing Gold Mining Claim.

DATED ON THE GROUND, this 1st day of July 1896

Witness  
Frank Wilson.

Lute Wilson

Recorded at request of Lute Wilson March 16<sup>th</sup> A.D. 1896, at 4 o'clock P.M., in Book 38 of Mines, Page 478 Records of Maricopa County, Arizona.

By H.R. Trittle (Seal) Deputy

F.A. Trittle County Recorder.

"No 1 Gould"

## Notice of Location.

-----  
 Know all Men by these Presents:

That I the undersigned, have this day located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water Privileges thereon or appurtenant thereto, under and according to the provisions of the Mining Laws of the United States, under which it is located.

This claim commences at this Monument and Notice placed upon the ledge, and runs Fifteen Hundred (1,500) feet in a Northerly direction along the ledge from discovery shaft

The interior boundaries are as follows, viz:

Commencing at this Monument and Notice, and running Three Hundred (300) feet in an easterly direction to monument at S.W. corner of claim; thence in a northerly direction parallel with the ledge Fifteen Hundred (1,500) feet to monument at N.W. corner of claim; thence in a westerly direction at right angles across the ledge Six Hundred (600) feet to monument at N.E. corner of claim; thence parallel with the lode in a southerly direction Fifteen Hundred (1,500) feet to monument at S.W. corner of claim; thence at right angles across the ledge in an easterly direction Three Hundred (300) feet to monument upon the ledge and place of beginning.

This ledge may be more generally described as situated this claim is 1 mile north of the Newmill in Crook Canyon and about 1/3 quarter of a mile east of the Bliss Claim in Massawahe Mining District, Yavapai County, Arizona Territory, and shall be known as the No 1 Gould Mining Claim.

DATED ON THE GROUND, this 1st day of Jan. 1896

Lute Wilson

Recorded at request of Lute Wilson March 5<sup>th</sup> A.D. 1896, at 2:40 o'clock P.M., in Book 37 of Mines, Page 512 Records of Yavapai County, Arizona.

(Seal)

F.A. Tritle County Recorder.

By H.R. Tritle Deputy.

The Last Dollar Mine

## Notice of Mining Location.

## Lode Claim.

To All Whom it May Concern:

This Mining Claim, the name of which is the The Last Dollar Mine Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by C.W. Finley M.J.Cox and F.R.Mendenhall the undersigned, on the 26th day of August, 1909.

The length of this claim is fifteen hundred feet, and we claim five hundred feet, in a northerly direction and one thousand feet in a southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with three hundred (300) feet in width of the surface grounds, on each side of the center of said vein. The general course of the lode deposit and premises is from the northerly to the southerly

The claim is situated and located in the Hassayampa Mining District in Yavapai County, in the Territory of Arizona, about four hundred feet in an easterly direction from the Franklin mine

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stones at a point in a northerly direction 500 feet from the discovery shaft (at which this notice is posted), being in the center of the north end line of said claim; thence easterly 300 feet to a monument of stones being the north east corner of said claim; thence southerly 1500 feet to a monument of stones being at the south east corner of said claim; thence westerly 300 feet to a monument of stones at the center of the south end of said claim; thence westerly 300 feet to a monument of stones being at the south west corner of said claim; thence northerly 1500 feet to a monument of stones being at the north west corner of said claim; thence easterly 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the revised Statutes of the United States and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines," approved March 20, 1895, and amended March 23, 1899, and March 13, 1901

Dated and posted on the ground, this 26th day of August 1909

C.W.Finley  
M.J.Cox  
F.R.Mendenhall

Recorded at request of E.Greenwood Oct 16, A.D. 1909, at 10:30 o'clock A.M., Book 55 of Mines, Page 137, records of Yavapai County, Arizona.

(Seal) F.J.Farley County Recorder.  
By F.H.Baldwin Deputy Recorder.

J →

Summit

Notice of Mining Location.  
Lode Claim.

To All Whom It May Concern:

This mining claim, the name of which is the Summit Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and locate for the purposes of exploration and purchase by Eugene Greenwood, citizen United States the undersigned, on the 1st day of January 1904

The length of this claim is fifteen hundred (1500) feet, and we claim one thousand (1000) feet in a northerly direction, and five hundred (500) feet in a southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with three hundred (300) feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the northerly to the southerly

The claim is situated and located in the Massayampa Mining District, in Yavapai County, in the Territory of Arizona, about one mile in a southerly direction from Storm Cloud mine and 3/4 mile southwest of the Mt Union Mine

The surface boundaries of the claim are marked upon the ground as follows: Beginning at Monument that is placed oppose the ledge running at a point in a southerly direction one thousand feet from the discovery shaft (at which this notice is posted), being in the center of the ..... ~~end line~~ of said claim; thence five hundred feet to a monument, being the center end corner of said claim; thence westerly direction 300 feet to a monument, being at the southwest corner of said claim; thence fifteen (1500) feet to a monument at the <sup>northwest</sup> center of the ..... end of said claim; thence six hundred (600) feet to a monument, being at the southeast corner of said claim; thence fifteen hundred (1500) feet to a monument at the southeast corner of said claim; thence..... feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.

Dated and posted on the ground this 1st day of January 1904

Wit: Eugene Greenwood  
Matt Hoack

Filed and recorded at request of E. Greenwood Feb. 25 A.D. 1904 at 12:55 o'clock P.M., Book 71 of Mines, page 164 Records of Yavapai County, Arizona.

(Seal) P. J. Farley County Recorder.  
By E. E. Butler  
Deputy Recorder.

Winiford Gould

South End  
Notice of Location.

Know all Men by these Presents:

That I the undersigned, have this day Located ~~Fifteen Hundred~~<sup>1350</sup> linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water privileges thereon or appurtenant thereto, under and according to the provisions of the United States Mining Laws, under which it is Located.

This claim commences at this Monument and Notice placed upon the ledge, and runs 1350 feet in a Northerly direction and ..... feet in a Southerly direction along the ledge. from discovery shaft

The Exterior boundaries are as follows, viz :

Commencing at a Monument of stone on West boundary line, distant Three Hundred (300) feet in a Westerly direction from Discovery Monument; thence in a Northerly direction parallel with the ledge 1350 feet to Monument of Stone at N.W. corner of claim; thence in a Easterly direction at right angles across the ledge Six Hundred (600) feet to Monument of Stone at N.E. corner of claim; thence in ~~1350~~ Southerly direction parallel with the ledge ~~Fifteen Hundred~~ feet to Monument of Stone at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to Monument of Stone at S.W. corner of claim; thence in a Northerly direction parallel with the ledge 1350 feet to Monument on West boundary and place of beginning.

This ledge may be more generally described as situated This claim joins the Pernobscot on the south end and joines the Flint Patented Ground on the north end Also side Lines the Surething on the east side and is about one half Mile from the Crook mine in Crook Canon, in Hass\_yampa Mining District, Navapai County, Arizona territory, and shall be known as the Winiford Gould Mining Claim.

DATED ON THE GROUND this 1. day of October 1899

Witnessed  
L.F. Wilson

Luther Wilson.

Recorded at request of Walter A. Simmons Dec. 19th A.D. 1899, at 3:25 o'clock P.M., in Book 49 of Mines, page 591 Records of Navapai County, Arizona.

(Seal) W.I. Johnson County Recorder.  
By.....Deputy.

pt →

"Penobscot"

Notice of Location,

Of the Penobscot Mining Claim, Under and in accordance with the provisions of an Act of Congress of the United States of America, approved May 10<sup>th</sup>, 1872, and amendments thereto, the undersigned claim for mining purposes 300 hundred, feet in width and 1500 hundred, feet in length along this vein or lode, called the Penobscot mine, and situated in Massarump Mining District, Marapai County, Arizona Territory, said mine or mineral claim is described and bounded as follows to-wit: Running along the ledge or vein from the monument in which this notice (duplicate) is placed 1500 feet Northerly and feet

The exterior boundaries commence at a stone monument on the vein at the Southerly end of the claim; running thence in a Westerly direction, at a right angle with the vein, 300 feet to a Monument; thence Northerly parallel with the vein 1500 feet to a monument; thence Easterly at a right angle with the vein 300 feet to a Monument; thence Southerly parallel with the vein 1500 feet to a Monument; thence Westerly at a right angle with the vein 300 feet to place of beginning. This claim is more particularly described as Situated in Creek Canyon, about one mile Northerly from Scopels astras and joins the Franklin Mine of the North end.

Dated on the ground, this 29 day of September 1890

Witness

Robert Blair Claimant

R.M. Dougherty.

Recorded at request of Robert Blair Dec. 27<sup>th</sup> A.D. 1890 at 2:35 o'clock P.M. in Book 31 of Mines page 5 Records of Marapai County, Arizona

By J. W. Akers  
Deputy

(L.S.)

Charles H. Akers  
County Recorder



Franklin.

## Notice of Location.

Know all Men by these Presents:

That I the undersigned, have this day Located Fifteen Hundred (1500) linear feet of this vein or lode bearing precious metals with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water Privileges thereon or appurtenant thereto, under and according to the provisions of the Mining Laws of the United States, under which it is Located.

This claim commences at this Monument and Notice, placed upon the ledge, and runs Fifteen Hundred (1500) feet in a Northerly direction along the ledge.

The Exterior boundaries are as follows, viz:

Commencing, at this Monument and Notice, and running Three Hundred (300) feet in an easterly direction to monument at S.E. corner of claim; thence in a northerly direction parallel with the ledge Fifteen Hundred (1500) feet to monument at N.E. corner of claim; thence in a westerly direction at right angles across the ledge Six Hundred (600) feet to monument at N.W. corner of claim; thence parallel with the lode in a southerly direction Fifteen Hundred (1500) feet to monument at S.W. corner of claim; thence at right angles across the ledge <sup>in an easterly direction</sup> Three Hundred (300) feet to monument upon the ledge and place of beginning.

This ledge may be more generally described as situated in Crook Canyon East fork of the Hassayampa and 1/2 mile North of Scopel Camp, in Hassayampa Mining District, Navapai County, Arizona Territory, and shall be known as the Franklin Mining Claim,

Dated on the Ground, this 2 day of January 1883.

F. Lawrence.

Recorded at the Request of F. Lawrence Jan. 3d, A.D. 1883 at 25 minutes past 10 o'clock A.M. in Book 24 of Mining Records of Navapai County, Arizona, pages 604-605.

(L.S.)

E. J. F. Morne  
County Recorder.

1883  
→

Franklin No 2

Notice of Location.

Know all Men by these Presents:

THAT we, the undersigned, have this day located fifteen hundred (1500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground three hundred (300) feet on each side of the center of vein, with all mineral deposits contained therein, and all timber growing within the limits of said claim, and all water and water privileges thereon or appertenant thereto, under and according to the provisions of the United States Mining Laws, under which it is located.

This claim commences at this Monument and notice placed upon the ledge, and runs 750 feet in a northerly direction and 750 feet in a southerly direction along the ledge, from discovery shaft.

The exterior boundaries are as follows, viz: Commencing at a monument of stone on west boundary line, distant three hundred (300) feet in a westerly direction from discovery monument; thence in a northerly direction parallel with the ledge 1500 feet to monument of stone at N.W. corner of claim; thence in an easterly direction at right angles across the ledge six hundred (600) feet to monument of stone at N.E. corner of claim; thence in a southerly direction parallel with the ledge fifteen hundred (1500) feet to monument of stone at S.E. corner of claim; thence at right angles across the ledge, in a westerly direction six hundred (600) feet to monument of stone at S.W. corner of claim; thence in a northerly direction parallel with the ledge 750 feet to monument on west boundary Thence easterly 300 feet and place of beginning.

This ledge may be more generally described as situated in Masayampa Mining Dist. on head of Crook Canon and joining Franklin claim on the south and about one mile in a westerly direction from Mt Union in..... Mining District, Yavapai County, Arizona Territory, and shall be known as the Franklin No 2 Mining Claim.

Dated on the ground this Twelfth day of March 1902.

F.R.Mendenhall  
G.W.Finley  
M.J.Cox

Recorded at request of F.R.Mendenhall, April 19<sup>th</sup> A.D. 1902, at 4:10 o'clock P.M., in Book 54 of Mines, Page 176, Records of Yavapai County, Arizona.

(Seal) P.J.Farley County Recorder.

By G.M.Dotson Deputy.

102

The Mountain ViewNotice of Mining Location.  
Lode Claim.

To All Whom it May Concern:

This Mining Claim, the name of which is the The Mountain View Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by Chas W. Finley, M.J. Cox and F.R. Mendenhall the undersigned, on the Twenty-Sixth day of August, 1902

The length of this claim is fifteen hundred (1500) feet, and we claim one thousand (1000) feet, in a northerly direction and five hundred (500) feet in a southerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with three hundred (300) feet in width of the surface grounds, on each side of the center of said vein. The general course of the lode deposit and premises is from the northerly to the southerly

The claim is situated and located in the Massayampa Mining District in Maricopa County, in the Territory of Arizona, about one mile in a south westerly direction from Mount Union and between the Crook and Franklin & Penobscot mines

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stones at a point in a northerly direction one thousand (1000) feet from the discovery shaft (at which this notice is posted), being in the center of the north end line of said claim; thence easterly 500 feet to a monument of stones being the north east corner of said claim; thence southerly 1500 feet to a monument of stones being at the south east corner of said claim; thence westerly 300 feet to a monument of stones at the center of the south end of said claim; thence westerly 300 feet to a monument of stones being at the south west corner of said claim; thence northerly 1500 feet to a monument of stones being at the north west corner of said claim; thence easterly 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XVIII, of the revised Statutes of the United States and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines," approved March 20th, 1895, and amended March 20, 1899, and March 15th, 1901.

Dated and posted on the ground, this 26th day of August 1902

C.W. Finley  
M.J. Cox  
F.R. Mendenhall

Recorded at request of E. Greenwood Oct 16 A.D. 1902, at 10:20 o'clock A.M., Book 55 of Mines, Page 126, Records of Maricopa County, Arizona.

(Seal) P.J. Farley County Recorder.  
By F.R. Baldwin Deputy Recorder.

"Gold Wedge"

Notice of Location.  
-----

Know all Men by these Presents:

That ..... the undersigned, have this day Located Fifteen Hundred (1,500) linear feet of this vein or lode, bearing precious metals, with all dips, spurs, angles and variations, with surface ground Three Hundred (300) feet on each side of the center of vein, with all Mineral Deposits contained therein, and all Timber growing within the limits of said claim, and all Water and Water Privileges thereon or appurtenant thereto, under and according to the provisions of the United States Mining Laws, under which it is Located.

This claim commences at this Monument and Notice placed upon the ledge, and runs 750 feet in a Northerly direction and 750 feet in a Southerly direction along the ledge: from discovery shaft.

The Exterior boundaries are as follows, viz:

Commencing at a Monument of Stone on West boundary line, distant Three Hundred (300) feet in a Westerly direction from Discovery Monument; thence in a Northerly direction parallel with the ledge 750 feet to Monument of Stone at N.W. corner of claim; thence in a Easterly direction at right angles across the ledge Six Hundred (600) feet to Monument of Stone at N.E. corner of claim; thence in a Southerly direction parallel with the ledge Fifteen Hundred (1,500) feet to Monument of Stone at S.E. corner of claim; thence at right angles across the ledge in a Westerly direction Six Hundred (600) feet to Monument of Stone at S.W. corner of claim; thence in a Northerly direction parallel with the ledge 750 feet to Monument on West boundary and place of beginning.

This ledge may be more generally described as situated on Mt Union and bounded on the east by the Mt Union Mine and about one hundred yards West of Joe Hobbs Cabin and about Six hundred feet east of Flints patented ground, in Hassayampa Mining District, Yavapai County, Arizona Territory, and shall be known as the Gold Wedge Mining Claim.

DAED ON THE GROUND this 16<sup>th</sup> day of June 1899

Wm O. Harrell,      Jos Hobbs  
R.A. Macdon,      Jeff Leforse

Recorded at request of W.O. Harrell. June 23rd A.D. 1899, at 12 o'clock N., in Book 49 of Mines, page 370 Records of Yavapai County, Arizona.

(Seal)      W.I. Johnson, County Recorder.

By .....Deputy.

127

"Yankoo Blade"Notice of Mining Location.  
Lode Claim.

To All Whom it May Concern:

This Mining Claim, the name of which is the Yankoo Blade Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by H.L. Sweeney the undersigned, on the 1 day of Jan, 1908.

The length of this claim is 1500 feet, and I claim 1500 feet, in an easterly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the east to the west.

The claim is situated and located in the Hassayampa Mining District in Yavapai County, in the Territory of Arizona, about 1/8 mile in a northerly direction from Bonitia mill.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stones at a point in an easterly direction 1500 feet from the discovery shaft (at which this notice is posted), being in the center of the east end line of said claim; thence north 300 feet to a monument of stones being the N.E. corner of said claim; thence West 1500 feet to a monument of stones being at the N.W. corner of said claim; thence southerly 300 feet to a monument of stones at the center of the West end of said claim; thence south 300 feet to a monument of stones being at the S.W. corner of said claim; thence easterly 1500 feet to a monument of stones at the S.E. corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XVIII, of the revised Statutes of the United States and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 18, 1901.

Dated and posted on the ground, this 1st day of January 1908.

H.L. Sweeney

Filed and recorded at request of H.L. Sweeney Nov 5 A.D. 1908, at 9 o'clock A.M., Book 66 of Mines, Page 198, Records of Yavapai County, Arizona.

(Seal) P.J. Farley County Recorder.  
By G.H. Dotson Deputy Recorder.

W  
D

TERRITORY OF ARIZONA, )  
 ) : ss.  
 County of Yavapai. )

I, J.C. Bradbury, County Recorder in and for  
 the County aforesaid, do hereby certify that I have compared the fore-  
 going copies with, and that the same are true and correct copies of the  
 notices of locations, as appears of record in my said office, of the  
 following named lode mining claims, situated in Creek Canyon, Mount  
 Union and Passayampa Mining Districts, Yavapai County, Arizona Territory,  
 and as the same appear of record at the books and pages as follows,  
 to-wit:-

<u>Name of Claim</u>	<u>Book</u>	<u>Page</u>
FRANKLIN	34	304.
PINOBSCOT	31	5.
NO. 1 GOLD	37	512.
SURE THING GOLD	38	473.
LYNK NO. 1	39	334.
LYNK NO. 2	38	375.
SPRUCE	43	431.
MT UNION	44	388.
MOUNT DAVIS	44	419.
HONDO	49	41.
GOLD RIDGE	49	373.
MANILLA	49	433.
WINIFORD GOULD	49	591.
FRANKLIN NO 2	54	173.
THE MOUNTAIN VIEW	56	123.
THE LAST DOLLAR MINE	56	137.
YANKEE BLADE	56	138.
COMET	58	210.
SUMMIT	71	134.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed my  
 Official Seal, this 13 day of September, A.D. 1903.

*J. C. Bradbury,*  
 County Recorder.

50  
 →

U. S. SURVEYOR GENERAL'S FINAL CERTIFICATE ON  
FIELD NOTES.

DEPARTMENT OF THE INTERIOR,  
OFFICE OF U. S. SURVEYOR GENERAL,

Phoenix, Arizona, .....

.....October 28, ....., 1908 .

I, U. S. Surveyor General for ..... District of Arizona. ....,

do hereby certify that the foregoing transcript of the Field Notes, return and approval

of the Survey of the mining claim of ..... Mount Union Consolidated Mining Co.  
known as the Mount Davis, Mt. Union, Spruce, Manilla, Comet, Hondo,  
Lynx No. 1, Lynx No. 2, Sure thing Gold, No. 1 Gould, The Last  
Dollar Mine, Summit, Winiford Gould, Penobscot, Franklin, Franklin  
No. 2, The Mountain View, Gold Wedge, Yankee Blade, .....

....., situate in ..... Hassayampa .....

..... Mining District, ..... Yavapai ..... County,

..... Arizona, ....., in Section approx ....., Township No. 12 N,

Range No. 1 W., unsur., ....., and designated as Survey

No. 2588 ....., has been correctly copied from the originals on  
file in this office; that said Field Notes furnish such an accurate description of said  
mining claim as will, if incorporated into a patent, serve fully to identify the premises,  
and that such reference is made therein to natural objects or permanent monuments as  
will perpetuate and fix the *locus* thereof.

And I further certify that five hundred dollars' worth of labor has been expended  
or improvements made upon <sup>or for each of</sup> said mining claim by claimant or its grantors, and  
that said improvements consist of 24 shafts, 5 tunnels, 8 cuts, 2 drifts,  
1 winze, 2 cross-cuts and 3 approaches, total value \$53270.  
Tunnel No. 2 and shaft No. 3 on the Franklin lode, value \$36020,  
and shaft No. 2 and tunnel No. 3 on the Comet lode, value \$7170,  
being common improvements for the benefit and development of this  
entire group, an undivided 1/19 interest in said improvements, value  
\$2273.16, is properly credited to each claim in this survey.

.....  
.....  
and that no portion of said labor or improvements has been included in the estimate of  
expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix,  
Arizona, ..... is correct and in conformity with the foregoing Field Notes.

..... Frank S. Ingalls, .....

..... United States Surveyor General for ..... Arizona. ....

4-687.

SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

October 28, 1908.

I, U. S. Surveyor-General for District of Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the

Mining Claim of Mount Union Consolidated Mining Co., known as the Mount Davis, Mt. Union, Spruce, Manilla, Comet, Hondo, Lynx No. 1, Lynx No. 2, Sure thing Gold, No. 1 Goold, The Last Dollar Mine, Summit, Winiford Gould, Penobscot, Franklin, Franklin No. 2, The Mountain View, Gold Wedge, Yankee Blade

situate in Hassayampa mining district,

Yavapai County, Arizona,

in Section Approx., Township No. 12 N., Range No. 1 W., unsur.

, designated as Survey No. 2588

executed by J. J. Fisher, U. S. Deputy Mineral

Surveyor, September 21-29, 1908, under my instructions dated

September 19, 1908, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for

survey is included in the field notes.

Frank A. Lyall

U. S. Surveyor-General for Arizona.



Large  
Map

# **POOR QUALITY**

**The following pages are scanned at the best possible quality setting. The original pages are of poor quality and this is the best possible reproduction.**

SURVEY No. 2003.

FRANKLIN.

Feet.

beginning at cor. No. 1 which is also a part of the Massachusetts Lode of this survey. Identical with cor. of location, measurement of stone 2 ft. high 1-1/8 ins. high.

Set a porphyry stone 24x10x8 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked F.1-2533, also on opposite side P.S.-2533, which is on a porphyry rock in place marked F.1-2533 bearing N. 85° 15' E. 251.3 feet.

Set a granite stone on a granite rock in place marked F.1-2533 bearing N. 89° 45' W. 11.7 feet. H. No. 1 Mass. map, Mining Dist. bearing N. 13° 55' E. 3278.1 ft. distant.

Thence S. 13° 55' W.

1100  
1700

To cor. No. 3 the MOUNTAIN VIEW LOPE of this survey, cor. No. 3 which is also cor. No. 1 FRANKLIN LOPE of this survey, identical with cor. of location, measurement of stone 2 ft. high 1-3/8 ft. high.

Set a granite stone 24x10x8 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked F.1-2533, also on opposite side P.S.-2533, which is on a granite rock in place marked F.1-2533 bearing N. 89° 45' W. 11.7 feet.

Set a granite stone on a granite rock in place marked F.1-2533 bearing S. 04° 15' E. 12.7 ft. distant.

Thence S. 04° 15' E.

500

To S. center end which is also the N. center end of the MOUNTAIN VIEW LOPE of this survey, identical with cor. of location,

Set a granite stone 24x10x8 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked F.1-2533 also on opposite side P.S.-2533, which is on a granite rock in place marked F.1-2533 bearing N. 89° 45' W. 11.7 feet.

600

To cor. No. 5 which is also cor. No. 4 FRANKLIN No. 3 of this survey, identical with cor. of location.

Set a granite stone 24x10x8 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked F.1-2533 also on opposite side P.S.-2533, no bearings available.

Thence N. 15° 30' E.

140  
1800

To cor. No. 2 YAMBERT BRASS LOPE of this survey, cor. No. 4 which is also cor. No. 5 FRANKLIN LOPE of this survey, cut a X on a granite rock in place marked F.1-2533 and on opposite side P.S.-2533, no bearings available, this cor. is identical with cor. of loc.

Thence N. 74° 30' W.

300

To N. center end which is also the S. center end of the MOUNTAIN VIEW LOPE of this survey, identical with loc.

Set a granite stone 24x10x8 ins. 12 ins. in ground alongside raised a mound of stone 3x3 ft. stone marked F.1-2533 also on opposite side S.C.E.P. 2533

Feet.

2.

600 To cor.No.1 the place of beginning survey of exterior boundaries.

\* \* \* \* \*

FRANKLIN No. 3 LODGE.

Beginning at cor.No.1 which is also cor.No.2 of FRANKLIN LODGE this survey, corner described above, whence U.S.M.S.No.1 Haskings M.D. bears  $T. 5^{\circ} 30' W.$  6877.0 feet distant,

Thence  $S. 1^{\circ} 45' W.$

1500 To cor.No.2 identical with cor.of loc. a monument of stone 1 ft. base 1-1/2 ft. high,

Set a granite stone 24x10x6 ins. 12 ins.in ground, alongside raised a mound of stone 3x3 ft. stone marked F.No.2, 2-2880, whence a X on a granite rock in place marked F.R.F.No.2, 2-2588 bears  $T. 37^{\circ} 30' W.$  17.1 ft.

A granite rock in place marked F.R.F.No.2, 2-2588 bears  $S. 70^{\circ} W.$  9.5 ft. distant.

Thence  $S. 74^{\circ} 50' E.$

800 To cor.No.1 identical with loc. a monument of stone 1 ft. base 1-1/2 ft. high,

Set a granite stone 20x15x8 ins. 15 ins.in ground, alongside raised a mound of stone 5x5 ft., stone marked F.No.3, 3-1830.

600 To cor.No.2, identical with cor.of loc. a monument of stone 1 ft. base 1-1/2 ft. high,

Set a granite stone 20x15x8 ins. 15 ins.in ground, alongside raised a mound of stone 5x5 ft. stone marked F.No.4, 3-1830, no bearings available.

Thence  $T. 1^{\circ} 45' E.$

1500 To cor.No.3 which is also cor.No.3 FRANKLIN LODGE of this survey, cor. described above.

Thence  $T. 74^{\circ} 50' N.$

800 To cor.No.1 which is also cor.No.2 of FRANKLIN LODGE this survey, monument described above.

600 To cor.No.1 the place of beginning survey of exterior boundaries.

\* \* \* \* \*

THE HORNBY VILLAGE

Feet.

Beginning at cor. No. 1 which is identical with cor. No. 1 E. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high.  
 Set a granite stone 24x15x10 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked N.V.1-2533,  
 Thence U.S.M.M. No. 1 Massawepa N.P. bears N. 25° 30' W. 70.2 ft. distant, no other bearings available.  
 Original cor. of loc. a mon. of stones 2 ft. base, 1 1/2 ft. high, bears N. 74° 30' W. 300 ft. distant.

Thence N. 17° 30' W.

1500.1

To cor. No. 2 whence S.W. cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high, bears N. 74° 30' W. 300 ft. distant.  
 Set a X on a granite rock in place marked L.V.2-2533 alongside raised a mound of stones 3x3 ft., no bearings available.

Thence S. 74° 30' E.

30

To S.O.E. identical with loc. a mon. of stones 2 ft. base 1-1/2 ft. high,  
 Set a granite stone 24x12x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked S.O.E. N.V. 2533.

300

To cor. No. 3, identical with cor. of loc. a mon. of stones 2 ft. base 1-1/2 ft. high,  
 Set a granite stone 24x12x6 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked N.V.3-2533,  
 Thence a X on a granite rock in place marked L.V.3-2533 bears N. 0° 50' W. 16.2 ft. distant,  
 A X on a granite rock in place marked B.R. N.V.3-2533 bears S. 14° 50' W. 16.8 ft. distant,

Thence N. 15° 30' E.

1100

To cor. No. 1 FRANKLIN and cor. No. 2 PENOBSCOT Loc. of this survey,

1500

To cor. No. 4, identical with cor. of loc., a mon. of stones 2 ft. base 1-1/2 ft. high,  
 Set a porphyry stone 24x3x8 ins. 12 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked N.V.4-2533,  
 Thence a X on a granite rock in place marked B.R. N.V.4-2533 bears S. 54° 30' W. 29.9 ft. distant,  
 A X on a granite rock in place marked B.R. N.V.4-2533 bears N. 42° 15' W. 35.2 ft. distant.

Thence N. 74° 30' W.

300

To cor. No. 1 the place of beginning survey of exterior boundaries.

\* \* \* \* \*

Feet.

PENOBSCOT LODE.

Beginning at cor.No.1 which is also cor.No.2 WINIFORD GOULD Lode of this survey, identical with cor.of loc. a mon.of stones 3 ft.base 1-1/2 ft.high,

Set a granite stone 24x10x3 ins. 12 ins.in ground, alongside raised a mound of stones 3x3 ft. stone marked P.I.-2582 and on opposite side W.G.S-2583,

Distance U.S.M.R.No.1 Hamarapet M.D. bears N.14°24'32" W. 30.2 ft. distant,

N E 182 S

Thence 2. 15° 30' W.

1162 To cor.No.4 MOUNTAIN VIEW Lode of this survey,

1300 To cor.No.2 which is also cor.No.1 FRANKLIN Lode of this survey, cor. described above.

Thence 3. 74° 30' E.

500 To S.C.E. which is also the N.C.E. the FRANKLIN Lode of this survey, cor. described above.

600 To Cor. No. 3, which is also Cor. No. 4 Franklin lode of this survey, cor. described above.

Thence 4. 15° 30' W.

70 To cor.No.1 YAKIMA BLADE and cor.No.2 GOLD WOOD Lodes of this survey,

1500 To cor.No.4 which is also cor.No.5 WINIFORD GOULD Lode of this survey, identical with cor.of loc. a mon.of stones 3 ft. base 1-1/2 ft.high,

Set a granite stone 24x10x3 ins. 12 ins.in ground, alongside raised a mound of stones 3x3 ft. stone marked P.I.-2582 and on opposite side W.G.S-2583,

Distance U.S.M.R.No.1 Hamarapet M.D. bears N.14°24'32" W. 30.2 ft. distant,

A M on a granite rock in place marked B.R.W.G.S-2583 bears N.33°W. 7.4 ft. distant,

Thence 5. 74° 30' W.

500 To N.C.E. which is also the S.C.E. WINIFORD GOULD Lode of this survey, identical with loc. a mon.of stones 3 ft. base 1-1/2 ft.high,

Set a granite stone 24x10x3 ins. 12 ins.in ground, alongside raised a mound of stones 3x3 ft. stone marked P.I.-2582 and on opposite side W.C.E.W.G.2583,

300 To cor.No.1 the place of beginning the survey of exterior boundaries,

WINIFORD GOULD LODE

Beginning at cor.No.1 identical with cor.of loc. a mon.of stones 3 ft. base 1-1/2 ft. high,

SURVEY No. 238.

WHELFORD GOLD LODGE.

Post.

also raised a mound of stones 3x3 ft. stone marked W.G.L-2383,

A X on an Oak 6 ins. diam. marked B.T.W.G.L-2384 bears N.51°15'E. 10.8 ft. distant,

A X on an Oak 8 ins. diam. marked B.T.W.G.L-2385 bears N.48°20'W. 14.1 ft. distant,

Cor.No.1 HASRAYSAYE H.L. bears N.01°00'W. 17.1 ft. distant,

Thence S. 13° 30' W.

1440

To cor.No.2 which is also cor.No.1 PHINDROG Lode of this survey, cor. described above,

Thence S. 74° 30' E.

300

To S.C.E. which is also the S.C. PHINDROG Lode of this survey, monument described above,

600

To cor.No.3 which is also cor.No.4 PHINDROG Lode of this survey, cor. described above,

Thence E. 14° 30' W.

70

To intersect line 1-2 No.1 GOLD Lode of this survey at N.8°45'E. 755 ft. from cor. 2.

723

To intersect line 1-4 No.1 GOLD and line 2-3 No.1 WHITE GOLD Lode of this survey at S.33°15'E. 174 ft. from cor.No.1 GOLD and cor.No.3 SURE THING GOLD Lode of this survey,

1440

To cor.No.4 identical with cor.No.3. a mon. of stones 3 ft. base 1-1/2 ft. high.

Set a granite stone 9x10x4 ins. 18 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked N.G.L-2386,

Thence a X on an Oak 8 ins. diam. marked B.T.W.G.L-2387 bears N.70°15'E. 6.4 ft. distant,

A X on an Oak 8 ins. diam. marked B.T.W.G.L-2388 bears S.00°W. 33.7 ft. distant,

Cor.No.5 GOVERNOR Lode, Not No.54 bears N.63°00'E. 107.3 ft. distant,

Thence N. 74° 30' W.

234.03

To intersect line 1-2 SURE THING GOLD Lode of this survey at N.8°45'E. 755 ft. from cor.No.2,

300

To H.C.E. identical with H.C.E. of Lode, a mon. of stones 3 ft. base 1-1/2 ft. high,

Set a granite stone 9x10x4 ins. 18 ins. in ground, alongside raised a mound of stones 3x3 ft. stone marked H.C.L-2389,

600

To cor.No.1 the place of beginning survey of this lode boundary,

\* \* \* \* \*

SURE TRING GOLD LODE.

Feet.

Beginning at cor.No.1 identical with cor.of loc. a mon.of stones 3 ft. base 1-1/8 ft.high,

Set a granite stone 3x17x3 ins. 18 ins.in ground,  
also raised a mound of stones 3x3 ft. stone set

in place marked B.T.C.E.1-3533 bears  
N. 11° 30' W. 31.2 ft. distant.

Set a granite stone 3x17x3 ins. 18 ins.in ground,  
also raised a mound of stones 3x3 ft. stone set

in place marked B.T.C.E.1-3533 bears  
N. 11° 30' W. 31.2 ft. distant.

N E 300 S

Thence S. 30° 45' W.

407.33

To C. corner line 1-3 <sup>Governor</sup> GOVERNOR Lode Lot No.34, at N.  
750. E. 123 ft. from cor.No.3,

506

To C. corner line 1-3 WILFORD GOULD Lode of this  
survey at N. 83° 30' W. 334.35 ft. from cor.No.4.

1233

To C. corner No.3 which is also cor.No.1 No.1 GOLD Lode of  
this survey, identical with cor.of loc. a mon.of stones  
3 ft. base 1-1/8 ft.high.

Set a granite stone 3x17x3 ins. 18 ins.in ground,  
also raised a mound of stones 3x3 ft. stone set

in place marked B.T.C.E.1-3533  
bears N. 11° 30' W. 31.2 ft. distant.

Thence S. 33° 1-1/2'

134

To C. corner line 1-4 WILFORD GOULD Lode of this survey  
at S. 17° 30' W. 712 ft. from cor.No.4.

500

To C. corner No.1 which is also the No.1 No.1 GOLD Lode of  
this survey, identical with cor. a mon.of stones  
3 ft. base 1-1/8 ft.high.

500

Set a granite stone 3x17x3 ins. 18 ins.in ground,  
also raised a mound of stones 3x3 ft. stone set

in place marked B.T.C.E.1-3533 also on opposite side N.C.E.No.1 G.2583.

To cor.No.2 which is also cor.No.1 No.1 GOLD Lode of  
this survey, identical with cor.of loc. a mon.of stones  
3 ft. base 1-1/8 ft.high.

Set a granite stone 3x17x3 ins. 18 ins.in ground,  
also raised a mound of stones 3x3 ft. stone set

in place marked B.T.C.E.1-3533 also on opposite side No.1 G.4-2583.

Set a granite stone 3x17x3 ins. 18 ins.in ground,  
also raised a mound of stones 3x3 ft. stone set

in place marked B.T.C.E.1-3533 bears  
N. 11° 30' W. 31.2 ft. distant.

Thence N. 12° 45' E.

To cor.No.1 MARK No.2 and cor.No.2 MARK No.1 Lode  
at

To cor.No.1 identical with cor.of loc. a mon.of stones  
3 ft. base 1-1/8 ft.high.

Set a granite stone 3x17x3 ins. 18 ins.in ground,  
also raised a mound of stones 3x3 ft. stone set

in place marked B.T.C.E.1-3533 bears  
N. 11° 30' W. 31.2 ft. distant.



SURVEY NUMBER 110

Page 1

THESE ARE THE

300

To N.C.E. identical with loc. 2 of survey No. 1. base 1-1/2 ft. high,

granite stone 12 in. dia. 18 in. in ground, alongside raised a granite stone 3 ft. distant, N.C.E. 110-2500.

517.11

To cor. No. 1 line 2-1-110-2500 base 1-1/2 ft. high, N.C.E. 110-2500.

600

To cor. No. 1 the place of the granite stone, N.C.E. 110-2500.

THESE ARE THE

Beginning at cor. No. 1 which is also cor. No. 2 of THESE GOLD LODES of this survey, as described above,

to cor. No. 1. base 1-1/2 ft. high, N.C.E. 110-2500.

THESE ARE THE

641.2

To cor. No. 1 line 2-1-110-2500 GOLD LODE of this survey, base 1-1/2 ft. high, N.C.E. 110-2500.

641.3

To cor. No. 2 GOLD LODE of this survey, base 1-1/2 ft. high, N.C.E. 110-2500.

1800

To cor. No. 3 which is also cor. No. 1 of THE LAST GOLD LODE of this survey, base 1-1/2 ft. high, N.C.E. 110-2500.

granite stone 12 in. dia. 18 in. in ground, alongside raised a granite stone 3 ft. distant, N.C.E. 110-2500 also on opposite side E.N. 1-2500.

See a X on a granite rock in place marked E.N. 1-2500 G, E-2500 bears N. 65° 30' E. 15.2 ft. distant,

A X on a granite rock in place marked E.N. 1-2500 bears S. 66° 45' W. 11.1 ft. distant,

THESE ARE THE

800

To E.C.E. which is also the E.C.E. of THE LAST GOLD LODE of this survey, identical with loc. 2 a granite stone 1 ft. base 1-1/2 ft. high,

granite stone 12 in. dia. 18 in. in ground, alongside raised a granite stone 3 ft. distant, N.C.E. 110-2500. The granite stone N.C.E. 110-2500

900

To cor. No. 3 which is also cor. No. 1 of THE LAST GOLD LODE of this survey, identical with loc. 2 a granite stone 1 ft. base 1-1/2 ft. high,

See a X on a granite rock in place marked No. 1 G, E-2500 also on opposite side E.N. 1-2500,

See a X on a granite rock in place marked No. 1 G, E-2500 bears N. 51° 45' E. 14.2 ft. distant,

A X on a granite rock in place marked E.N. 1-2500 bears N. 51° W. 5.1 ft. distant,

8.

Thence N. 3° 45' E.

5.  
1800

To cor. No. 2 LYNN No. 2 Lode of this survey,  
to cor. No. 3 which is also cor. No. 3 SURE THING GOLD  
Lode of this survey, corner described above.

Thence N. 66° 15' E.

300

To cor. No. 1 which is also the S.O.L. SURE THING S. L.  
Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above.

\* \* \* \* \*

THE LAST DOLLAR MINE

To cor. No. 1 which is also cor. No. 2, No. 1  
Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above.

Thence N. 3° 45' E.

604.8  
1800

To cor. No. 1 GOLD LODE and cor. No. 6 MICHELS FLAT  
Lode of this survey,  
to cor. No. 1 GOLD LODE and cor. No. 6 MICHELS FLAT  
Lode of this survey, corner described above,  
to cor. No. 1 GOLD LODE and cor. No. 6 MICHELS FLAT  
Lode of this survey, corner described above,  
to cor. No. 1 GOLD LODE and cor. No. 6 MICHELS FLAT  
Lode of this survey, corner described above.

Thence N. 66° 15' E.

To cor. No. 1 which is also cor. No. 2, SURE THING S. L.  
Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above.

To cor. No. 1 which is also cor. No. 2, SURE THING S. L.  
Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above.

To cor. No. 1 which is also cor. No. 2, SURE THING S. L.  
Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above.

Thence N. 66° 15' E.

To cor. No. 1 which is also cor. No. 2, SURE THING S. L.  
Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above,  
to cor. No. 1 Lode of this survey, corner described above.

THE LAST OCEAN TERN.

Page.

Traverse 1. 1911.

To S.O.L. which is also cor. No. 1 of this survey, described above,  
whence original cor. of loc. bears 2.5015' W. 337 ft. distant,  
Set a granite stone 4x6x6 ins. 12 inc. in ground,  
alongside raised a mound of stones 3x3 ft. stone 3x3 ft. S.C.B.S. 2538.

9419.2  
9419.2

19' 12" W.  
19' 12" W.

Traverse 2. 1911.

571.8  
547

To cor. No. 3 WALKER BLVD. of this survey,  
whence original cor. of loc. bears 2.5015' W. 337 ft. distant,  
Set a granite stone 4x6x6 ins. 12 inc. in ground,  
alongside raised a mound of stones 3x3 ft. stone 3x3 ft. S.C.B.S. 2538.

Whence K on a granite rock in place bears 1.5015' W. 337 ft. distant,  
A K on a granite rock in place bears 1.5015' W. 337 ft. distant,

Traverse 3. 1911.

560

To S.O.L. whence original cor. of loc. bears 2.5015' W. 337 ft. distant,  
Set a granite stone 4x6x6 ins. 12 inc. in ground,  
alongside raised a mound of stones 3x3 ft. stone 3x3 ft. S.C.B.S. 2538.

600

To cor. No. 3 whence original cor. of loc. bears 2.5015' W. 337 ft. distant,  
Set a granite stone 4x6x6 ins. 12 inc. in ground,  
alongside raised a mound of stones 3x3 ft. stone 3x3 ft. S.C.B.S. 2538.

Traverse 4. 1911.

573

To cor. No. 4 which is also cor. No. 2 of this survey, described above,

Traverse 5. 1911.

560

To S.O.L. which is also the S.O.L. of THE LAST OCEAN TERN  
Traverse of this survey, described above,

560

To cor. No. 1 the place of beginning survey of original  
boundaries.



Feet.

Thence S. 25° 30' W.

70  
1330

To cor.No.3 BULLOCKS and CORNER TO WHICH THIS LINE IS  
311. SURVEY.  
To cor.No.3 identical with cor.No.1 loc. a mound of stones  
2 ft. base 1-1/2 ft. high.  
Set a granite stone 12x12x12 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
N.B. 1-2588.  
Thence on Oak 5 ins. 1.7 dist. E.T.N.D.2-Cor. No. 2  
S. 2015' 14.7 ft. distant,  
On Oak 5 ins. dist. 1.1 E.T.N.D.2-20 3 ft. dist. 1.2  
10.0 ft. distant,

Thence S. 30° 30' W.

300

To S.C.E. identical with loc. a mound of stones 2 ft.  
base 1-1/2 ft. high,  
Set a granite stone 12x12x12 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
S.C. N.B. 2588,

300.7

To cor.No.3 identical with cor.No.2 loc. a mound of stones  
2 ft. base 1-1/2 ft. high,  
Set a granite stone 12x12x12 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
N.B. 1-2588, no bearings available,

Thence N. 3° 45' W.

374.2

To cor.No.1 W. 1/2 Sec. 20, T.10 S. R.12 E. DIST. 1.1  
1.0 OF THIS SURVEY.  
To cor.No.1 W. 1/2 Sec. 20, T.10 S. R.12 E. DIST. 1.1  
1.0 OF THIS SURVEY, DIST. 1.1 V.1.

1330

Thence N. 80° 22' W.

153.6

To N.C.E., which is also the S.C.E. Gold Wedge lode of  
this survey, identical with loc. a mon. of stones 2 ft.  
base, 1 1/2 ft. high. xxxxxxxxxxxxxxxxxxxxxxxx Set a granite stone  
24 x 8 x 6 ins. 12 ins. in ground, alongside raised a mound  
of stones 3x3 ft., stone marked N.C.E.Y.B.2588, and on opposite

307.2

side S.C.E  
G.W.2588.  
To cor.No.1 W. 1/2 place of beginning the curve, 1.1  
bearing boundaries.

\* \* \* \* \*

LINE No.1 LODE.

Beginning at cor.No.1 identical with cor.No.1 loc. a  
mound of stones 2 ft. base 1-1/2 ft. high,  
Set a granite stone 12x12x12 ins. 12 ins. in ground,  
alongside raised a mound of stones 3x3 ft. stone marked  
N.C.E. 1, 1-2588,  
Set a X on a granite rock in place marked B. 1.1  
1-2588 base N. 70° 15' E. 14.0 ft. distant,  
E.T.N.D. 1 Mass/ampa N.D. base N. 2° 22' W. 1.1  
ft. distant,

Thence S. 3° 45' W.

355

To cor.No.4 SURE THING GOLD lode of this survey.

18.

Foot.

1440

To cor.No.2 which is also cor.No.1 B.M. No.3 Lode of this survey, identical with cor.of loc. a mon.of stone 3 ft. base 1-1/8 ft. high,

Set a post with a stone 50-10x3 ins. 15 ins.in ground, along side which a round of stone 3x3 ft. stone marked B.L.E.L.No.1-2500 on opposite side B.No.3,1-2500.

Trace a line of white rock in place marked B.L.E.L.No.1-2500 bearing N. 40° 20' W. 100 ft. distant,

Trace a line of white rock in place marked B.L.E.L.No.1-2500 bearing S. 30° 20' W. 90 ft. distant.

B.M. No. 3. 250 15' E. 1/2 W.

500

To cor.No.3 which is also the W.C.M. of B.M. No.3 Lode of this survey, a mon.of stone 3 ft. base 1-1/8 ft. high,

Set a post with a stone 50-10x3 ins. 15 ins.in ground, along side which a round of stone 3x3 ft. stone marked B.L.E.L.No.1-2500 on opposite side B.C.E.L.No.3,2500

600

To cor.No.4 which is also cor.No.2 B.M. No.3 Lode of this survey, identical with cor.of loc. a mon.of stone 3 ft. base 1-1/8 ft. high,

Set a post with a stone 50-10x3 ins. 15 ins.in ground, along side which a round of stone 3x3 ft. stone marked B.L.E.L.No.1-2500 on opposite side B.No.3,1-2500, no bearing.

Trace a line of white rock

110

To cor.No.1 B.M. No.3 Lode of this survey,

1440

To cor.No.2 identical with cor.of loc. a mon.of stone 3 ft. base 1-1/8 ft. high,

Set a post with a stone 50-10x3 ins. 15 ins.in ground, along side which a round of stone 3x3 ft. stone marked B.L.E.L.No.1-2500, no bearing available,

B.M. No. 3. 250 15' E. 1/2 W.

300

To cor.No.1 identical with W.C.M. of loc. a mon. of stone 3 ft. base 1-1/8 ft. high,

Set a post with a stone 50-10x3 ins. 15 ins.in ground, along side which a round of stone 3x3 ft. stone marked B.L.E.L.No.1-2500.

400

To cor.No.1 the place of beginning survey of this lode

B.M. No. 3 B.M.

Bearing to cor.No.1 B.M. No.3 Lode of this survey,

To cor.No.2 B.M. No.3 Lode of this survey,

To cor.No.1 B.M. No.3 Lode of this survey,

To cor.No.1 B.M. No.3 Lode of this survey,

7 25° 45' 17" W

Trace a line of white rock

SURVEY No. 817.

LINE 1. 2. 3.

1500

To cor. No. 1 of this survey, identical with cor. of loc. 2 of stones 2 ft. base 1-1/8 ft. high.  
 Set a granite stone 19 inches high, also raised a mound of stones 3x3 ft. stone marked H.L.S. 1-2530,  
 A K on a granite rock in place marked B.H.S. 1-2530 bears N. 85° 50' E. 13.5 ft. distant.  
 A K on a granite rock in place marked B.H.S. 1-2530 bears N. 85° 50' E. 13.5 ft. distant.

Thence N. 85° 15' E.

300

To cor. No. 2 identical with cor. of loc. 2 of stones 2 ft. base 1-1/8 ft. high.  
 Set a granite stone 19 inches high, also raised a mound of stones 3x3 ft. stone marked H.L.S. 2-2530,

300

To cor. No. 3 identical with cor. of loc. 2 of stones 2 ft. base 1-1/8 ft. high.  
 Set a granite stone 19 inches high, also raised a mound of stones 3x3 ft. stone marked H.L.S. 3-2530;

A K on a granite rock in place marked B.H.S. 3-2530 bears N. 85° 50' E. 13.5 ft. distant.

Thence N. 59° 40' E.

410  
1.00

To cor. No. 3 UNDER side of 2 in survey,  
 To cor. No. 4 which is also cor. No. 3 LINE 1. 2. 3. of this survey. cor. described above.

Thence N. 86° 15' W.

300

To H.C.N. which is also the S.C.N. of LINE No. 1 side of this survey, non. described above.

300

To cor. No. 1 the place of beginning survey of cr. line boundaries.

\* \* \* \* \*

BOUND LOTS.

Beginning at cor. No. 1 which is also cor. No. 2 of this survey, identical with cor. of loc. 2 of stones 2 ft. base 1-1/8 ft. high.

Set a granite stone 19 inches high, also raised a mound of stones 3x3 ft. stone marked H.L.S. 1-2530, on opposite side C.S. 2530,

A K on a granite rock in place marked B.H.S. 1-2530 bears S. 17° E. 10.6 ft. distant,

A K on a granite rock in place marked B.H.S. 2-2530 bears N. 85° E. 13.6 ft. distant,

U.S.M.S. No. 1 Macayampa H.D. bears N. 31° 51' 30" W. 3310 ft. distant,

Feet.

Thence S. 3° 45' W.

410

To cor. No. 3 LYNN No. 1 and cor. No. 4 LYNN No. 2 Lodes of this survey.

1500

To cor. No. 3 identical with cor. of loc. a mon. of stones 3 ft. base, 1-1/2 ft. high.

Set a granite stone 8x10x6 ins. 12 ins. in ground, along side raised a mound of stones 3x3 ft. stone marked H.S.-1500, no bearings available.

Thence W. 89° 15' N.

500

To S.C.E. identical with S.C.E. of loc. a mon. of stones 3 ft. base 1-1/2 ft. high.

Set a granite stone 8x12x10 ins. 12 ins. in ground, along side raised a mound of stones 3x3 ft. stone marked S.C.E.H. 2550.

600

To cor. No. 3 identical with cor. of loc. a mon. of stones 3 ft. base 1-1/2 ft. high.

Set a granite stone 8x10x6 ins. 15 ins. in ground, along side raised a mound of stones 3x3 ft. stone marked H.S.-1500.

Thence a K on a granite rock in place marked B.R.H. 3-2550 bears S. 88° W. 23.7 ft. distant.

A K on a granite rock in place marked B.R.H. 3-2500 bears S. 81° E. 21 ft. distant.

Thence N. 2° 45' E.

1040

To cor. No. 1 SPANISH and cor. No. 2 ME. UNION Lodes of this survey.

1500

To cor. No. 4 which is also cor. No. 5 COMET Lode of this survey. Identical with cor. of loc. a mon. of stones 3 ft. base 1-1/2 ft. high.

Set a granite stone 8x10x6 ins. 12 ins. in ground, along side raised a mound of stones 3x3 ft. stone marked H.S.-1500 on opposite side C.S.-2500.

Set a granite rock in place marked B.R.H. 4-2500 bears S. 81° W. 21 ft. distant, no other bearings available.

Thence E. 89° 15' W.

1400

To S.C.E. which is also the S.C.E. COMET Lode of this survey. Identical with location, a mon. of stones 3 ft. base, 1-1/2 ft. high.

Set a granite stone 8x10x6 ins. 12 ins. in ground, along side raised a mound of stones 3x3 ft. stone marked H.S.-1500 and on opposite side S.C.E.C. 2500.

To cor. No. 1 the place of beginning, survey of exterior to interior.

COMET LODE.

To cor. No. 1 which is also cor. No. 2 LYNN Lode of this survey, identical with cor. of loc. a mon. of stones 3 ft. base 1-1/2 ft. high.



SURVEY No. 2333.

COCHIN LODGE.

Feet.

along the raised a mound of stones 3x3 ft. about 2 ft. C.1-2513, on opposite side N.3-2513,  
 and a X on a granite rock in place marked B.I.C.1-2513 bears S.19°W. 22.4 ft. distant,  
 and on a granite rock in place marked B.I.C.1-2513 bears S.13°E. 10.3 ft. distant,  
 U.S.M.No.1 Hassayampa N.D. bears N.40°E. 11.5 ft. distant,  
 500 ft. distant,

Thence N. 2° 15' W.

470  
1500

To cor.No.4, LYNN No.1 Lot of this survey,  
 To cor.No.2 which is also cor.No.1 FORD No.1 of this survey, cor. described above,

Thence S. 80° 15' E.

300

To S.C.E. which is also N.O.E. of FORD No.1 of this survey, men. described above,

600

To cor.No.3 which is also cor.No.4 FORD No.1 of this survey, cor. described above,

Thence N. 5° 45' E.

1040

To cor.No.1 W.T. DUNN and cor.No.2 WUNT LINDS Lot of this survey,

1500

To cor.No.4 which is also cor.No.5 MANILLA Lot of this survey, identical with cor. of loc. of stones 3 ft. base 1-1/2 ft. high.

Set a granite stone 24x6 ins. 12 ins. in ground, along the raised a mound of stones 3x3 ft. stone marked C.4-2513, on opposite side N.3-2513,

where a X on an Oak 12 ins. diam. marked B.I.C.1-2513 bears S.3°E. 21.1 ft. distant,

Thence N. 80° 15' W.

300

To N.O.E. which is also the S.C.E. of MANILLA Lot of this survey, identical with loc. of mound of stones 3 ft. base 1-1/2 ft. high,

Set a granite stone 24x6 ins. 12 ins. in ground, along the raised a mound of stones 3x3 ft. stone marked X.C.1-2513, on opposite side S.C.E. N.2513,

600

To cor.No.1 the place of beginning survey of boundary,

\* \* \* \* \*

MANILLA LODGE.

Beginning at cor.No.1 identical with cor. of loc. of mound of stones 3 ft. base 1-1/2 ft. high.

Set a granite stone 24x10x6 ins. 12 ins. in ground, along side raised a mound of stones 3x3 ft. stone marked C.1-2513,

where a X on a granite rock in place marked B.I.C.1-2513 bears S.76°15'W. 29 ft. distant,

U.S.M.No.1 Hassayampa N.E. bears N.49°14'12"W. 4553.4 ft. distant,

16.

Feet.

Thence S. 15° 31' E.

1500 To cor.No.2 which is also cor.No.1 COMET Lode of this  
Lode, cor. described above;

Thence S. 86° 15' E.

500 To S.C.M. which is also the F.C.M. of COMET Lode of  
this Lode, cor. described above;

600 To cor.No.3 which is also cor.No.4 COMET Lode of this  
Lode, cor. described above;

Thence N. 15° 31' W.

1500 To cor.No.4 identical with cor. loc. a mon. of stones  
8 ft. by 1-1/8 ft. high,

Set a granite stone 8x8x6 ins. 12 ins. in ground,  
along with raised a mound of stones 5x5 ft. stone marked  
B.L.1-2500, no bearings available.

Thence N. 30° 15' W.

500 To F.C.M. identical with loc. a mon. of stones 8 ft.  
by 1-1/8 ft. high,

Set a granite stone 8x8x6 ins. 12 ins. in ground,  
along with raised a mound of stones 5x5 ft.

600 To cor.No.1 the place of beginning survey of exterior  
Lode.

\* \* \* \* \*

PANILLA LODE.

Beginning at cor.No.1 identical with cor. of loc. a mon.  
of stones 8 ft. by 1-1/8 ft. high,

Set a granite stone 8x8x6 ins. 12 ins. in ground,  
along with raised a mound of stones 5x5 ft. stone marked  
B.L.1-2500,

Set a X on a granite rock in place marked B.L.1.  
B.L.1-2500 bears S. 84° 30' E. 7.5 ft. distant,

U.S.M. No.1 Halsey's Lode bears N. 52° 50' W. 5400.7  
ft. distant,

Thence S. 3° 45' W.

1040 To cor.No.3 PANILLA Lode. Cor.No.4 COMET Lode of this  
Lode.

1500 To cor.No.2 which is also cor.No.1 MT. UNION Lode of  
this Lode, cor. described above; cor. of loc. a mon. of stones  
8 ft. by 1-1/8 ft. high,

Set a granite stone 8x8x6 ins. 12 ins. in ground,  
along with raised a mound of stones 5x5 ft. stone marked  
B.L.1-2500 and an upright iron pipe marked B.L.1-2500,

Set a X on a granite rock in place marked B.L.1.  
B.L.1-2500 bears S. 84° 30' E. 7.5 ft. distant, no other  
bearings available.

BLANCHARD No. 2580.

BLANCHARD No. 2580.

Foot.

Thence S. 83° 15' E.

300

To S.C.N. which is also the N.C.E. HAZEL Lode of this survey, identical with loc. 2580.

On a granite side of HAZEL Lode, 18 ins. in ground, also raised a mound of stones 3x3 ft. stone marked N.C.E. 2580, on opposite side N.C.E. 2580.

600

To cor.No.8 which is also cor.No.4 BLANCHARD Lode of this survey, identical with cor.of loc. 2580. a mound of stones 3 ft. base 1-1/2 ft. high,

On a granite stone 5x18-18 ins. 18 ins. in ground, also raised a mound of stones 3x3 ft. stone marked N.C.E. 2580, on opposite side N.C.E. 2580.

On a granite rock in place marked E.R. 2580-2580 bears N. 62° 45' E. 30.0 ft. distant,

On a granite rock in place marked E.R. 2580-2580 bears S. 4° 45' E. 21.5 ft. distant,

Thence N. 8° 45' E.

1500

To cor.No.4 identical with cor.of loc. a mound of stones 3 ft. base 1-1/2 ft. high,

On a granite stone 5x18-18 ins. 18 ins. in ground, also raised a mound of stones 3x3 ft. stone marked N.C.E. 2580, no bearings available,

Thence N. 83° 15' W.

300

To S.C.N. identical with loc. a mound of stones 3 ft. base 1-1/2 ft. high,

On a granite rock in place marked N.C.E. 2580, also raised a mound of stones 3x3 ft. stone marked N.C.E. 2580, no bearings available,

600

To cor.No.1 the place of beginning survey of BLANCHARD Lode.

\* \* \* \* \*

BLANCHARD LODE.

Beginning at cor.No.1 which is also cor.No.8 BLANCHARD Lode of this survey, cor. described above,

Thence U.S.M.M.No.1 Homoyana N.C. bears E. 61° 45' W. 6407.0 ft. distant,

Thence S. 8° 15' W.

1040

To cor.No.3 COINER and Cor.No.6 HONDO Lodes of this survey,

1500

To cor.No.3 which is also cor.No.1 BLANCHARD Lode of this survey, identical with cor.of loc. a mound of stones 3 ft. base 1-1/2 ft. high,

On a granite rock in place marked N.C.E. 2580, and on opposite side S.1-2580, no bearings available,

Thence S. 86° 15' E.

500

To S.C.N. which is also the N.C.E. SPRUCE Lode of this survey,

13.

Foot.

Survey, identical with loc. a mon. of stones 3 ft. base  
1-1/2 ft. high,

600

On a granite stone 24x24x3 ins; 12 ins. in ground  
clearly raised a round of stone 3x3 ft. stone  
B.C. 1-1/2 ft. high, on opp. side N.C.E.S. 2500,

To cor. No. 3 which is also cor. No. 4 SPINCE loc. of  
this survey, identical with cor. loc. a mon. of stones  
3 ft. base 1-1/2 ft. high,

On a granite stone 24x24x3 ins; 12 ins. in ground  
clearly raised a round of stone 3x3 ft. stone  
B.C. 1-1/2 ft. high and on opposite side B.C. 2560,

There is a X on a granite rock in place marked B.R.  
B.C. 2560 base B. 10° W. 18 ft. distant,

A granite rock in place marked B.R. B.C. 2560  
base B. 10° W. 0.7 ft. distant,

Hence N. 3° 45' E.

1500

To cor. No. 1 which is also cor. No. 3 MOUNT DAVIS loc. of  
this survey, cor. described above,

Hence N. 36° 15' W.

300

To A.C.M. loc. which is also the loc. of MOUNT DAVIS loc. of  
this survey, cor. described above,

600

To cor. No. 1 on edge of boundary survey of enclosure  
MOUNT DAVIS,

\* \* \* \* \*

STATION LONE.

On a granite stone 24x24x3 ins; 12 ins. in ground  
clearly raised a round of stone 3x3 ft. stone  
B.C. 1-1/2 ft. high, on opp. side N.C.E.S. 2500,

There is a X on a granite rock in place marked B.C.  
B.C. 2560 base B. 10° W. 18 ft. distant,

Hence N. 3° 45' W.

1000

1400

To cor. No. 3 B.C. loc. of this survey,  
identical with cor. loc. a mon. of stones  
3 ft. base 1-1/2 ft. high,

On a granite stone 24x24x3 ins; 12 ins. in ground  
clearly raised a round of stone 3x3 ft. stone  
B.C. 1-1/2 ft. high, on opp. side N.C.E.S. 2500,

Hence N. 36° 15' W.

300

To cor. No. 1 identical with A.C.M. loc. of loc. a mon. of  
stones 3 ft. base 1-1/2 ft. high,

On a granite stone 24x24x3 ins; 12 ins. in ground  
clearly raised a round of stone 3x3 ft. stone  
B.C. 1-1/2 ft. high, on opp. side N.C.E.S. 2500,

600

To cor. No. 3 identical with cor. loc. a mon. of stones  
3 ft. base 1-1/2 ft. high,

On a granite stone 24x24x3 ins; 12 ins. in ground  
clearly raised a round of stone 3x3 ft. stone  
B.C. 1-1/2 ft. high, on opp. side N.C.E.S. 2500,

Feet.

S. 2-1500,  
 Hence a X on a granite rock in place marked B.H. 1-2587  
 2587 bears N. 63° 20' W. 12.5 ft. distant,  
 on a granite rock in place marked B.H. 1-2588  
 bears N. 63° 15' W. 12.5 ft. distant.

Thence S. 3° 45' E.

1490

Hence No. 1 which is also cor. No. 1 of UNION No. 1 of  
 this survey, cor. described above,

Thence S. 3° 15' E.

300

To C.C.E. which is also the N.C.C. of UNION No. 1 of  
 this survey, non. described above,

600

To cor. No. 1 place of beginning survey of exterior  
 boundaries.

Variation at all corners 14° 15' E.

\* \* \* \* \*

LOCATION.

This claim is located on unreserved lands appropria-  
 tely in Township 15 North, Range 2 West, Coconino  
 B. & M., in the Prescott Mining District, Maricopa  
 County, Arizona, <sup>in Prescott Forest Reserve,</sup> and is situated on the North  
 side of the Prescott River, Lot No. 54; on the West by Lode Claims  
 known, Charles Knowles claimant; on the South by  
 claims names unknown, R. A. Gilchrist & S. B. How-  
 land claimants; on the West by <sup>Survey No. 1588,</sup> and <sup>Survey No. 1588</sup> the  
 TCM patented Lode Claim <sup>Survey No. 1588</sup> owned by the  
 Mining Company, <sup>Survey No. 1588</sup> does not adjoin this  
 claim, as there is vacant land intervening.

VEINS.

- FRANKLIN, extends North 15° 30' E. 1000 feet and  
 15° 30' W. 500 feet from the discovery shaft,
- SHANLEY No. 2 extends N. 1° 45' E. 100 feet and S. 1° 45'  
 W. 500 feet from the discovery shaft and shaft,
- <sup>The</sup> MOUNTAIN VIEW, extends N. 15° 30' E. 550 feet and S. 15° 30'  
 W. 500 feet from the discovery shaft,
- W. GIBSON, extends N. 15° 30' E. 555 feet and S. 15° 30' W.  
 505 feet from the discovery shaft,
- W. WILFORD GOULD, extends N. 15° 30' E. 1440 feet and  
 S. 15° 30' W. 500 feet from the discovery shaft,
- W. WILFORD GOULD, extends S. 5° 45' W. 1235 feet from the  
 N.C.C. monument,
- W. WILFORD GOULD, extends N. 5° 45' E. 1400 feet and  
 S. 5° 45' W. 1000 feet from the discovery shaft,
- THE LAST DOLLAR MINE, extends N. 5° 45' E. 500 feet and  
 S. 5° 45' W. 1000 feet from the discovery shaft,