APR 27, 190

JUL 15.1909

4-683

MINERAL SURVEY No. 2647 A & B.

LOI No.		
ARIZONA	Land District.	

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

MONAF	RCH MINING	& SMELTIN	G COMPANY		
		KNO	WN AS THE		
HAZEL, SUI	PHURETTS,	LUCK SURE	, CARTHAGE,	DENVER, WASHING	TON Lodes,
and Monard	h Mining a	& Smelting	Company Mi	ll-Site Claim and	d Water Right,
	*	walk, mi-		75'	D: / : /
		White Pic	acno	Mining	District,
				Arizona.	
Approximat Section	e 32 <i>b</i> /	Township	8 North	Range 3 W of	G.& SR.M.
20000070 :	7	-, 2000,000	7 N.	3 Unsurv	reyed.
Surveye	d under ins	tructions do	ted March	30,, 19 09.	
			. 91h	I- A Ob.	
			by Clou	f ff, Clean	l Surveyor.
	×7 1 7 1	1 /		molace, 19	
(claim locate	d ser	weaton	notrae, 19	
S	Survey comm	nenced	April	3, 1909.	
S	Survey comp	leted.	April	16, , 1909.	
6—822	ice, oug comp			, ==	
Addre	ss of Clai	imants: Age	nt;		

Address of Claimant's Agent; T. P. Dozier,
Wickenburg, Arizona.

SURVEY 2647A. Feet. HAZEL LODE. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 51ft. long, 4ins. square, scribed 1-H-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone $3\frac{1}{2}x3\frac{1}{2}x2$ ft. high, whence
U.S.L.M. 2647 bears S.26°32'W. 74.00ft.

A Hornblende Schist Boulder, 28x24x2lins.
eled BR-x-1-H-2647A, bears N.37°15'E. 14.1ft. 28x24x2lins. high, chis-A Hornblende Schist Boulder 40x18x10ins. high, chiseled BR-X-1-H-2647A, bears S.52°40'E. 23.8ft. Thence N. 15000 W. Va.14°15'E. East End Center. 300.00 Identical with the location. A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed E-EC-H-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone $3\frac{1}{2}$ x $3\frac{1}{2}$ x2ft. high. No bearings available. Identical with Cor. No.1 Sulphuretts lode of this 359.85 survey. Road, course S.70°E. To Corner No.2. 420.00 600.00 Identical with Corner No.2 of the location.

A pine post 5½ft. long, 4ins. square, scribed 2-H2647A, set 18ins. in the ground, surrounded by a mound
of earth and stone 3½x3½x2ft. high, whence

A boulder of Schist and Quartz, 30x17x20ins. high,
Chiseled BR-X-2-H-2647A, bears S.43°55'E. 69.7ft. No other bearings available. Thence S.75°00'W. Va.14°15'E. Va.14°15'E. Road, course S.50°E. 119.00 Intersect line 1-2 carthage lode of this survey at N.45°E. 265.44ft. from Corner No.1-C. Road, course N.45°E. 297.29 1425.00 1459.00 Road, course North. 1500.00 To Corner No.3. Identical with Corner No.3 of the location. A pine post 5½ft. long, 4ins. square, scribed 3-H-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 3½x3½x2ft. high, whence
A Palo Verde tree 4ins. diam. blazed and scribed BT-X-3-H-2647A, bears S.76°07'E. 9.4ft.

A Palo Verde tree 5ins. diam. blazed and scribed BT-X-3-H-2647A, bears S. 9025 E. 31.7ft. Thence S.15000'E. Va.14°15'E. Road, course N. (Leads to Mill-Site: Sur. 2647B.)
Identical with Corner No.4 Sulphuretts lode of this 70.15 240.15 wash 2ft. wide, flows S.75°W. 300.00 West End Center. Identical with the location.

A pine post 51ft. long, 4ins. square, scribed W-EC-Feet H-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone $3\frac{1}{2}x3\frac{1}{2}x2$ ft. high. From this point the ledge of the claim has a course of N.75°E. 540ft. to the discovery cut, thence N.75°E. 960ft. to the E-EC, making a total length on ledge of 1500ft. No bearings available. 555.00 Wash 2ft. wide, flows S. 600.00 To Corner No.4. A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed 4-H-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone $3\frac{1}{2}x3\frac{1}{2}x2$ ft. high, whence
A Palo Verde tree 4ins. diam. Blazed and scribed BT-X-4-H-2647A, bears N.53°40'E. 81.8ft. An outcrop of Diabase rock, chiseled BR-X-4-H-2647A, bears N. 20°50'W. 51.5ft. Corner No. 4 of the location bears S. 7026'E. 8.5ft. Thence N. 75°00'E. TORY SERVICE Va.14015'E. Small wash, flows N.80°W.
Intersect line 4-1 Carthage lode of this survey 200.00 1242.62 S.45°E.539.57ft. from Corner No.1-C. 1500.00 To Corner No.1, the place of beginning. SULPHURETTS LODE. CORE TO MATALET Beginning at Corner No.1. Identical with Corner No.1 of the location and on line 1-2 Hazel lode of this survey. A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed 1-S-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone $3x3xl\frac{1}{2}$ ft. high, whence surrounded by a mound U.S.L.M. 2647 bears S.8º16'E. 418.14ft. No other bearings available. Identionl with Thence N.15000'W. Va.14°15'E. Road, course S.70°W.

Identical with Cor. No.2 Hazel lode of this survey. 60.15 240.15 300.00 East End Center. Identical with the location. A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed E-ECa S-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone $3\frac{1}{2}x3\frac{1}{2}x2$ ft. high. No bearings available. Intersect line 4-1 Denver lode of this survey S. 45°E 364.92ft. from Corner No.4-D. Intersect line 2-3 Carthage lode of this survey S.45°E. 15.1ft. from Cor, No.2-C.
419.54 Identical with Corner No.1 Luck Sure lode of this survey.
600.00 To Corner No.2. Identical with Corner No.2 of the location.

A pine post 5½ft. long, 4ins. square, scribed 2-S2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 4x4x2½ft high. No bearings available. Thence S. 75°00'W. Va.14015'E. Road, course S.25°W. 65.00 Intersect line 4-1 Denver lode of this survey at

S.45°E. 49.42ft. from Cor. No.4-D. Feet. Small wash, flows N.60°W. 299.00 Wash 35ft. wide, flows S.45°W. Edge of wash, flows N.78°W. Road in wash, course N.80°W. 778.00 1200.00 1352.00 Edge of wash. 1415.00 1500.00 To Corner No.3. Identical with Corner No.3 of the location. A pine post 52ft. manaxex long, 4ins. square, scribed 3-S-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 4x4x2ft. high, whence
A Palo Verde tree 6ins. diam. scribed BT-X-3-S-2647A. bears N. 24º 25 'W. 33. 4ft. A Diabase rook boulder 7x4.4x2ft. high, chiseled BR-X-3-S-2647A, bears S.55°25'W. 20.0ft. Thence S.15°00'E. Va.14015'E. Identical with Cor. No. 4 Luck Sure lode of this sur-180.46 vey. West End Center. 300.00 Identical with the location. A pine post 5½ft. long, 4ins. square, scribed W-EC-S-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 3½x3½x2ft. high, whence A Palo Verde tree 5ins. diam. blazed and scribed BT-X-EC-S-2647A, bears N.85°22'E.18.0ft. From this point the ledge of this claim has a course of N.75°60'E. 755ft. to the discovery cut, thence N.75°-00'E. 745ft. to the East End Center, making a total length of ledge on the claim 1500ft. No other bearings available. Identical with Cor. No.3 Hazel lode of this survey. 359.85 Road (to Mill-Site, Sur. 2647B.), course South. 430.00 600.00 To Corner No.4. Identical with Corner No. 4 of the location. A pine post 5½ft. long, 4ins. square, scribed 4-S-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 3½x3½x2ft. high, whence A Birds-eye Forphyry rock in place, 4x4ft.x8ins. high above the ground, chiseled BR-X-4-S-2647A, bears S.36°12 E. 13.9ft. A Palo Verde tree 5ins. diam. blazed and scribed BT-X-4-S-2647A, bears N. 59040 W. 52.0ft. Thence N. 75°00'E. Themse BALLY LEGH DA W Va.14°15'E. Intersect line 4-1 Carthage lode of this survey at S.45°E. 124.05ft. from Corner No.1-C 1500.00 To Corner No.1, the place of beginning. LUCK SURE LODE. Beginning at Corner No.1. Identical with Corner No.1 of the location and on line 1-2 Sulphuretts lode of this survey.

A pine post 52ft. long, 4ins. square, scribed 1-LS2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 4x4x2ft. high, whence U.S.L.M.2647 bears S.11°38'E. 836.4ft. No other bearings available.

Thence N.15.00'W. Feet. Va.14°15'E. 180.46 Identical with Corner No.2 Sulphuretts lode of this 193.60 Road, course West.

300.00 East End Center.

Identical mit. Identical with the location.

A pine post 5½ft. long, 4ins. square, scribed E_EC_
LS_2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 3½x3½x2ft. high. No bearings available. Intersect line 3-4 Denver lode of this survey N. 45°E. 328.60 210,69ft. from Cor. No.4-D. 596.80 To Corner No.2. Identical with Corner No. 2 of the location. A pine post 5½ft. long, 4ins. square, scribed 2-LS-2647A, set 12ins. in the ground to rock, surrounded by a mound of earth and rock 4x4x2ft. high, whence

The face of a cliff of Diabase rock, 20ft. high, chiseled BR-X-2-LS-2647A, bears N.46°51'W. 53.7ft. An outcrop of Diabase rock, chiseled BR-X-2-LS-2647A bears S. 63°48'W. 86.6ft. Thence S. 75°00'W. Va.14°15'E.

Edge of wash 25ft. wide, flows S.75°W.

Leave bed of wash, which here takes a West course. 40.00 156.00 200.00 Edge of wash. Center of wash, flows SW.
Wash 2ft. wide, flows SW. 257.00 1168.00 1500.00 To Corner No.3. Identical with Corner No.3 of the location.

A pine post 5½ft. long, 4ins. square, scribed 3-LS2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 3½x3½x2ft. high.

No bearings available. Thence S. 15°00'E. Va. 14015'E. Enter main wash at mouth of small wash which crosses 277.00 2/3/47/11/08/ line 2-3 at 1168ft. from Cor. No.2-LS. 296.80 West End Center. Identical with the location.
A pine post 5½ft. long, 4ins. square, scribed W-EC-LS-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 3½x3½x2ft. high (while this corner is set in the wash it is so thoroughly protected by natural conditions that no Witness Corner is necessary), A bluffmof Schistose rock, chiseled BR-X-EC-LS-2647A, bears N.29°51'E. 19.85ft.
A Palo Verde tree 4ins. diam. blazed and scribed BT-X-EC-LS-2647A, bears N.77°19'W. 103.5ft. prom this point the ledge of this claim has a course of N.75°E. 747ft. to the discovery cut, thence N.75°E. 753ft. to the East End Center, making total length of the ledge on this claim 1500ft. Road to Wickenburg, course N. 80°W. 350.00 366.00 Leave wash. Identical with Corner No.3 Sulphuretts lode of this 416.34 survey. To Corner No. 4. Identical with Corner No. 4 of the location. A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed 4-LS-2647A, set 18ins. in the ground, surrounded by a mound

Feet. of earth and rock 4x4x2ft. high, whence
An outcrop of Diabase rock 3x15x2ft. high, chiseled
BR-X-4-LS-2647A, bears S.26°33'E. 100.7ft. No other bearings available. Thence N. 75°00'E. 90.00 Road (to Mill-Site, Sur. 2647B), course South. Assay Office. 940.00 990.00 . Mill. Road, course S.25°W. 1133.00 Intersect line 4-1 Denver lode of this survey at S.45°E. 257.80ft. from Cor. No4-D. 1446.44 1500.0010 Corner No.1, the place of beginning. CARTHAGE LODE. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed 1-C-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone $3\frac{1}{2}x3\frac{1}{2}x2$ ft. high, whence

A boulder of Hornblende Schist, 54x28x26ins. high, chiseled BR-X-1-C-2647A, bears S.37046'W. 19.4ft. U.S.L.M. 2647 bears S.57027'E. 708.35ft. No other bearings available. Thence N. 45°00'E. Va.14°15'E. Intersect line 2-3 Hazel lode of this survey at S.75°W. 297.29ft from Cor. No.2-H. 300.00 North West End Center. Identical with the location.
A pine post 51/2ft. long, 4ins. square, scribed NW-EC -C-2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 3½x3½x2ft. high, whence

A boulder of Quartz-Porphyry 3x2.8x1.6ft. high, chiseled BR-X-EC-C-2647A, bears S.7°33!W. 28.6ft. An outcrop of Quartz-Porphyry, 12ins. thick, on Diabase rock, chiseled BR-X-EC-C-2647A, bears N.18°27'E. Intersect line 4-1 Denver lode of this survey at N.45°W. 1208.71ft. from Corner No.1-D. 566.21 To Corner No. 2. A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed 2-C-2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 3\frac{1}{2}x3\frac{1}{2}x2ft. high, whence

Cor. No.2 of the location bears N.7045'E. 48.4ft.

Cor. No.1, Luck Sure lode of this survey bears

N.16056'E. 14.28ft. No other bearings available. Thence S. 45°00'E. Va. 14°15'E. Va.14°15'E.

15.10 Intersect line 1-2 Sulphuretts lode of this survey at N.15000'W. 394.35ft. from Cor. No.1-S Road, course N. 45°E. 193.00 790.00 Intersect line 1-2 Denver lode of this survey at 1208.71 N.45°E. 33.79ft. from Cor. No.1-D

Teet. Wash 3ft. wide, flows S.45°W. 1362.00 1490.20 To Corner No.3. A pine post 5½ft. long, 4ins. square, scribed 3-C-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 4½x4½x2½ft. high, whence Corner No.3 of the location bears N.45°E. 20.4ft. A Palo Verde tree 6ins. diam. blazed and scribed BT-X-3-C-2647A, bears S.56°47'E. 27.3ft. No other bearings available. Thence S. 45000 W. Va. 14015 | E. 300.00 South East End Center.

Identical with the location.

A pine post 5 ft. long, 4ins. square, scribed SE-EC-C2647A, set 18ins. in the ground, surrounded by a mound of earth and stone3x3x2ft. high, whence
A boulder of Andesyte rock 2.6x3x1.6ft. high, chiseled BR-X-EC-C-2647A, bears S.63°59'W. 59.7ft. An Andesyte rock in place, 1.6x2x1.4ft.high above ground, chiseled BR-X-EC-C-2647A, bears S.13047'E. 45.7ft. From this point the ledge of this claim has a course of N. 45°W. 650ft. to the discovery cut, thence N. 45°W. 840.2ft. to the North West End center, making total length of ledge on the claim 1490.2ft. A pine post 52ft. long, 4ins. square, scribed 4-C-2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 3x3x2ft. high, whence Cor. No.4 of the location bears S.16900'E. 10.0ft. A boulder of Andesyte rock 1.6x1.9x1.6ft. high, chiseled BR-X-4-C-2647A, bears N.42934'E. 28.3ft.

A boulder of Andesyte rock 1.4x1.6x1ft. high, chiseled BR-X-4-C-2647A, bears N.58°30'W. 49.8ft. Thence N.45°00'W.
Va.14°15'E.

Ift. wide, flows SW. Wash 3ft. wide, flows SW.

Intersect east end line lacon lode, unsurveyed, Monarch
Mining and Smelting Co. Claimants, at S.15°E. 445.8ft. 167.00 435.87 Intersect line 4-1 Hazel lode of this survey at S. 750 W. from the N.E. Cor. -950.63 257.38ft. from Cor. No. 1-H, and N.E. Cor. Macon lode. Intersect line 4-1 Sulphuretts lode of this survey at 1366.15 S.75°W. 465.14ft. from Cor. No.1-S. 1490.20 To Corner No.1, the place of beginning. DENVER LODE. Beginning at Corner No.1. Identical with Corner No.1 of the location.

A pine post 5½ft. long, 4ins. square, scribed 1-Da

2647A, set 10ins. in the ground to rock, surrounded by a mound of earth and stone $4x4x2\frac{1}{2}$ ft. high, whence
An Andesyte rock in place 7x6x4ft. high above the
ground, chiseled BR-X-1-D-2647A, bears N.83°06'W. 39.0ft.
An Andesyte rock in place 2x11x3ft. high above the
ground, chiseled BR-X-1-D-2647A, bears S.52°05'W. 75.0ft.
U.S.L.M. 2647 bears N.83°39'W. 662.03ft. 1 × 18/1 of or wroning Thence N. 45°00'E.

Va.14015'E.

```
Intersect line 2=3 Carthage lode of this survey at S.45°E. 1208.71ft. from Cor. No.2-C.
Small wash, flows South.
South East End Center.
Identical with the location.
    33.79
 180.00
  300.00
                  Identical with the location.

A pine post 5½ft. long, 4ins. square, scribed SE-EC-D-2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence

A boulder of Birds-eye Porphyry 2x4x2ft. high, chiseled BR-X-EC-D-2647A, bears S.74°11'E. 30.7ft.

No other bearings available.

Intersect line 4-1 Washington lode of this survey at S.45°E. 1223.3ft. from Cor. No.1-W.
  388.30
                  S.45°E. 1223.3ft. from Cor. No.1-W.
To Corner No.2.
  600.00
                           Identical with Corner No.2 of the location.
A pine post 52ft. long, 4ins. square, scribed 2-D-7A, set 18ins. in the ground, surrounded by a mound of
                   2647A, set 18ins. in the ground, surrou earth and rock 32x32x2ft. high, whence
                   A Palo verde tree Sins, diam. blazed and scribed BT-X-2-D-2647A, bears S.18010'E. 19.9ft.
No other bearings available.
                   Thence N.45°00'W.
Va.14°15'E.
Va, 14°15'E.

Road, course West.

1223.30 Intersect line 1-2 Washington lode of this survey at

N.45°E. 211.7ft. from Cor. No.1-W.

1500.00 To Corner No.3.
                             A pine post 5 ft. long, 4ins. square, scribed 3-D-
                   2647A, set on a ledge of rock and surrounded by a mound of earth and stone 5x5x4ft. high ( the ledge is too broke
 222-70
                   en to mark as acorner in place), whence
A ledge of Porphyry rock lxl0ft., chiseled BR-X-3-D-
2647A, bears S.5046'E. 4.0ft.
A Porphyry rock in place 13x7x4ft. high above ground,
                   chiseled BR-X-3-D-2647A, bears S.77°29'W. 111.8ft.
Corner No.3 of the location bears N.45°E. 6.0ft.
                                Thence S. 45°00'W.
                   Va.14°15'E.

Wash 3ft. wide, flows North.

North West End Center.
                    ADJE ALA BLA
   192.00
   300.00
                   Identical with the location.

A pine post 5½ft. long, 4ins. square, scribed NW-EC-D-2647A, set 18ins. in the ground, surrounded by a mound of earth and stone 3½x3½x2ft. high, whence

A Diabase rock in place 2x2x1.4ft. high above ground,
                    chiseled BR-X-EC-D-2647A, bears S.85°14'W. 42.9ft.
                              A Granite boulder 1.4xl.8xl.4ft. high, chiseled BR-X
                   From this point the ledge of this claim has a course of S.45°E. 1200ft. to the discovery cut, thence S.45°E. 300ft. to the South-East End Center, making total length of ledge on this claim 1500ft.

Intersect line 1-2 Tuck Sure lode of this survey at N.15°W. 328.6ft. from Cor. No.1-LS.
To Corner No.4.
                    -EC-D-2647A, bears S.6°36'W. 33.0ft.
   389.31
                    To Corner No. 4.
   600.00
                    Identical with Corner No.4 of the location.

A pine post 5½7t. long, 4ins. square, scribed 4ºD-
2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 3½x3½x2ft. high, whence
    391 17
    T70 000
                    A Palo Verde tree 4ins. diam. blazed and scribed BT-
X-4-D-2647A, bears N.17°15'E. 24.5ft.
A Palo Verde tree 3ins. diam. blazed and scribed BT-
X-4-D-2647A, bears N.69°56'W. 26.8ft.
```

Thence S. 45°00'E. Teet Va.14015'E. Intersect line 2-3 Sulphuretts lode of this survey at S.75°W. 157.75ft. from Cor. No.2-S.
Road, course South-West.
Intersect line 4-1 Luck Sure lode of this survey at 49.42 130.00 257.80 S. 75°W., 53.56ft. from Cor. No.1-LS. 291.29 Intersect line 1-2 Carthage lode of this survey at S.45°W. 33.79ft. from Cor. No.2-C. Intersect line 1-2 Sulphuretts lode of this survey 364.92 at S.15°E. 273.23ft. from Cor. No.2-S.
Road, course South.
Road, course NW.
To Corner No.1, the place of beginning. 526.00 1070.00 1500.00 WASHINGTON LODE. Beginning at Corner No.1. Identical with Corner No.1 of the location.
A pine post 5½ft. long, 4ins. square, scribed 1-W2647A, set 12ins. in the ground to rock, surrounded by a mound of earth and rock 4x4x2ft. high, whence A Hornblende Schist rock in place, 7x15x8ft. high Above the ground, chiseled BR-X-1-W-2647A, bears N.569 23'E. 47.9ft. A Hornblende Schist rock in place, 2.6x4x1.6ft. high above the ground, chiseled BR-X-1-W-2647A, bears N.11001'W. 31.1ft. U. S. L. M. 2647 bears S.3°37'W. 1070.61ft. Thence N. 45°00'E. Va.14015'E. Wash 3ft. wide, flows NW. Intersect line 2-3 Denver lode of this survey at 25.00 211.70 N. 45°W. 1223.3ft from Cor. No.2-D. North West End Center. Identical with the location. A pine post 52ft. long, 4ins. square, scribed NW-E6-W-2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 32x32x2ft. high, whence A Quartz-Porphyry rock in place, 3x20x3ft. high above ground, chiseled BR-X-EC-W-2647A, bears S.64°12'W. A boulder of Andesyte rock 2.6x3x1.6ft high, chiseled BR-X-EC-W-2647A, bears S.19°28'E. 14.55ft.
Wash 8ft. wide, flows West 150ft. then turns to the 410.00 North. 600,00 To Corner No. 2. A pine post 51ft. long, 4ins. square, scribed 2-W-2647A, set 18ins. in the ground, surrounded by a mound of earth and rock 32x32x2ft. high, whence Cor. No.2 of the location bears N.36°02'W. 6.8ft. A Quartzite boulder 3.6x2.6x0.8ft. high, chiseled BR-X-2-W-2647A, bears S.50°31'W. 13.9ft. A Quartzite boulder 3x4x2.6ft. high, chiseled BR-X-2-W-2647A, bears S.87°57'E. 7.7ft. Thence S.45°00'E. Va. 14º15'E. Wash 8ft. wide flows West. 176.00 373.00 Small wash, flows North. 1024.16 Intersect the north side ine Monarch lode, unsurveyed, Monarch Mining and Smelting Co., claimants, at N. 73°45'E. 177.6ft. from the N.W.Cor.

T	Feet.	The state of the s
	1500.00	To Corner No.3.
		Identical with Corner No.3 of the location.
		A pine post 5½ft. long, 4ins. square, scribed 3-W-
	70 100	2647A, set 18ins. in the ground, surrounded by a mound of
		earth and rock 4x4x22ft. high, whence
		A Hornblende Schist Boulder 3.3x3.4x1.7ft. high.
		chiseled BR-X-3-W-2647A, bears N.50°38'W. 3.6ft.
	Printer 1	A Palo Verde tree 6ins. diam. blazed and scribed BT-
		X-3-W-2647A, bears N.85°38'W. 43.6ft.
	July 1	A-3-W-20-1A, Deals M. 00-30 W. 43.01 C.
	SPRETTANI	Management of the Control of the Con
	auto dina	Thence S. 45000 W.
	\$50500	Va. 14°15'E.
	300 00	South East End Center.
	300.00	
	A. C. S. C.	Identical with the location.
	i Ser	A pine post 52ft. long, 4ins. square, scribed SE-E6-
	S-BITTE I	W-2647A, set 18ins. in the ground, surrounded by a mound
		of earth and rock 3½x3½x2ft. high, whence
	37 - 12 - 1	A Quartzite boulder lx3xlft. high, chiseled BR-X-EC-
		W-2647A, bears N.8°22'E. 14.6ft.
1		A Quartzite boulder 2x2xlft. high, chiseled BR-X-EC-
	T Purch	W-2647A, bears N.62°32'w. 31.3ft.
	1000	From this point the ledge of the claim has a course
	4.6	of N.45°W. 300ft. to the discovery cut, thence N.45°W.
		1200ft. to the North-West End Center making total length
		of ledge on this claim 1500ft.
	380.08	Intersect the south side line of Monarch lode, unsurveyed, Mon-
	The second	arch Mining & Smelting Company claimants, at N.73°45'E.
		73.26ft. from the S.W.Con.
	600.00	To Corner No.4.
		Identical with Corner No. 4 of the location.
	735	A pine post 5½ft. long, 4ins. square, scribed 4-W-
	3 7 7 7	2647A, set 18ins. in the ground, surrounded by a mound of
	7.	earth and rock 3½x3½x2ft. high, whence
		A boulder of Birds-eye Porphyry 7x3x6ft. high, chisel-
	7.30.195	ed BR-X-4-W-2647A, bears N.0°18'W. 53.0ft. No other bearings available.
	THE PERSON	No other bearings avairable.
	The same of	THE PROPERTY OF THE PERSON OF
	4.0	Thence N. 45°00'W.
		Va.14°15'E.
	276.70	Intersect line 1-2 Denver lode of this survey at
	2.2	S.45°W. 211.7ft. from Cor. No.2-D.
	545.00	Road, course N.70°W.
	1022.00	Small wash, flows N.30°W. for 50ft. then parallel
		with the line.
	1500.00	
		1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
	4 1 X - 3	CONTRACTOR DE CONTRACTOR DE LA CONTRACTOR DEL CONTRACTOR DE LA CONTRACTOR
	and the sale	AREA. Acres.
	Total a	rea Hazel lode 20.661 Less area in conflict with Sulphuretts lode of this survey, including 2.479 acres, Common conflict Carthage lode. 8.269
	A service of the	Less area in conflict with Sulphuretts lode of
		this survey, including 2.479 acres, common conflict Carthage 13de. 8.269
		Net area Hazel lode 12.392
	De little	
	Total a	rea Sulphuretts lode 20.661
		Less area in conflict with Luck Sure lode of
	1.00	this survey, including 437 acres, common commer Deriver local. 6.214
	1111	Net area Sulphuretts lode 14:447
	A COLUMN	
	Total a	area Carthage lode 100 100 100 100 100 100 100 100 100 10
	7.00	Less area in conflict with
	The state of the s	Hazel lode of this survey (exclusive of 2.479 acres common
		conflict with Sulphuretts lode of this sur-

	Annual Control of the
	vey) Acres.
1 455 1560	which with Sulphuretts lode of this survey 3.064"
A real reservation	twith Denver lode of this survey (ex-
Area in comi	clusive of .034 acres common conflict with
	Grant and of this common 003"
7. 66.44	Sulphuretts lode of this survey)0.903"
1	Net area Carthage lode
100	The state of the s
Total an	rea Denver lode
	Less area in conflict with
	Sulphuretts lode of this survey
155	Sulphuretts lode of this survey of Luck Sure lode,
1 100	with Carthage lode, common conflict 0.057 Acres
12.0	WITH CAPTHAGE lode,
Area in conflic	with Juck Sure lode of this survey 0.825 " 882 including .437 acres common conflict with supports lode. 19.779
	including 437 act Net area Denver Lode
Total a	rea Washington lode
	Less area in conflict with Denver lode of
13,400	this survey
	Net area Washington lode 14.716
0000100	Tell Agency Agency at the state of the state
201000	
7 7	Summary:
1000	
100	Net area Washington lode
7.5	Net area Denver lode
100	Net area Carthage lode
1 3	Net area Sulphuretts lode 14.447 "
6	Net area Hazel lode
00 × 45 × 9	
Total	and net area Luck Sure lode
7	mail to the last of the last o
- Comple	Total Net area of lode claims 95.460 Acres.
A PART TO SA	
	THE LOTS, AND LOTTED AND LINE REPORTS, MANAGEMENT OF A VICTOR OF
	The state of the s
1000	SURVEY No. 2647B.
Children Co.	SURVEY No.2647B.
The state of	SURVEY No.2647B.
MOMADOU	The state of the s
MONARCH	SURVEY No.2647B. MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT.
	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT.
	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5 to long. 4ins. square, scribed 1-M-
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B. set 18ins. in the ground, surrounded by a mound of
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B. set 18ins. in the ground, surrounded by a mound of
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S. L. M. No. 2647 hears N. 13036 E. 12.545.9ft.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S. L. M. No. 2647 hears N. 13036 E. 12.545.9ft.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30'
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available.
	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East.
Feet.	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E.
Feet.	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M/~2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILLSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILLASITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30'E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft long, 4ins. square, scribed 2-M-
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILL SITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high. No bearings available.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high. No bearings available.
Feet. 326.00 421.00	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high. No bearings available.
Feet. 326.00 421.00 466.50	MINING & SMELTING COMPANY MILLASITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647E, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high. No bearings available. Thence South. Va.14°15'E.
Feet. 326.00 421.00 466.50	MINING & SMELTING COMPANY MILLASITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647E, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high. No bearings available. Thence South. Va.14°15'E.
Feet. 326.00 421.00 466.50	MINING & SMELTING COMPANY MILLOSITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M/~2647 bears N.13~36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey*~2647A bears N.16~30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high. No bearings available. Thence South. Va.14°15'E.
Feet. 326.00 421.00 466.50	MINING & SMELTING COMPANY MILLASITE CLAIM AND WATER RIGHT. Beginning at Corner No.1. Identical with Corner No.1 of the location. A pine post 5½ft. long, 4ins. square, scribed 1-M- 2647B, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2½ft. high, whence U.S.L.M. 2647 bears N.13°36'E. 12,545.9ft. Cor. No.4 Carthage lode, Survey 2647A bears N.16°30' E. 12016.4ft. No other bearings available. Thence East. Va. 14°15'E. Road to spring, course S.10°E. Center of wash 30ft. wide, flows SE. To Corner No.2. Identical with Corner No.2 of the location. A pine post 5½ft.long, 4ins. square, scribed 2-M- 2647E, set 18ins. in the ground, surrounded by a mound of earth and rock 4x4x2ft. high. No bearings available. Thence South. Va.14°15'E.

Feet.

A pine post 5½ft. long, 4ins. square, scribed 3ºM-2647B set 18ins. in the ground, surrounded by a mound of earth and rock $4x4x2\frac{1}{2}$ ft. high, whence

The East corner of the curb of a spring of water

bears N. 26°W. 251.2ft.

No other bearings available.

Thence West. Va. 14015'E.

250.00

Center of wash 30ft. wide, flows S.30°W.

466.50 To Corner No.4.

Identical with Corner No. 4 of the location.

A pine post $5\frac{1}{2}$ ft. long, 4ins. square, scribed 4-M-2647B, set 18ins. in the ground, surrounded by a mound of

earth and rock 4x4x2ft. high, whence
A Palo Verde tree 5ins. diam. blazed and scribed BTX-4-M-2647B, bears N.42°20'W. 13.85ft.

No other bearings available.

Thence North. Va.14°15'E.

466.50 To Corner No.1, the place of beginning.

Containing 4.99 Acres.

8-8 SXIX SELL dect A

LOCATION. 200 LOCATION.

The lode claims are situated in Approximate Sec. 32,

Tp.8 N., R.3 W., unsurveyed, of the G.& S.R.M. + The Mill-site and Water Right claim is situated in Approximate Sec. 7, Tp. 7 N., R.3 W., unsurveyed, of the G.

Both the mill-site and the lode claims are in the White Picacho Mining District of Yavapai County, Arizona Territory.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements upon each lode claim, placed thereon by the claimants and their grantors, is not less than five hundred dollars, and that said improvements consist of:

HAZEL LODE: No.1--The discovery cut, which bears from the W.EC of the claim N.75°E. 540ft., 4x10ft. face

running S.15°E. 16ft. in earth and rock, value \$ 100.00 An undivided one-fifth interest in Tunnel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of interest,

Total value of improvements on Hazel lode= \$1226.00

SULPHURETTS LODE:

No.1--The discovery cut, which bears from the W.EC of the claim N.75°E. 755ft. 4ft. wide 5ft. face, running S.10°E. 17ft. in rock. Value \$ 100.00 No.2--A Tunnel, the portal of which bears

N.40W. 334ft. from a point on line 1-4 of this claim N.75°E. 1085ft. from Cor. No.4-S. Value

2 - 11-11-1 CICLY determent in this
of an undivided one-fifth interest in this \$1126.00
No.3 A Shaft, which bears from Cor.
No.4-S N.46°E. 446ft., 4x6x26.5ft. deep.
cho with of the community state with Value and 260.00
No.4 A Cut, which bears from Cor.
No.4-S N.35°E. 230ft., 5ft. wide, 10ft.
face, running N.15°W. 25ft. in earth and
rock. companyed of hebroadeupt of Value 200:00
No.5 A Shaft, the collar of which bears
N. 48°45'W. 300ft. from Cor. No.1-S, 4x6x125ft.
deep in rock. Value 1250.00
We ob and a second
No.6A Tunnel, the portal of which bears
N. 60° 32! W. 334.32 ft. from 18 18 18 18 18 18 18 18 18 18 18 18 18
Corner No. 1,-,-5x7x7ft. to breast, running
N.45°E. in rock. Value 70.00
TV-Fill
Total value of improvements on Sulphuretts lode=\$3006.00
There even a region is build country for the second of the converse
we get mos : sou LUCK SURE LODE: 100 . T shellow give the distant
No.1 The discovery cut, which bears S. 75°W.
753ft. from the E EC of the claim, 4x10ft. face,
running S.759W. 14ft. in earth and rock. Value \$ 100.00
No.2A Cut, which bears S.15°E. 13ft.
from a point S.75°W. 156ft. from Cor. No.2-LS,
5xl2ft. face, running S.15°E.22ft. in rock.
with a chap equipm granting of sale of Value v150.00
No.3A Tunnel, which bears N.30040'E
CA ACL Com the W TO of this claim 5-7ft
64.4ft. from the W.EC of this claim, 5x7ft.
running N. 75°E. 7ft. to breast in rock. Value 70.00
No.4-A Cut, which bears N.85-28 W. 124 15 W. 221.92 ft. from a point N.75 W. 1010 ft. from Cor. No.4-L.5.
ft. from a point S:750W. 1010ft. from Cor. No. 4-1-3
2-S, 6xlOft. face, running North 14ft. in rock.
Value 100.00
No.5A Shaft, which bears 5.50046 B. N.15° W. 82.24 ft.
121ft. from a point NS. 75°NE. 1010ft. from Cor. No. 4-1-3.
No.2-S. 5x7x126ft. deep in rock. Value 1260.00
No.6A Shaft, which bears S.59016 E.118 N.16 W.96
ft. from a point NS. 750 NE 500 ft. from Cor. No. 24-L.S.
-S, 5x8x157ft. deep in rock. Value 1600.00
The same of the state of the same of the s
Total value of improvements on Luck Sure lode= \$3280.00
Total value of improvements on back bare rode- works
CADMILACTO TOTAL
CARTHAGE LODE:
No.1 The discovery cut, which bears
N. 45°W. 650ft. from the SE-EC of the claim,
8x10ft. face, running S.45°W. 10ft. in rock.
V K to des chings to the AT & Value 2 \$1100.00
No.2A Shaft, which bears N.25°E. 225
Pt from the face of the discourant cut Avev.
Tto I for the lace of the discovery out, Thor
ft. from the face of the discovery cut, 4x6x 10ft. deep in rock. Value 100.00
10ft. deep in rock.
An undivided one -fifth interest in Tun-
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts
An undivided one -fifth interest in Tun-
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest 1126.00 Total value of improvements on Carthage lode= \$1326.00
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest 1126.00 Total value of improvements on Carthage lode= \$1326.00 DENVER LODE: No.1The discovery cut, which bears N.45°W. 300ft. from the SE-EC of the claim, 4 x12ft. face, running North 19ft. in rock. Value \$100.00 No.2An Open Cut, the SE corner of which bears N.45°E. 119ft. from a point S.45°E.1250ft.
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest 1126.00 Total value of improvements on Carthage lode= \$1326.00 DENVER LODE: No.1The discovery cut, which bears N.45°W. 300ft. from the SE-EC of the claim, 4 xl2ft. face, running North 19ft. in rock. Value \$100.00 No.2An Open Cut, the SE corner of which bears N.45°E. 119ft. from a point S.45°E.1250ft. from Cor. No.4-D, 26x14ft. face, running N.40°E.
An undivided one -fifth interest in Tun- nel No.2, with its cross-cuts, on Sulphuretts lode of this survey. Value of the interest 1126.00 Total value of improvements on Carthage lode= \$1326.00 DENVER LODE: No.1The discovery cut, which bears N.45°W. 300ft. from the SE-EC of the claim, 4 x12ft. face, running North 19ft. in rock. Value \$100.00 No.2An Open Cut, the SE corner of which bears N.45°E. 119ft. from a point S.45°E.1250ft.

_		
	We 7 A Charlet about the constitutions	NATE OF
	No.3A Shaft, which bears S.57°25'W.25ft.	Se 20
	from the discovery point, 4x6x10ft. deep in rock	700 00
	Value	100.00
	No.4A Shaft, which bears S.76°38'W.58ft.	THE PERSON
	from the discovery point, 4x6x10ft. deep in rock.	
	Value	100.00
	No.5A Shaft, which bears N.45°E, 108ft.	
	from a point S.45°E. 1120ft from Cor. No.4-D,	200 00
	4x6x17ft. deep in rock. Value	170.00
	No.6-An Open Cut, the SW corner of which bears N.54°55'E's from the discovery point, 23x14	DOTE LA
	ft food marriag W 200W 45ft in male W-land	150 00
	ft. face, running N.20°W. 45ft. in rock. Value No.7A Cut, the face of which bears N.45°E.	450.00
	6ft. from a point on the center line of the	The state of
	claim S.45°E. 928ft. from the NW.EC. 5x9ft.	* Marie
	face, running S.45°W. 16ft. in rock and earth.	WATER OF
	Value	120.00
	No.8A Shaft, which bears N.45°E. 34ft.	120.00
	from a point S. 45°E. 290ft. from Cor. No. 4-D,	
	4x4x32ft.deep in rock. Value	320.00
	No.9A Shaft, which bears S.71º14'E. 381ft.	0.00
	from a point S.45°E. \$64.92ft. from Cor. No.42D,	
	4x6x16ft. deep in rock. Value	160.00
	No.10 A Shaft, which bears North 9.4ft.	中国有一
	from center of portal of Tunnel No.12, 4x6x128	
	ft. deep in rock. Value	1280.00
	No.11An Incline Shaft, which bears N.360	440070200
	30'E. 157ft. from a point S.45°E 364.92ft. from	THE RELLA
	Cor. No.4-D, 4x6x23ft. deep, on the incline, in	
		230.00
	No.12A Tunnel, portal of which bears N.45°C	OO'E.
	33.79 ft. from a point on line 4-1, S. 45° E. 549	9.29 ft.
	from Cor. 4, 6x8x49ft. to breast, in rock.	no-spinion
	This tunnel has a course from the portal of	The state of
Ī	S.16°45'W. 25ft., then N.89°49'W. 24ft. Value	800.00
	No.13 A Tunnel, the portal of which bears	
	S.45°W. 80ft. from a point N.45°W. 285ft.	12.17.04
	from Cor. No.2-D, 4x7ft. running S.40°E. 7ft.	
H	to breast, in rock. Value	70.00
	No.14A Shaft, which bears N.59005'W.	G. J. L.
	182ft. from Cor.No.2-D, 4x6x8ft. deep in rock	S. Warner
	and earth. Value	80.00
	No.15A Shaft, which bears N.63°08'W. 97	348.00
	ft. from Cor. No.2-D, 4x6x10ft. deep in rock.	700.00
	Value	100.00
	An undivided one-fifth interest in Tunnel	CC - ST F
	No.2 Sulphuretts lode of this survey. Value of interest	1126.00
	value of Hitelest	1.120.00
	Total value of improvements on Denver lode =	\$5706.00
	10001 Volume of Lings of Ontollog of Bolly of acco	
H	WASHINGTON LODE:	To the same
	No.1 The discovery cut, which bears N. 45°W.	Water Charles
	300ft. from the SE.EC of the claim, 4x10ft. face	ST CONT.
	running West 20ft. in earth and rock. Value	120.00
d	No.2A Shaft, which bears from Cor. No. 4,	11
9	N. 9° 42' W. 403.74 feet, 4 x 6 x	
-	10ft. deep in rock. Value	100.00
	An undivided one-fifth interest in Tunnel	Total Control
	No.2 Sulphuretts lode of this survey.	and a con-
	Value of interest	1126.00
	As an armin of the same of the	Angelon
	Total value of improvements on Washington lode	\$1346.00
1	NOTE: The tunnel referred to as No. 2 of Sulp	humatta
	mornie outlier referred to as no. 2 of but	TIME COURS

lode of this survey, from the portal has a course of S.88°36'E. 487ft. to breast. 472ft. from the portal two cross-cuts are opened; one having a course of S.1°30'W. 52.8ft. to the breast, the other running N.1°E. 24ft. to the breast. This tunnel is of common value to the Hazel, Sulphuretts, Denver, Washington and Carthage lodes of this survey, but is not of any value to the Luck Sure lode, being at too high a level to reach this lode by any system of laterals that might be devised, the main part of the Luck Sure lode laying at a lower level and across a deep wash from the tunnel.

Shaft No.5 on the Sulphuretts lode and Shaft No.10 on the Denver lode both open into this tunnel and serve as chutes for the ore from the upper workings on its way to the mill. This tunnel and its cross-cuts are designed to serve as a way for reaching the ore in the various claims embraced in this survey, except the Luck Sure lode,

and to facilitate its transportation to the mill.

I was told that there are drifts at the bottom of Shafts 5 and 6 of the Luck Sure lode, but, as they are inaccessible on account of water, I do not include them in the estimate.

Shaft NO.5 of Luck Sure lode has a claimed depth of about 150ft., but it is filled with muck up to the point of my measurement, hence I give only my actual measurement of depth.

The surface embraced by these claims is very broken, ascending sharply on the North, West and South toward Cor. No.2-D and Cor.No.1-H, which are on the peaks of two of the three buttes known locally as "The Three Black Buttes", the third peak lying midway between these points.

OTHER IMPROVEMENTS.

A house of lumber and corrugated metal, the SW corner of which bears, from a point on line 2-3 Sulphuretts lode S.75°W. 1010ft. from Cor. No.2-S, S.48°16'W. 240ft., 12x28ft., course of long sides N.40°E.

A blacksmith shop of lumber and corrugated metal, the NW corner of which bears, from a point on line 2-3 Sulphuretts lode S.75°W. 500ft. from Cor. No.2-S, S.41°

15 E. 271ft., 14x14ft., course of the sides North.

A powder magazine, the door of which bears from the same point S.33°E. 300ft. This is an excavation in

same point S.33°E. 300ft. This is an excavation in earth and rock, fitted with door, size 5x8ft.

A mill, the North corner of which bears from the same point S.14°E. 157ft., 48x43ft. of corrugated metal, lumber and concrete, course of long sides S.45°E. This mill is equipped with crusher, Chili mill, Buckingham filter, three Frue Vanners, 50HP Gas Engine, pumps and all smaller equippment necessary for its operation.

An assay house, the North corner of which bears from the same point S.4°30'W. 176ft., 12x20ft. of adobe and lumber, course of long sides S.45°E. This building is completely equipped with apparatus for assaying.

A metal distillate storage tank 8x4ft. bears from the same point S.3°15'W. 296ft.

the same point S.3º15'W, 296ft.

A dam of concrete and rock, the face of which intersects the center line of the Luck Sure lode 1007ft. from the W.EC, at a point 7ft. from the North end of the dam, runs S.45°E. 47ft. The face, or wall, of the dam is 7ft. high by 7ft. thick.

There is also approximately 3500ft. of well built wagon road traversing the claims.

All the above improvements belong to the claimants herein.

A shaft, which bears, from a point on line 2-3 Sulphuretts lode S.75°W. 1010ft. from Cor. No.2-S, S.48°16' W. 240ft., 4x6x15ft. deep in rock and earth, claimant unknown.

A cut which bears, from a point on line 2-3 Washington lode S.45°E. 514ft. from Cor. No.2-W, S.45°W. 192ft. claimant unknown.

INSTRUMENT.

This survey was made with a Gurley Surveyor's Model transit with solar attachment. Courses were deflected from the true meridian as determined by solar observations. The distances were measured with a 100ft steel tape.

NOTE:-This survey agrees with the location certificates, but in a few instances, noted in the field notes, the location monument had been built at the wrong point, due to incorrect measurements by the locators.

CONTIGUOUS LOCATIONS.

Beside the Monarch lode claim, unsurveyed, mentioned in the notes of Washington lode, and the Macon lode claim, unsurveyed, mentioned in the notes of the Carthage lode, there are no adjoining or conflicting claims, except the Jennie K lode claim, unsurveyed, Monarch Mining & Smelting Co. claimants, the South side line of which is identical with line 2-3 Luck Sure lode of this survey.

A DESCRIPTION OF U. S. L. M. NO. 2647 AND ITS LOCATION.

The Monument is a boulder of Hornblende Schist 20ins.wide, 14ins. thick, 38ins. long, set 16ins. in the ground to rock.

On the North face is chiseled USLM, in letters 3ins. high, and immediately below these letters 2647 is chiseled 2½ins. high. On top of the Monument a cross(X) is chiseled 2½x2½ins., the intersection of the arms being point of connection.

S.30°30'W. 5ft. from the monument is a mound of rock 6ft.

base, 5ft. high.

BEARINGS (Va.14°15'E.):

A ledge of Hornblende Schist, 20ins. high above the ground chiseled BR-X-USIM-2647, bears N.80°16'W. 9.47ft.
A boulder of Hornblende Schist, 2x3x3ft. high, chiseled

BR-X-USLM-2647# bears N.27045'E. 31.25ft.

The North pinnacle of White Picacho mountain bears S.80°20' East.

The chimney of the hotel at Hot Springs Junction bears S.10°20 W.

The center leg of a water tank tower at Wickenburg bears

S. 81º15 W. The South-West corner of C. W. Platt's house at Wickenburgh bears S.81°35'W.

The stack of the electric plant at Wickenburg bears S.79º34 W.

LOCATION:

The Monument is located in Lat. 33°58'30"N., as determined by three observations for latitude made with a Gurley Surveyor's Model Transit with a Gurley Solar attachment, and lies within the bounds of Carthage lode, Survey 2647A, Monarch Mining & Smelting Co. Claimants, S.26°32'W. 74.0ft. from Corner No.1, Hazel lode, same survey and claimants.

It stands on the extreme South point of the westernmost of three mountains locally known as "The Three Black Buttes", approximately 7½ miles to the East (see bearings) of the town of Wickenburg, Maricopa County, Arizona, but the monument lies within the bounds of Yavapai County.

The location is very prominent and nearly every point in the radius controlled by the monument is accessible by direct sight, while in every direction but the North-East direct sight on it is only controlled by the power of the glass used.

The Monument was established to control Survey 2647 A&B.

albut S. akii.

Respectfully submitted,

U. S. Mineral Surveyor.

Wickenburg, Arizona, April 26, 1909.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Albut J. Okin,
United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
boundaries described in the foregoing field notes of the survey of the mining claimsof
Monarch Mining & Imelting Company
known as the Hazel Quelphrusells, Lucks Ques, Carthags, Desser, Washington Lots and Monarch Mining & Smelting Co., Mill Set Claim and and showing the respective capacities in which they acted.
L. Wilkinson, Chainman.
John W. Davis., Chainman.
, Axman.
, Flagman.
FINAL OATHS OF ASSISTANTS.
We, LU Wilkinson.
and John M. Davis, do solemnly swear that we assisted albut
J. Okii, United States Mineral Surveyor, in marking the corners and surveying
the boundaries of the mining claim of 2 Monarch Mining &
Smelting Company
known as the Hagel, Sulfibrustle, Lucho Cure, Carthage, Jensey, Mashing to and Monacelo Mining & Smithing Company Mill-Site Claric and Water Region represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
and correctly executed, and the corner and boundary monuments established according to law and the instruc-
tions furnished by the United States Surveyor-General for Cryona.
L. Vilkinson, Chainman.
John M. Laves, Chainman.
, Axman.
, Flagman.
Subscribed and sworn to by the above-named persons before me this
day of April , 1909
/ Affluy
Mary Elle
1/2/Con- El puro Nov4/16/9/2 6-1013

FINAL OATH OF U.S. MINERAL SURVEYOR.

I, Albert D. Akin	, U. S. Mineral Surveyor,
do solemnly swear that, in pursuance o	f instructions received from the United States
Surveyor General for Arizo	na , dated
The Control of the Co	, I have, in strict conformity to the laws of the
United States, the official regulations ar	nd instructions thereunder, and the instructions
of said Surveyor General, faithfully and	d correctly executed the survey of the Mining
Claim of Monerch Mining	& Smelting Company
	, known as the Carthage, Benver, Washington lodes,
situate in White Picacho	Company Mill-Site Claim and Water 'Right Mining District,
Yayapai	County, Arizona approximate in Section
5/32 Township No. 8 North	Range No.3 W. of the G.& S.R.M.(unsurveyed)
and designated as Survey No. 2647 A	Range No.3 W. of the G.& S.R.M.(unsurveyed) & B, as represented
	ately show the boundaries of said mining claim
	the ground, and described in the attached copy
	ceived by me from the Surveyor General with
The second secon	s of said survey have been established and per-
	law, official regulations and instructions there-
A CONTRACTOR OF THE PARTY OF TH	r that the foregoing are the true and original
	ort therein, and that the labor expended and
	claim by claimant or 1ts grantors
	e character, extent, location, and itemized value
	cularity and full detail, and that no portion of
-	to this claim has been included in the estimate
of expenditures upon any other claim.	to this claim has been included in the estimate
of expenditures upon any other ciaim.	
	albut A akin
	albut A. akii, U. S. Mineral Surveyor.
•	
Subscribed and sworn to by the said	albert N. akin
II S. Mineral Surveyor, before me	Mary a. Boyd notary Public
tor Maricopa learning a	Crisana Per this 26 th
day of Opsil 19	Mary a. Boyd, Notary Belie Origana Per. this 26 th
	Mary a Bayd.
my commission	Mary a Dayd,
1 10 1044 610	

Affidavit of Five Hundred Dollars Improvements.

We, John Witherlay and E.S. Jones.
of lawful age, being first duly sworn according to law, depose and say: That we are acquainted with the
Hazel, Sulphuretts, Luck Sure, Carthage, Denver
and Washington mining claim, situate in White Picacho
mining district, Yavapai County, Arizona Territory, for which
the Monarch Mining & Smelting Company
ha. 5 made application for survey prior to application for patent under the provisions of the Act of Congress
approved May 10, 1872; and that the labor done and improvements made thereon by the applicant and
for each claim
their grantor exceed five hundred dollars in value, and further that we are not personally interested
in said mine.
1. Edfored
TERRITORY OF ARIZONA, County of Maricopa 88:
County of Marcopa
Sworn to and subscribed before me this 26th day
[SEAL.] of Open 1909
mulommission Mary a. Bayd.
Mary a. Boyd. 11786bi00-2-04 expires- Nov. 27th 1912. Notary Public

AMENDED

Motice of Mining Location

LODE CLAIM

	Co fill dubom in tiday Concern:
	This Mining Claim, the name of which is the Hazel
	Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and
	purchased by H.A.Suttle, a citizen of the United States, and deeded by
	him to the Monarch Mining & Smelting Co. (Locator must insert either "a citizen of the United States," or "who has declared his intention to become a citizen of the United States.")
	the undersigned, on the day of 1919
	The length of this claim is Fifteen hundred (1500) feet,
	and We claim five hundred thirty-seven (537) feet,
	in a Westerly direction and nine hundred
	sixty-three (963) feet in an Easterly direction from
	the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with three hundred (300) feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the
	East to the West
	The claim is situated and located in the White Picacho Mining District, in
	Yavapai County, in the Territory of Arizona, about ten miles
	in an Easterly direction from Wickenburg and about 21 miles North
	of the White Cloud mine
-	
1	The surface boundaries of the claim are marked upon the ground as follows: Beginning at
•	a monument of stone
	at a point in a Westerly direction five hundred thirty seven from
	the discovery shaft (at which this notice is posted), being in the center of the South-West end line of said claim; thence S. 15° E., 300 feet to a monument of stone
	end line of said claim; thence b. 13 M., 300 leet to a morrower of said claim; thence , being the South West corner of said claim; thence
	N. 75° E. 15000 feet to a monument of stone , being at the
	South East corner of said claim; thence N 15° W. 300 feet
	to a monument of stone at the center of the North East end of said claim; thence N.15° W. 300 feet to a monument of stone , being at the
	North East corner of said claim; thence S. 75° W. 1500
	feet to a monument of stone at the North West corner of said claim;
	thence S 15° E 300 feet to the place of beginning.
	All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.
	This is an Amended Location Notice of the Hazel
	Mining Claim, located by H.A. Suttle, a citizen of the United States
	on the 28th day of
	June 1904, and recorded in Book 72 of Records of Mines, at
	page 441, in the office of the County Recorder of the aforesaid County of Yavapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice.
-	Dated and posted on the ground this 24 day of March 1909.
	Monarch Mining and Smelting Co By C W Platt supt
	Filed and Recorded at request of T.P. Dozier, March 25, A.D. 1909, at
Ari	9:45 o'clock A.M., Book 86 of Mines, page 29, Records of Yavapai County, zona. (SEAL) J.C.Bradbury, County Recorder.
4	The U. W. Makeli Company Park Blooms Asirons 1,000m

AMENDED

Motice of Mining Location

22

LODE CLAIM

To All Whom It May Concern:	
This Mining Claim, the name of which is the Luck Sure	
Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and	
purchased by C.W.Platt a citizen of the United States, and deeded by	
him to the Monarch Mining & Smelting Co., (Locator must insert either "a citizen of the United States," or "who has declared his intention to become a citizen of the United States.")	
the undersigned, on the day of 19	
The length of this claim is fifteen hundred (1500) feet,	
and we claim seven hundred twenty-two (722) feet,	
in a westerly direction and seven hundred	
seventy-eight (778) feet in an Easterly direction from	
the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together	
with three hundred (300) feet in width of the surface grounds, on each	
side of the center of said claim. The general course of the lode deposit and premises is from the East to the West	
The claim is situated and located in the White Picacho Mining District, in	
Yavapai County, in the Territory of Arizona, about twelve miles	
in an Easterly direction from Wickenburg and joins the Sulphu-	
retts on the West side line.	
The surface boundaries of the claim are marked upon the ground as follows: Beginning at	
a monument of stone	
at a point in a Westerly direction 722 feet from	
the discovery shaft (at which this notice is posted), being in the center of the South-West	
end line of said claim; thence S. 15° E 300 feet to a monument of stone	
, being the South-West corner of said claim; thence	
N 75° E 1500 feet to a monument of stone , being at the South East corner of said claim; thence N 15° W. 300 feet	
to a monument of stone at the center of the North-East end of said claim;	
thence N. 15° W. 300 feet to amonument of stone, being at the	
North-East corner of said claim; thence S. 75° W. 1500	
feet to a monument of stone at the North West corner of said claim;	
thence S. 15° E. 300 feet to the place of beginning.	
All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.	
This is an Amended Location Notice of the Luck Sure	
Mining Claim, located by C.W.Platt, a citizen of the United States	
on the 19th day of May 1905, and recorded in Book 73 of Records of Mines, at	
page 376 in the office of the County Recorder of the aforesaid County of Yavapai	
to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice.	
Dated and posted on the ground this 24 day of March 19.09.	
led and recorded at request of) ozier, March 25, A.D. 1909, at 9:45) Monarch Mining & Smelting Co.	
ck A.M., Book 86 of Mines, page 27) By CW Platt	
der of Yavapai County, Arizona.) Supt. SEAL) J. C. Bradbury, County Recorder)	
1-09-2m	
Denuty Recorder	

AMENDED

Motice of Mining Location

LODE CLAIM

	Co Litt waisont he share woncern.
	This Mining Claim, the name of which is the Carthage
	Mining Claim, situate on lands belonging to the United States of America, and in which there
	are valuable mineral deposits, was entered upon and located for the purposes of exploration and
	purchased by Frank Ryland, a citizen of the United States, and deeded
	by his widow and legal heir to the Monarch Mining & Smelting Co. (Locator must insert either "a citizen of the United States," or "who has declared his intention to become a citizen of the United States,")
	the undersigned, on the 28 day of May 1900
	The length of this claim is fifteen hundred (1500) feet,
	and we claim six hundred fifty (650) feet,
	in an Easterly direction and Eight hundred
	fifty (850) feet in a Westerly direction from
	the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together
	with three hundred (300) feet in width of the surface grounds, on each
	side of the center of said claim. The general course of the lode deposit and premises is from the
	South East to the North West
	The claim is situated and located in the White Picacho Mining District, in
	Yavapai County, in the Territory of Arizona, about eight miles
-	in a North East direction from the Hassayampa river
-	
•	
-	The surface boundaries of the claim are marked upon the ground as follows: Beginning at
	a monument of stone
	at a point in a South Restanty direction 650 fort from
	at a point in a South Easterly direction 650 feet from
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim;
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone , being at the
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E 1500
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W. 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E. 1500 feet to a monument of stone at the South-East corner of said claim;
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E 1500
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone peing at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone peing at the South-West corner of said claim; thence S. 45° E. 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W. 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E. 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone , being at the South-West corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, ***********************************
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W. 300 feet to a monument of stone being at the South-West corner of said claim; thence S. 45° E. 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898. **EXXX** and recorded in Book 50 of Records of Mines, at page 349 in the office of the County Recorder of the aforesaid County of Yayapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone he ing at the South-West corner of said claim; thence S. 45° E. 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, **Example of the General County of Yavapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice is made and posted to correct errors in the description in the said original Location Notice
	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 500 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the South-East corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the Dace of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, ***Exist** and recorded in Book 50 of Records of Mines, at page 349in the office of the County Recorder of the aforesaid County of Yayapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice.
Fil	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 500 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the South-East corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the Dace of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, ***Exist** and recorded in Book 50 of Records of Mines, at page 349in the office of the County Recorder of the aforesaid County of Yayapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice.
Fil	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 500 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the South-East corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the Dace of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, ***Exist** and recorded in Book 50 of Records of Mines, at page 349in the office of the County Recorder of the aforesaid County of Yayapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice.
Fil que A.I	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 500 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the South-East corner of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the Dace of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, ***Exist** and recorded in Book 50 of Records of Mines, at page 349in the office of the County Recorder of the aforesaid County of Yayapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice.
Fil que A.I Boo	at a point in a. South Easterly direction 650. feet from the discovery shaft (at which this notice is posted), being in the center of the. South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° E 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, **Exist** and recorded in Book 50 of Records of Mines, at page 349in the office of the County Recorder of the aforesaid County of Yavapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice. Dated and posted on the ground this 24 day of March 1909. ed and Recorded at rest of T.P. Dozier, March 25, Monarch Mining & Smelting Co. Dated and posted on the ground this 24 day of March 1909.
Fill que A.I. Bood pro	at a point in a South Easterly direction 650 feet from the discovery shaft (at which this notice is posted), being in the center of the South-East end line of said claim; thence N. 45° E 300 feet to a monument of stone , being the North East corner of said claim; thence N. 45° W 1500 feet to a monument of stone , being at the North West corner of said claim; thence S. 45° W 300 feet to a monument of stone at the center of the North-West end of said claim; thence S. 45° W 300 feet to a monument of stone he ing at the South-West corner of said claim; thence S. 45° E. 1500 feet to a monument of stone at the South-East corner of said claim; thence N. 45° E 300 feet to the place of beginning. All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled, "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901. This is an Amended Location Notice of the Carthage Mining Claim, located by Frank Ryland, a citizen of the United States on the 26th day of October 1898, **Example of the General County of Yavapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice is made and posted to correct errors in the description in the said original Location Notice

TERRITORY OF ARIZONA,)
:ss.
County of Yavapai.)

I, J.C.Bradbury, County Recorder in and for the aforesaid County, and Custodian of the records of such office, do hereby certify that I have compared the foregoing copies with and that the same are true and correct copies of the amended noitces of locations, as the same appear of record in my said office, of the following named Lode Mining Claims, situate in White Picacho Mining District, Yavapai County, Arizona, viz:-

LUCK SURE Lode Mining Claim, the amended notice of location whereof is of record in Book 86 of Mines, page 27, records of Yavapai County, Arizona Territory.

CARTHAGE Lode Mining Claim, the amended notice of location whereof is of record in Book 86 of Mines, page 28, said records.

HAZEL Lode Mining Claim, the amended notice of Location whereof is of record in Book 86 of Mines, page 29, said records.

IN WITNESS WHEREOF, I have bhereunto setumy hand and affixed my official seal, this 25th day of March, A.D. 1909.



Amended

Notice of Mining Location. Quartz Claim.

To All Whom It May Concern:

This mining claim, the name of which is the Sulphuretts. Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by Frank Ryland the undersigned, on the 26th day of Oct 1898

The length of this claim is 1500 feet, and I claim 750 feet in an Easterly direction and 750 feet in a Westerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the East to the West

The claim is situated and lonted in the White Pecach Mining District, in Yavapai County, in the Territory of Arizona, about eight miles in a N.Easterly direction from the Hassayamp river

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stone at a point in an Easterly direction 750 feet from the discovery shaft(at which this notice is posted), being in the center of the East end line of said claim; thence N. 15° West 300 feet to a Mon. of stone, being the N.East corner of said claim; thence S. 75° West 750 feet to a Mon. of stone at the center of the North side line of said claim; thence S. 75° West 750 feet to a Mon. of stone being at the N.West corner of said claim; thence S. 15° East 300 feet to a Mon. of stone at the center of the West end of said claim; thence S. 15° E. 300 feet to a Mon of stone, being at the S.West corner of said claim; thence N. 75° East 750 feet to a Mon. of stone at the S.East corner of said claim; thence N. 75° East 750 feet to a Mon. of stone at the S.East corner of said claim; thence N. 75° East 750 feet to a Mon. of stone at the S.East corner of said claim; thence N. 75° East 750 feet to a Mon. of stone at the S.East corner of said claim; thence N. 75° East 750 feet to a Mon. of stone at the S.East corner of said claim; thence N. 15° West 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines," approved March 20th, 1895.

Dated and posted on the ground this 26th day of Oct 1898

Frank Ryland.

Filed and recorded at request of Frank Ryland Dec. 274 A.D. 1898 at 9:00 o'clock A.M. Book 50 of Mines Page 348. Records of Yavapai County, Arizona.

(SEAL) W.I.Johnson

By E.C. Averyt

Deputy Recorder.

TERRITORY OF ARIZNA,)
:ss.
County of Yavapai.

I, J.C.Bradbury, County Recorder in and for the the aforesaid County of Yavapai, and Custodian of the Records of such office do hereby certify that I have compared the foregoing with, and that the same are true and correct copies of the location notices, as appears of record in my said office, of the following described lode mining claims, situate in the White Picacho Mining District, Yavapai County, Arizona, viz:-

SULPHURETTS, the amended notice of location whereof is recorded in Book 50 of Mines, at page 348, records of Yavapai County, Arizona.

CARTHAGE, the original notice of location whereof is of record in Book 50 of Mines, at page 349, said records.

V DENVER, the original notice of location whereof is of record in Book 51 of Mines, at pages 68-69, said records.

WASHINGTON; the original notice of location whereof is of record in Book 51 of Mines, at page 70 said records.

HAZEL, the original notice of location whereof is of record in Book 72 of Nines, at page 441, said records.

LUCK SURE, the original notice of location whereof is of record in Book 73 of Mines, at page 376, said records.

JENNIE K., the original notice of location whereof is of record in Book 73 of Mines, at page 377, said records)

(MACON, the original mnotice of location whereof is of record in Bock 78 of Mines, at page 261, said records)

IN WITNESS WHEREOF, I have hereunto set my hand and affixed my official seal, this 3rd day of March, A.D. 1909.

Amended

Notice of Mining Location. Quartz Claim.

To All Whom It May Concern:

This mining claim, the name of which is the Denver Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by Frank Ryland the undersigned, on the 26th day of Oct 1898

The length of this claim is 1500 feet, and I claim 300 feet in a South easter_direction and 1200 feet in a North West direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the South East to the North West

The claim is situated and located in the White Pecach Mining District, in Yavapi County, in the Territory of Arizona, about eight miles in a N. East direction from the Hassayamp River

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stone at a point in a S.East direction 300% feet from the discovery shaft (at which this notice is posted), being in the center of the S.East end line of said claim; thence N.45° East 300 feet to a mon. of stone, being the N.East corner of said claim; thence N.45° West 750 feet to a mon. of stone at the center of the N.East side line of said claim; thence N.45° W.750 feet to a mon. of stone being at the N.West corner of said claim; thence S.45° W. 300 feet to a mon of stone at the center of the N.West end of said claim; thence S.45° W., 300 feet to a mon of stone, being at the S.West corner of said claim; thence S.45° E 750 feet to a mon. of stone being at the center of the S.West side line of said claim; thence S.45° East 750 feet to a monument at the S.East corner of said claim; thence N.45° East 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of An ACt of the General Assembly of Arizona, entitled "An Act Concerning Mines," approved March 20th, 1895.

Dated and posted on the ground this 26th day of Oct 1898

Frank Ryland

Filed and recorded at request of Frank Ryland Dec. 27# A.D. 1898 at 9:00 o'clock A M. Book 50 of Mines Page 347 = Records of Yavapai County, Arizona.

(SEAL)

W.I Johnson

County Recorder

By E.C.Averyt,

Deputy Recorder.

Amended

Notice of Mining Location. Quartz Claim.

To All Whom It May Concern:

This mining claim, the name of which is the Washington. Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by Frank Ryland the undersigned, on the 26th day of October 1898

The length of this claim is 1500 feet, and I claim 300 feet in a South east direction and 1200 feet in a N.West direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the syrface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the South east to the North West

The claim is situated and located in the W.Pecach Mining District, in Yavapi County, in the Territory of Arizona, about eight miles in a N.East direction from the Hassayampa river.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at a monument of stone at a point in a S.East direction 300 feet from the discovery shaft, (at which this notice is posted), being in the center of the S.East end line of said claim; thence N.45° East 300 feet to a monument of stone, being the N.East corner of said claim; thence N.45° W. 750 feet to a mon. of stone at the center of the N.East side line of said claim; thence N.45° W.750 feet to a mon. of stone being at the N. West corner of said claim; thence S. 45° W.300 feet to a mon. of stone at the center of the N.W. end of said claim; thence S.45° W.300 feet to a mon. of stone being at the S.West corner of said claim; thence S. 45° East 750 feet to a mon. of stone at the S.East corner of said claim; thence S.45° East 750 feet to a mon. of stone at the S.East corner of said claim; thence N.45° East 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act Concerning Mines," approved March 20th,1895.

Dated and posted on the ground this 26th day of Oct 1898

Frank Ryland.

Filed and recorded at request of Frank Ryland Dec. 27 4 A.D. 1898 at 9:00 o'clock A M. Book 50 of Mines Page 346 = Records of Yavapai County, Arizona.

(SEA L) W.I.Johnson

County Recorder.

By E.C.Averyt,

Deputy Recorder.

TERRITORY OF ARIZONA ,)
: ss.
County of Yavapai.)

I, J.C.Bradbury, County Recorder in and for the aforesaid County of Yavapai, and Custodian of the records of such office, do hereby certify that I have compared the foregoing copies with, and that the same are true and correct copies of the that notice of location, as the same appear of record in my said office, of the following named lode mining claims, situate in the Write Picacho Mining District, Yavapai County, Arizona Territory, to-wit:-

WASHINGTON, the amended notice whereof is of record in Book 50 of Mines, at page 346, records of Yavapai County, Arizona.

DENVER, the amended notice whereof is of record in Book 50 of Mines, at page 347, records aforesaid.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed my official seal, this 8th day of March, A.D. 1909.

Location Motice

of

The Monarch Mining & Smelting Company

Mill=Site Claim and Water Right.

know All Men by these Presents, That we the undersig	ned, have this
day located a Mill-Site for the purpose of erecting suitable works for reducing t	he ores of the
Sulphuretts, Hazel Luck Sure Washington, Denver&Carthage	Mining Claims
situate in White Picacho	Mining
district, Yavapai County,	Arizona
Territory. The exterior boundaries of said Monarch Mining & Smelting.	Company
Mill-Site Claim, are as follows, viz.:	
Commencing at a monument of stone at N. E. corner of claim, and running westerly direction, 466½ feet to monument of stone at N. W. corner of claim southerly direction, 466½ feet to monument of stone at S. W. corner of claim easterly direction, 466½ feet to monument of stone at S. E. corner of claim northerly direction, 466½ feet to monument of stone at N. E. corner of claim beginning. This location may be more generally described as being situated two and	m, thence in a n, thence in an n, thence in a a and place of
miles South of the above named claims, about seven mile	
Hot Springs junction and eight miles East of the Hassay	vampa river
That we have also located in connection with the said Mill-Site claim	re of the water
The dimensions of the ditch for diverting the water from its natural cour	se at the head,
being as follows: wide at top,	wide at
bottom, in depth, with a uniform grade of	
to the rod.	
Dated on the ground, this 24th day of Narch	1909.
Witness	
monarch mining & Smelting Co	
J W Meador By C W Platt Supt.	•
T.P.Desier	

AFFIDAVIT

This is to certify that the undersigned T.Persons Dozier and Guy T.Sayre, are citizens of the United States and reside at Wickenburg, Maricopa County, Arizona, and are familiar with the mill site, the location of which is hereto attached, that they have examined said mill site and to the best of their knowledge and belief said mill site is located on non mineral bearing land.

Witness our hands this 24th, day of March, A.D. 1909.

T.Persons Dozier

Guy T Sayre.

Before me D.J.Curry a Notary Public in and for the County of Maricopa Territory of Arizona, personally appeared T.Persons Dozier and Guy
T.Sayre to me personally known to be the same persons, and who acknowledged that they signed the same as their free and voluntary act and
deed for the uses and purposes therein set forth.

Witness my hand and Notarial Seal, this 24th, day of March, A.D.1909.

(Notarial Seal)

D.J.Curry Notary Public

My com. expires Nov. 14th, 1912.

Filed and recorded at request of T.P. Dozier, March 25, A.D. 1909, at 9:45 o'clock A.M., Book 6 Mill-Sites and Water Rights, pages....., Records of Yavapai County, Arizona.

(SEAL) J.C.Bradbury,
County Recorder.

TERRITORY OF ARIZONA,) : ss.
County of Yavapai.)

I, J.C.Bradbury, County Recorder in and for the aforesaid County of Yavapai, and Custodian of the records of such office, do hereby certify that I have compared the foregoing copy with, and that the same is a true and correct copy of the MONARCH MINING & S MELTING COMPANY Mill-Site Claim and Water Right, the situated in the White Picacho Mining District, Yavapai County, Arizona, the notice of location whereof is of record in Book 6 Mill) Sites and Water Rights, page...., Records of Yavapai County, Arizona.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed my official seal, this 25th day of March, A.D. 1989



U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

10.50	Phoenix, Arizona,	
	September 8, 190	9.
I, U. S. Surveyor-General forI	District of Arizona	
	anscript of the Field Notes, return and approval of the surv	
of the mining claim of Mona	arch Mining & Smelting Company.	
MONARCH MINING & SMELTIN	SURE, CARTHAGE, DENVER, WASHINGTON LODES . NG COMPANY MILL-SITE CLAIM AND WATER R	AND IGHT
	WHITE PICACHO	
	County, ARIZONA	
in Section	No. 8 N., Range No. 3 W., G&SRM, Unsure, ar	nd
designated as Survey No. 2647 A	& B., has been correctly copied from the originals on file	in
this office; that said Field Notes furni	sh such an accurate description of said mining claim as will,	if
incorporated into a patent, serve fully t	o identify the premises, and that such reference is made there	in
And I further certify that five he	than and fix the locus thereof. than and fix the locus thereof. than and that said improvements or its grantors, and that said improvements.	re- its
consist of 12 cuts, 5 tunnels	s, 15 shafts and 2 cross-cuts, total	
value \$15,890.00. Tunne	el No. 2 on the Sulphuretts lode, value	е
\$5630, being a common imp	provement for the development and bene-	fit
of the Hazel, Sulphuretts	s, Denver, Washington and Carthage lode	es,
an undivided 1/5 interest	t therein, value \$1126, is properly cre	e-
dited to each of said loo	les, the Luck Sure lode of this group,	
which can not be developed	ed or benefited by said tunnel No. 2,	:
not sharing in the value	thereof.	
and that no portion of said labor or in	aprovements has been included in the estimate of expenditure	es
upon any other claim.		
I further certify that the plat there	of, filed in the U.S. Land Office at Phoenix,	
Arizona is corre	ect and in conformity with the foregoing Field Notes.	
	Frank S. Ingalls,	
Unit	ted States Surveyor-General for Arizona.	

SURVEYOR=GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

	Phoenix, Ari	zona,	
		September 8,	, 190 <mark>.9</mark> •
I, U. S. Surveyor-General for	District of	Arizona	
do hereby certify that the foregoing	ng and hereto attached F	ield Notes and Return	of the Survey of the
Mining Claim of MONAR			
			, known as the
HAZEL, SULPHURETTS, LUC MONARCH MINING & SMEL			
situate in	WHITE PICACHO		mining district,
YAVAPAI	County,	A	RIZONA.
Approx. in Section 32 , 7	lownship No. 8 N. 7 N.	,, Range No	3 W., G&SRM.
Unsur., designated	as Survey No	2647A & B	
executed byAlber	t D. Akin	, U	. S. Deputy Mineral
Surveyor, April 3	-16,	, 1909, under m	y instructions dated
March 30,	, 190.9, have been	critically examined an	d the necessary cor-
rections and explanations made, a	nd the said Field Notes	and Return, and the St	arvey they describe,
are hereby approved. A true cop	y of the copy of the loca	ation certificate filed by	the applicant for
survey is included in the field not	08.		
	Mans	& Ingali	h-
	U. S. Su	rveyor-General for	rizona.

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956) BUREAU OF LAND MANAGEMENT M.S. 2647B ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Monarch Mining & Smelting Company Mill-Site and Water Right, Mineral Survey No. 2647B, located in sections 17 and 18, Township 7 North, Range 3 West, Gila and Salt River Meridian, Arizona, is hereby canceled.

This claim has not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Monarch Mining & Smelting Company Mill-Site and Water Right, M.S. 2647B, was canceled April 2, 2002, by memo 9605 (956) M.S. 2647B, which is now a part of the original field notes."

April 2, 2002 Date

Chief Cadastral Surveyor of Arizona