

SEP. 20. 1911

JAN 18 1913
MAR 6 1913

(4-683.)

Mineral Survey No. 2949.

Lot No.

Arizona Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Anona Gold Mining & Milling Company.

KNOWN AS THE

Anona No. One, Anona No. Two.

Plomosa Mining District,

Yuma County, Arizona

Section 28, approximately in Township 4 N., Range 17 W. Unsur.

Surveyed under instructions dated August 16, 1911.

by Edgar C. Dietrich,
U. S. Deputy Mineral Surveyor

Claim located see location notices, 1

Survey commenced August 31, 1911.

Survey completed September 3, 1911.

Attorney for claimants:-

Thos. F. Wilson,

Atty-at-Law,

Tucson, Arizona.

1.

Feet.

SURVEY No. 2949.

Anona No. One.

Beginning at Cor. No. 1, identical with Cor. No. 1 of the location, which is an old mound of stone 2 ft. base and 2 ft. high, I set a pine post 4x4x3ft. ~~set~~ 18" in ground surrounded by a md. of stone, 1-A No.1-2949 on its south-easterly face. No bearing trees or bearing rocks available.

U.S.L.M. 2949, bears N.44°-41'W., 721.6 ft. dist.

Thence S.22°-54'E.

Var. 12°-55'E.

153 Wash, 10 ft. wide, course easterly, begin ascent.

280 Top of spur easterly, begin descent.

432 Wash, 15 ft. wide, ^{course easterly} begin ascent.

530 Top of spur easterly, begin descent.

635 Wash, 10 ft. wide, ^{course easterly} begin ascent.

790 Top of spur easterly, begin descent.

1195 Wash, 20 ft. wide, course south-easterly, begin ascent.
To Cor. No. 2.,

1400 Old location monument, which is a md. of stone 2 ft. base 1½ ft. high, bears S.32°W., 53' dist. I set a pine post 4x4x3ft., ~~set~~ 18" in ground and surrounded by a md. of stone, marked 2-A No.1-2949 on its north-easterly face. No bearing trees or bearing rocks available.

Thence S.78°-51'E.

Var. 12°-55'E.

Over descending ground.

100 Wash, 10 ft. wide, course north-easterly, begin ascent.

300 Southerly end center monument, identical with the location which is a mound of stone 2' base, 18" high. Begin descent.

470 Wash, 15' wide, course northerly, begin ascent.

600 To Cor. No. 3,

Old location mon., which is a md. of stone 2' base, 2' high bears S.32°E., 50 ft. dist. I set a pine post 4x4x3ft. set 18" in ground and surrounded by a mound of stone, marked 3-A.No.1-2949 on its north-westerly face. No bearing trees or bearing rocks available.

Thence N.22°-54'W.

Var. 12°-55' E.

2.

Feet. Over descending ground.
 200 Wash, 15' wide, course easterly, begin ascent.
 215 Trail, easterly and westerly.
 550 Top of spur easterly, begin descent.
 658 Trail, easterly and westerly.
 1015 Wash 20 ft. wide course south-easterly, begin ascent.
 1300 Top of spur, easterly, begin descent.
 1400 To Cor. No. 4, identical with the location, which is a md.
 of stone 2' base, 2' high. I set a pine post 4x4x3 ft. set
 18" in the ground. marked 4-A.No.1-2949 on its south-west-
 erly face. No bearing trees or bearing rocks available.

Thence N. 78°-51'W.

Var. 12°-55'E.

Over descending ground.

120 Wash 10 ft. wide, course northerly.
 260 Trail, northerly and southerly.
 300 Northerly end center monument, identical with the location,
 which is a mound of stone 2' base, 2' high.
 600 To Cor. No. 1 the place of beginning.

Anona No. Two.

Beginning at Cor. No. 1, identical with the location, and
 with Cor. No. 1 of the Anona No. 1 lode of this survey as
 previously set and described by me, I mark same 1-A.No.2-
 2949 on its north-easterly face. From this corner U.S.L.M.
 2949 bears N.44°-41'W., 721.6 ft. dist.

Thence N. 22°-54'W.

Var. 12°-55'E.

Over ascending ground.

440 Top of spur, easterly, begin descent.
 613 Wash, 15' wide, course easterly, begin ascent.
 710 Top of spur, easterly, begin descent.
 806 Wash, 10ft. wide, course easterly, begin ascent.
 940 Top of spur, north-easterly, begin descent.
 1050 Wash, 15' wide, course north-easterly, begin ascent.
 1500 To Cor. No. 2,
 Old location monument, which is a md. of stone 2' base, 18"
 high, bears N.48°W., 67 ft. dist. I set a pine post 4x4x3ft
~~set~~ 18" in the ground and surrounded by a mound of stone,

Feet. marked 2-A.No.2-2949 on its south-easterly face.

No bearing trees or bearing rocks available.

Thence S. 78°-51'E.

Var. 12°-55'E.

Over descending ground.

300 Northerly end center monument, identical with the location, which is a mound of stone 2' base, 2' high.

600 To Cor. No. 3, Identical with the location, which is a md. of stone 2' base, 2' high. I set a pine post 4x4x3ft., set 18" in the ground and surrounded by a md. of stone, marked 3-A.No.2,2949, on its south-westerly face. No bearing trees or bearing rocks available.

Thence S. 22°-54'E.

Var. 12°-55'E.

Over descending ground.

30 Wash, 15' wide, course north-easterly, begin ascent.

190 Top of spur, north-easterly, begin descent.

338 Wash, 10' wide, course north-easterly, begin ascent.

470 Top of spur, north-easterly, begin descent.

689 Wash, 10' wide, course north-easterly, begin ascent.

900 Top of spur, easterly, begin descent.

1110 Wash, 10' wide, course north-easterly, begin ascent.

1200 Top of spur, north-easterly, begin descent.

1298 Wash, 10' wide, course north-easterly, begin ascent.

1500 To Cor. No. 4, identical with the location and with Cor. No. 4 of the Anona No. One lode of this survey as previously set and described by me. I mark same 4-A.No.2-2949 on its north-westerly face.

Thence N. 78°-51'W.

Var. 12°-55'E.

300 Southerly end center monument, identical with the location and with the northerly end center monument of the Anona No. One lode of this survey as previously described.

600 To Cor. No. 1 the place of beginning.

Areas.

Total area of Anona No. One lode 15.981 acres

Total area of Anona No. Two lode 17.119 acres

LOCATION.

These claims are located approximately in Sec. 28 T. 4 N R. 17 W., ^{Uns.} G. & S.R., B. & N., in the Plomosa Mining District, Yuma County, Arizona.

ADJACINING CLAIMS.

All of the land surrounding these claims is vacant land.

COURSE OF VEIN.

The presumed course of vein of the Anona No. One lode is from the southerly end center monument, N.22°-54'W., 1400 feet to the northerly end center monument.

The presumed course of vein of the Anona No. Two lode is from the southerly end center monument, N.22°-54'W., 1500 feet to the northerly end center monument.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements upon these claims, placed thereon by the claimants and their grantors, is not less than five hundred dollars for each claim and that the said improvements consist of:-

Anona No. One lode. From the southerly end center mon.

No. 1, Discovery Shaft, 4x6x12 ft.

bears N.22°-54'W., 715' dist. Value \$120

No. 2, Cut, 6x6x12 ft.

bears N.22°-54'W., 700' dist. Value \$120

No. 3, Shaft, 4x6x21 ft.

bears N.22°-54'W., 685' dist. Value \$250

No. 4, Shaft, 4x6x6 ft.

bears N.22°-54'W., 520' dist. Value \$60

From Cor. No. 2.

No. 5, Shaft 4x6x10 ft.

bears N.9°-45'E., 420' dist. Value \$100

From Cor. No. 1.

No. 6, Shaft, 4x6x20 ft.

bears S.44°E., 600' dist. Value \$300

NOTE:- This shaft constitutes part of the assessment and developement work for the Anona No. Two lode. This shaft is located in a gulch at the foot of a steep mountain

whose slope faces southerly. Beyond this point, economical handling of the ores from the surface would be impossible, as it is, down this gulch would be the only feasible route for a wagon road to reach these claims from the outside. For this reason I credit one-half of the value of this shaft to the Anona

No. Two lode. Value credited to this claim \$150

No. 7, Cut, 6x6x20 ft., course S.23°-45'E.

bears S.44°-00'E. 600' dist. Value \$200

(Shaft No. 6 is located at the mouth of this cut).

No. 8, Tunnel 5x6x90' an extension of Cut

No. 7 and on the same course. Value \$1000

Total value of the improvements on the

Anona No. One lode \$2000

Anona No. Two lode.

From the southerly end center monument,

No. 1, Discovery Cut, 6x6x20'

bears N.22° 54'W., 450' dist. Value \$200

From Cor. No. 4

No. 2, Cut 4x6x18ft.

bears N.72°-45'W., 290 ft. dist. Value \$180

~~No. 3, One-half the value of Shaft No. 6~~

Anona No. One lode *credited to this claim* Value \$150

Total value of the improvements on the

Anona No. Two Lode. \$530.

INSTRUMENT.

This survey was made with a Young & Sons light mountain transit. The courses were deflected from the true meridian as determined by a Polaris observation. The distances were measured with a 300' and a 100' graduated steel tape.

POLARIS OBSERVATION.

At Cor. No. 3 of the Anona No. One lode, on Aug. 31, 1911, at 8h 55m P.M. l.m.t., I observe Polaris at eastern elongation. I mark the line thus established by an iron pin 12" long driven in the ground 300' north of cor. On Sept. 1, 1911, at 7h 20m A.M. l.m.t. I deflect the azimuth of

6.

Polaris $1^{\circ}-24'$ to the west and from the true meridian thus established I deflect the courses of the lines of this survey.

 MINERAL MONUMENT.

As there is no public land corner or U. S. Min. Mon. in the vicinity of these claims, I proceed to establish U. S. Location Monument No. 2949, by setting a malpais rock $40 \times 20 \times 8$ inches set 20 inches in the ground and surrounded by a mound of stone and scribed U.S.L.M. 2949 with a monument of stone 6 feet base and 5 feet high alongside.

This U.S.L.M. is located on a prominent peak and from the same I take the following bearings:-

Picacho Mt. bears $S.46^{\circ}-00'E$.

Finger Rock on west end Eagle Tail Mts. bears $S.1^{\circ}-10'E$.

A high pointed peak bears $N.88^{\circ}-50'E$.

Castle Dome Peak bears $S.1^{\circ}-37'W$.

Quartzite (windmill at old stage station) bears $N.82^{\circ}-28'W$ about $9\frac{1}{2}$ miles dist.

House at the Guadalupe mine (on the road from Quartzite to Vicksburg) bears $N.33^{\circ}-22'E$. about 3 miles dist.

Salazar smelter bears $N.47^{\circ}-05'E$. about 1 mile dist.

 Note:- The difference between the discovery as given in the location notices and as found on the ground is due to errors in the location notices as the original monuments of the location were found in good shape and were the only monuments in this vicinity.

Edgar C. Dietrich
 U. S. Mineral Surveyor.

1.

Feet.	
	<p style="text-align: center;">SURVEY No. 2949.</p> <p style="text-align: center;">Anona No. One.</p> <p>Beginning at Cor. No. 1, identical with Cor. No. 1 of the location, which is an old mound of stone 2 ft. base and 2 ft. high, I set a pine post 4x4x3ft. set 18" in ground surrounded by a md. of stone, 1-A No.1-2949 on its south-easterly face. No bearing trees or bearing rocks available.</p> <p>U.S.L.M. 2949, bears N.44°-41'W., 721.6 ft. dist.</p> <p style="text-align: center;">Thence S.22°-54'E.</p> <p style="text-align: center;">Var. 12°-55'E.</p>
153	Wash, 10 ft. wide, course easterly, begin ascent.
280	Top of spur easterly, begin descent.
432	Wash, 15 ft. wide, ^{course easterly} begin ascent.
530	Top of spur easterly, begin descent.
635	Wash, 10 ft. wide, ^{course easterly} begin ascent.
790	Top of spur easterly, begin descent.
1195	Wash, 20 ft. wide, course south-easterly, begin ascent.
	To Cor. No. 2.
1400	Old location monument, which is a md. of stone 2 ft. base 1½ ft. high, bears S.32°W., 53' dist. I set a pine post 4x4x3ft., set 18" in ground and surrounded by a md. of stone, marked 2-A No.1-2949 on its north-easterly face. No bearing trees or bearing rocks available. <p style="text-align: center;">Thence S.78°-51'E.</p> <p style="text-align: center;">Var. 12°-55'E.</p> <p>Over descending ground.</p>
100	Wash, 10 ft. wide, course north-easterly, begin ascent.
300	Southerly end center monument, identical with the location which is a mound of stone 2' base, 18" high. Begin descent.
470	Wash, 15' wide, course northerly, begin ascent.
600	To Cor. No. 3.
	Old location mon., which is a md. of stone 2' base, 2' high bears S.32°E., 50 ft. dist. I set a pine post 4x4x3ft. set 18" in ground and surrounded by a mound of stone, marked 3-A No.1-2949 on its north-westerly face. No bearing trees or bearing rocks available. <p style="text-align: center;">Thence N.22°-54'W.</p> <p style="text-align: center;">Var. 12°-55'E.</p>

Feet.	Over descending ground.
200	Wash, 15' wide, course easterly, begin ascent.
215	Trail, easterly and westerly.
550	Top of spur easterly, begin descent.
658	Trail, easterly and westerly.
1015	Wash 20 ft. wide course south-easterly, begin ascent.
1300	Top of spur, easterly, begin descent.
1400	To Cor. No. 4, identical with the location, which is a md. of stone 2' base, 2' high. I set a pine post 4x4x3 ft. set 18" in the ground, marked 4-A.No.1-2949 on its south-westerly face. No bearing trees or bearing rocks available.
	Thence N. 78°-51'W.
	Var. 12°-55'E.
	Over descending ground.
120	Wash 10 ft. wide, course northerly.
260	Trail, northerly and southerly.
300	Northerly end center monument, identical with the location, which is a mound of stone 2' base, 2' high.
600	To Cor. No. 1 the place of beginning.

	Anona No. Two.
	Beginning at Cor. No. 1, identical with the location, and with Cor. No. 1 of the Anona No. 1 lode of this survey as previously set and described by me, I mark same 1-A.No.2-2949 on its north-easterly face. From this corner U.S.L.M. 2949 bears N.44°-41'W., 721.6 ft. dist.
	Thence N. 22°-54'W.
	Var. 12°-55'E.
	Over ascending ground.
440	Top of spur, easterly, begin descent.
613	Wash, 15' wide, course easterly, begin ascent.
710	Top of spur, easterly, begin descent.
806	Wash, 10ft. wide, course easterly, begin ascent.
940	Top of spur, north-easterly, begin descent.
1050	Wash, 15' wide, course north-easterly, begin ascent.
1500	To Cor. No. 2,
	Old location monument, which is a md. of stone 2' base, 18" high, bears N.48°W., 67 ft. dist. I set a pine post 4x4x3ft set 18" in the ground and surrounded by a mound of stone,

Feet. marked 2-A, No. 2-2949 on its south-easterly face.

No bearing trees or bearing rocks available.

Thence S. 78°-51' E. 84.9 ..

Var. 12°-55' E.

Over descending ground.

300 Northerly end center monument, identical with the location, which is a mound of stone 2' base, 2' high.

600 To Cor. No. 3, identical with the location, which is a mound of stone 2' base, 2' high. I set a pine post 4x4x3ft., set 18" in the ground and surrounded by a mound of stone, marked

3-A, No. 2, 2949, on its south-westerly face. No bearing trees

or bearing rocks available.

Thence S. 22°-54' E.

Var. 12°-55' E.

Over descending ground.

30 Wash, 15' wide, course north-easterly, begin ascent.

190 Top of spur, north-easterly, begin descent.

338 Wash, 10' wide, course north-easterly, begin ascent.

470 Top of spur, north-easterly, begin descent.

689 Wash, 10' wide, course north-easterly, begin ascent.

900 Top of spur, easterly, begin descent.

1110 Wash, 10' wide, course north-easterly, begin ascent.

1200 Top of spur, north-easterly, begin descent.

1298 Wash, 10' wide, course north-easterly, begin ascent.

1500 To Cor. No. 4, identical with the location and with Cor. No. 4 of the Anona No. One lode of this survey as previously set and described by me. I mark same 4-A, No. 2-2949 on its north-westerly face.

Thence N. 78°-51' W.

Var. 12°-55' E.

300 Southerly end center monument, identical with the location and with the northerly end center monument of the Anona No. One lode of this survey as previously described.

600 To Cor. No. 1 the place of beginning.

Areas.

Total area of Anona No. One lode 15.981 acres

Total area of Anona No. Two lode 17.119 acres.

LOCATION. These claims are located approximately in Sec. 28 T. 4 N R. 17 W. ^{Uns.} G. & S.R., B. & M., in the Plomosa Mining District, Yuma County, Arizona.

ADJOINING CLAIMS.

All of the land surrounding these claims is vacant land.

COURSE OF VEIN.

The presumed course of vein of the Anona No. One lode is from the southerly end center monument, N. 22°-54'W., 1400 feet to the northerly end center monument.

The presumed course of vein of the Anona No. Two lode is from the southerly end center monument, N. 22°-54'W., 1500 feet to the northerly end center monument.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements upon these claims, placed thereon by the claimants and their grantors, is not less than five hundred dollars for each claim and that the said improvements consist of:-

- Anona No. One lode. From the southerly end center mon. No. 1, Discovery Shaft, 4x6x12 ft. bears N. 22°-54'W., 715' dist. Value \$120
- No. 2, Cut, 6x6x12 ft. bears N. 22°-54'W., 700' dist. Value \$120
- No. 3, Shaft, 4x6x21 ft. bears N. 22°-54'W., 685' dist. Value \$250
- No. 4, Shaft, 4x6x6 ft. bears N/22°-54'W., 520' dist. Value \$60
- From Cor. No. 2.
- No. 5, Shaft 4x6x10 ft. bears N. 9°-45'E., 420' dist. Value \$100
- From Cor. No. 1.
- No. 6, Shaft, 4x6x20 ft. bears S. 44°E., 600'-dist. Value \$600

NOTE:- This shaft constitutes part of the assessment and development work for the Anona No. Two lode. This shaft is located in a gulch at the foot of a steep mountain

whose slope faces southerly. Beyond this point, economical handling of the ores would be impossible, as it is, down this gulch would be the only feasible route for a wagon road to reach these claims from the outside. For this reason

I credit one-half of the value of this shaft to the Anona

No. Two lode. Value credited to this claim \$150

No. 7, Cut, 6x6x20 ft., course S.23°-45'E.

bears S.44°-00'E.600' dist. Value \$200

(Shaft No. 6 is located at the mouth of this cut).

No. 8, Tunnel 5x6x90'an extension of Cut

No. 7 and on the same course. Value \$1000

Total value of the improvements on the

Anona No. One lode \$2000

Anona No. Two lode.

From the southerly end center monument,

No. 1, Discovery Cut, 6x6x20'

bears N.22° 54'W., 450' dist. Value \$200

From Cor. No. 4

No. 2, Cut 4x6x18ft.

bears N.72°-45'W., 290 ft. dist. Value \$180

NOTE

No. 3, One-half the value of Shaft No. 6

Anona No. One lode credited to this claim Value \$150

Total value of the improvements on the

Anona No. Two Lode. \$530.

INSTRUMENT.

This survey was made with a Young & Sons light mountain transit. The courses were deflected from the true meridian as determined by a Polaris observation. The distances were measured with a 300' and a 100' graduated steel tape.

POLARIS OBSERVATION.

At Cor. No. 3 of the Anona No. One lode, on Aug. 31, 1911, at 8h 55m P.M. l.m.t., I observe Polaris at eastern elongation. I mark the line thus established by an iron pin 12" long driven in the ground 300' north of cor. On Sept. 1, 1911, at 7h 20m A.M. l.m.t. I deflect the azimuth of

Polaris 1°-24' to the west and from the true meridian thus established I deflect the courses of the lines of this survey.

MINERAL MONUMENT.

As there is no public land corner or U. S. Min. Mon. in the vicinity of these claims, I proceed to establish U. S. Location Monument No. 2949, by setting a malpais rock 40x20x8 inches set 20 inches in the ground and surrounded by a mound of stone and scribed U.S.L.M. 2949 with a monument of stone 6 feet base and 5 feet high alongside.

This U.S.L.M. is located on a prominent peak and from the same I take the following bearings:-

- Picacho Mt. bears S.46°-00'E.
- Finger Rock on west end Eagle Tail Mts. bears S.1°-10'E.
- A high pointed peak bears N.88°-50'E.
- Castle Dome Peak bears S.1°-37'W.
- Quartzite (windmill at old stage station) bears N.82°-28'W about 9½ miles dist.
- House at the Guadalupe mine (on the road from Quartzite to Vicksburg) bears N.33°-22'E, about 3miles dist.
- Salazar smelter bears N.47°-05'E, about 1 mile dist.

Note:- The difference between the discovery as given in the location notices and as found on the ground is due to errors in the location notices as the original monuments of the location were found in good shape and were the only monuments in this vicinity.

Edgar C. Dietrich
U. S. Mineral Surveyor.

On J 13 Barnaga ... in Sec 25 T 4 N, R 18 W

At Cor. No. 3 of the Anona No. One lode, on Aug. 21, 1911, at 5h 5m A.M. I observe Polaris at eastern elongation. I mark the line thus established by an iron pin 12" long driven in the ground 300' north of cor. On Sept. 1, 1911, at 7h 50m A.M. I deflect the azimuth of

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Edgar C. Dietrich

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

Anona Gold Mining & Milling Company

known as the Anona No. One ~~and the~~ Anona No. Two

and showing the respective capacities in which they acted.

James F. Hughes, Chairman.

Budd Dozier, Chairman.

_____, Assman.

_____, Flagman.

FINAL OATHS OF ASSISTANTS.

We, James F. Hughes

and Budd Dozier, do solemnly swear that we assisted _____

Edgar C. Dietrich, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of _____

Anona Gold Mining & Milling Company

known as the Anona No. One ~~and the~~ Anona No. Two

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the United States Surveyor-General for Arizona.

James F. Hughes, Chairman.

Budd Dozier, Chairman.

_____, Assman.

_____, Flagman.

Subscribed and sworn to by the above-named persons before me this 18th

day of September, 1911

J. G. Power

Notary Public, Pima County, Arizona Territory.
By Commission Expires May 16th, 1912.

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Edgar C. Dietrich, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for Arizona, dated August 16, 1911., I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of The Anona Gold Mining & Milling Company, known as the Anona No. One Anona No. Two, situate in La Plomosa Mining District, Yuma County, Arizona, in Section approximately in 28, Township No. 4 N., Range No. 17 W., G. & S. R. B. & M., and designated as Survey No. 2949, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or its grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Edgar C. Dietrich
U. S. Mineral Surveyor.

Subscribed and sworn to by the said U. S. Mineral Surveyor, before me
day of September, 1911

Edgar C. Dietrich
a Notary Public
this 18th

H. G. Powers
Notary Public, Pima County, Arizona Territory.
My Commission Expires May 16th, 1912.

AUG. 16. 1911

NOTICE OF MINING LOCATION.

LODE CLAIM.

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the Anona No Two. Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by Anona Gold Mining & Milling Co. Citizens of the United States the undersigned, on the 20th day of January 1904

The length of this claim is 1500 feet and we claim 750 feet in a North Easterly direction, and 750 feet in a South Westerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposite and premises is from the North East. to the South West.

The claim is situated and located in the Plomosa Mining District, in Yuma County, in the Territory of Arizona, about 9 miles in a Easterly direction from Quartzsite and $1\frac{1}{2}$ miles in a Northerly direction from Dripping Springs.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at monument. at a point in a Southerly direction 750 feet from the discovery shaft (at which this notice is posted), being in the center of the South end line of said claim; thence 300 feet to a Monument., being the South East. corner of said claim; thence 1500 feet to a Monument., being at the North East corner of said claim; thence 300 feet to a Monument. at the center of the North end of said claim; thence 300 feet to a monument., being at the North West corner of said claim; thence 1500 feet to a Monument. at the South West corner of said claim; thence 300 feet to the place of beginning.

#2

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and an^{of} Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16th, 1901.

Dated and posted on the ground this 20# day of January 1904

Anona Gold Mining &

Milling Co. by Jno A Rivers

Manager

Filed and recorded at request of Jno A Rivers

February 27. A D 1904 at 4 P M.

C. P. Cronin.

County Recorder.

TERRITORY OF ARIZONA,)
) ss.
 COUNTY OF YUMA.)

I, J. M. POLHAMUS, COUNTY RECORDER in and for the County of Yuma, Territory of Arizona, do hereby certify that the foregoing is a true, full and correct copy of The Anona No. Two Mining Claim as filed for record in my office on the 27th day of February, A. D. 1904., and as appears of record Book Q, of Mines, Page 172, et seq., Records of Yuma County aforesaid.

In Witness Whereof I have hereunto set my hand and affixed my seal of office this 14th day of August, A. D. 1911.



J. M. Polhamus

County Recorder.

By

J. T. Tully

Deputy Recorder.

NOTICE OF MINING LOCATION.

AUG. 16 1911

LODE CLAIM.

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the "Anona No. One" Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purpose of exploration and purchase by The Anona Gold Mining & Milling Co Citizens of the United States the undersigned, on the 20th day of January 1904

The length of this claim is 1500 feet and We claim 750 feet, in a North Easterly direction, and 750 feet in a South Westerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the North East to the South West.

The claim is situated and located in the Plomosa Mining District, in Yuma. County, in the Territory of Arizona, about 9 Miles in a Easterly direction from Quartzsite and $1\frac{1}{2}$ Miles in a Northly direction from Dripping Springs

The surface boundaries of the claim are marked upon the ground as follows: Beginning at monument of stone at a point in a South Westly direction 750 feet from the discovery shaft (at which this notice is posted), being in the center of the South end line of said claim; thence 300 feet to a monument of stone, being the South East corner of said claim; thence 1500 feet to a monument, being at the North East corner of said claim; thence 300 feet to a monument. at the center of the North end of said claim; thence 300 feet to a Monument, being at the North West corner of said claim; thence 1500 feet to a Monument. at the South West corner of said claim; thence 300 feet to the place of beginning.

#2

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and an ^{of} Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16th, 1901.

Dated and posted on the ground this 20th day of January 1904

Anona Gold Mining and

Milling Company by

John A. Rivers

Manager.

Filed and recorded at request of John A. Rivers

February 27 A. D. 1904 at 4 P. M.

C. P. Cronin.

County Recorder.

TERRITORY OF ARIZONA,)
) SS.
 COUNTY OF YUMA.)

I, J. M. POLHAMUS , COUNTY RECORDER in and for the County of Yuma, Territory of Arizona, do hereby certify that the foregoing is a true, full and correct copy of The Anona No. One Mining Claim as filed for record in my office on the 27th day of February, A. D. 1904., and as appears of record Book Q of Mines, Page 171, et seq;, Records of Yuma County aforesaid.

In Witness Whereof I have hereunto set my hand and affixed my seal of office this 14th day of August, A. D. 1911.



J. M. Polhamus

County Recorder.

By

J. D. Gentry

Deputy Recorder.

U. S. SURVEYOR GENERAL'S FINAL CERTIFICATE ON
FIELD NOTES.

DEPARTMENT OF THE INTERIOR,
OFFICE OF U. S. SURVEYOR GENERAL,

Phoenix, Arizona,

May 8, 1913.

I, U. S. Surveyor General for Arizona,
do hereby certify that the foregoing transcript of the Field Notes, return and approval
of the Survey of the mining claim of

ANONA GOLD MINING & MILLING COMPANY

, known as the ANONA NO. ONE, ANONA NO. TWO,

, situate in PLOMOSA

Mining District, YUMA County,

ARIZONA, in Section Approx. 28, Township No. 4 N.,

Range No. 17 W., Uns., and designated as Survey

No. 2949, has been correctly copied from the originals on
file in this office; that said Field Notes furnish such an accurate description of said
mining claim as will, if incorporated into a patent, serve fully to identify the premises,
and that such reference is made therein to natural objects or permanent monuments as
will perpetuate and fix the *locus* thereof.

And I further certify that five hundred dollars' worth of labor has been expended
or for each of
or improvements made upon said mining claim by claimant or its grantors, and
that said improvements consist of 5 shafts, 4 cuts and 1 tunnel, total
value \$2530. Shaft No. 6 on the Anona No. One lode being a com-
mon improvement for the benefit and development of both the
Anona No. One and Anona No. Two lodes of this survey, an undivided
half interest therein, value \$150, is properly credited to each
of said claims.

and that no portion of said labor or improvements has been included in the estimate of
expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix,
Arizona, is correct and in conformity with the foregoing Field Notes.

Frank S. Ingalls,

United States Surveyor General for Arizona.

4-687.

SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

Office of U. S. Surveyor-General,

Phoenix, Arizona,

May 8, 1913

I, U. S. Surveyor-General for Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

ANONA GOLD MINING & MILLING COMPANY.

, known as the

ANONA NO. ONE, ANONA NO. TWO.

situate in PLOMOSA Mining District, YUMA County, ARIZONA.

in Section Approx. 28, Township No. 4 N., Range No. 17 W., Uns.

, designated as Survey No. 2949

executed by Edgar C. Dietrich, U.S. Deputy Mineral

Surveyor, August 31, -Sept. 3, 1911, 190, under my instructions dated

August 16, 1911, 190, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for

survey is included in the field notes.

Frank A. Ingalls

U. S. Surveyor-General for Arizona.