NO. 20 1975

4-683.

Minaral Curvey No 7006			
Mineral Survey No. 3226			
Lot No.			
Land District.			
FIELD NOTES			
OF THE SURVEY OF THE MINING CLAIM OF			
BUNKER HILL MINES COLDANY			
KNOWN AS THE			
OREGON, FLORODARA			
Mining District,			
COCHISE County,ARIZONA			
Sections 14 and 15 , Township 20 SOUTH , Range 22 E.G&SRB&M.			
Surveyed under instructions dated JULY 12th, 1915			
by Ralph L. Motz			
U. S. Doputy Mineral Surveyor			
Claim located see location notices			
Survey commenced August 2nd, 1915.			
Survey completed August 4th, 1915.			

Postoffice address of claimant's attorneys,
ELLINWOOD & ROSS,
BISBUE, ARIZONA.

OREGON.

Beginning at Cor No 1, the N E Cor, identical with location, and situated at the intersection of lines 6-7 Sur No 357 Knoxville lode and 3-4 Sur No 477 Prompter lode, at S 73° 32' E 1407.8 ft from Cor No 6 and N 73° 32' W 62.0 ft from Cor No 7 Knoxville lode, and N 3° 15' E 204.6 ft from Cor No 4 and S 3° 15' W 76.3 ft from Cor No 3 Prompter lode,

a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed 1-3226 0,

whence a limestoneledge 24 x 23 ins exposure and chiseled BR x 1-3226 brs S 33° Ol' E 15.0 ft., and a second limestone ledge with 16 x 37 ins exposure and like chiseling brs S 65° 11' W 22.7 ft.

The 1/4 Cor between Secs 14 and 15, T 20 S., R 22 E., G & S R B & M brs N 28° 09' W 460.9 ft.

thence S 3º 15' W

- 204.6 to Cor No 4 Sur No 477 Prompter lode
- to original location for east end center, being a pine post 4 ft. long 4 ins. sq. set 18 ins. in the ground in a mound of stones and scribed EECt-0-3226,
- 402.5 intersect line 2-3 Sur No 357 Knoxville lode at S 16° 03' W 91.8 ft from Cor No 2, and N 16° 03' E 197.2 ft from Cor No 3,
- to Cors No 1, 1 and 5 of Florodara lode of this survey,
 Sur No 337 Merry Christmas lode, and Sur No 477 Prompter
 lode, respectively, (from this point Cor No 6 Sur No 337
 Merry Christmas lode brs N 75° 58' W 449.9 ft., the intersection of lines 2-3 Sur No 357 Knoxville lode and Sur No
 337 Merry Christmas lode brs N 75° 58' W 22.5 ft., Cor No
 2 Sur No 337 Merry Christmas lode brs N 2° 59' E 297.4 ft.,
 and the intersection of lines 1-2 Sur No 337 Merry Christmas lode and 2-3 Sur No 357 Knoxville lode brs N 2° 59' E
 99.3 ft.)
- to Cor No 2, the S E Cor, identical with location and with Cor No 6 Florodara lode of this survey,

a pine post 4 ft. long 4 ins. sq. set 18 ins in the ground in a mound of stones and scribed 2-3226 0,

whence a limestone ledge 19 x 12 ins exposure and chiseled BR x 2-3226 brs S 65° 18' E 26.55 ft., and a second limestone ledge 57 x 30 ins exposure and like chiseling brs S 62° 26' W 13.45 ft.

thence N 73° 32' W

- intersect line 2-3 Sur No 357 Knoxville lode at N 16° 03' E 4.9 ft; Sind S 16° 03' W 284.1 ft from Cor No 2, (from this point the intersection of lines 6-1 Sur No 337 Merry Christmas lode and 2-3 Sur No 357 Knoxville lode brs N 16° 03' E 92.7 ft., and the intersection of lines 1-2 Sur No 337 Merry Christmas lode and 2-3 Sur No 357 Knoxville lode brs N 16° 03' E 190.2 ft.)
- intersect the section line between Secs 14 and 15, at S 0° 02' E 951.4 ft from the 1/4 Cor between Secs 14 and 15, and N 0° 02' W 1721.2 ft from the Cor of Secs 14,15,22 and 23,
- to Cor No 5 Florodara lode of this survey, and also intersect line 7-8 Sur No 679 Contact lode at S 5° 21' E 273.5 ft from Cor No 8, and N 5° 21' W 24.1 ft from Cor No 7,

3

whence a limestone ledge 29 x 19 ins exposure and chiseled BR x 3-3226 brs N 20° 51' W 20.2 ft., and a second lime-stone ledge 53 x 18 ins exposure with like chiseling brs. N 53° 20' E 15.05 ft.,

thence N 3° 15' E

- 62.2 intersect line 8-2 Sur No 679 Contact lode at S 84° 44' W 522.1 ft from Cor No 8 and N 84° 44' E 916.2 ft from Cor. No 3,
- 300.0 to original location for west end center, being a pine post 4 ft.long 4 ins. sq. set 18 ins. in the ground in a mound of stones and scribed WEC-0-3226,
- 317.8 intersect line 2-3 Gen No 191 Lucknow lode at N 46° 06' E 301.7 ft from Cor No 2, S 46° 06' W 1203.1 ft from Cor No 3,
- 600.0 to Cor No 4, the N W Cor, identical with location and-with Cor No 6 Sur No 357 Knoxville lode,

 a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed 4-3226 0,

 whence a limestone rock 13 x 8 x 9 ins. high and chiseled BR x 4-3226 brs S 12° 05' W 8.05 ft., and a limestone ledge with 18 x 15 ins exposure and like chiseling brs N. 22° 11' E 12.15 ft.

thence S 73° 32' E

- 75.0 intersect line 4-5 Sur No 872 Longfellow lode at S 8° 23' E 43.1 ft from Cor No 5, and N 8° 23' W 193.3 ft from Cor No 4, (The intersection of lines 4-5 Sur No 872 Longfellow lode and 2-3 Gen No 191 Lucknow lode brs S 8° 23' E 155.7 ft.)
- intersect line 2-3 Gen No 191 Lucknow lode at S 46° 06' W 887.0 ft from Cor No 3, and N 46° 06' E 617.8 ft from Cor No 2, (the intersection of lines 4-5 Sur No 872 Longfellow lode and 2-3 Hen No 191 Lucknow lode brs S 46° 06' W 162.5 ft.)
 - 958.0 intersect line 4-5 Sur No 337 Merry Christmas lode at S 3° 42' W 63.9 ft from Cor No 4, and N 3° 42' E 226.1 ft from Cor No 5, (the intersection of lines 4-5 Sur No 337 Merry Christmas lode and 3-4 Sur No 872 Longfellow lode brs S 3° 42' W 0.36 ft. The bearing of line 5-6 Sur No 337 Merry Christmas lode is S 3° 42' W 296.4 ft.)
- 959.7 intersect line 3-4 Sur No 872 Longfellow lode at N 85° 51' W 173.9 ft from Cor No 3, and S 85° 51' E 822.4 ft from Cor No 4, (the intersection of lines 4-5 Sur No 337 Merry Christmas lode and 3-4 Sur No 872 Longfellow lode brs N 85° 51' W 1.65 ft.)
- intersect the section line between Secs 14 and 15, at S 0° 02' E 342.2 ft from the 1/4 Cor between Secs 14 and 15 and N 0° 02' W 2330.4 ft from the Cor of Secs 14,15,22, and 23,
- 1407.4 intersect line 2-3 Sur No 337 Merry Christmas lode at S. 3° 31' W 76.2 ft from Cor No 3, and N 3° 31' E 206.5 ft from Cor No 2, (Line 3-4 Sur No 337 Merry Christmas lode brs. N. 75° 04' W. 446.6 ft.)

OREGON (Cont'd.)

1407.8 to Cor No 1, the place of the beginning.

FLORODARA.

Beginning at Cor No 1, identical with Cors No 1 and 5 of Sur No 237 Merry Christmas lode and Sur No 477 Prompter lode, respectively,

a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed 1-3226 F,

whence a limestone ledge 44 x 17 ins. exposure and chiseled BR x 1-3226 brs S 64° 20' E 23.6 ft., and a second limestone ledge 14 x 15 ins exposure and like chiseling brs N 69° 34' E 24.5 ft.

The 1/4 Cor between Secs 14 and 15, T 20 S., R 22 E., G & S R B & M brs N 11° 44' W 928.8 ft.

thence S 86° 30' E

- intersect line 2-3 Gen No 151 Mountain Top Lode at S 45° 27' W 780.5 ft from Cor No 2, and N 45° 27' E 547.5 ft from Cor No 3,
- along line 5-6 Sur No 477 Prompter lode to Cor No 2, the N E Cor, identical with location, and situated on line 5-6 Sur No 477 Prompter lode at S 86° 30' E 664.8 ft from Cor No 5, and N 86° 30' W 810.0 ft from Cor No 6,

a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed 2-3226 F,

whence a limestone ledge 18×21 ins exposure and chiseled BR x 2-3226 brs S 66° 07' E 17.8 ft., and a second limestone ledge 30 x 27 ins exposure with like chiseling brs S 5° 45' W 21.8 ft.

thence S 5° 21' E

- 300.0 to original location for east end center, being a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed EECt-F-3226,
- 417.1 intersect line 5-6 Gen No 151 Mountain Top Tode at N 45° 35' E 453.5 ft from Cor No 5, and S 45° 35' W 863.6 ft from Cor No 6,
- 600.0 to Cor No 3, the S E Cor, identical with location, a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed 3-3226 F,

whence a quartzite ledge 30 x 48 ins exposure and chiseled BR x 3-3226 brs S 55° 30' E 8.4 ft., and a quartzite rock 36 x 72 x 48 ins high with like chiseling brs N 9° 40' E 21.5 ft.

thence N 82° 58' W

- intersect line 5-6 Gen No 151 Mountain Top lode at N 45° 35' E 225.1 ft from Cor No 5, and S 45° 35' W 1092.0 ft from Cor No 6,
- 615.0 intersect line 3-4 Gen No 151 Mountain Top lode at N 51° 32' W 40.1 ft from Cor No 4, and S 51° 32' E 257.6 ft from Cor No 3,
- 681.4 intersect line 6-1 Sur No 431 Black Top lode at S 9° 37' W 19.5 ft from Cor No 6, and N 9° 37' E 607.8 ft from Cor No 1,

- intersect the section line between sections 14 and 15, at S 0° 02' E 1435.5 ft from the 1/4 Cor between Secs 14 amd 15, and N 0° 02' W 1237.1 ft from the Cor for Secs 14, 15,22 and 23, 914.4
- intersect 4-5 Sur No 431 Black Top lode at S 45° 57' W 126.4 ft from Cor No 5, and N 45° 57' E 230.4 ft from Cor No 4, Cor. No.6 said Black Top lode brs. 5.67°02'E. 287.2 ft. from Cor. No.5 thereat. 1036.1
- 1481.3 to Cor No 4, the S W Cor, identical with location, a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed 4-3226 F,

whence a limestone ledge 16 x 9 ins exposure and chiseled BR x 4-3226 brs N 74° 10' w 13.3 ft., and a second limestone ledge 67 x 71 ins exposure with like chiseling brs N 0° 16' W 48.1 ft.

thence N 5° 21' W

- to Cor No 6 Sur No 679 Contact lode, 277.9
- to original location for west end center, being a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed WEG-F-3226, 300.0
- 575.9 to Cor No 7 Sur No 679 Contact lode,
- intersect line 3-4 Sur No 357 Knoxville lode at N 73° 55' W 787.6 ft from Cor No 3, and S 73° 55' E 711.0 ft from 589.1 Cor No 4,
- to Cor No 5, the N W Cor, identical with location, and situated at the intersection of lines 2-3 Oregon lode 600.0 of this survey, and 7-8 Sur No 679 Contact lode,

a pine post 4 ft long 4 ins sq set 18 ins in the ground in a mound of stones and scribed 5-3226 F,

whence a limestone ledge 60 x 44 ins exposure and chiseled BR x 5-3226 brs S 13° 39' E 14.5 ft., and a second limestone ledge 37 x 26 ins exposure with like chiseling brs

644.8

- stone ledge 37 x 2b ins exposure with like chiseling brs N 69° 30' W 21.0 ft.
 thence S 73° 32' E
 intersect the section line between secs 14 and 15 at S 0°
 02' E 951.4 ft from the WC for 1/4 Cor for Secs 14 and 15, and N 0°
 intersect line 2-3 Sur No 357 Knoxville lode at N 16° 03'
 E 4.9 ft from Cor No 3, and S 16° 03' W 284.1 ft from Cor No 2, 791.6
- to Cor No 6, identical with Cor No 2 Oregon lode of this 835.4 survey, heretofore described to which I add 6-3226 F for this claim,

thence N 3° 15' E

to Cor No 1, the place of the beginning. ... 96.2

LODE LINES.

OREGON. -

The presumed course of the vein on this claim is from the east end center N 73° 32' W 1407.8 ft.

FLORODARA.

The presumed course of the vein on this claim is from the west end center S 82° 58' E 1481.3 ft.

des

AREAS.

	Total area Oregon lode	,
	ville lode 18.781 A.	
	Conflict with Lot No. 56 Luck-	
	now lode and Sur No 357 Knoxville lode (common) 0.696 A.	
	Conflict with Lot No. 56 Luck-	ı
	now, Sur No 357 Knoxville, and	
	Sur No 872 Longfellow lode (common) 0.236 A.	ı
	Conflict with Sur No 872 Longfellow	
	lode and Sur No 357 Knoxville	١
	A 05 t H 1 1 1 1 1 A 1 T 77 77 77 71	
	Christmas lode 5.178 A. ×	
	Conflict with Sur No 337 Merry Christmas lode, Sur No 872 Long-	
	fellow lode and Sur No 357 Knox-	
	ville lode (common) 0.000+A.	
	Conflict with Sur No 337 Merry Christmas lode and Sur No 357	
	Knoxville lode (common) 5.152 A.	ľ
	Conflict with Sur No 679 Contact	
	lode and Sur No 357 Knoxville	ı
l		1
	Total area of Florodara lode	•
	Conflict with Sur No 357 Knoxville lode 0.136 A.	
	Conflict with Lot No. 47 Mountain	
	Top lode 7.707 A. Conflict with Sur No 431 Black Top	
	lode 0.463 A.	-

IMPROVEMENTS.

I certify that the value of the labor or improvements made upon or for the benefit of each location of this survey, by the claimant or its grantors, is not less than five hundred dollars and that said improvements consist of:-

OREGON.

No.1. Shaft 4 x 6 x 10 ft deep brs from east end center on lode line 750.0 ft. \$80.00

No.2. 5 x 7 ft incline shaft, mouth of shaft brs from point on line 2-3 N 73° 32' W 550.1 ft from Cor No 2, N 14° 12' E 288.8 ft.

Mouth to Sta, 1 S 57° E 25.0 ft.7° incline.

Sta 1 to Sta 2 S 57° E140.0 ft.35° incline.

Sta 2 to Sta 3 S 70° E 67.0 ft.37° incline.

Sta 3 to face S 75° E 20.0 ft.

252 ft of shaft work Value 33780.00

At Sta 3 is a winze 4 x 6 x 15 ft

deep.

At face of shaft is a raise 4 x 6

x 25 ft high.

Value 250.00

Total

No.3. Shaft 4½ x 9 x 355 ft deep; two compartment, timbered, brs. from point on lode line 743.2 ft from west end center N 41° 28' E 26.0 ft.

Value of shaft
At 135 ft depth is Level No 1.

At 135 ft depth is Level No 1.
Shaft to Sta 1 S 30° W 12.0 ft.
Sta 1 to Sta 2 S 63° E 50.0 ft.
Sta 2 to Sta 3 S 60° E 45.0 ft.
Sta 3 to Sta 4 S 70° E 20.0 ft.

(5.)

```
N 78° W 30.0 ft.
N 60° W 30.0 ft.
                            Sta 7
                                                 to Sta
                            Sta 6
                                                to Face
                                                                                    S 37° W 50.0 ft.
S 43° W 35.0 ft.
S 43° W 70.0 ft.
N 65°W 20.0 ft.
                                                to Sta 7
to Sta 8
                            Sta 6
                            Sta
                            Sta
                                                 to Face
                            Sta 8
                                              to Face
                                                                                      S 66° E 25.0 ft.
                            Sta 8 to face
                                                                                                            387.0 ft. 0.K.
                             At Sta 1 N 78° W 20.0 ft is a 4 x 6 x 105
                   At 240 ft deep is Level No 2,
Shaft to Sta 9 N 76 ° E
                                                                                                                     12.0 ft.
                                                                                                                     43.0 ft.
60.0 ft.
                                                                                    58° E E S 65° E
                             Sta 10 to Sta 11
                             Sta 11 to Sta 12
                                                                                                                      50.0 ft.
                             Sta 12 to Sta 13
Sta 13 to Face
                                                                                                                      12.0 ft.
                                                                                                                      25.0 ft.
                                                                                                                .202.0 ft.
                    10.0 ft.
                                                                                                                      36.0 ft.
                                                                                                                      14.0 ft.
                                                                                     53° E E 57° E 
                                                                                                                      50.0 ft.
                                                                                                                      22.0 ft.
                                                                                                                   45.0 ft.
117.0 ft.
                             Sta 19 to Sta 20
                             Sta 20 to Sta 21
                                                                                                                      34.0 ft.
                             Sta 21 to Sta 22
                                                                                                                      17.0 ft.
                                                                                                                      21.0 ft.
                              Sta 22 to Face
                                                                                                                   366.0 ft. 0.
                             At Sta 20 is 32° incline winze, 4 x 6
                             x 218.0 ft deep brg S 67° E.
                             Total drifting as listed above 955 ft at $8.
                              per foot.
                                                                                                                                                  Value
                                                                                                                                                                          $7640.00
                              Total number of feet of winze as listed above 323 ft. at 310. per foot.
                                                                                                                                                 Value
                                                                                                                                                                           $3230.00
                     Shaft 4 x 6 x 150 ft deep brs from a point on line 2-3 N 73° 32' W 550.1 ft from Cor No 2, N 8° E 165.0 ft. T. Valu
No.4.
                                                                                                                                                                           $1875.00
                                                                                                                                                  Value
                      Shaft 4 x 6 x 150 ft deep brs from same point
No.5.
                     N 21° 20' E 183.5 ft.
                                                                                                                                                                            $1875.00
                                                                                                                                                  Value
                     Shaft 4 x 6 x 9 ft deep brs from same point N 32° 08' E 230.0 ft. Va
No.6.
                                                                                                                                                                           $ 75.00
                                                                                                                                                   Value
                      Shaft 7 x 10 x 8 ft deep, in bottom of which is
No.7.
                     a shaft 4 x 6 x 12 ft deep, brs from point on lode line 630.6 ft from west end center, N 85° 22' W 146.3 ft. Value $ 250.00
                     Shaft 4 x 6 x 13 ft deep brs from same point N 46° 26' W 88.5 ft. Value
No.8.
                                                                                                                                                  Value 3 110:00
                     Shaft 4 x 6 x 9 ft deep brs from Cor No 1 Florodara lode being on line 1-2 of this claim, N 5° 02' W 32.0.ft.
No.9.
                                                                                                                                          / Value
                                                                                                                                           to bornuntt
                                                                                                                                         wie Jook meri
                                                                                                                                 gob this
```

(6.)

No.lo	Incline shaft, 4 x 6 ft in cross section, shaft brg S 26° E, the mouth of shaft brs. from Cor No 1 Florodara lode of this survey, which is located line 1-2 of this claim, N 48° 0' W 45.8 ft. 60 ft deep at 70° incline is located Level No 27.0 ft deep at 75° incline to Level No 2, 23.0 ft deep at 80° incline to Level No 3, 19.0 ft deep at 85° incline to Level No 4, 17.0 ft deep at 85° incline to bottom. 146.0 ft deep. Value \$1825.00	ted 1.
	On Level No 1, Drift 4 x 6 x 15 ft brg N 64° E Drift 4 x 6 x 20 ft brg S 64° W	N = =
	On Level No 2, Drift 4 x 6 x 15 ft brg N 64° E Drift 4 x 6 x 70 ft brg S 64° W	e =
	On Level No 3, Drift 4 x 6 x 20.7ft brg N 64° E	
	On level No 4, Drift 4 x 6 x 22.3ft brg N 64° E Drift 4 x 6 x 145 ft brg S 64° W	
	Total drifting 308.0 ft. Value \$2465.00	
	Total value of Improvement #10. \$4290.00	
	This improvement has been made with the idea of benefiting and tending to develop both the claims of this survey. 1/2 of the total value of \$4290. has been allotted to each claim of this survey.	-
	1/2 allotted to this claim	\$2145.00
	Total improvements upon or allotted to this claim	\$32185.00 °×-
	FLORODARA.	
Nol.	Discovery shaft 4 x 6 x 10 ft deep brs from west end center on lode line 700 ft. Value	\$ 80.00
No.2.	Shaft 4 x 6 x 12 ft deep brs from Cor No 4 N 52° 26' E 391.7 ft. Value	\$ 100.00
No.3.	Shaft 4 x 6 x 12 ft deep brs from Cor No 5 S 64° 48' E 574.6 ft. Value	\$ 100.00
No.4.	Shaft 4 x 6 x 9 ft deep brs from Cor No 5, S 67° 58' E 620.0 ft. Value	\$ 75.00
No.5.	Shaft 5 x 5 x 10 ft deep brs from Cor No 5, S 19° 05' E 171.0 ft. Value	\$ 80.00
No.6.	Shaft 4 x 6 x 25 ft deep brs from Cor No 5, \$ 45° 39' E 166.9 ft. Value	\$ 250.00
No.7.	Shaft 4 x 6 x 12 ft deep brs from Cor No 4, N 34° 36' E 108.6 ft. Value	\$ 100.00
	1/2 interset in Improvement No.10 on Oregon claim of this survey, allotted to this claim	\$2145.00
	Total impro vements upon or allotted	\$2930.00
	Total improvements on group	\$35,115.00
T	OMILIA TIMBOTHIBURG	

OTHER IMPROVEMENTS.

OREGON.

No.11. Shaft 4 x 4 x 16 ft deep brs from point on line 2-3,

N 73° 32' W 550.1 ft from Cor No 2, N 49° 27' E 394.8 ft.

Ho.12. Shaft $4 \times 6 \times 47$ ft deep brs from same point N 55° 42' E 428.7 ft.

No.13. Shaft 4 x 6 x 30 ft. deep brs. from same point N 53° 54' E 454.0 ft.

No.14. Shaft 4 x 6 x 18 ft. deep brs from same point N 54° 30' E 474.6 ft.

No.15. Shaft 4 x 6 x 10 ft. deep brs from same point N 54° 32' E 484.6 ft.

No.16. Shaft 4 x 6 x 17 ft. deep brs from same point N 39° 48' E 577.3 ft.

ADJOINING CLAIMS .

North. Sur No 872 Longfellow lode; Sur No 337 Merry Christmas lode; Sur No 477 Prompter lode; Gen No 151, Mountain Toplode.

East. Sur No 477 Prompter lode; Gen No 151, Mountain Top lode.

South. Sur No 431 Black Top lode; Sur No 679 Contact lode.

West. Sur No 679 Contact lode; Gen No 191, Lucknow lode. This survey is almost entirely in conflict with Sur. No. 357 Knoxville lode. LOCATION.

This survey is located in the Tombstone Mining District, Cochise County, Arizona, in Secs 14 and 15, Tp 20 S., R 22 E., G & S R B & M.

INSTRUMENT.

This survey was made with a C. L. Berger & Sons No 1 C transit. The courses were deflected from the true meridian as determined by a Solar observation. The distances were measured with a 300 foot steel tape. Magnetic variation 12° 30' East at all corners.

REPORT.

W C for 1/4 Cor between Secs 1/4 and 1/5 T 20 S. R 22 E., is a limestone rock $4 \times 9 \times 10$ ins above ground, chiseled WC on west face. A monument of stones 3 ft west.

Cor of Secs 14, 15, 22 and 23 is a quartzite rock 6 x 18 x 9 ins above ground, chiseled II on east face, and III on south face. A monument of stones 2 ft west.

Lot No 47 Gen No 151 Mountain Top lode.

Cors No 2, 4, 5, and 6 are monuments of stones.

Cor No 3 is a 4 x 4" post not scribed.

I find line 2-3 to be S 45° 27' W 1328.0 ft instead of S 46° 49' W 1336.5 ft.

3-4 to be S 51° 32' E 297.7 ft instead of S 52° 02' E 299.97 ft.

5-6 to be N 45° 35' E 1317.1 ft instead of N 46° 49' E 1336.5 ft.

Lot No 56 Gen No 191 Lucknow lode.

Cor No 2 is a 4 x 4" post scribed L M C N o 2.

Cor No 3 is a monument of rocks.

I find line 2-3 to be N 46° 06' E 1504.8 ft instead of N 46° 59' E 1499.85 ft.

Sur No 337 Merry Christmas lode.

and it is a street of the deep have strong point on itsue set.

```
Cors No 1 and 3 are posts not scribed for this claim.
    Cors No 2 and 6 are posts scribed E END-MCNoII and
   MCNoVI.
   Cors No 4 and 5 are monuments of rocks.
   I find line 1-2 to be N 2° 59' E 297.4 ft instead of
   N 3° 36' E 298.0 ft.
                    2-3 to be N 3° 31' E 282.7 ft instead of
    N 3° 36' E 290.0 ft.
                    3-4 to be N 75° 04' W 446.6 ft instead of
   N 75° 48' W 470.0 ft.
                    4-5 to be S 3° 42' W 290.0 ft instead of
    S 3° 36' W 290.0 ft.
   5-6 to be S 3° 42' W 296.4 ft instead of S 3° 36' W 298.0 ft.
                   6-1 to be S 75° 58' E 449.9 ft instead of
    S 75° 48' E 470.0 ft.
Sur No 357 Knoxville lode.
Cors No 2, 3, 4, 5, and 6 are posts KMCN2, KMCN3, KMCN4
KMCN5 and KMCN6, respectively.
    Cor No 7 is a monument of rocks.
   I find line 2-3 to be S 16° 03' W 289.0 ft instead of S 16° 06' W 300.0 ft.
   3-4 to be N 73° 55' W 1498.6 ft instead of N 73° 48' W 1477.5 ft. 6-7 to be S 73° 32' E 1469.8 ft instead of
    s 73° 48' E 1477.5 ft:
Sur No 431 Black Top lode.
   Cors No 1 and 4 are 2 x 4"posts scribed NoI-BkTMC-USS.
   and NoIV-BkTMC-USS, respectively.
   Cors No 5 and 6 are monuments of rocks.

I find line 4-5 to be N 45° 57' E 356.8 ft instead of N 48° 15' E 335.0 ft.

5-6 to be S 67° 02' E 287.2 ft instead of
    S 70° E 300.0 ft.
                   6-1 to be S 9° 37' W 627.3 ft instead of
   S 10° W 627.0 ft:
Sur No 477 Prompter lode.
   Cors No 3, 4,5 and 6 are 4 x 4"posts scribed PIII, PIV, PV, and PVI, respectively. I find line 3-4 to be S 3° 15' W 280.9 ft instead of S 3° 25' W 285.6 ft.
   S 3° 25' W 296.4 ft.
    5-6 to be S 86° 30' E 1474.8 ft instead of S 86° 30' E 1482.0 ft:
Sur No 679 Contact lode.
    Cor No 2 is missing.
Cor No 3 is a monument of stones.
    Cors No 6, 7 and 8 are posts scribed CMCN6.CMCN7. and
   CMCN8., respectively.
I find line 6-7 to be N 5° 21' W 298.0 ft instead of N 5° 07' W 299.0 ft.

7-8 to be N 5° 21' W 297.6 ft instead of
   N 5° 07' W 300.0 ft. 8-3 to be S 84° 44' W 1438.3 ft instead of S 84° 52' W 1457.0 ft.
Sur No 872 Longfellow lode.
    Cors No 3, 4 and 5 are 4 x 4" posts scribed LMCN3,
    LMCN4 and LMCN5.
    I find line 3-4 to be N 85° 51' W 996.3 ft instead of
    N 85° 13' W 890.0 ft:
4\text{--}5 to be N 8° 23' W 236.4 ft instead of N 9° 50' W 232.5 ft.
                                      Ralph L. Moh
U.S. MINERAL SURVETOR.
```

Dated at Bisbee, Arizona.

November 27,1915.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

I <mark>nited States Deputy Miner</mark>	ral Surveyor, to assist in running, measuring, and marking the lines, corners, an
oundaries described in the f	oregoing field notes of the survey of the mining claim of
	Bunker Hill Nines Company
	Oregon, Florodara
nd showing the respective c	apacities in which they acted.
	I. II. Halleck , Chainman.
	, Chainman.
	Axman.
	Flagman.
	A TO A MILE OF A COLOMANIMO
FIL	NAL OATHS OF ASSISTANTS.
wx I. P. H. Hell	l cals
	LEUX
	Leck, I do solemnly swear that we assisted
ardv	, do solemnly swear that we assisted
ndx	, do solemnly swear that we assisted
lph La Motz	I
lph La Motz ne boundaries of the mining	, do solemnly swear that we assisted
lph La Motz ne boundaries of the mining	, do solemnly swear that we assisted
lph La Motz ne boundaries of the mining nown as the	, do solemnly swear that we assisted
lph La Motz ne boundaries of the mining nown as the epresented in the foregoing	, do solemnly swear that we assisted
lph La Motz ne boundaries of the mining nown as the epresented in the foregoing	, do solemnly swear that we assisted
lph La Motz ne boundaries of the mining nown as the epresented in the foregoing irection; and that said sur	, do solemnly swear that we assisted
lph L. Motz ne boundaries of the mining nown as the epresented in the foregoing irection; and that said sur prectly executed, and the o	, do solemnly swear that we assisted
lph La Motz ne boundaries of the mining nown as the epresented in the foregoing irection; and that said sur	, do solemnly swear that we assisted United States Deputy Mineral Surveyor, in marking the corners and surveying claim of Bunker Hill Mines Company Oregon, Floredara field notes as having been surveyed by said deputy mineral surveyor and under his vey has been in all respects, to the best of our knowledge and belief, faithfully an corner and boundary monuments established according to law and the instruction es Surveyor-General for Arizona.
lph L. Motz ne boundaries of the mining nown as the presented in the foregoing frection; and that said sur prectly executed, and the o	do solemnly swear that we assisted
lph L. Motz ne boundaries of the mining nown as the epresented in the foregoing irection; and that said sur prectly executed, and the o	, do solemnly swear that we assisted United States Deputy Mineral Surveyor, in marking the corners and surveying claim of Bunker Hill Mines Company Oregon, Floredara field notes as having been surveyed by said deputy mineral surveyor and under his vey has been in all respects, to the best of our knowledge and belief, faithfully an corner and boundary monuments established according to law and the instruction es Surveyor-General for Arizona.
lph L. Motz ne boundaries of the mining nown as the presented in the foregoing frection; and that said sur prectly executed, and the o	do solemnly swear that we assisted
lph La Motz ne boundaries of the mining nown as the epresented in the foregoing irection; and that said sur correctly executed, and the correctly	United States Deputy Mineral Surveyor, in marking the corners and surveying claim of Bunker Hill Mines Company Cregon, Florodara field notes as having been surveyed by said deputy mineral surveyor and under his vey has been in all respects, to the best of our knowledge and belief, faithfully an corner and boundary monuments established according to law and the instruction es Surveyor-General for Arizona. Chainman. Chainman.
lph La Motz ne boundaries of the mining nown as the presented in the foregoing irection; and that said sur prectly executed, and the ournished by the United State	To the states deputy Mineral Surveyor, in marking the corners and surveying claim of. Bunker Hill Lines Company Oregon, Floredare field notes as having been surveyed by said deputy mineral surveyor and under heavy has been in all respects, to the best of our knowledge and belief, faithfully an corner and boundary monuments established according to law and the instruction ses Surveyor-General for Arizons. Chainman. Chainman. Axman.
he boundaries of the mining nown as the epresented in the foregoing irection; and that said sur orrectly executed, and the ournished by the United Stat	, do solemnly swear that we assisted

Notary Public in and for the County of Cochise, State of Arizons.
My commission expires February 21st, 1916.

FINAL OATH OF U. S. DEPUTY MINERAL SURVEYOR

I, Ralph L. Hotz	, U. S. Deputy Mineral
	t, in pursuance of instructions received from the United
States Surveyor General for	Arizona , dated
July 12, 1915.	, I have, in strict conformity to the laws of the
United States, the official regulation	tions and instructions thereunder, and the instructions
of said Surveyor General, faithf	fully and correctly executed the survey of the Mining
Claim of Bunker Hi	ill Mines Company
	, known as the
Oreş	zon, Florodara ,
situate in	Tombstone Mining District,
Cochise	County, Arizona , in Sections
14 and 15, Township No. 2	20 S., Range No. 22 E. G & S R B & M
in the foregoing field notes, which as distinctly marked by monume of the location certificate, which said instructions, and that all the petuated in strict accordance with under; and I do further solemn field notes of said survey and improvements made upon said mare as therein fully stated, and thereof are specified therein with said labor or improvements so cr	th accurately show the boundaries of said mining claim ents on the ground, and described in the attached copy in was received by me from the Surveyor General with the corners of said survey have been established and pertain the law, official regulations and instructions thereally swear that the foregoing are the true and original my report therein, and that the labor expended and mining claim by claimant orits
Subscribed and sworn to by	Relph I. Wetz
	y the said Relph L. Motz
	this 27th
day of November,	-

AMENDED NOTICE OF MINING LOCATION LODE CLAIM

UUL 12 1015

TO ALL WHOM IT MAY CONCERN:

This mining claim, the name of which is the "FLORODARA" Mining Claim, situate on lands belonging to the United States of America, and in which there is a vein or lode of mineral bearing rock in place carrying gold, silver, copper and other valuable deposits, was entered upon and located for the purpose of exploration and purchase by the Bunker Hill Mines Company, a corporation, and citizen of the United States, the undersigned, on the Lag of gard 1915.

The length of this claim is 1500 feet, and we claim 700 feet of the lode in a Westerly direction and 800 feet of the lode in an Easterly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the claim and the lode therein is from the West to the East.

Mining District, in Cochise County, in the State of Arizona, and the discovery shaft thereof is about 8500 feet in a Southerly direction from the Court House, Tombstone, Arizona, in Sections 14 and 15, Township 20 South, Range 22 East, Gila and Salt River Base and Meridian, and is bounded on the North by the "Oregon," Survey No. 477 "Prompter," on the East by the "Black Tom", on the West by Survey No. 679, "Contact.

The surface boundaries of the claim are marked upon the ground as follows:

Beginning at a monument of stones and a post in a Westerly direction 700 feet from the discovery shaft, (at which this notice is posted), being in the center of the West end line of said claim; thence Northerly 300 feet to a monument of stones and a post being the Northwest corner of said claim; thence Easterly 1500 feet to a monument of stones and a post, being the Northeast corner of said claim; thence Southerly 300 feet to a monument of stones and a post being the center of the East end of said claim; thence Southerly 300 feet to a monument of stones and a post, being the Southeast corner of said claim; thence Westerly 1500 feet to a monument of stones and a post, being the southwest corner of said claim; thence Westerly 1500 feet to a monument of stones and a post, being the Southwest corner of said claim; thence, 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII of the Revised Statutes of the United States, and under the provisions of Chapter One, of Title XXXIV, of the Revised Statutes of Arizona, 1913.

This is an amended location notice of the "Florodara" mining claim, being located by M. D. Scribner, on the 10th day of February, 1902, and recorded in Book 15, Record of Mines, at page 562, in the office of the County Recorder of the aforesaid County of Cochise, to which reference is hereby made. And this amended location notice is made and posted by the Bunker Hill Mines Company, the present owner of said claim, to correct errors in the description in said above mentioned former location, and without waiving any right, title or interest heretofore acquired by virtue of said former location.

Dated and posted on the ground this 15 day of June 1915.

BUNKER HILL MINES COMPANY.

By

Superintendant.

AMENDED NOTICE OF MINING
LOCATION

"FLORODARA" LODE MINING
CLAIM

Dated 1915

County of Co.

I, Owen E. Murpa County Recorder and for the County and State aforesaid, do hereby certify that the within instrument was filed for record at o'clock, M., on this day of and duly recorded and duly recorded and off Mines records of Cochise County, Arizona, at pages Witness my hand and official seal the day and year first above vriten.

By J. Deputy

Deputy

294 · ANDERED

8-18

19 TO	lecorde	c's Office, Cochise Co., Ariz.
Filed	and reco	orded at request of
Du	JUN 19	Diel MCs 1915 A. D. 191
rt	The last term to the last to the last term to the last te	TPM.
Book_	50	Record of Mines
ages	mu &	murph
		County Recorder

15

AMENDED NOTICE OF MINING LOCATION LODE CLAIM

رادا ما المال ا

TO ALL WHOM IT MAY CONCERN:

This mining claim, the name of which is the "OREGON" Mining Claim, situate on lands belonging to the United States of America, and in which there is a vein or lode of mineral bearing rock in place carrying gold. silver, copper and other valuable deposits, was entered upon and located for the purpose of exploration and purchase by the Bunker Hill Mines Company, a corporation, and citizen of the UnitedStates, the undersigned, on the day of June 1915.

The length of this claim is 1500 feet, and we claim 750 feet of the lode in an Easterly direction, and 750 feet of the lode in a Westerly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the claim and the lode therein is from the East to the West.

The claim is situated and located in the Tombstone Mining District, in Cochise County, in the State of Arizona, and the discovery shaft thereof is about one and one-half miles in a Southerly direction from the City of Tombstone, and is situated in Sections 14 and 15. Township 20 South. Range 22 East, Gila and Salt River Base and Meridian; and is bounded on the North by the "Buckskin," on the East by Survey No. 477, "Prompter," on the South by the "Florodara," and No. 679 "Contact," and on the West by Lot No. 56. "Lucknow."

The surface boundaries of the claim are marked upon the ground as follows:

Beginning at a monument of stones and a post in a Westerly direction 750 feet from the discovery shaft. (at which this notice is posted), being in the center of the West end line of said claim; thence Northerly 300 feet to a monument of stones and a post, being the Northwest corner of said claim; thence Easterly 1500 feet to a monument of stones and a post, being the Northeast corner of said claim; thence Southerly 300 feet to a monument of stones and a post, being the center of the East end of said claim; thence Southerly 300 feet to a monument of stones and a post, being the Southeast corner of said claim; thence westerly 1500 feet to a monument of stones and a post, being feet to a monument of stones and a post, being the Southwest corner of said claim; thence Northerly 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII of the Revised Statutes of the United States, and under the provisions of Chapter One, of Title XXXIV, of the Revised Statutes of Arizona, 1913.

This is an amended location notice of the "Oregon" mining claim, being located by M. Parosich, Geo. Bravin, Frank Payla and Fred Calavita, on the first day of January. 1899, and recorded in Book 14, Record of Mines, at page 753, in the office of the County Recorder of the aforesaid County of Cochise, to which reference is hereby made; the amended location of said "Oregon" being made by Geo. Bravin, Frank Payla and F. Carlevato, on the 11th day of August, 1901, and recorded in Book 15, Record of Mines, at page 335, in the office of the County Recorder of the aforesaid County of Cochise, to which reference is hereby made. And this amended location notice is made and posted by the Bunker Hill Mines Company, the present owner of said claim, to correct errors in the description in said above mentioned former location and locations, and without waiving any right, title or interest heretofore acquired by virtue of said former location or locations.

Dated and posted on the ground this 18 day of June 1915.

BUNKER HILL MINES COMPANY

By

Superintendent



U.S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,					
February 19 , 19 16.					
I, U. S. Surveyor-General for District of Arizona					
do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey					
of the mining claim of					
BUNKER HILL MINES COMPANY					
known as the OREGON , FLORODARA .					
situate inTOMBSTONE					
Mining District, COCHISE County, ARIZONA.					
in Sections 14 and 15 Township No. 20 S., Range No. 22 E. , and					
designated as Survey No. 3226, , has been correctly copied from the originals on file in					
this office; that said Field Notes furnish such an accurate description of said mining claim as will, if					
incorporated into a patent, serve fully to identify the premises, and that such reference is made therein					
to natural objects or permanent monuments as will perpetuate and fix the locus thereof.					
And I further certify that five hundred dollars' worth of labor has been expended or improve- each of ments made upon said mining claims by claimant or its grantors, and that said improvements					
consist of 17 shafts, 1 raise, 3 winzes and 1263 ft. of drifting,					
total value \$35115.					
As improvement No.10 on the Oregon is a common improvement					
for the benefit and development of both of the lodes of this					
survey, an undivided one-half interest therein, value \$2145,					
is properly credited to each of the said lodes.					
and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.					
I further certify that the plat thereof, filed in the U.S. Land Office atPhoenix,					
Arizona. is correct and in conformity with the foregoing Field Notes.					
Frank P. Trott,					
United States Surveyor-General for Arizona.					

SURVEYOR=GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

Office of U.S. Surveyor-General,

	Pho	penix, Arizona,
		February 19 , 19 16
I, U. S. Surveyor-General for	District of Arizon	ıa
do hereby certify that the foregoing	ng and hereto attached Field Notes	and Return of the Survey of the
Mining Claim of		
	BUNKER HILL MINES COMP	PANY
		known as the
	OREGON, FLORODAR	IA
situate in	TOMBSTONE	Mining District,
COCHI SE	County,	ARIZONA.
in Section 8 14 and 15, ,	Township No. 20 S.,	Range No. 22 E.,
, designated a	s Survey No. 3226	· · · · · · · · · · · · · · · · · · ·
executed by	ph L. Motz,	, U. S. Deputy Mineral
Surveyor, Aug	ust 2-4, , , , , , , , , , , , , , , , , , ,	15, under my instructions dated
July 12,	, 1915., have been critically e	examined and the necessary cor-
rections and explanations made, a	nd the said Field Notes and Return	a, and the Survey they describe,
are hereby approved. A true cop	y of the copy of the location certif	icate filed by the applicant for
survey is included in the field note	es.	
	Frank St.	Book
	U. S. Surveyor-Genero	al for Arizona.

7360b5m3-03