

MINERAL SURVEY No. 3471.

Arizona Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Charles H. Clark, Trustee.

KNOWN AS THE

No. 5<sup>2</sup> Traction and No. 6<sup>2</sup> Traction Lodes Verde Mining District,

Yavapai County, Arizona.

Sections 27, 22, 23, Township 16 N, Range 2 E T4S R13E M.

Surveyed under Amended instructions dated May 17, 1918.

by Joseph McCarthy U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced July 19, 1918.

Survey completed July 24, 1918.

Address of claimant Anderson and Ellie Atty Prescott, Arizona

DATES OF AMENDED LOCATIONS.

See location notices.

# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by Joseph McCarthy  
 United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and  
 boundaries described in the foregoing field notes of the survey of the mining claim of \_\_\_\_\_  
Charles H. Clark Trustee  
 known as the No. 5 Traction and No. 6 Traction lodes  
 and showing the respective capacities in which they acted.

Philip S. Cowgill, Chairman.  
 \_\_\_\_\_, Chairman.  
 \_\_\_\_\_, Axman.  
 \_\_\_\_\_, Flagman.

## FINAL OATHS OF ASSISTANTS.

I Philip S. Cowgill  
 We, \_\_\_\_\_, do solemnly swear that we assisted Joseph  
McCarthy, United States Mineral Surveyor, in marking the corners and surveying  
 the boundaries of the mining claim of Charles H. Clark Trustee  
 known as the No. 5 Traction and No. 6 Traction lodes.  
 represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his  
 direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully  
 and correctly executed, and the corner and boundary monuments established according to law and the instruc-  
 tions furnished by the United States Surveyor-General for Arizona

Philip S. Cowgill, Chairman.  
 \_\_\_\_\_, Chairman.  
 \_\_\_\_\_, Axman.  
 \_\_\_\_\_, Flagman.

Subscribed and sworn to by the above-named persons before me this Tenth  
 day of August, 19 18

C. S. Gardner

Yavapai County, Arizona

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Joseph McCarthy, U. S. Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the United States  
Surveyor General for Arizona, dated  
May 17, 1918, I have, in strict conformity to the laws of the  
United States, the official regulations and instructions thereunder, and the instructions  
of said Surveyor General, faithfully and correctly executed the survey of the Mining  
Claim of Charles St. Clark Trustee  
, known as the  
No. 5 Tracton and No. 6 Tracton lodes,  
situate in Verde Mining District,  
Yavapai County, Arizona, in Sections  
22 & 27, Township No. 16 N, Range No. 2 E SR 13 & M and within the Prescott National  
22 & 27 450, 8 23 Forest,  
and designated as Survey No. 3471, as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim  
as distinctly marked by monuments on the ground, and described in the attached copy  
of the location certificate, which was received by me from the Surveyor General with  
said instructions, and that all the corners of said survey have been established and per-  
petuated in strict accordance with the law, official regulations and instructions there-  
under; and I do further solemnly swear that the foregoing are the true and original  
field notes of said survey and my report therein, and that the labor expended and  
improvements made upon said mining claim by claimant or his grantors  
are as therein fully stated, and that the character, extent, location, and itemized value  
thereof are specified therein with particularity and full detail, and that no portion of  
said labor or improvements so credited to this claim has been included in the estimate  
of expenditures upon any other claim.

Joseph McCarthy  
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Joseph McCarthy  
U. S. Mineral Surveyor, before me A Notary Public in and for Yavapai  
County, Arizona this 26th  
day of February, 19 19

C. S. Gardner  
NOTARY PUBLIC

Mineral Survey No. 3471.

No. 5 Traction Lode.

Beginning at Cor. No. 1.

Identical with Cor. No. 4. Sur. No. 1213  
Copper Chief lode and location monument.

A concrete monument 24 in. long 12 in. diam.  
at base and 6 to 8 in diam. at top, set 1 ft in the ground.

The core is a 2 in. iron pipe topped by a cap.  
containing a brass disk stamped + C. No. 4. 1213  
and No. 5. T. No. 1, 3471 whence

Alongside is a 4x5 in post 4 1/2 ft. long, in a  
mound of stones.

A cross on rock in place marked B+R No 5 T.  
1-3471 bears  $N 57^{\circ} 21' E$  7.95 ft.

The Sec. Cor. common to Sec's 22-23-26-27

$N 16^{\circ} 3. P. 2 E. 94 S. R. B. V. M.$  bears  $N 21^{\circ} 49' E$  258.25 ft.

Cor. 4 of No 2 lode identical with Cor. 1 of  
No 3 lode and Cor 3 of Treadwell lode all of  
Survey No. 1285 bears  $N 1^{\circ} 22' 30" E$  83.51 ft.

From Cor 3 of said Treadwell lode, Cor 4 of same  
lode bears  $N 19^{\circ} 08' 10" E$  637.08 ft.

Cor 17 Sur. No 1213 No 6 lode, recorded as being  
on line 3-4 of the Copper Chief lode same survey  
bears  $N 4^{\circ} 51' 20" E$  973.09 ft. and at a point on  
this line 71.77 ft. from Cor 4 of said Copper Chief lode  
line 1-2 sur No 1285, No 3 lode, identical with line  
4-3 No 2 lode same survey is intersected at  
 $S 18^{\circ} 46' E$  12.65 ft. from Cor's No 1 and No 4 thereof.

And at a point on the same line 85.61 ft.  
from Cor 4 of the Copper Chief lode line 4-1 of  
the No 3 lode is intersected at  $N 70^{\circ} 58' E$  5.54 ft from  
Cor No 1.

Whence  $N 85^{\circ} 34' 30" E$

Feet.  
182.06

Intersect line 4-1 sur. No 1285 No 2 lode, identical  
with line 3-2 sur No 1285 Treadwell lode, at  
 $S 69^{\circ} 16' 30" E$  196.22 ft. from Cor's No. 4. and No 3 thereof.

206.22

South end center, a mound of stones 3 ft diam. at  
base and 4 ft. high.

472.17

To Cor. No. 2. identical with location monument  
A concrete monument 12 in. diam. 18 in long, set  
flush with surface of trail, the brass disk is

stamped No. 5 Ft No 2-3471. The cross for exact corner is on the concrete  $N 6^{\circ} 33' 50'' E$  0.31 ft from the center of the brass disk.

A cross on rock in place marked B+R No. 5 Ft-2-3471 bears  $N 10^{\circ} 01' E$  7.70 ft.

Cov. No. 1 of No. 6. Traction code, this survey identical with Cov. No. 4 Treadwell code, sub No 1285 bears  $N 22^{\circ} 08' E$  700.55 ft.

Thence  $N 6^{\circ} 33' 50'' E$

581.83 Intersect line 4-5 sub. No. 1285 Treadwell code at  $S 70^{\circ} 14' 10''$  It 209.79 ft. from Cov. No. 4.

581.96 Intersect line 1-2 No 6 Traction code this survey at  $S 70^{\circ} 16' 30''$  It 209.72 ft. from. Cov. No. 1.

582.59 Intersect line from Cov 3 Kendrick code sub No 1285 to Cov. No 5 Treadwell code of same survey at  $S 69^{\circ} 43' 40''$  It 53.72 ft from Cov. No 3 of Kendrick

745.29 Intersect line 3-4 sub No 1285 Kendrick code at  $N 12^{\circ} 32'$  It 146.51 ft from Cov. No. 3.

1173.89 Intersect line 14-15 sub. No. 1213 No 6 code at  $N 21^{\circ} 16' 30''$  It 99.69 ft. from Cov No 15.

1332.29 Intersect line 1-4 of Jerome Townsite at  $N 50^{\circ} 18' 35''$  It 1382.83 ft from Cov. No. 4.

1447.33 Intersect line 1-4 No 6 Traction code, this survey at  $N 70^{\circ} 07'$  It 795.04 ft from Cov. No. 1.

1462.01 To Cov. No. 3. identical with location monument.

A concrete monument similar to Cov. No. 1 of this survey. The brass disk is stamped + No. 5 Ft No. 3. 3471, whence

A cross on a rock in place marked B+R No. 5. Ft 3-3471 bears  $S 76^{\circ} 40' E$  4.92 ft.

Cov No 15 sub. No 1213 No 6 code bears  $S 0^{\circ} 29' 20'' E$  379.13 ft. From Cov No 15 of the No 6 code, Cov No 16 thereof bears  $S 6^{\circ} 24'$  It 478.89 ft. and from said

Cov 16, Cov 17 of same code bears  $N 52^{\circ} 24' 30'' E$  550.43 ft. and from said Cov 17, Cov 18 of the same code bears  $N 6^{\circ} 20' 15'' E$  470.65 ft.

Thence  $S 85^{\circ} 34' 30'' E$

243.93 North end center. A mound of stones 3 ft diam. and 4 ft high.

397.40 Intersect the line between Sec's 22 & 23 T. 16 N. R. 2 E. at  $N 0^{\circ} 09' 30''$  It 1218.44 ft. from the corner common to Sec's 22-23-26-27 and  $S 0^{\circ} 09' 30'' E$  1418.87 ft. from the  $1/4$  Cov. between Sec's 22 and 23.

427.68 Intersect line 4-5 sub No 1051 Maine code identical with line 13-18 sub. No 1213 No 6 code at  $N 32^{\circ} 02'$  It 21.81 ft from Cov's No 5 and 18 thereof.

# Municipal Survey No 3471

- 450.15 To Cor. No. 4. Identical with location monument.  
 A concrete monument similar to Cor. No. 1 of this survey. The brass disk is stamped + No 57 No 4, 3471, whence  
 Cor. No. 5 Sur No 1051 Maine lode identical with Cor 3 of Sur. No 1213 Copper Chief lode and Cor No 18 of the No 6 lode, bears S 32° 53' E 19.96 ft.  
 Cor No 4 of Jerome Townsite bears S 31° 34' 10" E 1147.00 ft.  
 Hence S 5° 42' E
- 4.86 Intersect line 1-2 Sur. No. 1395 Amd. 16 to 1 lode at N 40° 58' E 6.04 ft. from Cor. No. 1; and line 5-6 Sur. No 1051 Maine lode at N 40° 58' E 15.79 ft from Cor. No. 5.
- 10.42 Intersect line 6-1 Sur No 1395 Amd. 16 to 1 lode at S 74° 06' E 3.55 ft. from Cor. No. 1.
- 11.48 Intersect line 2-3 Sur. No 1213 Copper Chief lode at N 61° 09' E 11.07 ft. from Cor. No. 3.
- 444.45 Intersect line 4-1 of Jerome Townsite at N 50° 18' 35" E 837.72 ft. from Cor. No. 4.
- 490 Cross under power lines running S 42' E  
 514.57 Intersect line between Sec's 22 & 23 T. 16. N. R. 2. E. at N 0° 09' 30" E 702.35 ft from corner common to Sec's 22-23-26-27 and S 0° 09' 30" E 1934.96 ft. from the 1/4 Sec. Cor. between Sec's 22 & 23.
- 1375.19 Intersect line 4-1 Sur No 1285 No 6 lode at N 70° 58' E 6.93 ft. from Cor. No. 1.
- 1391.93 Intersect line 1-2 of Sur No 1285 No 6 lode identical with line 4-3 of the No 2 lode, same survey at S 18° 46' E 15.21 ft from Cor's No 1 and No 4 thereof.
- 1461.36 To Cor. No. 1 the place of beginning.

## No 6 Fraction Lode.

Beginning at Cor. No. 1.  
 Identical with Cor. No. 4 Sur. No 1285 Treadwell lode and location monument.  
 A concrete monument 24 in long 12 in diam. at base and 6 to 8 in diam at top, set 1 ft in the ground.  
 The core is a 2 in. iron pipe topped by a cap containing a brass disk stamped + J- No 4 1285 and No. 6 F. No. 1. 3471 whence

A cross on rock in place marked B+R No. 6 F 1-3471 bears N 85° 18' E 15.70 ft.

The sec cor. common to Sec's 22-23-26-27 T16 R2E G4SRB4M bears S 34° 12' E 538.74 ft.

Cor 5 sur. No. 1285 Treadwell lode bears S 70° 14' 10" E 289.14 ft.

157.53 <sup>South end of center a ground station</sup> <sup>3 ft diam and 4 ft high</sup> <sup>hence</sup> S 70° 16' 30" E 209.72 Intersect line 2-3 No. 5 Traction lode, this survey at N 6° 33' 50" E 581.96 ft from Cor. No. 2.

268.68 Intersect line from Cor. No. 3 Kendrick sur. No. 1285 to Cor No 5 Treadwell, same survey at S 69° 43' 40" E 112.96 ft from Cor. 3 Kendrick and N 69° 43' 40" E 20.46 ft from Cor. No. 5 Treadwell.

289.10 To Cor. No. 2.

A cross on the concrete of location monument which is a 2 in iron pipe 18 in long set in a hole drilled in rock in place and a concrete mound 1 ft diam at base, 8 in diam at top and 1 ft high formed around the pipe. The cross for location corner which is also Cor No 5 Treadwell sur No 1285 bears S 70° 26' E 0.20 ft from the cross on the concrete and the disk is stamped + T No 5 1285 for the corner of the Treadwell and No 6 F No 2, 3472 for the corner of this survey.

Whence A cross on rock in place marked B+R No 6 F-2 3471 bears N 47° 54' E 11.46 ft.

416.00 Cross under Power <sup>Whence</sup> <sup>N 70° 26' 30" E</sup> <sup>6.26 ft</sup> <sup>cross gulch running northeasterly</sup> 755.00 Cross under Power 1024.00 Intersect line 1-4 of Jerome Townsite at S 50° 18' - 35" E 885.86 ft. from Cor No. 1

1487.31 To Cor No. 3.

Identical with Cor. No. 4 sur No 1285 Kendrick lode. Cor No 2 sur No. 960 Oddity lode. Cor No 3 sur No. 590 Hermit lode, and Cor No 14 sur No. 1213 No. 6 lode, and also location corner.

A concrete monument similar to Cor No 1 of this survey, the brass disk being stamped. + N. No. 4, 1285, O. No. 2, 960. H. No. 3, 590 No. 6, No 14, 1213 and No. 6 F. No 3, 3471.

Cor 3 sur. No. 1285 Kendrick lode bears S 12° 32' E 1463.66 ft.

Cor 15 of sur No 1213 No 6 lode bears S 21° 16' 30" E 1022.56 ft. and Cor 13 of said lode bears N 54° 01' E 352.39 ft. from the same point.

Cor No 1 of Jerome Townsite bears N 80° 17' - 40" E 630.77 ft.

# Mineral Survey No 3471

Thence N 70°16'30" E

- 140.09 North end center, a mound of stones 3 ft. diam and 4 ft. high.
- 225.00 Cross ~~Yagon~~ <sup>Yagon</sup> Road running southeasterly
- 260.00 Cross ~~Yagon~~ <sup>Yagon</sup> Road running northwesterly
- 297.62 To Coy. No. 4.

A concrete monument similar to Coy No 1 of this survey. The brass disk is stamped + No 6 Fr No 4 3471

- 105.630 ~~cross~~ <sup>cross</sup> ~~Yagon~~ <sup>Yagon</sup> Road running southeasterly
- 694.11 Intersect line 2-3 No 5 Fr lode this survey at S 6°33'50" W 14.68 ft from Coy. No. 3.
- 834.91 Intersect line 1-4 Jerome Townsite at S 50°18'35" E 1306.47 ft from Coy. No. 1.
- 1432.53 Intersect line 16-17 Sur. No. 1213 No. 6. lode at N. 52°24'30" E 176.58 ft. from Coy. No. 16.
- 1489.15 To Coy. No. 1, the place of beginning.

Variation at all corners 14°30' E - 15° E  
Lode lines

As near as can be determined from present developments the veins of the several locations embraced in this claim extend as follows from their respective discovery points.

- No 5 Fraction lode, 760.83 ft S 5°42' W and 700.53 ft S 5°42' E
- No 6 Fraction lode, 700.00 ft S 7°07' E and 789.15 ft S 7°07' W.

## Area.

Total area No 5 Fraction lode	Acres	15.467 ✓
Area in conflict with -		
Sur. No 1051 Maine lode		0.005 ✓
Sur No 1213 No 6 lode		6.460 ✓
Sur No 1213 Copper Chief lode		0.288 ✓
Sur No 1285 No 2 lode		0.179 ✓
Sur No 1285 No 2 lode (exclusive of its conflict with Sur. No. 1213 Copper Chief lode)		0.178 ✓
Sur No 1285 No <sup>Chief</sup> lode		0.001 ✓
Sur. No 1285 No <sup>Chief</sup> lode (exclusive of its conflict with Copper Chief lode Sur No 1213)		0.001 ✓
Sur No 1285 Treadwell lode		4.912 ✓
Sur. No 1285 Kendrick lode		0.090 ✓
Sur. No 1395 <u>Am.</u> 16 <sup>1</sup> lode		0.000 ✓



Total area No 6 Fraction lode	9.787 ✓
Area in conflict with - Suv. No. 1213 No. 6 lode	4.853 ✓
Suv. No 1285 Kendrick lode	2.221 ✓
No 5 Fraction of this survey	1.868 ✓
No 5 Fraction of this survey (exclusive of its conflict with Suv. No 1213 No 6 lode)	0.682 ✓
No 5 Fraction of this survey (exclusive of its conflict with Suv. No 1285 Kendrick lode)	1.778 ✓
No 5 Fraction of this survey (exclusive of its conflict with Suv. No. 1213 No. 6 lode and Suv. No. 1285 Kendrick lode)	0.592 ✓

### Location

This survey is located in Sec's <sup>27, 28</sup> <sup>21, 22</sup> <sup>23</sup> <sup>24</sup> T. 16 N. R. 2 E. G. & S. R. B & M. and within the Prescott National Forest.

Expenditure of Five Hundred Dollars  
I certify that the value of the labor and improvements made upon each of the locations embraced in said mining claim by the claimant or its grantors is not less than five hundred dollars and that said improvements consist of:

No 5 Fraction  
No. 1. The discovery cut, the face of which being the discovery point, is on the lode line  $N 50^{\circ} 42' E$  760.83 ft. from the south end center. 6 ft wide 8 ft face running  $S 24^{\circ} E$  10 ft to mouth.

No. 2. A cut and tunnel the mouth of said tunnel bearing from Cor. No. 1,  $N 16^{\circ} 03' E$  604.62 ft.

$3\frac{1}{2} \times 6$  ft. running  $N 12^{\circ} E$  51 ft. to face of tunnel.

From the mouth of the tunnel a  $3\frac{1}{2} \times 8$  ft. face cut runs  $S 12^{\circ} E$  20 ft to mouth

Value of cut and tunnel \$610.00

Mineral Survey No 3471

No. 6 Fraction

No. 1

The discovery tunnel. The discovery point being in the mouth of said tunnel is on the lode line N 70° 07' W 700 ft. from the south end center. From said discovery point a 3 1/2 x 6 ft tunnel runs S 49° E 21 ft to a point, thence S 60° E 34 ft to the face. Value of tunnel \$ 550.00

Instrument.

This survey was made with a C. P. Berger & Sons mining transit. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 100 ft. and 660 ft. steel tapes.

Adjoining Claims

These claims are adjoined on the north by the Oddity lode sur. No 960 Clark Montana Realty Co. claimant. Hermit lode sur No 590 United Verde Copper Co. claimant. Inaine lode sur. No 1051 Hull Copper Co. claimant. No 6 lode sur No 1213 Hull Copper Co. claimant. On the east by the

16 to 1 lode sur No 1395 Am. United Verde Extension Co. claimant. Copper Chief lode sur No 1213 Chas H. Clark Jr. claimant.

On the south by the No. 2 lode sur. No 1285 Hull Copper Co claimant of northern end. No 3 lode sur. No 1285 Hull Copper Co claimant of northern end.

On the west by the Treadwell lode sur. No 1285 Geopatra Copper Co claimant. Kendrick lode sur No 1285 Hull Copper Co claimant.

Report

The lines of this claim were run upon the ground by two closed traverses and the conflicts tied in from the several traverse points.

The sec. cor. common to Secs 22-23-26-27 T16 N R 2 E G & SR B & M is a 2 in iron pipe on which is a brass cap stamped + T16 N R 2 E S 22 S 23 S 27 S 26

All concrete monuments are similar to Cor No 1 of this survey unless otherwise noted.

Surv. No 1213 No 6 lode

The corners are concrete monuments replacing the original stone corners properly marked that were in place, and at Cor. No 18 a compromise corner was agreed by the several companies involved and it was set from private data in their offices; as this corner was not in place and the bearing rocks were all gone; said to be used in the construction of a stone wall for the school.

I find line 14-15 to be  $S 21^{\circ} 16' 30'' E$  1022.56 ft  
 instead of  $S 19^{\circ} 47' E$  1057.50 ft.  
 I find line 15-16 to be  $S 6^{\circ} 24' E$  478.89 ft  
 instead of  $S 5^{\circ} 40' E$  486.40 ft.  
 I find line 16-17 to be  $N 52^{\circ} 24' 30'' E$  550.43 ft  
 instead of  $N 53^{\circ} 00' E$  600.00 ft.  
 I find line 17-18 to be  $N 6^{\circ} 20' 15'' E$  470.65 ft  
 instead of  $N 5^{\circ} 40' E$  486.40 ft.  
 I find line 18-13 to be  $N 32^{\circ} 02' E$  981.66 ft.  
 instead of  $N 32^{\circ} 05' E$  1013.60 ft.

Surv. No. 1213 Copper Chief lode.

Cors 2-3-4 are concrete monuments as is also Cor 17 of No 6 lode same survey which is reported as being on line 3-4. Cor 3 was not in place its position being identical with Cor 18 of the No 6 lode and its position being determined as given.

I find line 2-3 to be  $S 61^{\circ} 09' E$  419.33 ft.  
 instead of  $S 61^{\circ} 00' E$  429.00 ft.  
 I find line 3-17 of No 6 lode to be  $S 6^{\circ} 20' 15'' E$  470.65 ft  
 instead of  $S 5^{\circ} 40' E$  486.40 ft.  
 I find line 17 of No 6 lode - 4 to be  $S 4^{\circ} 51' 20'' E$  973.09 ft.  
 instead of  $S 5^{\circ} 40' E$  993.00 ft.

Surv. No. 1051 Maine lode.

Cors 4 and 5 are concrete monuments. Cor 6 is not in place, and to replace it from the official calls and ties would give a different position for each one used. A compromise corner will be established when all private records of the companies involved have been examined as to the actual position this corner occupied.

Mineral Survey No 3471.

The bearing given here for line 5-6 is the one reported in Sur. No. 1395 Amd and is here used as it was the last official record that was made of this corner

Cor 5 is identical with Cor 18 of Sur No 1213 No 1 lode and Cor 3 Copper Chief lode same survey heretofore described.

I find line 4-5 to be  $S 32^{\circ} 02' E$  981.66 ft  
instead of  $S 32^{\circ} 05' E$  1013.60 ft.

Sur. No. 1395 Amd 16 to 1 lode.

Cors 1-2-6 are not in place and the B + Rs for Cors 1 and 6 have been used is the school wall, it is reported, along with the corners.

The bearing rock for Cor 2 is still in a wall as reported but the wall is supposed to have been rebuilt since originally constructed.

Cor 5 is a concrete monument, identical with Cor 2 Sur. No 1213 Copper Chief

The bearing of line 1-2 and 6-1 are given as recorded

I find the bearing of line 5-6 to be  $S 61^{\circ} 09' E$   
instead of  $S 61^{\circ} 00' E$  and the distance of Cor. 6 from Cor 3 Copper Chief Sur No 1213 is proportioned, as the actual length of line 2-3 of said Copper Chief is to the recorded distance.

This compromise proportioning makes.

Cor 3 Copper Chief to Cor 6 of 16 to 1	$N 61^{\circ} 09' E$	12.54 ft
instead of	$N 61^{\circ} 00' E$	12.82 ft
Line 6-1	$N 74^{\circ} 06' E$	4.78 ft
is	do	4.85 ft
instead of	$S 40^{\circ} 58' E$	9.75 ft
Cor 1 to Cor 3 Copper Chief	do	10.00 ft
is	do	
instead of		

Sur. No 1285 Cross<sup>hill</sup> lode.

All corners are concrete monuments  
I find bearing of line 1-2 to be  $S 18^{\circ} 46' E$   
instead of  $S 19^{\circ} E$

I find the bearing of line 4-1 to be  $S 70^{\circ} 58' E$   
instead of  $S 71^{\circ} 00' E$

Sur. No. 1285 No. 2 lode.

Cor 1 is a 2 in pipe set in a hole drilled in rock and concreted in place. Cor 4 is a concrete monument.

I find the bearing of line 4-1 to be  $S 69^{\circ} 16' 30'' E$   
instead of  $S 71^{\circ} 00' E$

Sur No 1285 Treadwell lode  
 Co's 2 & 5 are 2 in pipes set in holes drilled in rock  
 and concreted in place. Co's 3 & 4 are concrete monuments.  
 I make line 2-3 to be  $N 69^{\circ} 16' 30'' E$  576.04 ft  
 instead of  $N 71^{\circ} 00' E$  600.00 ft.  
 I make line 3-4 to be  $N 19^{\circ} 08' 10'' E$  637.08 ft.  
 instead of  $N 19^{\circ} 00' E$  625.00 ft.  
 I make line 4-5 to be  $S 70^{\circ} 14' 10'' E$  289.14 ft.  
 instead of  $S 71^{\circ} E$  300.00 ft.

Sur. No. 1285 Kendrick lode.  
 Co's 1-3-4 are concrete monuments. Cor 2 and  
 Cor 5 of Treadwell lode same survey are 2 in pipes  
 set in holes drilled in rock and cemented in place.  
 Cor 5 of Treadwell is reported as being on line  
 2-3 Kendrick  $N 53^{\circ} E$  315 ft from Cor No 2 or.  
 $S 53^{\circ} E$  120 ft from Cor 3. I make it  
 $S 69^{\circ} 43' 40'' E$  133.42 ft. from Cor 3.

I make line 3-4  $N 12^{\circ} 32' E$  1468.66 ft.  
 instead of  $N 11^{\circ} 53' E$  1493.70 ft.  
 Cor 3 Kendrick is reported as being identical with  
 Cor 16 of Sur No 1213 No 6 lode and I so find  
 it but I also find another B + R to the north  
 of the one reported. At Cor No 1 I find a  
 somewhat similar condition of double markings.

Jerome Townsite.  
 Cor 1 is a  $24 \times 24$  in stone 18 in exposed marked  
 + Cor No 1 I Cor's 2 and 4 are 5 in. iron pipes 2 ft exposed.  
 I make line 1-2  $N 26^{\circ} 03' E$  instead of  $N 26^{\circ} E$   
 and make line 4-1  $N 50^{\circ} 18' 35'' E$  2649.51 ft instead  
 of  $N 50^{\circ} E$  2667.00 ft.

Section line.  
 Sec. Cor. common to secs 22-23-26-27 and  
 $\frac{1}{4}$  sec Cor between Sec's 22 & 23 are iron pipes  
 with brass caps marked as reported.

I make this line  $N 0^{\circ} 09' 30'' E$  2637.31 ft.  
 instead of  $N 0^{\circ} 01' E$  2640.00 ft.

AMENDED  
NOTICE OF MINING LOCATION  
LODE CLAIM

TO ALL WHOM IT MAY CONCERN:

This Mining Claim, the name of which is the No. 5 Fraction Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by Chas. W. Clark, Trustee, A Citizen of the United States, the undersigned, on the 8th day of May, 19018.

The length of this claim is 1500 feet, and I claim 715 feet in a Northeasterly direction and 785 feet in a Southwesterly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with 300 feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the Northeast to the Southwest.

The claim is situated and located in the Verde Mining District, in Yavapai County in the State of Arizona, about 3/4 Mile in a Southwesterly direction from United Verde Copper Company's No. 3 shaft.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at A monument at a point in a Northeasterly direction 715 feet from the discovery shaft (at which this notice is posted), being in the center of the North end line of said claim; thence 300 feet to a monument, being the Northeast corner of said claim; thence 1500 feet to a monument, being at the Southeast corner of said claim; thence 300 feet to a monument at the center of the South end of said claim; thence 300 feet to a monument, being at the Southwest corner of said claim; thence 1500 feet to a monument at the Northwest corner of said claim; thence 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.

This is an Amended Location Notice of the No. 5 Fraction Mining Claim, located by G. W. Hull, on the 19th day of April, 1915, and recorded in Book 97 of Records of Mines, at page 374, in the office of the County Recorder of the aforesaid County of Yavapai to which reference is hereby made, and this amended Location Notice is made and posted to correct errors in the description in the said original Location Notice

Dated and posted on the ground this 8th day of May, 19018.  
Roy E. Cook  
Witness  
Chas. W. Clark, Trustee,  
By C. V. Hopkins  
As Agent

Filed and Recorded at request of Anderson & Ellis, May 13th A. D., 1918, at 11:00 o'clock A. M., Book 99 of Mines, Page 422, Records of Yavapai County, Arizona.  
(SEAL) E. A. McSWIGGIN, County Recorder  
By Lula McIntosh,  
Deputy Recorder



AMENDED  
NOTICE OF MINING LOCATION  
LODE CLAIM

To All Whom It May Concern:

This Mining Claim, the name of which is the No. 6 Fraction Mining Claim, situate on lands belonging to the United States of America, and in which there are valuable mineral deposits, was entered upon and located for the purposes of exploration and purchase by George W. Hull, a citizen of the United States, the undersigned, on the 19th day of April, 1915.

The length of this claim is fifteen hundred (1500) feet and I claim eight hundred (800) feet, in a northwesterly direction and seven hundred (700) feet in a southeasterly direction from the center of the discovery shaft, at which this notice is posted, lengthwise of the claim, together with three hundred (300) feet in width of the surface grounds, on each side of the center of said claim. The general course of the lode deposit and premises is from the northwest to the southeast

The claim is situated and located in the Verde Mining District, in Yavapai County, in the State of Arizona, about 1000 feet in a southwesterly direction from the town of Jerome.

The surface boundaries of the claim are marked upon the ground as follows: Beginning at monument at a point in a northwesterly direction 800 feet from the discovery shaft (at which this notice is posted), being in the center of the north end line of said claim; thence north-easterly 300 feet to a monument, being the most northerly corner of said claim; thence southeasterly 1500 feet to a monument, being at the most easterly corner of said claim; thence southwesterly 300 feet to a monument at the center of the south end of said claim; thence southwesterly 300 feet to a monument, being at the most southerly corner of said claim; thence northwesterly 1500 feet to a monument at the most westerly corner of said claim; thence northeasterly 300 feet to the place of beginning.

All done under the provisions of Chapter Six, of Title XXXII, of the Revised Statutes of the United States, and of an Act of the General Assembly of Arizona, entitled "An Act to Revise and Codify the Laws of the Territory of Arizona," approved March 16, 1901.

This is an Amended Location Notice of the No. 6 Fraction Mining Claim, located by Geo. W. Hull on the 17th., day of August, 1898, and recorded in Book 51 of Mines, at page 84, in the office of the County Recorder of the aforesaid County of Yavapai to which reference is hereby made, and this Amended Location Notice is made and posted to correct errors in the description in the said original Location Notice.

Dated and posted on the ground this 19th., day of April, 1915.

G. W. Hull.

Filed and recorded at request of G. W. Hull, June 30th., A.D. 1915, at 4:35 o'clock P. M., Book 86 of Mines, page 476, Records of Yavapai County, Arizona.

(SEAL)

L. S. Colwell, County Recorder

By E. A. McSwiggin,  
Deputy Recorder



STATE OF ARIZONA )  
                          ) SS  
COUNTY OF YAVAPAI )

I, EDITH RUFFNER, County Recorder in and for the  
aforesaid County of Yavapai and State of Arizona, and Custodian  
of the Records of such Office; DO HEREBY CERTIFY that I have  
compared the foregoing Copies with, and that the same are  
full, true and correct Copies of the Original Location Notice  
of the No. 5 FRACTION, Lode Mining Claim and the AMENDED Location  
Notice of the No. 6 FRACTION, Lode Mining Claim, as the same  
appear of Record in Books 97 and 86 at Pages 374 and 476,  
respectively, of the records of my said office.

IN WITNESS WHEREOF, I have hereunto  
set my hand and affixed my Official  
Seal, this 19th day of September,  
A.D. 1917.



*Edith Ruffner*  
\_\_\_\_\_  
COUNTY RECORDER  
OF  
YAVAPAI COUNTY  
ARIZONA

By *Rollin Butler*  
\_\_\_\_\_  
Deputy Recorder

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

FEB 9 1920, 191

I, U. S. Surveyor-General for District of Arizona.  
do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey  
of the mining claim of CHARLES W. CLARK, Trustee,  
known as the NO. 5 FRACTION and NO. 6 FRACTION Lodes,  
situate in VERDE  
Mining District, YAVAPAI County, ARIZONA,  
in Sections 22 & 27 <sup>unsur. & 23</sup> Township No. 16 N., Range No. 2 E., G&SRB&M, and  
designated as Survey No. 3471, has been correctly copied from the originals on file in  
this office; that said Field Notes furnish such an accurate description of said mining claim as will, if  
incorporated into a patent, serve fully to identify the premises, and that such reference is made therein  
to natural objects or permanent monuments as will perpetuate and fix the *locus* thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improve-  
ments made upon <sup>or for each of</sup> said mining claim by claimant or his grantors, and that said improvements  
consist of two cuts and 2 tunnels, total value \$1210.00

and that no portion of said labor or improvements has been included in the estimate of expenditures  
upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix,  
Arizona is correct and in conformity with the foregoing Field Notes.

Frank P. Trott,

United States Surveyor-General for Arizona

SURVEYOR-GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

FEB 9 1920, 191

I, U. S. Surveyor-General for District of Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

CHARLES W. CLARK, Trustee,

, known as the

NO. 5 FRACTION and NO. 6 FRACTION Lodes

situate in VERDE mining district,

YAVAPAI County, ARIZONA,

in Sections 22 & 27, Un<sup>sur.</sup> & 23 Township No. 16 N., Range No. 2 E., G&SRB&M,

designated as Survey No. 3471

executed by Joseph McCarthy, United States Mineral

Amended

Surveyor, July 19 - 24, 1918, under my instructions dated

May 17, 1918, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. A true copy of the copy of the location certificate filed by the applicant for

survey is included in the field notes.

Handwritten signature of Frank P. Smith

U. S. Surveyor-General for Arizona.