MINERAL SURVEY No. 3631

Arizona. Land District. FIELD NOTES OF THE SURVEY OF THE MINING CLAIM OF Black Giant Mines Company KNOWN AS THE NORTH STAR, LITTLE GEM NO.1, ANNA MC, RED ROSE and BUCK Lodes. Ellsworth Mining District, Yuma County, Arizona. Section 5 7,18, 12 Township 7 N. , Range 8 12 and 13 W. G.S.R.M. Surveyed under instructions dated November 12, ,, 1919. " amended November 24, 1919. by C. C. Thompson. U. S. Mineral Surveyor. See Claim located Location notices , 19 Survey commenced December 9, 1919. Survey completed December 18, 1919. Address of claimant H. W. Rose, Atty., Yuma, Ariz. DATES OF AMENDED LOCATIONS. 6-822

NORTH STAR LODE.

Beginning at Cor. No. 1.

A stone 7 x 12 x 24 ins. set 14 ins. in the ground, with mound of stone, chiseled INS-3631 and a cross at corner point,

whence,

The $\frac{1}{4}$ Cor. to Secs. 7 and 12, T. 7 N., Rs. 12 and 13 W., G. S. R. M., bears N. 62° 03' 00" E. 2048.10 ft. No other bearings available.

Feet.

Thence S. 34° 49' W.

300

The east end center, being a stone monument, on line.

411.06

Intersect line 2-3 Little Gem No. 1 lode of this survey, and also line 3-4 Wisconsin lode Sur. No. 3530 at S. 81° 12' E. 136.52 ft. from Cor. No. 3.

480

Road running easterly and westerly.

600

To Cor. No. 2.

Identical with Cor. No. 4 Teddy lode Sur. No. 3530 and with the N. E. Cor. American Flag lode unsurveyed, Vindicator Mining Company claimant.

> A 4 in. iron pipe showing 6 ins. above mound of earth and stone, stamped 2NS-3631 and T.4.3530.

No bearings available.

Thence N. 55° 11' W.

59.69 Intersect line 2-3 Wisconsin lode Sur. No. 3530 at S. 8° 48' W. 143.61 ft. from Cor. No. 3.

184

Road running easterly and westerly.

1500

To Cor. No. 3.

Identical with the N. W. Cor. American Flag lode unsurveyed,

A stone 12 x 14 x 24 ins. set 14 ins. in the ground, with mound of stone, chiseled 3NS-3631 and a cross at corner point.

No bearings available.

SURVEY NO. 3631.						
T	Feet.	Thence N. 34° 49' E.				
	3 00	The west end center, being a stone monument, on line.				
	600	To Cor. No. 4.				
	burgung.	A stone 7 x 11 x 24 ins. set 14 ins. in the ground,				
	2h 8	with mound of stone, chiseled 4NS-3631 and a cross at				
		corner point.				
		No bearings available.				
۱		A STATE OF B. H. SER OF B. R. SCAR				
		Thence S. ob 11. H.				
	1258.69	Intersect line 3-4 Little Gem No. 1 lode of this survey.				
	1500	To Cor. No. 1 the place of beginning.				
	VALUE - B	LITTLE GEM NO. 1 LODE.				
	org p	Beginning at Cor. No. 1.				
	200-100	A stone 4 x 14 x 26 ins. set 16 ins. in the ground,				
		with mound of stone, chiseled 1LG1-3631 and a cross at				
		corner point,				
	0888	whence,				
The 1 Cor. to Secs. 7 and 12, T. 7 N., Rs.12 and						
	13 W., G. S. R. M., bears N. 28° 35' 10" E. 1057.20 ft.					
The S. E. Cor. Mobile Bay lode unsurveyed, John						
		Jones and Thos. S. Leatherbury claimants, bears S. 71°				
		40' W. 461 ft.				
		No other bearings available.				
	.8 +	Thence S. 8º 48' W.				
	293.6	Intersect line 3-4 Red Rose lode of this survey. The east end center, being a stone monument, on line.				
	3 00	The east end center, being a stone this survey. 19 Intersect line 2-3 Anna Mo lode of this survey.				
	345.					
	600	To Cor. No. 2. A stone 6 x 12 x 28 ins. set 16 ins. in the ground,				
		with mound of stone, chiseled 2LG1-3631 and a cross at				
	ancorn.					
	23 6	corner point,				
		whence, Cor. No. 3-4 Anna Mo and Buck lodes respectively,				
		both of this survey, bears N. 77° 09' E. 143.36 ft.				
		both of this bulvey,				

Feet. Cor. No. 4 Red Rose lode of this survey bears N. 840 341 W. 293.29 ft.

No other bearings available.

Thence N. 81° 12' W.

102.00 Cor. No. 4 Wisconsin lode Sur. No. 3530 on line.

277.17 Intersect line 3-4 Red Rose lode of this survey.

Road running northerly and southerly.

1463.48 Intersect line 1-2 North Star lode of this survey.

1500 To Cor. No. 3.

On line 3-4 Wisconsin lode Sur No. 3530.

A stone 7 x 10 x 24 ins. set 14 ins. in the ground, with mound of stone, chiseled 3LG1-3631 and a cross at corner point,

whence,

Cor. No. 2 North Star lode of this survey bears S. 24° 04' W. 176.02 ft.

No other bearings available.

Thence N. 8º 48' E.

The west end center, being a stone monument, on line.

475.22 Intersect line 4-1 North Star lode of this survey.

600 To Cor. No. 4.

A stone 6 x 11 x 24 ins. set 14 ins. in the ground, with mound of stone, chiseled 4LG1-3631 and a cross at corner point.

No bearings available.

Thence S. 81° 12' E.

N. 24° 39' W. 648.37 ft. from its S. W. Cor.

928 Road running northerly and southerly.

N. 24° 39' W. 251.98 ft. from its S. E. Cor. when sweet said lot trans 165° 21' W. 650 ff.

1271.91 Intersect line 2-3 Anna Mc lode of this survey.

1500 To Cor. No. 1 the place of beginning.

24

ANNA MC LODE. Feet. Beginning at Cor. No. 1. A stone 7 x 14 x 28 ins. set 16 ins. in the ground, with mound of stone, chiseled 1AM-3631 and a cross at corner point, was a management whence, whence the same with the same and th The # Cor. to Secs. 7 and 12, T. 7 N., Rs. 12 and 13 W., G. S. R. M., bears S. 77° 00' E. 552 ft. No other bearings available. Thence S. 65° 21' W. The north end center, being a stone monument, on line. 300 600 To Cor. No. 2. A stone 8 x 12 x 24 ins. set 14 ins. in the ground, with mound of stone, chiseled 2AM-3631 and a cross at corner point. No bearings available. Thence S. 24° 391 E. 844.44 Intersect line 4-1 Little Gem No. 1 lode of this survey. Intersect line 3-4 Red Rose lode of this survey. 1222.41 1258.14 Intersect line 1-2 Little Gem No. 1 lode of this survey. To Cor. No. 3. 1500 Identical with Cor. No. 4 Buck lode of this survey. A stone 6 x 12 x 24 ins. set 14 ins. in the ground, with mound of stone, chiseled 4B-3AM-3631 and a cross at corner point. No bearings available. man mad have very many want yield from most speed. Thence N. 65° 21' E. 270.58 Intersect line 2-3 Red Rose lode of this survey. The south end center, being a stone monument, on line. 300 503.44 Intersect east boundary Sec. 12, T. 7 N. R. 13 W., G. S. R. M., at North 1393.78 ft. from its S. E. Cor. and at South 1279.42 ft. from the to Cor. on said east boundary

To Cor. No. 4.

600

Feet.

1500

Identical with Cor. No. 3 Buck lode of this survey.

A rock in place 10 x 12 ins. showing 4 ins. above
ground, with mound of stone, chiseled 3B-4AM-3631 and
a cross at corner point.

No bearings available.

Thence N. 24° 39' W.

210.42 Intersect east boundary Sec. 12, T. 7 N., R. 13 W., G. S. R. M., at North 1625.30 ft. from its S. E. Cor. and at South 1047.90 ft. from the 1 Cor. on said east boundary Sec. 12.

To Cor. No. 1 the place of beginning.

RED ROSE LODE.

Beginning at Cor. No. 1.

Identical with Cor. No. 1 Old Timer lode Sur. No. 3529.

A 4 in. iron pipe showing 6 ins. above mound of earth and stone, stamped 1RR-3631 and 0.T.1.3529, whence.

The S. W. Cor. Sec. 7, T. 7 N., R. 12 W., G. S. R. M., bears S. 74° 53' W. 57.74 ft.

SE GO. ESE . E 128

No other bearings available.

Thence N. 50° 56' E.

21.34 Intersect line 4-1 Buck lode of this survey.

The south end center, being a stone monument, on line.

600 To Cor. No. 2.

300

A stone 7 x 10 x 26 ins. set 16 ins. in the ground, with mound of stone, chiseled 2RR-3631 and a cross at corner point.

No bearings available.

Thence N. 39° 04' W.

827.97 Intersect east boundary Sec. 12, T. 7 N., R. 13 W., G. S. R. M., at North 1035.93 ft. from its S. E. Cor. and

Feet. at South 1637.27 ft. from the # Cor. on said east boundary Sec. 12.

1163.79 Intersect line 3-4 Buck and Anna Mc lodes of this survey.

1500 To Cor. No. 3.

A stone 5 x 14 x 26 ins. set 16 ins. in the ground, with mound of stone, chiseled 3RR-3631 and a cross at corner point.

No bearings available.

Thence S. 50° 56' W.

163.58 Intersect line 1-2 Little Gem No. 1 lode of this survey.

192.94 Intersect line 2-3 Anna Mc lode of this survey.

300 The north end center, being a stone monument, on line.

576.74 Intersect line 2-3 Little Gem No. 1 lode of this survey, and also line 3-4 Wisconsin lode Sur. No. 3530 at N. 81° 12° W. 175.17 ft. from Cor. No. 4.

600 To Cor. No. 4.

Identical with Cor. No. 4 Old Timer lode Sur. No. 3529.

A 4 in. iron pipe showing 10 ins. above mound of earth and stone, stamped 4RR-3631 and 0.T.4.3529, whence,

Cor. No. 4 Wisconsin lode Sur. No. 3530 bears S. 86° 22° E. 191.55 ft.

No other bearings available.

Thence S. 39° 04' E.

- 257.25 Intersect line 4-1 Wisconsin lode Sur. No. 3530 at S. 80 48' W. 189.82 ft. from Cor. No. 4.
- 1411.55 Intersect east boundary Sec. 12, T. 7 N., R. 13 W., G. S. R. M., at North 83.73 ft. from its S. E. Cor. and at South 2589.47 ft. from the 4 Cor. on said east boundary Sec. 12.
- 1500 To Cor. No. 1 the place of beginning.

0 18 4 7 1 2 10 10 10

Feet. Beginning at Cor. No. 1.

A stone 4 x 6 x 24 ins. set 14 ins. in the ground, with mound of stone, chiseled 1B-3631 and a cross at corner point,

whence,

The S. W. Cor. Sec. 7, T. 7 N., R. 12 W., G. S. R. M., bears N. 43° 04' W. 245.67 ft.

Cor. No. 1 Red Rose lode of this survey bears
N. 29° 56' W. 224.48 ft.

No other bearings available.

Thence N. 65° 21' E.

The south end center, being a stone monument, on line.

To Cor. No. 2.

A stone 5 x 12 x 28 ins. set 16 ins. in the ground, with mound of stone, chiseled 2B-3631 and a cross at corner point.

No bearings available.

Thence N. 24° 39' W.

1500 To Cor. No. 3.

Identical with Cor. No. 4 Anna Mc lode of this survey, previously described.

Thence S. 65° 21' W.

96.55 Intersect west boundary Sec. 7, T. 7 N., R. 12 W., G. S. R. M., at North 1393.78 ft. from its S. W. Cor. and at South 1279.42 ft. from the ‡ Cor. on said west boundary Sec. 7.

The north end center, being a stone monument, on line.

329.42 Intersect line 2-3 Red Rose lode of this survey.

600 To Cor. No. 4.

Identical with Cor. No. 3 Anna Mc lode of this survey, previously described.

Feet.

1097.79 Intersect east boundary Sec. 12, T. 7 N., R. 13 W., G. S. R. M., at North 186.08 ft. from its S. E. Cor. and at South 2487.12 ft. from the 4 Cor. on said east boundary Sec. 12.

1271.16 Intersect line 1-2 Red Rose lode of this survey.

1500

To Cor. No. 1 the place of beginning.

All corners of this survey are identical with the corners of the locations.

Variation at all corners of this survey 15° E.

LODE LINES.

As near as can be determined from present developments the veins of the locations embraced in this survey extend as follows from their respective discovery points:

North Star lode, 400 ft. S. 55° 11' E. and 1100 ft. N. 55° 11' W.

Little Gem No. 1 lode, 195 ft. N. 81º 12' W. and 1305 ft. S. 81° 12' E.

Anna Mc lode, 310 ft. S. 24° 39' E. and 1190 ft. N. 24° 39' W.

Red Rose lode, 140 ft. N. 39° 04' W. and 1360 ft. S. 39° 041 E.

Buck lode, 252 ft. N. 24° 39' W. and 1248 ft. S. 24° 391 E.

AREA.

20.661 Acres. Total area North Star lode Area in conflict with Wisconsin lode Sur. No. 3530 0.355 Acre.

20.661 " Total area Little Gem No. 1 lode Area in conflict with North Star lode of this survey 1.338 Acres. Area in conflict with Anna Mc lode of this survey 0.904 Acre.

Area in conflict with Red Rose lode
of this survey 0.975 Acre.

Area in conflict with Red Rose lode
exclusive of its conflict with Anna
Mc lode, both of this survey, 0.963 Acre.

Area in conflict with Mobile Bay lode
unsurveyed 6.200 Acres.

Total area Anna Mc lode

20.661 Acres.

Total area Red Rose lode

20.661 "

Area in conflict with Anna Mc lode

of this survey 1.607 Acres.

Area in conflict with Buck lode of this survey 11.678 Acres.

Area in conflict with Wisconsin lode

Sur. No. 3530 0.450 Acre.

Total area Buck lode

20.661

LOCATION.

This claim is located in the S. W. 1 and the N. W. 1 Secs. 7 and 18, T. 7 N., R. 12 W., and in the S. 2 and N. E. 1 Sec. 12, T. 7 N., R. 13 W., G. S. R. M., all unsurveyed, Ellsworth Mining District, Yuma County, Arizona.

ADJOINING CLAIMS.

This claim is joined on the south and west by the Old Timer lode Sur. No. 3529, Wisconsin lode Sur. No. 3530, and by the American Flag lode unsurveyed, Vindicator Mining Company claimant, and on the north by the Mobile Bay lode unsurveyed, John Jones and Thos. S. Leatherbury claimants.

Other adjoining claims unknown.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements made upon, or for the benefit of, each of the

locations embraced in this claim by the claimant or its grantors, is not less than five hundred dollars and that said improvements consist of:

North Star lode.

No. 1. The discovery shaft is on the center line 400 ft. from the center of line 1-2, 4 x 6 ft. x 8 ft. deep.

Value \$80.00

No. 2. A shaft which from Cor. No. 2 bears N. 36° 40° W. 588 ft., 4 x 6 ft. x 8 ft. deep.

Value \$80.00

No. 3. A shaft which from Cor. No. 2 bears N. 33° W. 517 ft., 4 x 6 ft. x 8 ft. deep.

Value \$80.00

Note: An undivided one-ninth interest in the common improvement which is No. 1 on the Wisconsin lode Sur.

No. 3530, value\$1497.22, is also credited to this claim.

Little Gem No. 1 lode.

No. 1. The discovery shaft is on the center line 195 ft. from the center of line 3-4, 4 x 6 ft. x 8 ft. deep.

Value \$80.00

Note: An undivided one-ninth interest in the common improvement which is No. 1 on the Wisconsin lode Sur. No. 3530, value \$1497.22, is also credited to this claim.

Anna Mc lode.

No. 1. The discovery shaft is on the center line 310 ft. from the center of line 3-4, 4 x 6 ft. x 7 ft. deep.

Value \$70.00

No. 2. A shaft which from Cor. No. 4 bears N. 35° 15' W. 415 ft., 4 x 6 ft. x 7 ft. deep.

Value \$70.00

No. 3 A shaft which from Cor. No. 4 bears N. 39° 10' W. 500 ft., 4 x 6 ft. x 7 ft. deep.

Value \$70.00

Note: An undivided one-ninth interest in the common improvement which is No. 1 on the Wisconsin lode Sur.

No. 3530, value\$1497.22, is also credited to this claim.

Red Rose lode.

No. 1. The discovery shaft is on the center line 140 ft. from the center of line 3-4, 4 x 6 ft. x 8 ft. deep.

Value \$80.00

Note: An undivided one-ninth interest in the common improvement which is No. 1 on the Wisconsin lode Sur.

No. 3530, value \$1497.22, is also credited to this claim.

Buck lode.

No. 1. The discovery shaft is on the center line 252 ft. from the center of line 3-4, 4 x 6 ft. x 7 ft. deep.

Value \$70.00

No. 2. A shaft which from Cor. No. 4 bears N. 75° E. 300 ft., 4 x 6 ft. x 30 ft. deep.

Value \$400.00

No. 3. A shaft which from Cor. No. 4 bears S. 87° 45' E. 349 ft., 4 x 6 ft. x 32 ft. deep.

vit verte dans mit erdrede en en value \$425.00

Note: An undivided one-ninth interest in the common improvement which is No. 1 on the Wisconsin lode Sur.

No. 3530, value \$1497.22, is also credited to this claim.

The incline shaft, improvement No. 1 Wisconsin lode Sur. No. 3530, 5 x 7 ft. x a total depth of 190 ft. together with its first and second levels, has been credited to the Wisconsin and Teddy lodes Sur. No. 3530 and to the Old Timer and Junction lodes Sur. No. 3529, claimant herein. This improvement has been extended as follows:

From the 190 ft. point this shaft, 7 x 11 ft. in cross section, has been sunk in its N. 60° E. direction 36 ft. on an incline of 43°30', thence 30 ft. on an incline of 60° to a total depth on this date of 256 ft. old and new work combined.

Further extension of this improvement consists of a drift 6 x 7 ft. which, from the N. W. side of the shaft at a point 161 ft. from the surface, has

been driven 102 ft. to face in a N. 56° W. direction.

From the S. E. side of the shaft on the same level a drift 6 x 7 ft. has been driven 40 ft. in a S. 43° E. direction, thence S. 62° E. 34 ft. to face.

From a point at the S. E. side of the shaft at 246 ft. from the surface a drift 4 x 6 ft. runs S. 40° E. 20 ft. to face.

Total value of all new work \$4500.00

Total value of common improvement \$13,475.00

Value of an undivided one-ninth interest, \$1497.22, credited to each lode location of this claim and to each of the Wisconsin and Teddy lodes Sur. No. 3530 and also to each of the Old Timer and Junction lodes Sur. No. 3529.

The surface of this entire claim, consisting of the aforesaid 9 lode claims, is gently rolling ground and the central position of improvement No. 1 Wisconsin lode Sur. No. 3530 makes possible the most effective development of the entire claim with the greatest economy. Therefore, an undivided one-ninth interest in this common improvement, value \$1497.22, is credited to each lode location of the claim.

OTHER IMPROVEMENTS.

None.

INSTRUMENT.

State State

This survey was made with a C. L. Berger & Sons
No. 4 transit. The courses were deflected from a meridian established in connection with my survey No. 3628.
The distances were measured with a Lufkin 660 ft. steel
tage.

REPORT.

The S. E. Cor. to Sec. 7, T. 7 N., R. 12 W., and the ‡ Cor. to Secs. 7 and 12, T. 7 N., Rs. 12 and 13

W., G. S. R. M., are the regular metallic posts as have been adopted by the General Land Office for use on the public surveys and are properly marked.

Cor. No. 3 Wisconsin lode Sur. No. 3530 is a \frac{3}{4} in. iron pipe showing 6 ins. above mound of earth and stone, stamped W.3.3530.

Cor. No. 4 Wisconsin lode Sur. No. 3530 is a \(\frac{3}{4} \) in. iron pipe showing 6 ins. above mound of earth and stone, stamped W.4.3530.

The S. E. Cor. Mobile Bay lode unsurveyed is a stone monument.

The course S. 54° 47° E., of the north side line American Flag lode unsurveyed, shown on the official plat of Sur. No. 3530, is in error.

I find the line between the \(\frac{1}{4}\) Cor. to Secs. 7 and 12 and the corner to Secs. 7, 18, 13 and 12, T. 7 N., Rs. 12 and 13 W., G. S. R. M., to be North 2673.2 ft. and that the length of the same line shown on the official plat of Sur. No. 3529 is in error.

Note: The disagreement between these field notes and the location notices is due to errors in the latter.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals em	ployed by C. C. Thompson
United States Mineral Surveyor, to assist in	running, measuring, and marking the lines, corners, and
boundaries described in the foregoing field no	tes of the survey of the mining claim of
Black Gi	ant Mines Company
	m No. 1. Anna Mc, Red Rose, Buck lodes
and showing the respective capacities in which	
	J. Byard Swift , Chainman.
	, Chainman.
	, Axman.
	Flagman.
FINAL OATH	S OF ASSISTANTS.
We, I. J. Byard Swift,	
	, do solemnly swear that we assisted
	Mineral Surveyor, in marking the corners and surveying
	k Giant Mines Company
	No. 1, Anna Mo, Red Rose, Buck lodes
	ing been surveyed by said mineral surveyor and under his
lirection; and that said survey has been in all r	espects, to the best of our knowledge and belief, faithfully
nd correctly executed, and the corner and bounds	ary monuments established according to law and the instruc-
ions furnished by the United States Surveyor-Ge	7
	J. Byard Lewift, Chainman.
	, Chainman.
	Axman.
	, Flagman,
	the above-named persons before me this 26
day of December	
	Tom Dodson
	Notary Public.

FINAL OATH OF U.S. MINERAL SURVEYOR.

I, C. C. Thompson , U. S. Mineral Surveyor						
do solemnly swear that, in pursuance of instructions received from the United States						
Surveyor General for Arizona						
Surveyor General for Arizona November 12, 1919 Amended Nevember 24, 1919, , I have, in strict conformity to the laws of the						
United States, the official regulations and instructions thereunder, and the instructions						
of said Surveyor General, faithfully and correctly executed the survey of the Minimum						
Claim of Black Giant Mines Company						
, known as the						
Morth Star, Little Gem No. 1, Anna Mo, Red Rose, Buck lodes ,						
situate in Ellsworth Mining District,						
all uns., Yuma County, Arizona in Section						
7, 18, 13 , Township No. 7 M., Range No. 12 and 13 W., G. S. R. M.,						
and designated as Survey No. 3631 , as represented						
in the foregoing field notes, which accurately show the boundaries of said mining claim						
as distinctly marked by monuments on the ground, and described in the attached copy						
of the location certificate, which was received by me from the Surveyor General with						
said instructions, and that all the corners of said survey have been established and per-						
petuated in strict accordance with the law, official regulations and instructions there-						
under; and I do further solemnly swear that the foregoing are the true and original						
field notes of said survey and my report therein, and that the labor expended and						
improvements made upon said mining claim by claims by cl						
improvements made upon said mining claim by claimant oritsgrantors are as therein fully stated and that the character content leads						
are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of						
said labor or improvements so credited to this claim has been included in the estimate						
of expenditures upon any other claim. except that portion of the common						
improvement shown in notes of Sur. Nos. 3529 and 3530.						
20 20 01 Dul. Nos. 3529 and 3530.						
Cl Ulmpan						
U. S. Mineral Surveyor.						
Subscribed and sworn to by the said C. C. Thompson						
U. S. Mineral Surveyor, before me a Motary Public						
this 26						
day of December , 19 19.						
Tomtodson						
Not over Data in						
0-1044 Notary Public.						
My Commission expires March 29, 1922.						

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,
April 22. , 19 20
I, U. S. Surveyor-General for Arizons.
do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey
of the mining claim of Black Giant Mines Company
known as the NORTH STAR, LITTLE GEM NO.1, ANNA MC, RED ROSE, BUCK Lodes situate in Ellsworth
Mining District, Yuma County, Arizona
in Section 5 7, 18, 1,2 Township No. 7 N., Range No. 12 and 13 W., GSR Mad
designated as Survey No, has been correctly copied from the originals on file in
this office; that said Field Notes furnish such an accurate description of said mining claim as will, if
incorporated into a patent, serve fully to identify the premises, and that such reference is made therein
to natural objects or permanent monuments as will perpetuate and fix the locus thereof.
And I further certify that five hundred dollars' worth of labor has been expended or improve- or for each of ments made upon said mining claim by claimant or its grantors, and that said improvements
consist of 11 shafts & 5/9 interest in incline shaft, No. 1 Wisconsin
lode, Sur. No. 3530, Value \$ 8991.10
•
and that no portion of said labor or improvements has been included in the estimate of expenditures
I further certify that the plat thereof, filed in the U.S. Land Office at Dhoenix,
is correct and in conformity with the foregoing Field Notes.
Frank P. Trott,
United States Surveyor-General for Arizona.

SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR OFFICE OF U. S. SURVEYOR GENERAL

	Phoenix, Arizona,				
	April 22. , 1920.				
I, U. S. Surveyor General for	Arizona,				
	nd hereto attached Field Notes and Return of the Survey of the				
Mining Claim ofB	lack Giant Mines Company				
	, known as the				
NORTH STAR, LITTLE GEM N	O.1, ANNA MC, RED ROSE and BUCK Lodes				
situate inEll	sworth mining district,				
	County, Arizona				
in Sections 7,18,12 all uns,.To	ownship No. 7 N. , Range No. 12, and 13 w. G. S. R. M				
executed byC.	C. Thompson U. S. Mineral				
Surveyor, December 9,-18	, 191 ⁹ , under my instructions dated				
November 12,	, 1919, have been critically examined and the necessary cor-				
rections and explanations made, and the said Field Notes and Return, and the Survey they describe,					
	by of the location certificate filed by the applicant for survey is				
n file in this office and a true copy of sa	id certified copy of said location certificate is included and made				
part of the transcript of the field note	28.				
	France Polivoit				

U.S. Surveyor General for Arizona.