

4-683

S.C.F.

AUG 13 1920

MINERAL SURVEY No. 3637

LOT No.

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

RURAL MINES, Inc.

KNOWN AS THE

WIRE SILVER lode

WALLAPAI Mining District,

MOHAVE County, ARIZONA

Section 18, Township 23 N., Range 17 W.

Surveyed under instructions dated Nov. 18, 1919

by Leon H. Foster U. S. Mineral Surveyor.

Claim located January 1st, 1916

Survey commenced July 20, 1920

Survey completed July 25, 1920

Address of claimant Gustave S. Duschues, Secy., Kingman, Arizona

DATES OF AMENDED LOCATIONS.

June 27th. 1919.

MINERAL SURVEY No. 3637

feet

Wire Silver lode.

Beginning Cor. No. 1.

A redwood post, 4 ins. square, 4 feet long set 15 ins. in the ground, in a mound of earth and stone and scribed W-S-1-3637. A nail in top of post marks the exact corner.

Identical with the location.

Cor. 4, Rural No. 2 lode, Sur. No. 2456 and Cor. 6, Buckeye lode, Sur. No. 1165 bears N. 24° 01' E. 10.18 ft and 38.80 ft. respectively.

A granite boulder, 4 ft. wide, 8 ft. long, 2 ft. above ground, marked X-R-4-2456 bears S. 87° 13' W. 8.77 feet.

The corner of sections 12 and 13, T. 23 N. R. 18 W. G. & S. R. B. & M. bears N. 82° 27' 40" W. 2073.08 ft. The corner of Secs. 7 and 18, T. 23 N., R. 17 W., G. & S. R. B. & M., bears N. 86° 56' 50" W. 2052.48 ft.

Thence S. 68° 02' 40" E.

30.00 Cross gulch running S. 25° W.

925.00 Cross gulch running south.

1498.02 To Cor. No. 2.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 12 ins. in the ground, in a mound of earth and stone, scribed W-S-2-3637.

Identical with the location and with Cor. No. 5 Buckeye lode, Sur. No. 1165.

A granite boulder, 3 ft. wide, 4 ft. long, 1 ft above ground, marked X-BR-W-S-2-3637, bears N. 24° 01' E.

16.50 feet.

Thence S. 24° 01' W.

300.00 To the easterly end center of the location.

A redwood post, 4 ins. square, 4 ft. long, set in the ground, in a mound of earth and stone. The discovery shaft bears N. 68° 02' 40" W. 740 ft. Intersect line 3-4, Buckeye lode, Sur. No. 1165 at S. 71° 55' 30" E. 1448.07 ft. and N. 71° 55' 30" W.

Survey No. 3637, continued

feet

8.73 ft. from cors. No. 3 and 4, respectively.

600.00

To Cor. No. 3.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 15 ins. in the ground, in a mound of earth and stone, scribed W-S-3-3637.

Identical with the location.

Cor. No. 4, Buckeye lode, Sur. No. II65 bears N. 27° 06' E. 161.42 feet.

Thence N. 68° 02' 40" W.

174.00

Cross gulch running south.

1258.00

Cross road running south.

1275.00

Cross transmission line running S. 45° W.

1445.00

Cross gulch running S. 20° W.

1498.02

To Cor. No. 4.

A redwood post, 4 ins. square, 4 ft. long, with a nail at the exact corner, set 12 ins. in the ground, in a mound of earth and stone, scribed W-S-4-3637.

A granite boulder, 3 ft. wide, 4 ft. long, 1 ft above ground, marked X-BR-R2-I, bears N. 57° 26' W. 13.08 feet.

Identical with the location.

Cors No. 2 and 3, Buckeye lode, Sur. No. II65 bear N. 84° 29' E. 69.30 ft. and N. 65° 30' E. 85.72 ft. respectively.

Cor No. I, Rural No. 2 lode, Sur. No. 2456, bears S. 24° 01' W. 7.70 feet.

Thence N. 24° 01' E.

33.93

To Cor. No. I, Buckeye lode, Survey No. II65, from which, Cor. No. 2, said Buckeye lode, brs. S. 66° 12' E. 60.30 ft. and from said Cor. No. 2, Cor. No. 3 Buckeye lode brs. N. 17° 20' E. 30.27 ft.

300.00

To the westerly end center of the location.

390.00

The discovery shaft bears S. 68° 02' 40" E. 758.02 ft. Cross road running west.

600.00

To Cor. No. I, the place of beginning.

Variation all corners. 15° E.

Survey No. 3637, Continued

Lode Line

As near as can be determined from present development, the vein of the Wire Silver lode extends N. 68° 02' 40" W. 758.02 ft. and S. 68° 02' 40" E. 740 ft. from the discovery shaft.

Area

Total area Wire Silver lode ----- 20.621 acres

Area in conflict with Buckeye lode, Survey No. II65 ----- 16.901 acres

Location

This survey is located in Mineral Park basin, in section 18, T. 23 N. R. 17 W. G. & S. R. B. & M. Wallapai Mining District, Mohave County, Arizona.

Expenditure of Five Hundred Dollars.

I certify that the value of the improvements and labor made upon and for the benefit of this lode claim by the claimant Company or its grantors, is not less than five hundred dollars and consists of the following:-

No. 1, The discovery shaft, 4 ft. wide, 6 ft. long, 10 feet deep, on the lode line 740 ft. from E.E.C., Value \$50.00

No. 2, The main working shaft, 5½ ft. wide, 11 ft. long, 170 ft. deep, timbered, two compartment, the south west corner of which bears N. 46° 40' E. 305 ft. from Cor.

No. 4 Course of long side, S. 67° E. Value \$8500.00

No. 3, The new work in drift easterly along the vein

Survey No. 3637. continued

for a distance of 170 ft. the beginning of which bears N. 87° W. 700 ft. from Cor. No. 2.

Value \$1700.00

Other improvements.

~~No. I,~~ The portal of a tunnel extending easterly along vein 650 ft. bears N. 53° E. 410 ft. from Cor. No. 4.

~~No. II,~~ A shaft, 4 ft. by 5 ft. 30 ft. deep, bears N. 58° 15' E. 450 ft. from Cor. No. 4.

~~No. III,~~ A shaft, 4 X 5 Ft. 40 ft. deep, bears N. 63° 30' E. 465 ft. from Cor. No. 4.

~~No. IV.~~ The face of an open cut, 4 ft. wide, 10 ft. high, extending N. 65° W. 25 ft. bears N. 68° 30' E. 500 ft. from Cor. No. 4.

~~No. V.~~ The face of an open cut, 5 ft. wide, 10 ft. high, extending S. 75° W. 30 ft. to its mouth and a tunnel 4 X 6 ft. extending S. 67° E. 40 ft. bears N. 71° 40' E. 525 ft. from Cor. No. 4.

~~No. VI~~ A trench, 3 ft. wide, 2 ft. deep, extending north 125 ft. bears N. 85° E* 550 ft. from Cor. No. 4.

~~No. VII,~~ The face of an open cut, 4 ft. wide, 5 ft. high, extending N. 65° W. 15 ft. bears N. 78° 20' E. 605 ft. from Cor. No. 4.

~~No. VIII,~~ The face of an open cut, 4 ft. wide, 10 ft. high, extending S. 66° W. 15 ft. and a tunnel 4 X 6 ft. extending S. 70° E. 20 ft. bears N. 82° E. 630 ft. from Cor. No. 4.

~~No. IX,~~ The face of an open cut, 4 ft. wide, 10 ft. high, extending south 16 ft. and a tunnel, 4 X 6 ft. extending north, 15 ft. bears S. 87° 30' W. 750 ft. from Cor. No. 2.

~~No. X,~~ A 4 X 6 ft. shaft, depth unknown, bears S. 86° 30' W. 690 ft. from Cor. No. 2.

~~No. XI.~~ A 4 X 6 ft. shaft, depth unknown with a

Survey No. 3637, continued,

tunnel, 4 X 6 ft. extending S. 80° W. 50 ft. bears S. 79° W. 490 ft. from Cor. No. 2.

The southwest corner of a blacksmith shop, 20 X 28 ft. course of long side north, bears N. 31° 15' E. 345 ft. from Cor. No. 4.

The southwest corner of a hoist house, 28 X 40 ft. course of long side north, bears N. 37° E. 366 ft. from Cor. No. 4.

The southwest corner of a framing shed and sawmill 20 X 28 ft. course of long side S. 89° E. bears N. 41° 15' E. 255 ft. from Cor. No. 4.

The southwest corner of a transformer house, 18 X 28 ft. course of long side N. 1° W. bears N. 74° E. 295 ft. from Cor. No. 4.

The southwest corner of a change room, 12 X 26 ft. course of long side N. 1° W. bears N. 24° E. 340 ft. from Cor. No. 4.

Report

The side and end lines and all other lines were run directly on the ground

All of the corners of the Buckeye lode are redwood posts, properly set and marked.

All of the corners of the Rural No. 2 lode, tied to in this survey are granite stones, properly marked and set. The Cor. bet. Secs. 7 and 18 could not be found.

The corner of sections 12 and 13, T. 23 N. R. 18 W. is a 3 inch iron pipe with a brass cap properly marked. The corner of Secs. 7 and 18, T. 23 N., R. 17 W., is a 2 inch iron pipe properly set and marked, and bears S. 1° 58' E. 162.77 ft. from the Cor. of Secs. 12 and 13, T. 23 N., R. 18 W.

Instrument and Meridian

This survey was run with a Berger and Sons Mining transit and with a 100 and 500 ft. steel tape.

The Meridian was determined by direct observation

Survey No. 3637, continued

on the sun.

Adjoining and Conflicting claims.

This claim is joined on the west by the Rural No. 2 lode, Survey No. 2456, on the north by the Susan B., on the east by Sheldon No. 1, and south by Silver Bell lodes, unsurveyed, claimant herein.

Leon H. Foster
U. S. Mineral-Surveyor

Kingman, Arizona.

Report

The side and end lines and all other lines were run directly on the ground. All of the corners of the Buckeye lode are redwood posts, properly set and marked. All of the corners of the Rural No. 2 lode, tied to in this survey are granite stones, properly marked and set. The corner of sections 12 and 13, T. 23 N., R. 15 W. is a 3 inch iron pipe with a brass cap properly marked. This survey was run with a barometer and aneroid barometer and with a 100 and 500 ft. steel tape. The meridian was determined by direct observation.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Leon H. Foster

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

Rural mines, inc.

known as the WIRE SILVER lode

and showing the respective capacities in which they acted.

L. A. Newton, Chainman.

XXXXXXXXXXXXXXXXXXXXXXXXXXXX, Chainman.

XXXXXXXXXXXXXXXXXXXXXXXXXXXX, Axman.

XXXXXXXXXXXXXXXXXXXXXXXXXXXX, Flagman.

FINAL OATHS OF ASSISTANTS.

We, I, L. A. Newton

and XXXXXXXXXXXXXXXXXXXX, do solemnly swear that we assisted _____

Leon H. Foster, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Rural Mines, Inc.

known as the Wire Silver lode

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the United States Surveyor-General for Arizona.

S. M. Newton, Chainman.

_____, Chainman.

_____, Axman.

_____, Flagman.

Subscribed and sworn to by the above-named persons before me this 17th

day of August, 19 20

Mary E. Cannon
Notary Public

My Commission Expires Nov. 20th, 1923.

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Leon H. Foster, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for Arizona, dated Nov. 18 1919, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of Rural Mines, Inc., known as the Wire Silver, situate in Wallapai Mining District, Mohave County, Arizona, in Section 18, Township No. 23 N., Range No. 17 W. G. & S. R. B. & M. and designated as Survey No. 3637, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or its grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Leon H. Foster
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Leon H. Foster
U. S. Mineral Surveyor, before me Mary E. Carrow
Mary E. Carrow this 17th
day of August, 19 20

Mary E. Carrow
Notary Public

My Commission Expires Nov. 20th, 1923.

4-1044



U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

September 29, 1920

I, U. S. Surveyor-General for District of Arizona
do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey
of the mining claim of Rural Mines, Inc.
known as the WIRE SILVER Lode
situate in Wallapai
Mining District, Mohave County, Arizona
in Section 18, Township No. 23 N., Range No. 17 W., and
designated as Survey No. 3637, has been correctly copied from the originals on file in
this office; that said Field Notes furnish such an accurate description of said mining claim as will, if
incorporated into a patent, serve fully to identify the premises, and that such reference is made therein
to natural objects or permanent monuments as will perpetuate and fix the *locus* thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improve-
ments made upon said mining claim by claimant or its grantors, and that said improvements
consist of 2 shafts and 170 ft. of drift, total value \$10,250

and that no portion of said labor or improvements has been included in the estimate of expenditures
upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix,
Arizona, is correct and in conformity with the foregoing Field Notes.

Frank P. Trott,

United States Surveyor-General for Arizona.

4-687

SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR OFFICE OF U. S. SURVEYOR GENERAL

Phoenix, Arizona,

September 29, 19 20

I, U. S. Surveyor General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of Rural Mines, Inc.

known as the WIRE SILVER Lode

situate in Wailapai mining district, Mohave County, Arizona

in Section 18, Township No. 23 N., Range No. 17 W.

designated as Survey No. 3637

executed by Leon H. Foster, U. S. Mineral Surveyor, July 20 - 25, 19 20, under my instructions dated

Nov. 18, 1919, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and made

a part of the transcript of the field notes.

[Handwritten signature]

U. S. Surveyor General for Arizona.

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S. 3637
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Wire Silver lode, Mineral Survey No. 3637, located in section 18, Township 23 North, Range 17 West, Gila and Salt River Meridian, Arizona, is hereby canceled.

This claim has not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Wire Silver lode, M.S. 3637 was canceled June 27, 2012, by memo 9605 (956) M.S. 3637, which is now a part of the original field notes."

June 27, 2012
Date

Stephen K. Hamner
Chief Cadastral Surveyor of Arizona