

MAY 18 1921

1

4-083.

MINERAL SURVEY No. 3702.

LOT No.

ARIZONA Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

J.L. WADE, JOHN F. WADE, and CHARLES SNELL,

KNOWN AS THE

MARTIN No. 2, MARTIN No. 3, MARTIN No. 4, MARTIN No. 5, MARTIN No. 6, MARTIN No. 7, MARTIN No. 8, MARTIN No. 9, MARTIN No. 10, MARTIN No. 11, MARTIN No. 12 and MARTIN No. 13 Lodes,

CRAWFORD Mining District,

APACHE, County, ARIZONA, (Navajo Indian reservation.)

Approx.

Sections 26, 27 and 35, Township 14 N., Range 7 W. Navajo Base & Mer.

Surveyed under instructions dated September, 13th., 1920.

by Allison L. Proeger U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced November, 17th., 1920.

Survey completed January, 31st., 1921.

8-822

Address of Claimant, J.L. Wade, Agent, Farmington New Mexico.,

DATES OF AMENDED LOCATIONS.

See location notices attached.

MINERAL SURVEY NO. 3702

Claims Martin No.	M & B. Desc. Pg.	Improvements Pg.	Loc. Notices <u>Red</u> Pg.
2	2	21	1
" 3	5	21	2
" 4	6	21	3
" 5	12	22	4
" 6	10	21	5
" 7	8	21	6
" 8	17	22	7
" 9	14	22	8
" 10	16	22	9
" 11	1	20	10
" 12	13	22	11
" 13	4	21	12

Feet.

Mineral SURVEY No.3702.

MARTIN No.11 LODE.

Beginning at Cor.No.1,

Identical with Cor.No.1 of the amended location.

A hewn cedar post,4 ft.long,5 ins.square, set 2 ft.in the ground, sur-
rounded by a mound of earth and stone, scribed 1-M.11,-3702, whence,

The face of a cliff, chiseled B.R.X,1-M.11,-3702, bears N.49° 55'E.
58.88 ft.

U.S.M.M.No.1 bears S.45° 08' 46"W.1531.95 ft.

THENCE, N.4° 47'E.

VAR.15° 25'E.

300.00 To west end center,

Identical with the west end center of the amended location.

A sandstone,2 ft.4 ins.long,9 ins.by 10 ins.square, set in a mound of
stone, chiseled E.C.M.11,-3702, whence,

The location monument, Martin No.11 lode, bears S.85° 13'E.300 ft.

600.00 To Cor.No.2,

Identical with Cor.No.2 of the amended location.

A hewn cedar post,3 ft.6 ins.long,5 ins.square, set 18 ins.in the ground
surrounded by a mound of earth and stone, scribed 2-M.11,-3702, whence,

The top of a rock in place, chiseled B.R.X,2-M.11,-3702, bears S.15°
48'W.41.80 ft.

THENCE, S.85° 13'E.

VAR.15° 25'E.

1135.00 Center of draw.Flows N.18° 00'W.

1500.00 To Cor.No.3,

Identical with Cor.No.3 of the amended location.

A hewn pinon post,3 ft.6 ins.long,6 ins.square, set 18 ins.in the ground
surrounded by a mound of earth and stone, scribed 3-M.11,-3702, whence,

The top of a rock in place, chiseled B.R.X,3-M.11,-3702, bears S.1° 45'
W.49.60 ft.

THENCE, S.4° 47'W.

VAR.15° 25'E.

300.00 To east end center,

Identical with the east end center of the amended location.

A hewn cedar post,3 ft.6 ins.long,6 ins.square, set 18 ins.in the
ground, surrounded by a mound of earth and stone, scribed E.C.M.11,-3702.

SURVEY No.3702,(Continued.)

MARTIN No.11 LODE,(Continued.)

600.00 To Cor.No.4,
 Identical with Cor.No.4 of the amended location.
 On line 4-1,Martin No.4 lode,of this survey.
 A hewn cedar post,4 ft.6 ins.long,6 ins.square,set 2 ft.6 ins.in the
 ground,surrounded by a mound of earth and stone,scribed 4-M.11,-3702,
 whence,
 The top of a rock in place,chiseled B.R.X,4-M.3,-1-M.4,-4-M.11,-3702,
 bears N.54° 16'E.45.90 ft.

THENCE,N.85° 13'W.

VAR.15° 25'E.

58.45 To Cor.Nos.1 and 4,Martin No.4 and Martin No.3 lodes,respectively,
 of this survey.
 100.00 Center of draw.Flows N.18° 00'W.
 387.57 To north end center,Martin No.3 lode of this survey.
 716.69 To Cor.Nos.1 and 4,Martin No.3 and Martin No.13 lodes,respectively,
 of this survey.
 1045.81 To north end center,Martin No.13 lode,of this survey.
 1374.93 To Cor.No.1,Martin No.13 lode,of this survey.
 1500.00 To Cor.No.1,the place of beginning.

MARTIN No.2 LODE.

Beginning at Cor.No.1,
 Identical with Cor.No.1 of the amended location.
 A hewn pinon post,3 ft.6 ins.long,4 ins.by 6 ins.square,set 18 ins.in
 the ground,surrounded by a mound of earth and stone,scribed 1-M.2,-
 3702,whence,
 U.S.M.M.No.1,bears N.77° 37'48"W.1515.05 ft.

THENCE,S.2° 30'E.

VAR.15° 25'E.

1500.00 To Cor.No.2,
 Identical with Cor.No.2,of the amended location.
 A hewn pinon post,3 ft.6 ins.long,5 ins.square,set 18 ins.in the
 ground,surrounded by a mound of earth,scribed 2-M.2- 3702,whence,
 A pinon tree,7 ins.in diameter,blazed and scribed B.T.X,2-M.2,-3702,
 bears S.53° 07'W.7.20 ft.

THENCE,S.85° 13'E.

Feet. (near SURVEY No.3702,(Continued.)

(near MARTIN No.2 LODE,(Continued.)

302.44 To south end center,

Identical with the south end center of the amended location.

A hewn pinon post,3 ft.6 ins.long,7 ins.square, set 18 ins.in the ground, scribed E.C.-M.2,-3702.

604.88 To Cor.No.3,

Identical with Cor.No.3 of the amended location.

A hewn pinon post,3 ft.6 ins.long,6 ins.square, set 18 ins.in the ground, surrounded by a mound of earth and stone, scribed 3-M.2,-3702, whence,

A cedar tree,5 ins.in diameter, blazed and scribed B.T.X,3-M.2,-3702, bears S.3° 41'W.20.40 ft.

VAR.15° 25'E.

1500.00 To Cor.No.4,

Identical with Cor.No.4 of the amended location.

On line 2-3, Martin No.13 lode, of this survey,

A hewn pinon post,3 ft.6 ins.long,5 ins.square, set 18 ins.in the ground, surrounded by a mound of earth and stone, scribed 4-M.2,-3702, whence,

The top of a rock in place, chiselled B.R.X,4-M.2,-3702, bears N.6° 29'W.

12.00 ft.

THENCE, N.85° 13'W.

VAR.15° 25'E.

43.47 To south end center, Martin No.13 lode, of this survey.

302.44 To north end center,

Identical with the north end center of the amended location.

A hewn pinon post,3 ft.6 ins.long,4 ins.square, set 18 ins.in the ground, surrounded by a mound of earth and stone, scribed E.C.M.2,-3702, whence,

The location monument, Martin No.2 lode, bears S.2° 30'E.165.55 ft.

372.59 To Cor.No.2, Martin No.13 lode, of this survey.

604.88 To Cor.No.1, the place of beginning.

MARTIN No.13 LODE.

Beginning at Cor.No.1,

Identical with Cor.No.1 of the original location.

On line 4-1, Martin No.11 lode, of this survey.

Feet.	SURVEY No.3702, (Continued.)
	MARTIN No.13 LOBE, (Continued.)
	A sandstone, 3 ft. long, 6 ins. square, set in a mound of earth and stone, chiseled 1-M.13, -3702, whence,
	The top of a rock in place, chiseled B.R.X, 1-M.13, -3702, bears S. 50° 44'E. 18.60 ft.
	U.S.M.M.No.1, bears 5.48° 31' 44"W. ^{1615.81} 1516.74 ft.
	THENCE, S. 19° 30'E.
	VAR. 15° 25'E.
1500.00	To Cor.No.2, Identical with Cor.No.2 of the original location, On line 4-1, Martin No.2 lode, of this survey.
	A hewn pinon post, 3 ft. 6 ins. long, 5 ins. square, set 18 ins. in the ground, Surrounded by a mound of earth and stone, scribed 2-M.13, -3702, whence, The face of a cliff, chiseled B.R.X, 2-M.13, -3702, bears S. 77° 52'E. 45.24 ft.
	THENCE, S. 85° 13'E.
	VAR. 15° 25'E.
70.15	To north end center, Martin No.2 lode, of this survey.
329.12	To south end center, Identical with the south end center of the original location.
	A hewn pinon post, 3 ft. 6 ins. long, 4 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed E.C.-M.13, -3702, whence, The location monument, Martin No.13 lode, bears N. 19° 30'W. 720.00 ft.
372.59	To Cor.No.4, Martin No.2 lode, of this survey.
658.24	To Cor.No.3, Identical with Cor.No.3 of the original location and with Cor.No.2, Martin No.3 lode, of this survey.
	A hewn pinon post, 3 ft. 6 ins. long, 5 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed 2-M.3, -3-M.13, -3702, whence, The top of a rock in place, chiseled B.R.X, 2-M.3, -3-M.13, -3702, bears N. 28° 12'W. 29.61 ft.
	THENCE, N. 19° 30'W.
	VAR. 15° 25'E.
1500.00	To Cor.No.4, Identical with Cor.No.4 of the original location and with Cor.No.1,

Feet.	<p style="text-align: center;">SURVEY No. 3702, (Continued.)</p>
	<p style="text-align: center;">MARTIN No. 13 LODE, (Continued.)</p>
	<p>Martin No. 3 lode, of this survey.</p>
31.82	<p>On line 4-1, Martin No. 11 lode, of this survey.</p>
	<p>A hewn pinon post, 3 ft. 6 ins. long, 5 ins. square, set 18 ins. in the</p>
	<p>ground, surrounded by a mound of earth and stone, scribed 4-M.13, -1-M.</p>
	<p>3, -3702, whence,</p>
	<p>The top of a rock in place, chiseled B.R.X, 4-M.13, -1-M.3, -3702, bears</p>
307.8	<p>S. 30° 44' W. 7.50 ft.</p>
	<p style="text-align: center;">THENCE, N. 85° 13' W.</p>
	<p style="text-align: center;">VAR. 15° 25' E.</p>
329.12	<p>To north end center,</p>
	<p>Identical with the north end center of the original location.</p>
	<p>On line 4-1, Martin No. 11 lode, of this survey.</p>
	<p>A hewn pinon post, 4 ft. long, 6 ins. square, set 20 ins. in the ground, sur-</p>
	<p>rounded by a mound of earth and stone, scribed E.C.-M.13, -3702.</p>
658.24	<p>To Cor. No. 1, the place of beginning.</p>
	<p style="text-align: center;">MARTIN No. 3 LODE.</p>
	<p>Beginning at Cor. No. 1,</p>
	<p>Identical with Cor. No. 1 of the amended location and with Cor. No. 4,</p>
	<p>Martin No. 13 lode, of this survey, heretofore described, whence,</p>
	<p>The top of a rock in place, chiseled B.R.X, 4-M.13, -1-M.3, 3702, bears</p>
	<p>S. 30° 44' W. 7.50 ft.</p>
	<p>U.S.M.M. No. 1 bears, S. 61° 27' 38" W. 2124.78 ft.</p>
	<p style="text-align: center;">THENCE, S. 19° 30' E.</p>
	<p style="text-align: center;">VAR. 15° 25' E.</p>
1500.00	<p>To Cor. No. 2,</p>
	<p>Identical with Cor. No. 2 of the amended location and with Cor. No. 3,</p>
	<p>Martin No. 13 lode, of this survey, heretofore described, whence,</p>
	<p>The top of a rock in place, chiseled B.R.X, 2-M.3, -3-M.13, -3702, bears</p>
	<p>N. 28° 12' W. 29.61 ft.</p>
	<p style="text-align: center;">THENCE, S. 85° 13' E.</p>
	<p style="text-align: center;">VAR. 15° 25' E.</p>
329.12	<p>To south end center,</p>
	<p>Identical with the south end center of the amended location.</p>
	<p>A hewn pinon post, 3 ft. 6 ins. long, 5 ins. square, set 18 ins. in the</p>
	<p>ground, surrounded by a mound of earth and stone, scribed E.C.-M.3, -3702,</p>

Feet.

SURVEY No. 3702 (Continued.)

MARTIN No. 3 LODE, (Continued.)

whence,

The location monument, Martin No. 3 lode, bears N, 19° 30' W. 657.59 ft.

658.24

To Cor. No. 3, identical with Cor. No. 3, of the amended location, and with Cor. No. 2, Martin No. 4 lode, of this survey.

A hewn pinon post, 4 ft. long, 5 ins. square, set 22 ins. in the ground, surrounded by a mound of earth and stone, scribed 2-M.4, -3-M.3, -3702.

No bearings available.

THENCE, N. 19° 30' W.

VAR. 15° 25' E.

1020.00

Center of draw, Flows N. 41° 45' W.

1500.00

To Cor. No. 4, identical with Cor. No. 4 of the amended location and with Cor. No. 1, Martin No. 4 lode, of this survey.

On line 4-1, Martin No. 11 lode, of this survey.

A hewn cedar post, 4 ft. long, 5 ins. square, set 2 ft. in the ground, surrounded by a mound of earth and stone, scribed 4-M.3, -1-M.4, -3702,

whence,

The face of a cliff, chiseled B.R.X, 4-M.3, -1-M.4, -4-M.11, -3702, bears N. 77° 04' E. 98.00 ft.

THENCE, N. 85° 13' W.

VAR. 15° 25' E.

41.55

Center of draw. Flows N. 18° 00' W.

329.12

To north end center, identical with the north end center of the amended location.

On line 4-1, Martin No. 11 lode, of this survey.

A sandstone, 2 ft. 6 ins. long, 5 ins. by 9 ins. square, set in a mound of stone, chiseled E.C.-M.3, -3702.

658.24

To Cor. No. 1, the place of beginning.

MARTIN No. 4 LODE.

Beginning at Cor. No. 1,

identical with Cor. No. 1 of the amended location and with Cor. No. 4, Martin No. 3 lode, of this survey, heretofore described, whence,

The face of a cliff, chiseled B.R.X, 4-M.3, -1-M.4, -4-M.11, -3702, bears N. 77° 04' E. 98.00 ft.

Feet.

(SURVEY No.3702,(Continued.)

MARTIN No.4 LODE,(Continued.)

U.S.M.M.No.1,bears S.69° 09' 35"W.2699,14 ft.

THENCE,S.19° 30'E.

VAR.15° 25'E.

480.00

Center of draw.Flows N.41° 45'W.

1500.00

To Cor.No.2,

Identical with Cor.No.2 of the amended location,and with Cor.No.3,
Martin No.3 lode,of this survey,heretofore described,

No bearings available.

THENCE,S.85° 13'E.

VAR.15° 25'E.

20.00

Center deep canon. Flows N.13° 30'W.

240.38

To south end center,

Identical with the south end center of the amended location.

A sandstone,3 ft,long,5 ins.by 9 ins.square,set in a mound of stone,
chiseled E.C.-M.4,-3702, whence,

The location monument,Martin No.4 lode,bears N.19° 30'W.600.02 ft.

569.50

To Cor.No.3,

Identical with Cor.No.3 of the amended location.

On line 1-2,Martin No.7 lode,of this survey.

A hewn pinon post,4 ft.long,6 ins.square,set 20"ins.in the ground,sur-
rounded by a mound of earth and stone,scribed 3-M.4,-3702,whence,

The top of a rock in place,chiseled B.R.X,3-M.4,-3702,bears S.48° 10'
W.27.80 ft.

THENCE,N.19° 30'W.

VAR.15° 25'E.

757.82

To Cor.No.1,Martin No.7 lode,of this survey.

1500.00

To Cor.No.4,

Identical with Cor.No.4 of the amended location.

A hewn pinon post,3 ft.6 ins.long,6 ins.square,set 18 ins.in the
ground,surrounded by a mound of earth and stone,scribed 4-M.4,-3702,

whence,

The top of a rock in place,chiseled B.R.X,4-M.4,-3702,bears N.25° 37'
E.30.00 ft.

THENCE,N.85° 13'W.

VAR.15° 25'E.

Feet.

SURVEY No.3702,(Continued.)

Martin No.4 Lode,(Continued.)

329.12 To north end center,
 Identical with the north end center of the amended location.
 A sandstone, 3 ft. long, 4 ins. by 12 ins. square, set in a mound of stone,
 chiseled E.C.M.4, -3702,

511.05 To Cor.No.4, Martin No.11 lode, of this survey.

569.50 To Cor.No.1, the place of beginning.

MARTIN No.7 LODE.

Beginning at Cor.No.1,
 Identical with Cor.No.1 of the amended location.

On line 3-4, Martin No.4 lode, of this survey.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the
 ground, surrounded by a mound of earth and stone, scribed 1-M.7, -3702,
 whence,

The top of a rock in place, chiseled B.R.X, 1-M.7, -3702, bears S.6° 30'
 E.11.80 ft.

U.S.M.M.No.1, bears S.86° 20' 43"W.3344.63 ft.

THENCE, S.19° 30'E.

Var.15° 25'E.

757.82 To Cor.No.3, Martin No.4 lode, of this survey.

1075.93 To Cor.No.2,

Identical with Cor.No.2 of the amended location.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set in a mound of earth
 and stone, scribed 2-M.7, -3702, whence,

The top of a rock in place, chiseled B.R.X, 2-M.7, -3702, bears S.13° 27'
 W.10.20 ft.

THENCE, S.0° 22'E.

VAR.15° 25'E.

449.45 To Cor.No.2,

Identical with Cor.No.3 of the amended location and with Cor.No.1,

Martin No.6 lode, of this survey.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 12 ins. in the
 ground, surrounded by a mound of earth and stone, scribed 3-M.7, -1-M.6,
 -3702, whence,

The top of a rock in place, chiseled B.R.X, 3-M.7, -1-M.6, -3702, bears S.
 1° 53'E.12.80 ft.

Feet. (SURVEY No. 3702, (Continued.)

(MARTIN No. 7 LODE, (Continued.)

THENCE, S. 73° 44' E. ... VAR. 15° 25' E.

313.10 To south end center, ... Identical with the south end center of the amended location, and with the north end center, Martin No. 6 lode, of this survey.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed E.C.M. 7, -E.C. M. 6, -3702, whence, ... The location monument, Martin No. 7 lode, bears N. 0° 22' W. 286.89 ft.

626.20 To Cor. No. 4, ... Identical with Cor. No. 4 of the amended location and with Cor. No. 6, Martin No. 6 lode, of this survey.

A hewn pinon post, 3 ft. long, 6 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed 4-M. 7, -6-M. 6, -3702, No bearings available. ... THENCE, N. 0° 22' W. ... VAR. 15° 25' E.

702.35 To Cor. No. 1, Martin No. 8 lode, of this survey.

729.77 To Cor. No. 5, ... Identical with Cor. No. 5 of the amended location.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 2 ft. in the ground, surrounded by a mound of earth and stone, scribed 5-M. 7, -3702, whence, ... A cedar tree, blazed and scribed B.T.X, 5-M. 7, -1-M. 8, -3702, bears N. 77° 39' W. 25.80 ft. ... THENCE, N. 19° 30' W. ... VAR. 15° 25' E.

744.85 To Cor. No. 6, ... Identical with Cor. No. 6 of the amended location.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed 6-M. 7, -3702, No bearings available. ... THENCE, N. 73° 44' W. ... VAR. 15° 25' E.

369.73 To north end center, ... Identical with the north end center of the amended location.

Feet.

(SURVEY No. 3702, (Continued.)

(MARTIN No. 7 LODE, (Continued.)

A hewn pinon post, 3 ft. long, 5 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed E.C.-M.7, -3702.

739.46

To Cor. No. 1, the place of beginning.

Identical with the south end center of MARTIN No. 6 LODE.

Beginning at Cor. No. 1, the north end center.

Identical with Cor. No. 1 of the amended location and with Cor. No. 3,

Martin No. 7 lode, of this survey, heretofore described, whence,

The top of a rock in place, chiseled B.R.X, 3-M.7, -1-M.6, -3702, bears

S. 1° 53' E. 12.80 ft.

U.S.M.M. No. 1, bears N. 71° 19' 36" W. 3905.54 ft.

THENCE, S. 0° 22' E.

VAR. 15° 25' E.

1391.21

To Cor. No. 2, a hewn pinon post, 3 ft. long, 5 ins. square, set 18 ins. in the ground,

Identical with Cor. No. 2 of the amended location.

A hewn pinon post, 4 ft. long, 6 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed 2-M.6, -3702,

No bearings available.

THENCE, S. 16° 16' W.

VAR. 15° 25' E.

110.69

To Cor. No. 3, identical with Cor. No. 3 of the amended location.

Identical with Cor. No. 3 of the amended location and with Cor. No. 1,

Martin No. 5 lode, of this survey.

A hewn pinon post, 4 ft. long, 7 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed 1-M.5, -3-M.6, -3702, whence,

The top of a rock in place, chiseled ^{BRX} 1-M.5, -3-M.6, -3702, bears S. 17°

39' W. 13.70 ft.

THENCE S. 73° 44' E.

VAR. 15° 25' E.

273.86

Intersect line 4-1, Martin No. 12 lode, of this survey, at S. 74° 57' W.

381.74 ft. from Cor. No. 4.

300.00

To south end center,

Identical with the south end center of the amended location, and with the north end center Martin No. 5 lode, of this survey.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set in a mound of earth and stone, scribed E.C.-M.6, -E.C.-M.5, -3702, whence,

Feet.

SURVEY No.3702,(Continued.)

MARTIN No.6 LODE,(Continued.)

The location monument, Martin No.6 lode, bears N.16° 16'E.154.54 ft.

575.00 Center of draw.Flows N.31° 00'E.

600.00 To Cor.No.4, Identical with Cor.No.4 of the amended location and with Cor.No.4, Martin No.5 lode, of this survey.

A hewn pinon post, 3 ft.6 ins.long, 7 ins.square, set 12 ins.in the ground, surrounded by a mound of earth and stone, scribed 4-M.6, -4-M.5, -3702, whence,

The face of a cliff, chiseled B.R.X, 4-M.6, -4-M.5, -3702, bears S.57° 10' W.25.91 ft.

THENCE, N.16° 16'E.

VAR.15° 25'E.

98.00 Center of draw.Flows N.45° 00'E.

198.39 To Cor.No.5, Identical with Cor.No.5 of the amended location and with Cor.No.4, Martin No.12 lode, of this survey.

A hewn pinon post, 4 ft.long, 6 ins.square, set 18 ins.in the ground, surrounded by a mound of earth and stone, scribed 5-M.6, -4-M.12, -3702, whence,

The face of a cliff, chiseled B.R.X, 2-M.10, -1-M.9, -5-M.6, -4-M.12, -3702, bears S.74° 12'E.78.00 ft.

THENCE, N.0° 22'W.

VAR.15° 25'E.

88.68 To Cor.Nos.1 and 2, Martin No.9 and Martin No.10 lodes, respectively, of this survey.

388.68 To west end center, Martin No.10 lode, of this survey.

688.68 To Cor.No.1, Martin No.10 lode, of this survey.

1299.71 To Cor.No.6, Identical with Cor.No.6, of the amended location, and with Cor.No.4, Martin No.7 lode, of this survey, heretofore described,

No bearings, available.

THENCE, N.73° 44'W.

VAR.15° 25'E.

313.10 To north end center, Identical with the north end center of the amended location, and with

Feet.

(From SURVEY, No. 3702, (Continued.)

(From MARTIN, No. 6 LODE, (Continued.)

the south end center, Martin No. 7 lode, of this survey, heretofore described.

626.20 To Cor. No. 1, the place of beginning.

MARTIN No. 5 LODE.

Beginning at Cor. No. 1,

Identical with Cor. No. 1 of the amended location, and with Cor. No. 3,

Martin No. 6 lode, of this survey, heretofore described, whence,

The top of a rock in place, chiseled B.R.X. 1-M, 5, -3-M, 6, -3702, bears

S. 17° 39' W, 13.70 ft.

U.S.M.M. No. 1, bears N. 53° 14' 05" W. 4591.05 ft.

THENCE, S. 16° 16' W.

VAR. 15° 25' E.

1500.00 To Cor. No. 2,

Identical with Cor. No. 2 of the amended location.

A hewn cedar post, 4 ft. long, 6 ins. square, set 2 ft. in the ground, surrounded by a mound of earth and stone, scribed 2-M, 5, -3702, whence,

The top of a rock in place, chiseled B.R.X. 2-M, 5, -3702, bears S. 13° 30' W.

36.20 ft.

THENCE, S. 73° 44' E.

VAR. 15° 25' E.

300.00 To south end center,

Identical with the south end center of the amended location.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set in a mound of stone, scribed, E.C.-M, 5, -3702, whence,

The location monument, Martin No. 5 lode, bears N. 16° 16' E. 100.00 ft.

320.00 Center of draw. Flows, N. 16° 00' E.

600.00 To Cor. No. 3,

Identical with Cor. No. 3 of the amended location, and with Cor. No. 2,

Martin No. 12, lode, of this survey.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed 3-M, 5, -2-M, 12, -3702.

No bearings available.

THENCE N. 16° 16' E.

VAR. 15° 25' E.

Feet. SURVEY No. 3702, (Continued.)

MARTIN No. 5 LODE, (Continued.)

1500.00 To Cor. No. 4, Identical with Cor. No. 4 of the amended location and with Cor. No. 4, Martin No. 6 lode of this survey, heretofore described, whence,

The face of a cliff, chiseled B.R.X, 4-M.6, -4-M.5, -3702, bears S. 57° 10' W. 25.91 ft.

THENCE, N. 73° 44' W. 1. A new pinon post, 3 ft. long, 6 ins. square, set 12 ins. in the ground, surrounded by a mound of earth and stone, scribed 1-M.12, -3702, whence,

25.00 Center of draw. Flows N. 31° 00' E.

300.00 To north end center, Identical with the north end center of the amended location and with the south end center Martin No. 5 lode, of this survey, heretofore described.

326.14 Intersect line 4-1, Martin No. 12 lode of this survey, at N. 74° 57' E. 120.80 ft. from Cor. No. 1.

600.00 To Cor. No. 1, the place of beginning.

MARTIN No. 12 LODE. Beginning at Cor. No. 1, Identical with Cor. No. 1, of the original location.

A new pinon post, 4 ft. long, 6 ins. square, set 12 ins. in the ground, surrounded by a mound of earth and stone, scribed 1-M.12, -3702, whence, The top of a rock in place, chiseled B.R.X, 1-M.12, 3702, bears N. 16° 25' E. 17.60 ft.

Cor. Nos. 1 and 3, Martin No. 5 and Martin No. 6 lodes, respectively, of this survey, bears N. 53° 32' W. 181.84 ft.

U.S.M.M. No. 1, bears N. 53° 14' 45" W. 4772.91 ft. THENCE, S. 0° 22' E. VAR. 15° 25' E.

640.00 Center of draw. Flows N. 32° 00' E.

1500.00 To Cor. No. 2, Identical with Cor. No. 2 of the original location, and with Cor. No. 3, Martin No. 5 lode, of this survey, heretofore described.

No bearings available. THENCE, N. 74° 57' E. VAR. 15° 25' E.

236.87 - To south end center,

Feet.

SURVEY No.3702,(Continued.)

MARTIN No.12 LODE,(Continued.)

Identical with the south end center of the original location,

A hewn pinon post,4 ft.long,7 ins.square, set 20 ins.in the ground, surrounded by a mound of earth and stone, scribed E.C.-M.12,-3702.

502.54

To Cor.No.3,

Identical with Cor.No.3 of the original location:

A hewn pinon post,3 ft.6 ins.long,6 ins,square, set 18 ins.in the ground,surrounded by a mound of earth and stone, scribed 3-M.12,-3702, whence,

The face of a cliff, chiseled B.R.X,3-M.12,-3702, bears N.80° 15'W.

21.00 ft.

THENCE, N.0° 22'W.

VAR.15° 25'E.

88.88

To Cor.No.2, Martin No.9 lode, of this survey.

1434.00

Center of draw. Flows N.45° 00'E.

1500.00

To Cor.No.4,

Identical with Cor.No.4 of the original location and with Cor.No.5

Martin No.6 lode, of this survey, heretofore described, whence,

The face of a cliff, chiseled B.R.X,2-M.10,-1-M.9,-5-M.6,-4-M.12,-3702

bears S.74° 12'E.78.00 ft.

THENCE, S.74° 57'W.

VAR.15° 25'E.

265.87

To north end center,

Identical with the north end center of the original location.

A hewn pinon post,4 ft.long,7 ins.square, set in a mound of stone, scribed, E.C.-M.12,-3702, whence,

The location monument, Martin No.12 lode, bears S.0° 22'E.823.39 ft.

381.74

Intersect line 4-1 and 3-4, Martin No.5 and Martin No.6 lodes, respectively, of this survey, at N.73° 44'W.326.14 ft. from Cor.Nos.4.

502.54

To Cor.No.1, the place of beginning.

MARTIN No.9 LODE.

Beginning at Cor.No.1,

Identical with Cor.No.1 of the amended location and with Cor.No.2,

Martin No.10 lode, of this survey.

A hewn pinon post,3 ft.6 ins.long,6 ins.square, set 12 ins.in the ground, surrounded by a mound of earth and stone, scribed 2-M.10,-1-M.9,-3702,

Feet.

SURVEY No. 3702, (Continued.)

MARTIN No. 9 LODE, (Continued.)

whence,

The face of a cliff, chiseled B.R.X, 2-M.10, 1-M.9, -5-M.6, -4-M.12, -3702,
bears S.34° 58'E. 131.67 ft.

U.S.M.M.No.1, bears N.58° 32' 05"W. 5051.65 ft.

THENCE, S.0° 22'E.

VAR.15° 25'E.

88.68 To Cor. Nos. 4 and 5, Martin No. 12 and Martin No. 6 lodes, respectively, of
this survey.

155.00 Center of draw. Flows N.45° 00'E.

1500.00 To Cor. No. 2,

Identical with Cor. No. 2 of the amended location.

On line 3-4, Martin No. 12 lode, of this survey.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the
ground, surrounded by a mound of earth and stone, scribed, 2-M.9, -3702,
whence,

The face of a cliff, chiseled B.R.X, 2-M.9, -3702, bears S.74° 23'W. 6 ft.

THENCE, East.

VAR.15° 25'E.

170.00 Center of draw. Flows N.41° 00'W.

248.18 To south end center,

Identical with the south end center of the amended location.

A hewn pinon post, 4 ft. long, 6 ins. square, set 18 ins. in the ground, sur-
rounded by a mound of earth and stone, scribed E.C.-M.9, -3702, whence,

The location monument, Martin No. 9 lode, bears N.0° 22'W. 589.53 ft.

548.18 To Cor. No. 3,

Identical with Cor. No. 3 of the amended location.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the ground
surrounded by a mound of earth and stone, scribed 3-M.9, -3702.

No bearings available.

THENCE, N.0° 22'W.

VAR.15° 25'E.

1500.00 To Cor. No. 4,

Identical with Cor. No. 4 of the amended location.

On line 2-3, Martin No. 10 lode, of this survey.

A hewn pinon post, 3 ft. long, 6 ins. square, set 9 ins. in the ground, sur-

Feet.

SURVEY No. 3702, (Continued.)

MARTIN No. 9 lode, (Continued.)

rounded by a mound of earth and stone, scribed 4-M.9, -3702, whence,

The top of a rock in place, chiseled B.R.X, 4-M.9, -3702, bears N. 8° 31' E. 25.80 ft.

THENCE WEST.

VAR. 15° 25' E.

300.00 To north end center,

Identical with the north end center of the amended location.

A hewn pinon post, 4 ft. long, 5 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed E.C.-M.9, -3702.

385.00 Center of draw. Flows N. 31° 45' W.

478.00 Center of draw. Flows north.

548.18 To Cor. No. 1, the place of beginning.

MARTIN No. 10 LODE.

Beginning at Cor. No. 1,

Identical with Cor. No. 1 of the amended location.

On line 5-6, Martin No. 6 lode, of this survey.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone, scribed 1-M.10, -3702, whence,

A cedar tree 12 ins. in diameter, blazed and scribed B.T.X, 1-M.10, -3702, bears S. 16° 37' W. 66.64 ft.

U.S.M.M. No. 1, bears N. 64° 40' 45" W. 4762.55 ft.

THENCE, S. 0° 22' E.

VAR. 15° 25' E.

300.00 To west end center,

Identical with the west end center of the amended location.

A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the ground, surrounded by a mound of earth and stone scribed E.C.-M.10, -3702, whence,

The location monument, Martin No. 10 lode, bears east 881.75 ft.

600.00 To Cor. No. 2,

Identical with Cor. No. 2 of the amended location, and with Cor. No. 1, Martin No. 9 lode of this survey, heretofore described, whence,

The face of a cliff, chiseled B.R.X, 2-M.10, -1-M.9, -5-M.6, -4-M.12, -3702, bears S. 34° 58' E. 131.67 ft.

Feet.	SURVEY No.3702,(Continued.)
	MARTIN No.10 LODE,(Continued.)
	THENCE,EAST.
	VAR.15° 25'E.
70.18	Center of draw.Flows north.
163.18	Center of draw.Flows N.31° 45'W.
248.18	To north end center Martin No.9 lode,of this survey.
548.18	To Cor.No.4,Martin No.9 lode,of this survey.
1500.00	To Cor.No.3, Identical with Cor.No.3 of the amended location. A hewn pinon post,4 ft.long,6ins.square, set 2 ft,in the ground,sur- rounded by a mound of earth and stone,scribed 3-M.10,3702,whence, The face of a cliff,chiseled B.R.X,3-M.10,-3702,bears S.10° 42'E.74.35 ft. THENCE,N.0° 22'W. VAR.15° 25'E.
295.00	Center of draw.Flows N.45° 00'W.
300.00	To east end center,
	Identical with the east end center of the amended location. A hewn pinon post,3 ft.6 ins.long,6 ins.square, set 18 ins.in the ground,surrounded by a mound of earth and stone,scribed E.C.-M.10,-3702.
600.00	To Cor.No.4, Identical with Cor.No.4 of the amended location. A hewn pinon post,4 ft.long,6 ins.square, set 18 ins.in the ground,sur- rounded by a mound of earth and stone,scribed 4-M.10,-3702,whence, The top of a rock in place,chiseled B.R.X,4-M.10,-3702,bears N.32° 15' W.10.90 ft. THENCE,WEST. VAR.15° 25'E.
98.65	To Cor.No.3,Martin No.8 lode,of this survey.
353.89	Center of draw.Flows N.40° 00'W.
441.27	To south end center,Martin No.8 lode,of this survey.
783.89	To Cor.No.2,Martin No.8 lode,of this survey.
1325.00	Center of draw.Flows N.24° 00'E.
1500.00	To Cor.No.1,the place of beginning.
	MARTIN No.8 LODE. Beginning at Cor.No.1,

14

Feet.

SURVEY No.3702,(Continued.)

MARTIN No.8 LODE,(CONTINUED.)

Identical with Cor.No.1 of the amended location.

On line 4-5 MARTIN No.7 lode,of this survey.

A hewn cedar post,4 ft.long,5 ins.square, set 2 ft.in the ground,sur-
rounded by a mound of earth and stone,scribed 1-M.8,-3702,whence,

A cedar tree 12 ins.in diameter,blazed and scribed,B.T.X,5-M.7,-1-M.8,
-3702,bears N.37° 11'W.41.10 ft.

U.S.M.M.No.1 bears N.80° 26' 29"W.4357.08 ft.

THENCE,S.28° 53'E.

VAR.15° 25'E.

780,00 Center,of draw.Flows N.5° 00'E.

1499,95 To Cor.No.2,

Identical with Cor.No.2 of the amended location,

On line 4-1,Martin No.10 lode of this survey.

A hewn pinon post,3 ft.6 ins.long,6 ins.square, set 18 ins.in the
ground,surrounded by a mound of earth and stone,scribed 2-M.8,-3702,
whence,

The top of a rock in place,chiseled B.R.X,2-M.8,-3702,bears S.51° 50'
W.23.80 ft.

THENCE,EAST.

VAR.15° 25'E.

342.62 To south end center,

Identical with the south end center of the amended location.

A hewn pinon post,3 ft.long,6 ins.square, set 18 ins.in the ground,sur-
rounded by a mound of earth and stone,scribed E.C.-M.8,-3702,whence,

The location monument,Martin No,8 lode,bears N.28° 53'W.803.30 ft.

430.00 Center of draw.Flows N.40° 00'W.

685.24 To Cor.No.3,

Identical with Cor.No.3 of the amended location,

On line 4-1,Martin No.10 lode,of this survey.

A hewn pinon post,4 ft.long,6 ins.square, set 18 ins.in the ground,sur-
rounded by a mound of earth and stone,scribed 3-M.8,-3702,whence,

The top of a rock in place,chiseled B.R.X,3-M.8,-3702,bears east 6.97'
ft.

THENCE,N.28° 53'W.

VAR.15° 25'E.

Feet. SURVEY No. 3702, (Continued.)
 MARTIN No. 8 LODE, (Continued.)

1499.95 To Cor.No.4,
 Identical with Cor.No.4 of the amended location.
 A hewn pinon post, 3 ft. 3 ins. long, 6 ins. square, set 12 ins. in the
 ground, surrounded by a mound of earth and stone, scribed 4-M.8, -3702,
 whence,
 The top of a rock in place, chiseled B.R.X, 4-M.8, -3702, bears S.40° 02'
 W.10.00 ft.

THENCE, WEST.
 VAR. 15° 25' E.

342.62 To north end center,
 Identical with the north end center, of the amended location.
 A hewn pinon post, 3 ft. 6 ins. long, 6 ins. square, set 18 ins. in the
 ground, surrounded by a mound of earth and stone, scribed E.C.-M.8, -3702.

345.00 Center of draw. Flows north.

685.24 To Cor.No.1, the place of beginning.

LODE LINES.

As near as can be determined from present development the veins of
 the several locations embraced in this survey extend as follows from
 their respective discovery points:

Martin No. 11 lode, 300 ft. running N. 85° 13' W. and 1200 ft. running S. 85°
 13' E.

Martin No. 2 lode, 165.55 ft. running N. 2° 30' W. and 1334.45 ft. running
 S. 2° 30' E.

Martin No. 13 lode, 720 ft. running S. 19° 30' E. and 780 ft. running N. 19°
 30' W.

Martin No. 3 lode, 842.41 ft. running N. 19° 30' W. and 657.59 ft. running
 S. 19° 30' E.

Martin No. 4 lode, 899.98 ft. running N. 19° 30' W. and 600.02 ft. running
 S. 19° 30' E.

Martin No. 7 lode, 302.72 ft. running N. 0° 22' W, thence 910.39 ft. running N. 19°
 30' W. and 286.89 ft. running S. 0° 22' E.

Martin No. 6 lode, 1345.46 ft. running N. 0° 22' W. and 154.54 ft. running
 S. 16° 16' W.

Martin No. 5 lode, 1400 ft. running N. 16° 16' E. and 100 ft. running S. 16°
 16' W.

Martin No.12 lode,823.39 ft.running N.0° 22'W. and 676.61 ft.running S.0° 22'E.

Martin No.9 lode,910.47 ft.running N.0°22'W. and 589.53 ft.running S.0° 22'E.

Martin No.10 lode,881.75 ft.running west and 618.25 ft.running east.

Martin No.8 lode,696.65 ft.running N.28° 53'W.and 803.30 ft.running S.28° 53'E.

AREAS.

Total area Martin No.11 lode, 20.661 acres. ✓

Total area Martin No.2 lode, 20.661 acres. ✓

Total area Martin No.13 lode, 20.661 acres. ✓

Total area Martin No.3 lode, 20.661 acres. ✓

Total area Martin No.4 lode, 17.876 acres. ✓

Total area Martin No.7 lode, 20.661 acres. ✓

Total area Martin No.6 lode, 20.661 acres. ✓

Total area Martin No.5 lode, 20.661 acres. ✓

Total area Martin No.12 lode, 16.740 acres. ✓

Area in conflict with, Martin No.5 lode,
of this survey, 7.627 acres. ✓

Area in conflict with, Martin No.6 lode,
of this survey, 0.743 acres. ✓

Total area Martin No.9 lode, 18.876 acres. ✓

Total area Martin No.10 lode, 20.661 acres. ✓

Total area Martin No.8 lode, 20.660 acres. ✓

LOCATION.

As near as can be determined from the present condition of the Public Survey, this survey is located in sections 26, 27 and 35, township 14 N. & Meridian range 7 W., Navajo Base Line, in the Carriso mountains, The approximate latitude is 36° 55' N. and the approximate longitude is 109° 12' W.

IMPROVEMENTS.

I certify, that the labor and improvements made upon or for the benefit of each of the locations, embraced in said mining claim, by the claimants or their grantors is as follows:

Martin No.11 Lode.

The discovery cut, the center of which being the discovery point, is on the lode line 300 ft. from the center of line 1-2, 4 ft wide, 2 ft. deep, running S.15° E. 10 ft. to the face and running N.15° W. 15 ft. to mouth.

No.2;- An open cut,the mouth of which bears from Cor.No.3,S.63° 40'W.
558 ft.6 ft.wide,2 ft.deep,running east 30 ft.to the face.

Martin No.2.

No.1:- The discovery cut,the mouth of which being the discovery point
,is on the lode line 165.55 ft.from the center of line 4-1,4 ft.wide,
3 ft.deep,running S.2° 00'E.15 ft.to the face.

Martin No.13.

No.1:- The discovery cut,the face of which being the discovery point,
is on the lode line 720 ft.from the center of line 2-3,4 ft.wide,1
foot deep,running N,19° 00'W.10 ft.to the mouth.

Martin No.3.

No.1:- The discovery cut,the face of which being the discovery point,
is on the lode line 657.59 ft.from the center of line 2-3, 4 ft.wide,
3 ft.deep,running N.18° 00'W.10 ft.to the mouth.

Martin No.4.

No.1:-The discovery cut,the face of which being the discovery point,
is on the lode line,899.98 ft.from a point on line 4-1,240.38 ft.
from Cor.No.1,6 ft.wide,2 ft.6 ins.deep,running S.30° 00'W.8 ft.to
the mouth.

Martin No.7.

No.1:- The discovery cut,the face of which being the discovery point,
is on the lode line 286.89 ft.from the center of line 3-4,6 ft.wide,
2 ft.deep,running S.10° 00'E.9 ft.to the mouth.

No.2:-An open cut,the mouth of which is on the lode line,540 ft.from
the center of line 3-4,5 ft.wide,1 foot deep,running north 15 ft.to

the face.

No.3:- An open cut, the mouth of which is on the lode line,720 ft.
from the center of line 6-1,4 ft.wide,18 ins.deep,running S.19° 00'E.
12 ft.to the face.

No.4:- An open cut,the mouth of which bears from Cor.No.1,S.50° 30'E.
525 ft.,5 ft.wide,3 ft.deep,running south 15 ft.to the face.

Martin No.6.

No.1:- The discovery cut,the face of which being the discovery point,
is on the lode line 154.54 ft.from the center of line 3-4,5 ft.wide,
2 ft.deep,running S.16° 00'W.10 ft.to the mouth.

No.2:- An open cut,the mouth of which is on the lode line 1165 ft.from
the center of line 6-1,3 ft.wide,1 foot deep,running south 10 ft.to

the face.

Martin No.5.

No.1:- The discovery cut, the mouth of which being the discovery point, is on the lode line 100 ft. from the center of line 2-3, 3 ft. wide, 18 ins. deep, running S.20° 00' W. 10 ft. to the face.

Martin No.12.

No.1:- The discovery cut, the face of which being the discovery point, is on the lode line 676.61 ft. from a point on line 2-3, 236.87 ft. from Cor.No.2, 4 ft. wide, 1 foot deep, running north 15 ft. to the mouth.

Martin No.9.

No.1:- The discovery cut, the center of which being the discovery point is on the lode line 589.53 ft. from a point on line 2-3, 248.18 ft. from Cor.No.2, 5 ft. wide, 2 ft. deep, running south 10 ft. and north 10 ft. from the discovery point.

Martin No.10.

No.1:- The discovery cut, the mouth of which being the discovery point, is on the lode line 618.25 ft. from the center of line 3-4, 3 ft. wide, 18 ins. deep, running west 8 ft. to the face.

Martin No.8.

No.1:- The discovery tunnel, the mouth of which being the discovery point, is on the lode line 803.30 ft. from the center of line 2-3, 3 ft. wide, 4 ft. high, running N.45° 00' E. 15 ft. to the face.

OTHER IMPROVEMENTS.

- No.1:- An indian hogan, the center of which bears from Cor.No.4, Martin Nell lode, N.59° 45' W. 249 ft.
- No.2:- An indian hogan, the center of which bears from Cor.No.4, Martin No.3 lode, N.87° 45' W. 164 ft.

INSTRUMENT.

The instrument used in making this survey was a C.L. Berger & Sons Mining Transit.

The courses were deflected from the true meridian as determined by direct solar observations.

The distances were measured with a five hundred foot steel tape.

REPORT.

The lode line of each of the locations of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode line.

U.S.M.M.No.1 is a sandstone,8 ins.by 20 ins.square,projecting 1 foot above the ground,chiseled with an X on top and U.S.M.M.No.1,FRESTON on the east side.

Diligent search and extensive inquiry was made for corners of the Public Survey within a radius of several miles of said claim,but there are apparently none to be found.As these corners are purported to have been established some fifty years ago,it is very probable that if any remain standing they have been buried by the shifting sands of this region.

ADJOINING CLAIMS.

None.

Note:- The discovery cut of each of the locations embraced in this survey shows ore or a vein in place. The Martin No.6 and Martin No.7 lodes,which have angles in their lode lines are located following the ledge or vein which outcrops and is readily traced upon the ground. The slight discrepancy between these notes and the amended location certificates of the Martin No,13 and Martin No.3 lodes with respect to their end lines and the ties to U.S.M.M.No.1 are due to errors in said certificates.

U.S.M. No. 1 is a carbonate, 5' thick by 30' in diameter, projecting 1 foot above the ground, enclosed with an X on top and U.S.M. No. 1, REGION on the west side.

Extensive search and extensive inquiry was made for corners of the Public Survey within a radius of several miles of said claim, but there are apparently none to be found. As these corners are supposed to have been established some fifty years ago, it is very probable that if any remain standing they have been cut off by the shifting sands of this region.

ADJOINING CLAIMS.

None.

Note: - The discovery of each of the locations embraced in this survey above are on a vein in place. The Martin No. 6 and Martin No. 7

claims, which have been in their beds and located following the strike of vein which occurs and is readily traced upon the ground. The slight discrepancy between these notes and the amended location certificates of the Martin No. 6 and Martin No. 7 claims with respect to their end lines and the ties to U.S.M. No. 1 are due to errors in field certificates.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Allison L. Kroeger,

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

J.L. Wade, John F. Wade and Charles Snell,

known as the Martin No. 2, Martin No. 3, Martin No. 4, Martin No. 5, Martin No. 6, Martin No. 7, Martin No. 8, Martin No. 9, Martin No. 10, Martin No. 11 and Martin No. 12 and Martin No. 13 lodes.

and showing the respective capacities in which they acted.

John Clarke, _____, *Chainman.*

_____, *Chainman.*

_____, *Arman.*

_____, *Flagman.*

FINAL OATHS OF ASSISTANTS.

~~XX~~ I, John Clarke, _____

and _____, do solemnly swear that ~~XX~~ I assisted _____

Allison L. Kroeger _____, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of J.L. Wade, John F. Wade and Charles Snell, _____

known as the Martin No. 2, Martin No. 3, Martin No. 4, Martin No. 5, Martin No. 6, Martin No. 7, Martin No. 8, Martin No. 9, Martin No. 10, Martin No. 11, Martin No. 12, and Martin No. 13 lodes, _____

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of ~~my~~ my knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the United States Surveyor-General for Arizona, _____

John Clarke, _____, *Chainman.*

_____, *Chainman.*

_____, *Arman.*

_____, *Flagman.*

Subscribed and sworn to by the above-named persons before me this 18th

day of February _____, 19 21

Robert S. Clements

_____, *Notary Public.*

My Commission Expires Sept. 26, 1921

FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Allison L. Kroeger, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the United States Surveyor General for ARIZONA, dated September, 13th. 1920, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Surveyor General, faithfully and correctly executed the survey of the Mining Claim of J. L. Wade, John F. Wade, and Charles Snell, Martin No. 2, Martin No. 3, Martin No. 4, Martin No. 5, Martin No. 6, Martin No. 7, Martin No. 8, Martin No. 9, Martin No. 10, Martin No. 11, Martin No. 12, & Martin No. 13, lodes situate in The Crawford, Mining District, Apache County, Arizona, in Section 26, 27 and 35, Township No. 14 N., Range No. 7 W. Navajo Base Line & Meridian, and designated as Survey No. 3702, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Surveyor General with said instructions, and that all the corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim or for the benefit of their grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Allison L. Kroeger
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Allison L. Kroeger
U. S. Mineral Surveyor, before me Robert S. Clements, a notary public
in and for La Plata County, Colo. this 18th
day of February, 1921

Robert S. Clements

Notary Public,
La Plata County, Colorado.

My Commission Expires Sept. 26, 1921

U. S. SURVEYOR GENERAL'S FINAL CERTIFICATE ON
FIELD NOTES.

DEPARTMENT OF THE INTERIOR,
OFFICE OF U. S. SURVEYOR GENERAL,

Phoenix, Arizona,

July 29, 1921.

I, U. S. Surveyor General for DISTRICT OF ARIZONA,
do hereby certify that the foregoing transcript of the Field Notes, return and approval
of the Survey of the mining claim of J. L. WADE, JOHN F. WADE and CHARLES
SNELL; known as the MARTIN No. 2, MARTIN No. 3, MARTIN No. 4, MARTIN
No. 5, MARTIN No. 6, MARTIN No. 7, MARTIN No. 8, MARTIN No. 9,
MARTIN No. 10, MARTIN No. 11, MARTIN No. 12, and MARTIN No. 13 Lodes,

, situate in CRAWFORD

Mining District, APACHE County,
Navajo Indian Reservation,
Arizona, Approx., in Sections 26, 27 & 35, Township No. 14 N.

Range No. 7 W., Navajo Base & Meridian, and designated as Survey
No. 3702, has been correctly copied from the originals on
file in this office; that said Field Notes furnish such an accurate description of said
mining claim as will, if incorporated into a patent, serve fully to identify the premises,
and that such reference is made therein to natural objects or permanent monuments as
will perpetuate and fix the locus thereof.

~~And I further certify that five hundred dollars' worth of labor has been expended
or improvements made upon said mining claim by claimants or their grantors, and
that said improvements consist of~~

~~and that no portion of said labor or improvements has been included in the estimate of
expenditures upon any other claim.~~

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix,
Arizona is correct and in conformity with the foregoing Field Notes.

Frank P. Trott,

United States Surveyor General for Arizona.

SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES
AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR
OFFICE OF U. S. SURVEYOR GENERAL

Phoenix, Arizona,

July 29, 1921

I, U. S. Surveyor General for DISTRICT OF ARIZONA,


do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of J. L. WADE, JOHN F. WADE, and CHARLES SNELL, known as the MARTIN no. 2, MARTIN No. 3, MARTIN No. 4, MARTIN No. 5, MARTIN No. 6, MARTIN No. 7, MARTIN No. 8, MARTIN No. 9, MARTIN No. 10, MARTIN No. 11, MARTIN No. 12, and MARTIN No. 13 Lodes,

situate in CRAWFORD mining district,
APACHE County, ARIZONA (Navajo Indian Reservation)

in Sections 26, 27 and 35, Township No. 14 N., Range No. 7 W., Navajo Base & Meridianⁿ, designated as Survey No. 5702

executed by Allison L. Kroeger, U. S. Mineral Surveyor, November 17th, 1920 - January 31st, 1921, under my instructions dated September 13th, 1920, have been critically examined and the necessary cor-

rections and explanations made, and the said Field Notes and Return, and the Survey they describe, are hereby approved. The certified copy of the location certificate filed by the applicant for survey is on file in this office and a true copy of said certified copy of said location certificate is included and made a part of the transcript of the field notes.



U. S. Surveyor General for Arizona

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S. 3702
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Martin No.2, Martin No.3, Martin No.4, Martin No.5, Martin No.6, Martin No.7, Martin No.8, Martin No.9, Martin No.10, Martin No.11, Martin No.12, and Martin No.13 lodes, Mineral Survey No. 3702, located in approx. sections 26, 27 and 35, Township 14 North, Range 7 West, (canceled), Navajo Base and Meridian, Arizona, and sections 5, 6, 7 and 8, Townships 40 North, Range 29 East (unsurveyed), Gila and Salt River Meridian, Arizona, are hereby canceled.

These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Martin No.2, Martin No.3, Martin No.4, Martin No.5, Martin No.6, Martin No.7, Martin No.8, Martin No.9, Martin No.10, Martin No.11, Martin No.12, and Martin No.13 lodes M.S. 3702, were canceled April 7, 2010, by memo 9605 (956) M.S. 3702, which is now a part of the original field notes."

April 7, 2010
Date

Stephen H. Hansen
Chief Cadastral Surveyor of Arizona