

JAN 20 1923

1

MINERAL SURVEY No. 3875

ARIZONA

Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

A. H. SHOUP

KNOWN AS THE

SEE BIRD, MONTE CRISTO, MONTE CARLO, CUPRITE, ANACONDA AND NEVADA lodes

GLOBE

Mining District,

GILA

County, ARIZONA

Sections 14 and 15, Township 1 N., Range 15 E., G. & S. R. M.

Surveyed under instructions dated December 27, 1922.

by Edwin T. Stewart

U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced January 1, 1923.

Survey completed January 14, 1923.

Address of claimant's Attorney, Charles L. Rawlins,
Box 98, Globe, Arizona.

DATES OF AMENDED LOCATIONS.

All December 22, 1922.

Feet.	MINERAL SURVEY NO. 3875.
	SEE BIRD Lode.
	Beginning at Cor. No. 1, identical with N.W. Cor. of the location.
	On line 3-4, Monte Cristo lode, this survey.
	A quartzite stone, 7 x 9 x 25 ins., chiseled cross at the exact corner and 1-SB-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence,
	The corner common to sections 10, 11, 14 and 15, T. 1 N., R. 15 E., G. & S.R.M., bears N.12°-53'-30"E. 562.35 ft.
	Cor. No. 2, Cuprite lode, this survey, bears S.09°-55'E. 293.15 ft.
	No other bearings available.
	Thence S.57°-04'E.
	Along line 4-3, Monte Cristo lode, this survey.
58.52	Intersect line 1-2, Cuprite lode, this survey, N.00°-18'W. 256.95 ft. from Cor. No. 2.
1358.25	To Cor. No. 3 of said Monte Cristo lode, and intersect line 4-1, Monte Carlo lode, this survey, N.32°-56'E. 95.0 ft. from Cor. No. 4.
1374.00	Intersect the north boundary of the S.W. ¹ / ₄ of the N.W. ¹ / ₄ of Sec. 14 (Robert Stead Homestead) N.89°-53'E. 1029.0 ft. from the N.W. Cor. and S.89°-53'W. 315.4 ft. from the N.E. Cor.
1497.60	To Cor. No. 2, identical with N.E. Cor. of the location. A quartzite stone, 6 x 7 x 24 ins., chiseled cross at the exact corner and 2-SB-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence The N.E. Cor. of the S.W. ¹ / ₄ of the N.W. ¹ / ₄ of Sec. 14 (Robert Stead Homestead) bears N.72°-14'E. 222.3 ft. Cor. No. 4, Monte Carlo lode, this survey, bears S.88°-38'W. 168.65 ft.
	A dacite stone, 2 x 4 x 8 ft., chiseled cross B.R.3875 on the north face bears S.63°-32'E. 26.5 ft.
	No other bearings available

Thence S. $32^{\circ}-56'W$.

148.20 Intersect line 3-4, Monte Carlo lode, this survey, S. $36^{\circ}-10'E$.
149.15 ft. from Cor. No. 4.

299.90 To S.E.E.C. monument of the location, from which the
discovery cut bears N. $57^{\circ}-04'W$. 594.0 ft.

A monument of stone, 3 ft. base, 3 ft. high.

599.90 To Cor. No. 3, identical with S.E. Cor. of the location.

A cross on dacite in place, about which is chiseled
3-SB-3875, with 4 x 4 post in monument of stone alongside.
No bearings available.

Thence N. $57^{\circ}-04'W$.

1045.80 To Cor. No. 2, Nevada lode, this survey, and intersect
the north boundary of the S.E. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15
(Robert Stead Homestead) S. $89^{\circ}-57'W$. 71.3 ft. from the
N.E. Cor., which is identical with the N.W. Cor. of the
S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of Sec. 14, and is an angle corner of
the north boundary of the Robert Stead Homestead.

1497.60 To Cor. No. 4, identical with S.W. Cor. of the location.
A quartzite stone, 6 x 10 x 24 ins., chiseled cross at the
exact corner and 4-SB-3875 on the side facing the claim,
set 12 ins. in the ground, with mound of stone alongside,
whence

A dacite stone, showing 1 x 4.5 x 4.5 ft. out of the ground,
chiseled cross B.R. 3875 on top, bears N. $32^{\circ}-56'E$. 3.67 ft.

Cor. No. 1, Nevada lode, this survey, bears N. $60^{\circ}-19'-30''E$.
433.6 ft.

No other bearings available.

Thence N. $32^{\circ}-56'E$.

234.20 Intersect lines 4-1 and 2-3, respectively, of Nevada and
Cuprite lodes, both of this survey, S. $85^{\circ}-50'W$. 250.0 ft.
from Cors. 1 and 2, from which corner, Cor. No. 2 of said
Nevada lode bears S. $00^{\circ}-18'E$. 460.2 ft.

300.00 To N.W.E.C. monument of the location.

A 4 x 4 pine post in monument of stone, with nail at the
exact point.

599.90 To Cor. No. 1, the place of beginning.

MONTE CRISTO Lode.

Beginning at Cor. No. 1, identical with N.W. Cor. of the location.

A quartzite stone, 7 x 7 x 24 ins., chiseled cross at the exact corner and 1-MC-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence

The corner common to sections 10, 11, 14 and 15, T. 1 N., R. 15 E., G. & S.R.M., bears N-71°-05'W. 55.0 ft.

A quartzite stone, 10 x 12 x 24 ins., out of the ground, chiseled cross B.R. 3875, bears S.41°-11'E. 10.55 ft.

No other bearings available.

Thence S.57°-04'E.

470.00 Bed of Irene Gulch, draining westerly.

1497.60 To Cor. No. 2, identical with N.E. Cor. of the location and Cor. No. 1, Monte Carlo lode, this survey.

On line 2-3, Baltic lode, Sur. 3758.

A quartzite stone, 7 x 8 x 24 ins., chiseled cross at the exact corner and 2-M C-3875 on the side facing this claim, set 12 ins. in the ground, with mound of stone alongside.

No bearings available.

Thence S.32°-56'W.

Along line 1-4 of said Monte Carlo lode.

300.00 To S.E.E.C. monument of the location, from which the discovery cut bears N.57°-04'W. 1006.6 ft.

A monument of stone, 3½ ft. base, 3 ft. high.

316.60 To N.W.E.C. of said Monte Carlo lode.

541.60 To Cor. No. 3, identical with S.E. Cor. of the location.

On line 1-2, See Bird lode, this survey, N.57°-04'W.

139.35 ft. from Cor. No. 2.

A quartzite stone, 4 x 8 x 24 ins., chiseled cross at the exact corner and 3-M C-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside.

No bearings available.

Thence N.57°-04'W.

Along line 2-1 of said See Bird Lode.

- 1299.73 Intersect line 1-2, Cuprite lode, this survey, S.00°-18'E. 110.55 ft. from Cor. No. 1.
- 1358.25 To Cor. No.1 of said See Bird lode.
- 1482.58 Intersect lines 4-1 and 2-3, respectively, of Cuprite and Anaconda lodes, this survey, S.85°-50'W. 153.30 ft. from Cors. 1 and 2.
- 1497.60 To Cor. No. 4, identical with S.W. Cor. of the location.
A quartzite stone, 4 x 6 x 24 ins., chiseled cross at the exact corner and 4-M C-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside.
Cor. No. 2, Anaconda lode, this survey, bears N.88°-58'E. 165.50 ft.
No other bearings available.
Thence N.32°-56'E.
- 241.60 To N.W.E.C. monument of the location. In the bed of Irene Gulch, draining westerly.
A monument of stone, 3 ft. base, 3 ft. high.
- 302.00 Intersect line 1-2, Anaconda lode, this survey, N.00°-18'W. 250.50 ft. from Cor. No. 2.
- 541.60 To Cor. No.1, the place of beginning.
MONTE CARLO Lode.
Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cor. No. 2, Monte Cristo lode, this survey.
On line 2-3, Baltic lode, Sur. 3758.
A quartzite stone, previously described, to which I add 1-MC on the side facing this claim.
The corner common to sections 10, 11, 14 and 15, T. 1 N., R. 15 E., G. & S.R.M., bears N.57°-33'-30"W. 1551.0 ft.
Cor. No.4, Nellie M. lode, Sur. 3758, bears S.04°-03'W. 288.8 ft.
Cors. 3 and 4, respectively, of Nellie M and Acre lodes, of Sur. 3758, bears S.23°-16'-20"E. 835.7 ft.
No other bearings available.
Thence S.36°-10'E.
Along line 3-2 of said Baltic lode.
- 220.50 To Cor. No.2 of said Baltic lode and intersect line 4-1,

- Nellie M lode, Sur. 3758, N.53°-50'E. 186.5 ft. from Cor. No.4, from which corner, Cor. No. 3 of said Nellie M lode bears S.36°-10'E. 594.1 ft.
- 814.60 Intersect lines 2-3 and 4-1, respectively, of Nellie M and Acre lodes of Sur. 3758, N.53°-50'E. 186.5 ft. from Cors. 3 and 4.
- 1391.90 Intersect line 2-3, Acre lode, Sur. 3758, N.53°-50'E. 186.5 ft. from Cor. No. 3, from which corner, Cor. No. 4 of said Acre lode bears N.36°-10'W. 577.3 ft.
- 1498.80 To Cor. No. 2, identical with S.E.Cor. of the location. A $\frac{1}{2}$ inch drill hole in dacite in place, about which is chiseled 2-M C-3875, with mound of stone alongside, whence Cor. No. 3, Acre lode, Sur. 3758, bears S.83°-39'W. 215.00 ft.
- No other bearings available.
- Thence S.32°-56'W.
- 316.60 To S.E.E.C. monument of the location, from which the discovery shaft bears N.36°-10'W. 1451.8 ft.
A monument of stone, 4 ft. base, 3 ft. high.
- 636.60 To Cor. No. 3, identical with S.W.Cor. of the location.
A quartzite stone, 8 x 8 x 24 ins., chiseled cross at the exact corner and 3-M C-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence
A dacite stone 5 x 6 x 12 ft., chiseled cross B.R.3875 on the southeast face, bears S.36°-15'W. 51.2 ft.
- No other bearings available.
- Thence N.36°-10'W.
- 857.60 Intersect the east boundary of the S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of Sec. 14 (Robert Stead Homestead) S.00°-11'W. 589.45 ft. from the N.E.Cor.
- 1349.65 Intersect line 2-3, See Bird lode, this survey, S.32°-56'W. 148.20 ft. from Cor. No. 2.
- 1498.80 To Cor. No. 4, identical with N.W.Cor. of the location.
A quartzite stone, 7 x 7 x 25 ins., chiseled cross at the

exact corner and 4-M C-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence

Cor. No. 2, See Bird lode, this survey, bears N.88°-38'E. 168.65 ft.

The N.E. Cor. of the S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of Sec. 14 (Robert Stead Homestead) bears N.79°-18'E. 387.0 ft.

A dacite stone showing 1 $\frac{1}{2}$ x 4 x 4 ft. out of the ground, chiseled cross B.R.-3875, bears S.06°-50'W. 25.5 ft.

No other bearings available.

Thence N.32°-56'E.

84.75 Intersect the north boundary of the S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of Sec. 14 (Robert Stead Homestead) S.89°-53'W. 334.2 ft. from the N.E. Cor., and N.89°53'E. 1010.2 ft. from the N.W. Cor.

95.00 To Cor. No. 3, Monte Cristo lode, this survey, and intersect line 1-2, See Bird lode, this survey, N.57°-04'W. 139.35 ft. from Cor. No. 2.

Along line 3-2 of said Monte Cristo lode.

320.00 To N.W.E.C. monument of the location.

A monument of stone, 4 ft. base, 3 ft. high.

336.60 To S.E.E.C. of said Monte Cristo lode.

636.60 To Cor. No. 1, the place of beginning.

CUPRITE Lode.

Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cor. No. 2, Anaconda lode, this survey.

A quartzite stone, 5 x 6 x 24 ins., chiseled cross at the exact corner and 1-C-3875 on the side facing this claim, set 12 ins. in the ground, with mound of stone alongside; whence

The corner common to sections 10, 11, 14 and 15, T. 1 N., R. 15 E., G. & S.R.M., bears N.09°-18'-30"E. 475.65 ft.

Cor. No. 4, Monte Cristo lode, this survey, bears S.88°-58'^{W.} 165.5 ft.

No other bearings available.

Thence S.00°-18'E.

110.55 Intersect lines 3-4 and 1-2, respectively, of Monte

Cristo and See Bird lodes, this survey, S.57°-04'E., 197.87 ft. from Cor. No.4 of said Monte Cristo lode and S.57°-04'E. 58.52 ft. from Cor. No.1 of said See Bird lode.

300.00 To E.E.C. monument of the location, from which the discovery cut bears S.85°-50'W. 309.0 ft.

367.50 To Cor. No. 2, identical with S.E. Cor. of the location and Cor. No. 1, Nevada lode, this survey.

A quartzite stone, 6 x 10 x 24 ins., chiseled cross at the exact corner and 2-C-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence

Cor. No. 1, See Bird lode, this survey, bears N.09°-55'W. 293.15 ft.

No other bearings available.

Thence S.85°-50'W.

Along line 1-4 of said ~~Caprite~~^{Nevada} lode.

250.00 Intersect line 4-1, See Bird lode, this survey, S.32°-56'W. 365.7 ft. from Cor. No. 1

1140.50 Center of Railroad, course northwest and southeast.

1278.60 To Cor. No. 3, identical with S.W. Cor. of the location and Cor. No. 4 of said Nevada lode.

On the east boundary of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (James S. Russell Homestead)

A dacite stone, 12 x 10 x 26 ins., chiseled cross at the exact corner and 3-C-3875 on the side facing this claim, set 12 ins. in the ground, with mound of stone alongside, whence

A sycamore tree, 19 ins. in diameter, scribed cross B.T. 3875, bears N.38°-31'W. 82.2 ft.

A sycamore tree, 9 ins. in diameter, scribed cross B.T. 3875, bears N.88°-01'E. 77.8 ft.

No other bearings available.

Thence N.00°-18'W.

Along the east boundary of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (James S. Russell Homestead)

- 67.50 To W.E.C. monument of the location.
A monument of stone, 3 ft. base, 3 ft. high.
- 173.10 Center of Railroad, course northwest and southeast.
- 367.50 To Cor. No. 4, identical with N.W. Cor. of the location, and Cor. No. 3, Anaconda lode, this survey.
On the east boundary of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (James S. Russell Homestead)
A quartzite stone, 8 x 9 x 25 ins., chiseled cross at the exact corner and 4-C-3875 on the side facing this claim, set 12 ins. in the ground, with mound of stone alongside, whence
A dacite stone, 8 x 24 x 36 ins. out of the ground, chiseled cross B.R.-3875 on top, bears S. 62°-00' E. 4.05 ft.
The S.E. Cor. of Sun Flower No. 1 lode, unsurveyed, bears S. 81°-49'-20" E. 694.6 ft.
No other bearings available.
Whence N. 85°-50' E.
Along line 3-2 of said Anaconda lode.
- 480.90 Intersect the southwest end line of the Sun Flower No. 1 lode, unsurveyed, N. 57°-15' W. 247.2 ft. from the S.E. Cor.
- 789.90 Intersect the southeast side line of the Sun Flower No. 1 lode, unsurveyed, N. 32°-42' E. 185.6 ft. from the S.E. Cor.
- 1125.30 Intersect line 3-4, Monte Cristo lode, this survey, S. 57°-04' E. 15.02 ft. from Cor. No. 4.
- 1278.60 To Cor. No. 1, the place of beginning.
ANACONDA Lode.
Beginning at Cor. No. 1, identical with N.E. Cor. of the location.
On the section line between sections 10 and ~~11~~¹⁵, T. 1 N., R. 15 E.
A quartzite stone, 6 x 8 x 24 ins., chiseled cross at the exact corner and 1-A-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence
The corner common to sections 10, 11, 14 and 15, T. 1 N.,

- R. 15 E., G. & S.R.M., bears S.89°-47'E. 79.4 ft.
- A quartzite stone showing 3 x 3.5 x 4 ft. out of the ground chiseled cross B.R.3875, bears S.89°-04'W. 9.1 ft.
- No other bearings available.
- Thence S.00°-18'E.
- 219.20 Intersect line 4-1, Monte Cristo lode, this survey, N.32°-56'E. 302.0 ft. from Cor. No. 4.
- 280.00 Bed of Irene Gulch, draining westerly
- 300.00 To E.E.C. monument of the location, from which the discovery shaft bears N.89°-47'W. 1211.8 ft.
- A monument of stone 3 ft. base, 3 ft. high.
- 469.70 To Cor. No. 2, identical with S.E. Cor. of the location and Cor. No. 1, Cuprite lode, this survey.
- A quartzite stone, previously described, to which I add 2-A for this claim.
- Cor. No. 4, Monte Cristo lode, this survey, bears S.88°-58'W. 165.5 ft.
- Thence S.85°-50'W.
- Along line 1-4 of said Cuprite lode.
- 153.30 Intersect line 3-4, Monte Cristo lode, this survey, S.57°-04'E. 15.02 ft. from Cor. No. 4.
- 488.70 Intersect the southeast side line of the Sun Flower No.1 lode, unsurveyed, N.32°-42'E. 185.6 ft. from the S.E. Cor.
- 797.70 Intersect the southwest end line of the Sun Flower No.1 lode, unsurveyed, S. 57°-15'W. ^{E. 351.7} ~~247.2~~ ft. from the S. ^{W.} ~~E.~~ Cor.
- 1278.60 To Cor. No. 3, identical with S.W. Cor. of the location and Cor. No. 4 of said Cuprite lode.
- On the east boundary of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (James S. Russell Homestead)
- A quartzite stone, previously described, chiseled 3-A on the side facing this claim.
- Thence N.00°-18'W.
- Along the east boundary of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (James S. Russell Homestead)
- 227.50 To W.E.C. monument of the location.
- A monument of stone, 2.5 ft. base, 3 ft. high.

350.50 Bed of Irene Gulch, draining westerly.
 567.50 To Cor. No. 4, identical with N.W. Cor. of the location, the N.E. and S.E. Cors., respectively, of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 and the S.W. $\frac{1}{4}$ of the S.E. $\frac{1}{4}$ of Sec. 10, the same being an angle corner of the east boundary of the James S. Russell Homestead.

On the section line between sections 10 and 15, T. 1 N., R. 15 E.

A quartzite stone, 7 x 9 x 25 ins., chiseled cross at the exact corner and 4-A-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence,

The S.W. Cor. of the Sun Flower No. 1 lode, unsurveyed, bears S.28°-37'E. 389.9 ft.

No other bearings available.

Thence S.89°-47'E.

Along the section line between sections 10 and 15, T. 1 N., R. 15 E.

405.50 Intersect the northwest side line of the Sun Flower No. 1 lode, unsurveyed, N.32°-42'E. 404.9 ft. from the S.W. Cor.
 1115.50 Intersect the southeast side line of the Sun Flower No. 1 lode, unsurveyed, N.32°-42'E. 786.7 ft. from the S.E. Cor.
 1275.80 To Cor. No. 1, the place of beginning.

NEVADA Lode.

Beginning at Cor. No. 1, identical with N.E. Cor. of the location and Cor. No. 2, Cuprite lode, this survey.

A quartzite stone, previously described, to which I add 1-N on the side facing this claim.

Cor. No. 4, See Bird lode, this survey, bears S.60°-19'-30" W. 433.60 ft.

The corner common to sections 10, 11, 14 and 15, T. 1 N., R. 15 E., G. & S.R.M., bears N.05°-07'-20"E. 840.25 ft.

Thence S.00°-18'E.

300.00 To E.E.C. monument of the location, from which the discovery shaft bears S.85°-50'W. 470.4 ft.

- A monument of stone, 3 ft. base, 3 ft. high.
- 460.20 To Cor. No. 2, identical with S.E. Cor. of the location. On the north boundary of the S.E. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (Robert Stead Homestead) S.89°-57'W. 71.3 ft. from the N.E. Cor., and on line 3-4, See Bird lode, this survey, S.57°-04'E. 451.8 ft. from Cor. No. 4.
- A limestone, 6 x 8 x 25 ins., chiseled cross at the exact corner and 2-N-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone alongside, whence,
- A cross on limestone in place, about which is chiseled B.R. 3875, bears N.89°-57'E. 5.15 ft.
- No other bearings available.
- Thence S.89°-57'W.
- Along the north boundary of the S.E. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (Robert Stead Homestead)
- 819.00 Center of Railroad, course northwest and southeast.
- 940.00 Bed of Pinal Creek, draining northwesterly.
- 1275.50 To Cor. No. 3, identical with S.W. Cor. of the location, the N.W. Cor. of the S.E. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (Robert Stead Homestead) and the S.E. Cor. of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (James S. Russell Homestead)
- A quartzite stone, 6 x 10 x 25 ins., chiseled cross at the exact corner and 3-N-3875 on the side facing the claim, set 12 ins. in the ground, with mound of stone ~~along~~ alongside.
- No bearings available.
- Thence N.00°-18'W.
- Along the east boundary of the N.W. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of Sec. 15 (James S. Russell Homestead)
- 68.30 To W.E.C. monument of the location.
- A monument of stone 2.5 ft. base, 3 ft. high.
- 312.00 Bed of Pinal Creek, draining northwesterly.
- 368.30 To Cor. No. 4, identical with N.W. Cor. of the location and Cor. No. 3, Cuprite lode, this survey.

On the east boundary of the N.W. 1/4 of the N.E. 1/4 of Sec. 15 (James S. Russell Homestead)

A dacite stone, previously described, to which I add 4-N on the side facing this claim.

Thence N.85°-50'E.

Along line 3-2 of said Cuprite lode.

- 138.10 Center of Railroad, course northwesterly and southeasterly.
- 1028.60 Intersect line 4-1, See Bird lode, this survey, N.32°-56'E. 234.2 ft. from Cor. No. 4.
- 1278.60 To Cor. No.1, the place of beginning.

Mean magnetic variation at all corners, 14°-30'E.

.....

LODE LINES.

As near as can be determined from present developments, the veins of the several locations embraced in this survey extend as follows from their respective discovery points:

See Bird lode, N.57°-04'W. 903.6 ft., and S.57°-04'E. 594.0 ft.

Monte Cristo lode, N.57°-04'W. 491.0 ft. and S.57°-04'E. 1006.6 ft.

Monte Carlo lode, N.36°-10'W. 47.0 ft. and S.36°-10'E. 1451.8 ft.

Cuprite lode, N.85°-50'E. 309.0 ft., and S.85°-50'W. 969.6 ft.

Anaconda lode, N.89°-47'W. 64.0 ft., and S.89°-47'E. 1211.8 ft.

Nevada lode, N.85°-50'E. 470.4 ft., and S.85°-50'W. 808.2 ft.

.....

AREAS.

Acres.

Total area See Bird lode,	20.625
Area in conflict with:	
S.E. 1/4 of the N.E. 1/4 of Sec. 15	
and S.W. 1/4 of the N.W. 1/4 of Sec. 14 (Robert Stead Homestead).....	8.052
S.E. 1/4 of the N.E. 1/4 of Sec. 15	
and S.W. 1/4 of the N.W. 1/4 of Sec. 14 (Robert Stead Homestead) exclusive of the common conflict, 0.387 acre, with the Monte Carlo lode, this survey.....	7.665

Total area Monte Cristo lode, 18.620

Total area Monte Carlo lode,	Acres.
Area in conflict with:	20.463'
S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of Sec. 14 (Robert Stead Homestead).....	2.844'
S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of Sec. 14 (Robert Stead Homestead) ex- clusive of the common conflict, 0.387 acres, with the See Bird lode, this survey.....	2.457'
See Bird lode, this survey.....	0.389'
See Bird lode, this survey, ex- clusive of the common conflict, 0.387 acre, with the S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of Sec. 14 (Robert Stead Homestead).....	0.002'
Nellie M lode, Sur. 3758.....	2.544'
Acre lode, Sur. 3758.....	2.472'

Total area Cuprite lode,	10.763'
Area in conflict with:	
Monte Cristo lode, this survey,....	0.194'
See Bird lode, this survey.....	0.981'
Sun Flower No.1 lode, unsurveyed...	0.527'

Total area Anaconda lode,	15.188'
Area in conflict with:	
Monte Cristo lode, this survey,....	0.492'
Sun Flower No. 1 lode, unsurveyed..	7.665'

Total area Nevada lode	12.131'
Area in conflict with:	
See Bird lode, this survey.....	2.532'

LOCATION.

This survey is located in sections 14 and 15, T. 1 N., R. 15 E., G. & S.R.M., Globe Mining District, Gila County, Arizona.

ADJOINING AND CONFLICTING CLAIMS.

An unknown claim, owner unknown; the Sun Flower No. 1 and Sun Flower No. 2 lodes, unsurveyed, owned by John Wallace, et al.; and the Four Hundred lode, unsurveyed, owned by The Dough Boy Copper Company, adjoin and conflict on the north. The Baltic, Nellie M. and Acre lodes of Sur. 3758, owned by The Dough Boy Copper Company, adjoin and conflict on the east. The Pittsburg lode, unsurveyed, owned by Frank Gill; an unknown claim, unsurveyed, owner unknown; and the Homestead of Robert Stead, adjoin and conflict on the south. And, The Homestead of James S. Russell adjoins on the west.

DISCOVERY AND IMPROVEMENTS.

I certify that the value of the labor and improvements made upon or for the benefit of, each of the claims in this survey, by the claimant or his grantors, is not less than five hundred dollars, and that said improvements consist of:-

See Bird.

No. 1, the discovery, cut, 6 x 6 x 17 ft., the center of the toe of which is on the lode line 594.0 ft. from the S.E.E.C., and which extends thence S.70°W. 11.0 ft.; thence N. 70°W. 6.0 ft. to face. Value, \$30.00

No. 2, a vertical shaft, partially timbered, 5 x 3.5 ft. in the clear, 110 ft. deep, the N.E.Cor. of which bears S.87°-11'W. 184.0 ft. from a point on the lode line 310.2 ft. from the S.E.E.C. Value, \$3000.00.

No. 3, 104 ft. of cut and tunnel, 4 x 6 ft., the center of the toe of which bears S.62°-43'E. 160.0 ft. from a point on the lode line 594.0 ft. from the S.E.E.C., and which extends thence S.50°E. 70 ft.; thence S.63°E. 34.0 ft. to face. Value, \$1000.00.

No. 4, 55 ft. of cut and tunnel, 4 x 6 ft., the center of the portal of which bears N.55°-18'^W. 249.0 ft. from a point on the lode line 310.2 ft. from the S.E.E.C., and which extends thence N.55°W. 45.0 ft. to face, and S.55°E. 10.0 ft. to toe. Value, \$500.00.

No. 5, 170 ft. of cut and tunnel, 4 x 6 ft., the center of the toe of which bears N.68°-39'W. 245.0 ft. from the last above described point, and which extends thence N.18°W. 14.0 ft.; thence N.41°W. 121.0 ft. to face. And, from a point S.41°E. 49.0 ft. from face, N.62°E. 35.0 ft. to face. Value, \$2000.00.

No. 6, cut, 10 x 12 x 15 ft., the center of the toe of which bears N.55°-18'W. 279.0 ft. from the last above described point, and which extends thence N.35°W. to face. Value, \$75.00

1/6th of improvement No. 2 on the Cuprite lode which is credited to this claim. Value, \$700.00

Monte Cristo.

No. 1, the discovery, cut, 4 x 10 x 15 ft., the center of the toe of which is on the lode line 491.0 ft. from the N.W.E.C., and which extends thence S.60°E. to face. Value, \$35.00

No. 2, 55 ft. of cut and tunnel, 4 x 7 ft., the center of the toe of which bears S.12°-10'W. 31.3 ft. from a point on the lode line 479.0 ft. from the N.W.E.C., and which extends thence S.08°E. 17.0 ft.; thence S.50°W. 38.0 ft. to face. Value, \$500.00.

1/6th of improvement No. 2 on the Cuprite lode which is credited to this claim. Value, \$700.00.

Monte Carlo.

No. 1, the discovery, shaft, 4 x 6 x 8 ft., the center of which is on the lode line 47.0 ft. from the N.W.E.C. Value, \$35.00.

1/6th of improvement No. 2 on the Cuprite lode which is credited to this claim. Value, \$700.00.

Cuprite.

No. 1, the discovery, cut, 6 x 12 x 33 ft., the S.E. Cor. of the face of which is on the lode line 309.0 ft. from the E.E.C., and which extends thence S.65°W. to toe. Value, \$150.00.

No. 2, a vertical shaft, timbered, 3.5 x 5.5 ft. in the clear, 100 ft. deep, the S.E. Cor. of which bears S.83°-14'W. 175.0 ft. from a point on the lode line 202.7 ft. from the E.E.C., and 153 feet of crosscutting, 4 x 6.5 ft., from the bottom of shaft, which extends from the south side of shaft in a general S.10°W. direction 97.0 ft. to face. And, from a point 46 ft. from face, S.20°E. 43.0 ft. to face. Also, from the north side of shaft, north 13.0 ft. to face. Value of shaft, \$2400.00. Value of crosscutting, \$1800.00. Total value of improvement, \$4200.00.

work
 This/has been performed by the owners of the claims as a common improvement for the development and mining of all the claims of the survey. At the present time the bottom of the shaft is below the surface of all the claims, and it is proposed to continue sinking to greater depth and extend drifts and crosscuts from lower levels toward and under each of the claims of the survey in order to more completely develop and mine them. The plan of developing and mining the claims of the survey from this improvement being a feasible and advantageous one, consistent with good mining practise, the value of the improvement is distributed equally to the six claims of the survey, \$700.00 being credited to each.

Anaconda.

No.1, the discovery, shaft 4 x 6 x 8 ft., the center of which is on the lode line 64.0 ft. from the ~~N.W.E.C.~~ Value, \$30.00.

1/6th of improvement No. 2 on the Cuprite lode which is credited to this claim. Value, \$700.00.

Nevada.

No. 1, the discovery shaft (caved) 5 x 7 x 5 ft., the center of which is on the lode line 470.4 ft. from the E.E.C. Value, \$30.00.

1/6th of improvement No.2 on the Cuprite lode which is credited to this claim. Value, \$700.00.

.....

OTHER IMPROVEMENTS.

A shaft, 4 x 6 x 18 ft., the S.E. Cor. of which bears N.76°-18'W. 157.0 ft. from a point on the lode line of the Cuprite lode, 202.7 ft. from the E.E.C.

A cut, 6 x 12 x 39 ft., the center of the toe of which bears S.86°-37'W. 395.6 ft. from the E.E.C. of the Anaconda lode, and which extends thence S.06°W. to face.

A caved shaft 7 x 8 x 36 ft., the center of which bears N.11°-20'W. 275.0 ft. from a point on the lode line of the Anaconda lode 453.5 ft. from the E.E.C.

A caved cut, 5 x 8 x 40 ft., the center of the toe of which bears N.09°-13'W. 279.0 ft. from the last described point, and which extends thence N.32°E. to face.

None of the above-described improvements are credited to the claims of the survey on account of not having been made by the claimant or his grantors.

.....

INSTRUMENT AND DETERMINATION OF MERIDIAN.

This survey was made with a $6\frac{1}{4}$ inch Berger transit. The distances were measured with a 660 ft. steel tape. The courses were deflected from the true meridian as determined by direct solar observations.

.....

REPORT.

In order to determine the boundaries of the Robert Stead and James S. Russell homesteads which the claims of this survey conflict with or adjoin, it was necessary to partially subdivide sections 14 and 15, T.1 N., R. 15 E., G. & S.R.M. All the corners of these sections required for this subdivision I found in place except the quarter corner between sections 15 and 14 and the quarter corner between sections 16 and 15. Careful search was made for these two corners, and not being found, I established points for them midway between the section corners controlling their reestablished positions, the notes of their original setting showing them to have been set midway between these corners. Beginning at the quarter corner between sections 10 and 15, I ran S.89°-47'E. 2710.4 ft. to the section corner common to sections 10, 11, 14 and 15; thence S.00°-04'W. 2593.8 ft. to the reestablished position of the quarter corner between sections 14 and 15; thence S.00°-04'W. 2593.8 ft. to the corner common to sections 14, 15, 22 and 23; thence N.89°-55'W. 2644.6 ft. to the quarter corner between sections 15 and 22. From this traverse, I compute the bearing of the north and south quarter line of section 15 to be N.00°-

39'-30" W. Then, from the corner common to sections 15, 16, 21 and 22, I ran N.00°-05'E. 5265.0 ft. to the corner common to sections 9, 10, 15 and 16, and set a point for the quarter corner between sections 15 and 16 mid way on this line, 2632.5 ft. from each section corner. I then determined the bearing of the east and west quarter line of section 15 by running from the point set for the quarter corner between sections 14 and 15, S.89°-41'W. to the point set for the quarter corner between sections 15 and 16. From the lines now run, I calculate the boundaries of the N.E. $\frac{1}{4}$ of section 15 to be, commencing at the corner common to sections 10, 11, 14 and 15, S.00°-04'W. 2593.8 ft. to the point set for the quarter corner between sections 14 and 15; thence S.89°-41'W. 2677.3 ft. to the center of section 15; thence N.00°-39'-30"W. 2619.0 ft. to the quarter corner between sections 10 and 15; thence S.89°-47'E. 2710.4 ft. to the place of beginning. I then determined the boundaries of the N.E. $\frac{1}{4}$ of the N.E. $\frac{1}{4}$ of section 15 to be, commencing at the corner common to sections 10, 11, 14 and 15, S.00°-04'W. 1296.9 ft.; thence S.89°-57'W. 1346.8 ft.; thence N.00°-18'W. 1303.3 ft.; thence S.89°-47'E. 1355.2 ft. to the place of beginning, the south and west boundaries of this subdivision being, respectively, the north and east boundaries of those portions of the Robert Stead and James S. Russell homesteads in section 15, and which lines coincide with lines of this survey. I then ran from the corner common to sections 10, 11, 14 and 15 N.89°-45'E. 2694.0 ft. to the quarter corner between sections 11 and 14; and, from the corner common to sections 14, 15, 22 and 23, S.89°-49'E. 2673.2 ft. to the quarter corner between sections 14 and 23. From this data and the line previously run between sections 14 and 15, I calculate the bearing of the north and south quarter line of section 14 to be N.00°-17'-40"E. I then found the bearing of the east and west quarter

line of section 14 by running from the point set for the quarter corner between sections 14 and 15, S.89°-59'E. to the quarter corner between sections 13 and 14. By calculation, I then determine the boundaries of the N.W. $\frac{1}{4}$ of section 14 to be, commencing at the quarter corner between sections 11 and 14, S.00°-17'-40"W. 2606.4 ft. to the center of section 14; thence N.89°-59'W. 2683.6 ft. to the point set for the quarter corner between sections 14 and 15; thence N.00°-04'E. 2593.8 ft. to the corner common to sections 10, 11, 14 and 15; thence N.89°-45'E. 2694.0 ft. to the place of beginning. (I then determine the boundaries of the S.W. $\frac{1}{4}$ of the N.W. $\frac{1}{4}$ of section 14 to be, commencing at the point set for the quarter corner between sections 14 and 15, N.00°-04'E. 1296.9 ft.; thence N.89°-53'E. 1544.4 ft.; thence S.00°-11'W. 1300.0 ft.; thence N.89°-59'W. 1341.8 ft. to the place of beginning,) this subdivision being the portion of the Robert Stead Homestead in section 14 that is in conflict with the claims of this survey.

Corners of the public survey, T. 1 N., R. 15 E.:

The corner common to sections 10, 11, 14 and 15 is a diabase stone showing 4 x 6 x 9 ins. out of the ground, with cross at the exact corner, two grooves on the east edge, four grooves on the south edge and 1 N on the north. Tie to this corner was made direct from Cor. No. 1 of the Monte Cristo lode. The quarter corner between sections 11 and 14 is a quartzite stone showing 6 x 6 x 10 ins. out of the ground, with cross at the exact corner, $\frac{1}{4}$ S 11 on the north and 14 on the south, with mound of stone alongside. The quarter corner between sections 14 and 23 is a dacite stone showing 6 x 6.5 x 7 ft. out of the ground, chiseled cross at the exact corner and 23- $\frac{1}{4}$ S-14 on the east face. The corner common to sections 14, 15 22 and 23 is a quartzite stone 9 x 9 x 12 ins. out of the

ground, with four grooves on the west edge, three grooves on the south edge, 15 E on the east and 1 N on the north. The quarter corner between sections 15 and 22 is a quartzite stone showing 4 x 8 x 10 ins. out of the ground, with cross at the exact corner, 22 on the south face and $\frac{1}{4}$ S 15 on the north face. The corner common to sections 15, 16, 21 and 22 is a 3 inch iron pipe, with cap divided in quadrants and stamped Sec. 15, Sec. 16, Sec. 21 and Sec. 22 in the respective quadrants, set in concrete base. This is not the original corner, but after a careful search in the vicinity I was unable to find any set stone or other evidence of a corner, and I am reliably informed that the original corner was removed on account of being in a small water course, where it would likely wash out, and this more permanent monument set in its place. The corner common to sections 9, 10, 15 and 16 is a quartzite stone showing 6 x 8 x 8 ins. out of the ground, with cross at the exact corner, four grooves on the south, 1 N on the north and three grooves on the east, with mound of stone alongside. The quarter corner between sections 10 and 15 is a quartzite stone showing 8 x 8 x 5 ins. out of the ground, with cross at the exact corner, $\frac{1}{4}$ S 10 on the north and 15 on the south. The quarter corner between sections 13 and 14 is a limestone, 4 x 9 x 9 ins. out of the ground, with cross at the exact corner, $\frac{1}{4}$ S on the west and 13 on the east.

Sun Blower No. 1 lode, unsurveyed:

All four of the corners of this claim are 4 x 4 posts.

Sur. 3758, Baltic, Nellie M and Acre lodes:

All the corners of these claims marking coinciding and conflicting lines with the lines of this survey are stones properly set and marked, with mounds of stone alongside.

I find the bearing and distance of lines 3-4, Nellie M and Acre lodes correct as approved. And I find the bearing of lines 2-3, Baltic lode, 2,3-4-1, Nellie M

lode and 2-3-4-1, Acre lode correct as approved.

I find no monuments or fences on the ground marking the boundaries of the Robert Stead or James S. Russell homesteads.

The disagreement between these notes and the location notices is due to errors in the latter.

Edwin P. Stewart
United States Mineral Surveyor.

Globe, Arizona,
January 19, 1923.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by Edwin T. Stewart

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

A.H. SHOUP

known as the See Bird, Monte Cristo, Monte Carlo, Cuprite, Anaconda and Nevada lodes

and showing the respective capacities in which they acted.

Charles Pennington, Chainman.

_____, Chainman.

_____, Axman.

_____, Flagman.

FINAL OATHS OF ASSISTANTS.

We, _____

and I, Charles Pennington, do solemnly swear that we assisted _____

Edwin T. Stewart, United States Mineral Surveyor, in marking the corners and surveying

the boundaries of the mining claim of A.H. Shoup

known as the See Bird, Monte Cristo, Monte Carlo, Cuprite, Anaconda and Nevada lodes,

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully

and correctly executed, and the corner and boundary monuments established according to law and the instruc-

tions furnished by the United States Surveyor-General for Arizona

Charles Pennington, Chainman.

_____, Chainman.

_____, Axman.

_____, Flagman.

Subscribed and sworn to by the above-named persons before me this 19th

day of January, 1923.

My Com. Ex. Nov. 12, 1924.

W. L. Harrison

Notary Public, Gila
County, Arizona.



FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Edwin T. Stewart, U. S. Mineral Surveyor,
do solemnly swear that, in pursuance of instructions received from the United States
Surveyor General for Arizona, dated
December 27, 1922, I have, in strict conformity to the laws of the
United States, the official regulations and instructions thereunder, and the instructions
of said Surveyor General, faithfully and correctly executed the survey of the Mining
Claim of A. H. Shoup,
known as the
SEE BIRD, MONTE CRISTO, MONTE CARLO, CUPRITE, ANACONDA AND NEVADA,
situate in GLOBE Mining District,
Gila County, Arizona, in Section S
14 and 15, Township No. 1 N., Range No. 15 E., G. & S. R. M.,
and designated as Survey No. 3875, as represented
in the foregoing field notes, which accurately show the boundaries of said mining claim
as distinctly marked by monuments on the ground, and described in the attached copy
of the location certificate, which was received by me from the Surveyor General with
said instructions, and that all the corners of said survey have been established and per-
petuated in strict accordance with the law, official regulations and instructions there-
under; and I do further solemnly swear that the foregoing are the true and original
field notes of said survey and my report therein, and that the labor expended and
improvements made upon said mining claim by claimant or his grantors
are as therein fully stated, and that the character, extent, location, and itemized value
thereof are specified therein with particularity and full detail, and that no portion of
said labor or improvements so credited to this claim has been included in the estimate
of expenditures upon any other claim.

Edwin T. Stewart
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Edwin T. Stewart
U. S. Mineral Surveyor, before me M. I. Harrison, a Notary Public
in and for Gila County, Arizona, this 19th
day of January, 19 23.

My Com. Ex. Nov. 12, 1924.

M. I. Harrison
Notary Public, Gila
County, Arizona.

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

February 24, 1923.

I, U. S. Surveyor-General for District of Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

A. H. Shoup

known as the SEE BIRD, MONTE CRISTO, MONTE CARLO, CUPRITE, ANAONDA, and NEVADA Lodes

situate in Globe

Mining District, Gila County, Arizona

in Sections 14 & 15, Township No. 1 N., Range No. 15 E.,

designated as Survey No. 3875, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claim by claimant or his grantors, and that said improvements consist of 5 shafts, 8 cuts, 4 tunnels and 3 crosscuts, total value \$11,585.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

Frank P. Trott

United States Surveyor-General for Arizona.

**SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES
AND SURVEY OF MINING CLAIM**

**DEPARTMENT OF THE INTERIOR
OFFICE OF U. S. SURVEYOR GENERAL**

..... Phoenix, Arizona,

..... February 24, 1923.

I, U. S. Surveyor General for District of Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of

..... A. H. Shoup

....., known as the

SEE BIRD, MONTE CRISTO, MONTE CARLO, CUPRITE, ANACONDA, and NEVADA
lodes

situate in Globe mining district,

..... Gila County, Arizona

in Section s. 14 and 15, Township No. 1 N., Range No. 15 E.

....., designated as Survey No. 3875

executed by Edwin T. Stewart, U. S. Mineral

Surveyor, January 1 - 14, 1923, under my instructions dated


..... December 27, 1922, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

..... 

U. S. Surveyor General for Arizona.

SUPPLEMENT TO FIELD NOTES
of
MINERAL SURVEY NO. 3875.

At point 960.83, on line 3-4 See Bird lode, intersect the line between Secs. 14 and 15, T. 1 N., R. 15 E., at S. 0° 01' E. 46.26 ft. from the N. E. Cor. of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of said Sec. 15, being also the N. W. Cor. of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of said Sec. 14.

Area See Bird lode in conflict with;

SE $\frac{1}{4}$ NE $\frac{1}{4}$ Sec.15,T. 1 N., R. 15 E., .038 Acres

SW $\frac{1}{4}$ NW $\frac{1}{4}$ Sec.14.T. 1 N., R. 15 E. 8.052 "

I certify that the above and foregoing correctly describes the intersection of line 3-4 See Bird lode with the line between Secs. 14 and 15, T. 1 N., R. 15 E., and shows the area of said claim in conflict with the SE $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 15, and the SW $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 14, T. 1 N., R. 15 E., assuming the course of said line between Secs. 14 and 15 to be N. 0° 01' W. as recorded in the notes of survey of such line.

I further certify that the said intersection has been shown upon the plat of Survey No. 3875 in red ink.

Charles M. Doulos
U. S. Surveyor General
for Arizona.

Phoenix, Arizona,
December 17, 1924.