

MINERAL SURVEY No. 3925

ARIZONA. Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Fred Smith, W.A. Jordan, O.E. Lyksett, A.L. Hougen, and Mrs. M.A. Carrier.

KNOWN AS THE

Broad Gauge, Double Eagle, Curtis, Hidden Spring, Florence and Fools lode claims.

Verde Mining District,

Yavapai County, Arizona.

Section 26 & 35, Township 16 N., Range 2 E.

Jan. 30, 1924.

Feb. 28, 1924.

Surveyed under instructions dated, 19

by J. William Waara U. S. Mineral Surveyor.

Claim located see location notices, 19

Survey commenced Jan. 31, 1924, 19

Survey completed Feb. 29, 1924., 19

Address of claimant Robert E. Morrison, Atty for claimants, Prescott Arizona.

DATES OF AMENDED LOCATIONS.

MINERAL SURVEY NO. 3925.

FOOLS Lode.

Beginning at Cor. No.1, situated on line 2-3 Hidden Spring lode of this survey, a shist reef 30x40x20 feet high with a substantial mound of stone alongsdie ; chiseled F 1 3925 with cross for exact corner point, whence,

A point on said shist reef, chiseled BxR F 1 3925, brs. S.47°-13'W. 3.1 feet.

The Souht 1/4 corner section 26 T. 16 N.R.2 E, Gila and Salt River Base and Meridian, brs. S. 31°-50'E. 1040.0 feet.

No other bearings available.

Feet

Thence N.71°-16'W.

760

Cross Mescal Gulch, flows easterly.

1364.6

Intersect line 1-2 103 lode Sur. No. 1413, S.44°-57'E. 139.2 feet from Cor. No.1, and 42.8 feet from its intersection with line 3-5 Venture<sup>No.1</sup> South Lode Sur. No. 870.

1409.7

Intersect line 3-5 Venture<sup>No.1</sup> South lode Sur.No. 870, S.38°-00'W. 315.5 feet from Cor.No.5. and 20.1 feet from its intersection with line 1-2 103 lode Sur.No. 1413

1467.2

TO COR. NO. 2, a shist stone 6x8x22 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled F 2 3925 with cross on top for exact corner point, whence,

A diorite rock in place 3x4x4 feet exposed and chiseled BxR F 2 3925, brs. S.8°-05'W. 26.6 feet.

Sur.No.1413

Cor. No.1 103 lode/bts. N.1°-03'W. 65.6 feet.

Thence N.47°-13'E.

45.5

Intersect line 1-2 103 lode Sur.No. 1413, S.44°-57'E. 49.0 feet from Cor. No.1

250

Cross road, brs. S.E. to N.W.

335.0

WEST CENTER END, a mound of stone.

338.9

Cor.No. 5 Venture<sup>No.1</sup> South lode Sur. No. 870, situated i

338.9

on line 1-2 Calumet lode Sur.No. 2910, N.45°-40'W. 154.7 feet from Cor.No.2.

604.9 Intersect line 2-3 Bald Eagle lode Sur.No. 2910, N.82°-49'E. 92.6 feet from Cor. No. 2

667.7 TO COR. NO. 3, a shist reef 6x20x6 feet exposed with a substantial mound of stone alongside; chiseled F 3 3925 with cross for exact corner point, whence,

Cor.No.2 Bald Eagle lode Sur.No. 2910, brs. S.68°-32'W.148.3 feet

No other bearings available.

Thence S.71°-21'E.

83.9 Intersect line 2-3 Bald Eagle lode Sur. No. 2910, N.82°-49'E. 219.2 feet from Cor. No.2.

170.7 Intersect line 2-3 Calumet lode Sur. No. 2910, N.46°-34'E. 402.8 feet from Cor. No.2.

210.0 Cross road, brs. N.E. to S.W.

1000.0 Cross Mescal Gulch, flows northeast.

1468.3 TO COR. NO. 4, situated on line 1-2 Curtis lode of this survey, N.47°-13'E. 348.2 feet from Cor. No.1, a shist boulder 4x6x3 feet exposed with a substantial mound of stone alongside; chiseled F 4 3925 with cross for exact corner point.

No bearings available.

Thence S.47°-13'W.

3.1 West Center end Curtis lode of this survey. a substantial mound of stone.

335.0 EAST CENTER END, a substantial mound of stone.

348.2 Cor.No. 1 Curtis lode, identical with Cor. No. 3 Hidden Spring lode, both of this survey, hereafter described.

670.0 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 15°E.

BROAD GAUGE Lode.

Beginning at pt. for cor. <sup>No.1</sup> where it was impracticable to set a stone, due to sloping ground, so I set a witness cor: S.87°-54'W.1.4 ft. a schist stone 6x12x22 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled B G 1 3925

with cross on top for exact corner point, whence a

A schist rock in place 8x12x6 inches exposed and  
chiseled BxR B G 1 3925 brs. S.44°-26'E. 52.8 ft.

From the true point for corner.

The EAST 1/4 corner Sec.26, T.16 N.R.2 E. brs.  
N.62°-57'E. 1730.5 feet.

Cor.No.2 Monmont lode Sur.No.1375 brs. N.70°-  
02'W. 385.7 feet.

Thence S.87°-54'W. ( from true cor.Pt.

1.4 Witness corner previously described.

190.8 Intersect line 4-1 Double Eagle lode of this survey,  
S.60°-08'E. 581.9 feet from Cor.No.4.

274.1 Intersect line 1-2 Monmont lode Sur.No. 1375, S.31°-59'E.  
167.1 feet from Cor.No.2.

798.9 Intersect line 3-4 Double Eagle lode of this survey  
S.18°-17'W. 328.7 feet from Cor.No.4.

1240.0 Cross Mescal Gulch, flows northerly.

1420.9 TO COR.NO.2, a point on a cliff 200x20x50 feet high with a  
substantial mound of stone alongside; chiseled B G 2  
3925 with cross for exact corner point, whence,

Cor.No.3 Bald Eagle lode Sur.No.2910, brs.  
N.70°-09'W. 228.2 feet.

No other bearings available.

Thence N.44°-31'W.

329.6 Intersect line 3-4 Bald Eagle lode, Sur.No.2910, S.5°-  
58'E. 289.8 feet from Cor.No.4.

406.0 WEST CENTER END, a mound of stone.

600.0 Cross road brs. N.E. to S.W.

700.4 Intersect line 1-4 Bald Eagle lode Sur.No.2910, identical  
with line 3-4 Stonewall lode Sur.NO.1543, S.84°-05'W. 231.1  
feet from Cor.Nos.4 and 3 respectively.

755.5 TO COR. NO.3, a diorite stone .6x8x24 inches long set twelve  
inches in the ground with a substantial mound of stone  
alongside; chiseled B G 3 3925 with cross on top for exact  
corner point, whence,

A diorite reef 6x3x2 feet exposed and chiseled

BxR B G 3 3925, brs. S.44°-23'E. 8.2 feet.

Cor.No.4 Bald Eagle lode Sur. No. 2910, identical with Cor.No.3. Stonewall lode and Cor. No.4 Spoke lode, both Sur. No.1543 brs. S.86°-42'E. 269.0 ft.

Thence N.87°-04'E.

195.0 Cross road brs. north and south.

271.1 Intersect line 2-3 Stonewall lode, identical with line 1-4 Spoke lode, both Sur.No. 1543, N.4°-15'E. 29.4 feet from Cor.Nos. 3 and 4 respectively.

1216.9 Intersect line 2-3 Mescal Fraction lode Sur.No. 3923, N.41°-43'W. 558.7 feet from Cor.No.2 and 29610 feet from its intersection with line 3-4 Spoke lode at a point N.82°-53'W. 244.4 feet from Cor.No.3 of said Spoke lode.

1219.0 Cross Mescal Gulch, flows northeasterly.

1360.0 Cross Mescal Gulch, flows southeasterly

1402.6 TO COR. NO.4, a diorite rock in place 15x15x10 feet high with a substantial mound of stone alongside; chiseled B G 4 3925 with cross for exact corner point, whence,

A point on the same cliff, chiseled BxR B G 4 3925 brs. S.44°-50'E. 13.1 feet.

Thence S.44°-31'E.

95.0 Cross Mescal Gulch, flows, northeasterly.

362.6 Intersect line 2-3 Spoke lode Sur.No. 1543, N.4°-48'E.

2.2 feet from Cor.No.3. Cor. 4 said Spoke lode brs N. 82° 53'w. 1397.40 ft from Cor. No. 3 thereof.

376.9 EAST-CENTER END, a mound of stone.

418.4 Intersect line 1-2 Mescal Fraction lode Sur.No. 3923, identical with line 2-3 Monmont lode Sur.No. 1375, N.39°-50'E. 167.0 feet from Cor.Nos. 2 and 2 respectively.

782.9 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 15°-00'E.

DOUBLE EAGLE Lode.

Beginning at Cor.No.1, a schist stone in place 2x1x1 foot exposed with a substantial mound of stone alongside; chiseled D E 1 3925 with cross on top for exact corner point, whence,

T.16<sup>4</sup>N.R.2<sup>2</sup>E.

The East 1/4 corner Section 26, brs. N. 36°-49'E.

1562.1 feet.

A schist reef 3x2x2 feet exposed and chiseled

BxR D E 1 3925 brs. N.83°-46'E. 16.1 feet.

Thence S. 18°-17'W.

260.0 EAST CENTER END, a mound of stone.

518.9 TO COR. NO. 2, a schist stone 6x6x22 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled D E 2 3925 with cross on top for exact corner point, whence,

A schist reef 4x3x2 feet exposed and chiseled

BxR D E 3925, brs, N.59°-20'E. 18.8 feet.

Cor.No. 3 Last Chance lode Sur.No. 2934 brs.

N.66°-32'W. 149.9 feet.

Thence N. 63°-03'W.

138.4 Intersect line 3-4 Curtis lode of this survey, S.47°-13'W.  
162.9 feet from Cor. No. 3.

205.8 Intersect line 1-2 Monmont lode Sur. No. 1375, S.31°-59'E.  
1173.2 feet from Cor. No.2.

700.0 Cross small gulch, flows northerly.

1485.9 TO COR. NO.3, identical with Cor. No. 2 Curtis lode of this survey, a point on <sup>top of</sup> a schist reef 50 feet high with a substantial mound of stone alongside, chiseled D E 3, C 2, 3925 with cross on top for exact corner point.

No bearings available.

Thence N.18°-17'E.

267.3 Intersect line 1-2 Bread Gauge lode of this survey,  
S.87°-54'W. 798.9 feet from Cor. No. 1.

300.0 WEST CENTER END, a mound of stone.

596.0 TO COR NO. 4, a point on schist cliff facing creek,  
with a substantial mound of stone alongside; chiseled  
D E 4 3925 with cross for exact corner point.

No bearings available.

Thence S.60°-08'E.

428.8 Intersect line 1-2 Monmont lode Survey No. 1375, S.31°-

59'E. 73.6 feet from Cor. No.2.

581.9 Intersect line 1-2 Broad Gauge lode of this survey,  
S.87°-54'W. 190.8 feet from Cor. No.1.

880.0 Cross small gulch, flows northerly.

1499.6 TO THE PLACE OF BEGINNING. All corners are identical with  
their respective locations Variation at all corners 15° -  
00'E.

CURTIS Lode.

Beginning at Cor. No.1, identical with Cor.No.  
3 Hidden Spring lode of this survey, and situated on line  
4-1 Fools lode of this survey, S.47°-13'W. 348.2 feet  
from Cor. No. 4. a diorite stone 6x8x22 inches long set  
twelve inches in the ground with a substantial mound of  
stone alongside; chiseled C 1, H S 3, 3925 with cross on  
top for exact corner point, whence,  
T.16 N.R.2 E.  
The South 1/4 corner section 26, /brs. S.15°-50'E.  
1146.0 feet.

No other bearings available.

Thence N,47°-13'E.

345.1 WEST CENTER END, a mound of stone.

348.2 Cor.No.4 Fools lode, previously described.

697.7 COR.NO. 2, identical with Cor. No.3 Double Eagle lode of  
this survey, previously described.

Thence S.69°-16'E.

790.0 Cross small gulch, flows northerly.

1090.5 Intersect line 1-2 Monmont lode Sur.No. 1375, S.31°-59'E.  
944.4 feet from Cor. No.2.

1412.2 TO COR. NO.3, a schist stone 6x8x24 inches long set  
twelve inches in the ground with a substantial mound of  
stone alongside; chiseled C 3 3925, with cross on top  
for exact corner point, whence,  
Cor. No.1 Monmont lode Sur. No.1375, brs.  
S.12°-18'W. 279.0 feet.

No other-bearing available.

Thence S.47°-13'W.

- 162.9 Intersect line 2-3 Double Eagle lode of this survey,  
N.63°-03'W. 138.4 feet from Cor. No.2.
- 175.6 Intersect line 3-4 Last Chance lode Sur.No. 2934, S.39°-  
42'E. 7.3 feet from Cor. No.3.
- 198.3 Intersect line 1-2 Monmont lode Syr.No. 1375, N.31°-59'W.  
162.6 feet from Cor..No.1, & S.31° 59'E. 1237.5 ft. from Cor No.2.
- 200.0 EAST CENTER END, a mound of stone.
- 518.4 TO COR. NO. 4, identical with Cor. No.4 Hidden Spring  
lode of this survey, a schist stone 6x12x24 inches long  
set twelve inches in the ground with a substantial mound  
of stone alongside; chiseled C 4 H S 4 3925 with cross  
on top for exact corner point, whence,  
A schist rock in place 3x2x1 foot exposed and  
chiseled BxR H S 4 C 4 3925; brs. S.52°-31'W. 20.9 feet.  
Thence N.75°-24'W.
- 7.3 Intersect line 2-3 Last Chance lode Sur.No.2934, S.47°-  
04'W. 347.1 feet from Cor. No.3
- 515.8 Cross small gulch, flows northerly.
- 1500.8 TO THE PLACE OF BEGINNING. All corners are identical with  
their respective locations. Variation at all corners 15°  
-00'E.
- HIDDEN SPRING Lode/  
Beginning at Cor. No.1, identical with Cor. No.  
4 Florence lode of this survey, a schist stone 6x6x20 inch-  
es long set twelve inches in the ground with a substantial  
mound of stone alongside; chiseled F4,H S 1 3925 with  
cross on top for exact corner point, whence,  
T.16 N.R.2 E.  
The south 1/4 corner sec. 26, brs. S.64°-54'W.  
798.1 feet.
- A schist rock in place 1x2x1 foot exposed and  
chiseled BxR H S 1 3925, brs. S.33°-41'W. 15.7 feet.
- No other bearings available.  
Thence N.75°-33'W.
- 5.3 Intersect line 2-3 Last Chance lode Sur.No.2934, S.47°-  
04'W. 914.0 feet from Cor. No.3.
- 220.0 Cross small gulch flows northerly.



1503.2 TO COR. NO. 2, identical with Cor. No.3 Florence lode of this survey, a point on a schist reef 20x10x1 foot exposed with a substantial mound of stone alongside; chiseled H S 2 F 3 3925 with cross for exact corner point, whence .A schist outcrop 6x10x4 feet exposed and chiseled BxR F 3 3925, brs. N.61°-33'W. 12.8 feet.

Thence N.47°-13'E.

219.4 WEST CENTER END, a mound of stone.

250.8 Cor.No.1 Fools lode of this survey, previously described.

572.6 TO COR. NO.3 identical with Cor. No.1 Curtis lode of this survey, and situated on line 1-4 Fools lode of this survey, previously described.

Thence S.75°-24'E.

985.0 Cross small gulch, flows northerly.

1493.5 Intersect line 2-3 Last Chance lode Sur.No. 2934, S.47°-04'W. 347.1 feet from Cor. No.3/

1500.8 TO COR. NO. 4, identical with Cor. No. 4 Curtis lode of this survey, previously described.

Thence S. 47°-13'W.

355.8 EAST CENTER END, a mound of stone.

568.1 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations, Variation at all corners 15°-00'E.

FLORENCE Lode.

Beginning at Cor. No.1, a schist stone 6x8x18 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled F 1 3925 with cross on top for exact corner point, whence,

T.16 N.R.2 E.

The south 1/4 corner section 26, brs. N.76°-38'W.

292.0 feet. Cor. No. 3 Prosperity lode Sur.No.2934, brs. N.7°-11'W. 411.5 feet

Thence N.75°-17'W.

~~265.9 Intersect the section line between sections 26 and 35 N.89°-55'E. 27.0 feet from the south 1/4 Cor.Sec.26.~~

339.0 Intersect line 2-3 Prosperity lode Sur. No.2934, S.40°-38'W. 424.5 feet from Cor. No.3.

666.5 Intersect line 4-1 Indiana lode Sur. No.2934, S.57°-02'E.

- 415.3 feet from Cor. No.4.
- 1219.9 Intersect line 3-4 Indiana Lode Sur.No.2934, S.65°-26'W.  
205.4 feet from Cor. No.4.
- 1342.9 Intersect line 2-3 103 lode Sur.No. 1413, S.54°-55'W.  
157.6 feet from Cor. No.2.
- 1498.3 TO COR. NO.2, a point on face of cliff 10x20x 30 feet high, with a substantial mound of stone alongside; chiseled F 2 3925 with cross for exact corner point,whence,  
A point on top of a cliff 10x20x10 feet exposed and chiseled BXR F 2 3925, brs. N.47°-13°E. 60.6 ft.  
Thence N.47°-13'E.
- 233.9 Intersect line 1-2 103 lode Sur. No.1413, N.44°-57'W.  
152.2 feet from Cor. No.2.
- 349.6 WEST CENTER END, a mound of stone.
- 588.6 TO COR. NO.3, identical with Cor. No.2 Hidden Spring lode of this survey, previously described.  
Thence S.75°-33'E.
- 1283.2 Cross small gulch, flows northerly.
- 1497.9 Intersect line 2-3 Last Chance lode Sur.No.2934, N.47°-04'E. 373.1 feet from Cor. No.2.
- 1503.2 TO COR. NO.4, identical with Cor. No.1 Hidden Spring lode of this survey, previously described.  
Thence S.47°-13'W.
- 259.9 EAST CENTER END, a mound of stone.
- 376.2 Intersect line 1-2 Last Chance lode, identical with line 3-4 Prosperity lode, both Sur.No.2934, S.39°-42'E. 3.3 feet and 335.1 feet ~~respectively~~ from cor.Nos. 2 and 3, respectively.
- 386.0 Cross small gulch, flows northerly.
- ~~Intersect the section line between sections, 26 and 35~~
- ~~497.5 N.89°-55'E. 357.6 feet from the South 1/4 corner sec.26.~~
- 597.7 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 15°-00'E.

LODE LINES.

As near as can be determined from the present developments, the veins on the respective lodes extend as follows from the discovery:

FOOLS lode.

N.71°-16'W. 997.2 ft. and S.71°-16'E. 470 feet:

BROAD GAUGE lode

S.87°-54'W. 1136.9 ft and N.87°-54'E. 284.0 ft.

DOUBLE EAGLE lode

N.61°-29'W. 822.1 feet and S.61°-29'E. 670 feet.

CURTIS lode

N.74°-32'W. 846.5 feet and S.74°-32'E.640 feet.

HIDDEN SPRING Lode

N.75°-19'W. 1184.4 ft and S.75°-19'E. 315. ft.

FLORENCE lode

N.74°-54'W. 952.0 ft and S.74°-54'E. 540.0 ft.

AREAS

Fools Lode,

	Acres.	Acres
Total Area - - - - -		19.801
Area in conflict with		
Venture <sup>No.1</sup> South lode Sur.No.870 -	0.197	
103 lode Sur.No.1413 - - - - -	0.047	
Calumet lode Sur.No.2910 - - -	1.280	
Bald Eagle lode Sur.No.2910 - -	0.053	
Bald Eagle lode Sur.No.2910 ex-		
clusive of its conflict with Calumet lode		
Sur.No.2910 - - - - -	0.053	
Venture <sup>No.1</sup> South lode Sur.No.870		
exclusive of its conflict with 103 lode Sur.		
No. 1413. - - - - -	0.160	

Broad Gauge lode

Total area - - - - -	18.525
Area in conflict with	
Stonewall lode Sur.No. 1543 - -	0.205
Spoke lode, Sur.No.1543 - - - - -	4.027
Mescal Fraction lode Sur.No.3923	1.726
Menmont lode Sur.No. 1375 - - - -	1.151
Bald Eagle lode Sur.No. 2910 - - -	0.769
Mescal Fraction lode Sur.No.3923	
exclusive of its conflict with Spoke lode	
Sur. No. 1543. - - - - -	-0.590

DOUBLE EAGLE lode

	Acres	Acres
Total area	- - - - -	18.799
Area in conflict with		
Broad Gauge lode	- - - - -	2.151
Monmont lode Sur.No. 1375	- - - - -	7.589
Broad Gauge lode exclusive of its conflict with Monmont lode Sur.No.1375	- - - - -	2.073

CURTIS lode

Total area	- - - - -	17.645
Area in conflict with		
Double Eagle lode	- - - - -	2.364
Monmont lode Sur.No. 1375	- - - - -	0.655
Last Chance lode Sur.No.2934	- - - - -	0.053
Double Eagle lode exclusive of its conflict with Monmont lode Sur.No. 1375	-- --	1.735
Last Chance lode Sur. No.2934,ex- clusive of its conflict with Monmont lode Sur. No.1375.	- - - - -	0.049

HIDDEN SPRING Lode

Total area	- - - - -	16.550
Area in conflict with		
Last Chance lode Sur.No.2934	- - - - -	0.069

FLORENCE lode

Total area	- - - - -	17.210
Area in conflict with		
Last Chance lode Sur.No.2934	- - - - -	0.033
Indiana lode       "   "   "	- - - - -	0.826
Prosperity lode   "   "   "	- - - - -	2.337
103 lode Sur.No. 1413	- - - - -	0.623

LOCATION

This survey is located in Sec. 26 and 35 T. 16 N.R. 2 E. of the Gila and Salt River Base and Meridian, within the Prescott National Forest, Verde Mining District, Yavapai County, State of Arizona.

EXPENDITURE OF FIVE HUNDRED DOLLARS

I hereby certify that the value of the labor and improvements made upon or for the benefit of the locations embraced in this survey by the claimants or their grantors is not less than five hundred dollars, and that said improvements consist of:-

Fools Lode

No.1 Disc. cut and tunnel, the mouth of cut brs. N.71°-16'W. 470 feet from the East Center End, cut 4x8x10 foot face, tunnel 4x6 running as follows from the portal

S.56°E. 10.0 ft to sta.1; thence S.26°E. 50.0 ft to sta.2  
 thence S.44°E. 25 ft. to sta.3; thence S.19°W. 39.0 ft.  
 to sta.4; thence S. 46°W. 110.0 ft. to sta. 5; thence  
 S:33°W. 50.0 ft to sta. 6; thence S. 60°W. 6.0 ft. to face,  
 having a total length of 290.0 ft.

Value cut \$100.00  
 Tunnel \$2900.00

No.2 A cut, the face of which brs. N.27°W. 290 ft.,/4x10  
 x10 foot face, running N.W. to mouth.

Value \$100.00

Broad Gauge lode.

No.1 Discovery cut and tunnel, the mouth of cut brs.  
 S.18°W. 240 ft. from Cor. No.4, running S.47°E. 8.0 ft  
 at 66.6, under Discovery,  
 to portal, thence S.47°E./93 ft. to sta.1, thence N.71°E.  
 18 ft to sta.2; thence N.71°E. 8.0 ft. to face; also  
 from sta. 2 S.70°E. 15.0 ft to filled in drift. From sta.  
 1, S.46°-20'E. 88.0 ft.to face, having a total length of  
 tunnel, 222 ft, 4x6 ftin size, and cut 4x8x10 foot face.

Value cut \$100.00  
 Tunnel \$2220.00

Double Eagle lode.

No.1 Discovery shaft, the center of which brs.  
 N.61°-29'W. 670 ft from the East Center End, 4x6x50 feet  
 deep, estimated.

Value \$750.00

Curtis Lode. ( Insert \* on Page 15.)

No.2 shaft, the center of which brs. N.54°W.  
 from Cor. No.4  
 495.0 ft., 4x6x20 ft deep.

Value \$250.00

No.3 Shaft, the center of which brs. N.28°W. 510  
 feet from Cor. No.4, 4x6x50 feet deep, estimated,

Value \$750.00

No.4, cut and tunnel, the mouth of cut brs.  
 N.31°W. 510 ft from Cor. No.4, running S.46°E. 17 to  
 portal of tunnel, thence S.46°E. 67.0 ft to sta.1; thence  
 South 35.0 ft to face. Cut 4x12x17, tunnel 4x6x119 ft

Value cut \$100.00  
 tunnel \$1190.00

## Hidden Spring lode,

No.1 Discovery cut and tunnel, the mouth of cut  
 brs. N.74°W. 315 ft from the East Center End, running  
 thence N.50°W. 15 ft. to portal, thence N.60°W. 48.0 ft.  
 to sta.1; thence S.56°W. 36.0 ft to sta.2; thence S.36°W.  
 45.0 ft to sta. 3; thence S.46°W. 20.0 ft to sta.4; thence  
 S.56°W. 22.0 ft to face. From sta. 1, N.18°E. 10 ft to ~~fit~~  
 filled in drift. From Sta. 3 N.48°W. 37.0 ft to face.  
 cut 4x15x10 foot face, tunnel 4x6x 218 ft. long.

Value cut	\$100.00
tunnel	\$2180.00

## Florence lode.

No.1 Discovery cut and tunnel, the mouth of  
 cut brs. S.89°W. 660 ft from Cor. No.4, running thence  
 S65°W. 25 ft to portal of caved in tunnel, thence S.45°W.  
 at 32.4, under discovery,  
 / 50.0 ft (estimated) to face. cut 4x25x10 foot face, tunnel  
 4x6x50 ft.

Value cut	\$150.00
tunnel	\$500.00

No.2 cut , the mouth of which brs. S.87°W.  
 625 ft from Cor. No.4, 4x20x10 foot face, brs. southwest.

Value	\$100.00
-------	----------

## ADJOINING CLAIMS

This survey is bounded on the east, and south by  
 the Mescal Fraction, Sur.No.3923, Monmont Sur.No.1375,  
 Last Chance, Prosperity and Indiana lodes, Sur.No. 2934,  
 Verde Combination Copper Company, claimant, on the south  
 west and west by the 103 lode Sur.No.1413, Calumet, and  
 Bald Eagle lodes Sur.No.2910, Calumet & Jerome Copper  
 Company claimant, Venture <sup>No.1</sup> south lode Sur.No.870, United  
 Verde Copper Company claimant, and the Spoke and Stonewall  
 lodes, <sup>Sur. No. 1543</sup> Green Monster Copper Company, claimant, also  
 Jordan and Waara lodes unsurveyed, Messrs, Jordan, Smith,  
 Lyksett, Houggen , claimants.

## INSTRUMENT

This survey was made with a Lietz Light Mountain

transit theodolite, No. 13,5929. The courses were deflected from the true meridian as determined by the direct solar observations. The distances were measured with a 500 foot steel tape.

#### REPORT

The east and south 1/4 corners Sec. 26, are pipe corners properly set and marked for said corners.

Sur. No. 1375.

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the courses and distances of the lines adjoining this survey.

Sur. No. 1413

The corners adjoining this survey are concrete monuments. I do not agree with the courses and distances of lines adjoining this survey.

Sur. No. 870

The corners adjoining this survey are concrete monuments. I do not agree with the courses of lines adjoining this survey.

Sur. No. 1543

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the courses and distances of lines adjoining this survey.

Survey No. 2934.

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with all of the courses and distances of lines adjoining this survey.

Survey No. 3923

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey.

Survey No. 2910. The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with all of the courses and distances of lines adjoining this survey.

The discrepancies found existing between the claims as marked by the location monuments and as described in the location notices are due to errors in the location notices.

The discrepancies between the lines of this survey and prior approved surveys are due to errors in the latter.

Owing to the fact that a Notary Public was not available at the completion of this survey, and to avoid delays and expense to obtain an acknowledgment, in filling "Final Oath for Surveys", I took the acknowledgments of my assistants.

*J. Hollister Warren*  
U.S. Mineral Surveyor

~~Supplemental on improvements, insert under "Curtis lode"~~

~~Curtis lode,~~

\* No.1 Discovery cut and tunnel, the mouth of tunnel  
brs. N.74°-32'W. 640 ft from the East Center end, cut  
4x12x12 foot face brs. north to mouth, tunnel 3x5x34, brs.  
south.

Value	cut	\$ 50.00
	tunnel	300.00



# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by J. William Waara

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of Fred Smith, W.A. Jordan, O.E. Lyksett, A.L. Hougen and Mrs. M.A. Carrier

known as the Double Eagle, Broad Gauge, Fools, Florence, Curtis, and Hidden Spring lodes and showing the respective capacities in which they acted.

Temp Gamel, Chainman.

Temp Gamel, Chainman.

Elbert Maders, Axman.

....., Flagman.

## FINAL OATHS OF ASSISTANTS.

We, Temp. Gamel

and Elbert Maders, do solemnly swear that we assisted J. William Waara

....., United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Fred Smith, W.A. Jordan, O.E. Lyksett, A.L. Hougen, and Mrs. M.A. Carrier

known as the Double Eagle, Broad Gauge, Fools, Florence, Curtis and Hidden Spring lodes

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the United States Surveyor-General for Arizona

Temp Gamel, Chainman.

....., Chainman.

Elbert Maders, Axman.

....., Flagman

Subscribed and sworn to by the above-named persons before me this 1st

day of March, 19 24

J. William Waara  
U. S. Mineral Surveyor

4-686.

# FINAL OATH OF U. S. MINERAL SURVEYOR.

I, J. William Weara, U. S. Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the United States  
Surveyor General for Arizona, dated  
~~Jan. 30 1924~~  
Feb. 28 1924, I have, in strict conformity to the laws of the  
United States, the official regulations and instructions thereunder, and the instructions  
of said Surveyor General, faithfully and correctly executed the survey of the Mining  
Claim of Fred Smith, W.A. Jordan, O.E. Lyksett, A.L. Hougen and  
Mrs. M.A. Carrier, known as the  
Double Eagle, Broad Gauge, Foola, Florence, Curtis, & Hidden Spring, lodes  
situate in Verde Mining District,  
Yavapai County, Arizona, in Section  
26 & 35, Township No. 16 N., Range No. 2 E. G. & S.R. B & M.,  
and designated as Survey No. 3925, as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim  
as distinctly marked by monuments on the ground, and described in the attached copy  
of the location certificate, which was received by me from the Surveyor General with  
said instructions, and that all the corners of said survey have been established and per-  
petuated in strict accordance with the law, official regulations and instructions there-  
under; and I do further solemnly swear that the foregoing are the true and original  
field notes of said survey and my report therein, and that the labor expended and  
improvements made upon said mining claim by claimants or their grantors  
are as therein fully stated, and that the character, extent, location, and itemized value  
thereof are specified therein with particularity and full detail, and that no portion of  
said labor or improvements so credited to this claim has been included in the estimate  
of expenditures upon any other claim.

J. William Weara  
U. S. Mineral Surveyor.

Subscribed and sworn to by the said J. William Weara  
U. S. Mineral Surveyor, before me A Notary Public  
this 24<sup>th</sup>  
day of June, 19 24

My commission expires  
Apr 26, 1927

E. J. Horne  
Notary Public  
My Commission Expires April 26, 1927

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

February 9, 1925.

I, U. S. Surveyor-General for Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of Fred Smith, W. A. Jordan, O. E. Lyksett, A. J. Hougen and Mrs. M. A. Carrier

known as the Broad Gauge, Double Eagle, Curtis, Hidden Spring, Florence and Fools Lode Claims situate in VERDE

Mining District, YAVAPAI County, ARIZONA

in Sections 26 & 35, Township No. 16 N., Range No. 2 E., and

designated as Survey No. 3925, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon each of said mining claims by claimants or their grantors, and that said improvements consist of 3 shafts, 8 cuts and 6 tunnels, total value \$11,840.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Charles M. Donohoe

United States Surveyor-General for Arizona.

**SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES  
AND SURVEY OF MINING CLAIM**

**DEPARTMENT OF THE INTERIOR  
OFFICE OF U. S. SURVEYOR GENERAL**

Phoenix, Arizona,

February 9, 1925

I, U. S. Surveyor General for Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of Fred Smith, W. A. Jordan, O. E. Lyksett, A. L. Hougen, and Mrs. M. A. Carrier

known as the

Broad Gauge, Double Eagle, Curtis, Hidden Spring, Florence and Fools lode claims,

situate in VERDE mining district,

Yavapai County, Arizona

in Sections 26 & 35, Township No. 16 North, Range No. 2 East,

designated as Survey No. 3225

executed by J. William Waara, U. S. Mineral

Surveyor, January 31 to February 29, 1924, under my instructions dated

Jan. 30, and Feb. 28, 1924, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

*Charles M. Donohoe*

U. S. Surveyor General for

Feet

Amendment to Field Notes  
of  
Mineral Survey No. 3925.

-----

Description of conflict between the Fools lode, Survey No. 3925, and the Ohio lode, Survey No. 3951.

Beginning at point 605.5 on line 2-3 of the Fools lode, being at the point of intersection of line 2-3 Fools lode, and line 4-1 Ohio lode,

Thence S. 43° 49' E.

along line 4-1 Ohio lode,

1154.48 to an intersection with line 1-2 Fools lode;

Thence N. 71° 16' W.,

along line 1-2 Fools lode,

1211.01 to an intersection with line 2-3 Ohio lode;

Thence N. 44° 57' W.,

along line 2-3 Ohio lode,

76.87 to Cor. No. 3 Ohio lode;

Thence N. 44° 40' E.,

along line 3-4 Ohio lode,

291.36 to an intersection with line 2-3 Fools lode;

Thence N. 47° 13' E.,

along line 2-3 Fools lode,

268.60 to the place of beginning.

Area Fools lode in conflict with;

Ohio lode, Sur. No. 3951,	7.932 Acres
---------------------------	-------------

Ohio lode, Sur. No. 3951, exclusive of its conflict with the Venture No. 1 South lode, Sur. No. 870,	7.818 "
--	---------

Ohio lode, Sur. No. 3951, exclusive of its conflict with the Calumet lode, Sur. No. 2910,	6.997 "
---	---------

Ohio lode, Sur. No. 3951, exclusive of its conflict with the Bald Eagle lode, Sur. No. 2910,	7.932 "
--	---------

-----

Description of conflict between the Hidden Spring lode, Sur. No. 3925, and the Ohio lode, Sur. No. 3951.

Beginning at Cor. No. 2 Hidden Spring lode,

Thence N. 47° 13' E.,

**Feet** along line 2-3 Hidden Spring lode;  
 179.95 to an intersection with line 4-1 Ohio lode;  
           Thence S. 43° 49' E.,  
           along line 4-1 Ohio lode,  
 128.44 to Cor. No. 1 Ohio lode;  
           Thence S. 44° 40' W.,  
           along line 1-2 Ohio lode,  
 96.93 to an intersection with line 1-2 Hidden Spring lode;  
           Thence N. 75° 33' W.,  
           along line 1-2 Hidden Spring lode,  
 157.85 to Cor. No. 2, the place of beginning, containing  
           .417 acres.

-----

Description of conflict between the Florence lode, Sur. No. 3925, and the Ohio lode, Sur. No. 3951.

Beginning at Cor. No. 3 of the Florence lode,  
           Thence S. 75° 33' E.,  
           along line 3-4 Florence lode,  
 157.85 to an intersection with line 1-2 Ohio lode;  
           Thence S. 44° 40' W.,  
           along line 1-2 Ohio lode,  
 434.77 to Cor. No. 2 Ohio lode;  
           Thence N. 44° 57' W.,  
           along line 2-3 Ohio lode,  
 152.20 to an intersection with line 2-3 Florence lode;  
           Thence N. 47° 13' E.,  
           along line 2-3 Florence lode,  
 354.70 to the place of beginning, containing 1.299 acres.

-----

PUBLIC SURVEY OFFICE,  
 Phoenix, Arizona,  
 May 11, 1927.

I certify that the above and foregoing correctly describes the conflict between the Fools, Hidden Spring and Florence lodes, Sur. No. 3925, and the Ohio lode, Sur. No. 3951, as appears in the record of said Sur. No. 3951 and that the areas of said conflicts are correct as stated.

I further certify that the plats of Survey No. 3925 on file in this office, the General Land Office, and the Phoenix Land Office, have been amended to show said conflicts.

*John D. Claus*  
 Office Cadastral Engineer