MINERAL SURVEY No. 3946

Arizona Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Phelps Dodge Corporation			
KNOWN AS THE			
IRON QUEEN and STAMBOUL lodes			
Copper Mountain Mining District.			
Greenlee County, Arizona.			
Sections 20 - 21 , Township A.S. , Range 29 E. G.& S.R. N			
Surveyed under instructions dated March 21, 1924			
by N. Decerno			
U. S. Mineral Surveyor.			
Claim located See location notices , 19			
Survey commenced May 3. , 19 24			
Survey completed			
Address of claimant Phelps Dogge Corporation, Morenci, Ariz.			
DATES OF AMENDED LOCATIONS.			
6—822			

Feet

MINERAL SURVEY NO. 3946

IRON QUEEN Lode.

Beginning at Cor. No.1, identical with Loc. Mon. On line 1-2 Stamboul lode of this Sur.

A porphyry rock 6 x 10 x 10 ins above ground, set 12 ins in the ground, chiseled with cross (x) 1 IQ - 3946, with md of stone 3 1/2 ft. base by 3 ft. high alongside, whence the 1/4 Cor. bet. Secs. 20-21 T. 4 S., R. 29 E., brs. N. 87° 27' E., 731.77 ft.

No other bearings are available.

Thence N.11° 02'W. Va. 13° 30' E.

185.7 To E. end center Stamboul lode of this Sur., hereinafter described.

266.3 Pipe line brs. southeasterly.

321.3 To W. end center, identical with Loc. Mon.

An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped W. Cr. I Q.

552.2 To Cor. No.2 Stamboul lode of this Sur. and Cor. No. 2 Sur. No.2857

**Tode*
Norfolk**, claimant herein, hereinafter described.

642.6 To Cor. No.2, identical with Loc. Mon. and Cor. No.3, Sur. No.2857

First West Extension of the Thompson lode. On line 1-2 Sur. No.2857

Norfolk lode, at S. 11° 02' E., 642.6 ft. ft. from Cor. No.1

A pine post 4 x 6 ins 4 ft. high, set firmly in the ground and surrounded with md. of stone, scribed 2 I Q - 3946, 3 F W E T-2857.

No bearings are available.

Thence N. 57° 57' E. Va. 13° 30' E.

415.0 Road brs, southeasterly.

940.0 Road brs. easterly.

1080.0 Road brs. northerly

1499.0 To Cor. No.2, Súr. No.2857, First West Extension of the Thompson lode, on line 3-4 Sur. No.2857 Iron King lode at S.11°39'E., 44.4 ft. from Cor. No.4 and N. 11° 39' W., 555.6 ft. from Cor. No.3

1500.0 To Cor. No.3, identical with Loc. Mon.

A linestone rock 7 x 14 x 12 ins. above ground, set 12 ins. in the ground, chiseled with cross (x) 3 I Q - 3946 with md of stone 3 1/2

Feet

MINERAL SURVEY NO. 3946

IRON QUEEN Lode, Cont'd.

ft. base by 3 ft. high alongside.

Cor. No.4 Sur. No.2857 Iron King lode brs. N. 10°42' W.,43.72 ft No other bearings are available.

> Thence S.11° 02' E. Va. 13° 30' E.

Intersect line 3-4 Sur. No. 2857, Iron King lode at S.11°39' E., 87.09 131.13 ft. from Cor. No.4 and N.11°39' W.,468.87 ft. from Cor. No. 3.

To E. end center, identical with Loc. Mon. 321.3

> An iron pipe 2 ins. diam by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped E. Cr. I.Q.

642.6 To Cor. No.4, identical with Loc. Mon.

> A porphyry rock 6 x 8 x 12 ins. above ground, set 12 ins in the ground, chiseled with cross (x) 4 I Q - 3946, with md of stone 3 1/2 ft. base by 3 ft. high alongside.

> > No bearings are available.

Thence S. 57° 57' W. Va. 13° 30' E.

550.0 Road brs southeasterly.

1160.0 Pipe line brs. southeasterly.

1500.0 To Cor. No. 1, the place of beginning.

STAMBOUL Lode.

Beginning at Cor. No.1,

A porphyry rock 6 x 12 x 10 ins. above ground, set 12 ins. in the ground, chiseled with cross (x) 1 S-3956 with md. of stone 3 1/2 ft base by 3 ft. high alongside, whence the 1/4 Cor. bet. Secs. 20-21 T. 4 S. R. 29 E. brs. N. 73° 13' E. 727.43 ft.

Loc. Mon. brs. S. 11° 02' E., 9.6 ft.

No other bearings are available.

Thence N. 11°02' W. Va. 13° 30' E.

To Cor. No.1 Iron Queen lode of this Sur., heretofore described. 180.8

366.5 To E. end center, identical with Loc. Mon.

Feet.

MINERAL SURVEY NO. 3946

STAMBOUL Lode.

An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped E. Cr. S.

447.1 Pipe line brs. southeasterly.

502.1 To W. end center Iron Queen lode of this Sur., heretofore described

735.0 To Cor. No.2, identical with Loc. Mon. and Cor. No.2 Sur. No.2857
Norfolk lode.

A porphyry rock 6 x 8 x 12 ins. above ground, set 12 ins. in the ground, chiseled with cross (x) 2 S - 3946, 2 N - 2857, with md of stone 3 1/2 ft. base by 3 ft. high alongside.

No bearings are available.

Thence S. 43° 43' W. Va. 13° 30' E.

304.0 Pipe line brs. southeasterly.

1500.0 To Cor. No.3, identical with Loc. Mon. and Cor. No. 3 Sur. No.2857

Norfolk lode, on line 1-2 Sur. No.2857 Margarita Lode. at. S.11°02'E.
622.9 ft. from Cor. No.1.

A quartzite rock 6x8x12 ins. above ground, set 12 ins. in the ground, chiseled with cross (x) 3 S - 3946, 3 N- 2857 with md of stone 3 1/2 ft. base by 3 ft. high alongside.

No bearings are available.

Thence S. 11°02' E. Va. 13° 30' E.

207.10 To Cor. No.2 Sur. No.2857 Margarita lode.

366.5 To W. end center, identical with Loc. Mon.

An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped W. Cr. S.

753.0 To Cor. No.4, identical with Loc. Mon.

A quartzite boulder in place, 12×14 ins. showing 5 ins. above ground, chiseled with cross (x) 4 S - 3946 with md of stone 3 1/2 ft. base by 3 ft. high alongside.

No bearings are available.

Thence N. 43° 43' E. Va. 13° 30' E.

Feet

MINERAL SURVEY NO. 3946

STAMBOUL Lode - Cont' d.

1500.00

To Cor. No. 1, the place of beginning.

LODE LINES.

As near as can be determined from the present developments, the veins of the several locations embraced in this claim, extend as follows from their respective discovery points;-

Iron Queen lode, 16 ft. N.57°57'E., and 1484 ft. S. 57°57' W. Stamboul lode , 440 ft. N. 43° 43' E., and 1060 ft. S. 43° 43' W.

AREA.

Acres. 20.656 V Total area Iron Queen lode --Area in conflict with: Sur. No. 2857 Iron King lode ---- 0.001 V 20.613

Total area Stamboul lode -----

The survey of each lode of this location is identical with the respective locations as staked upon the ground.

LOCATION.

This survey is located in the E 1/2 Sec. 20, and the N. W. 1/4Sec. 21 , T. 4 S., R. 29 E., G. & S. R. M.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements made upon, or for the benefit of each of the locations embraced in said mining claim by the claimant or its grantors is not less than five hundred dollars, and that said improvements consist of:

IRON QUEEN Lode.

No.1 The discovery point on the center line, 16 ft. from the center of line 3-4, A md. of stone on cropping.

No value.

No.2, A shaft, the center of which brs. from Cor. No.4 N. 15°30' W., 280.0, 4 x 6 ft. 10 ft. deep.

Value \$100.0

No.3, A tunnel, the mouth of which brs. from Cor. No. 1 N.24°45'E., 365 ft., running N. 70° E.,50 ft. to Sta.l, thence N. 70°E.,70 ft. to Sta. 2. From Sta.l a cross cut 4 x 6 ft. running N.40 W., 35 ft. to face. From Sta. 1, a cross cut 4 x 6 ft., running S. 40 ° E.,35 ft. to face. From Sta. 2, a cross cut 4x6 ft., running N. 30° E., 20 ft.

MINERAL SURVEY NO. 3946

EXPENDITURE OF FIVE HUNDRED DOLLARS.

IRON QUEEN Lode- Cont'd.

to face. From Sta. 2, A drift 4 x 6 ft. running N. 60 ° E., 100 ft to face.

Total value \$3150.0

STAMBOUL LODE.

No.1, The discovery tunnel, the mouth of which being the discovery point, on the center line 440 ft. from the center of line 1-2 4 x 6 ft. running S. 30° W., 50 ft. to face.

Value \$500.00

No.2 A tunnel, the mouth of which brs. from Cor. No.1 N. 82°30' W., 4 x 6 ft. running S. 25° W.,75 ft. to face.

Value \$750.0

No. 3 A tunnel, the mouth of which brs. from Cor. No.1 N. 59° W., 240 ft. running S. 15° W. 10 ft. to cave.

Value \$100.

No. 4 A cut, the mouth of which brs. from Cor. No.1 S. 64° 30° W., 675 ft. 4 1/2 ft. wide, 10 ft. face running S. 82° W., 15 ft. to face.

Value \$100.0

INSTRUMENT.

This survey was made with a Gurley mountain transit, the courses were deflected from the true meridian, as determined by direct solar observations. The distances were measured with a 500 ft. steel tape.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the corners were established by running around the claims.

The 1/4 Cor. bet. Secs.20-21 T. 4 S. R. 29 E., consists of an iron post with brass cap on top, stamped 1/4 S. 20, S. 21.

Sur. No.2857 First West Extension of the Thompson, Norfolk, Iron King and Margarita lodes. All that remains of Cor. Nos 3-4 Iron King and Cor. No. 2 Margarita are decayed stumps, 4 x 6 ins. surrounded with mds. of stone. Cor. Nos. 2-3 Norfolk lode were also in badly decayed condition. I set stones in the exact position of the original corners, chiseled with the number of the corner and the survey.

All courses and distances were found to be correct as approved .

MINERAL SURVEY No.3946

ADJOINING CLAIMS.

On the north by Sur. No.2857 Norfolk and First West Extension of the Thompson lodes.

On the east by Sur. No. 2857 Iron King lode.

On the west by Sur. No. 2857 Margarita lode.

SOLAR OBSERVATION.

Direct solar observation taken Monday May 5, 1924 at 2:28 P.M.

solar time, - sun bisected. Lat. 33.º 03! - Lon. 109.º 22!

Difference in time 9 h 45 m

Apparent declination 16° 15' 8.5" / 6'57 " 16° 22' 06"/

P = 90° - Decl = 73° 37' 54"

L = 33° 03' H = 51° 33' P = 73° 37' 54" 2) 158° 13' 54" S= 79° 06' 57"

S-L = 46° 03'57"

S-H = 27° 33'57"

9.8574012 9.6653628 0.0766550

Sin 1/2 A = $\sqrt{\sin(S-L)(S-H)}$

2) $\frac{0.2063273 \sqrt{19.8057463}}{9.9028731} = 53^{\circ} 05^{\circ} 30^{\circ} = 1/2 \text{ A}$ $106^{\circ} 11^{\circ} 00 = \text{A}.$

Cos L Cos H

180° - 106° 11' = S. 73° 49'W. > bearing of sun.

84° 51 = Ang. to left from sun.

S. 11° 02' E., Course of line.

Set up at Cor. No.3 Stamboul- F S to Cor. No. 4.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individua	ls employed by T.N. Stevens
	st in running, measuring, and marking the lines, corners, and
	ld notes of the survey of the mining claim of
	os Dodge Corsoration
	STAMBOUL Lodes
and showing the respective capacities in	which they goted
	I.P. Campbell , Chainman.
	, Chainman.
	, Awman.
	Flagman.
FINAL OAT	THS OF ASSISTANTS.
We, I. I.P. Campbell	
	, do solemnly swear that we assisted
T.N. Stevens, United S	States Mineral Surveyor, in marking the corners and surveying
the boundaries of the mining claim of	Phelms Dodge Corporation
known as the IRON QUEEN AND ST	
	having been surveyed by said mineral surveyor and under his
	all respects, to the best of omyknowledge and belief, faithfully
	oundary monuments established according to law and the instruc-
ions furnished by the United States Surveyo	r-General for Arizona
	Teneral for Arizona 9 Place Jehel Chainman.
	, Chainman.
	, Axman.
	, Flagman
Subscribed and sworn to	by the above-named persons before me this
day of	, 19
ly Commission Expires November 30, 1924	, 1924
express November 30, 1924	6 While
	Motory Culle

FINAL OATH OF U.S. MINERAL SURVEYOR.

I,T.N. Stevens	, U. S. Mineral Surveyor.
do solemnly swear that, in pursuance of instruct	ions received from the United States
Surveyor General for Arizona	datad
March 21, 1924 , , I have,	in strict conformity to the laws of the
United States, the official regulations and instruct	ions thereunder and the instructions
of said Surveyor General, faithfully and correctly	executed the survey of the Main
Claim ofPhelps Dodge Corporation	should the survey of the lyining
	- a
IRON QUEEN and STAMBOUL lod	es ·
situate in Copper Mountain	Mining District
Greenlee County,	Arizona i G : -
20 -21 Township No. 4 S., Range No.	, in Section s
and designated as Survey No. 3946	er h. g. x D. R. M.
in the foregoing field notes which converted.	as represented
in the foregoing field notes, which accurately show as distinctly marked by manufacture at the	the boundaries of said mining claim
as distinctly marked by monuments on the ground,	and described in the attached copy
of the location certificate, which was received by n	ne from the Surveyor General with
said instructions, and that all the corners of said su	rvey have been established and per-
petuated in strict accordance with the law, official	regulations and instructions there-
under; and I do further solemnly swear that the	foregoing are the true and original
field notes of said survey and my report therein,	and that the labor expended and
improvements made upon said mining claim by clai	mant orgrantors
are as therein fully stated, and that the character,	extent, location, and itemized value
thereof are specified therein with particularity and	full detail, and that no portion of
said labor or improvements so credited to this claim	has been included in the estimate
of expenditures upon any other claim.	
	111230
	N. Coenn
	U. S. Mineral Surveyor.
.0 5.	
	Tereus
U. S. Mineral Surveyor, before me RW La	ugwriting notary Public
wand for Forma grunty Cles	me this 20 th
day of 1924	
en commission	laugionthy
gares only 19 1928 What	3 H: (3. 60
6—1044	vina 10 teligne

U. S. SURVEYOR GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

DEPARTMENT OF THE INTERIOR,
OFFICE OF U. S. SURVEYOR GENERAL,

Ph	oenix, Arizona,
	July 25 , 1 924.
I, U. S. Surveyor General for	District of Arizona
do hereby certify that the foregoing transc	cript of the Field Notes, return and approval
of the Survey of the mining claim of	and approval
Phelps D	odge Corporation
, known as the	RON QUEEN and STAMBOUL lodes
, situa	te in Copper Mountain
Mining District,	Greenlee County,
Ari zona , in Sec	tion 8 20 - 21 , Township No. 4 S.
Range No. 29 E.	been correctly copied from the originals on
and that such reference is made therein to will perpetuate and fix the <i>locus</i> thereof. And I further certify that five hundred or improvements made upon said mining of	ft, 1 cut, 1 tunnels, 3 crosscuts.
and that no portion of said labor or improve expenditures upon any other claim. I further certify that the plat thereof file	ments has been included in the estimate of ed in the U.S. Land Office at Phoenix.
Arizona, is correct and in conf	ormity with the foregoing Field Notes.
United States Symposium	Charles M. Donohoe
o 6—168	General for Arizona.

SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR OFFICE OF U. S. SURVEYOR GENERAL

	Phoenix, Arizon	a,
	July	25, 192 4
I, U. S. Surveyor General for		
do hereby certify that the foregoing and heret		
Mining Claim of		
Phelps I	Odge Corporation	
		, known as the
IRON AUE		
situate in	opper Hountain	_ mining district,
Greenlee C	ounty,arizona	
in Section S 20 - 21 , Township	No, Range No	29_E
, designated as Survey No.		
executed by		
Surveyor,Nay 3 - 6	, 1924, under my ir	nstructions dated
Maroh 21 , 192	24, have been critically examined an	nd the necessary
orrections and explanations made, and the said		
re hereby approved. The certified copy of the		
n file in this office and a true copy of said cere	tified copy of said location certificate	is included and
nade a part of the transcript of the field notes.		
El Carrier de la	arles M. Donole	9 8 C .
	U. S. Surveyor General forAri	