## MINERAL SURVEY No. 3998

ARIZONA

Land District.

## FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

SHELDON MINING COMPANY	
New Strike, New State. Luther Junior Eagle Flo	rence.
Willetts, Monroe, The Penn, Lovekin, Dyson, and Walker	Ellinor lodes
Yayapai County, Arizona.	
Section 20-29-30, Township 121, Range	
Surveyed under instructions dated Jan. 14, 1	
by J.WILLIAM WAARA	
	S Mineral Surveyor.
Claim located SEE LOCATION SNOTICES.	.19
Survey commenced Jan. 10	19 26
Survey completed Feb. 6	19 26
Address of claimant Sheldon Mining Company O'Sullivan and Morga DATES OF AMENDED LOCATIONS. Pr	
See location notices	
G—822	

#### MINERAL SURVEY NO. 3998 '

Beginning at Cor. No.1, a granite stone 6x12x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled N S 1 3998 with cross on top for exact corner point, whence,

The S.E.Cor Sec. 32 T.13 N.E.1 W of the Gila and alt River Base and Meridian brs. N.51°-03'-30"E. 5282.7 feet.

A granite rock in place 3x3xl foot exposed and chiseled BxR N S 1 3998 brs. S.26°-56'E. 20.0 ft.

-Cor. No. 4 Euroka lode Sur. No. 1173 brs. S.

Thence S. 0°-39'E.

8 Intersect line 1-2 Capital lode Sur. No. 1359 N.56 -53'E.

1337.8 ft from Cor. No.2. and 402.8 ft from its intersection

with line 1-4 Eureka lode Sur. No. 1173.

357.0 EAST CENTER END, a mound of stone.

TO COR. NO.2, identical with Cor. No. 3 Eureka lode Sur. No. 1173 and Cor. No. 5 Eagle lode of this survey, a granite stone 8xfOxl2 inches exposed with a substantial mound of stone alongside; chiseled N S 2,E 5 3998, E No. 3 1173 with cross on top for exact corner point, whence

A granite rock in place 4x3xl foot exposed and chi-'sel'ed BxR E '5 3998 brs. S.69°-02'W. 14.9 ft.

A pine tree 20 inches in diameter, being bearing tree for Cor. No. 3 Eureka lode Sur. No. 1173, brs. No. 346-48'W. 19.3 ft. scribed BxT E 3'1173.

Cor. No. 4 Eureka lode Sur. No. 1173 brs. N.46°-

04'W. 493.1 ft. Thence S.51°-30'W.

895.0 Cross road brs. northwest to southeast. 1025.0 Cross Lynx Creek, flows southeasterly.

1136.7 TO COR. NO. 3, identical with Corners No. 4 Eagle lode,
No.2 Florence lode, No.1 Willetts lode, all of this survey,
a quartz diorite stone 8x10x28 inches long set twelve inches
in the ground with a substantial mound of stone alongside;

14.8

586.6

Lesino.

(1)

chiseled NXS 3,E 4, F 2, W 1 3998 with cross on top for exact corner point, whence,

A quartz diorite boulder 4x6x4 ft exposed and chiseled BxR F 2 3998 brs. N.31 -18'W. 29.1 ft.

Thence S.54°-35'W.

282.1 TO COR. NO. 4, a granite stone loxlox26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled N.S 4 3998 with cross on top for exact corner point.

No bearing available. Thence N.00°-39'V. Cross Lynx Greek, flows easterly, Cross road, brs west to east.

355.0 WEST CENTER END, a mound of stone.

402.8 Intersect line I-5 Florence lode, identical with line 3-4 Ellinor lode, both of this survey, S.48°-22'W. 117.5

> ft from Cor. Nos. 1 and 3 respectively. Cross small creek, flows southeasterly. TO COR. NO. 5, identical with Cor. No. 2 Capital lode Sur. No. 1359 situated on line 1-2 Ellinor lode of this survey, N.50 -14'W. 243.0 ft from Cor. No.2, a granite stone 10x12x15 inches exposed with a substantial mound of stone alongside; chiseled C No. 2 1359, N S 5 3998 with cross on top for exact corner point, whence,

A granite boulder being bearing rock for Cor. No. 2 Capital lode Sur. No. 1359 brs. N.1 -26'W. 18.8 ft.chiseled BxR C No.2 1359 Thence N. 56°-21'E.

Intersect line 1-4 Eureka lode Sur. No. 1173, N. 49°-31'E. 87.8 ft from Cor. No. 4. and 73.2 ft from its intersection with line 1-2 Capital lode Sur. No. 1359 at a point N.56°-53'E. 935.0 ft from Cor. No. 2 said Capital lode. TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Magnetic Variation 14 -30'E.

#### LUTHER JUNIOR Lode.

Beginning at Cor. No.1, a granite stone 8x14x30 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled I J 1 3998 with cross on top for exact corner point, whence,

140.0 175.0

525.0 712.0

1007.6

1345.8

.3

The S.E.Cor. Sec. 32 T.13 N.R.1 W brs.N.45°-49'-20"E. 4946.3 ft.

A granite rock in place 1x2x1 foot exposed and chiseled BxR L J 1 3998 brs. N.37°-53'W. 9.2 ft.

Cor. No. 2 Eberhart lode Sur. No. 1317 brs. S.40°-11'W. 502.4 feet.

Cor. No. 3 Eureka lode Sur.No.1173 brs. S.50°-20'W. 720.8 feet.

Seed exclotered obe! Thence 3.24-45'E. .xco esentil

.

- 29.0 Intersect line 1-2 Eberhart lode Sur. No. 1317, N.432-15'E. 490.8 feet from Cor. No.2 and 91.25feet from its intersection with line 2-3 Eureka lode Sur. No. 1173.
- Intersect line 2-3 Eureka lode Sur. No. 1174, N.53\_-54'E.

  710.3 feet from Cor. No.3,(464.1 feet from its intersection with line 1-2 Begle lode identical with line 3-4 this lode, and 86.29 feet from its intersection with line 1-2.

  Eberhart lode Sur. No. 1317.
- 246.6 NORTHEAST CENTER END, a mound of stone.
- 330.0 Cross road brs. southwest to northeast.
- 390.0 CCross Lynx Creek, flows northeasterly.
- 524.3 Witness corner to Cor. No.2, hereafter described.
- 541.6 TO POINT FOR COR. NO.2, situated on line 2-3 Hidden
  Treasure lode Sur. No.1603, S.51 -13 W. 138.1 feet from
  Cor. No.2; where it was impracticable to set a stone for
  corner due to point failing face of embankment, so f
  established a witness corner N.24 -45 W. 17.3 feet. a
  diorite stone 6x12x24 inches long set twelve inches in
  the ground with a substantial mound of stone alongside,
  chiseled W C L J 2 3998 with cross on top for exact corner point, whence,

No bearings available.

Thence S. 51 -13'W. (from true cor.pt.)

- 363.9 Intersect line 2-3 Eberhart lode Sur. No. 1317, S.380-
- 30'E..429.3 feet from Cor. No.2. pt.for
  TO POINT FOR COR.NO.3, identical with Cor. No.2 Eagle
  lode of this survey, and, situated on line 2-3 Hidden

Treasure lode Sur. No.1603, S.51 -13'W. 607.2 feet from

(3)

Cor. No.2; where it was impracticable to set a stone for corner due to point falling in Lynx Creek, so I established a witness corner N.24°-45'W. 22.4 feet, a diorite rock in place 3x2xl foot exposed with a substantial mound of stone alongside; chiseled W C E J 3 3998, E 2 with cross on top for exact corner point, whence (from true Cor.pt.)

A rock in place 6x2x4 feet exposed and chiseled BxR E 2 3998 brs. S.83 -14'E. 48.8 feet.

Thence N.24\_-45'W.(from true cor.pt.)

22.4 Witness cor. to 'Cor.No.3 of this lode heretofore described

40.0 Cross road brs southwest to northeast.

252.3 SOUTHWEST CENTER END, A mound of stone.

285.0 Northeast Center end Eagle lode of this survey.

442.5 Cor. No.2 Eberhart lode Sur. No. 1317.

517.7 Intersect line 2-3 Eureka lode Sur.No.1173, N.53 -54 E.

246.2 feet from Cor. No.3.

533.5 TO COR.NO.4 identical with Cor. No.1 Eagle lode of this survey, a granite stone 6x10x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled E l L J 4 3998 with cross on top for exact corner point, whence,

A granite rock in place 3x2xl foot exposed and chiseled BxR L J 4 3998 brs. N.6--27'W. 16.7 feet.

Cor.No.3 Eureka lode Sur.No.1173 brs. S.50°-28'W. 249.7 feet.

Thence N.50°-16'E.

471.1 TO THE PLACE OF REGINVING. All corners are identical with their respective locations. Variation at all corners 14° 30'E.

Beginning at Cor. No.1 identical with Cor. No. 4 Luther Junior lode of this survey, previously described, whence,

The S.E.Cor Sec. 32 T.13 N.R.1 W brs. N.46°-12'-30"E. 5415.9 feet.

Therice S, 24°-45'E.

15.2 Intersect line 2-3 Eureks lode Sur.No.1173, N.53 -54 E.

246.2 feet from Cor. No.3.

4

- 91.0 Cor. No. 2 Eberhart lode Sur. No. 1317.
- 248.5 NORTHEAST CENTER END, a mound of stone.
- 281.2 Southwest center end, Luther Junior lode of this survey a mound of stone.
- 493.5 Cross road brs. southwest to northeast.
- 511.1 Witness corner to Cor. Nos 2 and 3 Eagle and Luther Junior/respectively, previously described.
- 533.5 TO POINT FOR COR. NO. 2, identical with foint for Cor.No.

  3 Luther Junior lode of this survey, previously described.

  Cor.No. 3 Hidden Treasure lode Sur. No. 1603 brs. S.51°-13'W.

  546.0 from the true corner point. w.C. previously described, brs. N.24'45'W. 22.4ff.

  Thence S. 508-47'W. (from true Cor.pt.)
- -315.0 Cross Lynx Creek, flows northerly.
- 546.66 Intersect line 1-2 Monroe lode of this survey, identical with line 1-4 Rowe lode Sur. No. 1700, and line 3-4 Hidden Treasure lode Sur. No. 1603, S.29°-26'-30"E. 4.2 feet from Cor.Nos. 1,1,and 3 respectively, of said lodes.
- 691.66 Cross Lynx Creek, flows easterly.
- 1389.6 TO COR. NO. 3 identical with Cor. No.5 Monroe lode of this survey, situated on line 1-2 Willetts lode of this survey, N.24°-45'W. 79.0 ft from Cor. No.2, a porphyry stone 8x12x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled E 3,M 5 3998 with cross on top for exact corner point.

No bearing available.

Thence N. 24°-45'W.

- 11.3 Intersect line 1-2 Rowe lode Sur. No. 1700, S.51°-14'W.
  841.0 ft from Cor. No.1.
- 234.6 Northeast Center end Willetts lode of this survey, a mound of stone.
- 285.0 SOUTHWEST CENTER END, a mound of stone.
- 2 Florence lode, 3 New State lode, all of this survey, previously described.

Thence N. 51°-30'E.

- 111.7 Cross Creek, flows southeasterly.
- . 241.7 Cross road brs. northwest to southeast.

1136.7 TO COR. NO.5 identical with Cor. No.2 New State lode of this survey, and Cor. No.3 Eureka lode Sur. No.1173, previously described.

Thence N. 50°-28'E.

except Cor.No.5/
except Cor.No.5/
249.7 TO THE PLACE OF BEGINNING. All corners/are identical with
their respective locations. Variation at all corners 14 -

# Monroe lode.

Beginning at Cor. No.1, identical with Cor.

No.1 Rowe lode Sur.No. 1700 and Cor. No.3 Hidden Treasure
lode Sur. No. 1603, a diorite stone 6x12x 14 inches ex
ppsed with a post 4x4x4.5 feet long set in the ground
alongside; chiseled M 1 3998, R 1 1700, H Tal603 with

cross on top for exact corner point, whence,

A diorite rock in place 5x4x5 ft exposed and chiseled BxR R 1 1700,M 1 3998 brs. S.32°-44°E. 100.0 ft.

The S.E.Cor. Sec. 32 T.13 N.R.1 W.brs. N.41°-57'E.

Thence S.29°-26',-30"E.

- 4.2 Intersect line 2-3 Eagle lode of this survey, N.50°-47'E.
  842.94 ft. from Cor. No.3.
  - , 90.0 Crosscreek, flows easterly.
  - 300.0 NORTHEAST CENTER END, a mound of stone.
  - 320.0 Cross Creek, flows northerly.
  - 597.6 TO COR. NO.2 identical with Cor. No.5 The Penn lode of this survey, and Cor. No.4 Hidden Treasure lode Sur.No. 1603 and Cor. No. 4 Rowe lode Sur. No. 1700, a granite stone 6x14x14 inches exposed with a substantial mound of stone alongside; chiseled M. 2, T. P. 5,3998, H. T. 4 1603, R. 4 1700 with cross on top for exact corner point, whence,

A nail in blaze of pine tree 24 inches in diameter scribed BxT R 4 1700 brs. S.50°-23'W. 10.8 ft.

Thence S. 51°-29'W.

120.0 Cross creek ,flows northerly.

327.0 Intersect line 3-4 The Penn lode of this survey, S.27°-54'E.

16.6 ft from Cor. No.4.

- 1475.0 Cor. No. 3 Rowe lode Sur. No. 1700, whence Cor. No. 4 brs. N.29°-54'W. 590.6 ft.
- 1479.9 TO COR. NO. 3, a porphyry stone 6x12x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled M 3 3998 with cross on top for exact corner point, whence, AOM. SESE, O.Ft.

A porphyry rock in place 3x2x0.5 ft exposed and chiseled BxR M 3 3998 brs. S.51 -13'W. 13.9 ft.

Thence N. 29°-26'-30"W.

- 297.6 SOUTHWEST CENTER END, a mound of stone.
- 469.5 Intersect line 2-3 Willetts lode of this survey, S.48°-18 W. 638.8 ft.from Cor. No.2.
- 591.4 TO COR. NO.4 identical with Cor. No. 2 Rowe lode Sur. No. 1700, a porphyry stone 6x10x12 inches exposed, with a substantial mound of stone alongside; chiseled M 4 3998, R 2 1700 with cross on top for exact corner point, whence,

A porphyry reef 6x10x4 feet exposed and chiseled BxR R 2 1700, M 4 3998 brs. S.59°-48'E. 37.4 ft.

> A porphyry reef 3x3x3 ft. exposed and chiseled BxR R 2 1700 brs. N.74°-51'E. 48.5 ft.

Cor. No. 2 Willetts lode of this survey brs. N. 59°-18' E. 624.4 ft.

## Thence N.52°-13'E.

an neors after 637.4 TO COR. NO.5, identical with Cor. No. 3 Eagle lode of this survey, previously described, situated on line 1-2 Willets lode of this survey, N.24 -45'W. 79.0 ft. from Cor. No.2.

## Thence N.50°-30'E.

- 698.8 Cross creek, flows easterly.
- except Cor.No.5/
  843.8 TO THE PLACE OF BEGINNING. All corners/are identical with their respective locations. Variation at all corners 14°-30'E. They live cor. Hos. S. and A respectively

The Penn Lode.

Beginning at Cor. No.1, identical with Cor. No.1 Hidden Treasure lode Sur. No. 1603, Cor. No. 2 Golden

FOR B TO OFF. - NO. 7. E FIRST FORK

No.1
Fleece/lode Sur. No. 1589, 'Cor. No. 2 Golden Fleece No.4
lode Sur. No. 1589, a granite stone 6x10x12 inches exposed
with a substantial mound of stone alongside; chiseled
T P 1 3998, H T 1 1603, G F 1-2 1589, G F 4-2 1589, with
cross on top for exact corner point, whence,

8

The S.E.Cor. Sec. 32 T.13 N.R.1 W brs. N. 34°-23' 40"E. 5225.0 ft.

Cor. No. 3 Golden Fleece No. 4 lode Sur. No. 1589 brs.
S.24°-21'E. 475.1 ft.

Thence S.27°-54'E.
300.0 NORTHEAST CENTER END, a mound of stone.

310.0 Cross creek, flowsnortherly

465.2 Intersect line 3-4 Golden Fleece No.4 lode Sur. No. 1589.

N.45°-02'E. 30.8 ft. from Cor. No.3, whence Cor.No.4 of Intersect line 2-3 Stockbridge lode Sur.No.1841 N .11°-00'W. 310.515te from Cor. No.27 and 27.5 ft. from its intersection with line 2-3 of this lode.

598.8 TO COR. NO. 2a granite stone 6x10x26 inches long set

twelve inches in the ground with a substantial mound of

stone alongside; chiseled T P 2 3998 with cross on top for

exact corner point, whence, Cor. No. 3 Stockbridge lode
Sur.No. 1841 brs. S.9 -35'E. 28711 ft.

A Quartz diorlte boulder 2x6x2 feet exposed and

chiseled BxR T P 2 3998 brs. S.71 -46'W. 24.9 ft.

Thence S.49°-21'W.

8.2 Intersect line 2-3 Stockbridge lode Sur. No. 1841 N.11°
09'We 283.0 ft; from Sur. No.3.

20.0 Cross creek, flows northerly.

20.0 Cross creek, flows northerly.

1491.4 TO COR. NO.3, a diorite stone 10x12x24 inches long set

twelve inches in the ground with a substantial mound of
stone alongside; chiseled T P 3 3998 with cross on top

for exact corner point, whence, Cor. No. 2 Vinegar Lode
Sur. No. 1841 brs. N.53°-48'E. 351.3 ft.

A porphyry rock in place, 2x1x0.3 ft. exposed and
chiseled BxR T P 3 3998 brs. S.34 -58'E. 14.5 ft.

Thence N. 27°-54'W.

ess.s Cross arres,

298.8 SOUTHWEST CENTER END, a mound of stone.

435.0 Cross creek, flows northeasterly.

582.2 Intersect line 2-3 Monroe lode of this survey, identical w with line 3-4 Rowe lode Sur.No. 1700, S.51 -29'W. 327.0 feet from Cor.Nos.2 and 4 respectively.

598.8 TO COR. NO.4, a granite rock in place 2x2x0.5 feet exposed with a substantial mound of stone alongside; chiseled

T.P 4 3998 with cross on top for exact corner point.

No bearings available.

(8)

Thence N. 54°-22'E.

220.0 Cross creek, flows northerly.

324.4 TO COR. NO. 5 identical with Cor. No.2 Monroe lode of this survey, Cor. No. 4 Hidden Treasure lode Sur. No. 1603, and Cor. No. 4 Rowe lode Sur. No. 1700, previously described.

Thence N. 47°-57'E.

except Cor. No.5

1168.7 TO THE PLACE OF BEGINNING. All corners/are identical with
their respective locations. Variation at all corners 14°30'E.

#### New Strike lode.

Beginning at Cor. No.1, a granite stone 8x12

x 24 inches long set twelve inches in the ground with a

substantial mound of stone alongside; chiseled NS1 3998

with cross on top for exact corner point, whence,

ASPE, DIL 25 ft, from Cor. Ho.A.

The S.E.Cor. Sec. 32 T.13 N.R.1 W. brs. N.54°-16'-20"E. 6625.5 ft.

Cor. No.1 Ellinor lode of this survey brs. S.51°-

#### Thence S. 8 -40'E.

- and line 2-3nCapital lode Sur. No. 1359, S.50°-14'E.

  75.57 ft. from Cor. No.1 Ellinor, and N.50 -14'W. 177.03

  feet from Cor. No. 2 Capital lode Sur. No. 1359.
  - 265.0 NORTHEAST CENTER END, a mound of stone.
- 350.0 Cross creek, flows easterly.
- Florence lode both of this survey, S.48°-22'W. 206.4 ft. from Cor.Nos. 3 and 1 respectively.
  - 658.0 TO COR. NO. 2, a granite stone 8x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled N S 2 3998 with cross on top for exact corner point, whence,

A granite rock in place 4x4x2 feet exposed and chiseled BxR N S 2 3998 bbs. S.42 -13'W. 18.1 ft.

No. 32 -32'E. 262.9 ft.

#### Thence S. 42 -41'W.

- 140.0 Cross road, brs. west to east.
- 410.0 Cross creek, flows easterly.
- 1027.51 Intersect Northeasterly end line Copper No.2 lode unsurveyed, N.44°-47'W. 67.34 ft. from the southeast Corner of said lode.and S.44°-47'E. 522.66 ft from the N.E.Cor. of said lode.
- 1314.0 Intersect line 3-4 Florence lode of this survey, S.24°-48'E. 211.25 ft. from Cor. No.4.
- 1319.37 TO COR. NO. 3 identical with Cor. No. 1 Lovekim lode of this survey, a granite stone 6x10x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled L 1, N S 3 3998 with cross on top for exact corner point, whence,

L 1 3998 brs.N.49°-35'E.51.6 ft.

Cor.No.3 Florence lode of this survey brs. S.26°-53'E. 136.4 ft.

The S.E.Cor Copper No. 2lode unsurveyed brs.

N. 55 -48'E. 296.6 ft.

Thence N.23°-28'W.

213.3 TO COR. NO.4 being Southwest center end of this lode, and identical with Cor.No.4 Florence lode of this survey, a granite stone 8x12x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled F 4 N S 4 3998 with cross on top for exact corner point, whence,

A porphyry rock in place 6x8x4 ft exposed and chiseled BxR N S 4 3998 brs. N.35°-41'W. 46.7 ft.

Thence N.8 -40'W.

- 50.0 Cross creek, flows northeasterly.
- 70.0 Cross road brs. southwest to northeast.
- 182.15 Intersect line 4-5 Ellinor lode of this survey N.50\_-14'W.
  154.3 ft. from Cor. No.4.
- 363.0 TO COR. NO.5, situated on northeasterly end line Copper No.2 lode unsurveyed, N.44\_-47'W, 546.5 ft. from the southeast (10)

es. 44°47'E 435ff. from the N.E. Cor thereof.

corner of said lode, a granite stone 8x8x24 inches long

set twelve inches in the ground with a substantial mound

of stone alongside; chiseled N S 5 3998 with cross on

top for exact corner point, whence,

A granite rock in place 3x3x0.5 ft exposed and chiseled BxR N S 5 3998 brs. S.73°-47'W. 11.4 ft.

Thence N. 41°-15'E.

60.0 Cross creek, flows easterly.

1068.0 Cross creek, flows easterly.

1361.46 Intersect line 1-2 Ellinor lode of this survey, identical and line 2-3 Capital lode Sur. No. 1359, S.50°-14'E.

10.37 ft. from Cor. No.1 Ellinor lode, and N.50°-14'W.

242.23 ft. from Cor. No. 2 Capital lode.

.1418.0 •TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°-

## Ellinor lode.

torms rot

Beginning at Cor. No.1 situated on line 2-3 Capital lode Sur.No.1359 N.50°-14'W. 252.6 ft. from Cor. No.2, and on line 1-2 Champion lode Sur. No. 1354, N.47°-40'E. 149.2 ft. from Cor. No.2, a granite stone 6x12x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled E 1 3998 with cross on top for exact corner point, whence,

cross on top for erect corner reint.

The S.E.Cor. Sec. 32 T. 13 N.R. 1 W. brs. N.54°-15'E. 6683.2 ft.

A granite rock in place 3x2xl foot exposed and chise chiseled BxR E 1 3998 brs. N.67°-49'E. 34.9 ft.

Cor.No.1 New Strike lode of this survey brs. N. 51°-35'E. 57.8 ft.

#### Thence S.50°-14'E.

- 10.37 Intersect line 1-5 New Strike lode of this survey N.41°-15'E. 1361.46 ft. ftom Cor. No. 5.
- 75.57 Intersect line 1-2 New Strike lode of this survey, S.8°-40'
  E. 85.19 ft. from Cor. No.1.
- 199.6 NorthEAST CENTER END, a mound of stone.

- 252.6 Cor.No. 2 Capital Lode. Sur. No. 1359, identical with Cor. 5 New State lode of this survey.
- 495.6 TO COR. NO.2, a granite stone 6x10x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled E 2 3998 with cross on top for exact corner point, whence,

A granite boulder 6x4x3 feet exposed and chiseled BxR E 2 3998 brs. S.29°-26'W. 42.0 ft.

Thence S.51 -36'W.

- 79.2 Witness Corner to Cor. No.3 hereafter described.
- 121.8 TO POINT FOR COR.NO.3, identical with point fem Cor. No.1

  Florence lode of this survey, where it was impracticable to set a stone for corner due to point falling in creek bed, so I established a witness corner N.51°-36'E. 42.6 ft. a granite rock in place 2x2xl foot exposed with a substantial mound of stone alongside; chiseled W C E.3 3998 with cross on top for exact corner point. No bearings available.

Thence S,48°-22'W.

- 117.5 Intersect line 4-5 New State lode of this survey, S.O°-39'
  E. 309.2 ft. from Cor. No. 5.
- 206.4 Intersect line 1-2 New Strike lode of this survey, S.8°-40'E. 572.5 ft. from Cor. No.1.
- 747.2 Cross road brs. east to west.
- 767.2 Cross creek, flows easterly.
- 1285.1 Intersect Northeasterly end line of the Copper No.2 lode unsurveyed, S.44 -47'E. 348.3 ft. from the Northeast Cor. of said lode.
- 1377.2 TO COR. NO. 4 identical with Cor. No.5 Florence lode of this survey, a porphyry stone 8x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled E 4 F 5 3998 with cross on top for exact corner point. No bearings available.

Thence N.50°-14'W.

- 25.0 Cross creek, flows northeasterly.
- 70.0 Cross road brs. southwest to northeast.
- 154.3 Intersect line 4-5 New Strike lode of this survey, S.8 -40'E.

180.85 ft. from Cor. No.5

303.0 SOUTHWEST CENTER END, Amound of stone.

Intersect northwesterly side line Copper No.2 lode unsurveyed 344.9 identical with southeasterly side line Grasshopper lode unsurveyed, S.45°-18'W. 124.7 ft. from the N.E.Cor of said Copper No. 2lode identical with the most easterly corner of said Grasshopper lode.

TO COR. NO.5 identical with Cor. No.1 American Flag lode 489.7 Sur. No. 1355 End Cor. No. 2 Shelton lode Sur. No. 1355, and the most northerly corner Grasshopper lode unsurveyed, a porphyry stone 6x10x12 inches exposed with a substantial mound of stone alongside, chiseled E 5 3998, A F No.1 1355, S No. 2 1355 with cross on top for exact corner point, whence;

A granite rock in place 4x2xl foot exposed and chiseled BxR E 5 3998 brs. S.18°-00'W. 38.2 ft.

A granite rock in place 2x1x1 foot exposed and chiseled S 2 1355 brs. N.2°-43'W. 58.6 ft. Cor. No. 1 Shelton lode Sur. No. 1355 brs. N. 49°E. 1199.2 ft. The most easterly corner of the Grasshopper lode unsurveyed brs. S.88 -36'E. 200.0 ft..

Thence N.48 -29'E.

1190.0 Cross creek, flows easterly.

1198.4 Intersect line 1-4 Shelton lode identical with line 2-3 Short Cut lode, both Sur. No. 1355, N. 45 -30'W. 10.8 ft. from cor. Nos. 1 and 2 respectively, whence Cor. No. 2 Shelton lode brs. S.49°-00'W. 1199.2 ft. and Cor No.1 Short Cut lode brs. N. 442-22'E. 150.1 ft.

1348.8 TO COR. NO.6, identical with Cor. No. 2 Champion lode Sur. No. 1354 and Cor. No. 1 Short Cut lode Sur. No. 1355, a granite-stone 6x10x12 inches exposed with a substantial mound of stone alongside; chiseled S C No.1 1355, C No.2 1354, E 6 3998 with cross on top for exact corner point. Cor. No. 2 Short Cut lode Sur. No. 1355 brs. S. 44°-22'W. 150. 1ft. No bearings available.

Along line 2-1 Champion lode Sur. No. 1354/ TO THE PLACE OF BEGINNING. All corners are identical with except Cor. Nos. 3 and 6 149.2 their respective locations. Variation at all corners 14°-30'E.

(13)

29.6

155.0

210.0

239.6

349.6

Florence lode.

Beginning at the point for Cor. No.1 identical with Point for Cor. No. 3 Ellinor lode of this survey previously described from which point I established a witness corner S.24°-48'E. 29.6 ft. a granite rock in place 3x2x2 ft. exposed with a substantial mound of stone alongside; chiseled W C F 1 3998 with cross on top for exact corner point. No bearings available. The S.E.Cor. Sec. 32 T.13 N.R.1 W. brs. N.50°-05'-40"E. 6698.4 ft. from true cor. point. Thence S.24.°-48'E. (from true. cor.pt.) Witness corner previously described . Cross road brs. southwest to northeast. Cross creek, flows easterly. NORTHEAST CENTER END, a mound of stone. TO COR. NO. 2 identical with Cor. Nos. 3 New State lode, 4 Eagle lode and 1 Willetts lode all of this survey, and

previously described.

Cor. No.4 New State lode, this sur., brs.S.54°-35'W.282.1ft.

Thence S.48 -22'W.

1428.56 Intersect line 1-2 Lovekin lode of this survey, S.56°-57'.

E. 136.74 ft. from Cor. No.1.

1499.4 TO COR. NO. 3 identical with Cor. No.4 Willetts lode of this survey, a porphyry stone 8x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled F 3 W 4 3998 with cross on top for exact corner point. No bearings available.

The S.E. Cor Copper. No.2 lode. brs. N. 32 -29'E. 341.9 ft.
Thence N. 24°-48'W.

80.66 Intersect southeasterly side line Copper No.2 lode unsurveyed, S.45°-18'W. 305.92ft. from the S.E.Cor. and 26.02 feet from its intersection with line 1-2 Levekin lode of this

110.0 SOUTHWEST CENTER END, A MOUND OF STONE.

128.4 Intersect line 1-2 Lovekin lode of this survey, S.56°-57'E.

9.32 ft. from Cor. No.1.

138.35 Intersect line 2-3 New Strike lode N.42°-41'E. 5.37 ft. from Cor. No.3.

LOOK OX XX SOUTHWEST CHNEEK LIND XX EX BORRIO OF SPOREXX

349.6 TO COR. NO. 4 identical with Cor. No.4 New Strike lode of

1741

this survey, previously described whence location monument three foot base and three ft. high brs. N.24°-48'W. 0.25 ft. Thence N. 48 -16'E. TO COR. NO.5 identical with Cor. No. 4 Ellinor lode of this 122.2 survey, previously described. Thence N. 48 -22'E. Intersect northeasterly end line Copper No. 2 lode unsurveyed 92.1 N. 44 -47'W. 241.7 ft from the S.E.Cor. and 174.36 ft. from its intersection with line 2-3 New Strike lode of this survey. 610 Cross creek, flows southeasterly. 630 Cross road brs. west to east. 1170.8 Intersect line 1-2 New Strike lode of this survey, N.8°-40'W. 85.5 ft.from Cor. No.2. 1259.7 Intersect line 4-5 New State lode of this survey, N.O\_-39'W. 402.8 ft. from Cor. No.4. except Cor. No. 4 and Cor. No. 5 1377.2 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14° 30'E. Willetts lode. Beginning at Cor. No. 1 identical with Cor. Nos. 2 Florence lode, 3 New State lode, 4 Eagle lode all of this survey, previously described, whence, The S.E.Cor. Sec. 32, T.13 N.R.1 W brs. N.476-15'E... 6797.8 ft. Thence S. 24°-45'E. this survey Southwest center end Eagle lode, previously described. NORTHEAST CENTER END, a mound of stone. 311.9 535.2 Intersect line 1-2 Rowe lode Sur. No. 1700, N.51 -14'E. 640.0 ft. from Cor. No.2. 546.5 Cor. No. 3 Eagle lode identical with Cor. No. 5 Monroe lode both of this survey, previously described. Gor. No.4 Monroe lode brs. 5.52° 13'W 637.4 ft. 625.5 TO COR. NO. 2, a porphyry stone 6x8x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled W 2 3998 with cross on top for

1751

BxR W 2 3998 brs. S.56°-59'E. 29.8 ft.

A porphyry boulder 3x2x1 foot exposed and chiseled

exact corner point, whence,

# 10 as	angeli i	Thence S.48°-18'W.	
6	37.8	Intersect line 2-3 Rowe lode Sur. No. 1700, S.29 -54'E.	
aid?	to eff	121.7ft. from Cor. No.2	
6	38.8	Intersect line 3-4 Monroe lode of this survey, S.29°-26'-	
		30"E. 121.9 ft. from Cor. No.4.	
15	00.0	TO COR. NO. 3, a granite stone 6x8x26 inches long set	
	1 .12	twelve inches in the ground with a substantial mound of	
VIII S	plat i	stone alongside; chiseled W 3 3998 with cross on top	
		for exact corner point, whence,	
		An oak tree 24 inches in diameter and scribed BxT	
	78 gK',	W 3 3998 brs. N.6°-32'W. 17.6 ft.	
	313.6 343.7	Thence N.24 -45'W.  SOUTHWEST CENTER END, a mound of stone.  Intersect line 2-3 Lovekin lode of this survey, S.46 -53'W.	
	4.5.	226.0 ft. from Cor. No.2.	
6	27.2	TO COR. NO. 4 identical with Cor. No.3 Florence lode of	
0	ers 14	this survey, previously described.	
		Thence N.48°-22'E.	
	70.84	Intersect line 1-2 Lovekin lode of this survey, N.56=-57'W.	
	too d	275.46 ft. from Cor. No.2.	
14	499.4	TO THE PLACE OF BEGINNING. All corners are identical with	
		their respective locations. Variation at all corners 14°	
	7.69.1-	30'E. ard W 1:9.W SI, V, 15 . Dog . reg. Y. 2 sal	
		Lovekin lode.	
		Beginning at Cor. No.1 identical with Cor.	
	.bedi	No.3 New Strike lode of this survey, previously described,	
		whence, .Ample to broom a .City Arthieu de Arthurit C. Eli	
	10/0/2	The S.E.Cor. section 32 T.13 N.R.1 W brs. N.48°-21'-	
		30"E. 8261.8 ft.	
95	ores le	The S.E.Cor. Copper No.2 lode unsurveyed brs. N.55°	
		-48'E. 296.6 ft.	
	tes s	Thence S.56°-57'E.	
	9.32	Intersect line 3-4 Florence lode of this survey, N.24 -48	
		W. 128.4 ft. from Cor. No.3.	
		Intersect the southeasterly side line of the Copper No.2 lode	3
		unsurveyed, S.4518'W. 279.9 ft. from the S.E.Cor. and N.45°-18'E. 1213.1 ft. from the S.W.Cor. NORTHEAST CENTER END, a mound of stone.	
	110.0	(16)	

136.74 Intersect line 2-3 Florence lode identical with line 4-1 Willetts lode both of this survey, N.48°-22'E. 70.84 ft. from Cor.Nos. 3 and 4 respectively.

412.2 TO COR. NO. 2, a granite stone 8x8x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled L 2 3998 with cross on top for exact corner point, whence,

A porphyry rock in place 3x2x3 feet exposed and chiseled BxR L 2 3998 brs. S.68--13'E. 24.7 ft.

Cor.No.4 Willetts lode of this survey brs. N.70°-01'W.

302.0 ft.
Cor.No.4 Monroe lode of this survey brs. N .69°-17'E./
Thence S. 46 -53'W.

226.0 Intersect line 3-4 Willetts lode of this survey, S.24°-45'E. 283.5 ft. from Cor. No.4/

1375.5 TO COR. NO. 3 identical with Cor. No. 2 Dyson lode of this survey, a granite stone 8x8x24 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled L 3 D 2 3998 with cross on top for exact corner point.

Thence N.56°-57'W.

184.6 SOUTHWEST CENTER END, a mound of stone.

298.8 Northeast center end, Dyson lode.

342.0 Intersect the southeasterly side line Ninety Eight lode unsurveyed. S.53°-40'W.el60.5ft from the S.E.Cor.

360.9 Cross creek, flows northeasterly.

370.9 Cross old road brs.southwest to northeast.

485.9 TO COR. NO.4 identical with Cor. No. 1 Dyson lode of this survey, a granite stone 6x12x26 inches long set twelve inches in the ground with a substantial mound of stone alongside; chiseled D 1 L 4 3998 with cross on top for exact corner point, whence,

A granite boulder lxlxl foot exposed and chiseled BxR D 1 3998 brs. S.18 -39'E. 11.5 ft.

The S.W.Cor. Copper No.2 lode, identical with S.E. Cor. Ninety Eight\_lode, both unsurveyed, brs. N.86°-12'E. 250.5 ft.

identical with S.W.Cor. Ninety Eight lode, unsurveyed, Cor.No.2 Ninety Seven lode Sur.No.1631, brs. S. 32 -16'
W. 369.3 ft.

Thence N. 49°-49'E.

Intersect Southwest end Copper No. 2 lode, identical with line Northeast end Ninety Eight lode, both unsurveyed, N. 45°-20'W. 149.2 ft. from the S.W. and S.E. cors respectively.

450 Cross road brs. southwest to northeast.

· 890 Cross creek, flows northeasterly.

1395.1 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°

·Dyson lode.

Beginning at Cor. No.1 identical with Cor. No. 4 Lovekin lode of this survey, previously described, whence, The S.E.Cor. Sec. 32 T.13 N.R.1 W. brs. N. 48 -34'-20"E. 9656.0 ft.

Thence S. 56°-57'E.

115 Cross old road brs. southwest to northeast.

125 Cross creek, flows northeasterly.

143.9 Intersect the southeasterly side line of the Ninety Eight lode unsurveyed, N.53°-40'E.394.4 ft. from the S.W.Cor.

187.1 NORTHEAST CENTER END, a mound of stone.

301.3 Southwest Center end Lovekin lode.

485.9 Tô COR. NO.2 identical with Cor. No.3 Lovekin lode of this survey, previously described.

Thence S. 33 -49'W.

1500.0 TO COR. NO.3, a granite stone 8x10x24 inches long set twelve inches in the ground with a substantial mound of stone alongside, chiseled D 3 3998 with cross on top for exact corner point, whence,

An oak tree 12 inches in diameter and scribed BxT D 3 3998 brs. S.23°-25'W. 7.2 ft.

Thence N. 56 -57'W.

298.8 SOUTHWEST CENTER END, a mound of stone.

530.0 TO COR. NO.4 situated on line 2-3 Ninety Seven lode Sur.N o.

1631 N.36°-33'E.127.0 ft. from Cor. No.3 and S.36°-33'W.

11:32.6 ft. from Cor. No.2., a granite stone 8x14x24 inches
long set twelve inches in the ground with a substantial

(781

mound of stone alongside; chiseled D 4 3998 with cross on top for exact corner point, whence,

A granite rock inplace 3x2x1 foot exposed and chiseled BxR D 4 3998 brs. N.70°-20'W. 34.5 ft.

Cor. No.3 Brooklyn lode Sur. No. 1996 brs. S. 56°-51'E. 125.8 ft.

Thence N. 35°-30'E.

1115.0 Cross creek, flows northeasterly.

Intersect line 1-2 Ninety Seven lode Sur.No.1631, identical with Southwesterly end line Ninety Eight lode unsurveyed,
N.46°-55'W. 21.0 ft. from Cor.No.2 and S.W.Cor. respectively.

1170 Cross road brs. southwest to northeast.

1501.3 TO THE PLACE OF BEGINNING. All corners are identical with their respective locations. Variation at all corners 14°-30'E.

#### LODE LINES.

As near as can be determined from the present developments, the veins on the respective lodes extend as follows from their discoveries;

New State lode. N.56°-28'E. 530.0 ft. and S.56°-28'W. 815.8 ft.

Luther Junior lode. N.46°-17'E. 461.2 ft. and S.46°-17'W. 20.0 ft.

Eagle lode N.50°-47'E. 870.0 ft. and S.50°-47'W. 519.6 ft.

Monroe lode N.51°-29'E. 100.0 ft. and S.51°-29'W. 1379.9 ft.

The Penn lode N.49°-21'E. 200.0 ft. and S.49°-21'W. 1291.4 ft.

New Strike lode N.38°-21'E. 280.0 ft. and S.38°-21'W. 1203.1 ft.

N.48°-53'E. 30.0 ft. and S.48°-53'W. 1470.0 ft.

Florence 1 odd. N. 48°-22'E. 750.0 ft. and S. 48°-22'W. 749.4 ft.

Willetts lode N.48°-18'E. 1070 ft. and S.48°-18'W. 430.0 ft.

Lovekin lode N.42°-02'E. 180.0 ft. and S.42°-02'W. 1172.3 ft.

Dyson lode.
N. 33°-49'E. 220.0 ft and S. 33°-49'W. 1280.0 ft.
(19)

AREAS		
NEW STATE LODE	acres	acres
Total area	2-405 ° 0.192 °	17.026
LUTHER JUNIOR Lode		
1011	-0.307	5.616
EAGLE LODE	THE SECTION AND ADDRESS OF THE PARTY OF THE	
Total area	0.146	16.621
MONROE LODE		
Total area	19.726 1.437 0.040 e 0.000	19.760
THE PENN LODE		
Monroe lode of this survey  Monroe lode of this survey exclusive of its conflict with Rowe lode Sur. No	0.061 0.002 0.157 0.061	19.511
Total area	0.760	/

ELLINOR LODE	
Total area	***
FLORENCE LODE	The second second
Total area	
WILLETTS LODE	
Total area 20.631  Area in conflict with  Rowe lode Sur.No.1700 1.516  Rowe lode Sur.No.1700 exclusive of its conflict with Monroe lode of this survey	
LOVEKIN LODE	
Area in conflict with  Florence lode of this survey 0.100  Willetts lode of this survey 0.914  Ninety Eight lode unsurveyed 0.569  Copper No.2 lode unsurveyed 2.811  Copper No.2 lode unsurveyed exclusive of its conflict with Florence lode  of this survey 2.797	
DYSON LODE	
Total area	
LOCATION	
This survey is located in sections 20-29-30 T121N.R.1	
W. unsurveyed, of the Gila and Salt River Base and Meridia	
within the Prescott National Forest, Walker Mining Distric	t
Yavapai County, State of Arizona.	

EXPENDITURE OF FIVE HUNDRED DOLLARS

I hereby certify that the value of the labor and improvements made upon or for the benefit of the several locations embraced in this survey by the claimant or

its grantors is not less than five hundred dollars for each claim and that said improvements consists of;

No.1 Discovery Shaft, the center of which brs. S.56°
28'W. 530ft. from the Northeast center end, 4x6x8 ft. deep
waved. Value \$80.00

No.2 a shaft, the center of which brs. N.50°E. 935.0 feet from Cor. No.4, 4x8x200 ft deep.

Value \$6000.00

No.3 a shaft, the center of which brs. N.46°-00'E. 957 ft. from Cor.No.4, 4x6x40 ft. deep.

Value \$500.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur.No. 1354 (Described under Common Improvements)

Value \$600.00

#### LUTHER JUNIOR Lode

No.1 Discovery cut, the center of which brs. N.46°17'E. 20 ft. from the southwest center end, 4x17x10.5 foot
face, brs. north.

Value \$100.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur.
No.1354

Value #600.00

#### EAGLE Lode

No.1 Discovery cut and tunnel, the mouth of the tunnel brs. N.50°-47'E. 519.6 ft. from the southwest center end, cut, 4x20x10 foot face, tunnel 4x6x35 ft. long caved, brs. north.

Value cut \$100.00 Tunnel 350.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur.

No. 1354. Value \$600.00

#### MONROE Lode

No.1 discovery shaft, the center of which brs. S.51°-29'W. 100 ft. from the northeast center end, 4x6x10 ft. deep caved.

Value \$100.00

No. 2 a cut and tunnel, the mouth of cut brs. S.51°-

29(W. 65 ft. from the northeast center end. thence
S.59°-03'W. 36 ft. mouth of tunnel, 160.8 ft. to sta.No.1
incline
thence S.45°-27'W. 60.0 ft/shaft to left 6 ft deep.and
raising to the surface about 60 ft.;120 ft to cave-in.

4x6 ft having a total length of 280.8 ft. Shaft is old
work, while tunnel was cleaned out and retimbered.

Value cut and tunnel
\$2808.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur. No. 1354. Value \$600.00

. THE PENN Lode.

No.ldiscovery cut, the face of which brs. S.49°-21'W.

200 ft. from the northeast center end, 4x16x10 foot face.
brs. S.W. Value \$100.00

To be accredited to this lode is an equal unidvided 1/30th interest in Improvement No.1 Champion lode Sur. No. 1354. Value \$600.00

NEW STRIKE Lode.

No.1 discovery cut, the face of which brs. S. 38°-21'W.
280 ft. from the northeast center end, 4x18x10 foot face
brs. S.W. Value \$100.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur. No. 1354. Value \$600.00

ELLINOR Lode.

No.1, Discovery cut, the face of which brs. S.48--53'W.

30 ft. from the northeast center end, 4x16x10 foot face.

brs. north.

Value \$100.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur. No.1354. Value \$600.00

FLORENCE Lode.

No.1 discovery cut, the face of which brs. N.48°-22'E.
749.4 ft. from the southwest center end, 4x14x10 foot
face. brs. S.W. Value \$100.00

To be accredited to this lode is an equal undivided

1/30th interest in Improvement No.1 Champion lode Sur.
No. 1354 Value \$600.00

WILLETTS Lode

No.1 discovery shaft, the center of which brs. N.48°-18'E. 430 ft. from the southwest center end, 4x6x8 ft. deep. Value \$80.00

To be accredited to this lode is an equal undivided 1/3oth interest in Improvement No.1 Champion lode Sur.

No. 1354.- Value \$600.00

LOVEKIN Lode

No.1 discovery cut, the face of which brs. S. 42°-02'W. cut
180 ft. from the northeast center end, 4x26x11 foot face
tunnel 4x6x2.5 ft. brs N.E.
Value \$100.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur. No. 1354. Value \$600.00

DYSON Lode.

No.1 discovery cut, the face of which brs. S. 33°-49(
W. 220 ft. from the northeast center end, 4x19x10.5 foot
face. brs. S.E. Value \$100.00

To be accredited to this lode is an equal undivided 1/30th interest in Improvement No.1 Champion lode Sur.

No. 1354. Value \$600.00

#### COMMON IMPROVEMENT

Improvement No.1 Champion lode Sur.No.1354, designated as such for brevity in reporting, the center of which brs. N.37°-08' W 369.8 ft.fromCor.No.1Ellinor lode, is the main shaft of the Sheldon Mining Company, claimants of this survey. It is situated centrally in a group of 30 patented and unpatented claims owned by it. The shaft is 850 feet deep 1½ compartment, and is now being enlarged to 2½ compartments, said enlargement having reached the 350 foot level at the present date. A winze extends down from the 850 level to the 1150 foot level. This shaft is so situated that drifts and cross-cut run from its lower levels will develope all of the claims embraced in this

survey as well as the patented claims upon which it is situated, and also will develope seven claims to the north west of the shaft and contiguous to the patented claims. I consider the shaft a common improvement and of such a nature as to redound to the benefit of the following lode claims;

American Flag, Sur. No. 1355; Shelton, Sur. No. 1355; Short Cut, Sur. No. 1355; Champion, Sur. No. 1354; Eink, Sur. No. 1354; Fortune, Sur. No. 1354; Eureka, Sur. 1173; Capital, Sur. No. 1359; First North Extension Capital Sur. No. 3237; Mid-Night Snap, Sur. No. 3655, White House Sur. No. 2369; Ninety Seven lode, Sur. No. 1631; New State, Luther Junior, Eagle, Monroe, The Penn, New Strike, Ellinor, Florence, Willetts, Lovekin, and Dyson of this survey; and M & S, M & S No. 1 Copper lode, Copper Lode No. 1, Copper Lode No. 2, Copper lode No. 3, Copper lode No. 4 all unsurveyed, all contiguous claims owned by the claimant of this survey.

The old shaft is 4x9 and is being enlarged to 4x13 ft.

Total depth of enlarged shaft 350 ft.

Value

\$18000.00

To be accredited to each claim of this survey is an equal undivided 1/30th interest in the above mentioned improvement.

Value \$600.00

#### OTHER IMPROVEMENTS

A house, 15x40 ft. long frame construction, the S.E. Eagle lode/ gable brs. N.31°-15'E. 615 ft. from Cor. No.3/brs.west.

A house, 24x42 ft. frame construction, the S.W.Cor. brs. N.80°E. 30 ft from Cor. No.2 Ellinor lode of this survey. brs. northwest.

A cut, the face of which brs. S.33-49'W. 235 ft. from the N.E.Center end Dyson lode, 4x15x10 foot face.brs.

A cut, the face of which brs. S.33°-49'W. 205 ft. from the N.E.Center end Dyson lode, 4x16x10 foot face, and tunnel 4x6x8 ft long brs. S.E.

#### ADJOINING CLAIMS.

This survey is bounded on the northwest by the Ninety seven lode Sur. No. 1631, American Flag lede, Shelton lode and Short Cut lode all Sur. No. 1355, Champion lode Sur. No. 1354, Capital lode Sur. No. 1359, Eureka lode Sur. No. 1173, all owned by the Sheldon Mining Company, the Ninety Eight lode unsurveyed, Chas. H. Dunning and John unsurveyed Harlan claimants, Copper No. 2 lode, Arizona Victory Mining Company, claimant, and Grasshopper lode, unsurveyed John Harlan claimant; on the northeast by the Eberhart 10 lode Sur. No. 1317, Zehnxbukaxakainani; xmaxkbaxaanikaasi hyxthe Hidden Treasure lode Sur. No. 1605, John Duke claimant, Golden Fleece No. 4 lode Sur. No. 1589, Bed Rock Mining Company, claimant, Stockbridge lode Sur. No. 1841, John Ryan trustse, claimant.on the southeast by U.S. land and Porphyry No.1 and Forphyry No.2 lodes, XXXX all unsurveyed, and Raven lodes, W.P.McLeod claimant, on the southwest by the Brooklyn lede Sur. No. 1996, Fairbanks Morse Co. cleiment and U.S.Land. The Rowe lode Sur. No. 1700 is entirely covered by the claims of this survey.

#### INSTRUMENT

This survey was made with a Lietz Light Mountain transit No. 9503. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 500 foot steel tape.

#### REPORT

The southeast corner of Sec. 32 T.13 N.R.1 W. is a stone set and chiseled as described in the field notes of said survey. This is the nearest corner of the Public Survey that can be found and identified, diligent search having been made for corners which come within the prescribed limits of this survey.

Sur.No.1173

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of line 3-4 of this survey, and the section corner tie.

Sur.No. 1317

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of the section corner tie.

Sur.No. 1355

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and
survey. I do not agree with the course and distance of
line 1-2 Shelton lode, and line 1-2 Short Cut lode and
the section corner ties.

-org er Sur. No. 1354 e sidt mintojba eremos od

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course of line 1-2 Champion lode, and the tie to the section corner.

Sur. No. 1359

perly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of of line 1-2 and 2-3, and the section corner tie.

Sur. No. 1589

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of line 3-4 of this survey and the section corner tie.

Sur. No. 1603

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey, except where otherwise reported in this survey. I do not agree with the course and distance of lines 2-3 3-4 and 4-1 and the section corner tie.

Sur.No. 1631

The corners adjoining this survey are stones pre-

perly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of line 1-2 and 2-3 and t

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not agree with the course and distance of any lines of this survey and the section corner tie.

Sur. No. 1841

The corners adjoining this survey are stones preperly set and chiseled with the number of the corner and
survey. I do hot conflict with this survey.
Sur. No. 1996.

The corners adjoining this survey are stones properly set and chiseled with the number of the corner and survey. I do not conflict with this survey.

Ninety Eight, Copper No.2, Grasshopper, Porphyry No.1

Porphyry No.2 and Raven lodes.

The corners of these lodes are stone monuments substantially built and of proper size, except for the last three lodes. The claimant has been unable on several occasions to show me his monuments, although attempts have been made in the presence of witnesses.

The discrepancies found existing between the claims as marked by the location monuments and as described in the location notices are due to errors in the location notices.

The discrepancies between the lines of this survey and prior approved surveys are due to errors in the latter.

S-4 and 4-1 and the section corner tie.

Jus. Mineral Surveyor

to rot series with the course and distance of lines 2-3

-erg ecore ers veryon sint galato; bs everyon en

# FINAL OATHS FOR SURVEYS.

### LIST OF NAMES.

A list of the names of the individuals em	ployed by J. William Waara	
United States Mineral Surveyor, to assist in		
boundaries described in the foregoing field not		
Mining Company		
New Strike. New Sta	te, Luther Junior, Eagl	lo Tomana
known as the Willetts, Monroe, Th	ne Penn, Lovekin, Dyson,	and Ellinor lodes
and showing the respective capacities in which		
	Temp Gamel	Cit t
		, Chainman.
		, Chainman.
		Axman.
		, Flagman.
FINAL OATH	S OF ASSISTANTS	
xxe, I. Temp Gamel		
*	Т	
and	, do solemnly swear that waassisted	J. William Waara
, United States	Mineral Surveyor, in marking the	corners and surveying
the boundaries of the mining claim ofSh	sidon wining company	
37		
New Strike, New State known as the Willetts, Monroe, The	Penn, Lowekin, Dyson,	, Florence, and Ellinor lodes
represented in the foregoing field notes as having	ig been surveyed by said mineral s	unmorron and an Jan 1.
lirection; and that said survey has been in all re	spects, to the best of our knowledge	e and belief, faithfully
and correctly executed, and the corner and bounda	ry monuments established according	to law and the instruc-
OFFICE ALL COMMON COMMO		
ions furnished by the United States <del>Surveyor Ge</del>		
	Temp yaml	, Chainman.
		, Chainman.
		, Flagman.
Subscribed and sworn to by t	he above-named persons before me	this 12 th.
day of April	, 19 26	
	Mary a. /	Brance
	77 40 47 00, 71	
Ty'commission expires	Notary Pu	blic
		6-1043

# FINAL OATH OF U. S. MINERAL SURVEYOR.

I, J.William Waara	II. S. Mineral Surveyor
do solemnly swear that, in pursuance of instructions receive	ved from the Office Codestrol Engineer
at Phoenix Arizona, dated	January 14 1026
I have, in strict conformity to the laws of the United Stat	es the official regulations
tions thereunder, and the instructions of said Office Cadas	tral Engineer faithfull
executed the survey of the Mining Claim of Sheldon	Mining Company
New Strike, New State, Luther Junior, Ea Monroe, The Pemn, Lovekin, Dyson, and El	Linor lodes
situate in Walker	Mining District
Yavapai County,	Arizona. in Section
125 N. Range No. 1	W. Incingrated
and designated as Survey No. 3998	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
in the foregoing field notes, which accurately show the bound	aries of said mining claim as 1. 4.
marked by monuments on the ground, and described in the	attached copy of the least'
cate, which was received by me from the Office Cadastral	Engineer with add to the location certifi-
that all corners of said survey have been established and I	corporated in the state of the
the law, official regulations and instructions thereunder; and	The family and accordance with
foregoing are the true and original field notes of said survey	1 do further solemnly swear that the
labor expended and improvements made upon said mining cl	and my report therein, and that the
grantors are as therein fully stated, and that the showest	aim by claimant orlts.
grantors are as therein fully stated, and that the character, thereof are specified therein with particularity and the land	extent, location, and itemized value
thereof are specified therein with particularity and full deta	all, and that no portion of said labor
or improvements so credited to this claim has been included any other claim.	in the estimate of expenditures upon
any other claim.	
Jlou	U. S. Mineral Surveyor.
Subscribed and sworn to by the said J. William W.	aara
U. S. Mineral Surveyor, before me a Notary P	ublic
	this 12 th.
day of April , 192 6	
Mary	a. Brown Notary Public
My commission	Notary Public
My Commission expires.  My Commission Expires July 17, 1926	

## U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

# Department of the Interior, PUBLIC SURVEY OFFICE OFFICE OF U. S. SURVEYOR GENERAL,

Phoenix, Arizona,	
<u>March 31</u> , 19 28	
I, U. S. Surveyor-General for DEFICE CADASTRAL ENGINEER At Phoenix, Arizona,	
do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey	
of the mining claim of	
Sheldon Mining Company	
NEW STRIKE, NEW STATE, LUTHER JUNIOR, EAGLE, FLORENCE, known as the WILLETTS, MONROE, THE PENN, LOVEKIN, DYSON, and ELLINOF	1006
situate in	
Mining District, Yavapai County, Arizona	
in Section 20, 29, 30, Township No. 128 N., Range No. 1 W., Unsur, and	
designated as Survey No3998, has been correctly copied from the originals on file in	
this office; that said Field Notes furnish such an accurate description of said mining claim as will, if	
ncorporated into a patent, serve fully to identify the premises, and that such reference is made therein	
o natural objects or permanent monuments as will perpetuate and fix the locus thereof.	
And I further certify that five hundred dollars' worth of labor has been expended or improve- or for each of nents made upon said mining claims by claimant. or 118. grantors, and that said improvements	
onsist of 5 shafts, 9 cuts and 3 tunnels, total value \$10,718, also	
11-30ths of the value of a common improvement designated as No.	
l on the Champion lode, Sur. No. 1354, \$6600, making a total of	
\$17,318.	
nd that no portion of said labor or improvements has been included in the estimate of expenditures	
oon any other claim.	
I further certify that the plat thereof, filed in the U.S. Land Office atPhoenix,	
rizona, is correct and in conformity with the foregoing Field Notes.	
John D. Adams	
United States Surveyor General for. Office CADASTRAL ENGINEER	

# SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

### DEPARTMENT OF THE INTERIOR

OFFICE OF U. S. SURVEYOR GENERAL

PUBLIC SURVEY OFFICE

	Phoenix, Arizona
	March 31 , 192 8.
I, U.S. Surveyor General for	OFFICE CADASTRAL ENGINEER . at Phoenix, Arizona,
do hereby certify that the foregoing	and hereto attached Field Notes and Return of the Survey of the
Mining Claim ofS	heldon Mining Company
NEW STRIKE, NEW STATE,	LUTHER JUNIOR, EAGLE, FLORENCE, WILLETTS, IN, DYSON, and ELLINOR lodes
	Walker mining district,
Yavapai	County,Arizona
in Sections , 20,29,30 ,,	Township No. 12½ N., Range No.1 W., Unsur.
, designated	as Survey No3998
executed byJ. W:	illiam Waara , U. S. Mineral
Surveyor, January 1	)- February 6 , under my instructions dated
January 14	, 1926, have been critically examined and the necessary
corrections and explanations made, a	nd the said Field Notes and Return, and the survey they describe,
	copy of the location certificate filed by the applicant for survey is
	of said certified copy of said location certificate is included and
made a part of the transcript of the f	
GOVERNMENT HE INTING OFFICE	U. S. Surveyor General for Office Cadastral Engineer

AMENDMENT TO FIELD NOTES MINERAL SURVEY NO. 3998.

Conflict Raven lode, unsurveyed, with Willetts lode, Sur. No. 3998.

Beginning at Cor. No. 2, Lovekin lode, Sur.No. 3998, thence N. 69° 17' E. 600.9 ft. to Cor. No. 4

Monroe lode, said survey, thence S. 29° 26' 30" E.,

along line 4-3 said Monroe lode, 121.9 ft. to its intersection with line 2-3 willetts lode, said survey, thence S. 48° 18' W., along line 2-3 said willetts lode, 861.2

ft. to Cor. No. 3 Willetts lode, thence N. 24° 45' W.,

along line 3-4 Willetts lode, 343.7 ft. to its intersection with line 2-3 Lovekin lode, thence N. 46° 53' E.,

along line 3-2 Lovekin lode, 226 ft. to the place of beginning, containing 4.982 acres.

With Monroe and The Penn lodes, Sur. No. 3998.

Beginning at Cor. No. 3 Monroe lode, Sur. No. 3998, thence N. 29° 26' 30" W., along line 3-4 said lode, 175 ft. to a point, thence N. 53° 23' E. 1465 ft. to a point, thence S. 29° 26' 30" E. 125.6 ft. to an intersection with line 4-5 The Penn lode, Sur. No. 3998, at N. 54° 22' E. 316.6 ft. from Cor. No. 4 thereof, 126 ft. to an intersection with line 2-3 Monroe lode, Sur. No. 3998, at S. 51° 29' W. 7.9 ft. from Cor. No. 2 thereof, and 600 ft. to a point, thence S. 55° 23' W. 330 ft. to a point on line 3-4 The Penn lode, thence N. 27° 54' W., along line 3-4 The Penn lode, 465 ft. to the point of intersection of line 3-4 The Penn lode with line 2-3 Monroe lode, thence S. 51° 29' W., along line 2-3 Monroe lode, thence S. 51° 29' W., along line 2-3 Monroe lode, 1152.9 ft. to the place of beginning, containing 8.477 acres.

即 .

uetai

S. 100

53 1 E.

#### DEPARTMENT OF THE INTERIOR,

PUBLIC SURVEY OFFICE,

Phoenix, Arizona, January 5, 1929.

I, Office Cadastral Engineer, at Phoenix, Arizona, do hereby certify that the foregoing correctly describes the conflict between the Raven lode, unsurveyed, and the Willetts lode of Survey No. 3998, and the conflict between the Porphyry No. 1 lode, unsurveyed, and the Monroe and The Penn lodes of Survey No. 3998, as described in the "Application to Purchase" dated October 1, 1928, of the Sheldon Mining Company.

I further certify that the plats of said Survey No. 3998, on file in this office, the General Land Office and the Phoenix Land Office, have been correctly amended in red ink to show such conflicts, and that such amendment is made in accordance with letter "N" of December 22, 1928, from the Commissioner of the General Land Office.

> Cadastral Engineer. Office

1.9 24. 2201