

4-683

MINERAL SURVEY No. 4023

Arizona Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Eleanor Godwin

KNOWN AS THE

Victory No. 1 and Victory No. 2 lodes
Dos Cabezas Mining District,
Cochise County, Arizona

Sections 1 and 2, Township 15 S, Range 27 E

Surveyed under instructions dated Sept 15, 1926.

by John A. Rockfellow
U. S. Mineral Surveyor.

Claim located See Notices, 19

Survey commenced January 22, 1927

Survey completed February 5, 1927

Address of claimant W.D. Simmons, Atty in Fact
for claimant of Gibbs & Gibbs attorneys,
DATES OF AMENDED LOCATIONS. 106 N. Central Ave
Phoenix
Ariz.

SURVEY NO 4023

Feet	<p>Victory No.1 lode.</p> <p>Beginning at Cor.No.1, the N.E. corner. Set a porphyry 8x6 ins. 18 ins. long, 12 ins. in the ground, chisel a cross (x) at exact point and VI 1-4023. Raise a mound of stone along-side.</p> <p>Whence: Cor. of location, a stone monument, bears N 41° 57' E 589.0 ft.</p> <p>The $\frac{1}{4}$ Sec. Cor. on South boundary of Sec. 36 T. 14 S., R 27 E bears N 74° 21' E 897.9 ft.</p> <p>X B R 1-4023 chiseled on a granite reef bears N 19° 34' E 62.9 ft.</p>
Feet	<p>Thence S 36° 08' W Va. 13° 30' E</p> <p>Gulch 4 ft. wide, course S. Easterly.</p>
267.0	<p>To Cor. No. 2 Set a quartzite rock 24x10x5 ins., 6 ins. in ground to bed rock: chisel cross (X) at exact point, and VI 2-4023 and raise a mound of stone alongside.</p> <p>Whence: Cor. of location, on a stone monument, bears S. 39° 45' E. 95.5 ft.</p> <p>X B R 2-4023 chiseled on a diorite reef bears S. 16° 17' W. 53.16 ft.</p> <p>X B T 2-4023 Scribed on a blaze on a mesquite tree 5 ins. in diam. bears N 24° 40' W 5.88 ft.</p> <p>Thence N. 39° 45' W. Va. 13° 25' E.</p>
1097.6	<p>S. Center End, chisel a cross (X) on a small projection of quartzite bed rock and build around it a monument of stone 4 ft. base $3\frac{1}{2}$ ft. high.</p> <p>Whence, S Center End of location a stone monument bears N. 39° 45' W. 35.1 ft.</p>
309.0	<p>Monument. S.C. End of location.</p>
344.1	<p>To Cor. No. 3, identical with location and with corner No. 3 of Victory No. 2 lode of this survey, a stone monument built on a granite reef. Chisel a cross (X) at exact point, ^{on the reef, and} VI, V2 on the respective lodes. Raise a monument of stone along-side.</p> <p>Thence N 36° 07' E Va 13° 50' E</p>
602.1	

- 813 Barbed wire fence bears Ely. and Wly.
- 816.5 To Cor. No. 4 on South boundary of Sec 36 T 14 S, R 27 E
 Set a porphyry rock 10 X 5 ins. 19 ins. long. 12 ins. in the
 ground; chisel a cross (X) at exact point and V1 4-4023
 Raise a monument of stone along-side.
 Whence: Cor. of location a stone monument bears
 N 36° 07' E 1052.8 ft.
 X B R 4-4023 chiseled on a granite 36 X 28 X 14 ins,
 bears N 53° 22' W 43.55 ft.
 X B R 4-4023 chiseled on porphyry bed rock in reef
 bears S 8° 25' E 7.30 ft.
 Thence N 89° 45' E Va. 13° 15' E
- 353.4 N Center End and corner No 5 Set a porphyry rock
 6 X 4 ins. 19 ins. long, 13 ins. in the ground: chisel a
 cross (X) at exact point, and V1 5-4023
 Whence: N. Center End of location a stone monument
 bears N 35° 31' E 670.0 ft.
 X B R 5-4023 chiseled on a granite rock 36 X 36 X 30 ins.
 bears ~~S 22° 30' E 95.0 ft.~~ *N 30° 08' E 52.35 ft.*
~~X B R chiseled on a granite 30 X 13 X 6 ins. bears N 20° 38' E 25.8 ft.~~
- 309.0 To Cor. No. 1, the place of beginning.
 Victory No. 2 lode.
 Beginning at Cor. No. 1, the S corner: Set a granite
 7 X 6 ins. 24 ins. long, 18 ins. in ground: Chisel a cross (X)
 at exact point and V2 1-4023. Raise a monument of stone
 along-side.
 Whence: Cor. of location, a stone monument,
 bears S 38° 15' W 367.0 ft.
 The $\frac{1}{4}$ Sec. corner bet. Secs: 1-2 T 15 S., R 27 E.
 bears S 38° 15' W 370.4 ft.
 X B R 1-4023 chiseled on a granite in place
 48 X 16 X 10 ins. bears N 75° 11' W 31.05 ft.
 Thence N 39° 45' W Va 13° 20' E
- 301.0 S.W. Center End. Set a small stake and surround it
 with monument of stone 4 ft. base, 3 ft. high.

Whence: S.W.Center End of location a stone monument bears S44°46'W 363.0 ft.

366.17 Intersect line bet.Secs. 1-2,T 14 S,R 27 E,at N 0°29' W 572.43^{ft.} from $\frac{1}{2}$ Sec.Cor.

602.0 To Cor.No.2 Set a porphyry rock 8 X 6 ins^{24 ins.} long, 10 ins.in ground to bed rock.Chisel a cross(X) at exact point and V2 2-4023 and raise a monument of stone along-side.

Whence: Cor.of location,a stone monument bears N 68°28' W 181.5 ft.

X B R 2-4023 chiseled on rock in place in a porphyry reef 18 X 14 X 6 ins. bears N 79°36'W 25.55 ft.

X B R 2-4023 chiseled on porphyry 24 X 6 X 10 ins. bears N 16°18'E 42.30 ft.

Thence N 45°04'E Va 13°40'E

209.1 Intersect line bet.Secs.1-2 at No0°29'W 901.44 ft.from $\frac{1}{2}$ Cor 1499.25 To Cor.No.3,identical with location and with Cor. No.3,Victory No.1 lode of this Survey,previously described.

Thence S 39°45' E Va 13°50'E

258.0 Stone monument.N.E.Center End of location.

293.1 N.E.Center End identical with S Center End Victory No.1 lode,previously described.

Whence: The corner of location bears N 39°45'W 35.1 ft.

594.1 To Cor.No.4 Set a quartzite rock 14 X 14 X 12 ins., 4 ins.in ground to bed rock.Chisel a cross(X) at exact point and V2 4-4023,and raise a monument of stone along-side.

Whence:The corner of location a stone monument bears S 39°45'E 103.5 ft.

Cor.No.2 of Victory No.1 lode of this survey bears S 39°45'E 8 ft. This corner previously described and connected with bearing rocks.

Thence S 44°46'W Va 13°25'E

1500. To Cor.No.1 the place of beginning.

AREA.

	Acres
Victory No.1 lode	13.800
Victory No.2 lode	20.499

AREA IN CONFLICT WITH SEC. 2 (PATENTED LAND)
T. 15 S., R. 27 E.

0.564

LOCATION.

This claim is located in Dos Cabezas Mining Dist.
 Cochise County, Ariz., in Secs. 1 and 2 of T 15 S, R 27 E,
 G. and S.R.M.

ADJOINING CLAIMS.

On the north of Victory No.1 lode ^{Sec. 36 T 14 S.,}
 R 27 E, patented land Claimant Mrs. Jas. Riggs.
Also Victory No. 3 lode, unsurveyed, claimed by this claimant
 On the S.W. end of Victory No.2 lode, ^{Sec. 2, T15 S.,}
 R 27 E, patented land Wm. De Board, Claimant.

On the East of the Victory No.1 and Victory No.2,
 the Bull Hill lode unsurveyed, Claimant, Mr. Bean.

Lode Lines.

The presumed course of the Veins or Lodes is as
 follows:

On the Victory No.1 lode

From Discovery Shaft. N 36° 08' E 443.6 ft to N.C.E.
 and S 36° 08' W 654.0 ft. to S.C.E.

On the Victory No.2 lode

From Discovery Shaft N 44° 46' E 371 ft. to N.E.C.E.
 and S 44° 46' W 1129 ft. to S.W.C.E.

Improvements.

I certify that the value of labor and improvements
 made upon or for the benefit of each of the locations
 embraced in said mining claim by the claimant or her
 grantors is not less than five hundred dollars, and
 said improvements consist of :

On the Victory No. 1 Lode

No. 1 Discovery shaft the center of the easterly side of which
 bears S 36° 08' W, 443.6 ft. from N. Center End.

Shaft irregular; average 6 X 5 ft. 8ft deep.
 Value \$75.00
 No. 2 From a point on lode line at N 36°08' E 306.6 ft.
 from S.C.E.
 A shaft, the center of which bears S 48°44' W 98 ft.
 Shaft 6 X 6 ft. now 4 ft. deep, once deeper.

Value \$40.00
 No. 3 A shaft the center of which bears N 47°45' E 74 ft.:
 Shaft 6X.6 ft. 3 ft. deep, once deeper.

Value \$30.00
 No. 4 A shaft the center of which bears N 46°10' E 118.5 ft.:
 Shaft 6 X 4 ft. 20 ft. deep.

Value @ \$10.00 per ft. \$200.00
 No. 5 A shaft the center of which bears N 47°35' E 143.5 ft.:
 Shaft 6X 4 ft. 3 ft. deep, once deeper.

Value \$20.00
 No. 6 From a point on line 1-2 at S 36°08' W 729.0 ft. from
 Cor. No. 1.

A shaft the center of footwall of which bears N 53°52' W
 19 ft.. Shaft 6 X 4 ft. 52 ft. deep, timbered for 16 ft.
 from top. A short drift is said to extent westward from
 bottom, but could not be measured on account of water in
 shaft. This shaft, on an incline to the west, is at the
 base of a round hill or quartz blow-out, known as Bull Hill,
 seamed with gold bearing quartz: the center of hill is
 approximately the S. Center End of Victory No. 1, and N.
 Center end of Victory No. 2 lodes, and has a radius of
 about 350 to 400 ft., with a height of 100 ft. or more.
 The shaft is sunk for the purpose of getting under the
 hill and developing the quartz seams for the common
 benefit of the two lodes.. Hence this work is rated as
 Common Improvement.

Value of Shaft at \$11. per ft. \$572.00
 Timbering 2 in. lagging and
 3 square sets 720 ft. at .05 36.00
 Truck hauling form Willcox

20 miles \$20.00
 Labor in timbering 20.00
 Total value Improvement #6 \$648.00
 One-half assigned to this lode - - - - - 324.00
 Total value improvements Victory No. 1 lode \$689.00

On the Victory No. 2 lode.

No. 1 Discovery shaft the center of which bears from N.E. Center end S 44°46' W 371 ft.: Shaft 7 X 6 ft. 6 ft. deep, once much deeper.

Value \$75.00

No. 2 A shaft the center West side of which bears from N.E. Center End S 44°46' W 316 ft. Shaft 6 X 4 ft. 18 ft. deep.

Value at \$10.00 per ft. \$180.00

one-half common improvement, No. 6 on Victory No. 1 lode, 324.00

Total value improvements on

and for Victory No. 2 lode \$579.00

Other Improvements.

On Victory No. 1 lode:

From point on lode line at N 36°08' E 625' ft. from S. Center End:

A shaft the center of which bears S 53°32' E 59 ft.

Shaft 10 X 10 ft., 2 ft. deep, once deeper. This old work under former location. Claimant unknown.

Instrument.

This Survey was made with a Young & Sons Mountain Transit No. 6855 provided with a Smith Solar Attachment. The courses were deflected from true meridian as determined by direct solar observations. The distances were measured with 500 ft. and 50 ft. steel tapes.

The disagreement between these field notes and the Public Survey lines as recorded are due to error in the latter.

Report

The $\frac{1}{4}$ Cor. on the south boundary of Sec. 36; is a stone set in the ground surrounded by a circle of stones and chiseled $\frac{1}{4}$ on the north. The $\frac{1}{4}$ Cor. between Secs. 1 and 2 is a stone set in the ground in a circle of stones with a monument alongside and chiseled $\frac{1}{4}$ on the East. The closing corner of Secs. 1 and 2 is a rock set in the ground in a circle of stones and chiseled one notch on the East and five notches on the West. The Corner of Secs. 35 and 36 is a mound of stone, the marked stone missing.

Washington, D.C.

Dec. 30, 1887

John A. Rockwell
 U. S. Mineral Surveyor.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by John A. Rockfellow
United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
boundaries described in the foregoing field notes of the survey of the mining claim of _____

known as the Eleanor Godwin
Victory No. 1 and Victory No. 2 Lodes
and showing the respective capacities in which they acted.

Edwin F. Mettler Chainman.
_____, Chainman.
_____, Arman.
_____, Flagman.

FINAL OATHS OF ASSISTANTS.

We, I, Edwin F. Mettler
and _____, do solemnly swear that we assisted John A.
Rockfellow, United States Mineral Surveyor, in marking the corners and surveying
the boundaries of the mining claim of Eleanor Godwin

known as the Victory No. 1 and Victory No. 2 Lodes
represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
and correctly executed, and the corner and boundary monuments established according to law and the instruc-
tions furnished by the Office Cadastral Engineer at Phoenix, Ariz
~~United States Surveyor-General for~~

Edwin F. Mettler Chainman.
_____, Chainman.
_____, Arman.
_____, Flagman.

Subscribed and sworn to by the above-named persons before me this 11th
day of February, 1917

R. H. Cornelius
Notary Public

My Commission
Expires Jan 31-1931



FINAL OATH OF U. S. MINERAL SURVEYOR.

I, John A. Rockefeller, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer, at Phoenix, Ariz., dated Sept 15 1926

I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly executed the survey of the Mining Claim of Eleanor Godwin


known as the Victory No. 1 & Victory No. 2 lodes situate in Dos Cabezas Mining District, Cochise County, Arizona, in Section No. 1 & 2, Township No. 155, Range No. 27 E

and designated as Survey No. 4023, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Office Cadastral Engineer with said instructions, and that all corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or her grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

John A. Rockefeller
U. S. Mineral Surveyor.

Subscribed and sworn to by the said John A. Rockefeller
U. S. Mineral Surveyor, before me Lee O. Woolley, a Notary Public in and for Cochise County, Arizona this 2nd day of March, 1927. My Commission Expires Jan. 7, 1929

Lee O. Woolley
Notary Public



U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

OFFICE OF U. S. SURVEYOR-GENERAL,
PUBLIC SURVEY OFFICE

Phoenix, Arizona,

March 9, 1927.

I, U. S. Surveyor-General for ~~OFFICE CADASTRAL ENGINEER~~, at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Eleanor Godwin

known as the VICTORY NO. 1, and VICTORY NO. 2 lodes

situate in Dos Cabezas

Mining District, Cochise County, Arizona

in Section 1 & 2, Township No. 15 S., Range No. 27 E., and

designated as Survey No. 4023, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon ^{or for each of} said mining claims by claimant or her grantors, and that said improvements consist of 8 shafts, total value \$1268.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

John D. Adams

~~United States Surveyor-General for~~ OFFICE CADASTRAL ENGINEER

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR PUBLIC SURVEY OFFICE

At Phoenix, Arizona,

March 9, 1927

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

Eleanor Godwin

, known as the

VICTORY NO. 1, and VICTORY NO. 2 lodes

situate in Dos Cabezas mining district,

Cochise County, Arizona

in Section s. 1 and 2, Township No. 15 S., Range No. 27 E.

, designated as Survey No. 4023

executed by John A. Rockfellow, U. S. Mineral

Surveyor, January 22 - February 5, 1927, under my instructions dated

September 15, 1926, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

Office Cadastral Engineer, Phoenix, Arizona