MINERAL SURVEY No. 4032

Arizona	Land	District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

	C.J. Greens, W.E. Steineck, and J.F.	Reilly
	KNOWN AS THE	
	REILLY lode	
	Comobabi	
	Pima County,	
Section	31 , Township 16 S.,	, Range 5 E., Uns.
Surve	eyed under instructions dated December	U. S. Mineral Surveyor.
	Claim located See location notice	, 19
	Survey commenced December 13,	, 19 26
	Survey completed. January 27,	
	Address of claimant C.J. Greene, Ber	311, Tueson, Arizona.
	DATES OF AMENDED LOCA	TIONS.
	.)	
-822		

Feet.

MINERAL SURVEY NO. 4032

REILLY lode.

Beginning at Cor. No.1, identical with Loc. Mon.

An iron pipe 1 in. diam. with cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 1 R- 4032, with md of stone alongside, whence the Cor. to Tps. 16217 S., Rs. 425 E., G.&S.R.M. brs. S.52°39' W., 5145.25 ft.

No other bearings are available.

Thence N.36°35'W. Va. 13°45'E.

300. To W. end center, identical with Loc. Mon.

A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed W. Cr. R.

600.0 To Cor. No.2, identical with Loc. Mon.

An iron pipe 1 in. diam. with cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 2 R- 4032, with md of stone alongside.

No bearings are available.

Thence N.53°25'E. Va. 13°45'E.

400.0 Gulch brs. westerly.

1500.0 To Cor. No.3, identical with Loc. Mon.

An iron pipe 1 in. diam. with cap on top, 18 ins. above ground set 18 ins. in the ground, stamped 3 R. - 4032, with md of stone alongside.

No bearings are available.

Thence S.36°35'E. Va. 13°45'E.

300.0 To E. end center, identical with Loc. Mon.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground, and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed E. Cr. R.

410.0 Gulch brs. westerly.

600.0 To Cor. No.4. identical with Loc. Mon.

An iron pipe 1 in. diam. with cap on top, 18 ins. above ground.

Feet.

MINERAL SURVEY NO. 4032.

REILLY lode.

set 18 ins. in the ground, stamped 4 R - 4032, with md of stone alongside.

No bearings are available.

Thence S.53°25'W. Va. 13°45'E.

1000.0

Road brs. southwesterly.

1500.0

To Cor. No.1, the place of beginning.

LODE LINE.

As near as can be determined from the present development, the vein embraced in this location, extends as follows from its discovery;

AREA.

Total area Reilly lode ----

Acres. 20.661

The survey of this lode is identical with the original location as staked upon the ground.

LOCATION.

This survey is located approximately in the N.E. 1/4 Sec. 51, T.16 S., R. 5 E., Unsurveyed.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements made upon or for the benefit of the location embraced in said mining claim by the claimants or their grantors is not less than five hundred dollars, and that said improvements consist of:

No. 1, the discovery cut of the Reilly lode, the face of which being the discovery point, is on the center line, 750.0 ft. from the center of line 1-2. 4 1/2 ft. wide, 10 ft. face, running North, 15 ft. to mouth.

Value \$100.0

No.2 A cut, the mouth of which brs. from Cor. No.3, S.13°30'E., 210.0 ft. 4 ft. wide, 8 ft. face, running N. 60° E., 15 ft. to face.

Value \$100.0

MINERAL SURVEY NO. 4032.

REILLY lode.

EXPENDITURE OF FIVE HUNDRED DOLLARS .- Cont'd.

No.3 A cut, the mouth of which brs. from Cor. No.1, N.33 W., 200.0 ft. 4 1/2 ft. wide, 8 ft. face, running N. 38 W., 15 ft. to face.

Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.4, S. 72 W., 670.0 ft. 6 x 8 ft. 370.0 ft. deep. (timbered.) At the 100 ft. level is a drift 4 x 6 ft. running N.56 W., 48 ft., thence N.25 E., 61.5 ft., thence N.5 E., 46 ft., thence N. 73° W., 16 ft. to a point at the beginning of improvement No.4. From this point is a drift 4 x 6 ft. running N.64 W., 60 ft. to face. at same point is another drift 4 x 6 ft. running S.20° W., 20 ft. to face. consisting of 80 ft. of drifting made subsequent to the location of the Reilly lode.

Value \$800.0

Other improvements.

A shaft, the center of which is on the center line 570.0 ft. from the center of line 1-2, 4 x 6 ft. 10 ft. deep.

A tunnel, the mouth of which brs. from Cor. No.4, S.77° W.,790 ft. 4 x 6 ft. running S. 68° E.,45 ft. to face.

An inclined shaft. the center of which brs from Cor. No.4 S.79°15' W.,785 ft. 4 x 6 ft. 100 ft. deep.

An iron clad blacksmith shop, the N.E. Cor. of which brs. from Cor. No.4, S.83°45'W.,725.0 ft.10 x 12 ft., course of long sides, S.50°E.

INSTRUMENT.

This survey was made with a Gurley mountain transit, the courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 500 ft. steel tape.

MINERAL SURVEY NO. 4032.

REPORT.

The lode line of this location was run directly upon the ground, the corners were established by running around the claim.

The Corner common to Tps. 16 and 17 S., Rs. 4 and 5 E., consists of an iron post about 4 ins. diam., capped with brass and showing 2 ft. above ground, stamped S.36, S31, S 1, and S.6., T 16 S., T.17 S. R.4 E. and R.5 E.

Adjoining Claims.

There are no adjoining or conflicting claims known.

SOLAR OBSERVATION.

Direct solar observation, taken, Wednesday, January 26, at 9:36 AM Solar time. - Sun bisected. Lat. 32°00; Lon. 111°52' Difference in time 5 hours.

Apparent declination = 18°53'23.5" $\sin 1/2 A = \sqrt{\sin (S-L)(S-H)}$ 3' 6.5" Cos L Cos H 18°50'17 " Dec'1 = 90 108°50'17" = P L = 32°00' H = 26°13'03" ('App't H = 26°15')
P = 108°50'17" 2) 167 03 20" 83 31'40" = S S-L = 51°31'40" 9.8937118 S-H = 57 °18 '37" 9.9251095 0.0715795 0.0471477 19.9375485 9.9687742 = 68°32' 137°04'

180°-137°04' = S.42°56'E. = bearing of sun. 6°21' = Ang. to right from Sun. S.36°35' E = Course of line.

Set up at Cor. No.2, F.S. to Cor. No.1

The Golden Age Mine is a little over a mile in a S.E.direction from this survey. As near as I can learn, this is the nearest property to the Reilly lode.

The distance from Sells, or Indian Oasis, to the Reilly mine is exactly six miles in a N. E. direction, the location notice being in error in this respect.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names	of the individuals employed byT.N. Stevens
United States Mineral S	urveyor, to assist in running, measuring, and marking the lines, corners, and
boundaries described in	he foregoing field notes of the survey of the mining claim of
	C.J. Greene.W.E. Steineck, and J.F. Reilly
	REILLY lode
	ve capacities in which they acted.
	Frank Bingochea , Chainman.
	, Chainman.
	, Axman.
	\cdots , Flagman.
F	NAL OATHS OF ASSISTANTS.
We, I, Frank Bing	ochea:
and	, do solemnly swear that we assisted
	, United States Mineral Surveyor, in marking the corners and surveying
	ing claim of C.J. Greene, W.E. Steineck, and J.F. Reilly
known as the	REILLY lode
represented in the foregoi	ng field notes as having been surveyed by said mineral surveyor and under his
	rvey has been in all respects, to the best of our knowledge and belief, faithfully
	the corner and boundary monuments established according to law and the instruc-
Of: tions furnished by the Uni	ice Cadastral Engineer, at ed States Surveyor-General for Phoenix, Arizona.
	Frank Bingochea, Chainman.
	, Chainman.
	, Axman.
	, Flagman.
Subsci	ibed and sworn to by the above-named persons before me this 29
	ay of January , 1927
	1 Ethers
my co	unicaion expires N. A. P. 10.
7 2	ay of Jamay, 1927 Ethusiak Luciak 27-30. Solver Motary Public 6-1043

FINAL OATH OF U. S. MINERAL SURVEYOR.

I,T.N. Stevens	, U. S. Mineral Surveyor
	ctions received from the Office Cadastral Engineer
	, dated December 3, 1926
	United States, the official regulations and instruc-
	Office Cadastral Engineer, faithfully and correctly
executed the survey of the Mining Claim of	and correctly
C.J. Greene, W.E. Steineck, and	J.F. Reilly , known as the
REILLY 10	de, known as the
situate inComobabi	Mining District,
	county, Ariz., in Section
	ge No. 5 E., Unsurveyed.
and designated as Survey No. 4032	, as represented
	ow the boundaries of said mining claim as distinctly
	cribed in the attached copy of the location certifi-
	Cadastral Engineer with said instructions, and
	lished and perpetuated in strict accordance with
	reunder; and I do further solemnly swear that the
	f said survey and my report therein, and that the
	aid mining claim by claimant or their
	ne character, extent, location, and itemized value
thereof are specified therein with particularity	and full detail, and that no portion of said labor
or improvements so credited to this claim has be	een included in the estimate of expenditures upon
any other claim.	
	11.197
	1.N. O Cours
	U. S. Mineral Surveyor.
	7 - 0 4
Subscribed and sworn to by the said	
U. S. Mineral Surveyor, before me	a notary public
of Juna Co., C.	igana this 29th
day of January, 192 7	
0	EDMO.
	No to the Time
my commission e	Notary Public $2-27-30$
(/53	

U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior,

PUBLIC SURVEY OFFICE

	Phoenix, Arizona,
	March 9, 19.27
I, U. S. Surveyor-General	ral for OFFICE CADASTRAL ENGINEER T. Phoenix, Arizons
do hereby certify that the fo	oregoing transcript of the Field Notes, return and approval of the survey
of the mining claim of	
C.	J. Greene, W. E. Steineck, and James F. Reilly
	REILLY lode
situate in	Comobabi
Mining District,	Pima County, Arizona
	Township No. 16 S., Range No. 5 E., Unsur., and
designated as Survey No	4032 , has been correctly copied from the originals on file in
	Notes furnish such an accurate description of said mining claim as will, if
incorporated into a patent, se	erve fully to identify the premises, and that such reference is made therein
to natural objects or perman	ent monuments as will perpetuate and fix the locus thereof.
And I further certify th	nat five hundred dollars' worth of labor has been expended or improve-
ments made upon said mini	ng claim by claimants or their grantors, and that said improvements
consist of 3 cuts an	nd 80 ft. of drifting, total value \$1100.
	•
•	
and that no portion of said	labor or improvements has been included in the estimate of expenditures
upon any other claim.	
I further certify that the	plat thereof, filed in the U.S. Land Office at Phoenix.
Arizona,	is correct and in conformity with the foregoing Field Notes.
	John D. Adams
	United States Surveyor General for OFFICE CADASTRAL ENGINEER

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR

PUBLIC SURVEY OFFICE

	At	Phoenix, Ari	zona,
		<u>N</u>	larch 9 , 192 7
I, Office Cadastral Engineer at	hoenix, Arizo	na,	
do hereby certify that the foregoing and			
Mining Claim of			
C. J. Greene, W			
			, known as the
	REILLY lode		
situate in			
Pima	County,	Ari	zona
in Section31, Townsh	ір No16	-S, Ra	nge No5_E., Unsur
, designated as Surv			
executed byT_N_S			
Surveyor,Dec.13, 1926	- Jan. 27	, 1927, unde	r my instructions dated
December 3	, 1926, have b	een critically exam	nined and the necessary
corrections and explanations made, and t			
are hereby approved. The certified copy			
on file in this office and a true copy of	said certified copy or	f said location cer	tificate is included and
made a part of the transcript of the field			
		Not.	Dilden .
SOVERMMENT PRINTING OFFICE	Office Co	idastral Engineer	Phoonis Asi