

MINERAL SURVEY No. 4048

Arizona Land District

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Myra A. Emery

KNOWN AS THE

~~CONTENTION, PROSPERITY, TIT FOR TAT, CAMDEN, CAMDEN NO. 2, CAMDEN NO 3 lodes.~~

Pima Mining District,

Pima County, Arizona.

Section 10, 11, 15, Township 17 S, Range 12 E.

Surveyed under instructions dated June 28, 1927

by J. N. Stevens

U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced July 11, 1927

Survey completed August 15, 1927

Address of claimant R.W. Langworthy, Atty for Claimant, Tucson, Ariz.

DATES OF AMENDED LOCATIONS.

See location notices.

Feet	MINERAL SURVEY NO. 4048
	CONTENTION Lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. Nos. 3 and 4 Camden No.2 and Prosperity lodes respectively of this Sur.
	An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 1 Cen., 3 C. No.2, 4 P. 4048, with md of stone alongside, whence the Cor. to Secs. 10, 11, 14 and 15, T. 17 S. R. 12 E. brs. S.77°39' E., 1467.5 ft.
	No other bearings are available.
	Thence N. 12°19' W. Va. 13°45' E.
100.00	Gulch brs northeasterly.
300.00	To E. end center, identical with Loc. Mon. and W. end center Prosperity lode of this Sur.
	A pine pest 4 ins. sq. by 4 ft. high, set firmly in the ground, and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed E. Cr. Cen. , W. Cr. P.
335.82	Intersect line 1-2 Sur. No. 2855 Redman lode , Claimant unknown at S.75°51'W., 259.67 ft. from Cor. No.1 and N.75°51'E., 900.13 ft. from Cor. No.2
360.00	Gulch brs. southeasterly.
600.00	To Cor. No.2, identical with Loc. Mon. and Cor. No.3 Prosperity lode of this Sur.
	An iron pipe 2 ins. diam. with lead cap on top, 18 ins above ground, set 18 ins. in the ground, stamped 2 Cen., 3 P - 4048 with md of stone alongside.
	Cor. No.1 Sur. No.2855 Redman lode brs. S.57°44'50" E., 364.6 ft.
	No other bearings are available.
	Thence S.65°06'W., Va. 13°45'E.
928.62	Intersect lines 2-3 and 4-1 Sur. No.2855 Redman and New Exemption lodes respectively at N.16°31'W., 90.9 ft. from Cor. Nos. 1 and 2; and S.16°31'E., 509.1 ft. from Cor. Nos. 3,4.
1500.00	To Cor. No.3, identical with Loc. Mon.
	An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 3 Cen - 4048, with md of stone alongside, whence Cor. Nos 2,1 Sur. No.2855 Redman and New

Feet.

MINERAL SURVEY NO. 4048

CONTENTION Lode- Cont'd.

Exemption lodes respectively brs. N.74°15'10" E., 565.30 ft.

No other bearings are available.

Thence S.12°19'E.,
Va. 13°30'E.

- 90.24 To Cor. No.2 Tit For Tat lode of this Sur., hereinafter described,
also intersect line 1-2 Sur. No. 2855 New Exemption lode at S.65°17'W.
577.77 ft. from Cor. No.1 and N.65°17'E., 801.16 ft. from Cor. No.2.
- 300.0 To W. end center, identical with the Loc. Mon.
A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and
surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed
W. Cr. Cen.
- 390.24 To E. end center Tit For Tat Lode of this Sur., hereinafter describd.
- 600.0 To Cor. No.4, identical with Loc. Mon.
An iron pipe 2 ins. diam.with lead cap on top, 18 ins. above
ground, set 18 ins. in the ground, stamped 4 Con.-4048 with md of stone
alongside?
Cor. No.1 Tit For.Tat lode of this Sur. brs. S.12°19'E., 90.24 ft.
No other bearings are available.
Thence N.65°06'E.,
Va. 13°45'E.
- 1500.00 To Cor. No.1, the place of beginning.
PROSPERITY Lode.
Beginning at Cor. No.1, identical with Loc. Mon. and Cor. Nos.
1,2 and 2, Camden, Camden No.3 and Camden No.2 lodes respectively
of this Sur.
An iron pipe 2 ins. diam. with lead cap on top , 18 ins. above ground
ground, set 18 ins. in the ground, stamped 1 P, 1 C, 2 C No.3, 2 C
No.2 - 4048 with md of stone alongside, whence the Cor. to Secs.
10,11,14,15, T. 17S.,R.12 E. brs. S.2°28'E.; 862.37 ft.
No other bearings are available.
Thence N.12°19'W.
Va. 13°45'E.
- 300.00 To E. end center, identical with Loc. Mon. and W. end center
Camden lode of this Sur.

Feet.

MINERAL SURVEY NO. 4048

PROSPERITY Lode - Cont'd.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed E. Cr. P, W. Cr. C.

600.0 To Cor. No.2, identical with Loc. Mon. and Cor. No.2 Camden lode of this Sur.

An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 2 P, 2 C - 4048 with md of stone alongside.

No bearings are available.

Thence S. 68°35'W.
Va 13°45'E.

650.00 Road brs. southerly.

1258.81 Intersect line 4-1 Sur. No.2855 Redman lode at S.16°31'E., 305.2 ft. from Cor. No.4 and N.16°31'W., 294.8 ft. from Cor. No.1 .

1500.00 To Cor. No.3, identical with Loc. Mon. and Cor. No.2, Contention lode of this Sur., heretofore described. Cor. No.1 Sur. No.2855 Redman lode brs. S.57°44'50"E., 364.6 ft.

Thence S.12°19'E.,
Va. 13°45'E.

240.0 Gulch brs easterly.

264.18 Intersect line 1-2, Sur. No.2855 Redman lode at S.75°51'W., 259.87 ft. from Cor. No.1 ~~(and N.75°51'E., 900.13 ft. from Cor. No. 2.)~~

300.00 To W. end center, identical with Loc. Mon. and E. end center Contention lode of this Sur., heretofore described.

500.00 Gulch brs. northeasterly.

600.00 To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 1-3, Contention and Camden No.2 lodes respectively of this Sur., heretofore described.

Thence N. 68°35'E.
Va. 13°45'E.

500.00 Gulch brs southeasterly.

750.0 Road brs. southerly.

1500.00 To Cor. No.1, the place of beginning.

Feet.

MINERAL SURVEY NO. 4048

T.F.T FOR TAT Lode.

Beginning at Cor. No.1, identical with Loc. Mon.

An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 1 - T F T - 4048, with md of stone alongside, whence the cor to Secs. 10,11, 14 and 15 , T.17 S., R. 12 E. Brs. N.81°40' 40" E., 2804.3 ft.

No bearings are available.

Thence N. 12°19' W.

Va. 13°45'E.

90.24 To Cor. No.4 Contention lode of this Sur. , heretofore described.
300.00 To E. end center, identical with Loc. Mon.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft base by 3 ft. high, scribed E. Cr. T F T.

394.24 To W. end center Contention lode of this Sur., heretofore described

600.00 To Cor. No.2, identical with Loc. Mon. On line 1-2 Sur. No.2855 New Exemption lode , at S.65°17'W., 577.77 ft. from Cor. No. 1

An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 2,T F T - 4048, with md of stone alongside.

Cor. No.3 Contention lode of this Sur. Brs. N.12°19'W.,90.24 ft.

No other bearings are available.

Thence S.65°17'W.

Va. 13°45'E.

212.0 Road brs southeasterly.
801.16 To Cor. No.2 Sur. No.2855 New Exemption Lode
975.0 Gulch brs. easterly.
1460.0 Road brs southwesterly.
1500.0 To Cor. No.3, identical with Loc. Mon.

An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 3 T F T- 4048, with md of stone alongside.

No bearings are available.

Feet

MINERAL SURVEY NO. 4048

TIT FOR TAT Lode-Cont'd.

Thence S.12°19'E.
Va. 13°45'E.

75.0 Road brs southwesterly .

300.0 To W. end center, identical with Loc. Mon.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed W. Cr. T F T.

600.0 To Cor. No.4, identical with Loc. Mon.

An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 4 T F T - 4048 with md of stone alongside,

No bearings are available.

Thence N. 65°17' E.
Va. 13°45'E.

1425.0 Road and gulch brs. southeasterly.

1500.0 To Cor. No.1, the place of beginning.

CAMDEN Lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. Nos. 1,2 and 2, Prosperity, Camden No.2 and Camden No.3 lodes respectively of this Sur. heretofore described. , whence the Cor. to Secs. 10,11, 14 and 15 T.17S., R.12 E. brs. S.2°28'E., 862.37 ft.

Thence N. 12°19'W.
Va. 13°45'E.

300.0 To W. end center , identical with Loc. Mon. and E. end center Prosperity lode of this Sur., heretofore described.

600.0 To Cor. No.2, identical with Loc. Mon. and Cor. No.2 Prosperity lode of this Sur., heretofore described.

Thence N. 84°29'E.
Va. 13°45'E.1035.00 Road brs. northerly.
1200.65 To Cor. No.3, identical with Loc. Mon.

An iron pipe 2 ins. diam. with lead cap on top , 18 ins. above ground, set 18 ins. in the ground, stamped 3 C - 4048 with md of stone alongside.

Feet.

MINERAL SURVEY NO. 4048

CAMDEN Lode - Cont'd.

No bearings are available.

Thence S. 12°19'E.
Va. 13°45'E.

300.0

To E. end center, identical with Loc. Mon.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed E. Cr. C.

600.0

To Cor. No.4, identical with Loc. Mon. on line 2-3 Camden No.3 lode of this Sur. at S. 84°29' W., 299.35 ft. from Cor. No.3.

An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 4 C - 4048, with md of stone alongside.

No bearings are available.

Thence S. 84°29'W.
Va. 13°45'E

1200.65

To Cor. No.1, the place of beginning.

CAMDEN NO.2 Lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1 Camden No.3 lode of this Sur.

An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 1 C No.2, 1 C No.3 - 4048 with md of stone alongside, whence the Cor. to Secs. 10, 11, 14, 15, T. 17 S. R. 12 E. brs. S. 18°16'W. 290.0 ft.

No other bearings are available.

Thence N. 12°19' W.
Va. 13°45'E.

300.0

To E. end center, identical with Loc. Mon. and W.end center Camden No3 lode of this Sur.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed E. Cr. C No.2, W. Cr. C No.3.

305.0

Gulch brs. northeasterly.

600.0

To Cor. No.2, identical with Loc. Men. and Cor. Nos.1,1 and 2, Prosperity, Camden and Camden No. 3 lodes respectively of this Sur. heretofore described.

Feet.	MINERAL SURVEY NO. 4048	
	CAMDEN NO. 2 lode- Cont'd.	
	Thence S. 68°35'W. Va. 13°45'E.	
750.0	Road brs. southerly.	
1000.0	Gulch brs. southeasterly.	
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 1 and 4, Contention and Prosperity lodes respectively of this Sur., heretofore described.	
	Thence S. 12°19' E. Va. 13°45'E.	
300.0	To W. end center, identical with Loc. Mon. A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed W. Cr. C No.2	
305.0	Gulch brs. easterly.	
600.0	To Cor. No.4, identical with Loc. Mon. An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 4 C No.2 - 4048, with md of stone alongside.	
	No bearings are available.	
	Thence N. 68°35'E. Va. 13°45'E.	
250.0	Gulch brs. northeasterly.	
1050.0	Road brs. southerly.	
1500.0	To Cor. No.1, the place of beginning.	
	CAMDEN NO.3 lode.	
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1 Camden No.2 lode of this Sur., heretofore described. , whence the Cor. to Secs. 10,11,14 and 15 T. 17 S. R. 12 E. brs. S. 18°16'W., 290.0 ft.	
	Thence N. 12°19'W., Va. 13°45'E.	
300.0	To W. end center, identical with Loc. Mon. and E. end center Camden No 2 lode of this Sur., heretofore described.	
305.0	Gulch brs northeasterly.	
600.0	To Cor. No.2, identical with Loc. Mon. and Cor. Nos.1,1 and 2,	

Feet.	MINERAL SURVEY NO. 4048
	CAMDEN No.3 lode - Cont'd.
	Camden, Prosperity and Camden No.2 lodes respectively of this Sur., heretofore described.
	Thence N. 84°29'E. Va. 13°45'E.
1200.65	To Cor. No.4 Camden lode of this Sur., heretofore described.
1210.0	Gulch brs. northeasterly.
1500.0	To Cor. No.3, identical with Loc. Mon.
	An iron Pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 3 C No.3- 4048 with md of stone alongside.
	No bearings are available.
	Thence S.12°19'E Va. 13°45'E.
300.0	To E. end center, identical with Loc. Mon.
	An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped E. Cr. C No.3.
600.00	To Cor. No, 4, identical with Loc. Mon.
	An iron pipe 2 ins. diam. with lead cap on top, 18 ins. above ground, set 18 ins. in the ground, stamped 4 C No3 - 4048, with md. of stone alongside.
	No bearings are available.
	Thence S. 84°29'W. Va. 13°45'E.
1500.00	To Cor. No.1, the place of beginning.

MINERAL SURVEY NO. 4048

Lode Lines.

As near as can be determined from the present developments, the veins of the several locations embraced in this claim, extend as follows from their respective discoveries.

Contention lode, 50.0 ft. S. 65° 06' W., and 1450.0 ft. N. 65° 06' E.

Prosperity lode, 540.0 ft. S. 68° 35' W., and 960.0 ft. N. 68° 35' E.

Tit For Tat lode, 300.0 ft. N. 65° 17' E., and 1200.0 ft. S. 65° 17' W.

Camden lode, 100.0 ft. S. 84° 29' W., and 1100.65 ft. N. 84° 29' E.

Camden No. 2 lode, 485.0 ft. S. 68° 35' W., and 1015.00 ft. N. 68° 35' E.

Camden No. 3 lode, 500.0 ft. S. 84° 29' W., and 1000.00 ft. N. 84° 29' E.

AREA.

	Acres
Total area Contention lode -----	20.165
Area in conflict with-	
Sur. No. 2855 New Exemption lode ----	1.174
Sur. No. 2855 Redman lode -----	3.687
Total area Prosperity lode -----	20.401
Area in conflict with-	
Sur. No. 2855 Redman lode -----	1.601
Total area Tit For Tat lode -----	20.179
Total area Camden lode -----	16.422
Total area Camden No. 2 lode -----	20.401
Total area Camden No. 3 lode -----	20.516

LOCATION.

This survey is located in S 1/2 Sec. 10, S.W. 1/4 Sec. 11, and N. 1/2 Sec. 15, T. 17 S., R. 12 E.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements made upon or for the benefit of each of the locations embraced in said mining claim by the claimant or her grantors is not less than five hundred dollars and that said improvements consist of :

Contention lode.

No. 1, the discovery ^{shaft} point, on the center line 50 ft. from the center of line 3-4, 4 x 6 ft. 50 ft. deep.

Value \$500.0

No. 2. A shaft, the center of which hrs. from Cor. No. 4, N. 6° 30' W., 275.0 ft. 4 x 6 ft. 200 ft. deep.

Value \$2000.0

MINERAL SURVEY NO. 4048

EXPENDITURE OF FIVE HUNDRED DOLLARS - Cont'd.

PROSPERITY Lode.

No.1 The discovery shaft, on the center line ⁵⁴⁰450 ft. from the center of line 3-4, 4x 6 ft. 150 ft. deep. Value \$1500.0

No.2 A shaft, the center of which brs. from Cor. No.2 S.47°45'W., 875. ft. 4 x 6 ft. 50 ft. deep. Value \$500.0

No.3 A shaft, the center of which brs. from Cor. No.2, S.44° W., 750.0 ft. 4 x 6 ft. 100. ft. deep. Value \$1000.0

No.4 A shaft, the center of which brs. from Cor. No.2, S.42°W., 700.0 ft. 4 x 6 ft. 10 ft. deep. Value \$100.0

Tit For Tat Lode.

The discovery No.1 shaft, the center of which being the discovery point, on the center line 300.0 ft. from the center of line 1-2, 4 x 6 ft. 10 ft. deep. Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.2, S.29°W., 425 ft., 4x6 ft. 50 ft. deep. Value \$500.0

No.3 A shaft, the center of which brs. from Cor. No.2, S.27°15'W., 400.0 ft. 4 x 6 ft. 35 ft. deep. Value \$350.0

Camden Lode.

No.1, The discovery shaft, the center of which being the discovery point, on the center line 100 ft. from the center of line 1-2, 4 x 6 ft. , 10 ft. deep. Value \$100.0

No.2 A shaft, on the center line, 95 ft. from the center of line 3-4, 4 x 6 ft. 10 ft. deep. Value \$100.0

No.3 A shaft, the center of which brs. from Cor. No.3, S.59°54'W., 265. ft. 4 x 6 ft. 60 ft. deep. Value \$600.0

No.4 A shaft, the center of which brs. from Cor. No.1 N.70°45'E., 570.0 ft. 4 x 6 ft. 8 ft. deep. Value \$80.0

MINERAL SURVEY NO. 4048

EXPENDITURE OF FIVE HUNDRED DOLLARS.- Cont'd.

CAMDEN NO. 2 lode.

No. 1, the discovery tunnel, the mouth of which being the discovery point, on the center line, 485 ft. from the center of line 3-4, 4 x 5 ft. running N.25° W., 50 ft. to face.

Value \$500.00

No.2 A shaft, the center of which brs. from Cor. No.3, S.77°30'E., 460.0 ft. 6 x 8 ft. 400 ft. deep (Timbered)

Value \$12000.0

No.3 A shaft, the center of which brs. from Cor. No.3, S.68°45'E., 300.00 ft. 4 x 6 ft. 70 ft. deep.

Value \$700.0

No.4 A shaft, the center of which brs. from Cor. No.3, S.63°45'E., 325 ft. 4 x 6 ft 50 ft. deep.

Value \$500.0

Camden No.3 lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line 500 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep.

Value \$80000

No.2 A shaft, the center of which brs. from Cor. No.2, S.68°30'E., 570.0 ft. 4 x 6 ft. 50 ft. deep.

Value \$500.0

No.3 A shaft, on the center line, 630 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep.

Value \$80.0

No.4 A shaft, the center of which brs. from Cor. No.2 S.46°15'E., 205 ft. 4 x 6 ft. 20 ft. deep.

Value \$200.0

No.5 A shaft, the center of which brs. from Cor. No.2 S.64°E., 275 ft. 4 x 6 ft. 8 ft. deep.

Value \$80.0

OTHER IMPROVEMENTS.

A frame, iron clad hoist and engine house, the N.W. corner of which brs. from Cor. No.3, Camden No.2 lode S.82°45'E., 425 ft.

24 x 30 ft. Course of long sides N.25°W.,

MINERAL SURVEY NO. 4048

INSTRUMENT.

This survey was made with a Gurley mountain transit, the courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 500 ft. steel tape.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the corners were established by running around the claims.

The Cor. to Secs. 10,11,14,15 , T. 17 S., R. 12 E. is a porphyry rock 8 x 8 ins. showing 12 ins. above ground, chiseled with two notches on the E face and four notches on the S. face. This is the nearest corner of the public survey that can be found or identified.

A diligent search was made for the 1/4 Cors. bet. Secs. 10 and 15, 9 and 10, 15 and 16 and the Cor. to Secs. 9,10,15 and 16 and I fail to find any evidence of same.

Sur. No. 2855, New Exemption and Redman lodes. All corners consist of pine posts 4 ins. sq by 4 ft. high, properly set and scribed with the number of the corners and the survey, except Cor. No.2 of the New Exemption lode which is a 4 x 4 inch stump broken off at the ground in a md of stone.

Lines 1-2, 2-3 and 4-1, Sur. No.2855 Redman lode fail to furnish the courses as approved (S75°58'W.,N.16°24'W and S.16°-24'E. respectively) and same are properly given in these field notes.

Line 1-2 Sur. No.2855 New Exemption lode fails to furnish the course and distance as approved (S.65°24'W.,1380 ft) and same is properly given herein.

Adjoining Claims.

On the North by Sur. No.2855 New Exemption and Redman lodes and Jackson and Annette lodes U N S , claimants unknown.

On the East by Vinie lode Uns, Geo.F. Gray Claimant and Camden Extension lode Uns., claimant herein.

On the South by South Camden, Chicago No.1, Chicago, Elsie and Elsie No.1 lodes, Uns. All belonging to claimant herein.

FINAL OATHS FOR SURVEYS.

LIST OF NAMES.

A list of the names of the individuals employed by T.N. Stevens

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of

Myra A. Emery

known as the CONTENTION, PROSPERITY, TIT FOR TAT, CAMDEN, CAMDEN NO. 2, CAMDEN NO. 3 lodes and showing the respective capacities in which they acted.

Charles Keenan, Jr., Chainman.

Chainman.

Asman.

Flagman.

FINAL OATHS OF ASSISTANTS.

We, I Charles Keenan, Jr.

and _____, do solemnly swear that we assisted T.N. Stevens

_____, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Myra A. Emery

known as the CONTENTION, PROSPERITY, TIT FOR TAT, CAMDEN, CAMDEN NO. 2, CAMDEN NO. 3 lodes represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of ^{my}our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the ~~United States Surveyor General~~ OFFICE CADASTRAL ENGINEER

Charles Keenan, Jr., Chainman.

Chainman.

Asman.

Flagman.

Subscribed and sworn to by the above-named persons before me this 26th

day of August, 1927

[Signature]

Notary Public



FINAL OATH OF U. S. MINERAL SURVEYOR.

I, T.N. Stevens, U. S. Mineral Surveyor,
do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer,
at Phoenix, Arizona, dated June 28, 1927,
I have, in strict conformity to the laws of the United States, the official regulations and instruc-
tions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly
executed the survey of the Mining Claim of Myra A. Emery
....., known as the
CONTENTION, PROSPERITY, TIT FOR TAT, CAMDEN, CAMDEN NO. 2, CAMDEN NO. 3 lodes,
situate in Pima Mining District,
Pima County, Arizona, in Section 8
10, 11, 15, Township No. 17 S, Range No. 12 E. G. & S. R. M.,
and designated as Survey No. 4048, as represented
in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly
marked by monuments on the ground, and described in the attached copy of the location certifi-
cate, which was received by me from the Office Cadastral Engineer with said instructions, and
that all corners of said survey have been established and perpetuated in strict accordance with
the law, official regulations and instructions thereunder; and I do further solemnly swear that the
foregoing are the true and original field notes of said survey and my report therein, and that the
labor expended and improvements made upon said mining claim by claimant or her
grantors are as therein fully stated, and that the character, extent, location, and itemized value
thereof are specified therein with particularity and full detail, and that no portion of said labor
or improvements so credited to this claim has been included in the estimate of expenditures upon
any other claim.

T.N. Stevens
U. S. Mineral Surveyor.

Subscribed and sworn to by the said T.N. Stevens
U. S. Mineral Surveyor, before me E. J. Runk
Notary Public this 26th
day of August, 1927

E. J. Runk
Notary Public



U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior, PUBLIC SURVEY OFFICE OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona,

September 29, 1927.

I, U. S. Surveyor-General for OFFICE CADASTRAL ENGINEER, at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Myra A. Emery

known as the CONTENTION, PROSPERITY, TIT FOR TAT, CAMDEN, CAMDEN NO. 2, CAMDEN NO. 3 lodes

situate in Pima

Mining District, Pima County, Arizona

in Section S 10, 11, 15, Township No. 17 S, Range No. 12 E., and

designated as Survey No. 4048, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claim by claimant or her grantors, and that said improvements consist of 21 shafts and 1 tunnel, total value \$22070.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

John D. Adams

United States Surveyor-General for OFFICE CADASTRAL ENGINEER

~~SURVEYOR GENERAL'S~~ CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR
~~OFFICE OF U. S. SURVEYOR GENERAL~~
PUBLIC SURVEY OFFICE

Phoenix, Arizona,

September 29, 1927

I, ~~U. S. Surveyor General for~~ OFFICE CADASTRAL ENGINEER, at Phoenix, Arizona,

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

Myra A. Emery

known as the

CONTENTION, PROSPERITY, TIT FOR TAT, CAMDEN, CAMDEN NO. 2, CAMDEN NO. 3 lodes

situate in Pima mining district,

Pima County, Arizona

in Sections 10, 11, 15, Township No. 17 S., Range No. 12 E.

designated as Survey No. 4048

executed by T. H. Stevens, U. S. Mineral

Surveyor, July 11 - August 13, 1927, under my instructions dated

June 28, 1927, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

John D. Adams

~~U. S. Surveyor General for~~ OFFICE CADASTRAL ENGINEER