

4-683

MINERAL SURVEY No. 4061

Arizona.

Land District.

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

Edwin A. Stone

KNOWN AS THE

COPPER BELL NOS. 1,2,3,4,5,6,7,8,9. FLAT IRON, J.B.M., FOX NOS. 1,2, MARY B. ECLIPSE, KING, M.G., SUNSHINE AND DARBY NO. 1 lodes.

Ajo

Mining District,

Pima

County,

Arizona.

Sections 26,27,34 and 35 Township 12 S., Range 6 W.,

Surveyed under instructions dated January 27, 19 28

by J. N. Stevens

U. S. Mineral Surveyor.

Claim located See location notices, 19

Survey commenced February 1, 19 28

Survey completed February 16, 19 28

Address of claimant John W. Mays, Ajo, Ariz., Atty. for Claimant.

DATES OF AMENDED LOCATIONS.

See location notices.

Feet

MINERAL SURVEY NO. 4061

COPPER BELL No.1. Lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2  
Copper Bell No.2 lode of this Sur.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground  
set 18 ins. in the ground, stamped 1 C B No.1, 2 C.B. No.2 - 4061  
with md of stone alongside, whence the 1/4 Cor. bet. Secs. 34-35,  
T.12 S., R. 6 W. brs. S.72°04'50" E., 737.36 ft.

No other bearings are available.

Thence N.86°17'W.  
Va. 13°45'E.

300.00 To S. end center, identical with Loc. Mon. An iron pipe 2 ins.  
diam by 4 ft. long , set firmly in the ground and surrounded with  
md of stone 3 1/2 ft. base by 3 ft. high, stamped S. Cr. C B. No.1

600.0 To Cor. No.2, identical with Loc. Mon.  
An iron pipe 2 ins. diam. with cap on top , 24 ins. above ground  
set 18 ins. in the ground with concrete base, stamped 2 C.B. No.1 -  
4061 with md. of stone alongside.

No bearings are available.

Thence N.1°12'E.,  
Va. 13°45'E.

420.0 Road brs. northeasterly .

630.0 Road brs. easterly.

1500.0 To Cor. No.3, identical with loc. Mon. and Cor. Nos. 3 and 3  
No.1  
Mary B and Fox, lodes of this Sur.

An iron pipe 2 ins. diam. with cap on top, 24 ins above ground  
set 18 ins. in the ground with concrete base, stamped 3 C.B. No.1,  
3 M. B., 3 F. No.1 - 4061 with md of stone alongside.

No bearings are available.

Thence S. 86°17'E.  
Va. 13°45'E.

70.0 Road brs. southerly.

300.0 To N. end center, identical with Loc. Mon. and S. end center  
Fox No.1 lode of this Sur.

A pine post 4 ins sq by 4 ft. high, set firmly in the ground and  
surrounded with md of stone , scribed N. Cr. C.B. No.1, S. Cr.

F. No.1



Feet.

## MINERAL SURVEY NO. 4061

## COPPER BELL NO/ 1 Lode - Cont'd.

600.0 To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 4,3 and 3, Fox No.1, Fox No.2 and Copper Bell No.2 lodes respectively of this Sur.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 4 C.B. No.1, 4 F. No.1, 3 F.No.2, 3 C.B. No.2 - 4061 with md. of stone alongside.  
No bearings are available.  
Thence S.1°12'W.  
Va. 13°45'E.

775.0 Road brs. southeasterly.

960.0 Road brs. easterly.

1500.0 To Cor. No.1, the place of beginning.

## COPPER BELL NO. 2 Lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor No.1 Copper Bell No. 3 lode lode of this Sur.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 1 C.B. No.2, 1 C.B. No.3 - 4061 with md. of stone alongside, whence the 1/4 Cor. bet. Secs. 34-35 T.12S., R. 6 W. brs. S.28°41'E., 214.28 ft.

No bearings are available.

Thence N.86°17'W.  
Va. 13°45'E.

300.0 To S. end center, identical with Loc. Mon.

An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md 3 1/2 ft. base by 3 ft. high, stamped S. Cr. C.B. No.2.

600.0 To Cor. No.2, identical with Loc. Mon. and Cor. No.1, Copper Bell No.1 lode of this Sur., heretofore described.

Thence N. 1°12' E.  
Va. 13°45'E.

540.0 Road brs. easterly.

725.0 Road brs. southeasterly.

1500.0 To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 4, 4 and 3 Copper Bell No.1, Fox No.1 and Fox No.2 lodes respectively of this Sur., heretofore described.



Feet.	MINERAL SURVEY NO. 4061
	COPPER BELL NO. 2 Lode, Cont'd.
	Thence S. 86° 17'E. Va. 13°45'E.
300.0	To N. end Center, identical with Loc. Mon. and S. end center Fox No.2 lode of this Sur. A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. C. B. No.2, S. Cr. F. No.2.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 4, 4, 4 Fox No.2 Eclipse and Copper Bell No. 3 lodes of this sur. An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 4 C.B No.2, 4 F. No.2, 4 E., 4 C. B. No.3 - 4061 with md of stone alongside.
	No bearings are available.
	Thence S. 1°12' W., Va. 13°45'E.
830.0	Road brs. easterly.
1020.0	Gulch brs. easterly.
1500.0	To Cor. No.1, the place of beginning.
	COPPER BELL NO. 3 Lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1, Copper Bell No.2 lode of this Sur., heretofore described, whence the 1/4 Cor. bet. Secs. 34-35 T. 12S. R. 6 W., brs. S. 28°41'E., 214.28 ft.
	No other bearings are available.
	Thence S. 86°17' E. Va. 13°45'E.
300.0	To S. end center. An iron pipe 2 ins. diam. by 4 ft. long, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped S. Cr. C.B. No.3 .
600.0	To Cor. No.2, identical with Loc. Mon. and Cor. No.1, Copper Bell No.4 lode of this Sur.



Feet.

MINERAL SURVEY NO. 4061

COPPER BELL NO. 3 Lode- Cont'd.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 2 C.B. No.3, 1 C.B. No.4- 4061 with md of stone alongside.

No bearings are available.

Thence N. 13°12'E.

Va. 13°45'E.

- 610.0 Gulch brs. easterly.
- 850.0 Road brs. easterly.
- 1500.0 To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 3, 4, 4 Eclipse, Flat Iron and Copper Bell No.4 lodes respectively of this sur.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 3 C.B. No.3, 3 E., 4 F.I., 4 C.B. No.4 - 4061 with md of stone alongside.

No bearings are available.

Thence N. 86°17' W.,

Va. 13°45'E.

- 300.0 To N. end center, identical with Loc. Mon. and S. end center Eclipse lode of this Sur.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. C.B' No.3, S. Cr. E.

- 600.0 To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 4,4, and 4, Copper bell No.2, Fox No.2 and Eclipse lodes. of this Sur., heretofore described.

Thence S. 1°12' W.

Va. 13°45'E.

- 830.0 Road brs. easterly.
- 1020.0 Gulch brs. easterly.
- 1500.0 To Cor. No.1, the place of beginning.

COPPER BELL NO. 4 lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2, Copper Bell No.3 lode of this Sur., heretofore described, whence the 1/4 Cor. bet. Secs. 34-35, T. 12S., R. 6 W. brs.



Feet.	MINERAL SURVEY NO. 4061.
	COPPER BELL No.4 Lode - Cont'd.
	S. 73°16'W., 517.82 ft.
	Thence S. 86°17'E. Va. 13°45'E.
300.0	To S. end center, identical with Loc. Mon. An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped S. Cr. C.B. No.4 .
600.0	To Cor. No.2, identical with Loc. Mon. and Cor. No. 1, Copper Bell No.5 lode of this Sur. An iron pipe 2 ins. diam' with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 2 C.B. No.4, 1 C.B. No.5 -4061 with md of stone alongside, whence the 1/4 Cor. Bet. Secs. 34-35, T. 12S. R. 6 W. brs. S. 84°15' W., 1100.19 ft. No other bearings are available.
	Thence N.1°12' E. Va. 13°45'E.
730.0	Gulch brs. easterly.
940.0	Road brs. easterly.
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 3, 3 and 4, Flat Iron, Copper Bell No.9 and Copper Bell No.5 lodes respectively of this Sur. An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 3 C.B. No.4, 3 F. I. , 3 C.B. No.9, 4 C. B. No.5 - 4061 with md of stone alongside.
	No bearings are available.
	Thence N. 86°17'W. Va. 13°45'E.
300.0	To N. end center, identical with Loc. Mon. and S. end center Flat iron lode of this Sur. A pine post 4 ins. sq by 4 ft. high, set firmly in the ground, and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. C. B. No.4, S Cr. F.I.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 3,3 and 4



Feet.

MINERAL SURVEY NO. 4061

COPPER BELL No.4 lode - Cont'd.

Copper Bell No.3, Eclipse and Flat Iron lodes respectively of this sur., heretofore described.

Thence S. 1°12'W.  
Va. 13°45'E.

- 650.0 Road brs. easterly.
- 890.0 Gulch brs. easterly.
- 1500.0 To Cor. No.1, the place of beginning.

COPPER BELL No.5 lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2 Copper Bell No.4 lode of this Sur., heretofore described, whence the 1/4 Cor. bet. Secs. 34-35, T. 12S., R. 6 W. brs. S.84°15' W., 1100.19 ft.

Thence S. 86°17' E.  
Va. 13°45'E.

- 300.0 To S. end center, identical with Loc. Mon.  
An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, stamped S. Cr. C.B. No.5.

- 600.0 To Cor. No.2, identical with Loc. Mon.  
An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground with concrete base, stamped 2 C.B. No.5-4061 with md. of stone alongside alongside.

No bearings are available.

Thence N. 1°12'E.  
Va. 13°45'E.

- 89.74 To Cor. No.3 Copper Bell No.6 lode of this Sur., hereinafter described.
- 719.74 Gulch brs. southeasterly.
- 909.74 Road brs. easterly.
- 1159.74 Road and gulch brs. southeasterly.
- 1429.74 Gulch brs. southeasterly.
- 1500.0 To Cor. No.3, identical with Loc. Mon. and Cor. No.4 Copper Bell No.9 lode of this Sur. On line 2-3 Copper Bell No.6 lode of this Sur.



Feet.

MINERAL SURVEY NO. 4061.

COPPER BELL No. 5 lode - Cont'd.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 3 C.B. No.5, 4 C.B. No.9 -4061 with md. of stone alongside.

No bearings are available.

Thence N. 86°17'W.

Va. 13°45'E.

300.0 To N. end center, identical with Loc. Mon. and S. end center Copper Bell No.9 lode of this Sur.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. C.B. No.5, S. Cr. C.B. No.9.

340.0 Road brs southeasterly.

510.0 Gulch brs. southeasterly.

600.0 To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 3,3,3 , Copper Bell No.4, Flat Iron and Copper Bell No.9 lodes of this Sur., heretofore described.

Thence S.1°12'W.

Va. 13°45'E.

560.0 Road brs. easterly.

770.0 Gulch brs. easterly.

1500.0 To Cor. No.1, the place of beginning.

COPPER Bell No.6 Lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1 Copper Bell No.7 lode of this Sur. On line 2-3 Sunshine lode of this Sur. at N.84° 49'W., 885.5 ft. from Cor. No.2

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 1 C.B. No.6, 1 C.B. No.7 -4061 with md. of stone alongside, whence the 1/4 Cor. bet. Secs. 26-35 T.12 S. R. 6 W. brs. N.17°20'10"E., 1083.13 ft.

No other bearings are available.

Thence N.84°49'W.

Va. 13°45'E.

300.0 To N. end center, identical with Loc. Mon. On line 2-3 Sunshine lode of this Sur.



MINERAL SURVEY NO. 4061

COPPER BELL NO. 6 Lode -Cont'd.

Feet.	
597.39	To Cor. No.3 Sunshine lode of this Sur. hereinafter described. and intersect line 4-1 Copper Bell No.9 lode of this Sur. at N.2°52'E. 89.6 ft. from Cor. No.4.
600.0	To Cor. No.2, identical with Loc. Mon. An iron pipe 2 ins. diam. with cap on top 24 ins. above ground, set 18 ins. in the ground, stamped 2 C.B. No.6 - 4061. with md.of stone alongside
	No bearings are available.
	Thence S. 1°12'W. Va. 13°45'E.
89.74	To Cor. Nos. 4 and 3 , Copper Bell No.9 and Copper Bell No. 5 lodes respectively of this Sur., heretofore described.
160.0	Gulch brs. easterly.
430.0	Gulch and road brs southeasterly.
680.0	Road brs. southeasterly.
870.0	Gulch brs. southeasterly.
1500.0	To Cor. No.3, identical with Loc. Mon. on line 2-3 Copper Bell No.5 lode of this Sur.
	An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 3 C. B. No.6 - 4061. with md.of stone alongside.
	Cor. No.2 Copper Bell No.5 lode brs. S.1°12'W., 89.74 ft.
	No other bearings are available.
	Thence S. 84°49'E., Va. 13°45'E.
300.0	To S. end center, identical with Loc. Mon.
	An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md.of stone 3 1/2 ft. base by 3 ft. high, stamped S. Cr. C.B. No.6
340.0	Gulch brs. easterly.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. No.4 Copper Bell No.7 lode of this Sur.



Feet.	MINERAL SURVEY NO. 4061
	COPPER BELL NO. 6 lode - Cont'd.
	An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 4 C.B. No.6, 4 C.B. No.7- 4061 with md of stone alongside.
	No bearings are available.
	Thence N. 1°12'E., Va. 13°45'E.
70.0	Gulch brs. easterly.
340.0	Gulch brs. southeasterly.
710.0	Road brs. southeasterly.
950.0	Gulch brs. southeasterly.
1160.0	Gulch brs. southeasterly.
1500.0	To Cor. No.1, the place of beginning.
	COPPER BELL NO. 7 lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1
	Copper bell No.6 lode of this Sur. heretofore described.,
	whence the 1/4 Cor. bet. Secs. 26-35 T. 12 S., R. 6 W. brs.
	N.17° 20' 10" E., 1083.13 ft.
	Thence S.84°49'E., Va. 13°45'E.
300.0	To N. end center, identical with Loc. Mon.
	A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. C.B. No.7
600.0	To Cor. No.2, identical with Loc. Mon. and Cor. No.1 Copper Bell No.
	8 lode of this Sur. On line 2-3 Sunshine lode of this Sur. at N. 84°49'W., 285.5 ft. from Cor. No.2.
	An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 2 C.B. No.7, 1 C.B. No.8-4061 with md. of stone alongside.
	No bearings are available.
	Thence S. 1°12'W. Va. 13°45'E.
750.0	Gulch brs. southeasterly.
925.0	Road brs. southeasterly.



Feet.	MINERAL SURVEY NO. 4061
	COPPER BELL NO. 7 lode - Cont'd.
1050.0	Road brs. southeasterly.
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. No.4 Copper Bell No.8 lode of this.
	An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 3 C.B. No.7, 4 C.B. No.8 - 4061 with md. of stone alongside.
	No bearings are available.
	Thence N. 84°49'W. Va. 13°45'E.
10.0	Gulch brs. southeasterly.
300.0	To S. end center, identical with Loc. Mon.
	An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, stamped 3 Cr. C.B. No.7
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. No.4 Copper Bell No. 6 lode of this Sur., heretofore described.
	Thence N. 1° 12'E. Va. 13°45'E.
70.0	Gulch brs. easterly.
340.0	Gulch brs. southeasterly.
710.0	Road brs. southeasterly.
950.0	Gulch brs. easterly.
1160.0	Gulch brs. southeasterly.
1500.0	To Cor. No.1, the place of beginning.
	COPPER BELL NO. 8 lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2 Copper Bell No. 7 lode of this Sur., heretofore described.
	on line 2-3 Sunshine lode of this Sur. at N.84°49'W., 285.5 ft. from Cor. No.2. , whence the 1/4 Cor. bet. Secs.26-35 T. 12S., R. 6 W. brs. N.14°10'30" W., 1122.25 ft. from
	No other bearings are available.
	Thence S.84°49'E. Va. 13°45'E.
285.5	To Cor. No.2 Sunshine lode of this Sur. hereinafter described and



Feet.

## MINERAL SURVEY NO. 4061.

## COPPER BELL NO. 8, Lode.-Cont'd.

Intersect line 2-3 Sur. No.3881 Copper Ridge No.11 lode, Copper Ridge Mining Co. Claimant, at S. 59°43'E., 527.19 ft. from Cor. No.2 and N. 59°43'W., 972.81 ft. from Cor. No.3.

300.0 To N. end center, identical with Loc. Mon.

An iron pipe 2 ins. diam. by 4 ft. long, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped N. Cr. C.B. No.8.

600.0 To Cor. No.2, identical with Loc. Mon.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 2 C.B. No.8 - 4061 with md of stone alongside.

No.11  
Cor. No.3 Sur. No. 3881 Copper Ridge lode brs. S.48°44'30" E.,  
700.82 Ft.

No other bearings are available.

Thence S. 1°12'W.,  
Va. 13°45'E.

152.66 Intersect line 2-3, Sur. No.3881 Copper Ridge No.11 lode at N.59°43'W., 613.8 ft. from Cor. No.3 and S.59°43'E., 886.2 ft. from Cor. No.2.

1070.0 Road brs. southeasterly.

1260.0 Gulch brs. southeasterly.

1410.0 Gulch brs. northeasterly.

1500.0 To Cor. No.3, identical with Loc. Mon.

An iron pipe 2 ins. diam. with cap on top 24 ins. above ground set 18 ins. in the ground in concrete base, stamped 3 C.B. No.8-4061 with md. of stone alongside.

No bearings are available.

Thence N.84°49'W.  
Va. 13°45'E.

100.0 Road brs. southeasterly and Gulch brs. northeasterly.

300.0 To S. end center, identical with Loc. Mon.

An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, stamped S. Cr. C.B. No.8



Feet.	MINERAL SURVEY NO. 4061
	COPPER BELL NO. 8 lode - Cont'd.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. No.3 Copper Bell No.7 lode of this Sur., heretofore described.
	Thence N.1°12'E. Va. 13°45'E.
450.0	Road brs. southeasterly.
575.0	Road brs southeasterly.
750.0	Gulch brs. southeasterly.
1500.0	To Cor. No.1, the place of beginning.
	COPPER BELL NO. 9 lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.3
	Sur. No.3488 Wolverine No.12 lode, New Cornelia Copper Co. claimant, on line 1-2 Sur. No.3488 Bright Star No.2 lode at S. 2°52'W., 389.6 ft. from Cor. No.1 and N.2°52'E., 210.4 ft. from Cor. No.2.
	An iron pipe 3 ins. diam. with copper cap on top showing 2 ft. above ground, stamped 1 C.B No.9 -4061, 3 Wolv. No.12 - 3488 with md of stone alongside, whence the 1/4 Cor. bet. Secs. 26-35 T.12S.; R.6 W., brs. S.63°09'30" E., 949.45 ft.
	No other bearings are available.
	Thence N.86°17'W. Va. 13°45'E.
300.0	To N. end center, identical with Loc. Mon. and S. end center No.12 Sur. No.3488 Wolverine lode.
	A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. C.B. No.9, S. Cr. W. No.12.
600.0	To Cor. No. 2, identical with Loc. Mon. and Cor. No.2 Flat Iron lode of this Sur. and Cor. Nos.4 -4 Sur. No.3488 Wolverine No.11 and Wolverine No.12 lodes.
	An iron pipe 3 ins. diam. with copper cap on top showing 24 ins. above ground, stamped 2 C.B. No.9, 2 F.I. - 4061 and 4 Wolv No.11 4 Wolv. No.12 - 3488 with md. of stone alongside.
	U.S.M.M. No.1 brs. N.3°11'20" E., 2449.5 ft.
	No other bearings are available.
	Thence S. 2°52'W. Va. 13°45'E.



Feet.

MINERAL SURVEY NO. 4061  
COPPER BELL NO. 9 lode. -Cont'd.

1400.0

Road brs. southeasterly.

1460.0

Gulch brs. southeasterly.

1500.0

To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 3,3 and 4

Flat Iron, Copper Bell No.4 and Copper Bell No.5 lodes respectively of this Sur., heretofore described.

Thence S.86°17' E.  
Va. 13°45'E.

90.0

Gulch brs. southeasterly.

260.0

Road brs. southeasterly.

300.0

To S. end center, identical with Loc. Mon. and N. end center Copper Bell No.5 lode of this Sur., heretofore described.

600.0

To Cor. No.4, identical with Loc. Mon. and Cor. No.3 Copper Bell No.5 lode of this Sur., heretofore described.

On line 2-3 Copper Bell No.6 lode of this Sur. at S. 1°12'W., 89.74 ft. from Cor. No.2

Thence N.2°52'E.  
Va. 13°45'E.

89.6

Intersect line 1-2 Copper Bell No.6 lode of this Sur. at S.84°49'E., 2.61 ft. from Cor. No.2. Also at Cor. No.3 Sunshine lode of this Sur., hereinafter described.

389.6

To W. end center Sunshine lode of this Sur., hereinafter described.

689.6

To Cor. Nos. 3-4 Darby No.1 and Sunshine lodes respectively of this Sur., hereinafter described.

989.6

To W. end center Darby No.1 lode of this Sur., hereinafter described.

1289.6

To Cor. No.4 Darby No.1 lode of this Sur. and Cor. No.2 Sur. No. 3488 Bright Star No.2 lode, hereinafter described.

1500.0

To Cor. No.1, the place of beginning.

FLAT IRON Lode.

Beginning at Cor. No. 1, identical with Loc. Mon. and Cor. No.2 Eclipse lode of this Sur. and Cor. Nos. 4 and 3, Sur. No.3488 Wolverine No. 8 and 11 lodes respectively.

An iron pipe 3 ins. diam. with copper cap on top, showing 24 ins. above ground, stamped 1 F.I, 2 E.-4061 and 4 Wolv.No.8, 3 Wolv.11-3488 with md. of stone alongside, whence the Cor. to Secs.26,27,34,35



Feet.	MINERAL SURVEY NO. 4061
	FLAT IRON Lode - Continued.
	T.12 S., R. 6 W. brs. S.49°43'10" W., 784.8 ft.
	No other bearings are available.
	Thence S. 86°17'E.
	Va. 13°45'E.
300.0	To N. end Center, identical with Loc. Mon. and S. end center Sur.No.3488 Wolverine No.11 lode.
	A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. F.I, S. Cr. Wolv. No.11 .
600.0	To Cor. No. 2, identical with Loc. Mon. and Cor. No.2 Copper Bell No. 9 lode of this Sur. and Cor. Nos. 4 Sur. No.3488 Wolverine Nos 11 and 12 lodes, heretofore described.
	Thence S. 2°52'W.
	Va. 13°45'E.
1400.0	Road brs. southeasterly.
1460.0	Gulch brs. southeasterly.
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 3,4 and 3, Copper Bell No.4, Copper Bell No.5 and Copper Bell No.9 lodes respectively of this Sur., heretofore described.
	Thence N. 86°17' W.
	Va. 13°45'E.
300.0	To S. end center, identical with Loc. Mon. and N. end center Copper Bell No.4 lode of this Sur., heretofore described.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 3,3 and 4, Eclipse, Copper Bell No.3 and Copper Bell No.4 lodes respectively of this Sur., heretofore described.
	Thence N. 2°52' E.
	Va. 13°45'E.
130.0	Gulch brs. easterly.
550.0	Road brs. southeasterly.
1500.0	To Cor. No.1, the place of beginning.



Feet.

## MINERAL SURVEY NO. 4061.

## J. B. M. lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2 King lode of this Sur. and Cor. No.3. Sur. No.3598 Fire Fly lode, Little Ajo Mining Co., Claimant.

A pine post 4 ins. sq showing 24 ins. above ground set firmly in the ground and surrounded with md of stone, scribed 1 J.B. M., 2 K. - 4061, 3 F.F. - 3598, with md of stone alongside., whence the 1/4 Cor. bet. Secs. 27,34, T. 12S. R. 6 W. brs. S. 25° 17'E., 818.71 ft.

No other bearings are available.

Thence N. 86°17'W.

Va. 13°45'E.

300.0 To N. end center, identical with Loc. Mon.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. J.B. M.

600.0 To Cor. No.2, identical with Loc. Mon.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, in concrete base, stamped 2 J.B.M.-4061 with md. of stone alongside.

No bearings are available.

Thence S. 2°52'W.

Va. 13°45'E.

860.0 Road brs. southeasterly.

960.0 Gulch brs. southeasterly.

1100.0 Gulch brs. easterly.

1500.0 To Cor. No.3, identical with Loc. Mon.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, in concrete base, stamped 3 J.B. M. - 4061 with md. of stone alongside.

No bearings are available.

Thence S. 86°17'E.

Va. 13°45'E.

300.0 To S. end center, identical with Loc. Mon.

A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and



Feet.	MINERAL SURVEY NO. 4061
	J.B. M. lode, Cont'd.
	surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed S. Cr. J.B. M.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. No.3 King lode of this Sur.
	An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 4 J.B. M., 3 K - 4061 with md of stone alongside.
	No bearings are available.
	Thence N. 2°52'E. Va. 13°45'E.
270.0	Gulch brs. easterly.
390.0	Road brs. southeasterly.
1500.0	To Cor. No.1, the place of beginning.
	FOX No.1 Lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2 Fox No.2 lode of this Sur. and Cor. Nos. 4 and 3 Sur. No.3488 Hope No.1 and Wolverine No.7 lodes respectively.
	An iron pipe 3 ins. diam. showing 24 ins. above ground with copper cap on top, stamped 1 F. No.1, 2 F. No.2, -4061, 4 Hope No.1, 3 Wolv. No.7 - 3488 with md of stone alongside, whence the Cor. to Secs. 26,27,34 and 35 T. 12S. R. 6 W. brs. S.45°39'20"E., 837.21 ft.
	No other bearings are available.
	Thence N. 86°17'W. Va. 13°45'E.
300.0	To N. end center, identical with Loc. Mon. and S. end center Sur.No.3488 Hope No.1 lode of Alpine post 4 ins. sq by 4 ft. high set firmly in the ground and surrounded with md.of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. F. No.1, S. Cr. H. No.1
600.0	To Cor. No.2, identical with Loc. Mon. and Cor. No.2 Mary B. lode of this Sur. and Cor. Nos3 Sur. No.3488 Hope No.1 lode and Cor. No.4 Sur. No.3598 Fire Fly No.1 lode.
	An iron pipe 3 ins diam. showing 24 ins. above ground with copper cap on top, stamped 2 F.No.1, 2 M.B. -4061, 3 Hope No.1-3488, 4 F.F. No.1-3598, with md of stone alongside.



Feet.	MINERAL SURVEY NO. 4061
	FOX NO. 1 Lode Cont'd.
	No bearings are available.
	Thence S. 2°52'W. Va. 13°45'E.
740.0	Road brs. northeasterly.
860.0	Gulch brs. northeasterly.
1500.00	To Cor. No.3, identical with Loc? Mon. and Cor. Nos.3,3 Copper Bell No.1 and Mary B lodes of this Sur., heretofore described.
	Thence S. 86°17'E. Va. 13°45'E.
70.0	Road brs. southerly.
300.0	To S. end center, identical with Loc. Mon. and N. end center Copper Bell No.1 lode of this Sur., heretofore described.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. Nos. 4,3 and 3, Copper Bell No.1, Copper Bell No.2 and Fox No.2 lodes respectively of this Sur., heretofore described.
	Thence N. 2°52'E. Va. 13°45'E.
850.0	Road and Gulch brs. northeasterly.
1170.0	Road brs. northeasterly.
1500.0	To Cor. No.1, the place of beginning.
	FOX NO. 2 Lode.
	Beginning at Cor. No.1 identical with Loc. Mon. and Cor. No.1 Eclipse lode of this Sur. also Cor. Nos. 3-4 Sur. No.3488 Wolverine No.8 and Wolverine No.7 lodes respectively.
	An iron pipe 3 ins. diam. with copper cap on top, showing 24 ins. above ground, stamped 1 F. No.2, 1 E.-4061, 3 Wolv. No.8, 4 Wolv. No.7 - 3488 with md. of stone alongside. Whence the Cor. to Secs. 26,27,34 and 35 T. 12 S. R. 6 W. brs. South 546.28 ft.
	No other bearings are available.
	Thence N. 86°17' W. Va. 13°45'E.
280.0	Road and gulch brs. northeasterly.
300.0	To N. end center, identical with Loc. Mon. and S. end center Sur. No.
	3488 Wolverine No.7 lode.



Feet.	MINERAL SURVEY NO. 4061
	FOX NO. 2 Lode - Cont'd.
	A pine post 4 ins. sq by 4 ft. high set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. F. No.2, S. Cr. Wolv. No.7.
600.0	To Cor. No.2, identical with Loc. Mon and Cor. No. 1 Fox No.1 lode of this Sur. and Cor. Nos. 3-4 Sur. No.3488 Wolverine No.7 and Hope No.1 lodes respectively, heretofore described.
	Thence S. 2°52'W. Va. 13°45'E.
320.0	Road brs. northeasterly.
650.0	Road and gulch brs. northeasterly.
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 4, 4 and 3 Fox No.1, Copper Bell No.1 and Copper Bell No.2 lodes respectively of this Sur., heretofore described.
	Thence S. 86°17'E. Va. 13°45'E.
300.0	To S. end center, identical with Loc. Mon. and N. end center Copper Bell No.2 lode of this Sur., heretofore described.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. Nos.4,4 and 4 Copper Bell No.2, Copper Bell No.3 and Eclipse lodes of this Sur. heretofore described.
	Thence N. 2°52'E. Va. 13°45'E.
25.0	Gulch brs. easterly.
1050.0	Road brs. southeasterly.
1500.0	To Cor. No.1, the place of beginning.
	MARY B. lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2 M.G. Lode of this Sur. and Cor. Nos. 3 and 4 Sur. No. 3598 Fire Fly No.1 and Fire Fly No.2 lodes respectively.
	A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed 1.M.B., 2 M.G. - 4061, 3 F.F. No.1, 4 F.F. No.2 - 3598 with md of stone alongside, whence the 1/4 Cor. bet. Secs. 27 - 34 T. 12S., R. 6 W. brs. S.51°59'40" W., 1075.96 ft.

No other bearings are available.



Feet.	MINERAL SURVEY No.4061
	MARY B. lode -) Cont'd.
	Thence S. 86°17'E.
	Va. 13°45'E.
299.7	To N. end center, identical with Loc. Mon. and S. end center Sur. No.3598 Fire Fly No.1 lode.
	A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft high, scribed N. Cr. M.B., S. Cr. F.F. No.1 .
599.7	To Cor. No.2 , identical with Loc. Mon. and Cor. No.2 Fox No.1 lode of this Sur., and Cor. No.4 Sur. No.3598 Fire Fly No.1 lode and Cor. No. 3 Sur. No.3488 Hope No.1 lode, heretofore described.
	Thence S. 2°52'W.
	Va. 13°45'E.
740.0	Road brs. northeasterly.
860.0	Gulch brs. northeasterly.
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 3,3 Fox No.1 and Copper Bell No.1 lodes of this Sur., heretofore described.
	Thence N. 86°17'W.
	Va. 13°45'E.
300.0	To S. end center, identical with Loc. Mon.
	A pine post 4 ins. sq by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed S. Cr. M.B.
599.7	To Cor. No.4, identical with Loc. Mon. and Cor. No.3 M.G. lode of this Sur.
	An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins in the ground , stamped 4 M.B. , 3 M. G. - 4061 with md. of stone alongside.
	No bearings are available.
	Thence N.2°52'E.
	Va. 13°45'E.
400.0	Road brs. northeasterly.
470.0	Gulch brs. northeasterly.
1500.0	To Cor. No.1, the place of beginning.



Feet.	MINERAL SURVEY NO. 4061
	. ECLIPSE - Lode. .
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1 Fox No.2 lode of this Sur. and Cor. Nos. 4 and 3 Sur. No.3488, Wolverine No.7 and Wolverine No.8 lodes respectively, heretofore described, whence the Cor. to Secs. 26,27,34 and 35 T.12S. R. 6 W., brs. South 546.28 ft.
	Thence S.86°17'E. Va. 13°45'E.
300.0	To N. end center, identical with Loc. Mon. and S. end center Sur. No.3488 Wolverine No.8 lode.
	A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. E., S Cr. Wolv. No.8 .
600.0	To Cor. No.2, identical with Loc. Mon. and Cor. No.1 Flat Iron lode of this Sur. and Cor. Nos. 4,3 Sur. No.3488 Wolverine No.8 and Wolverine No.11 lodes respectively, heretofore described.
	Thence S. 2°52'W. Va. 13°45'E.
950.0	Road brs. southeasterly.
1370.0	Gulch brs. easterly.
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. Nos. 3,4 and 4 Copper Bell No.3, Copper Bell No.4 and Flat Iron lodes respectively of this Sur., heretofore described.
	Thence N. 86°17'W. Va. 13°45'E.
300.0	To E. end center, identical with Loc. Mon. and N. end center Copper Bell No. 3 lode of this Sur., heretofore described.
600.0	To Cor. No.4 , identical with Loc. Mon. and Cor. Nos. 4,4 and 4 Fox No.2, Copper Bell No.2, and Copper Bell No.3 lodes of this Sur., heretofore described.
	Thence N. 2°52'E. Va. 13°45'E.
25.0	Gulch brs. easterly.
1050.0	Road brs. southeasterly.
1500.0	To Cor. No.1, the place of beginning.



Feet.

MINERAL SURVEY NO. 4061.

KING Lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1 M.G. lode of this Sur. and Cor. Nos. 4 and 3, Sur. No.3598 Fire Fly and Fire Fly No.2 lodes respectively .

A pine post 4 ins. sq. showing 24 ins. above ground , surrounded with md of stone , scribed 1 K, 1 M.G. -4061 , 4 F.F., 3 F.F. No.2 -3598 with md of stone alongside, whence the 1/4 Cor. bet. Secs. 27 and 34 T. 12S., R. 6 W. brs. S. 19°33'W., 744.3 ft.

No other bearings are available.

Thence N. 86°17'W.  
Va. 13°45'E.

300.0 To N. end center, identical with Loc. Mon. and S. end center Sur. No.3598 Fire Fly lode.

A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with. md of stone 3 1/2 ft. base by 3 ft. high, scribed. N. Cr. K, S. Cr. F.F.

600.0 To Cor. No.2, identical with Loc. Mon. and Cor. No.1 J.B. M. lode of this Sur. and Cor. No.3, Sur. No.3598 Fire Fly lode, heretofore described.

Thence S. 2°52'W.  
Va. 13°45'E.

1110.0 Road brs. southeasterly.

1230.0 Gulch brs. easterly.

1500.0 To Cor. No.3, identical with Loc. Mon. and Cor. No.4 J.B. M. lode of this Sur., heretofore described.

Thence S. 86°17'E.  
Va. 13°45'E.

300.0 To S. end center, identical with Loc. Mon.

A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed S. Cr. K.

310.0 Road brs. southwesterly.

600.0 To Cor. No.4, identical with Loc. Mon. and Cor. No.4 M.G. lode of this Sur.

An iron pipe 2 ins. diam. with cap on top 24 ins. above ground set 18 ins. in the ground, stamped 4 K, 4 M.G. - 4061 with md of stone alongside.



Feet.	MINERAL SURVEY NO. 4061
	King Lode. Cont'd.
	No bearings are available.
	Thence N. 2°52'E. Va. 13°45'E.
320.0	Gulch brs. easterly.
1500.0	To Cor. No.1, the place of beginning.
	M.G. Lode.
	Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.1
	King lode of this Sur. and Cor. Nos. 4 and 3 Sur. No.3598 Fire Fly
	and Fire Fly No.2 lodes respectively, heretofore described.
	The $\frac{1}{2}$ Cor. between Secs. 27 and 34, T.12S., R.6 W., brs. S.19° 33' W. 744.3 ft. Thence S. 86°17'E. Va. 13°45'E.
300.0	To N. end center, identical with Loc. Mon. and S. end center Sur. No.3598 Fire Fly No.2 lode.
	A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed N. Cr. M.G., S. Cr. F.F. No.2.
600.0	To Cor. No.2, identical with Loc. Mon. and Cor. No.1 Mary B. lode of this Sur. and Cor. Nos. 4 and 3 Sur. No.3598, Fire Fly No.2 and Fire Fly No.1 lodes respectively, heretofore described.
	Thence S. 2°52'W. Va. 13°45'E.
1030.0	Gulch brs. northeasterly.
1100.0	Road brs. northeasterly.
1500.0	To Cor. No.3, identical with Loc. Mon. and Cor. No.4 Mary B. lode of this Sur., heretofore described.
	Thence N. 86°17'W. Va. 13°45'E.
300.0	To S. end center, identical with Loc. Mon.
	A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed S. Cr. M.G.
430.0	Road brs. southwesterly.
600.0	To Cor. No.4, identical with Loc. Mon. and Cor. No.4 King lode of this Sur., heretofore described.



Feet.

MINERAL SURVEY No.4061

M.G. Lode - Cont'd.

Thence N. 2°52'E.  
Va. 13°45'E.

1500.0 To Cor. No.1, the place of beginning.

SUNSHINE Lode.

Beginning at Cor. No.1, identical with Loc. Mon. and Cor. No.2  
Darby No.1 lode of this Sur.

An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground,  
set 18 ins. in the ground, stamped 1 S, 2 D No.1 -4061 with md. of stone  
alongside, whence the 1/4 Cor. bet. Secs. 26 and 35 T. 12S. R. 6 W.  
brs. N. 48°51'40"W., 782.27 ft.

Cor. Nos 1 and 1 Sur. No.3881 , Copper Ridge No.6 and Copper Ridge  
No.11 lodes brs. N. 44°41'W., 259.8 ft.

No other bearings are available.

Thence S. 2°52'W.  
Va. 13°45'E.

300.0 To E. end center, identical with Loc. Mon.

A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground  
and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed  
E. Cr. S.

600.0 To Cor. No.2, identical with Loc. Mon. On line 2-3 Sur. No.3881  
Copper Ridge No.11 lode at S.59°43'E.527.19 ft. from Cor. No.2  
and on line 1-2 Copper Bell No.8 lode of this Sur.

An iron pipe 2 ins. diam. with cap on top 24 ins. above ground,  
set 18 ins. in the ground, stamped 2 S -4061.

No bearings are available.

Thence <sup>N</sup> 84°49'W.  
Va. 13°45'E.

285.5 To Cor. Nos. 1 and 2, Copper Bell No.8 and Copper Bell No.7 lodes  
respectively of this Sur., heretofore described.

585.5 To N. end center Copper Bell No.7 lode of this Sur., heretofore  
described.

885.5 To Cor. Nos. 1 and 1, Copper Bell No.6 and Copper Bell No.7 lodes  
of this Sur., heretofore described.

1185.5 To N. End Center Copper Bell No.6 lode of this survey, heretofore described.

1482.89 To Cor. No.3, identical with Loc. Mon. On line 4-1 Copper Bell



Feet.	MINERAL SURVEY NO. 4061 SUNSHINE Lode. - Cont'd.
	<p>No. 9 lode of this Sur.</p> <p>An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground set 18 ins. in the ground, stamped 3 S - 4061.</p> <p>Cor. No.2 Copper Bell No.6 lode of this Sur. Brs.N.84°49'W.,2.61 ft/</p> <p>No other bearings are available.</p> <p>Thence N. 2°52'W. Va. 13°45'E.</p>
300.0	<p>To W. end center, identical with Loc. Mon.</p> <p>An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, stamped W. Cr. S.</p>
600.0	<p>To Cor. No.4, identical with Loc. Mon. and Cor. No.3 Darby No.1 lode of this Sur. On line 4-1 Copper Bell No.9 lode of this Sur.</p> <p>An iron pipe 2 ins. diam. with cap on top, 24 ins. above ground, set 18 ins. in the ground, stamped 4 S, 3 D. No.1 - 4061 with md. of stone alongside.</p> <p>No bearings are available.</p> <p>Thence S. 84°49'E. Va. 13°45'E.</p>
1205.81	<p>Intersect line 1-2 Sur. No.3881 Copper Ridge No.11 lode at S.30°17'W 184.92 ft. from Cor. No.1 and N.30°17'E.,415.08 ft. from Cor. No.2.</p>
1482.89	<p>To Cor. No.1, the place of beginning.</p> <p>DARBY NO. 1 lode.</p> <p>Beginning at Cor. No.1, identical with Loc. Mon. On line 2-3 Sur. No.3488 Bright Star No.2 lode at N. 84°49'W.,17.85 ft. from Cor. No.3.</p> <p>An iron pipe 2 ins. diam. with cap on top, 3 ft. above ground, set 12 ins. in drilled hole in conglomerate ledge, surrounded with md. of concrete, 18 in. base by 12 ins. high, stamped 1 D. No.1-4061 with md. of stone alongside, whence the 1/4 Cor. bet. Secs. 26 and 35 T. 12S. R. 6 W. brs. S. 82°13'10" W.,624.9 ft.</p> <p>No other bearings are available.</p> <p>Thence S. 2°52'W. Va. 13°45'E.</p>
55.08	<p>Intersect line 1-2 Sur. No.3881 Copper Ridge No. 6 lode at S.30°</p>



Feet.

MINERAL SURVEY NO. 4061  
DARBY NO.1 lode - Cont'd.

17' W., 183.67 ft. from Cor. No.2 and N. 30°17'E., 416.33 ft. from Cor. No.1.

524.09 Intersect lines 4-1 Sur. No.3881, Copper Ridge No.6, and Copper Ridge No.11 lodes at S. 59°43'E., 215.96 ft. from Cor. Nos.1 and N.59°43'W., 1284.04 ft. from Cor. Nos.4.

600.0 To Cor. No.2, identical with Loc. Mon. and Cor. No.1 Sunshine lode of this Sur., heretofore described.

Thence N. 84°49'W.  
Va. 13°45'E.

277.08 Intersect line 1-2 Sur. No.3881 Copper Ridge No.11 lode at S.30°17'W., 184.92 ft. from Cor. No.1.

1482.89 To Cor. No.3, identical with Loc. Mon. and Cor. No.4 Sunshine lode of this Sur. heretofore described. On line 4-1 Copper Bell No.9 lode of this Sur.

Thence N. 2°52'E.  
Va. 13°45'E.

300.0 To W. end center, identical with Loc. Mon.

An iron pipe 2 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, stamped

W. Cr. D No.1

600.0 To Cor. No.4, identical with Loc. Mon. and Cor. No.2 Sur. No.3488 Bright Star No.2 lode. On line 4-1 Copper Bell No.9 lode of this Sur.

An iron pipe 3 ins. diam. with copper cap on top, showing 24 ins. above ground, stamped 4 D. No.1 -4061, 2 B.S. No.2 -3488.

No bearings are available.

Thence S. 84°49'E. (~~Rec. S. 84°48'30"E~~)  
Va. 13°45'E.

1482.89 To Cor. No.1, the place of beginning.



MINERAL SURVEY NO. 4061

Lode Lines.

As near as can be determined from the present developments, the veins of the several locations embraced in this claim, extend as follows from their respective discoveries.

Copper Bell No.1 lode,	450.0 ft. S.1°12'W., and 1050.0 ft. N.1°12'E.
Copper Bell No.2 lode,	525.0 ft. N.1°12'E., and 975.0 ft. S.1°12'W.
Copper Bell No.3 lode,	100.0 ft. N.1°12'E., and 1400.0 ft. S.1°12'W.
Copper Bell No.4 lode,	100.0 ft. N.1°12'E., and 1400.0 ft. S.1°12'W.
Copper Bell No.5 lode,	200.0 ft. N.1°12'E., and 1300.0 ft. S.1°12'W.
Copper Bell No.6 lode,	100.0 ft. N.1°12'E., and 1400.0 ft. S.1°12'W.
Copper Bell No.7 lode,	100.0 ft. N.1°12'E., and 1400.0 ft. S.1°12'W.
Copper Bell No.8 lode,	100.0 ft. N.1°12'E., and 1400.0 ft. S.1°12'W.
Copper Bell No.9 lode,	415.0 ft. N.2°52'E., and 1085.0 ft. S.2°52'W.
Flat Iron lode,	100.0 ft. N.2°52'E., and 1400.0 ft. S.2°52'W.
J.B.M. lode,	150.0 ft. S.2°52'W., and 1350.0 ft. N.2°52'E.
Fox No.1 lode,	200.0 ft. S.2°52'W., and 1300.0 ft. N.2°52'E.
Fox No.2 lode,	300.0 ft. N.2°52'E., and 1200.0 ft. S.2°52'W.
Mary B. Lode ,	110.0 ft. N.2°52'E., and 1390.0 ft. S.2°52'W.
Eclipse lode.,	375.0 ft. N.2°52'E., and 1125.0 ft. S.2°52'W.
King lode,	100.0 ft. S.2°52'W., and 1400.0 ft. N.2°52'E.
M.G. lode,	125.0 ft. S.2°52'W., and 1375.0 ft. N.2°52'E.
Sunshine lode,	22.0 ft. N.84°49'W., and 1460.89 ft. S.84°49'E.
Darby No.1 lode ,	110.0 ft. N.84°49'W., and <sup>1372.69</sup> <del>1390.0</del> ft. S.84°49'E.

AREA.

	Acres.
Total area Copper Bell No.1 lode-----	20.641
Total area Copper Bell No.2 lode -----	20.641
Total area Copper Bell No.3 lode -----	20.641
Total area Copper Bell No.4 lode -----	20.641
Total area Copper Bell No.5 lode -----	20.641
Total area Copper Bell No.6 lode.-----	20.611
Area in conflict with-	
Copper Bell No.9 lode, of this Sur.-	0.003
Total area Copper Bell No.7 lode -----	20.611
Total area Copper Bell No.8 lode -----	20.611
Area in conflict with-	
Sur. No. 3281 Copper Ridge No. 11 lode	.550



MINERAL SURVEY No.4061

AREA - Continued.

	Acres.
Total area Copper Bell No.9 lode -----	20.659
Total area Flat Iron lode -----	20.659
Total area J.B.M lode. -----	20.659
Total area Fox No.1 lode -----	20.659
Total area Fox No.2 lode -----	20.659
Total area Mary B. lode -----	20.649
Total area Eclipse lode -----	20.659
Total area King lode -----	20.659
Total area M.G. lode -----	20.659
Total area Sunshine lode -----	20.409
Area in conflict with -	
Sur. No.3881 Copper Ridge No.11 lode - 4.418	
Total area Darby No.1 lode -----	20.409
Area in conflict with-	
Sur. No.3881 Copper Ridge No.11 lode - 0.700	
Sur. No.3881 Copper Ridge No.6 lode - 1.032	

LOCATION.

This Survey is located in the S. 1/2 Secs 26, and 27 and the N 1/2 and the SE 1/4 of Sec. 35. Secs. 34 and 35, T. 12S., R. 6 W.

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements made upon or for the benefit of each of the locations embraced in said mining claim by the claimant or his grantors is not less than five hundred dollars, and that said improvements consist of :

Copper Bell No.1 lode.

No.1 The discovery shaft, the center of which being the discovery point , on the center line 450 ft. from the center of line 1-2, 4 x 6 ft. 8ft. deep.

Value \$100.0

No.2 A shaft, on the center line 475 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.3 A shaft, the center of which brs. from Cor. No.3, S.23°30'E., 650.0 ft., 4 x 6 ft. 40 ft. deep.

Value \$400.0



## MINERAL SURVEY NO.4061

## EXPENDITURE OF FIVE HUNDRED DOLLARS.

## Copper Bell No.2 lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line, 525.0 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.3 S.33°30'E., 440.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.3 Antrench the N. end of which brs. from Cor. No.4 S.32°W., 170.0 ft. 4 ft. wide, 4 ft. deep, running South 60 ft.

Value \$200.0

No.4 A shaft, the center of which brs. from Cor. No.4 S.3°W., 325.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.2 ,N.22°15'E., 730.0 ft. , 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.6 A shaft, on the center line, 450 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep.

Value \$100.0

## Copper Bell No.3 lode.

No.1, the discovery shaft, the center of which being the discovery point, on the center line , 100 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.2 A cut, the mouth of which brs. from Cor. No.4 , S.55°E., 270.0 ft. 4 1/2 ft. wide, 6 ft. face running N.50°E., 30 ft. to face , at face is a shaft. 4 x 6 ft. 8 ft. deep.

Value cut and shaft. \$200.0

No.3 A shaft, the center of which brs. from Cor. No.3 S.49°30'W., 50 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.1, N.15°15'E., 650.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0



MINERAL SURVEY NO. 4061

EXPENDITURE OF FIVE HUNDRED DOLLARS , Cont'd.

Copper Bell No.4 lode.

No.1, the discovery, <sup>shaft</sup> the center of which being the discovery point, on the center line 100 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.4 S.80°15'E., 240.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.3 A trench, the N. end of which brs. from Cor. No.3, S.87°W., 60.0 ft. 4 1/2 ft. wide, 4 ft. deep, running S. 30° W., 30 ft. to S. end.

Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.1 N.7°30'E., 780.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.5 A shaft., the center of which brs. from Cor. No. 2 N.33°15'W., 440.0<sup>ft</sup> 4 x 6 ft. 8 ft. deep.

Value \$100.0

Copper Bell No.5.

No.1 A shaft, the center of which being the discovery point, on the center line 200 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.2 A shaft, the center of which brs. from the N. end center S.47°30' W., 60.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.3 A cut, the mouth of which brs. from Cor. No.3 S.35°45'W., 110.0 ft. 4 ft. wide, 8 ft. face, running S.30° W., 12 ft. to face.

Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.4 S.7°45'E., 310 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.4, S.7°45'E., 380.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.6 A shaft, the center of which brs. from Cor. No.1, N.24°30'E., 650.0 ft. 4 x 6 ft. 4 ft. deep.

Value 40.0



MINERAL SURVEY NO. 4061

Expenditure of Five Hundred Dollars, Cont'd.

Copper Bell No.6 lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line 100.0 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, the center of which hrs. from Cor. No. 1, S.69°30'W., 190.0 ft. 4 x 6 ft. 7 ft. deep. Value \$80.0

No.3 A shaft, the center of which hrs. from Cor. No.1, S.37°W., 400.0ft, 4 x 6 ft. 8 ft. deep. Value 100.0

No.4 A shaft, the center of which hrs. from Cor. No.1, S.27°30'W., 475.0ft, 4 x 6 ft. 8 ft. deep. Value 100.0

No.5 A shaft, the center of which hrs. from Cor. No. 3 N.77°45'E., 275ft, 4 x 6 ft. 8 ft. deep. (caved) Value \$100.0

No.6 A cut, the mouth of which hrs. from Cor. No.4, N.10°15'W., 81.0 ft. 4 ft. wide 8 ft. face running N.10°W., 15 ft. to face. Value \$100.0

Copper Bell No.7

No.1, the discovery shaft, the center of which being the discovery point, on the center line, 100 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$ 100.0

No.2 A shaft, the center of which hrs. from Cor. No.2 S.17°W., 140.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.3 A shaft, the center of which hrs. from Cor. No.3 N.43°15'W., 290.0 ft. 4 x 12 ft. 8 ft. deep. Value \$200.0

No.4 A shaft, the center of which hrs. from Cor. No. 3 N.44°W., 260.0 ft. 4 x 12 ft. 8 ft. deep. Value \$200.0

No.5 A shaft, the center of which hrs. from Cor. No.3, N.43°15'W., 230.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

Copper Bell No.8.

No.1 The discovery shaft, the center of which being the discovery point, on the center line 100.0 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, the center of which hrs. from Cor. No.3, N.9°W., 650.0 , 4 x 6 ft. 8 ft. deep. Value \$100.0



MINERAL SURVEY NO. 4061

EXPENDITURE OF FIVE HUNDRED DOLLARS , Cont'd.

Copper Bell No.8 lode, Cont'd.

No.3 A shaft, the center of which brs. from Cor. No.3, N.9°W., 635.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.4, A shaft, the center of which brs. from Cor. No.3, N.9°W., 600.0 ft. 4 x 20 ft. 8 ft. deep. Value \$300.0

No.5 A shaft, the center of which brs. from Cor. No.3, N.20°15'W., 380.0 ft. 4 x 6 ft. 6 ft. deep. Value \$60.0

Copper Bell No.9 lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line 415 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.1, S.22°30'W., 100.0 ft. 4 x 12 ft. 8 ft. deep. Value \$200.0

No.3 A shaft, the center of which brs. from Cor. No.1, S.28°W., 565.0 ft. 4 x 6 ft. 8ft. deep. Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.1, S.22°30'W., 560.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.3, N.18°45'E., 770.0 ft. 4 x 6 ft. 8ft. deep. Value \$100.0

No.6 A shaft, the center of which brs. from Cor. No.3, N. 8°30'E., 715 ft., 4 x 6 ft. 8ft. deep. Value \$100.0

No.7 A shaft, the center of which brs. from Cor. No.3, N.25°30'E., 515.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.8 A shaft, the center of which brs. from Cor. No.3, N.30°30'E., 220.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.9 A shaft, the center of which brs. from Cor. No.1, S.7°W., 850.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

Flat Iron lode.

No.1, the discovery shaft, the center of which being the discovery point, on the center line, 100 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.1, S.22°E., 330.0 ft., 4 x 6 ft. 8 ft. deep. Value \$100.0



## MINERAL SURVEY NO. 4061

## EXPENDITURE OF FIVE HUNDRED DOLLARS - Cont'd.

## Flat Iron lode, Cont'd.

No.3 A shaft, the center of which brs. from Cor. 2 S.17°W., 410.0 ft. 4 x 6 ft. 10 ft. deep. Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.4, N.16°E., 640.0<sup>#</sup>, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.4, N.28°E., 490.0 ft. 4 x 6 ft. 4 ft. deep. Value \$40.0

No.6 A shaft, the center of which brs. from Cor. No.4, N.34°45'E., 380.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.7 A shaft, the center of which brs. from Cor. No.3, N.50°45'W., 220.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.8 A cut, the face of which is on the center line, 30 ft. from the center of line 3-4, 4 ft. wide, 4 ft. face, running N.40°E., 12 ft. to mouth. Value \$50.0

## J.B. M. lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line, 150.0 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, on the center line, 180 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.3 A shaft, the center of which brs. from Cor. No.4, N.41°30'W., 230.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.4 N. 9° W., 545.0 ft. 4 x 6 ft. 4 ft. deep. Value \$40.0

No.5 A shaft, the center of which brs. from Cor. No.4, N.6°30'W., 590.0 ft. 4 x 12 ft. 8 ft. deep. Value \$200.0

No.6 A shaft, the center of which brs. from Cor. No.4, N.6°30'W., 700.0, 4 x 6 ft. 10 ft. deep. Value \$100.0

No.7 A shaft, on the center line, 80 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.8 A shaft, the center of which brs. from Cor. No.1, S.37°W., 110.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0



MINERAL SURVEY NO. 4061

EXPENDITURE OF FIVE HUNDRED DOLLARS - Cont'd.

Fox No.1 lode.

No.1, the discovery shaft, the center of which being the discovery point, on the center line, 200 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2, A shaft, the center of which brs. from Cor. No.3, N.43°30'E., 290.0 ft. 4 x 6 ft. 15 ft. deep. Value \$150.0

No.3 A shaft, on the center line 600 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.3, N.25°30'E., 650.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.3, N.27°E., 645.0 ft. 4 x 6 ft., 8 ft. deep. Value \$100.0

No.6 A shaft, the center of which brs. from Cor. No.3, N.30°E., 625.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.7 A shaft, the center of which brs. from Cor. No.1, S.48°W., 175.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

Fox No.2 lode.

No.1, The discovery shaft, the center of which being the discovery point, on the center line, 300 ft. from the center of line 1-2, 4 x 6 ft. 50 ft. deep. Value \$500.0

No.2 A shaft, on the center line, 325 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.3 A shaft, the center of which brs. from Cor. No.1, S.46°W., 470.0 ft. 4 x 6 ft. 8ft. deep. Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.1 S.56°W., 340.0 ft. 4 x 6 ft. 8 ft. deep (caved) Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.3, N.35°E., 340.0 ft. 4 x 6 ft. 12 ft. deep. Value \$120.0

No.6 A shaft, the center of which brs. from Cor. No.4, N.13°W., 660.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No. 7 A shaft, the center of which brs. from Cor. No.4 N.1°W., 720.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.8 A shaft, the center of which brs. from Cor. No.4, N.2°E., 710.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0



## MINERAL SURVEY NO. 4061

## EXPENDITURE OF FIVE HUNDRED DOLLARS. Cont'd.

## Mary B. lode.

No.1 A shaft, the center of which being the discovery point, on the <sup>lode</sup> center line 110 ft. from the <sup>a point on</sup> center of line 1-2, <sup>299.7 ft. from Cor. No.1,</sup> 4 x 12 ft. 10 ft. deep.

Value \$200.0

No.2 A shaft, the center of which brs. from the N. end center, S. 14° W., 115.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.3, A shaft, the center of which brs. from the N. end center, S. 21°45'E., 100.0 ft. 4 x 20 ft. 8 ft. deep.

Value \$300.0

No.4 A shaft, on the center line, 20 ft. from the center of line 1-2, 4 x 6 ft. 16 ft. deep.

Value 100.0

No.5 A shaft, on the center line, 192 ft. from the center of line 3-4, 4 x 6 ft. 10 ft. deep.

Value \$100.0

## ECLIPSE Lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line, 375 ft. from the center of line 1-2, 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.1, S. 10°45'E., 380.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.3 A cut, the face of which brs. from Cor. No.2, S. 9° W., 300.0 ft. 4 ft. wide, 8 ft. face, running S. 10° E., 15 ft. to mouth.

Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.4, N. 4°45'E., 775.0 ft. 4 x 6 ft. 40 ft. deep.

Value \$400.0

No.5 A shaft, the center of which brs. from Cor. No.4, N. 8°45'E., 775.0 ft. 4 x 6 ft. 10 ft. deep.

Value \$100.0

No.6 A shaft, the center of which brs. from Cor. No. 4, N. 4°45'E., 710.0 ft., 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.7 A shaft, the center of which brs. from Cor. No.4, N. 11°15'E., 690.0 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.0

No.8 A shaft, the center of which brs. from Cor. No.4, N. 31°45'E., 490.0<sup>ft.</sup>, 4 x 6 ft. 8 ft. deep.

Value \$100.0



## MINERAL SURVEY NO. 4061

## EXPENDITURE OF FIVE HUNDRED DOLLARS - Cont'd.

## King lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line 100.0 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.4, N.48°30'W., 310.0 ft. 4 x 6 ft. 16 ft. deep. Value \$200.0

No.3 A trench, the south end of which brs. from Cor. No.3, N.35°E., 120.0 ft. 4 ft. wide, 3 ft. deep, running N.35°E., 60 ft. to N. end. Value \$200.0

No.4 A shaft, the center of which brs. from Cor. No.2, S.21°30'E., 600.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

## M.G. Lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line, 125 ft. from the center of line 3-4 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, the center of which brs. from the S. end center, N.43°30'W., 35 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.3 A shaft, on the center line, 165 ft. from the center of line 3-4, 4 x 6 ft. 14 ft. deep. Value \$180.0

No.4 A shaft, the center of which brs. from the S. end center, N.15°E., 170.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.4, N.15°30'E., 350.0 ft. 4 x 6 ft. 10 ft. deep. Value \$100.0

## Sunshine lode.

No.1 The discovery shaft, the center of which being the discovery point, on the center line 22 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep. Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.3, N.56°30'E., 200.0 ft. 4 x 20 ft. 10 ft. deep. Value \$300.0

No.3 A shaft, the center of which brs. from Cor. No.3, N.63°E., 200.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0



## MINERAL SURVEY NO. 4061

## EXPENDITURE OF FIVE HUNDRED DOLLARS - Cont'd.

## Sunshine lode, Cont'd.

No.4 A shaft, the center of which brs. from Cor. No.3, N.63°E.,  
230.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.1, N.86°W.,  
560.0 ft. 4 X 6 ft. 10 ft. deep. Value 100.0

No.6 A shaft, the center of which brs. from Cor. No.1, N.89°30'W.,  
450.0 ft. 4 x 6 ft. 10 ft. deep. Value \$100.0

No.7 A shaft, the center of which brs. from Cor. No. 3 ,N.71°30'E.,  
460.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.8 A cut, the mouth of which brs. from Cor. No.3, N.73°30'E.,  
350.0 ft. 4 ft. wide, 8 ft. face running East. 12 ft. to face.  
Value \$100.0

## Darby No.1 lode.

No.1 The discovery shaft, the center of which being the discovery  
point, on the center line 110.0 ft. from the center of line 3-4,  
4 x 6 ft. 10 ft. deep. Value \$100.0

No.2 A shaft, the center of which brs. from Cor. No.4, S. 1° E.,  
280.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.3 A shaft, the center of which brs. from Cor. No.4, S.22°45'E.,  
210.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.4 A shaft, the center of which brs. from Cor. No.4, S.17°E.,  
200.0 ft. 4 x 6 ft. 8 ft. deep. Value \$100.0

No.5 A shaft, the center of which brs. from Cor. No.4, S.60°30'E.,  
650.0 ft. 4 x 10 ft. 8 ft. deep. Value \$180.0

## OTHER IMPROVEMENTS.

A shaft on the center line Copper Bell No.9 lode , 20 ft. from the  
center of line 1-2 . 4 x 6 ft. 8 ft. deep.

A shaft on the center line Flat Iron lode, 20 ft. from the center  
of line 1-2, 4 x 6 ft. 8 ft. deep.

A shaft, on the center line Fox No.1 lode, 20 ft. from the center  
of line 1-2, 4 x 6 ft. 8 ft. deep.

A shaft, on the center line Fox No.2 lode, 20 ft. from the the  
center of line 1-2, 4 x 6 ft. 8 ft. deep.

A shaft, on the center line Eclipse lode 20 ft. from the center of  
line 1-2, 4x6 ft. 8 ft deep.



## MINERAL SURVEY NO. 4061 .

## Instrument.

This survey was made with a Gurley mountain transit, the courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 500 ft. steel tape.

## REPORT.

The lode lines of each location of this claim were run directly upon the ground , and the corners were established by running around the claims.

The 1/4 Corners bet. secs. 27~~34~~; 34 and 35; and 26 and 35 are all iron pipe capped with brass and stamped 1/4 with the number of the sections. The Cor. to Secs. 26, 27, 34 and 35 is an iron pipe 2 ins diam. capped with brass and stamped S.26, S 27, S.34 and S.35, T<sup>12</sup>S. R. 6 W.,

Cor. Nos. 3 and 4, Sur. No. 3598, Fire Fly and Fire Fly No.2 lodes and Cor. No.3 Fire Fly No.1 lode , All corners are pine posts 4 ins. sq properly set and scribed with the numbers of the corners and the survey. I find all courses and distances to be correct as approved.

Sur. No. 3488, Hope No.1, Wolverine Nos. 7, 8, 11 and 12 and Bright Fire Fly No.1 lode. Star No.2 lodes and Cor. No.4 Sur. No. 3598, All corners consist of iron pipe 3 ins. diam . showing 24 ins. above ground and stamped with the number of the corner and the survey .

I find all courses and distances to be correct as approved except line 2-3 Bright Star No.2 lode which fails to furnish the course and distance as approved ,(S. 84°48'30"E., 1500.0 ft.) and same is properly given in these field notes.

Sur. No. 3881, Copper Ridge Nos 6 and 11 lodes. All corners consist of iron pipe , 1 in. diam. capped with brass and stamped with the number of the corner and the survey.

I find all courses and distances to be correct as approved .

U.S. M.M. No.1 Consists of an iron pipe 2 1/2 ins. diam. by 15 ft. high surrounded with md of stone- Stamped U.S.M.M. No.1 Ajo Mining Dist. Pima County, Established Dec. 14, 1882 by L.D. Chillson, Re set Dec. 28, 1917 by Paul Fernald.



## MINERAL SURVEY NO. 4061

## ADJOINING CLAIMS.

On the north by Sur. No.3598, Fire Fly, Fire Fly No.1 and Fire Fly No.2 lodes, and Sur. No.3488 , Hope No.1, Wolverine No.7, Wolverine No.8, Wolverine No.11, Wolverine No.12 and Bright Star No.2 lodes.

On the East by Sur. No.3881 Copper Ridge No.6 and Copper Ridge No.11 lodes.

On the South by Copper Bell No.10 lode, unsurveyed, claimant herein,  
No other adjoining or conflicting claims known.

## Solar Observations.

The true courses of the lines of this Sur. were ascertained by direct solar observations submitted with the field notes of Mineral Survey Nos. 3598 and 3881.



# FINAL OATH OF U. S. MINERAL SURVEYOR

I, T.N. Stevens, U. S. Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer,  
at Phoenix, Arizona, dated January 27 1928,  
I have, in strict conformity to the laws of the United States, the official regulations and instruc-  
tions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly  
executed the survey of the Mining Claim of Edwin A. Stone  
\_\_\_\_\_, known as the  
COPPER BELL NOS. 1,2,3,4,5,6,7,8,9, FLAT IRON, J.B.M., FOX Nos.1,2, MARY B.,  
ECLIPSE, KING, M.G., SUNSHINE, and DARBY NO. 1 lodes.  
situate in Ajo Mining District,  
Pima County, Arizona, in Section  
26,27,34 and 35, Township No. 12 S., Range No. 6 W.  
and designated as Survey No. 4061, as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly  
marked by monuments on the ground, and described in the attached copy of the location certifi-  
cate, which was received by me from the Office Cadastral Engineer with said instructions, and  
that all corners of said survey have been established and perpetuated in strict accordance with  
the law, official regulations and instructions thereunder; and I do further solemnly swear that the  
foregoing are the true and original field notes of said survey and my report therein, and that the  
labor expended and improvements made upon said mining claim by claimant or his  
grantors are as therein fully stated, and that the character, extent, location, and itemized value  
thereof are specified therein with particularity and full detail, and that no portion of said labor  
or improvements so credited to this claim has been included in the estimate of expenditures upon  
any other claim.

T.N. Stevens  
U. S. Mineral Surveyor.

Subscribed and sworn to by the said T.N. Stevens  
U. S. Mineral Surveyor, before me E. J. Crisick  
Notary Public this 29<sup>th</sup>  
day of February, 1928

E. J. Crisick  
Notary Public



# FINAL OATHS FOR SURVEYS.

## LIST OF NAMES.

A list of the names of the individuals employed by T.N. Stevens

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of \_\_\_\_\_

Edwin A. Stone

known as the COPPER BELL NOS. 1,2,3,4,5,6,7,8,9, FLAT IRON, J.B.M., FOX NOS. 1,2, MARY B., ECLIPSE, KING, M.G., SUNSHINE and DARBY NOS. 1 lodes.

and showing the respective capacities in which they acted.

\_\_\_\_\_  
L.J. Booher, Chainman.

\_\_\_\_\_, Chainman.

\_\_\_\_\_, Axman.

\_\_\_\_\_, Flagman.

## FINAL OATHS OF ASSISTANTS.

We, L. L.J. Booher

and \_\_\_\_\_, do solemnly swear that we assisted \_\_\_\_\_

T.N. Stevens, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Edwin A. Stone

known as the COPPER BELL NOS. 1,2,3,4,5,6,7,8,9, FLAT IRON, J.B.M. FOX NOS. 1,2, MARY B., ECLIPSE, KING, M.G., SUNSHINE and DARBY NO. 1 lodes.

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of ~~our~~ knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the ~~United States Surveyor General~~ OFFICE CADASTRAL ENGINEER

L. J. Booher, Chainman.

\_\_\_\_\_, Chainman.

\_\_\_\_\_, Axman.

\_\_\_\_\_, Flagman.

Subscribed and sworn to by the above-named persons before me this 29<sup>th</sup>

day of February, 19 28

[Signature]  
Notary Public





U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

Department of the Interior, PUBLIC SURVEY OFFICE OFFICE OF U. S. SURVEYOR-GENERAL,

Phoenix, Arizona.

March 28, 1928

I, U. S. Surveyor-General for OFFICE CADASTRAL ENGINEER

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Edwin A. Stone known as the COPPER BELL NOS. 1, 2, 3, 4, 5, 6, 7, 8, 9, FOX NOS. 1, 2, MARY B., ECLIPSE, KING, W.G., SUNSHINE, and DARBY NO. 1 lodes situate in Ajo

Mining District, Pima County, Arizona

in Section 26, 27, 34, Township No. 12 S, Range No. 6 W., and

designated as Survey No. 4061, has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon each of said mining claims by claimant or his grantors, and that said improvements consist of 107 shafts, 6 cuts, and 3 trenches, total value \$13,940.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona, is correct and in conformity with the foregoing Field Notes.

John D. Adams

United States Surveyor-General for OFFICE CADASTRAL ENGINEER



~~SURVEYOR GENERAL'S~~ CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR  
~~OFFICE OF U. S. SURVEYOR GENERAL~~  
PUBLIC SURVEY OFFICE

Phoenix, Arizona,

March 28, 1928

~~I, U. S. Surveyor General for~~ OFFICE CADASTRAL ENGINEER

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

Edwin A. Stone

, known as the COPPER BELL NOS. 1,2,3,4,5,6,7,8,9, FLAT IRON, J.B.M., FOX NOS.1,2, MARY B., ECLIPSE, KING, M.G., SUNSHINE, and DARBY NO.1 lodes

situate in Ajo mining district,

Pima County, Arizona

in Sections 26, 27, 34, 35, Township No. 12 S., Range No. 6 W.

, designated as Survey No. 4061

executed by T. N. Stevens, U. S. Mineral

Surveyor, February 1 - 16, 1928, under my instructions dated

January 27, 1928, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

~~U. S. Surveyor General for~~ OFFICE CADASTRAL ENGINEER