

MINERAL SURVEY No. 4062 A & BCORONADO NATIONAL FORESTARIZONALand District**FIELD NOTES**

OF THE SURVEY OF THE MINING CLAIM OF

Muriel Huggett, of Oracle, Pinal County, Arizona.

KNOWN AS THE

POOR MANS LUCK lode; POOR MANS EXTENSION lode; POOR MANS EX-
TENSION NO. 2 lode; POOR MANS LUCK mill-site; POOR MANS EX-
TENSION mill-site.OLD HATMining District,PINALCounty,ARIZONASection unsurveyed
20, 28 & 29, Township 10 South, Range 16 EastSurveyed under instructions dated January 9, 1933.By Emmet R. MarxU. S. Mineral Surveyor.Claim located Lode Claims, September 26, 1923
Mill-Sites, May 9, 1925Survey commenced January 16, 1933Survey completed February 4, 1933Address of claimant care of Conner and Jones, Attorneys,
Consolidated National Bank Building,
Tucson, Arizona.

DATES OF AMENDED LOCATIONS

POOR MANS LUCK lode, January 27, 1928POOR MANS EXTENSION LODE January 27, 1928POOR MANS EXTENSIONNO. 2 lode January 27, 1928POOR MANS LUCK mill-site February 2, 1928POOR MANS EXTENSION mill-site February 10, 1928

SURVEY NO. 4062A

feet

Feet

Mineral Survey No. 4062A and B was made with a Young and Sons Mountain Transit, No. 6855, with a Smith Solar attachment. The horizontal limb of the transit is 5 1/2 inches in diameter and has two verniers reading to one minute of arc. It has a vertical arc of 60° with one vernier reading to one minute. The instrument was in good condition at the time of the survey and all adjustments were in good order. The meridian was determined by an observation on Polaris at Western elongation at Corner No. 1 of Poor Mans-Extension lode, the details of which observation are shown in the calculation sheets herewith submitted for examination. All azimuths in this record are referred to the true meridian thus determined, by the method of deflection angles and calculated courses.

The lines were measured with a Keuffel and Esser flat wire tape No. 7610, 500 ft. in length, graduated every foot, the foot at either end being graduated to tenths; and with a Keuffel and Esser 50 ft. steel tape graduated to hundredths throughout. Both tapes were less than one year old and were unbroken and unrepared.

All lines and connections of this survey were run by direct methods.

The magnetic variation observed at each corner of the Survey gave a uniform value of 14°30' E.

POOR MANS LUCK lode

Beginning at Cor. No. 1 of the Poor Mans Luck lode, on line 2-3 Poor Mans Extension lode of this survey, where I

Set an iron pipe with brass cap for Cor. No. 1, mkd. x PML 1 4062A; from which

The Southwest Cor. of section 21, T. 10 S., R. 16 E., G. & S. R. B. & M. - bears N. 67° 05' E. 2451.1 ft. dist.; an iron pipe with brass cap marked and witnessed as described in the official record.

An oak tree, 14 ins. diam., bears S. 64° 05' W. 27.7 ft. dist., mkd. x PML 1 - 4062A - BT.

An oak tree, 16 ins. diam., bears N. 44° 41' E. 54.9 ft. dist., mkd. x PML 1 - 4062A - BT.

A corner of the location bears S. 51° 03' E. 73.5 ft. dist. Thence S. 70° 58' W.

314.0 Set an iron pipe with brass cap for the center of South End line, mkd. x SEC-PML 4062A; from which

A corner of the location bears S. 14° 47' E. 29.7 ft. dist.

688.0 Cor. No. 2 Set an iron pipe with brass cap for Cor. No. 2, mkd. x PML 2 4062A; from which

An oak tree, 14 ins. diam., bears S. 2° 06' E. 27.2 ft. dist., mkd. x PML 2 - 4062A - BT.

An oak tree, 8 ins. diam., bears N. 74° 10' E. 17.9 ft. dist., mkd. x PML 2 - 4062A - BT.

A corner of the location bears S. 53° 45' W. 18.7 ft. dist.

Feet	Thence N. 36°35' W.
446.0	Center of wash, 8 ft. wide, course N. 35° E.
697.0	Center of Peppersauce Arroyo, 12 ft. wide, course N. 67° E.
1483.33	Cor. No. 3 Set an iron pipe with brass cap for Cor. No. 3, mkd. x PML 3 4062A; from which An oak tree, 8 ins. diam., bears N. 33° 08' E. 69.5 ft. dist., mkd. x PML 3 - 4062A - BT. Rice Peak bears S. 22° 53' W. A corner of the location bears S. 70° 33' W. 130.4 ft. dist.
314.0	Thence N. 70° 58' E. Set an iron pipe with brass cap for the center of the North End line, mkd. x NEC PML 4062A; from which An oak tree, 8 ins. diam., bears N. 43° 00' E. 46.2 ft. dist., mkd. x NEC PML - 4062A - BT. Bassett Peak bears S. 84° 36' E. A corner of the location bears N. 38° 21' E. 12.7 ft. dist.
628.0	Cor. No. 4 Set an iron pipe with brass cap for Cor. No. 4, mkd. x PML 4 4062A; from which An oak tree, 8 ins. diam., bears S. 40° 34' W. 50.9 ft. dist., mkd. x PML 4 - 4062A - BT. An oak tree, 16 ins. diam., bears N. 38° 27' W. 59.3 ft. dist., mkd. x PML 4 - 4062A - BT. A corner of the location bears N. 18° 51' E. 55.8 ft. dist.
125.0	Thence S. 36° 35' E. Ravine, 8 ft. wide, course S. 28° E.
491.9	Intersect line 2-3 Poor Mans Extension No. 2 lode of this survey.
1750.0	Center of Peppersauce Arroyo, 16 ft. wide, course N. 79° E.
830.0	Wagon Road, bears N. 85° E.
1228.5	Intersect the common line 3-4 Poor Mans Extension and 2-1 Poor Mans Extension No. 2 lodes of this survey.
1483.3	Cor. No. 1, and place of beginning.
	POOR MANS EXTENSION lode. Beginning at Cor. No. 1 of the Poor Mans Extension lode, identical with the location; where Set an iron pipe with brass cap for Cor. No. 1, mkd. x PMX 1 4062A; from which The Southwest Cor. of section 21, T. 10 S., R. 16 E., G. & S. R. B. & M., bears N. 32° 59' E. 1669.3 ft. dist.; an

Feet	An oak tree, 24-ins. diam., bears S. 47° 30' W. 62.7 ft. dist., mkd. x PMX 1 - 4062A - BT.
	An oak tree, 18 ins. diam., bears S. 45° 59' E. 95.9 ft. dist., mkd. x PMX 1 - 4062A - BT.
	Thence S. 55° 05' W. 12.0 ft.
104.0	Wagon road, bears N. 72° W.
182.0	Center of Peppersauce Arroyo, 16 ft. wide, course S. 75° E.
290.0	Set an iron pipe with brass cap for the center of the South End line, mkd. x SEC PMX 4062A.
590.0	Cor. No. 2. Set an iron pipe with brass cap for Cor. No. 2, mkd. x PMX 2 - 4062A; from which
	An oak tree, 12 ins. diam., bears N. 46° 58' W. 58.5 ft. dist., mkd. x PMX 2 - 4062A - BT.
	An oak tree, 12 ins. diam., bears S. 53° 44' W. 28.45 ft. dist., mkd. x PMX 2 - 4062A - BT.
	A corner of the location bears S. 35° 29' W. 102.0 ft. dist.
	Thence N. 47° 50' W.
352.0	Ravine, 3 ft. wide, course N. 43° E.
880.0	Ravine, 2 ft. wide, course N. 60° E.
1166.8	Cor. No. 1 Poor Mans Luck lode of this survey.
1428.1	Cor. No. 3. Set an iron pipe with brass cap for Cor. No. 3, mkd. x PMX-3 PMX2-2 4062A; from which
	An oak tree, 10 ins. diam., bears N. 58° 53' E. 49.4 ft. dist., mkd. x PMX 3 - 4062A - BT.
	An oak tree, 16 ins. diam., bears S. 1° 27' W. 11.2 ft. dist., mkd. x PMX 3 - 4062A - BT.
	A corner of the location bears S. 55° 05' W. 112.0 ft. dist.
	An oak tree, 18 ins. diam., bears N. 55° 05' E. 112.0 ft. dist.
51.0	Intersect line 4-1 Poor Mans Luck lode of this survey.
290.0	Set an iron pipe with brass cap for the center of North End line, mkd. x NEC-PMX SEC-PMX2 4062A; from which
	A corner of the location bears N. 21° 31' E. 111.8 ft. dist.
340.0	Wagon road bears S. 52° E.
374.0	Center of Peppersauce Arroyo, course S. 38° E.
590.0	Cor. No. 4. Set an iron pipe with brass cap for Cor. No. 4, mkd. x PMX-4 PMX2-1 4062A; from which
	An oak tree, 8 ins. diam., bears S. 34° 40' W. 19.7 ft. dist., mkd. x PMX 4 - 4062A - BT.
	An oak tree, 14 ins. diam., bears N. 25° 09' E. 17.4 ft.

- Feet dist., mkd. x PMX 4 - 4062A - BT.
 A corner of the location bears N.55°05'E. 189.0 ft. dist.
 Thence S. -47°50' E.
- 13.0 Ravine, 5 ft. wide, course S.38°W.
- 1428.1 Cor. No. 1, and place of beginning.
 POOR MANS EXTENSION NO. 2 lode
- Beginning at Cor. No. 1 of the Poor Mans Extension No. 2 lode, which is identical with Cor. No. 4 of Poor Mans Extension lode of this survey; from which
- The Southwest Corner of section 21, T. 10 S., R. 16 E., G. & S. R. B. & M., bears N.77°21'E. 2016.4 ft. dist.
 Thence S.55°05'W.
- 216.0 Center of Peppersauce Arroyo, course S.38°E.
- 250.0 Wagon road, bears S.52°E.
- 300.0 The center of the South End line, which is identical with the center of the North End line of Poor Mans Extension lode of this survey; from which
- A corner of the location bears N.70°11'E. 94.5 ft. dist.
- 539.0 Intersect line 4-1 Poor Mans Luck lode of this survey.
- 590.0 Cor. No. 2, which is identical with Cor. No. 3 of Poor Mans Extension lode of this survey.
 Thence N. 32°37' W.
- 410.0 Wagon road, bears N.85°E.
- 484.0 Center of Peppersauce Arroyo, course N.79°E., 16 ft. wide.
- 736.9 Intersect line 4-1 Poor Mans Luck lode of this survey
- 1325.0 Ravine, 7 ft. wide, course S.15°E.
- 1500.0 Cor. No. 3.
 Set an iron pipe with brass cap for Cor. No. 3, mkd. x PMX2-3 4062A; from which
 An oak tree, 18 ins. diam., bears S.4°07'E. 31.4 ft. dist., mkd. x PMX2-3 - 4062A - BT.
- A smooth rock, 13 ins. by 26 ins. face, in granite cliff bears N.16°18'E. 24.9 ft. dist., mkd. x PMX2-3 4062A - BR.
- A corner of the location bears N.34°47'W. 53. ft. dist.
 Thence N. 55°05' E.
- 10.0 Ravine, 6 ft. wide, course S.45°E.
- 290.0 Set an iron pipe with brass cap for the center of the North End line, mkd. x NEC2 PMX2 4062A.; from which
 A corner of the location bears N.40°17'W. 27.6 ft. dist.
- 590.0 Cor. No. 4.
 Set an iron pipe with brass cap for Cor. No. 4, mkd. x PMX2-4 4062A; from which
- An oak tree, 20 ins. diam., bears N.49°32'E. 159.4 ft. dist., mkd. x PMX2-4 - 4062A - BT.
- Rice Peak bears S.25°25'W.

Feet A corner of the location bears N. 31° 09' E. 143.5 ft. dist.
Thence S. 32° 37' E.

1096.0 Ravine, 4 ft. wide, course S. 65° W.

1500.0 Cor. No. 1, and place of beginning.

LODE LINES

The presumed course of the vein of each of the several lode locations embraced in this survey, counted from the respective points of discovery, is as follows:

POOR MANS LUCK lode, N. 36° 35' W., 136 ft.; and S. 36° 35' E. 1347.3 ft.

POOR MANS EXTENSION lode, N. 48° 13 1/2' W., 557 ft.; and S. 48° 13 1/2' E., 871.1 ft.

POOR MANS EXTENSION NO. 2 lode, N. 32° 37' W., 826 ft.; and S. 32° 37' E., 674 ft.

POOR MANS LUCK Mill-Site

Beginning at Cor. No. 1 of the Poor Mans Luck mill-site where I

Set an iron pipe with galvanized iron cap, in a position identical with the location, with top mkd. x PMLMS-1 - PMXMS-4 - USMS 4062B; from which

The 1/4 sec. cor. on the South boundary of section 21, T. 10 S., R. 16 E., G. & S. R. B. & M., an iron pipe with brass cap marked as described in the official record, bears N. 32° 10' E. 1688.4 ft. dist.

Cor. No. 1 Poor Mans Luck lode bears N. 83° 11' W. 4028.8 ft. dist.

A mesquite tree, 8 ins. diam., bears N. 19° 37' W. 39.5 ft. dist., mkd. x PMXMS-4 - 4062B - BT.

A black walnut tree, 18 ins. diam., bears S. 23° 38' E. 50.8 ft. dist., mkd. x PMXMS-4 - 4062B - BT.

Thence S. 9° 58' E.

120.0 Wagon road, bears S. 85° E.

268.0 Center of Peppersauce Arroyo, course N. 80° E., 18 ft. wide.

400.0 Cor. No. 2. Set an iron pipe with galvanized iron cap, in a position identical with the location, for Cor. No. 2, with top marked x PMLMS-2 - PMXMS-3 - USMS 4062B; from which

An oak tree, 10 ins. diam., bears S. 73° 24' W. 37.6 ft. dist., mkd. x PMXMS-3 - 4062B - BT.

A sycamore tree, 48 ins. diam., bears N. 4° 44' E. 83.4 ft. dist., mkd. x PMXMS-3 - 4062B - BT.

Thence S. 80° 02' W.

322.5 Center of Highway, bears S. 80° E.

544.5 Cor. No. 3, identical with the location.

Feet 1 Set an iron pipe with galvanized iron cap for Cor. No. 3, mkd. x PMLMS-3 - 4062B; from which

An oak tree, 9 ins. diam., bears S. 53°55' W. 43.25 ft. dist., mkd. x PMLMS-3 - 4062B - BT.

An oak tree, 12 ins. diam., bears N. 54°58' W. 23.2 ft. dist., mkd. x PMLMS-3 - 4062B - BT.

Thence N. 9°58' W.

68.0 Wagon road, bears N. 60° E.

123.0 Center of Peppersauce Arroyo, 18 ft. wide, course N. 60° E.

400.0 Cor. No. 4, identical with the location. Set an iron pipe with galvanized iron cap for Cor. No. 4, mkd. x PMLMS-4 - USMS 4062B; from which

A limestone outcrop 3 ft. wide by 18 ins. high bears N. 89°30' W. 9.2 ft. dist., mkd. x PMLMS-4 - 4062B - BR.

A cat-claw tree, 8 ins. diam., bears N. 35°07' E. 78.8 ft. dist., mkd. x PMLMS-4 - 4062B - BT.

Thence N. 80°02' E.

518.0 Center of Highway, bears S. 40° W.

544.5 Cor. No. 1, and the place of beginning. The Poor Mans Luck Mill site contains 5.00 Acres. POOR MANS EXTENSION Mill-Site

Beginning at Cor. No. 1 of the Poor Mans Extension Mill-Site, identical with the location, where

Set an iron pipe with galvanized iron cap for Cor. No. 1, mkd. x PMXMS-1 USMS 4062B; from which

The 1/4 Sec. Cor. on the South boundary of section 21, T. 10 S., R. 16 E. of G. & S. R. B. & M., bears N. 20°30' E. 1160.1 ft. dist.

Cor. No. 1 Poor Mans Extension lode bears S. 84°22' W. 3159.3 ft. dist.

A mesquite tree, 9 ins. diam., bears N. 0°13' E. 8.1 ft. dist., mkd. x PMXMS-1 - 4062B - BT.

A mesquite tree, 9 ins. diam., bears S. 1°07' E. 6.4 ft. dist., mkd. x PMXMS-1 - 4062B - BT.

Thence S. 9°58' E.

38.0 Wagon road; bears S. 50° W.

67.0 Center of Peppersauce Arroyo, 18 ft. wide, course N. 50° E.

400.0 Cor. No. 2; identical with the location. Set an iron pipe with galvanized iron cap for Cor. No. 2, mkd. x PMXMS-2 - USMS 4062B; from which

An oak tree, 10 ins. diam., bears S. 7°23' E. 55.8 ft. dist., mkd. x PMXMS-2 - 4062B - BT.

An oak tree, 10 ins. diam., bears N. 23°24' W. 25.7 ft. dist., mkd. x PMXMS-2 - 4062B - BT.

Feet
 600.0 Thence S. 55° 11' W.
 Cor. No. 3, which is identical with Cor. No. 2 of the Poor Mans Luck Mill-Site of this survey and agrees with a corner of the location.
 Thence N. 9° 58' W.
 132.0 Center of Peppersauce Arroyo, 18 ft. wide, course N. 60° E.
 280.0 Wagon road, bears N. 60° E.
 400.0 Cor. No. 4, which is identical with Cor. No. 1 of the Poor Mans Luck Mill-site of this survey and agrees with a corner of the location.
 Thence N. 55° 11' E.
 600.0 Cor. No. 1, and the place of beginning.
 The Poor Mans Extension Mill-Site contains 5.00 acres.

AREAS		Acres
Total area, Poor Mans Luck lode		20.389
Total area, Poor Mans Extension lode		18.853
Area in conflict with Poor Mans Luck lode of this survey		0.149
Total area, Poor Mans Extension No. 2 lode		20.300
Area in conflict with Poor Mans Luck lode of this survey		0.432
Total area, Poor Mans Luck Mill-Site		5.000
Total Area, Poor Mans Extension Mill-Site		5.000

LOCATION

This survey is located on unsurveyed ground in what would be sections 28, 29 and 20 of township 16 South, range 16 East, G. & S. R. B. & M., which sections are entirely within the Coronado National Forest.

EXPENDITURE OF \$500

I certify that the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or her grantors is not less than \$500, and that said improvements consist of:

- on **POOR MANS LUCK** lode
- No. 1 The discovery tunnel of the Poor Mans Luck lode, the portal of which is on the lode line 136 ft. S. 36° 35' E. from the North End Center; 6x4 ft. in size, 10 ft. deep running N. 15° W. and dipping 10° from the horizontal.
Value, \$70
- No. 2 A tunnel 5x5 ft. in size, the portal of which bears S. 85° 15' E. 326 ft. from Cor. No. 3 Poor Mans Luck lode, and runs N. 15° W. 48 ft., thence N. 60° W. 11 ft. to breast, and dips 10° from the horizontal.
Value, \$400
- No. 3 A tunnel 6x5 ft. in size, the portal of which bears

S.82°20'E 265 ft. from Cor. No. 3 Poor Mans Luck lode, and runs N.15°W. 11 ft. to breast.

Value, \$95

No. 4 An open cut 6 ft. wide, the face of which bears S.56°W. 126 ft. from Cor. No. 4 Poor Mans Luck lode; runs S.68°W. 14 ft. to 7 ft. face.

Value, \$25

No. 5 An open cut 4 ft. wide, the face of which bears S.16°15'E 344 ft. from Cor. No. 4 Poor Mans Luck lode; runs N.60°W. 12 ft. to 9 ft. face.

Value, \$20

No. 6 An open cut 4 ft. wide, the face of which bears S.14°30'E 371 ft. from Cor. No. 4 Poor Mans Luck lode; runs N.60°W. 15 ft. to 7 ft. face.

Value, \$20

No. 7 An open cut 9 ft. wide, the face of which bears S.21°55'E 665 ft. from Cor. No. 4 Poor Mans Luck lode; runs N.33°W. 18 ft. to 11 ft. face.

Value, \$45

No. 8 An open cut 6 ft. wide, the face of which bears N.7°30'W. 443 ft. from Cor. No. 2 Poor Mans Luck lode; runs S.30°E. 10 ft. to 9 ft. face.

Value, \$25

on POOR MANS EXTENSION lode

No. 1 The discovery tunnel of the Poor Mans Extension lode, the portal of which being the discovery point is on the lode line 557 ft. from the North End Center; 10x5 ft. in size, runs N.42°E. 10 ft. to breast with a dip of 30° from the horizontal.

Value, \$115.

No. 2 A n inclined shaft, the center of which at the surface is on the lode line 538 ft. from North End Center; 6x5 ft., 18 ft. deep on a 45° ineline. A tunnel-raise 5x5 ft., 18 ft. long, connects it to the breast of the discovery tunnel running from the bottom of shaft.

Value, \$270

No. 3 An inclined shaft, the center of which at the surface is on the lode line 501 ft. from the North End Center; 7x3 ft., 12 ft. deep, dips 45° to the Northeast.

Value, \$60

No. 4 A tunnel, the portal of which is on the lode line 450 ft. from North End Center, 10x5 ft. in size, runs 41 ft. to breast N.62°E., at a dip of 30° from the horizontal. A triangular slope on the South side extends from a point 23 ft. from portal to the breast, and projects 15 ft. to an apex, Southerly.

Value, \$540

No. 5 A tunnel, the portal of which is S.27°W. 145 ft. from Cor. No. 4 Poor Mans Extension; 8x5 ft. in size, runs N.75°E. with a 30° dip from horizontal, 47 ft. to breast.

Value, \$425

No. 6 A tunnel, the portal of which is on the lode line 628 ft. from north end center; 8x3 ft. in size, runs 9 ft. N.E. with 30° dip to breast. At breast a 3x3 ft. crosscut extends 10 ft. S.E. and 12 ft. N.W.

Value, \$90

No. 7 A tunnel, the portal of which is on the lode line 648 ft. from North End Center; 7x3 ft. in size, runs 6 ft. N.E. with 30° dip to breast.
Value, \$30

on POOR MANS EXTENSION NO. 2 lode

No. 1 The discovery out of the Poor Mans Extension No. 2 lode, the face of which being the discovery point, is on the lode line 674 ft. from south end center; 5 ft. wide, 8 ft. face, runs N. 15° W. to face and portal of tunnel 5x5 ft. in size, running N. 15° W. 68 ft. to breast. The east wall of the tunnel is stoped out four ft. wide for a distance of 13 ft. commencing 19 ft. from portal. The west wall of the tunnel is stoped out 9 ft. wide for a distance of 18 ft. commencing 11 ft. from portal; and from the center of breast of this stope a crosscut runs N. 75° E. to breast. The stopes and the crosscut are 4 ft. high. The floor of the whole working dips 17° from the horizontal towards the East. Crosscut is 4 ft. wide
Value, \$680

No. 2 A shaft, the center of which is on the lode line 742 ft. from north end center; 4x5 ft., 8 ft. deep.
Value, \$25

No. 3 An open out, 5 ft. wide, the face of which bears S. 19° 25' W. 280 ft. from Cor. No. 4 Poor Mans Extension No. 2 lode; runs N. 50° W. 32 ft. to 8 ft. face.
Value, \$60

No. 4 An open out, 3 1/2 ft. wide, the face of which bears N. 44° W. 700 ft. from Cor. No. 1 Poor Mans Extension No. 2 lode; runs West 12 ft. to 7 ft. face.
Value, \$30

No. 5 A shaft, the center of which bears N. 33° 45' W. 575 ft. from Cor. No. 1 Poor Mans Extension No. 2 lode; 8x12 ft., 5 ft. deep
Value, \$25

No. 6 An open out, 9 ft. wide, the face of which bears N. 52° - 30' W. 540 ft. from Cor. No. 1 Poor Mans Extension No. 2 lode; runs West 18 ft. to 10 ft. face. The North side of out at a point four ft. from face is the center of portal of a tunnel 4 1/2 x 6 ft. in size, running N. 27° W. 29 ft. to breast.
Value, \$300

No. 7 A tunnel, the portal of which bears N. 55° 00' W. 368 ft. from Cor. No. 1 Poor Mans Extension No. 2 lode; 5x5 ft. in size, runs N. 47° 30' E. 80 ft. to breast, with a dip of 30° from the horizontal. A stope 14 ft. wide by 5 ft. high extends from a point on the North wall of the tunnel 20 ft. from portal to a point 40 ft. from portal. A stope 20 ft. wide by 5 ft. high extends from a point on the South wall of the tunnel 32 ft. from portal to the breast.
Value, \$2000

OTHER IMPROVEMENTS

A concrete dam, the center of which bears N. 15° 52' W. 618 ft. from Cor. No. 2 Poor Mans Luck lode, 2 ft. wide, 4 ft. high, 17 ft. long. Extends S. 6° E. & N. 6° W.
Claimant herein.

A frame shack, the Southeast corner of which bears N.30°00'W. 595 ft. from Cor. No. 2 Poor Mans Extension lode; 10 x 12 ft. in size, the long sides bear N.15°E. Claimant herein.

A frame shack, the Northwest corner of which is N.74°E. 306 ft. from Cor. No. 3 Poor Mans Luck Mill-Site; 13 x 19 ft. in size, the long sides bear East and West. Claimant herein.

A concrete box spring, 2x2 ft. bears N.68°32'W. 251.6 ft. from Cor. No. 2 Poor Mans Luck Mill-Site. Claimant herein.

A concrete box spring, 2x3 ft., bears N.70°20'W. 296.0 ft. from Cor. No. 2 Poor Mans Luck Mill-Site. Claimant herein.

A Fresno bridge, 5x8 ft. timber construction, bears N.71°50'W. 365 ft. from Cor. No. 2 Poor Mans Luck Mill-Site. Claimant herein.

A concrete water tank, 10 ft. outside diameter, 9 ft. inside diameter, 2 ft. deep, the center of which bears S.60°21'W. 82.7 ft. from Cor. No. 1 Poor Mans Extension lode. Claimant herein.

Memo.

The location certificate of the Poor Mans Extension lode calls for a monument of stones at the center of the south end line. There is no such monument to be found at present; and it is quite probable that it has been destroyed by a minor land slide, the terrain in the vicinity being too steep to maintain a monument of loose stones indefinitely.

An open cut, 9 ft. wide, the face of which bears N.52°00'W. 340 ft. from Cor. No. 1 Poor Mans Extension lode; runs West 18 ft. to 10 ft. face. The North side of cut at a point four ft. from face is the center of portal of a tunnel 18 ft. in size, bearing N.37°W. 39 ft. to breast. Value, \$300

A tunnel, the portal of which bears N.52°00'W. 340 ft. from Cor. No. 1 Poor Mans Extension lode; 8 ft. in size, runs N.47°30'E. 80 ft. to breast, with a dip of 30° from the horizontal. A slope 14 ft. wide by 5 ft. high extends from a point on the North wall of the tunnel 20 ft. from portal to a point 40 ft. from portal. A slope 20 ft. wide by 5 ft. high extends from a point on the South wall of the tunnel 24 ft. from portal to the breast. Value, \$2000

OTHER IMPROVEMENTS

A concrete dam, the center of which bears N.15°52'W. 319 ft. from Cor. No. 2 Poor Mans Luck lode, 2 ft. wide, 4 ft. high, 17 ft. long. Extends S.2°E. & N.8°W. Claimant herein.

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by Emmet R. Marx

United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of Muriel Huggett of Oracle, Pinal County, Arizona

POOR MANS LUCK, POOR MANS EXTENSION, POOR MANS EXTENSION NO. 2,
known as the POOR MANS LUCK MILLSITE, POOR MANS EXTENSION MILLSITE

and showing the respective capacities in which they acted.

Glenton G. Sykes , Chainman.

Gilbert W. Sykes , Chainman.

..... , Axman.

..... , Flagman.

FINAL OATHS OF ASSISTANTS

We, Glenton G. Sykes

and Gilbert W. Sykes , do solemnly swear that we assisted Emmet R. Marx

..... , United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Muriel Huggett

POOR MANS LUCK, POOR MANS EXTENSION, POOR MANS EXTENSION NO. 2.
known as the POOR MANS LUCK MILLSITE, POOR MANS EXTENSION MILLSITE.

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at Phoenix, Arizona.

Glenton G. Sykes , Chainman.

Gilbert W. Sykes , Chainman.

..... , Axman.

..... , Flagman.

Subscribed and sworn to by the above-named persons before me this 8th

day of February , 19 33

Genevieve
Nathaniel

My commission expires March 6, 1933.


FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Emmet R. Marx, U. S. Mineral Surveyor, do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer, at Phoenix, Arizona, dated January 9, 1933, I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly executed the survey of the Mining Claim of Muriel Huggett, of Oracle, Pinal County, Arizona. ^{known as the} Poor Mans Extension lode; Poor Mans Luok lode; Poor Mans Extension No. 2 lode; Poor Mans Luok mill-site; Poor Mans Extension mill-site. situate in Coronado National Forest in Old Hat Mining District, Pinal County, Arizona, in Section unsurveyed sections 20, 28 & 29, Township No. 10 S., Range No. 16 E., G. & S. R. E. & M., and designated as Survey No. 4062 A & B, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached ^{copies} ~~copy~~ of the location certificates, which ~~was~~ ^{were} received by me from the Office Cadastral Engineer with said instructions, and that all corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or her grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Emmet R. Marx
U. S. Mineral Surveyor.

Subscribed and sworn to by the said Emmet R. Marx
U. S. Mineral Surveyor, before me Charity Ross
this 11th
day of February, 1933

Charity Ross
Notary Public



GOVERNMENT PRINTING OFFICE

My Comm. Expires June 4, 1934.

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

Department of the Interior

PUBLIC SURVEY OFFICE

Phoenix, Arizona

March 2, 1933

Acting Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of Muriel Huggett, of Oracle, Pinal Co., Arizona

known as the Poor Mans Luck, Poor Mans Extension, and Poor Mans Extension No. 2, lode; and Poor Mans Luck, and Poor Mens Extension, Mill Sites. situate in OLD HAT

Mining District PINAL County ARIZONA

in Section, Township No. 10 South, Range No. 16 East, and

designated as Survey No. 4062 A & B, has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each lode location embraced in said mining claim by claimant Muriel Huggett or her grantors,

and that said improvements consist of 4 shafts, 9 cuts, and 11 tunnels,

Value: \$5340.00

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix Arizona is correct and in conformity with the foregoing Field Notes.

Sherman C. Fiske Acting Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR PUBLIC SURVEY OFFICE

At Phoenix, Arizona

March 2, 1933

Acting I, Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of Muriel Huggett, of Oracle, Pinal County, Arizona

known as the POOR MANS LUCK? POOR MANS EXTENSION, and POOR MANS EXTENSION No. 2 lodes, and POOR MANS LUCK and POOR MANS EXTENSION Mill Sites situate in Coronado National Forest, OLD HAT mining district, Pinal County Arizona

Unsurveyed in Sections 20, 28 & 29, Township No. 10 South, Range No. 16 East

G. & S. R. B. & M, designated as Survey No. 4062 A. & B

executed by Emmet R. Marx, U. S. Mineral Surveyor, January 16, 1933 to February 4, 1933, under my instructions dated January 9, 1933, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copies of the location certificates filed by the applicant for survey are on file in this office and true copies of said certified copies of said location certificates are included and made a part of the transcript of the field notes.

Sherman C. Fiske Acting Office Cadastral Engineer.