MINERAL	SURVEY	No.	4187
	2010111	110.	

	Arisone	3	Land District
	F	IELD NO	TES
	OF THE SUR	RVEY OF THE M	INING CLAIM OF
		Nancy Blake	
14		KNOWN AS TH	HE .
	WAR IN	G lode	
		Pima	Mining District,
	Pima	County,	Arizona
			, Range
	eyed under instruction		
		By	N Clerus
			U. S. Mineral Surveyor.
	Claim locatedMa	rch 21. 1926	, 19
			, 19 1936
			, 19.36.
			ucson, Arizona,
		OF AMENDED LO	
	360		
322			
			U R. GOVERNMENT PRINTING OFFICE: 1937

Feet

#### MINERAL SURVEY NO. 4187

Mineral survey No.4187 was made with a Gurley mountain transit with horizontal limb 6.5 ins. diam. having two opposite verniers and full vertical circle, 5 ins. diam. having one double vernier. the verniers read to one minute of arc.

The instrument was in good condition of the time of the survey and all adjustments were in good order. A P.M. altitude observation for azimuth and at noon on the meridian for latitude and time were made on a line of the survey, the details of which observations are shown in the calculation sheets herewith submitted for examination.

All azimuths in this record are referred to the true meridian by the method of deflection angles, and calculated courses.

The lines were measured with a Lufkin steel tape, 500 feet in length, graduated every foot, with the first and last foot graduations to tenths and hundredths. The tape was correct at the time of the survey. All lines and connections of this survey were run directly upon the ground.

The magnetic variation observed at each corner gave a uniform value of 14°30'E.

#### WARING Lode.

Beginning at Cor. No.1 of the waring lode, identical with the northeast corner of the Snake in the Grass lode, unsurveyed, where I set a steel post 2 ins. diam. with lead cap on top, 24 ins. above ground, set 18 ins. in the ground and surrounded with md of stone, stamped 1 w - 4187, from which the Cor. to Secs. 10.11, 14 and 15 T. 17 S. R. 12 E. brs. N. 63° 24° 30" W., 9286.7 ft. dist., consist ing of a porphyry rock 8 x 8 ins. showing 12 ins. above ground, chiseled with two notches on the B. face and four notches on the S. face. This is the nearest standing corner of the public survey that can be found or identified.

Loc. Mon. brs. N.16°34°W., 4.0 ft.

No other bearings are available.

Thence S. 18°34'E.

75.00

Gulch brs. easterly.

156.0

Gulch brs. northeasterly.

#### MINERAL SURVEY No.4187 Waring Lode.

300.00 To W. end center, identical with Loc. Mon. where Iset a brass pipe 2 ins. diam. 4 ft. high, firmly in the ground
and surrounded with md of stone, piperstamped W.Cr.W.

600.00 To Cor. No.2, identical with Loc. Mon. and southeast corner of the Snake in the Grass lode, unsurveyed, where I set a steel post 2 ins. dism. with lead cap on top, 24 ins. above ground, set 18 ins. in the ground, and surrounded with md. of stone stamped 2 W, -4187

No bearings are available.

#### Thence N. 71°26 年.

from the south,

To Cor. No.3, in water course, identical with Loc. Non. where I 
Set a steel post 2 ins. diam., with lead cap on top, 24 ins. above

ground, set 18 ins. in the ground and surrounded with md of stone
stamped 3 W - 4187. This corner is firmly embedded in
large boulders below the surface of the wash, and is set
to withstand any possible floods, as the drainage area
is only a few hundred feet.

To bearings are available.

#### Thence N.18°34'W.

- 100.0 N. bank of gulch brs. northeasterly.
- 200.0 Tucson-Twin Buttes highway brs. northwesterly.
- 300.00 To E. end center, identical with Loc. Mon. where I set a brass pipe 2 ins. diem. 4 ft. high, firmly in the ground
  and surrounded with md of stone, pipe stamped E. Cr. W.
- 590.0 Road brs. northeasterly.
- 500.0 To Cor. No.4, identical with Loc. Mon. where I
  Set a steel post 2 ins. diam. with lead cap on top, 24 ins. above

  ground, set 18 ins. in the ground, and surrounded with md of stone,

  Stamped 4 W 4187.

No bearings are available.

#### Thence S.71°26'W...

- 226.0 Tucson- Twin Buttes highway brs. northwesterly.
- 316.2 Fence brs. northeesterly.
- 1500.00 To Cor. No.1 and place of beginning .

#### MINERAL SURVEY NO 4187 WARING Lode.

#### LODE LINE.

The presumed course of the vein of the location embraced in this survey counted from its discovery point, is as follows:

.TOO. 11 B .. 32, 55

waring lode, N/71°26'E., 470.0 ft.and S.71°26'W., 1030.0 ft.

, AREA.

\$ 0% TO

a. disoners.

## 

. Invertee fore to the day

This survey is located in the S.E. 1/4 Sec. 13, T.17 S. R.12 E. 

## EXPENDITURE OF \$500

I certify that the value of the labor and improvements made upon or for the benefit of the lode location embraced in said mining claim by the claimant or his grantors is not less than \$500. and that said improvements consist of:

The Discovery shaft of the Waring lode, the center of which being the discovery point is on the lode lone, 470 ft. from the center of line 3-4, 4 x 6 ft. 8 ft. deep.

Value \$100

- A cut, the mouth of which brs. from Cor. No.3, N.84°45°W., 735 ft. No.2 4 1/2 ft. wide, 8 ft. face, running S. 40° W., 15 ft. to face. 11, 14 and 15, neretofort desc Value \$100.0
- No.3 A cut, the mouth of which brs. from Cor. No.3 N.86°15.W., 700 ft. 4 1/2 ft. wide 10 ft. face, running S. 49° W. 21 ft. to face. From the face is a tunnel 4 x 6 ft. running S. 71° W. 7 ft. to face.

Value Cut and tunnel \$200

- AND DESIGNATION OF THE PARTY OF A cut, the mouth of which brs. from Cor. No.3, N.82° W., 570.0 ft., No.4 4 1/2 ft. wide, 8 ft. face, running N.18.30 W., 25 ft. to face. Value \$125.0
- out, the face of which brs. from Cor. No.3 N.82 W., 550. ft. No.5 4 1/2 ft. wide 6 ft. face, running S. 18°E., 20 ft. to mouth.
- Value \$100. A shaft, the center of which brs. from Cor. No. 4, S.38°45°W., No.6 530 ft. 4 x 6 ft. 8 ft. deep.

Value \$100.00

#### OTHER IMPROVEMENTS.

A cut, the mouth of which brs. from Cor. No.3, N.80°15'W.,420.0 ft. 4 ft. wide, 10 ft. face, running N. 18 W., 50 ft. to face.

A shaft, the center of which brs. from Cor. No.3 N.74 º15 ·W.,505 ft 4 x 6 ft. 10 ft. deep.

A shaft, the center of which brs. from Cor. No.4 S.32.45.W. 475 ft. 5 x 8 ft. 100 ft. deep (inclined to south and timbered)

A shaft, the center of which brs. from Cor. No.4 S.29 45 W., 430 ft. 8 x 8 ft. 6 ft. deep,

A shaft, the center of which brs. from Cor. No.4 S. 9.30.W., 340 ft. 4 x 6 ft. 8 ft. deep.

#### MINERAL SURVEY NO. 4187

#### OTHER IMPROVEMENTS.

An open trench, the east end of which brs. from Cor. No.4, S.0°30'W. 330. ft. 4 ft. wide, 4 ft. deep, running S.71°30'W., 45 ft.

A shaft, the S.E. Cor. of which brs. from Cor. No.4, S.42°15'W., 510 ft. 5 x 18, ft., 8 ft. deep.

A shaft, the center of which brs. from Cor. No.4 , S. 45°05 W., motel eren, cring lode -495 ft. 4 x 8 ft. 10 ft. deep. Claimant of each unknown.

A concrete tank 6 ft. diam. by 10 ft. high, the center of which bears from Cor. No. 4 S. 36° W., 485. ft.

Claimant herein

A frame shack, the N.E. Cor. of which brs. from. Cor. No.4, S.66°30'W., 380 ft., 13 x 20 1/2ft course of long sides, N.84 W. Claimant herein

A frame shack, the N.E. Cor. of which brs. from Cor. No.4 , S.56 30 W., 540 ft. 9 x 32 ft., course of long sides N.73 W., Claimant herein

1 .00

The foundation of a new house, under construction, the S.E. Cor. of which brs. from Cor. No.4, S.49 30 W., 474 ft. 16 x 42, t. course of long sides, N.45 W. dorn's to return out abol pairs out to Trais va-

#### OTHER CORNER DESCRIPTIONS.

The Tiscovery shart of the waring lode, the center of which being the accounty point is on the lode lone, 470 ft. from the

velue fino

Tosa Jenus bue the enlay

. A diligent search was made for all the corners and 1/4 corners of . the public survey within a radius of two miles of this survey and the cor. to Secs. 10, 11, 14 and 15, heretofore described is the nearest standing corner that can be found or identified. a cut, the housh of which brs. from Cor. No. 3 M. 65°15'W., 700 ft. & 1/2 ft. vide ld ft. face, running S. 65° W. 21 ft. to face. From the face is a turnel 4 x 6 ft. running 9, 21° W. 7 ft. to

ADJOINING CLAIMS.

out, the wonth of which brs. from Cor. No. 3, T. 620 T. . 570.0 ft. On the West by Snake In The Grass lode, Uns., J. Blake, Claimant.

There are no other adjoining or conflicting claims known.

A out, the fire of which hrs. from cor. No. 5 1.02 %. 550. ft. 4 L/2 ft. wide 6 ft. face, running 8, 18 %. fc ft. to mouth. and the senter of which bra. from dor. no. 4. 3. 35 45 7. . 630 ft. 4 x 6 ft. 8 ft. deep.

TOURS TIPO.OO

CHARA IMPROVEMENTS.

A out, the mouth of which are, from Cor. Ho.5, H. Boels: W., 420.0 ft. 4 ft. wide, if ft. face, requing H. 1878.. Fo ft. to face.

a smalt, the center of witch bra. from Cor. No. 3 W. 74 "15'W., Eos ft 4 x 6 ft. 10 ft. deen.

A shaft, the senter of which brs. from Con. Ho.4 8.32 45.8. 475 ft. 5 x 8 ft. 100 ft. doep ( inclined to south and timbored)

abut, the center of which bre. from Cor. No.4 6.29 45 tw. 450 ft. 6 x 6 ft. 6 ft. 6eep.

A seart, the center of which bre, from dor. 10.4 7, 9000 T. 340 ft. 4 x 6 ft. 8 ft. desp.

# FINAL OATHS FOR SURVEYS

## LIST OF NAMES

	yor, to assist in running, measuring, and marking the lines, corners, and
boundaries described in the fe	oregoing field notes of the survey of the mining claim of
	Nancy Blake
known as the	Waring lode
and showing the respective ca	
	Ray P. Rodriquez , Chainman.
	, Chainman.
	, Axman.
	, Flagman.
FINA	AL OATHS OF ASSISTANTS
We, I. Ray P. Rodriqu	10%
XXX	, do solemnly swear that wb assisted
	, United States Mineral Surveyor, in marking the corners and surveying
he boundaries of the mining $\epsilon$	claim of
he boundaries of the mining of	claim of Varing lode Nancy Blake
he boundaries of the mining of	claim of
nown as the	claim of Nancy Blake  Aring lode  eld notes as having been surveyed by said mineral surveyor and under his
nown as the	Plaim of Nancy Blake  Paring lode  Peld notes as having been surveyed by said mineral surveyor and under his has been in all respects, to the best of our knowledge and belief, faithfully corner and boundary monuments established according to law and the instruc-
nown as the	Plaim of Nancy Blake  Raring lode  Eld notes as having been surveyed by said mineral surveyor and under his has been in all respects, to the best of our knowledge and belief, faithfully corner and boundary monuments established according to law and the instruc-
nown as the	Plaim of Nancy Blake  Paring lode  Peld notes as having been surveyed by said mineral surveyor and under his has been in all respects, to the best of our knowledge and belief, faithfully corner and boundary monuments established according to law and the instruc-
nown as the	claim of Nancy Blake  Paring lode  Eld notes as having been surveyed by said mineral surveyor and under his has been in all respects, to the best of our knowledge and belief, faithfully corner and boundary monuments established according to law and the instructional dastral Engineer, at Phoenix, Arizona
nown as the	claim of
nown as the	Plain of
epresented in the foregoing fictive and that said survey and correctly executed, and the correctly executed, and the correctly executed and the correctly ex	claim of
epresented in the foregoing ficting and that said survey and correctly executed, and the carting cons furnished by the Office Ca	eld notes as having been surveyed by said mineral surveyor and under his has been in all respects, to the best of our knowledge and belief, faithfully corner and boundary monuments established according to law and the instructural Engineer, at
epresented in the foregoing fictive and that said survey and correctly executed, and the correctly executed and the correctly exe	claim of
epresented in the foregoing fictive and that said survey and correctly executed, and the cating ions furnished by the Office Ca	claim of

# DEPARTMENT OF THE INTERIOR GENERAL LAND OFFICE

## FINAL OATH OF U. S. MINERAL SURVEYOR

T.N. Stevens , U. S. Mineral Surveyor,
do solemnly swear that, in pursuance of instructions received from the/Office Cadastral
Engineer, at, dated, dated,
I have, in strict conformity to the laws of the United States, the official regulations
and instructions thereunder, and the instructions of said Office Cadastral Engineer,
faithfully and correctly executed the survey of the mining claim of
Nancy Blake , known as the
situate inPimaMiningsoftkstrict,
Pima County, Arizona , in Section
13 , Township No. 17 9 , Range No. 12 E
and designated as Survey No, as represented
in the foregoing field notes, which accurately show the boundaries of said mining claim
as distinctly marked by monuments on the ground, and described in the attached copy of
the location certificate, which was received by me from the Office Cadastral Engineer
with said instructions, and that all corners of said survey have been established and
perpetuated in strict accordance with the law, official regulations and instructions
thereunder; and I do further solemnly swear that the foregoing are the true and original
field notes of said survey and my report therein, and that the labor expended and im-
provements made upon said mining claim by claimant orher
grantors are as therein fully stated, and that the character, extent, location, and
itemized value thereof are specified therein with particularity and full detail, and
that no portion of said labor or improvements so credited to this claim has been in-
cluded in the estimate of expenditures upon any other claim.
1.92
UNDOCETENS.
(U. S. Mineral Surveyor)
Subscribed and sworn to by the said
U. S. Mineral Surveyor, before me O. P. Richy
this this
day of June , 1936
My Commission 11- 2
effino Nor 29 1939

# CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

# UNITED STATES DEPARTMENT OF THE INTERIOR GENERAL LAND OFFICE PUBLIC SURVEY OFFICE

	At.	Phoenix,	Arlzona,	
Acting I/Office Cadastra	d Engineer at Phoenix, Ari	zona,		
do hereby certify that	the foregoing and hereto attached	Field Notes and	Return of the	e Survey of the
Mining Claim of				
	Nancy Blake			
				, known as the
	WARING lode			
situate in	Pima		· 1	nining district,
	Pima County, Ar	izona,		
in Section13	, Township No	17 S.	, Range No.	12 E.
	designated as Survey No	4187		
executed by	T. N. Stevens			U. S. Mineral
Surveyor,	May 30 - June 3	, 1936,	under my inst	ructions dated
May 21,	1936 , hav	e been critically	examined and	the necessary
corrections and explan	ations made, and the said Field Not	es and Return, a	nd the Survey	they describe,
are hereby approved.	The certified copy of the location of	ertificate filed by	y the applican	t for survey is
on file in this office an	d a true copy of said certified copy	y of said location	certificate is	included and
made a part of the tran	nscript of the field notes.			
		00	-	

Sheringu G. Frake

Acting Office Cadastral Engineer.

6-7131 U. S. GOVERNMENT PRINTING OFFICE: 1830

# OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

# Department of the Interior

PUBLIC SURVEY OFFICE

			rnoenix, Ar	12012.	
			J	uly 1	10 36
Acting I/Office Cadastral Eng	gineer & 8t				
do hereby certify that the f	oregoing trans	script of the F	ield Notes, return	and approval of	the survey
of the mining claim of					
		lancy Bla	ke		
known as the		ARING 10	âe .		
situate in		Pima			
Mining District	Pima		County	Ari	zona
in Section 13, To	wnship No	17 S.	, Range No	12 E.	, and
designated as Survey No.	4187	, has bee	n correctly copied f	from the origins	als on file in
this office; that said Field					
incorporated into a patent, s	erve fully to id	lentify the pro	emises, and that such	h reference is m	ade therein
to natural objects or perma	nent monume	ents as will p	erpetuate and fix th	ne locus thereof	
I further certify that F	ive Hundred	Dollars worth	of labor has been e	xpended or imp	provements
made upon, or for the be	enefit of, eacl	h location e	nbraced in said m	ining claim b	y claimant
		or	her		grantors,
and that said improvement	s consist of	2 shafts	4 outs, an	d 1 tunne	l, total
value \$725.00					
***************************************					
and that no portion of said l	abor or impro	vements has	been included in the	estimate of ex	penditures
upon any other claim.					
I further certify that th	e plat thereof	f, filed in the	U. S. Land Office a	Phoenia	£ 9
Arizona,	is correct a	and in conform	nity with the foreg	oing Field Not	es.
			Character 6	nd ata	
			Sherman C.	Tice Cadastral E	