

MINERAL SURVEY No. 4204

Arizona Land District

FIELD NOTES

OF THE SURVEY OF THE MINING CLAIM OF

George N. Lobb

KNOWN AS THE

DEWBERRY Lode.

Pioneer Mining District,

Pinal County, Arizona

Section 8, Township 2 S., Range 12 E.

Surveyed under instructions dated Aug. 20, 1937

By J. N. [Signature]
U. S. Mineral Surveyor,
General Land Office

Claim located December 23, 1921

Survey commenced Sept 21, 1937

Survey completed Sept 24, 1937

Address of claimant George N. Lobb, Box 46 Superior, Arizona.

DATES OF AMENDED LOCATIONS

Feet.

MINERAL SURVEY No. 4204

Mineral survey No:4204 was made with a Gurley Mountain transit with horizontal limb 6.5 ins. diam. having two opposite verniers and full vertical circle, 5 ins: diam. having one double vernier. The verniers read to one minute of arc.

The instrument was in good condition at the time of the survey; all adjustments were in good order. A p.M. altitude observation for azimuth and noon on the meridian for latitude and time were made on a line of the survey, the details of which observations are shown in the calculation sheets, herewith submitted for examination.

All azimuths in this record are referred to the true meridian by the method of of deflection angles, and calculated courses.

The lines were measured with a Kufkin steel tape, 500 ft. in length graduated every foot with the first and last foot graduations to tenths and hundredths. The tape was correct at the time of the survey.

All lines and connections in this survey were run directly upon the ground.

The magnetic variation observed at each corner gave a uniform value of 14°45' E.

DEWBERRY Lode.

Beginning at Cor. No.1 of the Dewberry lode, identical with Cor. No.11, Sur. No.167 H E S .

A limestone rock 14 x 24 ins. showing 18 ins. above ground, firmly set, with md of stone alongside, chiseled with cross (X) 11 H E S - 167, 1 DB - 4204, from which the Cor. to Secs. 4,5, 8 and 9 T. 2 S. R. 12 E. brs. N.72°49'17"E., 1880.60 ft. dist. consisting of a porphyry rock 8 x 10 ins. showing 8 ins. above ground, chiseled with 4 notches on the E. face and 5 notches on the S. face.

Loc. Mon. brs. N. 14°E., 6.5 ft. dist. hereinafter described
A Palo Verde tree 5 ins. diam brs. S. 51°40'W., 22.65 ft. dist.
Blazed and scribed 11 H E S -167, 1 D B - 4204

No other bearings are available.

Thence S. 14°00'W.,

234.0 ~~Line~~ N. bank Queen Creek, Course northwesterly.

300.0 S. bank Queen Creek.

305.0 To E. end center, identical with Loc. Mon. Where I -
Set a willow post 4 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md. of stone, scribed E C - D B.

351.0 Fence brs. northwesterly.

555.2 To Cor. No.10, H E S 167. Hereinafter described.

565.0 Fence brs. northwesterly.

610.0 To Cor. No.2 Where I -

Set a steel post 2 ins. diam. with lead cap on top, 24 ins. above ground, set 18 ins. in the ground and surrounded with md. of stone, stamped 2 DB - 4204, from which

A cross (X) - 2 DB - 4204 chiseled on N. edge of limestone ledge 5 ft. high by 40 ft. long brs. S.28°35'E., 16.2 ft. dist.

A mesquite tree 5 ins. diam. brs. N. 32°10'W., 8.0 ft. dist., blazed and scribed 2 DB - 4204., B.T.

Loc. Mon. brs. S. 9°50'W., 22 ft. dist. hereinafter described

No other bearings are available.

Feet.

MINERAL SURVEY No.4204

Feet.

Thence N. 86°50'W.

310.0 Gulch brs. northwesterly.

1500.00 To Cor. No.3, identical with Loc. Mon. Where I-
Set a steel post 2 ins. diam. with lead cap on top, 24 ins. above ground, 18 ins. in the ground and surrounded with md of stone, stamped 3 D B - 4204.

No bearings are available.

Thence N. 14°00'E.

305.0 To W. end center, identical with Loc. Mon. Where I-
Set a mesquite post 4 ins. diam. by 4 ft. high, 50% firmly in the ground and surrounded with md of stone, scribed W. C-D B.

470.0 South bank Queen Creek brs. westerly.

550.0 North bank Queen Creek brs. westerly.

610.0 To Cor. No.4. Where I-
Set a steel post 2 ins. diam with lead cap on top, 24 ins. above ground, 18 ins. in the ground and surrounded with md of stone, stamped 4 D B - 4204.

A mesquite tree 8 ins. diam. brs. S. 0°55'W., 34.3 ft. dist. Blazed and scribed 4-4204 B.T.

Location Mon. Brs. N.86°50'W., 70.4 ft. dist. Hereinafter described.

No other bearings are available.

Thence S. 86°50'E.

200.0 N. bank Queen Creek, brs. southwesterly.

400.0 S. bank Queen Creek brs southwesterly.

725.0 Fence brs. southeasterly.

765.0 S. bank Queen Creek brs. northwesterly.

840.0 N. Bank Queen Creek brs. northwesterly.

1125.0 Road brs. southerly.

1370.0 Road brs. southwesterly.

1500.0 To Cor. No.1 and place of beginning.

LODE Line.

The presumed course of the vein of the lode location embraced in this survey, counted from the point of discovery, is as follows:

Dewberry lode, S.86°50'E., 530.0 ft. and N. 86°50'W., 970.0 ft.

AREA.

Total area, Dewberry lode ----- 20.631 Acres.

LOCATION.

This survey is located in the N. 1/2 Sec. 8, T. 2 S. R. 12 E., G. & S. R. B. M. in the Crook National Forest.

The survey is identical with the location as marked upon the ground.

MINERAL SURVEY No.4204

EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements made upon or for the benefit of the location embraced in said mining claim by the claimant or his grantors is not less than \$500.0 and that said improvements consist of :

- No.1 The discovery point of the Dewberry lode is on the center line 530 ft. from the center of line 1-2.
A md of stone on cropping.
No Value.
- No.2 A cut, the mouth of which brs. from Cor. No.1 , S. 69°35'W., 630.0 ft. 4 1/2 ft. wide, 10 ft. face, running S.75°W., 10 ft. to face.
At Face is a tunnel 4 x 6 ft. running S. 75° W., 20 ft. to breast.
Value Cut and tunnel \$300.0
- No.3 A shaft, the center of which brs. from Cor. No.1, S.73°15'W., 670.0 ft. 5 ft. diam. 18 ft. deep.
Value \$180.0
- No.4 A shaft, (partly timbered) the center of which brs. from Cor. No.1 S. 63°W., 530.0 ft. 5 x 5 ft. 25 ft. deep.
Value \$300.0

OTHER IMPROVEMENTS.

A frame dwelling house, the N.E. Cor. of which brs. from Cor. No.1 S. 58°30'W., 560.0 ft. 20 x 26^{ft}, Course of long sides N, 62°W.

Adjoining claims.

- On the East by Homestead Entry Sur. No.167
- On the South by Dew Drop lode, Uns. Claimant herein
- On the West by Twelve One lode Uns. Claimant herein.

Other Corner Descriptions.

H.E. S. No.167
 Line 10 - 11 was found to be 555.2 ft. instead of 561 (8.5 Chs) as approved. Cor. No.10 Consists of a lava rock 6 x 12 ins. showing 18 ins above ground, with md of stone alongside, chiseled 10 H.E.S.-167
 A diligent search was made for the 1/4 Cor. bet. Secs. 5 and 8, T.2 S. R. 12 E. and same was found to have been obliterated.

All loc. Corners consist of md of stone.

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by T.N. Stevens

~~United States~~ Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and ~~General Land Office~~

boundaries described in the foregoing field notes of the survey of the mining claim of _____

George N. Lobb

known as the DEWBERRY Lode

and showing the respective capacities in which they acted.

Henry Waer, Chainman.

_____, Chainman.

_____, Axman.

_____, Flagman.

FINAL OATHS OF ASSISTANTS

~~Mr~~ I. Henry Waer

~~and~~ _____, do solemnly swear that we assisted _____

T.N. Stevens, ~~United States~~ Mineral Surveyor, in marking the corners and surveying ~~General Land Office~~

the boundaries of the mining claim of George N. Lobb

known as the Dewberry lode

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at Phoenix, Ariz

Henry Waer, Chainman.

_____, Chainman.

_____, Axman.

_____, Flagman.

Subscribed and sworn to by the above-named persons before me this 28th

day of October, 1937

My Commission expires 11/29/39

[Signature]
Notary Public

FINAL OATH OF U. S. MINERAL SURVEYOR

I, T.N. Stevens, ~~U.S.~~ ^{U.S.} Mineral Surveyor,
General Land Office

do solemnly swear that, in pursuance of instructions received from the Office Cadastral Engineer, at Phoenix, Arizona, dated Aug. 20, 1937,

I have, in strict conformity to the laws of the United States, the official regulations and instructions thereunder, and the instructions of said Office Cadastral Engineer, faithfully and correctly executed the survey of the mining claim of George W. Lobb, known as the Dewberry lode, situate in Pioneer Mining District, Pinal County, Ariz., in Section 8, Township No. 2 S., Range No. 12 E. and designated as Survey No. 4204, as represented in the foregoing field notes, which accurately show the boundaries of said mining claim as distinctly marked by monuments on the ground, and described in the attached copy of the location certificate, which was received by me from the Office Cadastral Engineer with said instructions, and that all corners of said survey have been established and perpetuated in strict accordance with the law, official regulations and instructions thereunder; and I do further solemnly swear that the foregoing are the true and original field notes of said survey and my report therein, and that the labor expended and improvements made upon said mining claim by claimant or his grantors are as therein fully stated, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of said labor or improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

T.N. Stevens
(~~U.S.~~ ^{U.S.} Mineral Surveyor)
General Land Office

Subscribed and sworn to by the said T.N. Stevens

~~U.S.~~ ^{U.S.} Mineral Surveyor, before me O.V. Richy Notary Public

Pima County, Arizona this 28th

day of October, 1937

My Commission expires 11/29/39

O.V. Richy
Notary Public

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

Department of the Interior

PUBLIC SURVEY OFFICE

Phoenix, Arizona,

November 10, 1937

I, Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

George N. Lobb

known as the DEWBERRY Lode

situate in Pioneer

Mining District Pinal County Arizona

in Section 8, Township No. 2 S., Range No. 12 E., and

designated as Survey No. 4204, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant or his grantors, and that said improvements consist of 1 cut and tunnel and 2 shafts, total value \$780.

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Sherman C. Fiske

Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

DEPARTMENT OF THE INTERIOR PUBLIC SURVEY OFFICE

At Phoenix, Arizona

November 10, 1937, 1937

I, Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

George N. Lobb

, known as the

DEWBERRY Lode

situate in Pioneer mining district,

Pinal County, Arizona

in Section 8, Township No. 2 S., Range No. 12 E.

, designated as Survey No. 4204

executed by T. N. Stevens, U. S. Mineral

Surveyor, September 21 - 24, 1937, under my instructions dated

August 20, 1937, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

Shuman C. Fisher

Office Cadastral Engineer.