MINERAL SURVEY No. 4214

Arizona Land District
Lana District
Chief of the Load No. 2 Petruary 22, 1912 -
FIELD NOTES
OF THE SURVEY OF THE MINING CLAIM OF
A. G. Hull
KNOWN AS THE Lucinda, Soprise, Diana, Berkley, Lorina, Chief of Dome, Chief of the Dome No.1, Chief of the Dome No.2, Chief of the Dome No.4, Chief of the Dome No.5, Hull No.3, Hull No.4, Hull No. 5 lodes. Castle Dome Mining District,
Yume County, Arizona
Approx. Section s 10 & 15 , Township 4 S , Range 19 W., Unsur. Surveyed under instructions dated May 4, , 19 38.
By Harlow D. Phelps
Mineral Surveyor. G.L.O
Nov. 9, 1887, Feb. 7, 1888, Feb. 21, 1902, Jan. 22, 1906, Jan. 1, 2, 22, 1911,
Claim located Aug.1, 1911, Jan.1,10,1918, 19
Survey commenced May 26, , 19 38
Survey completed June 17, , 19 38
Address of claimant's Attys; Ellinwood & Ross, Phoenix, Ariz.
DATES OF AMENDED LOCATIONS
April 19, 1938
6—822 U R. GOVERNMENT PRINTING OFFICE: 1927

Claims located.

Lucinda Soprise Diana Berkley			August 1, 1911 November 9, 1887 January 2, 1911 January 22, 1906
Lorina	MODEL II		February 21, 1902
Chief of Dom			February 7, 1888
Chief of the	Dome No.	1	January 22, 1911
Chief of the	Dome No.	2	February 22, 1911
Chief of the	Dome No.	3	January 22, 1911
Chief of the	Dome No.	4	January 22, 1911
Chief of the	Dome No.	5	January 22, 1911
Hull No. 2			January 1, 1918
Hull No. 3		MICH COLD	January 1, 1918
Hull No. 4			January 10, 1918
Hull No. 5			February 25, 1918

STE-B

Feet

Mineral Survey No. 4214 was made with a Gurley Precise Transit No. 241014, model No. 92, with horizontal limb 5.65 ins. diam., having two double opposite verniers, and full vertical circle 5 ins. diam., having one double vernier; the verniers read to one minute of arc. Extra eye piece equipped with colored glass was used for making direct observation upon the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order. An a.m. altitude observation of the sun for azimuth and at noon, on the meridian, for latitude and time, were made at a corner of the survey, the details of which observations are shown in the calculation sheets herewith submitted for examination.

All azimuths in this record are referred to the true meridian thus determined, by the method of deflection

angles and calculated courses.

The lines were measured with a Lufkin steel tape 500 feet in length, graduated every foot for the entire length, each end foot being graduated in tenths and hundredths; the tape was compared with a Lufkin standard at a time before the beginning of the survey and found to be correct.

All lines and connections of this survey were run by direct method.

The magnetic variation observed at each corner of the survey gave a uniform value of 14° 45' E.

DIANA LODE

Beginning at Cor. No. 1 of the Diana lode, which is identical with Cor. No. 2 Sur. No. 1379 Lola lode and agrees with a corner of the location, where I -

Set a galvanized iron post 3 ft. long, l in. diam. 24 ins. in the ground, for Cor. No. 1, with brass cap mkd. U.S. Min. Sur. X D-1-S-1-H2-1-H3-1-4214; from which

U.S.L.M. No. 1379 in Twp. 4 S., R. 18 or 19 W. unsurveyed, bears N. 270 18' W., 565.6 ft. dist., a porphyry rock marked, U.S.L.M. No. 1379-X, along side a mound of stone.

No local bearing objects or bearing trees available.

Thence N. 320 48! W.

1162.6 |Cor. No. 2

Identical with Cor. No. 1 Sur. No. 1379 Lola lode, and agrees with a corner of the location.

Set a galvanized iron post 3 ft. long, l in. diam., 24 ins. in ground, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X D-2 H3-4; CD5-1 CD-1-4214.

No local bearing objects or bearing trees available.

Thence S. 570 12' W.

The north end center, agreeing with the north end center of the location, being a mound of stone 3 ft. high, 3 ft. base.

600.0 Cor. No. 3

Identical with Cor. No. 4 Sur. No. 1379 Lola lode, and agrees with a corner of the location.

Feet	Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X D-3; CD-4; CD3-1, B-1-4214, from which
	A Cottonwood, 13 ins. diam., bears N. 54° 03' W., 71.7 ft. dist., mkd. X D-3-4214 BT
	Thence S. 32° 48' E.
1150.0	Road to Yuma and Dome, Arizona, bears West and East
1162.6	Cor. No. 4
	Identical with Cor. No. 3 Sur. No. 1379 Lola lode, and agrees with a corner of the location.
	Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 4, with brass cap mkd. U. S. Min. Sur. X D-4, S-2-4214; from which
	A brass cap set with cement in a Porphyry boulder, 6 ins. above ground, mkd. U. S. Geological Survey, 1925, Elev. 1400 ft., bears S. 830 43' W., 396.3 ft. dist.
	Thence N. 57° 12' E.
15.0	Road to Yuma and Dome, Arizona, bears West and East.
300.0	The south end center, agreeing with the south end center of the location, being a mound of stone 3 ft. high, 3 ft. base.
600.0	Cor. No. 1 and place of beginning.
	SOPRISE LODE
	Beginning at Cor. No. 1 of the Soprise lode which is identical with Cor. No. 1 Diana lode of this survey hereinbefore described and agrees with a corner of the location.
	Thence S. 57° 12' W.
300.0	The north end center, agreeing with the north end center of the location and identical with the south end center of Diana lode of this survey, hereinbefore described.
585.0	Road, to Yuma and Dome, Arizona, bears west and east.
600.0	Cor. No. 2
	Identical with Cor. No. 4 Diana lode of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence S. 32° 48' E.
337.4	Intersect Cor. No. 1, Lorina lode of this survey, herein-after described.
1500.0	Cor. No. 3
	Agrees with a corner of the location.
	Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X S-3-4214.
	No local bearing objects or bearing trees available.
the state of the s	

N	Feet	Thence N 57° 12' E.
	75.0	Road to Yuma and Dome, Arizona, bears, North and South.
	300.0	The south end center, agreeing with the south end center of the location, being a mound of stone 3 ft. high, 3 ft. base.
	600.0	Cor. No. 4
		Agrees with a corner of the location.
		Set an iron post 3 ft. long, l in. diam., 24 ins. in ground for Cor. No. 4, with brass cap, mkd. U. S. Min. Sur. X S-4; H2-2:4214; from which
		A Palo Verde, 6 ins. diam., bears S. 89° 38' W., 68.3 ft. dist. mkd. X S-4-4214- BT.
	1500.0	Thence N. 32° 48' W. Cor. No. 1 and place of beginning.
		LORINA LODE
	1	Beginning at Cor. No. 1 of the Lorina lode, on line 2-3 Soprise lode, and agrees with a corner of the location, where I
		Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in a drill hole in solid rock and securely wedged, for Cor. No. 1, with brass cap mkd U. S. Min. Sur. X Lo-1,-B-4-4214; from which
		U.S.L.M. No. 1379, hereinbefore described, bears N. 30 12' E., 1113.0 ft. dist.
		A point on a metamorphosed schist bed rock, level with the ground, bears S. 32° 48' E., 3.5 ft. dist., mkd. X BR Lo1-4214.
		Thence S. 57° 12' W.
	300.0	The north end center, identical with Cor. No. 1. Lucinda lode of this survey, hereinafter described, and agrees with the north end center of the location.
	600.0	Cor. No. 2
		Agrees with a corner of the location.
		Set a galvanized iron post, 3 ft. long, 1 in. diam., 20 ins. in ground to bed rock and in mound of stone, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X Lo2,-B-3,-H4-4-4214.
		No local bearing objects or bearing trees available.
	1030.36	Thence S. 32° 48' E. Intersect line 1-4 Lucinda lode of this survey.
	1500.0	Cor. No. 3
		Agrees with a corner of the location
		Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X Lo3-4214.

	Feet	A porphyry boulder 24 ins. x 24 ins., 10 ins. above ground, bears S. 64° 02' E., 38.7 ft. dist. mkd. X Lo-3-4214 BR. Thence N. 57° 12' E.
	300.0	
	410.0	Road to Yuma and Dome, Arizona, bears N. 10° E. and S. 15° W.
	600.0	Cor. No. 4
		Agrees with a corner of the location.
		Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 4, with brass cap mkd. U. S. Min. Sur. X Lo4-4214.
944		No local bearing objects or bearing trees available.
		Thence N. 32° 48' W.
	215.0	Road to Yuma and Dome, Arizona, bears North and S. 5° W.
	337.4	Cor. No. 3 Soprise lode of this survey hereinbefore described.
	1500.0	Cor. No. 1, and place of beginning.
		LUCINDA LODE
		Beginning at Cor. No. 1 of the Lucinda lode, which agrees with a corner of the location and is identical with the north end center Lorina lode of this survey, where I Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground for Cor. No. 1, with brass cap mkd. U. S. Min. Sur. X Lu1-4214; from which
		U. S. L. M. No. 1379, hereinbefore described, bears N. 13° 52' E., 1312.0 ft. dist.
		Thence S. 73° 26' W.
	300.0	The north end center, agreeing with the north end center of the location, being a mound of stone 3 ft. high,
	312.46 600.0	3 ft. base. Intersect lines 2-3 and 1-4 Berkley and Hull No.4 lodes, Cor. No. 2 of this survey, respectively.
		Agrees with a corner of the location.
		Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X Lu2-4214.
THE PERSON		No local bearing objects or bearing trees available.
		Thence S. 16° 34' E.
	174.70	Intersect line 3-4 Hull No. 4 lode of this survey.
	1500.0	Cor. No. 3
		Agrees with a corner of the location.
	DOWN BELLEVA	

-			÷
	Feet	Set a galvanized iron post 3 ft. long, l in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X Lu3-4214.	
		No local bearing objects or bearing trees available.	
		Thence N. 73° 26' E.	
	300.0	The south end center, agreeing with the south end center of the location, being a mound of stone 3 ft. high, 3 ft. base.	
	600.0	Cor. No. 4	
		Agrees with a corner of the location.	
		Set a galvanized iron post 3 ft. long, l in. diam., 24 ins. in ground, for Cor. No. 4, with brass cap mkd. U. S. Min. Sur. X Lu4-4214, from which	
		Cor. No. 3, Lorina lode, of this survey, bears N. 83° 50' E., 133.3 ft. dist.	
		No local bearing objects or bearing trees available.	
		Thence N. 16° 34' W.	
	426.85	Intersect line 2-3 Lorina lode of this survey.	
	1500.0	Cor. No. 1 and place of beginning.	
		BERKLEY LODE	
		Beginning at Cor. No. 1 of the Berkley lode, which is identical with Cor. No. 3 Diana lode, of this survey, hereinbefore described, and agrees with a corner of the location; from which	
		U. S. L. M. No. 1379, hereinbefore described, bears S. 80° 17' 30" E., 887.5 ft. dist.	
		Thence S. 57° 12' W.	
	300.0	The north end center, agreeing with the north end center of the location, being a mound of stone, 3 ft. high, 3 ft. base.	
	600.0	Cor. No. 2	
		Agrees with a corner of the location.	
		Set a galvanized iron post, 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X B-2,-CD3-4,-H5-1,-H4-1-4214.	
		No local bearing objectsor bearing trees available.	
		Thence S. 32° 48' E.	
•	900.0	Road to Yuma and Dome, Arizona, bears S. 70° W. and N. 75° E.	
	1412.65	Intersect line 1-2 Lucinda lode, of this survey.	
	1500.0	Cor. No. 3	
		Identical with Cor. No. 2 Lorina lode, of this survey, hereinbefore described, and agrees with a corner of the location.	
	100 100 100		

dirp-

-		
	Feet	Thence N. 57° 12' E.
	300.0	The south end center, agreeing with the south end center of the location and identical with Cor. No. 1 Lucinda lode, of this survey, hereinbefore described.
	600.0	Cor. No. 4
		Identical with Cor. No. 1 Lorina lode of this survey, hereinbefore described, and agrees with a corner of the location.
		Thence N. 32° 48' W.
	337.4	Intersect Cor. No. 4 Diana lode of this survey, herein- before described.
	350	Road, brs. West and east.
	1500.0	Cor. No. 1 and place of beginning.
		CHIEF OF DOME LODE
		Beginning at Cor. No. 1 of the Chief of Dome lode, which is identical with Cor. No. 2 Diana lode, of this survey, hereinbefore described, and agrees with a corner of the location; from which
		U. S. L. M. No. 1379, hereinbefore described, bears S. 370 58' E., 602.1 ft. dist.
		Thence N. 32° 48' W.
	1500.0	Cor. No. 2
		Agrees with a corner of the location.
		Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X CD-2, CD5-4, CD4-1, CD1-1-4214.
		No local bearing objects or bearing trees available.
		Thence S. 57° 12' W.
	300.0	The north end center, agreeing with the north end center of the location, being a mound of stone, 3 ft. high, 3 ft. base.
	600.0	Cor. No. 3
		Agrees with a corner of the location
		Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X CD-3, CDl-4, CD2-1, CD3-2-4214.
		No local bearing objects or bearing trees available.
		Thence S. 32° 48' E.
	1500.0	Cor. No. 4
		Identical with Cor. No. 3 Diana lode, of this survey, hereinbefore described, and agrees with a corner of the location.

	Feet	Thence N. 570 12' E.	
	300.0	The south end center, agreeing with the south end center of the location, and identical with the north end center of the Diana lode of this survey, hereinbefore described.	
	600.0	Cor. No. 1 and place of beginning.	
		CHIEF OF THE DOME No. 1 lode	
		Beginning at Cor. No. 1 of the Chief of the Dome No. 1 which is identical with Cor. No. 2 Chief of Dome lode of this survey, hereinbefore described, and agrees with a corner of the location; from which	
		U. S. L. M. No. 1379 hereinbefore described bears S. 34° 17' E., 2100.4 ft. dist.	
		Thence N. 32° 48' W.	
	1500.0	Cor. No. 2	
		Agrees with a corner of the location.	
		Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 2 with brass cap mkd. U. S. Min. Sur. X CD1-2, CD4-4-4214.	
		No local bearing objects or bearing trees available.	
		Thence S. 57° 12' W.	
	300.0	The north end center, agreeing with the north end center of the location, being a monument of stone 3 ft. high, 3 ft. base.	
	600.0	Cor. No. 3	
		Agrees with a corner of the location.	
		Set a galvanized iron post 3 ft. long, l in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X CDl-3, CD2-2-4214.	
		No local bearing objects or bearing trees available.	
		Thence S. 32° 48' E.	
	1500.0	Cor. No. 4	
		Identical with Cor. No. 3, Chief of Dome lode of this survey, hereinbefore described, and agrees with a corner of the location.	
		Thence N. 57° 12' E.	
	300.0	The South end center, agreeing with the south end of the location and identical with the north end center of the Chief of Dome lode of this survey, hereinbefore described.	
	600.0	Cor. No. 1 and place of beginning.	
•		CHIEF OF THE DOME No. 2 Lode	
		Beginning at Cor. No. 1 Chief of the Dome No. 2, which is identical with Cor. No. 3 Chief of Dome lode of this survey, hereinbefore described, and agrees with a corner of the location; from which	

	U. S. L. M. No. 1379 hereinbefore described bears S. 50° 06' E., 2199.3 ft. dist.
	Thence N. 32° 48' W.
1500.0	Cor. No. 2
	Identical with Cor. No. 3 Chief of the Dome No. 1 lode of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence S. 57° 12' W.
300.0	The north end center agreeing with the north end center of the location, being a monument of stone 3 ft. high, 3 ft. base.
600.0	Cor. No. 3
	Agrees with a corner of the location.
	Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X CD2-3-4214.
	No local bearing objects or bearing trees available.
	Thence S. 32° 48' E.
1500.0	Cor. No. 4
	Agrees with a corner of the location.
	Set a galvanized iron post, 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 4, with brass cap mkd. U. S. Min. Sur. X CD2-4, CD3-3, H5-2-4214.
	No local bearing objects or bearing trees available.
	Thence N. 57° 12' E.
300.0	The south end center, agreeing with the south end center of the location, being a monument of stone, 3 ft. high, 3 ft. base.
600.0	Cor. No. 1 and place of beginning.
	CHIEF OF THE DOME No. 3 Lode
	Beginning at Cor. No. 1 Chief of the Dome No. 3 lode, which is identical with Cor. No. 3 Diana lode and Cor. No. 1 Berkley lode, of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence N. 32° 48' W.
1500.0	Cor. No. 2
	Identical with Cor. No. 3 Chief of Dome lode of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence S. 57° 12' W.
300.0	The north end center, agreeing with the north end center of the location and identical with the south end center of the Chief of the Dome No. 2 lode of this survey, hereinbefore described.
600.0	Cor. No. 3

11

Identical with Cor. No. 2 Chief of the Dome No. 1 lode, of this survey, hereinbefore described, and agrees with a corner of the location.

Feet	Thence S 32° 48' E.
1500.0	Cor. No. 1 and place of beginning.
	CHIEF OF THE DOME No. 5 Lode
	Beginning at Cor. No. 1 of the Chief of the Dome No. 5 lode, which is identical with Cor. No. 2 Diana lode and Cor. No. 1 Chief of Dome lode, of this survey, hereinbefore described and agrees with a corner of the location.
	Thence N. 57° 12' E.
300.0	The south end center agreeing with the south end center of the location, being a mound of stone, 3 ft. high, 3 ft. base.
600.0	Cor. No. 2
	Agrees with a corner of the location.
	Set a galvanized iron post, 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X CD5-2; H3-3-4214.
	No local bearing objects or bearing trees available.
	Thence N. 32° 48' W.
1500.0	Cor. No. 3
0 0	Identical with Cor. No. 2 Chief of the Dome No. 4 lode, of this survey, hereinbefore described and agrees with a corner of the location.
	Thence S. 57° 12' W.
300.0	The north end center, agreeing with the north end center of the location, and identical with the south end center of the Chief of the Dome No. 4 lode of this survey, hereinbefore described.
600.0	Cor. No. 4
	Identical with Cor. No. 2 Chief of Dome lode of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence S. 32° 48' E.
1500.0	Cor. No. 1 and place of beginning.
	HULL No. 3 Lode
	Beginning at Cor. No. 1 of the Hull No. 3 lode which is identical with Cor. No. 1 Diana lode of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence N. 57° 12' E.
300.0	The South end center, agreeing with the south end center of the location, being a monument of stone 3 ft. high, 3 ft. base.
600.0	Cor. No. 2
	Agrees with a corner of the location.

Feet	Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X H3-2, H2-4-4214.
	No local bearing objects or bearing trees available.
	Thence N. 32° 48' W.
1162.6	Cor. No. 3
	Identical with Cor. No. 2 Chief of the Dome No. 5, here- inbefore described, and agrees with a corner of the location.
	Thence S. 57° 12' W.
300.0	The north end center, agreeing with the north end center of the location, and identical with the south end center of the Chief of the Dome No. 5 lode, of this survey, hereinbefore described.
600.0	Cor. No. 4
	Identical with Cor. No. 2 Diana lode of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence S. 32° 48' E.
1162.6	Cor. No. 1 and place of beginning.
	HULL No. 2 Lode.
	Beginning at Cor. No. 1 of the Hull No. 2 lode which is identical with Cor. No. 1 of the Diana lode, of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence S. 32° 48' E.
1500.0	Cor. No. 2
	Identical with Cor. No. 4, Soprise lode of this survey, hereinbefore described, and agrees with a corner of the location.
	Thence N. 57° 12' E.
300.0	The south end center, agreeing with the south end center of the location, being a monument of stone 3 ft. high, 3 ft. base.
600.0	Cor. No. 3
	Agrees with a corner of the location.
	Set a galvanized iron post 3 ft. long, l in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X H2-3-4214.
	A Palo Verde 6" diam. bears N. 23° 56' E., 50.6 ft. dist., mkd. X H2-3-4214.
	No local bearing objects or bearing trees available.
	Thence N. 32° 48' W.
1500.0	Cor. No. 4

	Feet	Identical with Cor. No. 2, Hull No. 3 lode of this survey, hereinbefore described, and agrees with a corner of the location.
		Thence S. 57° 12' W.
	300.0	The north end center, agreeing with the north end center of the location, and identical with the south end center of the Hull No. 3 lode of this survey, hereinbefore described.
	600.0	Cor. No. 1 and place of beginning.
N.		HULL No. 4 Lode
		Beginning at Cor. No. 1 of the Hull No. 4 lode, which is identical with Cor. No. 2 of the Berkley lode of this survey, hereinbefore described, and agrees with a corner of the location.
		U. S. L. M. No. 1379, hereinbefore described, bears N. 82° 45' E., 1390.2 ft. dist.
		Thence S. 57° 12' W.
	300.0	The north end center, agreeing with the north end center of the location, being a monument of stone 3 ft. high, 3 ft. base.
	600.0	Cor. No. 2
		Agrees with a corner of the location
		Set a galvanized iron post, 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 2, with brass cap mkd. U. S. Min. Sur. X H4-2, H5-4-4214
		No local bearing objects or bearing trees available.
		Thence S. 32° 48' E.
	850.0	Road to Yuma and Dome, Arizona, bears S. 57° W. and N. 57° E.
	1500.0	Cor. No. 3
100		Agrees with a corner of the location.
		Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X H4-3-4214.
		No local bearing objects or bearing trees available.
N.		Thence N. 57° 12' E.
	275.08	Intersect line 2-3 Lucinda lode, of this survey.
	300.0	The south end center, agreeing with the south end center of the location, being a mound of stone 3 ft. high, 3 ft. base.
	600.0	Cor. No. 4
		Identical with Cor. No. 2, Lorina lode of this survey, hereinbefore described, and agrees with a corner of the location.
		Thence N. 32° 48' W.

7-	
Feet 87.35	Intersect line 1-2 Lucinda lode, of this survey.
600.0	Road, bears S. 70° W. and N. 75° E.
1500.0	Cor. No. 1 and place of beginning.
	HULL No. 5 Lode
	Beginning at Cor. No. 1 of the Hull No. 5 lode, which is identical with Cor. No. 2 Berkley lode and Cor. No. 1 of the Hull No. 4 lode of this survey, hereinbefore described and agrees with a corner of the location.
	Thence N. 32° 48' W.
1500.0	Cor. No. 2
	Identical with Cor. No. 4, Chief of the Dome No. 2 lode, of this survey, hereinbefore described, and agrees with a corner of the location
	Thence S. 57° 12' W.
300.0	The north end center, agreeing with the north end center of the location, being a monument of stone 3 ft. high, 3 ft. base.
600.0	Cor. No. 3
	Agrees with a corner of the location.
	Set a galvanized iron post 3 ft. long, 1 in. diam., 24 ins. in ground, for Cor. No. 3, with brass cap mkd. U. S. Min. Sur. X H5-3-4214.
	No local bearing objects or bearing trees available.
	Thence S. 32° 48' E.
1500.0	Cor. No. 4
	Identical with Cor. No. 2 Hull No. 4 lode, of this survey, hereinbefore described and agrees with a corner of the location.
	Thence N. 57° 12' E.
300.0	The south end center, agreeing with the south end center of the location and identical with the north end center of the Hull No. 4 lode, of this survey, hereinbefore described.
600.0	Cor. No. 1 and place of beginning.
	LODE LINES
	The presumed course of the vein of each of the several lode locations embraced in this survey, counted from the respective points of discovery, is as follows:
	Diana lode, N. 32° 48' W., 80 ft.; and S. 32° 48' E., 1082.6 ft.
	Soprise lode, N. 32° 48' W., 440 ft.; and S. 32° 48' E., 1060 ft.
	Lorina lode, N. 32° 48' W., 20 ft.; and S. 32° 48' E., 1480 ft.

Lucinda lode, S. 16° 34' E., 610 ft.; and N. 16° 34' W., 890 ft.
Berkley lode, S. 32° 48' E., 100 ft.; and N. 32° 48' W., 1400 ft.
Chief of Dome lode, S., 32° 48' E., 155 ft.; and N. 32° 48' W., 1345 ft.
Chief of the Dome No. 1 lode, S. 32° 48' E., 300 ft.; and N. 32° 48' W., 1200 ft.
Chief of the Dome No. 2 lode, S. 32° 48' E., 300 ft.; and N. 32° 48' W., 1200 ft.
Chief of the Dome No. 3 lode, N. 32° 48' W., 650 ft.; and S. 32° 48' E., 850 ft.
Chief of the Dome No. 4 lode, S. 32° 48' E., 300 ft.; and N. 32° 48' W., 1200 ft.
Chief of the Dome No. 5 lode, N. 32° 48' W., 300 ft.; and S. 32° 48' E., 1200 ft.
Hull No. 3 lode, S. 32° 48' E., 140 ft.; and N. 32° 48' W. 1022.6 ft.
Hull No. 2 lode, S. 32° 48' E., 10 ft.; and N. 32° 48' W. 1490 ft.
Hull No. 4 lode, S. 32° 48' E., 340 ft.; and N. 32° 48' W. 1160 ft.
Hull No. 5 lode, N. 32° 48' W., 375 ft.; and S. 32° 48' E. 1125 ft.
AREAS Acres.
Total area, Diana lode 16.014
Total area, Soprise lode 20.661
Total area, Lorina lode 20.661
Total area, Lucinda lode 20.661
Area in conflict with-
Lorina lode, of this survey 3.548
Berkley lode, of this survey 0.301
Hull No. 4 lode, of this survey 0.902
Total area, Berkley lode 20.661
Total area, Chief of Dome lode 20.661
Total area, Chief of the Dome No. 1 lode 20.661
Total area, Chief of the Dome No. 2 lode 20.661
Total area, Chief of the Dome No. 3 lode 20.661
Total area, Chief of the Dome No. 4 lode 20.661
Total area, Chief of the Dome No. 5 lode 20.661
Total area, Hull No. 3 lode 16.014
100a1 a10a, 11a11 No. 0 10a0 10.014

Acres Total area, Hull No. 2 lode - - - -20.661 20.661 Total area, Hull No. 4 lode - - -20.661 Total area, Hull No. 5 lode - - -

LOCATION

This survey is located approximately in Secs. 10 and 15, T. 4 S., R. 19 W., Unsur. of the G. & S. R. M. XXX., Arizona.

EXPENDITURE OF \$500

I certify that the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors is not less than \$500., and that said improvements consist of : DIANA

The discovery shaft of the Diana lode, (known as No. 3 shaft), the center of which being the discovery point is on the lode line S. 32° 48' E., 80 ft. from the north end center, 5 x 7 ft. single compartment, with manway, 435 ft. deep, including a 63 ft. sump below the 372 ft. No. 1 level.

Value \$45,000

Value of one-fifteenth interest, \$3,000.

This improvement was started about September 1928 and completed in 1929 for the development of a total of fifteen lode claims of this group, all of which are contiguous lode claims owned in common within the range of benefit of said shaft.

This improvement is a vertical shaft replacing an irregular incline shaft at this location, and is completely timbered with creosoted timber.

Five hundred dollars and over have been expended in this improvement for the development of each lode of this survey subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore an undivided one-fifteenth interest in its

value is hereby credited to each of said lodes.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode

claim.

- A shaft, 4 x 7 ft., (known as No. 4 shaft), caved below the 100 ft. level, the center of which bears S. 75° 45'E., 375 ft., from Cor. No. 3, Diana lode. The underground development consists of 150 ft. of drifting from the 100 ft. level, bears N. 33° W. and S. 33° E. Value \$7,500. No. 2
- A shaft, 4 x 6 ft., (known as No. 5 shaft), caved below the 85 ft. level, the center of which bears S. 57° E., No. 3 595 ft., from Cor. No. 3 Diana lode. Value \$3,000.
- A shaft, 4 x 5 ft., (known as No. 6 shaft), 150 ft. deep, the center of which bears N. 5° 10' W., 545 ft. from Cor. No. 4 Diana lode. No. 4 Value \$5,000.

No. 5	A shaft, 4 x 6 ft., with wood head frame, known as No. 7 shaft, 135 ft. deep, the center of which bears N. 120 20' E., 375 ft. from Cor. No. 4 Diana lode. A drift about 220 ft. long connects No. 6 and No. 7 shafts, on the 100 ft. level, bears N. 35 W. Value \$12,000.
No. 1	The discovery of the Soprise lode, being a point on the presumed outcrop of the vein, S. 32° 48' E., 440 ft. from the north end center and marked by a mound of stone 3 ft. base, 3 ft. high.
No. 2	A shaft, (known as No. 12 shaft), the center of which bears S. 37° 21' E., 442 ft., from the north end center of the Soprise lode, 4 x 6 ft., caved below the 100 ft. level. Value \$4,000.
No. 3	A shaft, 4 x 6 ft., with wood head frame, (known as No. 11 shaft, 175 ft. deep, all timbered, the center of which bears S. 36° 45' E., 385 ft. from the north end center of Soprise lode. Value \$10,000.
No. 4	A shaft, 4 x 6 ft., (known as No. 13 shaft), caved, depth unknown, the center of which bears S. 37° E. 495 ft. from the north end center of Soprise lode. Value \$4,000. LORINA
No. 1	The discovery shaft of the Lorina lode, the center of which being the discovery point, is on the lode line, S. 32° 48' E., 20 ft. from the north end center, 4 x 6 ft., 8 ft. deep. Value \$100.
No. 1	The discovery of the Lucinda Lode, being a point on the presumed outcrop of the vein, N. 16° 34' W., 610 ft. from the South end center and marked by a mound of stone 3 ft. base, 3 ft. high.
No. 2	A shaft, the center of which bears N. 22° 11' W., 613 ft., from the south end center of the Lucinda lode; 4 x 6 ft., 15 ft. deep. Value \$150.
No. 3	A shaft, 4 x 5 ft., 150 ft. deep, the center of which bears N. 82° E., 240 ft. from Cor. No. 2 Lucinda lode. Value \$5000.
No. 4	A shaft, 4 x 10 ft., 45 ft. deep, the center of which bears N. 33° W., 570 ft. from Cor. No. 4 Lucinda lode. Value \$2,000.
No. 1	The discovery shaft of the Berkley lode, the center of which, being the discovery point, is on the lode line, N. 32° 48' W., 100 ft., from the south end center, 4 x 6 ft., 8 ft. deep. Value \$100. CHIEF OF DOME
No. 1	The discovery shaft of the Chief of Dome lode, (known as No. 1 shaft), the center of which being the discovery point, is on the lode line, N. 32 48' W., 155 ft., from the south end center, 4 x 6 ft., 372 ft. deep. Partly caved. Value \$20,000.
No. 2	A shaft, 4 x 6 ft., (known as No. 2 shaft), caved below the 50 ft. level, the center of which bears N. 320 48' W.,

0.110-6

MINERAL SURVEY No. 4214, ARIZONA 30 ft. from the south end center of the Chief of Dome lode Value \$2,000. The underground development between this shaft, No. 1 Disc. shaft of the Chief of Dome lode and No. 1 Disc. shaft of the Diana lode, consists of drifts and stopes from the 50 ft., 185 ft., 260 ft., and 372 ft. levels; total of about 1400 linear feet, bears N. 33° W and S. Value \$21,000. CHIEF OF THE DOME NO. 1 No. 1 The discovery shaft of the Chief of the Dome No. 1 lode, the center of which being the discovery point, is on the lode line, N. 32° 48' W., 300 ft. from the south end center, 4 x 6 ft., 10 ft. deep. Partly caved.

Value \$125. CHIEF OF THE DOME NO.2 The discovery shaft of the Chief of the Dome No. 2 lode, the center of which being the discovery point, is on the lode line, N. 32° 48' W., 300 ft. from the south end center, 4 x 6 ft., 8 ft. deep. No. 1 Value \$100. CHIEF OF THE DOME NO.3
The discovery shaft of the Chief of the Dome No. 3 lode, No. 1 the center of which being the discovery point is on the lode line, S. 32° 48' E., 650 ft. from the north end center, 4 x 12 ft., 10 ft. deep. Partly caved. Value \$150. CHIEF OF THE DOME NO.4 The discovery shaft of the Chief of the Dome No. 4 lode, No. 1 the center of which, being the discovery point, is on the lode line, N. 32° 48' W., 300 ft. from the south end center, 4 x 6 ft., 10 ft. deep. Partly caved. Value \$125. Value \$125.

CHIEF OF THE DOME NO.5

The discovery shaft of the Chief of the Dome No. 5 lode, the center of which being the discovery point, is on the lode line, S. 32° 48° E., 300 ft. from the north the longer of the first the longer of the longer than No. 1 end center, 4 x 6 ft., 10 ft. deep. Value \$125. HULL NO. 2 The discovery shaft of the Hull No. 2 lode, the center of which being the discovery point, is on the lode line, N. 32° 48' W., 10 ft. from the south end center, No. 1 4 x 12 ft., 10 ft. deep. Partly caved. Value \$175. HULL NO. 3 The discovery of the Hull No. 3 lode being a point on the presumed outcrop of the vein, N. 320 48' W., 140 ft. from the south end center and marked by a mound of stone, No. 1 3 ft. base, 3 ft. high. A shaft, the center of which bears N. 42° 55' W., 142 ft. No. 2 from the south end center of the Hull No. 3 lode, 5 x 10 ft., caved below a depth of 5 ft. Value \$100. HULL NO. 4 The discovery of the Hull No. 4 lode, being a point on the presumed outcrop of the vein, N. 32° 48' W. 340 ft. from No. 1 the south end center and marked by a mound of stone, 3 ft. base, 3 ft. high. A shaft, the center of which bears N. 260 W., 342 ft.from No. 2 the south end center of the Hull No. 4 lode, 4 x 6 ft., 10 ft. deep. Partly caved. Value \$125. HULL NO. 5 The discovery shaft of the Hull No. 5 lode, the center of which being the discovery point is on the lode line, No. 1

n. s. Government printing office: 1931 6-8155

feet, 8 ft. deep. Value \$100.

S. 320 48' E., 375 ft. from the north end center, 4 x 6

OTHER IMPROVEMENTS

A shaft, 4 x 5 ft., caved, depth unknown, the center of which bears N. 53° W., 620 ft. from Cor. No. 4 Soprise lode.

Claimant unknown.

A shaft, 3 x 18 ft. 10 ft. deep, the center of which bears N. 47° W., 345 ft. from Cor. No. 3 Soprise lode. Claimant unknown.

A frame residence, the N.E. corner of which bears S. 79° W., 355 ft. from Cor. No. 4 Diana lode; 34 x 53 ft. in size; the long side bears S. 80° W. Claimant herein.

A frame boarding house, the N. E. corner of which bears N. 68° W., 505 ft. from Cor. No. 4 Diana lode; 16 x 32 ft. in size; the long side bears S. 12° E. Claimant herein.

A frame bunk house, the S.E. cor. of which bears N. 68° W., 575 ft., from Cor. No. 4 Diana lode; 16 x 20 ft. in size; the long side bears N. 12° W. Claimant herein.

A frame warehouse, the S. E. cor. of which bears N. 73° W., 550 ft. from Cor. No. 4 Diana lode; 17 x 32 ft. in size; the long side bears N. 12° W. Claimant herein.

A 5873 gal. galvanized iron tank, the center of which bears S. 29° E., 478 ft. from the north end center of the Diana lode; 10 ft. diam., 10 ft. high. Claimant herein.

A 15,995 gal. galvanized iron tank, the center of which bears S. 360 W., 60 ft. from the north end center of the Diana lode; $16\frac{1}{2}$ ft. diam., 10 ft. high. Claimant herein.

A Compressor house, the N.W. corner of which bears S. 49° W., 83 ft. from the north end center of the Diana lode; 16 x 20 ft. in size; the long side bears South. Claimant herein.

A blacksmith shop, the N.W. corner of which bears S. 76° E., 170 ft. from the north end center of the Diana lode; 12 x 16 ft. in size; the long side bears South. Claimant herein.

Hoist and pump house, the N. W. Cor. of which bears S. 30° E., 72 ft., from the north end center of the Diana lode; 16 x 25 ft. in size; the long side bears S. 57° W. Claimant herein.

OTHER CORNER DESCRIPTIONS

At all corners of this survey, identical with corners of Survey No. 1379, Lola lode, I set the cross (X) on the brass cap at the exact corner point and securely set the rock of the previous survey flush with the iron pipe. Survey No. 1379 Lola lode; Cors. Nos. 1, 2, 3 & 4 are porphyry rocks, properly marked. Lines 1-2 and 3-4 were found to be S. 32° 48' E. and N. 32° 48' W., 1161.6 ft. instead of S. 32° 49' E., and N. 32° 49' W., 1162.1 ft. as approved; lines 2-3 and 4-1 were found to be N. 57° 12' E. and S. 57° 12' W., instead of N. 57° 11' E. and S. 57° 11' W., as approved. From Cor. No. 1 U. S.L. M. No. 1379 bears S. 37° 58' E., 602.1 ft. instead of S. 37° 50' E., 602.8 ft. as approved.

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by Harlow D. Phelps
United States Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and
boundaries described in the foregoing field notes of the survey of the mining claim of A.G. Hull
known as the Lucinda, Soprisq Diana, Berkley, Lorina, Chief of Dome, Chief of Dome
No. 1, Chief of the Dome No. 2, Chief of the Dome No. 3, Chief of the Dome
known as the No. 4, Chief of the Dome No. 5, Hull No. 2, Hull No. 3, Hull No. 4, Hull No. 5, lodes.
Hull No. 4, Hull No. 5 lodes.
and showing the respective capacities in which they acted.
A. E. Fries , Chainman.
, Chainman,
, Awman.
, Flagman.
FINAL CATTLE OF ASSISTANTS
FINAL OATHS OF ASSISTANTS
We, I, A. E. Fries
and, do solemnly swear that we assisted
Harlow D. Phelps , Ukika Sintes Mineral Surveyor, in marking the corners and surveying
the boundaries of the mining claim of A. G. Hull
known as the Lucinda, Soprise, Diana, Berkley, Lorina, Chief of Dome,
Chief of the Dome No. 1, Chief of the Dome No. 2, Chief of the Dome
known as the No. 3, Chief of the Dome No. 4, Chief of the Dome No. 5,
Hull No. 2, Hull No. 3, Hull No. 4, and Hull No. 5 lodes represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his
Top-oscillation in the foregoing next notes as having seen surveyed by said mineral surveyer and under his
direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully
and correctly executed, and the corner and boundary monuments established according to law and the instruc-
tions furnished by the Office Cadastral Engineer, at Phoenix, Arizona.
a.E. Fries, Chainman.
, Chainman.
· Chainman.
, Axman.
, Flagman
The second secon
Subscribed and sworn to by the above-named persons before me this.
day of
M-2 July
My Commission Expires April 25, 1943.

DEPARTMENT OF THE INTERIOR GENERAL LAND OFFICE

FINAL OATH OF *** MINERAL SURVEYOR

I, Harlow D. Phelps , Mineral Surveyor, G.L.C
do solemnly swear that, in pursuance of instructions received from the Office Cadastral
Engineer, at Phoenix, Arizona , dated May 4, 1938.
I have, in strict conformity to the laws of the United States, the official regulations
and instructions thereunder, and the instructions of said Office Cadastral Engineer,
faithfully and correctly executed the survey of the mining claim of A.G. Hull
Lucinda, Soprise, Diana, Berkley, Lorina, Chief of Dome, Chief of the Dome No.1, Chief of the Dome No.2, Chief of the Dome No.3, Chief of the Dome No.4, Chief of the Dome No.5, Hull No.2, Hull No.3, Hull No.4 and Hull No.5 lodes . Mining District,
Yuma County, Arizona. Approx. , in Section
10 & 15 , Township No. 4 S. , Range No. 19 W., Unsur.
and designated as Survey No. 4214 , as represented
in the foregoing field notes, which accurately show the boundaries of said mining claim
as distinctly marked by monuments on the ground, and described in the attached copy of
the location certificate, which was received by me from the Office Cadastral Engineer
with said instructions, and that all corners of said survey have been established and
perpetuated in strict accordance with the law, official regulations and instructions
thereunder; and I do further solemnly swear that the foregoing are the true and original
field notes of said survey and my report therein, and that the labor expended and im-
provements made upon said mining claim by claimant orhis
grantors are as therein fully stated, and that the character, extent, location, and
itemized value thereof are specified therein with particularity and full detail, and
that no portion of said labor or improvements so credited to this claim has been in-
cluded in the estimate of expenditures upon any other claim.
Harlow Shelfs Mineral Surveyor) G.L.O.
Subscribed and sworn to by the said Harlow D. Phelps
WXXX Mineral Surveyor, before me M. E. Darrow
this 26th
day of July 19 38
My commission expires Notary Public
4-30-1941

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES -

Department of the Interior

PUBLIC SURVEY OFFICE

Phoenix, Arizona,
September 14, 1938.
I, Office Cadastral Engineer, at Phoenix, Arizona,
do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey
of the mining claim of A. G. Hull, known as the LUCINDA, SOPRISE, DIANA, BERKLEY, LORINA, CHIEF OF DOME, CHIEF OF THE DOME NO.2, CHIEF OF THE DOME NO.3, CHIEF OF THE DOME NO.4, CHIEF OF THE DOME NO.5, HULL NO.4, and HULL NO.5 lodge
situate inCastle Dome
Mining District Approx. In Sections 10 & 15 Township No. 4 S., Range No. 19 W., Unsur., and
designated as Survey No, has been correctly copied from the originals on file in
this office; that said Field Notes furnish such an accurate description of said mining claim as will, if
incorporated into a patent, serve fully to identify the premises, and that such reference is made therein
to natural objects or permanent monuments as will perpetuate and fix the locus thereof.
I further certify that Five Hundred Dollars worth of labor has been expended or improvements
made upon, or for the benefit of, each location embraced in said mining claim by claimant
or his grantors,
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975.
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. shaft on the Diana lode, is properly credited to each of the claims
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. shaft on the Diana lode, is properly credited to each of the claims in this survey.
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. shaft on the Diana lode, is properly credited to each of the claims in this survey.
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. shaft on the Diana lode, is properly credited to each of the claims in this survey.
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. shaft on the Diana lode, is properly credited to each of the claims in this survey. and that no portion of said labor or improvements has been included in the estimate of expenditures
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. shaft on the Diana lode, is properly credited to each of the claims in this survey. and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.
and that said improvements consist of 24 shefts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. sheft on the Diana lode, is properly credited to each of the claims in this survey. and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim. I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix.
and that said improvements consist of 24 shafts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. shaft on the Diana lode, is properly credited to each of the claims in this survey. and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.
and that said improvements consist of 24 shefts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. sheft on the Diana lode, is properly credited to each of the claims in this survey. and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim. I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix.
and that said improvements consist of 24 shefts, 1 sump, and 1170 ft. of underground workings, total value \$141,975. A one-fifteenth interest, value \$3,000, in No. 1, Dis. sheft on the Diana lode, is properly credited to each of the claims in this survey. and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim. I further certify that the plat thereof, filed in the U. S. Land Office at Phoenix.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

UNITED STATES DEPARTMENT OF THE INTERIOR GENERAL LAND OFFICE PUBLIC SURVEY OFFICE

At Phoenix, Arizona,
September 14 , 19 38
I, Office Cadastral Engineer at Phoenix, Arizona,
do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of
A. G. Hull
known as the LUCINDA, SOPRISE, DIANA, BERKLEY, LORINA, CHIEF OF DOME, CHIEF OF THE DOME NO.1, CHIEF OF THE DOME NO.2, CHIEF OF THE DOME NO.3, CHIEF OF THE DOME NO.4, CHIEF OF THE DOME NO.5, HULL NO.2, HULL NO.3, HULL NO.4, and HULL NO.5 lodes
situate in mining district,
Yuma County, Arizona
Approx. in Sections 10 & 15 , Township No. 4 S. , Range No. 19 W., Unsur
, designated as Survey No. 4214
executed by Harlow D. Phelps , U. S. Mineral
Surveyor, May 26 - June 17, 1938, under my instructions dated
May 4,, 1938, have been critically examined and the necessary
corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,
are hereby approved. The certified copy of the location certificate filed by the applicant for survey is
on file in this office and a true copy of said certified copy of said location certificate is included and
nade a part of the transcript of the field notes.
1

6-7131 U. S. GOVERNMENT PRINTING OFFICE: 1930

Office Cadastral Engineer.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT ARIZONA STATE OFFICE

9605 (952) M.S. 4214

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Chief of the Dome No. 1, 2, 3, 4 and 5 and Hull No. 5 lodes, Mineral Survey No. 4214, located in sections 23, 24, 25 and 26, Township 4 South, Range 19 West, Gila and Salt River Meridian, Arizona, are hereby canceled.

These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Chief of the Dome No. 1, 2, 3, 4 and 5 and Hull No. 5 lodes, M.S. 4214 were canceled December 28, 1998, by memo 9605 (952) M.S. 4214, which is now a part of the original field notes."

December 28, 1998
Date

Chief Cadastral Surveyor of Arizona