

Oct. 19 '40

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

MINERAL SURVEY NO. 4242

ARIZONA Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

BRIGHTER DAYS MINING CORPORATION

Known As The

FIRST of JULY, COMPRESSOR, EASTSIDE, TUNNEL, FRACTION, Mountain
SIDE, MOUNTAIN TOP, & HILLSIDE lodes. Wallapai Mining District,

MOHAVE County, ARIZONA

Section 6-7, Township 23 North, Range 17 & 18 West.

Surveyed under instructions dated July 8, 1940

by I. H. Foster
Mineral Surveyor.

Claim located See back hereof, 19

Survey commenced July 16, 1940

Survey completed October 1st, 1940

Address of claimant's Atty., Charles P. Elmer, Box 107,
Kingman, Arizona

DATES OF AMENDED LOCATIONS

First of July, Compressor, East Side, Tunnel, Fraction
Mountain Side and Mountain Top lodes, amended June 15,
1940

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

	Dates of Location
First of July,	July 2, 1922 ✓
Compressor	, Oct. 2, 1922 ✓
East Side	, Mar. 25, 1930 ✓
Tunnel	, July 2, 1926 ✓
Fraction	, Mar. 25, 1930 ✓
Mountain Side,	July 2, 1926 ✓
Mountain Top,	July 2, 1926 ✓
Hillside	, April 9, 1940 ✓

FIELD NOTES

of the Survey of the Mining Claims of

Known as the

of the Survey of the Mining Claims of

of the Survey of the Mining Claims of

County, Arizona

of the Survey of the Mining Claims of

Surveyed under instructions dated

by

Mineral Surveyor

State located

Survey commenced

Survey completed

DATE OF AMENDED LOCATION

of the Survey of the Mining Claims of

of the Survey of the Mining Claims of

1940

Mineral Survey No. 4242

feet

Mineral Survey No. 4242 was made with a Berger and Sons' transit No. 17069, with 5 in. plates having opposite verniers, and a 4 1/2 in. vertical circle, all reading to 1 minute; the eye piece is equipped with a colored glass shade set in the dust shutter for making direct observations on the sun. This instrument was in good condition of the survey and the adjustments in good order.

at the time
An A. M. observation of the sun for azimuth and an observation on the meridian at noon for latitude were made at the point of beginning. Time used was Pacific Standard, checked by Western Union. Details of the observations are shown on the accompanying calculation sheets, submitted for examination. All Azimuths in this record are referred to the true meridian thus established by the method of deflection and calculated courses.

All lines were measured direct with a 100 and 500 foot steel tapes, graduated every foot, with the first and last foot marked for tenths and hundredths; both tapes were in good condition and correct at the time of survey.
Variation at all corners of the survey is 15° 30' East.

Hillside lode.

Beginning at Cor. No. 1.

A cross cut on a granite Boulder in place, 3 by 5 feet, 18 inches above ground. Marked H.I-4242.

Identical with Cors. No. 1 and 2, Tunnel and Compressor lodes, this survey.

The corner of sections 12, T. 23 N. R. 18 W. G. & S. R. 23 E. M. bears S. 21° 16' E. 1034.43 feet.

Thence S. 73° 15' W.

323.71 Intersect the lode line at the southeast end center monument of the location.
647.42 To Cor. No. 2

Set a granite stone 8 by 10 inches, 30 inches long, in the ground 18 inches in a mound of earth and stone. A monument of stone 3 ft. high erected alongside. Corner marked with a cross for the exact point and H-2-4242.

Thence N. 38° 49' W.

1500.00 To Cor. No. 3

An iron pipe, 2 in. dia., 4 ft. long, with an iron cap, 2 ft. in the ground, in a mound of earth and stone.

Survey No. 4242, continued

feet

feet

Hillside lode continued,
 Cap marked with a punch mark for the exact corner and stamped H-3-4242.
 Thence N. 73° 15' E.
 the lode line at
 323.71 Intersect the northwest end center monument of the location.
 647.42 To Cor. No. 4
 A granite boulder 18 by 30 inches, 18 inches high, solid in the ground, with a cross cut for the exact corner and marked H-4-4242. A monument, 3 ft. high alongside. Identical with Cor. No. 2, Tunnel lode, this survey.
 Thence S. 38° 49' E.
 1500.00 To Cor. No. 1, the place of beginning.
 All corners are identical with the location.
 No suitable bearing objects available.
 * * * * *

Tunnel lode

Beginning/Cor. No. 1

A granite boulder in place, previously described, marked T-I-4242
 Identical with Cors. No. 1 and 2, Hillside and Compressor lodes, this survey.
 The corner of sections 18 1/2 T. 23 N. R. 18 W. G. & S. R. ~~18~~ M. 12 bears S. 21° 16' E. 1034.43 feet.
 Thence N. 38° 49' W.
 1500.00 To Corner No. 2
 A granite boulder in place, previously described, marked T-2-4242.
 Identical with Cor. No. 4, Hillside lode, this survey.
 Thence N. 73° 15' E.
 the lode line at
 318.42 Intersect the northwest end center monument of the location.
 636.84 To Corner No. 3.
 A 2 in. iron pipe, 4 ft. long with an iron cap, set 30 inches in the ground, in a mound of earth and stone, Cap stamped T-3-4242.
 A granite boulder in place, 6 by 4 feet by 5 ft. high marked X-BR-T-3-4242 bears S. 25° 42' W. 9.95 ft.

Survey No. 4242, continued

feet		feet
	<p>Identical with Cor. No. 12, First of July lode, this survey.</p> <p>Thence S. 38° 49' E.</p> <p>To corner No. 4</p> <p>A granite stone, 7 by 10 inches, 15 inches high, set in a mound of earth and stone, with a cross at the exact corner which I marked T-4-4242, for this claim.</p> <p>A granite boulder in place, 4 by 6 ft. by 2 ft. high marked X-BR-S-4-I493 bears N. 80° 30' E. 4.15 ft.</p> <p>Identical with Cors. No. 1-3 and 4, First of July and Compressor lodes, this survey and Samoan lode, Sur. No. 1493, respectively.</p> <p>Thence S. 73° 15' W.</p>	
1500.00	<p>the lode line at</p> <p>318.42 Intersect the southeast end center monument of the location.</p> <p>636.84 To Cor. No. 1, the place of beginning.</p> <p>All corners are identical with the location.</p> <p>*****</p> <p>First of July lode</p> <p>Beginning Cor. No. 1.</p> <p>A granite stone, previously described, marked FJ-I-4242.</p> <p>Identical with Cors. No. 3-4-4, Compressor and Tunnel lodes, this survey, and Samoan lode, Sur. No. 1493, respectively.</p> <p>The corner of sections 12, T. 23 N. R. 18 W. G. & S. R. B. & M. bears S. 11° 33' 30" W. 1171.27 feet.</p> <p>Thence N. 38° 49' W.</p> <p>To Cor. No. 2.</p> <p>A 2 inch iron pipe, previously described, stamped FJ-2-4242.</p> <p>Identical with Cor. No. 3, Tunnel lode, this survey.</p> <p>Thence N. 53° 40' E.</p> <p>the lode line at</p> <p>300.00 Intersect the northwest end center monument of the location.</p> <p>600.00 To To Cor. No. 3.</p> <p>A granite stone 8 by 8 in. by 30 in. long, set 20 inches in the ground in a mound of earth and stone. A cross marks the exact point, Marked FJ-3-4242.</p>	

6

Survey No. 4242, cont.,

feet

feet

A granite boulder in place, 3 by 3 ft. by 3 ft. high marked X-BR-FJ-3-4242, bears N. 22° 30' W. 8.60 ft.

On line I-4, Brighter Days lode Sur. No. 1510, at N. 22° 30' W. 1155.90 ft. and S. 22° 30' E. 247.10 ft. from Cors. No. 1 and 4, respectively.

Thence S. 38° 49' E. To Cor. No. 3, Mountain Side lode/and intersect line Sur. No. 1510, at N. 67° 30' E. 338.44 ft. from Cor. No. 1.

To Cor. No. 4. A granite stone, 8 by 10 in. 15 in. above ground, set in a mound of stone, with a cross at the exact point, marked FJ-4-4242, for this claim. Identical with Cors. No. 2 and 3, Mountain Side lode, this survey and Samoan lode, Sur. No. 1493, respectively.

A granite boulder in place, 3 by 2 ft, 16 in. above ground, marked X-BR-3-1493, bears N. 53° 40' E. 3.75 ft.

Thence S. 53° 40' W. the lode line at Intersect the southeast end center monument of the location. To Cor. No. 1, the place of beginning.

All corners are identical with the location.

Compressor lode Beginning/Cor. No. 1.

A granite boulder in place, 2 by 3 ft. 1 ft. above ground, with a cross cut at the exact point, marked C-I-4242. A stone monument erected alongside.

The corner of sections I, T. 23 N. R. 18 W. G. & S. R. bears N. 64° 33' W. 568.73 ft., and the Closing Cor. of Secs. 6 & 7, T. 23 N., R. 17 W., bears N. 83° 56' W. 520.54 ft. Thence N. 36° 20' W.

To Cor. No. 2. A granite boulder, previously described, marked C-2-4242.

Survey No. 4242, cont.,

feet		feet
	<p>Compressor lode, cont.,</p> <p>Identical with Cors. No. 1, Hillside and Tunnel lodes, this survey.</p> <p>Thence N. 73° 15' E.</p> <p>the lode line at</p>	
318.42	Intersect the northwest end center monument of the location.	
636.84	To Cor. No. 3.	
	A granite stone previously described, marked C-3-4242.	
	Identical with Cors. No. 4-I-4, Tunnel and First of July lodes, this survey and Samoan lode Sur. No. 1493, respectively	
	Thence S. 36° 20' E.	
1500.00	To Cor. No. 4.	
	A granite stone, 8 by 20 in. 15 inches above ground, with a stone monument alongside. A cross cut in stone marks the exact point; mark same as C-4-4242, for this claim.	
	Identical with Cor. No. 1, Samoan lode, Sur. No. 1493.	
	A granite boulder in place, 3 by 5 ft. 30 in. above ground, marked X-BR-I-1493, bears S. 48° 30' E. 11.20 Ft.	
	Thence S. 73° 15' W.	
318.42	the lode line at	
636.84	Intersect the southeast end center monument of the location.	
	To Cor. No. 1, the place of beginning.	
	All corners are identical with the location.	

	Mountain Side lode.	
	Beginning/Cor. No. 1.	
	A granite stone, 6 by 15 ins 30 ins long, set 20 ins in the ground, in a mound of earth and stone. A cross marks the exact point; Marked MS-1-4242	
	On line 2-3, Samoan lode, Sur. No. 1493, at N. 36° 20' W. 295.35 ft. and S. 36° 20' E. 1204.65 ft. from Cors. No. 2 and 3, respectively.	
	The corner of sections 18, T. 23 N. R. 18 W. G. & S. R. B. & M. bears S. 69° 35' 30" W. 1527.57 Ft.	

Survey No. 4242, cont.,

feet	Mountain Side lode, Cont.,	feet
1204.65	<p>Thence N. 36° 20' W. To Cor. No. 2.</p> <p>A granite stone, previously described, marked MS-2-4242.</p> <p>Identical with Cor. No. 3, Samoan lode, Sur. No. 1493 and Cor. No. 4, First of July lode, this survey.</p>	
295.57	<p>Thence N. 38° 49' W. To Cor. No. 3.</p> <p>A granite stone, 7 by 12 in. by 30 in. long, set 20 in. in the ground, in a mound of earth and stone, with a cross at the exact point and marked MS-3-4242.</p> <p>On line 3-4, First of July lode, this survey, at S. 38° 49' E. 1204.43 ft. from Cor. No. 3.</p>	
3.50	<p>On line 1-2, Brighter Days lode, Sur. No. 1510, at N. 67° 30' E. 338.44 ft. from Cor. No. 1. Thence N. 67° 30' E.</p> <p>A granite boulder in place, 4 by 5 ft. by 3 ft. above ground, marked X-BR-MS-3-4242.</p>	
261.56	<p>To Cors. No. 2 and 1, Brighter Days lode, Sur. No. 1510 and Fraction lode, this survey, respectively.</p>	
309.61	<p>Intersect the northwest end center monument of the location.</p>	
604.42	<p>To the southeast end center, Fraction lode, this survey.</p>	
619.22	<p>To Cor. No. 4.</p> <p>A granite stone, 15 by 15 in. by 36 in. long, set 20 in. in the ground, in a mound of earth and stone. A cross at the exact point, marked MS-4-4242.</p> <p>Identical with Cor. No. 2, Mountain Top lode, this survey.</p>	
1500.00	<p>Thence S. 36° 49' E. To Cor. No. 5.</p> <p>A granite stone, 8 by 8 in. by 30 in. long, set 20 in. in the ground, in a mound of earth and stone, with a cross at the exact point and marked MS-5-4242.</p>	

Survey No. 4242, cont.,

feet

Identical with Cor. No. 1, Mountain Top lode, this survey.

A 12 in. pinon tree, blazed on north side, scribed M95 BT-4242, bears S. 14° 50' E. 11.90 ft.

Thence S. 67° 30' W.

309.61 Intersect the lode line at the southeast end center monument of the location.

619.22 To Cor. No. 1, the place of beginning.

All corners are identical with the location.

Mountain Top lode

Beginning Cor. No. 1.

A granite stone, previously described, marked MT-1-4242.

Identical with Cor. No. 5, Mountain Side lode, this survey.

The corner of sections 1a, T. 23 N. R. 18 W. G. & S. R. ~~Bix~~ M. bears S. 68° 59' 30" W. 2146.41 feet.

Thence N. 56° 49' W.

1500.00 To Cor. No. 2.

A granite stone, previously described, marked MT-2-4242.

Identical with Cor. No. 4, Mountain Side lode, this survey.

Thence N. 67° 30' E.

264.93 To Cor. No. 5, Fraction lode, this survey, and intersect line I-4, East Side lode, this survey, at N. 54° 38' W.

1121.81 ft. from Cor. No. 4.

309.61 Intersect the lode line at the northwest end center monument of the location.

619.22 To Cor. No. 3.

A granite stone, 6 by 18 in. by 30 in. long, set 20 in. in the ground, in a mound of earth and stone, with a cross at the exact point, and marked MT-3-4242.

A granite boulder in place, 2 by 4 ft. by 2 ft. above ground, marked X-BR-MT-3-4242, bears S. 67° 30' W. 5.90 ft-

10

Survey No. 4242, cont.,

feet

980.40 Thence S. 36° 49' E.
 To Cor. No. 4, East Side lode, this survey.

1500.00 To Cor. No. 4.
 A granite stone, 12 by 15 ins. by 30 in. long, set
 20 ins. in the ground, in a mound of earth and stone, with
 a cross at the exact point and marked MT-4-4242.

309.61 Thence S. 67° 30' W.
 the lode line at
 Intersect the southeast end center monument of the location.

619.22 To Cor. No. 1, the place of beginning.
 All corners are identical with the location.

* * * * *

East Side Lode

Beginning Cor. No. 1.
 A granite stone, 7 by 12^{ins.}, 20 ins above ground, in
 a mound of stone, marked ES-I-4242.

Identical with Cors. No. 1 and 4, Queen lode, Sur.
 No. 1510 and Fraction lode, this survey, respectively.

A granite reef, 4 ft. high, marked X-RR-1-1510,
 bears N. 8° 50' E. 19 ft.

The corner of sections $\frac{12}{12}$, T. 23 N. R. 18 W. 6. & 6.
 R. ~~Block~~ M. bears S. 24° 26' 40" W. 2516.06 ft.

300.00 Thence N. 31° 45' E.
 the lode line at
 Intersect the northwest end center monument of the location,

Identical with the southeast end center of Queen
 lode, Sur. No. 1510.

600.00 To Cor. No. 2.
 A granite stone, 8 by 12 ins by 30 in, long, set
 30 in. in the ground in a mound of earth and stone, with
 a cross for the exact point, marked ES-2-4242 and Q-2-1510.

Identical with Cor. No. 2, Queen lode, Sur. No. 1510.

1500.00 Thence S. 54° 38' E.
 To Cor. No. 3.
 A granite stone, 10 by 12 in, by 30 in, long, set

Survey No. 4242, cont.,

feet	East Side lode, cont.,	feet
	20 in. in the ground, with a mound of earth and stone, a cross marks the exact point, and marked ES-3-4242.	
	The south end of a granite dike, 5 ft. high, marked X-RR-ES-3-4242, bears N. 77° 00' W. 18.80 feet.	
	Thence S 31° 45' W.	
300.00	Intersect the southeast end center monument of the location.	
600.00	To Cor. No. 4	
	A granite stone, 20 by 15 inches, 36 in. long, set 20 in. in the ground, in a mound of earth and stone, with a cross for the exact point and marked ES-4-4242.	
	A granite boulder, 4 by 5 ft. 2 ft. above ground, marked X-BR-ES-4-4242, bears N. 36° 49' W. 5.40 ft.	
	On line 3-4 Mountain Top lode, this survey.	
	Thence N. 54° 38' W.	
1121.81	To Cor. No. 5, Fraction lode, this survey, and intersect line 2-3, Mountain Top lode, this survey, at S. 67° 30' W. 354.29 ft. from Cor. No. 3.	
1500.00	To Cor. No. 1, the place of beginning.	
	All corners are identical with the location.	

	Fraction lode	
	Beginning Cor. No. 1.	
	A granite stone, 15 by 5 in. 18 inches above ground, marked 2-1510 and F-1-4242.	
	Identical with Cor. No. 2, Brighter Days lode, Sur. No. 1510.	
	A granite Boulder, in place, 3 by 4 ft. 3 ft. above ground, marked X-BR-F-1-4242, bears N. 67° 30' E. 21.98 ft.	
	The corner of sections 11 & 12, T. 23 N. R. 18 W. G. & S. R. 1 & 2 M. bears S. 22° 54' W. 1990.23 ft.	
	Thence N. 42° 40' 30" W.	
964.89	To Cor. No. 2, east end center, Mountain Side lode, this survey.	
342.86	A granite stone, 5 by 15 in. by 30 in long, set 20 in. in the ground, in a mound of earth and stone, with a cross at the exact point and marked F-2-4242.	

11
12

Survey, No 4242, cont.,

feet	feet
	Traction lode, cont.,
	A granite boulder, 5 by 6 ft. by 3 ft above ground, marked X-BR-F-2-4242, bears N. 67° 30' E. 7.25 ft. Thence N. 67° 30' E.
25.00	Intersect the lode line at the northwest end center monument of the location.
333.04	To Cor. No. 3. A granite stone, 5 by 12 in. by 30 in. long, set 20 in. in the ground, in a mound of earth and stone, with a cross for the exact point and marked F-3-4242.
	A granite boulder, 5 by 7 ft., 2 ft. above ground, marked X-BR-3-4242 bears S. 67° 30' W. 11 ft.
	On lines 4-I, and 2-3, Queen and Brighter Days lodes, Sur. No. 1510, at S. 58° 15' E. 399.75 (and N. 58° 15' W. 721.25 ft.) from Cor. No. 4 and S. 22° 30' W. 905.59 ft. and S. 22° 30' E. 497.41 ft. from Cors. No. 2 and 3, Brighter Days lode, respectively.
721.25	Thence S. 58° 15' E. To Cor. No. 4. A granite stone, previously described, marked F-4-4242.
	Identical with Cors. No. 1 and I, Queen lode, Sur. No. 1510, and East Side lode, this survey.
	Thence S. 54° 38' E.
378.19	To Cor. No. 5. A granite stone, 10 by 12 in. by 36 in. long, set 20 ins. in the ground, in a mound of earth and stone, with a cross at the exact point and marked F-5-4242.
	On line 4-I, and line 2-3, East Side and Mountain Top lodes, this survey, at N. 54° 38' W. 1121.81 ft. from Cor. No. 4 and N. 67° 30' E. 264.93 ft. from Cor. No. 2, respectively.
	Thence S. 67° 30' W.
264.93	To Cor. No. 2 and 4, Mountain Top and Mountain Side lodes this survey.
279.73	Intersect the lode line at the south east end center monument of the location.

Survey No. 4242, cont.,

feet

574.54

To the northwest end center, Mountain Side lode location.

622.59

this survey.

To Cor. No. I, the place of beginning,

All corners are identical with the location.

The end-center monuments of location of the lodes of this survey are all stone monuments 3 ft. high.

Lode Lines.

The presumed course of the vein of each of the several lode locations embraced in this survey, counted from the respective points of discovery, is as follows:

Hillside lode: N. 38° 49' W. 1060 ft. and S. 38° 49' E. 440 ft. from the discovery cut.

Tunnel lode: N. 38° 49' W. 760 ft. and S. 38° 49' E. 740 ft. from the discovery cut.

First of July: N. 38° 49' W. 1250 ft. and S. 38° 49' E. 250 ft. from the discovery cut.

Compressor: N. 36° 20' W. 65 ft. and S. 36° 20' E. 1435 ft. from the discovery cut.

Mountain Side: N. 36° 49' W. 220 ft. and S. 36° 49' E. 1280 ft. from the discovery cut.

Mountain Top: N. 36° 49' W. 70 ft. and S. 36° 49' E. 1430 ft. from the discovery cut.

East Side: N. 54° 38' W. 90 ft. and S. 54° 38' E. 1410 ft. from the discovery cut.

Fraction: N. 58° 15' W. 891.29 ft. and S. 58° 15' E. 225 ft. from the discovery cut.

Areas

Hillside lode: ----- Acres 20.661

Tunnel lode ----- 20.323

First of July lode ----- 20.642

Area in conflict with Brighter Days lode, Sur. No. 1510 4.490

~~Not Area, First of July ----- 16.457~~

Compressor lode ----- 20.661

Mountain Side lode ----- 20.483

Mountain Top lode ----- 20.661

Survey No. 4242, cont.,

Areas, cont.,

	Acres
East Side lode -----	20.620
Area in conflict with Mountain Top lode, this survey -----	3.863
Net Area, East Side lode -----	16.757
Fraction lode -----	10.131
Area in conflict with Brighter Days lode Sur. No. 1510 -----	3.462
Net Area, Fraction lode -----	6.669

Location

This survey is located in Sections I-6 and 7, T₃ 23 N., R_s 17 & 18 W. G. & S. R. ~~Box~~ M. in the Wallapai Mining District, East of the Town of Chloride.

All claims are identical with the location.

Expenditure of Five Hundred Dollars

I certify that the value of the labor and improvements made upon or for the benefit of each of the locations embraced in said mining claims by the claimants or their grantors is not less than five hundred dollars, and that said improvements consist of:-

Hillside lode:

No. 1, The discovery cut, on the lode line at 440 ft. from the southeast end center, 4 ft. wide, 10 ft. high, extending N. 40° W. 15 ft. to mouth. Value ----- \$40.00

No. 2, The portal of a cross cut tunnel, which bears N. 15° 30' W. 570 ft. from Cor. No. 2, 5 ft. wide, 7 ft. high, running N. 72° 25' E. 1309 ft., valued at \$26180.00
I/II value to this claim ----- \$2380.00

Tunnel lode:

No. 1, the face of the discovery cut, on the lode line at 740 ft. from the southeast end center, 5 ft. wide, 10 ft. high, extending West 15 ft. Value ----- \$40.00

I/II interest in Improvement No. 2, Hillside lode this survey.----- \$2380

Survey No. 4242, cont.,

Improvements, cont.,

First of July lode:

No. 1, the face of the discovery cut, on the lode line at 250 ft. from the southeast end center, 5 ft. wide, 10 ft. high, extending South 15 ft. Value ----- \$40.00

No. 2, the southwest corner of a shaft, at N. 10° 40' W. 527 ft. from Cbr. No. 1. thence N. 40° W. 8 ft., 6 ft. wide, 12 ft. deep. Value ----- \$75.00

No. 3, The southeast corner of a shaft, bears N. 42° 50' E. 410 ft. from Cor. No. 1, runs N. 40° W. 4 ft. 4 ft. wide, 200 ft. deep. Value ----- \$6000.00

No. 4, the portal of a cross-cut tunnel, bears N. 27° W. 230 ft. from Cor. No. 1, 4 ft. wide, 7 ft. high, runs to bottom of shaft, improvement No. 3, 390 Ft., thence N. 40° W. a drift, 4 by 7 ft. runs 300 ft. Value ----- \$13800.

I/II interest in improvement No. 2, Hillside lode/---\$2380.00
this survey.

Compressor lode:

No. 1, the face of the discovery cut, on the lode line at 65 ft. from the northwest end center, 4 ft. wide, 10 ft. high, extending West 15 ft. Value ----- \$40.00

I/II interest in improvement No. 2, Hillside lode/---\$2380.00
this survey.

Mountain Side lode:

No. 1, The face of a cut, on the lode line at 220 ft. from the northwest end center, 5 ft. wide, 10 ft. high, extending S. 53° W. 15 ft. Value ----- \$40.00

I/II interest in improvement No. 2, Hillside lode/---\$2380.00
this survey.

Mountain Top lode:

No. 1, the face of the discovery cut, on the lode line at 70 ft. from the northwest end center, 5 ft. wide, 10 ft. high, extending N. 30° E. 15 ft. Value --- \$40.00

I/II interest in improvement No. 2 Hillside lode/---\$2380.00
this survey.

East Side lode:

No. 1, the face of the discovery cut, on the lode line at 90 ft. from the northwest end center, 4 ft. wide, 10 ft. high, extending East 15 ft. Value ----- \$40.00

I/II interest in Imp. No. 2 Hillside lode/---\$2380.00
this survey.

Survey No. 4242, cont.,

Improvements, cont.,

Fraction lode:-

No. 1, the face of the discovery cut, on the lode line at 225 ft. from the southeast end center, 5 ft. wide 10 high, extending S. 70° W. 15 ft. Value ----- \$40.00

1/11 interest in improvement No. 2 Hillside lode/ - \$2380.00

Improvement No. 2, Hillside lode, is a cross cut tunnel 1309 ft. long. This tunnel will cut the veins of the group at five hundred feet below any existing workings and it is the intention of the claimants to continue until all veins are intersected. The eight claims of this survey and the Brighter Days and Queen lodes, Sur. No. 1510 and the Samoan, Sur. No. 1493, are held and worked as one group, making the tunnel a common improvement to/11 claims, its value of \$26180.00 makes each 1/11 interest \$2380.00

Other Corner descriptions

The corners of the Brighter Days and Queen lodes, Sur. No. 1510 and of the Samoan lode, Sur. No. 1493, are granite stones, properly set and marked, Cor.No.2 of the Queen lode was reset by me in the original md. of stone. Courses and distances of the claim lines check as approved. # The ties to section corner

I |, T. 23 N. R. 18 W. does not check with the record of the ties from the three above claims. The present/ corner is a 2 1/2 inch iron pipe, properly set and marked. The closing Cor. of secs. 6 & 12, T. 23 N. R. 17 W. bears S. 1° 24' W. 189.2 ft. from the Cor. of Secs. 1 & 12, T. 23 N., R. 18 W., instead of S. 1° 32' W. 189.42 ft. as of record. The 1/4 corner between sections 6 and 12 could not be found, after diligent search therefor.

The difference between this survey and the location notices is due to error in the latter.

The relation between the Brighter Days and Queen lodes, of Sur. 1510, as shown by me are from actual ties and any difference with the record of Sur. 1510 is due to error in the latter.

Mineral Surveyor, C. L. O.

#Cor. No.3 of the Samoan lode was reestablished by me in accordance with the record course and distance from Cor.No.4. This corner is in a steep canyon and the original corner is covered with brush and debris.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by L. H. Foster

Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of _____

Brighter Days Mining Corporation

known as the First of July, Compressor, East Side, Tunnel, Fraction, Mountain Side, Mountain Top and Hillside lodes.

and showing the respective capacities in which they acted.

- Matt O. Hanhila , *Chainman.*
- XXXXXXXXXXXXXXXXXXXX , *Chainman.*
- XXXXXXXXXXXXXXXXXXXX , *Azman.*
- XXXXXXXXXXXXXXXXXXXX , *Flagman.*

FINAL OATHS OF ASSISTANTS

~~WX~~ I, Matt O. Hanhila _____

and XXXXXXXXXXXXXXXXXXXX _____, do solemnly swear that ~~we~~^I assisted _____

L. H. Foster _____, United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Brighter Days Mining Corporation

known as the First of July, Compressor, East Side, Tunnel, Fraction, Mountain Side, Mountain Top and Hillside

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at Phoenix, Arizona

- Matt O. Hanhila , *Chainman.*
- XXXXXXXXXXXXXXXXXXXX , *Chainman.*
- XXXXXXXXXXXXXXXXXXXX , *Azman.*
- XXXXXXXXXXXXXXXXXXXX , *Flagman.*

Subscribed and sworn to by the above-named persons before me this 17th

day of October _____, 1940

My Commission Expires Nov. 20, 1943

Mary E. Aron
Notary Public

FINAL OATH OF U. S. MINERAL SURVEYOR

I, L. H. Foster, U. S. Mineral Surveyor,
do solemnly swear that, in pursuance of instructions received from the Office Cadastral
Engineer, at Phoenix, Arizona, dated July 8, 1940,
I have, in strict conformity to the laws of the United States, the official regulations
and instructions thereunder, and the instructions of said Office Cadastral Engineer,
faithfully and correctly executed the survey of the mining claim of
Brighter Days Mining Corporation, known as the
First of July, Compressor, East Side, Tunnel, Fraction, Mountain Side,
Mountain Top & Hillside lodes
situate in Wallapai Mining District,
Mohave County, Arizona, in Section
I-6-7, Township No. 23 North, Range No. 17 & 18 West
and designated as Survey No. 4242, as represented
in the foregoing field notes, which accurately show the boundaries of said mining claim
as distinctly marked by monuments on the ground, and described in the attached copy of
the location certificate, which was received by me from the Office Cadastral Engineer
with said instructions, and that all corners of said survey have been established and
perpetuated in strict accordance with the law, official regulations and instructions
thereunder; and I do further solemnly swear that the foregoing are the true and original
field notes of said survey and my report therein, and that the labor expended and im-
provements made upon said mining claim by claimant or its
grantors are as therein fully stated, and that the character, extent, location, and
itemized value thereof are specified therein with particularity and full detail, and
that no portion of said labor or improvements so credited to this claim has been in-
cluded in the estimate of expenditures upon any other claim.

L. H. Foster
(U. S. Mineral Surveyor)

Subscribed and sworn to by the said L. H. Foster
U. S. Mineral Surveyor, before me Mary C. Cannon
Mary C. Cannon this 16
Oct day of Oct, 1940

My Commission Expires Nov. 20, 1943

Mary C. Cannon
Mary C. Cannon

OFFICE CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

United States
Department of the Interior
GENERAL LAND OFFICE
PUBLIC SURVEY OFFICE

Phoenix, Arizona,

December 19, 1940

I, Office Cadastral Engineer at Phoenix, Arizona,

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of

Brighter Days Mining Corporation

known as the FIRST OF JULY, COMPRESSOR, EAST SIDE, TUNNEL, FRACTION, MOUNTAIN SIDE, MOUNTAIN TOP, and HILLSIDE lodes

Wallapai

Mining District Mohave County Arizona

in Sections 1, 6, 7, Township No. 23 North, Range No. 17 & 18 West, and

designated as Survey No. 4242, has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant or its grantors, and that said improvements consist of 2 shafts, 8 cuts, and 2 crosscut tunnels, total value \$22,575, \$7140 of which is credited to claims other than those in this survey,

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the District Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

Sherman C. Fiske

Office Cadastral Engineer.

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

UNITED STATES DEPARTMENT OF THE INTERIOR GENERAL LAND OFFICE PUBLIC SURVEY OFFICE

At Phoenix, Arizona

December 19, 1940

I, Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the Mining Claim of

Brighter Days Mining Corporation

known as the FIRST OF JULY, COMPRESSOR, EAST SIDE, TUNNEL, FRACTION, MOUNTAIN SIDE, MOUNTAIN TOP, and HILLSIDE lodes

situate in Wallapai mining district,

Mohave County, Arizona

in Sections 1, 6, 7, Township No. 23 North, Range No. 17 & 18 West

designated as Survey No. 4242

executed by L. H. Foster, Mineral

Surveyor, July 16 - October 1, 1940, under my instructions dated

July 8, 1940, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

Sherman C. Fiske Office Cadastral Engineer.

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S. 4242
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The First of July, Compressor, East Side, Tunnel, Fraction, Mountain Side, Mountain Top and HILLTOP, lodes, Mineral Survey No. 4242, located in sections 1, 6 and 7, Township and 23 North, Ranges 17 and 18 West, Gila and Salt River Meridian, Arizona, are hereby canceled.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"First of July, Compressor, East Side, Tunnel, Fraction, Mountain Side, Mountain Top and HILLSIDE lodes, M.S. 4242 were canceled June 27, 2012, by memo 9605 (956) M.S. 4242, which is now a part of the original field notes."

June 27, 2012
Date



Chief Cadastral Surveyor of Arizona