

7/10/45  
8/22/45

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

MINERAL SURVEY NO. 4284

ARIZONA Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

DOVER COPPER MINING COMPANY

Known As The

Anita No. 13, Anita No.15, Anita No. 16, Anita No. 17, Anita No.18

Anita No. 32 and Victory Fraction lodes, Copper Mountain Mining District,

Greenlee County, Arizona.

Section 12, Township 4 S., Range 28 E.

Surveyed under instructions dated April 17, 1944

by J.WILLIAM WAARA  
Mineral Surveyor.

Anita Nos.13,15,16,17,18, Anita No.32,  
Claims located Sept. 8, 1925; July 20, 1929, 19  
Victory Fraction, April 8, 1943  
Survey commenced April 17, 1944, 19  
Survey completed May 30 1944, 19

Address of claimant Gibbs and Gibbs Attys.  
Homebuilders Bldg, Phoenix Ariz.

DATES OF AMENDED LOCATIONS

Anita No.32,  
March 10, 1944

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

MINERAL SURVEY NO. 4884

ARIZONA

FIELD NOTES

of the Survey of the Mineral Lands of

the Territory of Arizona

Known as the

Anticline No. 15, Anticline No. 16, Anticline No. 17, Anticline No. 18

Anticline No. 19, Anticline No. 20, Anticline No. 21, Anticline No. 22

County

Anticline No. 23, Anticline No. 24, Anticline No. 25, Anticline No. 26

Anticline No. 27, Anticline No. 28, Anticline No. 29, Anticline No. 30

by J. W. ...  
Mineral Surveyor

Anticline No. 31, Anticline No. 32, Anticline No. 33, Anticline No. 34

Anticline No. 35, Anticline No. 36, Anticline No. 37, Anticline No. 38

Anticline No. 39, Anticline No. 40, Anticline No. 41, Anticline No. 42

Anticline No. 43, Anticline No. 44, Anticline No. 45, Anticline No. 46

Anticline No. 47, Anticline No. 48, Anticline No. 49, Anticline No. 50

Anticline No. 51, Anticline No. 52, Anticline No. 53, Anticline No. 54

Anticline No. 55, Anticline No. 56, Anticline No. 57, Anticline No. 58

LIST OF MINERAL LOCATIONS

Anticline No. 59, Anticline No. 60, Anticline No. 61, Anticline No. 62

## MINERAL SURVEY NO. 4284

Mineral Survey No. 4284 was made with a Lietz Light mountain transit No. 9503 Model No.9 with a horizontal limb 5 inches in diameter having double opposite verniers and full vertical circle 5 inches in diameter, having double opposite verniers; the horizontal verniers reading to thirty seconds of arc, and the vertical verniers reading to one minute of arc; the eye piece is fitted to receive a prismatic eye piece suitable for making direct observations upon the sun or Polaris. The instrument was in good condition at the time of the survey and all adjustments were in good order. Observations upon Polaris were made <sup>for latitude</sup> ~~at times~~ ~~of day as recorded~~, the details of which observations are shown in the calculations sheets herewith submitted for examination. All azimuths in this record are referred to the true meridian thus determined, by the method of deflection angles and calculated courses.

The lines were measured with a 1/8 inch steel tape 500 feet in length, graduated every foot, which was compared with a steel standard tape at the time of beginning the survey and found correct.

All lines and connections of this survey were run by direct methods. The magnetic variation observed at each corner of the survey gave a uniform value of 13° -50' E.

## ANITA NO. 17 LODE

Beginning at Cor. No.1 of the Anita No. 17 lode;

Identical with Cor. No.1 Anita No. 15 lode of this survey. An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone; marked A 17-1, A 15-1-4284 with its center for exact corner point, whence,

The West 1/4 sec. corner Sec. 12, T. 4 S., R. 28 E., Gila and Salt River Base and Meridian brs.  $S. 89^{\circ} - 32' - 30'' W.$

763.16 feet.

No other bearings available.

		Thence N.9°-08'W.
293.7	Intersect the lode line at the WEST CENTER END,	built a substantial mound of stone.
360.05	Intersect line 1-2 New S P Millsite Sur. No. 4256B,	S.65°W. 1.6 feet from Cor. No. 2.
594.0	COR. NO.2.	An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 17-2- 4284 with its center for exact corner point, whence, A volcanic boulder 3x4x3 feet exposed and chiseled BxR A 17-2-4284 brs. N.4°-33'E. 42,7 feet.
		Thence N. 76°-53'E.
1104.64	Intersect line 3-4 Victoria lode Sur. No. 3145 ,	N.8°-57'W. 649.63 feet from Cor. No. 3, <del>592.32 feet from its inter-</del> <del>section with line 1-4 of this lode.</del>
1500.0	COR. NO. 3.	Identical with Cor. No. 4 Anita No. 18 lode of this survey. This corner fell at a point where it was impossible to set a pipe for corner due to boulders; from this corner I esta- blished a witness corner S.9°-08'E. 1.0 feet. An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked <sup>W C</sup> /A 17-3, A 18-4-4284 with its center for exact corner point, whence, from witness cor. A granite boulder 4x3x3 feet exposed and chiseled BxR A 17-3-4284 brs. N.86°-23'W. 49.2 feet. From true corner point, Cor. No. 3 Victoria lode Sur. No. 3145 brs. S. 21°-13'W. 784.6 feet. Cor. No. 4 Anita No. 32 lode of this survey brs. N.79°- 07'E. 430.8 feet. Thence S.9°-08'E (from true cor. pt.)
1.0	Intersect witness corner to Cor. No.3 of this lode identical	witness with/Cor. No. 4 Anita No. 18 lode of this survey.
190.0	Cross Dover Millsite road, brs. southwest to northeast.	
276.6	Cross gulch, flows southwesterly.	
Intersect the lode line at the 300.7	EAST CENTER END,	built a substantial mound of stone.
342.22	Intersect line 2-3 Victoria lode Sur. No. 3145,	N.40°-41'E.

	518.98 feet from Cor. No. 3 <del>and 422.02 feet from its intersection with line 1-4 of this lode, identical with line 1-2 Anita No. 15 lode, both of this survey.</del>
591.6	COR. NO. 4  Identical with Cor. No. 3 Anita No. 18 lode, Cor. No. 3 Anita No. 16 lode, Cor. No. 2 Anita No. 15 lode all of this survey.  An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone; marked A 17-4, A 18-3, A 16-3, A 15-2-4284 with its center for exact corner point, whence,  Cor. No. 3 Victoria lode Sur. No. 3145 brs. S. 68 -42'W. 405.6 feet.  No other bearings available.  Thence S.76 -48'W.
323.23	Intersect line 2-3 Victoria lode Sur. No. 3145, N.40-41'E. 96.96 feet from Cor. No. 3.
397.31	Intersect line 3-4 Victoria lode Sur. No. 3145, N.8 -57'W. 57.31 feet from Cor. No. 3.
570.0	Cross Dover Millsite road, brs. southwest to northeast.
1050.0	Cross gulch, flows southwesterly. <i>Sur. No. 4256 B<sub>2</sub></i>
1499.3	Intersect line 2-3 New S P Millsite, <i>Sur. No. 4256 B<sub>1</sub></i> S.9 -00'E. 360.4 feet from Cor. No. 2.
1500.0	TO COR. NO. 1 and the place of beginning.  ANITA NO. 15 LODE  Beginning at Cor. No. 1 of the Anita No. 15 lode;  Identical with Cor. No. 1 of the Anita No. 17 lode, of this survey, previously described.  Thence N.76 -48'E. <i>Sur. No. 4256 B<sub>1</sub></i>
0,70	Intersect line 2-3 New S P Millsite, <i>Sur. No. 4256 B<sub>1</sub></i> N.9 -00'W. 299.6 feet from Cor. No. 3.
450.0	Cross gulch, flows southwesterly.
930.0	Cross Dover millsite road, brs southwest to northeast.
1102.69	Intersect line 3-4 Victoria lode Sur. No. 3145, N.8 -57'W. 57.31 feet from Cor. No. 3.
1176.77	Intersect line 2-3 Victoria lode Sur. No. 3145, N.40 -41'E.

	96.96 feet from Cor. No.3.
1500.0	COR. NO. 2 Identical with Cor. No. 4 Anita No.17 lode, Cor. No.3 Anita No. 18 lode, Cor. No. 3 Anita No. 16 lode, all of this survey and previously described. Thence S. 9°-08'E.
	Intersect the lode line at the
300.7/	EAST CENTER END, built a substantial mound of stone.
591.5	Intersect Cor. No. 2 Anita No. 16 lode of this survey.
601.4	COR. NO. 3 Identical with Cor. No. 2 Anita No. 13 lode of this survey. An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 15-3, A 13 -2-4284 with its center for exact corner point, whence, <del>Cor. No. 2 Marget No. 19 lode Sur. No. 4256A brs. S. 31-07°-50'W. 578.5 feet.</del> No other bearings available. Thence S. 76°-49'W.
1500.0	COR. NO. 4 Identical with Cor. No.1 Anita No. 13 lode of this survey. An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 15-4 A 13-I-4284 with its center for exact corner point, whence, No bearings available. Thence N. 9°-08'W.
	Intersect the lode line at the
300.7/	WEST CENTER END, built a substantial mound of stone.
301.85	Intersect Cor. No. 3 New S P Millsite Sur. No. 4256B.
418.0	Cross Dover Millsite road, brs southwest to northeast.
572.0	Cross gulch, flows southwesterly.
601.4	TO COR, NO.1 and the place of beginning. ANITA NO. 13 LODE. Beginning at Cor. No. 1 of the Anita No. 13 lode; Identical with Cor. No. 4 Anita No. 15 lode of this survey, previously described, whence, T. 4S, R. 28 E, The West 1/4 sec. corner Sec. 12, brs. N. 55°-36'-45" W. 1040.5 feet.

Thence N.76°-48'E.

1500.0 COR. NO. 2.

Identical with Cor. No. 3 Anita No. 15 lode of this survey, previously described.

Thence S.9°-08'E.

Intersect the lode line at the  
300.7/ EAST CENTER END, built a substantial mound of stone.

601.4 COR. NO. 3.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 13-3-4284 with its center for exact corner point, whence,  
**Cor. No.2 Margot No.19 lode Sur. No. 4256A brs.S.21°-07'-30"W. 578.5 feet.**  
No other bearings available.

Thence S. 76°-48'W.

1500.0 COR. NO. 4

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 13-4-4284 with its center for exact corner point, whence,  
**No bearings available.**

Intersect the lode line at the  
300.7 WEST CENTER END, built a substantial mound of stone.  
601.4 TO COR. NO.1, and the place of beginning.

ANITA NO. 32 LODE

Beginning at Cor. No. 1 of the Anita No. 32 lode;

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 32-1-4284 with its center for exact corner point, whence,  
T.4 S., R.28 E.,  
The North 1/4 sec corner Sec. 12, brs. N. 7°-29'-30"E.  
1203.5 feet.

Cor. No. 3 Dominion lode Sur. No. 3145 brs. N.76°-50'E.  
315.44feet.

Cor. No. 2 Victoria lode Sur. No. 3145 brs. S.72°-05'-30"E. 352.02 feet.

A granite boulder 4x3x3 feet exposed and chiseled BxR A 32-1-4284 brs. S.80°-52'W. 5.6 feet.

Thence N.76°-02'E.

- 110.0 Cross gulch, flows southwesterly.
- 205.0 Cross Dover Millsite road, brs southwest to northeast.
- 315.80 Intersect line 1-2 Victoria lode Sur. No. 3145, identical with line 3-4 Dominion lode Sur. No. 3145, N.8°-47'W. 186.64 feet from Cor. No.2 and 4.42 feet from Cor. No.3, respectively.
- 447.0 Cross Dover Mine Road, brs north to south.
- 1449.4 COR. NO. 2  
An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 32-2-4284 with its center for exact corner point, whence,  
A limestone reef 20x4x2 feet exposed and chiseled BxR A 32-2-4284 brs. N.7°-17'W. 4.70 feet.  
Thence S.9°-00'E.
- 141.6/ Intersect the lode line at the EAST CENTER END, built a substantial mound of stone.
- 282.2 Intersect Cor. No. 4 Victor lode Sur. No. 3345, identical with Cor. No. 4 Victory Fraction lode of this survey.
- 303.57 Intersect line 2-3 Dominion lode Sur. No. 3145, S.88°-52'-30"E. 1147.18 feet from Cor. No. 3, and 32.81 feet from its intersection with line 3-4 Victor lode Sur. No. 3345.
- 441.6 COR. NO. 3  
Identical with Cor. No. 3 Victory Fraction lode of this survey.  
An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 32-3, V F-3-4284 with its center for exact corner point, whence,  
Cor. No. 1 Anita No. 18 lode of this survey brs. S.79°-27'-30"W. 383.43 feet.  
No bearings available.  
Thence S. 76°-19'-30"W.
- 384.55 Intersect line 1-2 Anita No. 18 lode of this survey, S.9°-08'E. 21.02 feet from Cor. No.1 (and 5.53 feet from its intersection with line 3-4 Victor lode Sur. No. 3345.



- 398.41 Intersect line 3-4 Victor lode Sur. No. 3345, S.55°-12'-30"W. 440.97 feet from Cor. No.4 ~~and 15.3 feet from its intersection with line 1-2 Anita No. 18 lode of this survey.~~
- 1137.0 Cross Dover Mine Road, brs. north to south.
- 1447.75 COR, NO.4
- This corner fell at a point where it was impracticable to set a pipe corner due to bed rock; from this corner I established a witness corner N.9°-00'W. 1.5 feet.
- An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 32-4-4284 W C with its center for exact corner point, whence, ~~from true corner point,~~
- No bearings available.
- Thence N.9°-00'W. (from true Cor.Pt.) 1.5 Intersect witness corner for Cor. No. 4 of this lode.
- 8.27 Intersect line 2-3 Victoria lode Sur. No. 3145, S.40°-41'W. 411.68 feet from Cor. No.2, ~~(and 21.89 feet from its intersection with line 1-4 Anita No. 18 lode of this survey.)~~
- 21.02 Intersect line 1-4 Anita No. 18 lode of this survey, S.76°-19'-30"W. 1063.2 feet from Cor. No.1 ~~and 16.68 feet from its intersection with line 2-3 Victoria lode Sur. No. 3145.~~
- 235.0 Cross Dover Millsite road brs. southwest to northeast.
- 292.4/ **Intersect the lode line at the WEST CENTER END,** built a substantial mound of stone.
- 295.0 Cross Gulch, flows southwesterly.
- 434.0 TO COR. No.1 and the place of beginning.

ANITA NO. 18 LODE.

Beginning at Cor. No.1 of the Anita No. 18 lode;

This corner fell at a point where it was impracticable to set a pipe corner or mark a rock in place for a corner due to bed rock; from this corner I established a witness corner S. 9°-08'E. 3.00 feet.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven 18 inches into a crevice on the slope of a granite reef 20 feet high, and surrounded by a

substantial mound of stone; marked W C A 18-1-4284 with its center for exact corner point, whence from witness corner,

A granite reef 20 feet high chiseled BxR A 18-1-4284 on its north face, brs. N.11°-51'W. 8.5 feet.

From true cor. pt.

T. 4 S., R. 28 E.,

The North 1/4 corner Sec. 12, brs. N.34°-53'W. 1645.00 feet.

Cor. No.4 Victor lode Sur. No. 3345 brs. N.57°-07'E. 419.2 feet.

Thence S.9°-08'E.(from true cor. pt.)

3.00 Intersect witness corner for Cor. No.1 of this lode.

15.49 Intersect line 3-4 Victor lode Sur. No. 3345, N.55°-12'-30" E. 1061.53 feet from Cor. No.3, and S.55°-12'-30"W.

425.67 feet from Cor. No.4 of said survey.

21.02 Intersect line 3-4 Anita No. 32 lode of this survey, N.76°-19'-30"E. 1063.20 feet from Cor. No.4, and ~~13.86 feet from~~

~~its intersection with line 3-4 Victor lode Sur. No. 3345.~~

300.7 Intersect the lode line at the EAST CENTER END, built a substantial mound of stone.

521.98 Intersect line 3-4 Anita No. 20 lode Sur. No. 4256A, N.78°-01'-30"E. 664.1 feet from Cor. No. 3, & S.78°-01'-30" W. 826.4 ft. from Cor. No. 4.

591.7 COR. NO. 2.

Identical with Cor. No. 4 Anita No. 16 lode of this survey.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick driven in a crevice of rock in place and surrounded by a substantial mound of stone, marked A 18-2, A 16-4-4284 with its center for exact corner point, whence, No bearings available.

Cor. No. 3 Anita No. 20 lode Sur. No. 4256A brs. S.84°-02'-30"W. 664.3 feet.

Cor. No.3 Victor lode Sur. No. 3345 brs. S.87°-49'W. 964.0 feet.

Cor. No. 2 Victor lode Sur. No. 3345 brs. S. 49°-30'-

30"W. 814.0 feet.

Thence S.76°-19'-30"W.

675.1 Intersect line 2-3 Anita No. 20 lode Sur. No. 4256A, S.3°-01'E. 90.76 feet from Cor. No. 3.

850.0 Cross Dover Mine road brs north to south.

869.71 Intersect line 2-3 Victor lode Sur. No. 3345, S.35°-00'E. 205.88 feet from Cor. No.3.

1495.2 COR. NO. 3

Identical with Cor. No. 3 Anita No. 16 lode, Cor. No. 2 Anita No.15 lode, Cor. No. 4 Anita No. 17 lode all of this survey, previously described.

Thence N.9°-08'W.

249.38 Intersect line 2-3 Victoria lode Sur. No. 3145, N.40°-41'E. 518.98 feet from Cor. No. 3.

Intersect the lode line at the WEST CENTER END, built a substantial mound of stone.

290.9/

315.0 Cross gulch, flows southwesterly.

401.6 Cross Dover Millsite road brs. southwest to northeast. of this lode

590.6 Intersect witness corner to Cor. No.4/, identical with witness corner to Cor. No. 3 Anita No.17 lode of this survey.

591.6 COR. NO.4

Identical with Cor. No. 3 Anita No. 17 lode of this survey, previously described.

Thence N. 76°-19'-30"E.

110.0 Cross gulch, flows southerly.

175.0 Cross Dover Millsite road, brs. southwest to northeast.

432.0 Intersect line 4-1 Anita No.32 lode of this survey, N.9°-00'W. 21.02 feet from Cor. No.4 and ~~12.75 feet from its intersection with line 2-3 Victoria lode Sur. No.3145.~~

448.68 Intersect line 2-3 Victoria lode Sur. No. 3145, N.40°-41'E. 1104.43 feet from Cor. No.3 and ~~585.45 feet from its intersection with line 3-4 of this lode,~~ and S.40°-41'W. 389.88 feet from Cor. No. 2.

740.0 Cross Dover mine site road, brs. north to south.

1495.2 TO COR. NO. 1 and the place of beginning.

## ANITA NO. 16 LODE.

Beginning at Cor. No.1 of the Anita No. 16 lode;

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 16-1-

4284 with its center for exact corner point, whence,

The East 1/4 sec. cor. Sec. 12, brs. S.84°-45'E. 1521.0 feet.

Cor. No. 2 Anita No.20 lode, identical with Cor. No.3 Margot No.22 lode, both Sur. No. 4256A brs. S.82°-46'-30"W. 728.4 feet.

Cor. No.3 Margot No. 19 lode, identical with Cor. No. 4 Margot No.18 lode both Sur.No.4256A brs.S.6°-20'W.1280.9 ft. No other bearings available.

Thence S. 76°-19'-30"W.

739.06 Intersect line 2-3 Margot No. 22 lode Sur. No. 4256A, S.30°-06'E. 83.24 feet from Cor. No. 3.

1010.0 Cross Dover Mine road brs. north to south.

1495.2 COR. NO.2 On line 2-3 Anita No.15 lode of this survey, N.9°-08'W. 9.9 feet from Cor. No. 3.

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked A 16-2-4284 with its center for exact corner point, whence,  
No bearings available.

Thence N.9°-08'W.

300.7/ Intersect the lode line at the WEST CENTER END, Built a substantial mound of stone.

591.5 COR. NO. 3

Identical with Cor. No.2 Anita No.15 lode, Cor. No.4 Anita No.17 lode, Cor. No.3 Anita No.18 lode, all of this survey, previously described.

Thence N.76°-19'-30"E.

625.49 Intersect line 2-3 Victor lode Sur. No. 3345, N.35°-00'W. 394.42 feet from Cor. No.2 and 361.55 feet from its intersection with line 2-3 Anita No.20 lode Sur. No. 4256A.

645.2 Cross Dover Mine road, brs north to south.

820.1 Intersect line 2-3 Anita No.20 lode Sur. No. 4256A. N.3° -  
01'W. 516.74 feet from Cor. No.2 and 342.49 feet from its  
intersection with <sup>line</sup> 2-3 Victor lode Sur. No. 3345.

1495.2 COR. NO.4

Identical with Cor. No.2 Anita No.18 lode of this sur-  
vey, previously described.

Thence S. 9° -08'E.

89.3 Intersect line 1-2 Victor lode Sur. No. 3345, N.55 -11'E.  
771.3 feet from Cor. No.2, and S. 55° 11' W. 715.85 ft. from Cor.No.1.

Intersect the lode line at the  
290.8/ EAST CENTER END, built a substantial mound of stone.

531.5 Intersect line 1-2 Anita No. 20 lode, identical with line  
3-4 Margot No.22 lode, both Sur. No. 4256A, N.78° -03' -30"  
E.728.9 feet from Cors No. 2 and 3 respectively.

591.5 TO COR. NO.1 and the place of beginning.

#### VICTORY FRACTION LODGE

Beginning at Cor. No.1 Victory Fraction lode;

An iron pipe 30 inches long fitted with a brass cap  
4x4x1 inch thick, driven 18 inches into the ground and  
surrounded by a substantial mound of stone, marked V F-1-  
4284 with its center for exact corner point, whence,  
The East 1/4 sec. cor Sec. 12, brs. S. 47° -41' E. 1366.4  
feet.

Cor. No.1 Victor lode Sur. No. 3345 brs. N.1° -21' -30"E.  
123.5 feet.

Cor. No.3 Anita No.21 lode Sur. No. 4256A brs. S.78° -  
29'W. 117.13 feet.

No other bearings available.

Thence S.76° -33'W.

Intersect the lode line at the  
139.0/ SOUTH CENTER END, built a substantial mound of stone.

258.9 Intersect witness corner to Cor. No.2 of this lode.

269.0 COR. NO.2.

This corner fell at a point where it was impracticable  
to set a pipe corner due to bed rock; from this corner I  
established a witness corner N.76° -33'E. 10.1 feet.

An iron pipe 30 inches long fitted with a brass cap

4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone marked V F-2-4284 W C, with its center for exact corner point, whence From true Cor. pt.

Cor. No. 3 Anita No. 21 lode Sur. No. 4256A brs. N.75°-03'-30"E. 151.98 feet.

Cor. No. 1 Victor lode Sur. No. 3345 brs. N.54°-53'E. 323.4 feet.

No bearings available.  
Thence N.6°-01'W.

1.92 Intersect line 1-2 Victor lode Sur. No. 3345, S.55°-11'W.

322.48 feet from Cor. No. 1, ~~296.94 feet from its intersection with line 6-1 of this lode~~, 181.23 feet from its intersection with line 3-4 Anita No. 21 lode Sur. No. 4256A, and 15.35 feet from its intersection with line 3-4 Anita No. 20 lode Sur. No. 4256A.

7.91 Intersect line 3-4 Anita No. 20 lode Sur. No. 4256A S.78°-01'-30"W. 470.92 feet from Cor. No. 4, ~~268.12 feet from its intersection with line 6-1 of this survey~~, 150.95 feet from ~~Cor. No. 3~~ and ~~4256A~~, 13.52 feet from its intersection with line 1-2 Victor lode Sur. No. 3345.

523.3 COR. NO. 3

Identical with Cor. No. 3 Anita No. 32 lode of this survey, previously described.

Thence N.9°-00'W.

138.03 Intersect line 2-3 Dominion lode Sur. No. 3145, N.88°-52'-30"W. 354.82 feet from Cor. No. 2, ~~240.33 feet from its intersection with line 6-1 of this lode~~, <sup>and</sup> 239.79 feet from its intersection with line 3-4 Anita No. 21 lode, <sup>Sur. No. 4256A,</sup> 11.6 feet from its intersection with line 4-1 Victor lode Sur. No. 3345.

159.4 COR. NO. 4

On line 2-3 Anita No. 32 lode of this survey.

Identical with Cor. No. 4 Victor lode Sur. No. 3345,

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked V F-4-4284, V 4 3345 with its center for exact corner point, whence,

A reef 6x8x5 feet exposed, chiseled BxR V 4 3345, brs. N.15°-38'W. 18.9 feet. ( no space for additional markings)

Cor. No.2 Dominion lode Sur. No. 3145 brs. S.85°-31'E. 359.2 feet.

Cor. No.4 Anita No. 21 lode Sur. No. 4256A brs. S.84°-38'-30"E. 244.28 feet.

Cor. No.1 Victor lode Sur. No. 3345 brs. S.35°-00'-30"E. 600.1 feet. The intersection of line 4-1 Victor lode with line 2-3 Sur. No. 3145, Dominion lode, is 26.05 ft. from Cor.No.4 Victor lode. Thence N.76°-33'E.

Intersect the lode line at the 107.0 NORTH CENTER END, built a substantial mound of stone. 237.4 COR. NO. 5

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked V F-5-4284 with its center for exact corner point, whence,

A quartzite reef 4x2x2 feet exposed and chiseled BxR V F 5 4284, brs. S.65°-33'W. 4.0 feet.

Thence S. 9°-00'E.

79.0 COR. NO.6

Identical with Cor. No.4 Anita No.21 lode Sur. No. 4256A

An iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, driven 18 inches into the ground and surrounded by a substantial mound of stone, marked V F 6 4284, A 21-4-4256A with its center for exact corner point, whence,

~~The intersection of line 3-4 Anita No.21 lode Sur.No.4256A with lines 2-3 Sur.No.3145 Dominion lode, 4-1 and 1-2 Sur.No.3345 Victor lode, brs. S.1°-32'-30"W. 3.03, 312.67, 549.8 ft respectively.~~

Cor. No.2 Dominion lode Sur. No. 3145 brs. S.87°-22'E. 115.05 feet.

Cor. No. 3 Anita No. 21 lode Sur. No. 4256A brs. S. 1°-32'-30"W. 615.9 feet. The intersection of line 3-4 Anita No.21 lode, Sur.No.4256 A, with lines 2-3, Sur. No. 3145, Dominion lode, 4-1 and 1-2, Sur.No.3345, Victor lode, brs. S. 1° 32' 30" W. 3.03, 312.67, and 549.8 ft., respectively.

Thence S. 9° 24' 30" E.

- 3.08 Intersect line 2-3 Dominion lode Sur. No. 3145, N.88°-52'-30"W. 114.44 feet from Cor. No.2.
- 431.02 Intersect line 4-1 Victor lode Sur. No. 3345, <sup>Cor.1,</sup> N.35°00'30"W. 53.39 ft. from <sup>Cor.1,</sup> S.35°-00'-30"E. 546.71 feet from Cor. No.4, 520.66 feet from its intersection with line 2-3 Dominion lode Sur. No. 3145, 137.56 feet from its intersection with line 3-4 Anita No. 21 lode Sur. No. 4256A,
- 490.13 Intersect line 1-2 Victor lode Sur. No. 3345, S.55°-11'W. 25.54 feet from Cor. No.1.
- 599.56 Intersect line 2-3 Anita No. 21 lode Sur. No. 4256A, N.78°-01'-30"E. 117.17 feet from Cor. No. 3. and line 3-4 Anita No.20 lode Sur.No.4256A,S.78°-01'-30'W. 202.8 ft. from Cor. No.4.
- 600.5 TO COR. NO.1 and the place of beginning.

LODE LINES

The presumed course of the vein of each of the several lode locations embraced in this survey, counted from the respective points of discovery, is as follows;

ANITA NO. 17 lode

S.76°-53'W. 10 feet and N.76°-53'E. 1490 feet.

ANITA NO. 15 lode

S.76°-48'W. 1465 feet and N.76°-48'E. 35 feet.

ANITA NO. 13 lode

S.76°-48'W. 1485 feet and N.76°-48'E. 15 feet.

ANITA NO. 32 lode.

S.76°-02'W. 400 feet and N.76°-02'E. 1049.4 feet.

ANITA NO.18 lode.

S.76°-19'-30"W. 460 feet and N.76°-19'-30"E. 1035.2 feet.

ANITA NO. 16 lode.

S.76°-19'-30"W. 24 feet and N.76°-19'-30"E. 1471.2 feet.

VICTORY FRACTION lode.

S.8°-38'-30"E. 572.2 feet and N.8°-38'-11"W. 105.0 ft.

AREAS

	Acres
/ Anita No. 13 lode, total area	20.657
/ Anita No. 15 lode, total area	20.657
Area in conflict with;	
Sur. No. 3145 Victoria lode	.486
Sur. No. 4256B New S P Millsite	.002



	Acres
Anita No. 16 lode, total area	20.239
Area in conflict with	
Sur. No. 3345, Victor lode	4.380
Sur. No. 4256A, Anita No. 20 lode	8.376
Sur. No. 4256A, Anita No. 20 lode exclusive of its conflict with Sur. No. 3345 Victor lode	4.750
Sur. No. 4256A, Marget No. 22 lode	1.196
Anita No. 17 lode, total area	20.363
Area in conflict with	
Sur. No. 3145, Victoria lode	4.449
Sur. No. 4256B, New S.P. Millsite	.009
Anita No. 18 lode, total area	20.245
Area in conflict with	
Sur. No. 3145 Victoria lode	1.757
Sur. No. 3345, Victor lode	8.242
Sur. No. 4256A Anita No. 20 lode	1.222
Sur. No. 4256A, Anita No. 20 lode exclusive of its conflict with Sur. No. 3345 Victor lode	.000
Anita No. 32 lode, total area	14.507
Area in conflict with	
Sur. No. 3145, Victoria lode	2.208
Sur. No. 3145, Dominion lode	3.994
Sur. No. 3345, Victor lode	0.727
Sur. No. 3345, Victor lode exclusive of its conflict with Sur. No. 3145 Dominion lode	0.719
Anita No. 18 lode of this survey	0.511
Anita No. 18 lode of this survey exclusive of its conflict with Sur. No. 3145 Victoria lode	0.509
Anita No. 18 lode of this survey, exclusive of its conflict with Sur. No. 3345 Victor lode	0.510
Victory Fraction lode, total area	3.886
Area in conflict with	
Sur. No. 3145, Dominion lode	0.281
Sur. No. 3345 Victor lode	2.156
Sur. No. 3345 Victor lode, exclusive of its conflict with Sur. No. 3145 Dominion lode	2.154
Sur. No. 4256A, Anita No. 20 lode	0.027
Sur. No. 4256A Anita No. 20 lode, exclusive of its conflict with Sur. No. 3345 Victor lode	0.026
Sur. No. 4256A Anita No. 21 lode	0.805
Sur. No. 4256A Anita No. 21 lode, exclusive of its conflict with Sur. No. 3145 Dominion lode	0.805
Sur. No. 4256A Anita No. 21 lode, exclusive of its conflict with Sur. No. 3345 Victor lode	0.511

**LOCATION**

*SW 1/4 of the NW 1/4*

This survey is located in lots 1, 2, 3, 4, 5, N.W. 1/4 of the S.E. 1/4, N.E. 1/4 of the S.W. 1/4 and N.W. 1/4 of the S.W. 1/4 Sec. 12, T. 4 S.R. 28 E. of the Gila and Salt River Base— and Meridian, Greenlee County, State of Arizona.

The survey of the various lodes embraced in this survey is identical with the respective amended locations

as marked on the ground.

EXPENDITURE OF FIVE HUNDRED DOLLARS

I hereby certify that the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors is not less than five hundred dollars, and that said improvements consist of;

Anita No. 13 lode

No.1 The discovery shaft of the Anita No. 13 lode, the center of which is on the lode line and bears S.76°-48'W. 15 feet from the East Center End, 4x6x8 feet deep. Value \$80.00

Anita No. 15 lode.

No.1 The discovery shaft of the Anita No. 15 lode, the center of which is on the lode line and bears S.76°-48'W. 35 feet from the East Center End, 4x6x8 feet deep. Value \$80.00

Anita No. 16 lode

No.1 The discovery cut of the Anita No. 16 lode, the center of the face of which is on the lode line and bears N.76°-19'-30"E. 24 feet from the West Center End, a cut 4x14x10 foot face, brs. southeast to its face. Value \$125.00

Anita No. 17 lode

No.1 The discovery cut of the Anita No. 17 lode, the center of the face of which is on the lode line and bears N.76°-53'E. 10.0 feet from the West Center End, cut 4x16x10 foot face, brs. northerly to face. Value \$100.00

No.2 A shaft and tunnels, the center of the shaft brs. S.85°W. 510 feet from Cor. No. 4, shaft 4x6x40 feet deep, tunnel 4x6xft. running northerly 75 feet, also tunnel 4x6 ft. running southerly 35 feet. (inaccessible)

Value shaft \$500.00 tunnels \$1575.00

Anita No. 18 lode

No.1 The discovery cut of the Anita No. 18 lode, the center of the face of which is on the lode line and bears N.76°-19'-30"E. 460 feet from the West Center End, cut 4x25x10 foot face, brs. southerly to face.

Value \$300.00

Anita No. 32 lode

No.1. The discovery cut of the Anita No. 32 lode, the center of the face of which is on the lode line and bears N.76°-02'E. 400 feet from the West Center End, 4x15x10 feet face, brs southeasterly to face. (in road excavation)

Value \$100.00

Victory Fraction lode.

No.1 The discovery cut and shaft, of the Victory Fraction lode, the center of the face of cut is on the lode line and bears S.82-38'E. 105 feet from the North Center End, cut 4x12x8 foot face brs. easterly, shaft 4x6x8 feet deep at face of cut.

Value \$200.00

An interest in a Common Improvement described as follows in Mineral Survey No. 4283, wherein an interest was allotted to the lodes of this survey as mentioned therein, to wit;

(Check on file with 4283)

A privately constructed road, owned by the Dover Copper Mining Company and constantly maintained and repaired by the company, and claimant herein, traverses about 2600 feet across patented mining claims owned by other parties before reaching southerly boundary of the Anita No.1 lode Sur. No. 4283; thence across Sur. No. 4283 as shown in the survey plat, continuing across claims of this survey/ of the company, eventually reaching the operating mine of the company in Horseshoe Canyon, all as shown completely on the common improvement plat describing additional lode claims owned by the Dover Copper Mining Company, sharing in this common improvement.

Value of 9600 foot section of road, original construction costs, together with continuous repairs and yearly maintenance by the Dover Copper Mining Company.

\$17,600.00

Value of one thirty second interest 550.00

This improvement/ constructed for the development, and also maintained for the development of all of the/lodes

of Mineral Survey No. 4283, all of the 7 lodes of this survey, and the Anita No. 6, Anita No. 7, Anita No. 10, Anita No. 11, Anita No. 12, Anita No. 14, Margot No. 20 Fraction, Anita No. 25 Fraction, Margot No. 18 Fraction, Margot No. 19 Fraction, all unsurveyed, which are all the contiguous lode claims owned in common within the range of benefit and accessibility of said road.

The road traverses a rough mountain slope area, midway through this survey and other lode claims as platted, and with necessary laterals affords the only means of access to the lodes and the most practical and economical means of continuing the development of each of the stated lode claims.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each lode of this survey and 25 additional surveyed and unsurveyed lodes subsequent to its location and to the time since common ownership and contiguity have prevailed; therefore an undivided one thirty-second interest in its value and expenditure is hereby credited to each of said lodes of this survey and a like interest apportioned to each of the other stated lodes.

#### OTHER IMPROVEMENTS

None.

#### OTHER CORNER DESCRIPTIONS.

The corners of Sec. 12 T. 4 S. R 28 E. are pipes with caps properly set and marked as called for in the field notes of the Official Survey thereof.

Sur. No. 3145.

All corners of the Victoria and Dominion lodes of this survey are pine posts firmly set and properly marked.

Line 3-4 Victoria lode was found to be N.8°-57'W instead of N.8°-47'W. Line 2-3 Victoria lode was found to be S.40°-41'W. 1494.31 feet instead of N.40°-37'E. 1493.7 feet. Line from Cor. No. 2 Victoria lode to Cor. No. 3 Dominion lode

was found to be N.8°-47'W. 182.22 feet instead of N.8°-47' W. 181.2 feet. Line 2-3 Dominion lode was found to be N.88°-52'-30"W. 1502.0 feet instead of N.88°-53'W. 1500.0 feet as of record. Sur. No. 3345

All corners of the Victor lode of this survey are pine posts firmly set and properly marked. I replaced Cor. No. 4 of this lode with an iron pipe as described for Cor. No. 4 Victory Fraction lode of this survey with which corner is identical.

Line 2-3 Victor lode was found to be N.35°-00'-00"W. 600.3 feet instead of N.34°-56'W. 600.0 ft. Line 3-4

was found to be N.55°-12'-30"E. 1487.2 feet instead of N.55°-14'E. 1495.9 feet. Line 4-1 was found to be S.35°-00'-30"E, 600.1 feet instead of S.34°-56'E. 600.0 feet.

Line 1-2 was found to be S.55°-11'W. 1487.15 feet instead of S.55°-14'W. 1495.9 feet.

Sur. No. 4256A

Line 3-4 Anita No. 21 lode was found to be S.1°-32'-30"W 615.9 feet instead of S. 1°-31'W. 615.7 feet. Line 3-4

Anita No. 20 lode was found to be N.78°-01'-30"E. 1490.5 feet instead of N.77°-56'E. 1500.0 feet. Line from Cor. No. 3 Anita No. 21 lode to Cor. No. 4 Anita No. 20 lode was

found to be N.78°-01'-30"E. 319.97 feet instead of N.77°-56'E. 320.68 feet. Line 1-2 Anita No. 20 lode identical with line

3-4 Margot No. 22 lode was found to be N.78°-03'-30"E. instead of N.77°-56'E. ~~1500.0 feet~~ Line 2-3 Margot No. 22

lode was found to be N. 3°-06'W. 604.8 feet instead of N.3°-01'W. 607.5 feet. The ties from Cor. No. 3 Anita No.13 lode

and Cor. No. 1 Anita No. 16 lode to corners No.2 and 3 respectively of the Margot No. 19 lode, indicate serious displacement of said line 2-3 from its record position. The course

of said line was found to be N.81°-07'E. 1440.6 feet instead of N.77°-56'E. 1500.0 feet. This ~~was~~ <sup>course was</sup> determined independently

of the ties heretofore mentioned, however making a proper closure.

~~The above disclosure of line 2-3 Magnet No. 19 lode, together with other similar known displacements of lines of said survey, warrant an investigation as to the necessity of an amended survey of Sur. No. 4256A, before additional official surveys, conflicting therewith, would complicate the condition to a greater extent.~~

**THIS SURVEY.**

The corners of this survey may be more particularly described, such as a 3/4 inch black iron pipe 30 inches long fitted with a brass cap 4x4x1 inch thick, which cap was welded onto the upper end of the pipe. The top surface of the cap had the identification "U S MINERAL SURVEY" in raised letters, cast in the moulding of the cap. The sides of the cap were smooth surfaces upon which were stamped the designation of the corner and survey.

**REPORT**

Owing to the distance from the nearest Notary Public and the expense and delay which would be involved for my assistants to appear before one, I took the acknowledgment of my assistants in my capacity as a Mineral Surveyor.

The discrepancies found existing between the claims as marked by the location monuments and as described in the location notices are due to errors in the location notices.

*William Waara*  
Mineral Surveyor G.L.O.

4284

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

FINAL OATHS FOR SURVEYS

LIST OF NAMES

A list of the names of the individuals employed by J. William Waara

Mineral Surveyor, to assist in running, measuring, and marking the lines, corners, and boundaries described in the foregoing field notes of the survey of the mining claim of Dover Copper Mining Company

known as the Anita No. 13, ~~Anita No. 14~~, Anita No. 15, Anita No. 16, Anita No. 17  
Anita No. 18, Anita No. 32 and Victory Fraction lodes

and showing the respective capacities in which they acted.

- Ascencion P. Rios ..... , Chainman.
- Juan Morales ..... , Chainman.
- Alfredo Contreras ..... , Axman.
- ..... , Flagman.

FINAL OATHS OF ASSISTANTS

We, Ascencion P. Rios, Juan Morales,

and Alfredo Contreras ..... , do solemnly swear that we assisted J. William

Waara ..... , United States Mineral Surveyor, in marking the corners and surveying the boundaries of the mining claim of Dover Copper Mining Company

known as the Anita No. 13, ~~Anita No. 14~~, Anita No. 15, Anita No. 16, ~~Anita No. 17~~  
Anita No. 17, Anita No. 18, Anita No. 32, and Victory Fraction  
lodes

represented in the foregoing field notes as having been surveyed by said mineral surveyor and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and correctly executed, and the corner and boundary monuments established according to law and the instructions furnished by the Office Cadastral Engineer, at Phoenix Arizona.

- Ascencion P. Rios ..... , Chainman.
- Juan Morales ..... , Chainman.
- Alfredo Contreras ..... , Axman.
- ..... , Flagman.

Subscribed and sworn to by the above-named persons before me this 29

day of May ..... , 19 44

J. William Waara  
Mineral Surveyor G.L.O.





UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

FINAL OATH OF MINERAL SURVEYOR

I, J. William Waara....., Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the Office Cadastral  
Engineer, at Phoenix Arizona....., dated April 17, 1944.....,  
I have, in strict conformity to the laws of the United States, the official regulations  
and instructions thereunder, and the instructions of said Office Cadastral Engineer,  
faithfully and correctly executed the survey of the mining claim of Dover.....  
Copper Mining Company....., known as the  
Anita No. 13, Anita No. 15, Anita No. 16, Anita No. 17, Anita No. 18,,  
Anita No. 32 and Victory Fraction lodes.  
situate in Copper Mountain..... Mining District,  
Greenlee..... County, Arizona....., in Section  
12....., Township No. 4 S......, Range No. 28 E......  
and designated as Survey No. 4284....., as represented  
in the foregoing field notes, which accurately show the boundaries of said mining claim  
as distinctly marked by monuments on the ground, and described in the attached copy of  
the location certificate, which was received by me from the Office Cadastral Engineer  
with said instructions, and that all corners of said survey have been established and  
perpetuated in strict accordance with the law, official regulations and instructions  
thereunder; and I do further solemnly swear that the foregoing are the true and original  
field notes of said survey and my report therein, and that the labor expended and im-  
provements made upon said mining claim by claimant or its.....  
grantors are as therein fully stated, and that the character, extent, location, and  
itemized value thereof are specified therein with particularity and full detail, and  
that no portion of said labor or improvements so credited to this claim has been included  
in the estimate of expenditures upon any other claim. ....

J. William Waara  
(Mineral Surveyor)

Subscribed and sworn to by the said J. William Waara  
Mineral Surveyor, before me J. E. Hammond, a Notary Public  
this 25th  
day of April, 1945

J. E. Hammond  
My Commission Expires Nov. 22, 1947

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

FINAL OATH OF MINERAL SURVEYOR

I, J. William Davis, Mineral Surveyor,  
do solemnly swear that, in pursuance of instructions received from the Office of the  
Engineer at Butte, Montana, dated April 15, 1911,  
I have, in strict conformity to the laws of the United States, the official regulations  
and instructions thereunder, and the instructions of said Office, laboring faithfully  
and diligently and expending the money of the mining claim of LOVEX  
Copper Mining Company, known as the  
Little No. 10, Little No. 11, Little No. 12, Little No. 13, Little No. 14, Little No. 15,  
Little No. 16 and Little No. 17 mining claims,  
situated in Butte County, Montana, in Section  
12, Township No. 3, Range No. 1,  
and located as Survey No. 4282, as represented  
in the foregoing field notes, which accurately show the location of said mining claim  
as distinctly marked by monuments on the ground, and described in the attached copy of  
the location certificate, which was received by me from the Office of the District Engineer  
with said instructions, and that all corners of said survey have been established and  
correlated in strict accordance with the law, official regulations and instructions  
thereunder; and I do hereby solemnly swear that the foregoing are the true and original  
field notes of said survey and my report thereon, and that the labor expended and im-  
provements made upon said mining claim by claimant or his agent  
thereon are as therein fully stated, and that the character, extent, location, and  
dimensives thereof are specified therein with particularity and full detail, and  
that no portion of said labor or improvements so credited to this claim has been included  
in the estimate of expenditures upon any other claim.

J. William Davis  
Mineral Surveyor  
April 15, 1911  
At Butte, Montana



CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF  
MINING CLAIM

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE  
PUBLIC SURVEY OFFICE

At Phoenix, Arizona

September 25, 1945

I, Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the  
Mining Claim of Dover Copper Mining Company

known as the

Anita No. 13, Anita No. 15, Anita No. 16, Anita No. 17,

Anita No. 18, Anita No. 32 and Victory Fraction lodes

situate in Copper Mountain mining district,

Greenlee County, Arizona

in Section 12, Township No. 4 S., Range No. 28 E.

, designated as Survey No. 4284

executed by J. William Waara, Mineral

Surveyor, April 17 to May 30, 19 44, under my instructions dated

April 17, 19 44, have been critically examined and the necessary

corrections and explanations made, and the said Field Notes and Return, and the Survey they describe,

are hereby approved. The certified copy of the location certificate filed by the applicant for survey is

on file in this office and a true copy of said certified copy of said location certificate is included and

made a part of the transcript of the field notes.

*Office Cadastral Engineer.*

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF  
MINING CLAIM

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE  
Phoenix, Arizona

Know all men by these presents, that I, John C. ... of the County of Greenlee, State of Arizona, do hereby certify that the following is a true and correct copy of the original field notes and survey of the mining claim known as the Victory claim, situated in the Greenlee County, State of Arizona, and that the same were filed for record in the office of the General Land Office, at Phoenix, Arizona, on the 12 day of April, 1911.

The said field notes and survey were made by W. J. ... and were approved by me on the 12 day of April, 1911.

The said mining claim is situated in the Greenlee County, State of Arizona, and is bounded and described as follows:

Section 12, T. 12 N., R. 12 E., S. 12 S., Arizona

Witness my hand and the seal of the General Land Office at Phoenix, Arizona, this 12 day of April, 1911.

Special Agent in Charge

CADASTRAL ENGINEER'S FINAL CERTIFICATE ON FIELD NOTES

United States  
Department of the Interior

GENERAL LAND OFFICE  
PUBLIC SURVEY OFFICE

Phoenix, Arizona

September 25, 1945

I, Office Cadastral Engineer at Phoenix, Arizona

do hereby certify that the foregoing transcript of the Field Notes, return and approval of the survey of the mining claim of Dover Copper Mining Company

known as the Anita No. 13, Anita No. 15, Anita No. 16, Anita No. 17, Anita No. 18, Anita No. 32 and Victory Fraction lodes

situate in Copper Mountain

Mining District Greenlee County Arizona

in Section 12, Township No. 4 S., Range No. 28 E., and

designated as Survey No. 4284, has been correctly copied from the originals on file in

this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.

I further certify that Five Hundred Dollars worth of labor has been expended or improvements made upon, or for the benefit of, each location embraced in said mining claim by claimant or its grantors, and that said improvements consist of

and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.

I further certify that the plat thereof, filed in the District Land Office at Phoenix, Arizona is correct and in conformity with the foregoing Field Notes.

E. A. Thompson  
Office Cadastral Engineer.

United States  
Department of the Interior  
GENERAL LAND OFFICE  
PUBLIC SURVEY OFFICE

Survey No. 10000

September 25, 1915

I, the undersigned, being duly qualified, do hereby certify that the

field notes of the above named survey, as shown to me, are correct and

correctly describe the land therein contained, and that the same

have been correctly surveyed and measured according to the laws of

the United States, and that the same are in accordance with the

instructions of the General Land Office, and that the same are

correctly and lawfully surveyed and measured, and that the same

are in accordance with the laws of the United States, and that the

same are in accordance with the instructions of the General Land

Office, and that the same are in accordance with the laws of the

United States, and that the same are in accordance with the

instructions of the General Land Office, and that the same are

correctly and lawfully surveyed and measured, and that the same

are in accordance with the laws of the United States, and that the

same are in accordance with the instructions of the General Land

Office, and that the same are in accordance with the laws of the

United States, and that the same are in accordance with the

instructions of the General Land Office, and that the same are

correctly and lawfully surveyed and measured, and that the same

are in accordance with the laws of the United States, and that the

same are in accordance with the instructions of the General Land

Office, and that the same are in accordance with the laws of the

United States, and that the same are in accordance with the

instructions of the General Land Office, and that the same are

correctly and lawfully surveyed and measured, and that the same

are in accordance with the laws of the United States, and that the

same are in accordance with the instructions of the General Land

Office, and that the same are in accordance with the laws of the

E. A. Thompson

Surveyor General

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (942)  
BUREAU OF LAND MANAGEMENT M.S. 4284  
ARIZONA STATE OFFICE

---

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Anita No. 13, Anita No. 15, Anita No. 16, Anita No. 17, Anita No. 18, Anita No. 32, and Victory Fraction lodes, Mineral Survey No. 4284, located in Township 4 South, Range 28 East, Gila and Salt River Meridian, Arizona, are hereby canceled. As of this date, this notice of cancellation will become part of the field notes for Mineral Survey No. 4284, page 38.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Anita No. 13, Anita No. 15, Anita No. 16, Anita No. 17, Anita No. 18, Anita No. 32, and Victory Fraction lodes, M.S. 4284 were canceled February 15, 1996, by memo 9605 (942) M.S. 4284 which is now a part of the original field notes."

February 15, 1996  
Date

  
\_\_\_\_\_  
Acting Chief Cadastral Surveyor of Arizona

