
4-683

UNITED STATES 17 PM 1:44 DEPARTMENT OF THE LINTERIOR BUREAU OF LAND MANAGEMENTONA



MINERAL SURVEY NO. 4373

Arizona Land District.
FIELD NOTES
Of The Survey Of The Mining Claim Of
J. P. Halford
Known As The
Midnight Wonder lode Quartz Mountain Mining District,
Quartz Mountain Mining District,
Yavapai County, Arizona
Section 9 , Township $13N$, Range $2N$ Surveyed under order dated $Feb.13th$, 1953
by Richard L. Merritt Mineral Surveyor.
Claim located June 15th, 1929
Survey commenced April 157 , 1953 Survey completed May 15t , 1953
Survey completed May 1953 Address of claimant Prescott, Arizona
Address of Claimant 17000011, 171120170
DATES OF AMENDED LOCATIONS
Feb. 6th 1953
U. S. GOVERNMENT PRINTING OFFICE 16—53972-2



SURVEY NO. 4373

This survey was made with a Berger transit No. 17503, with horizontal limb 5-1/8 ins. in diam., having two double opposite verniers, and full vertical circle 5 ins. diam., having one double vernier; the verniers read to one minute of arc; a prismatic eyepiece with colored glass was attached to the eyepiece of the transit for making direct observations upon the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by a P.M. altitude observation on the sun, the details of which observation are shown in the calculation sheets submitted for examination. Details of meridian altitude observation on the sun for latitude and a F.M. observation on the sun for time are submitted for examination.

The lines were measured with a Lufkin steel tape 500 feet in length, graduated every foot, the first foot being graduated to tenths and hundredths.

All lines and connections of this survey were run by direct methods.

The magnetic variation observed at each corner of this survey gave a uniform value of 14°30'E.

Feet

MIDNIGHT WONDER LODE

At cor. No. 1 of the Midnight Wonder lode.

Set a granite stone $10 \times 12 \times 26$ ins., 16 ins. in the ground, surrounded by a mound of stones, mkd. X MW 1 - 4373; from which

The south 1/4 cor. of sec. 9, T. 13 N., R. 2 W., G. and S. R. B. and M., bears S.7°29'20"E., 618.39 ft. dist.; an iron post, 3/4 ins. diam., 14 ins. above the ground, with brass cap firmly set, marked and witnessed as described in the official record.

Cor. No. 1 Şur. No. 4113 Midnight Wonder lode bears N.57°25'E., 330.39 ft. dist.

Thence S. 57°25'W.

.741.35

Intersect line 2-3 Sur. No. 4113 Stay Cowboy lode at a point from which Cor. No. 2 bears S.6°21'30"W., 178.62 ft. dist.

1085.0

Center of Granite Creek, 50 ft. wide, course North.

1118.61

Cor. No. 2.

Set a granite stone 8 x 12 x 30 ins., 16 ins. in the ground, surrounded by a mound of stones, mkd. X 2 MW - 4373; from which

Cor. No. 2 Sur. No. 4113 Midnight Wonder lode bears S.57°25'W., 51.0 ft. dist.

Cor. No. 4 Sur. No. 4099 Grove.lode bears N.57°36'40"E., 74.49 ft. dist.

A corner of the location bears \$.57°25'W., 381.39 ft. dist.

A granite rock in place, 6 x 6 x 4 ft., above the ground, bears S.20°22'W., 79.88 ft. dist., mkd. X B R 2 MW - 4373.

SURVEY NO. 4373

	Feet	Thence N.89°24'W.	
	55.34	Intersect line 2-3 Sur. No. 4113 Midnight Wonder lode at a point from which Cor. No. 2 bears S.23°47'E., 30.65 ft. dist., and Cor.No. identical with Cor. No. 2 Sur. 4072 Fraction lode brs. N. 23°47' W., 570.35 ft. dist. Center of road, bears S.5°E., and N.5°W., U.S.Highway 89	3
	89.59	Center of road, bears S.5°E., and N.5°W., U.S.Highway 89	
	313.3	Cor. No. 3.	
	Le be	Set a granite stone 12 x 14 x 24 ins., 16 ins. in the ground, surrounded by a mound of stones, mkd. X 3 MW - 4373; from which	
	.00.3	A corner of the location bears 5.2°13'W., 208.83 ft. dist.	
	7101	The southwest cor. of small house bears N.72°14'E., 8.65 ft. dist.	
	# 3 B	The southeast cor. of a house bears N.77°28'W., 14.1 ft. dist.	
		The northeast cor. of same house bears N.25°42'W., 30.3 ft. dist.	
	3,35%	Thence N.2°13'E.	
	156.425	Lode line; discovery point bears N.57°25'E., 1170.0 ft. dist.	
	521.68	Cor. No. 4.	
		Set a granite stone 12 x 12 x 30 ins., 16 ins. in the ground, mkd. X 4 MW - 4373; from which	
	to the second	Cor. No. 3 Sur. No. 4113 Midnight Wonder lode bears N.57°25'E., 6.33 ft. dist., identical with Cor. No. 2 Sur. No. 4072 Fraction lode.	
	noit arvit d	Thence N. 57° 25'E.	
	6.33	Cor. No. 3 Sur. No. 4113 Midnight Wonder lode, identical with Cor. No. 2 Sur. No. 4072 Fraction lode.	
1	52.5	Center of road bears North and South, U.S. Highway 89	
	146.0	Center of Granite Creek, 50 ft. wide, bears North.	
	826.5	Intersect line 2-3 Sur. No. 4113 Stay Cowboy lode at a point from which Cor. No. 3 bears N.6°21'30"E.,-405.34 ft. dist., and Cor. No. 2 bears S. 6°21'30" W., 949.85 ft. dist.	
	1500.C	Cor. No. 5.	
		Set a granite stone 8 x 12 x 24 ins., 16ins. in the ground, mkd. X 5 MW - 4373; from which	
		Cor. No. 4 Sur. No. 4113 Midnight Wonder lode bears N.57°25' E., 6.33 ft. dist.	
	, era dea,	Cor. No. 1 Sur. No. 4072 Fraction lode bears N.57°25'E., 6.73 ft. dist.	
		Cor. No. 4 Sur. No. 4113 Stay Cowboy lode bears N.87°06'40" E., 76.38 ft. dist.	
	Jaio	Thence S.2°13'W.	
	365.255	Lode line; discovery point bears S.57°25'W., 330.0 ft. dist.	
	730.51	Cor. No. 1, and place of beginning.	

No. 1.

No. 2.

No. 3.

No. 4.

No. 5.

No. 6.

No. 7.

SURVEY NO. 4373

-		
	AREAS Total area, Midnight Wonder lode Area in conflict with- Sur. No. 4113 Midnight Wonder lode Sur. No. 4113 Stay Cowboy lode	Acres 19.905 18.320 9.742
	LOCATION This survey is located in the SW 1/4 sec. 9, T. 13 N.,	R. 2 W.
	The survey of the Midnight Wonder lode is wholly within amended location as marked on the ground; Cors. Nos. 1, are identical with corners of the location, mounds of stoft. base by 3 ft. high, which were rebuilt alongside; Cor 2 and 3 differ to the extent previously shown.	n the 4 and 5 ones, 3
	EXPENDITURES	
	The improvements and the value of the labor and improvemente made upon or for the benefit of the lode location embrace said mining claim by the claimant or his grantors are as	ed in
	The discovery shaft of the Midnight Wonder lode, the centwhich being the discovery point, is on the center line from the center of line 5-1; 8 x 7 ft., 6 ft. deep. Value, \$100.	ter of 330 ft.
	A cut, the west end of which bears N.44°40°W., 296 ft. fr No. 1 Midnight Wonder lode; 8 ft. wide, 6 ft. deep, rur N.50°E., 40 ft. to face. Value, \$200.	
	A shaft, the center of which bears S.28°18'W., 509 ft. fr No. 5 Midnight Wonder lode; 4 x 6 ft., 38 ft. deep; fr bottom of this shaft a tunnel 4 x 6 ft., runs S.10°E., 3 face; caved. Value, \$1200.	om the
	A shaft, the center of which bears N.33°14'W., 288 ft. fr No. 1 Midnight Wonder lode; 8 x 8 ft., 6 ft. deep. Value, \$100.	com Cor.
	A shaft, the center of which bears N.20°52'W, from Cor. Midnight Wonder lode; 3 x 5 ft., 15 ft. deep; timbered. Value, \$300.	
	A shaft, the center of which bears N.66°10'W., 330 ft. fr No. 1 Midnight Wonder lode; 3 x 8 ft., 12 ft. deep; cav Value, \$200.	
	A shaft, the center of which bears N.73°30'W., 330 ft. fr No. 1 Midnight Wonder lode; 8 x 8 ft., 6 ft. deep. Value, \$100.	rom Cor.
	OTHER IMPROVEMENTS	

OTHER IMPROVEMENTS

A house, the SW corner of which bears N.72°14'E., 8.65 ft. from Cor. No. 3 Midnight Wonder lode; 8.1 x 8.0 ft. in size; the long side bears North.

A house, the SW corner of which bears N.84°11'E., 505 ft. from Cor. No. 4 Midnight Wonder lode; 37×26.5 ft. in size; the long side bears N.5°W.

5

-678 b

A house, the SE corner of which bears N.1°17'E., 364 ft. from Cor. No. 2 Midnight Wonder lode; 15 x 12.5 ft. in size; the long side bears West.

A shed, the SE corner of which bears S.83°20'W., 442 ft. from Cor. No. 1 Midnight Wonder lode; 18 x 12 ft. in size; the long side bears N.15°W.

A house, the SE corner of which bears S.81°05'W., 470 ft. from Cor. No. 1 Midnight Wonder lode; 31.5 x 23 ft. in size; the long side bears N.25°W.

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

Sur. No. 4113 Stay Cowboy lode; Cors. Nos. 1, 2, 3, and 4 are granite stones, firmly set and properly marked. Line 2-3 was found to be correct as approved.

Sur. No. 4113 Midnight Wonder lode; Cors. Nos. 1, 2, 3, and 4 are granite stones, firmly set and properly marked. All lines were found to be correct as approved.

Sur. No. 4099 Grove lode; Cor. No. 4 is a granite stone, firmly set and properly marked.

FIELD ASSISTANTS

Tidely was a lader of the control of

the state of the s

in the state of the second points of the state of the sta

Name

Capacity

L. J. Graham

Chainman

Dean Harris

Chainman

4-6686 (Sept. 1947)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

I, Richard L. Merritt, Mineral Surveyor,
hereby certify upon honor that in pursuance of an order received from the Office
Cadastral Engineer, at Albuquerque, New Mexico,
dated Feb. 13th 1953, I have faithfully and correctly executed the survey
of the mining claim of J.P. Halford
, known as the Midnight Wonder lode
(lode, placer, or millsite), situate in The South West
quarter Section 9 T. 13N, R. 2W, Giland Salt River Meridian, Arizona, and designated
as Survey No. 4373 (State) , which is represented in the fore-
going field notes as having been executed by me and under my direction, and that said
survey has been made in strict comformity with said order, the Manual of Instructions
for the Survey of the Public Lands of the United States, and in the specific manner
described in the foregoing field notes, and I do further certify that the labor ex-
pended and improvements made upon or for the benefit of the lode
(lode or placer) location— embraced in the said mining claim by claimant— or
are fully stated in my report therein, and that the character, extent, location, and
itemized value thereof are specified therein with particularity and full detail, and
that no portion of, or interest in, said labor and improvements so credited to this
claim has been included in the estimate of expenditures upon any other claim.
Prescott Arizona Richard & Menitt
(Place) (Mineral Surveyor)
May 15' 1953
(Date)

(TACA (AGE))

BONDARN CALLORS

CHARLING NO STRUCKUE

soverene fate atM - Markeyor	
	entheren al lud tomas some cilian educati
Aprile oth foreseasting too mor has gifted a	the same to the same of the sa
	the state of the state of the state of the
(scinition teachy and)	
Setzuginah ban	Terleting.
	Fibed soons good perved so serve high judge
enois unique do Lument out vielvo atserdir	e produce the product of their lines and grades
united States, and to the specific paragraph	and the chart of the part of the
	de eston biolicationes en la formest
	Tritol to good when electricized one bedrag
,	ato salala Dice est el hancole - entra el
The application and act	body to a task uponed by his behold visite, and
	stant bettledge and temens somer beningers
which of hittherwise sections for the	
lateformethe yearseque consideran.	No examples and at network med and evalu-

CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

UNITED STATES DEPARTMENT OF THE INTERIOR

RUBERAKKANDSKOPPICE BUREAU OF LAND MANAGEMENT

RUBERASCOPPICATION DIVISION of Cadastral Engineering

	At Albuquerque, New Mexico
	July 9 , 1953
I,	OfficeCadastral Engineer at Albuquerque, New Mexico
do hereby certify that	he foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of	J. P. Halford
	J
	Midnight Wonder lode
	untain mining district,
	Yavapai County, Arizona
in Section 2	, Township No. 13 North , Range No. 2 West
G&SRM Arizona , d	lesignated as Survey No. 14373
executed by <u>Richard</u>	I. Merritt , Mineral
Surveyor, April 1 t	o May 1, 1953 , under my instructions dated
February 13, 19	53 , have been critically examined and the necessary
corrections and explana	tions made, and the said Field Notes and Return, and the Survey they describe,
are hereby approved.	The certified copy of the location certificate filed by the applicant for survey is
included and made a pa	rt of these field notes.
	Georf Well
	Geo. H. Well, Office Cadastral Engineer.

U. S. COVERNMENT PRINTING OFFICE 16-20618-1

ANY SERVICE OF THE SE

PALL THE CONTROL OF THE RESERVE TO THE PARTY OF THE PROPERTY.