

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 4459

ARIZONA Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

DECKER ENTERPRISES, INC.

Known As The

See reverse side

Hassayampa Mining District,

Yavapai County, Arizona

Section Approx. 12, Township 12 N., Range 2 W. G. & S.R. Mer. (Unsurveyed).

Surveyed under order dated August 4, 1958

by Harvey W. Smith
Mineral Surveyor.

Claim located See reverse side, 19

Survey commenced August 15, 1958

Survey completed December 20, 1958

Address of claimant 4700 North Central Ave., Phoenix, Arizona

DATES OF AMENDED LOCATIONS

See reverse side

NAME OF CLAIM	DATE OF LOCATION	DATE OF RECORD	AMENDED LOC. DATE	AMENDED LOC. RECORD. DATE
STARLIGHT	July 1, 1945	July 16, 1945	June 28, 1952	July 31, 1952
STARLIGHT NO. 1	July 1, 1945	July 16, 1945	June 28, 1952	July 31, 1952
STARLIGHT NO. 2	July 1, 1945	July 16, 1945	June 28, 1952	July 31, 1952
RONALD	July 7, 1952	July 31, 1952	none	
EDWARD	July 7, 1952	July 31, 1952	none	
CHARLES	July 12, 1952	July 31, 1952	none	
NANCIE	July 7, 1952	July 31, 1952	none	
WESTERNER	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
MAN-OF-WAR	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
B. FRANK	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
TOMLINSON	June 28, 1952	July 31, 1952	none	
PATRICIA	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
MARJORIE	June 3, 1936	June 3, 1936	July 12, 1952	July 31, 1952
JOE B. III	June 3, 1936	June 3, 1936	July 12, 1952	July 31, 1952
MAYTIE	July 7, 1952	July 31, 1952	none	
STRANOE	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952

~~Check~~
Feet

This survey was made with a C. L. Berger & Sons transit, No. 15045, with a horizontal limb $6\frac{1}{4}$ ins. diam., having two double opposite verniers, and a full vertical circle 5 ins. diam., having one double vernier; the verniers read to one minute of arc. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in the record were determined by the horizontal-angle-right method referred to the Meridian determined by the following observation:

December 18, 1958, at Cor. No. 2, Joe B. III lode in latitude $34^{\circ} 23' 33''$ N. and longitude $112^{\circ} 25'$ W., I make a series of six altitude observations upon the sun for azimuth at approximately equal time intervals, three each with the telescope in direct and reversed positions, observing opposite limbs of the sun and reading the horizontal angle from Cor. No. 1, Joe B. III Lode about six-hundred feet westerly, counterclockwise to the sun southwest.

Local standard time of observation

105th Meridian time 2:00 P. M.

Declination of sun, Greenwich

Apparent noon on day of observation $23^{\circ} 23' 04''$ S.

Mean observed vertical angle $28^{\circ} 10' 20''$

Mean horizontal angle from reference 89.011

Pt. to sun's center $51^{\circ} 51'$

True bearing of line 1-2, Joe B. III Lode S. $76^{\circ} 04'$ W.

The lines were measured with a Lufkin steel tape, 300 Ft. in length, graduated every foot for 299 feet and the remaining foot graduated to tenths and hundredths; the tape was compared with a standard at the time of beginning the survey, and found correct.

All lines and connections of this survey were run by direct methods.

CHAINS

Feet

The magnetic declination observed at each corner of the survey gave a uniform value of $14^{\circ} 30'$ E.

STRANGER LODE

At cor. No. 1 of the Stranger lode.

Set a galvanized iron post 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. - M S 4459 S I X: from which

U. S. L. M. No. 1 ^{Sur. No. 4459} bears N. $27^{\circ} 34'$ W., 2837.70 ft. dist.

A galvanized iron post, 24 ins. long, $3/4$ ins. diam; set in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M. S. 4459 U S L M I X.

Cor. No. 4, Joe B. III lode, this survey, bears S. $79^{\circ} - 45'$ E., 77.82 ft. dist.

A yellow pine, 12 ins. diam. bears N. $8^{\circ} - 30'$ W., 24.0 ft. dist., mkd. 4459 S. 1 B T.

Thence N. $86^{\circ} 49' 30''$ E.

73.07 Intersect line 4 - 1, Joe B. III lode, this survey.

170.78 Intersect line 3 - 4, Joe B. III lode, this survey.

300.0 Lode line; discovery pt. bears. S. $20^{\circ} 19'$ E., 80.0 ft. dist.

599.9 Cor. No. 2

Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 S 2 X; from which

A yellow pine, 12 ins. diam. bears S. $15^{\circ} 00'$ E., 14.0 Ft. dist., mkd. 4459 S. 2 B T.

Chains Feet	
	<p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence S. $20^{\circ} 19'$ E.</p>
620.0	Unimproved road, bears N. 45° E. & S. 45° W.
640.0	Right bank, Crook Canyon Creek, 15 ft. wide, course S. 15° W.
890.0	Left bank, Crook Canyon Creek, 15 ft. wide, course S. 40° E.
1040.0	Right bank, Crook Canyon Creek, 15 ft. wide, course South.
1144.36	<p>Cor. No. 3</p> <p>Set a galvanized iron post, 24 ins. long $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly set within the iron post mkd. M S 4459 S 3 X; from which</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence S. $86^{\circ} 49' 30''$ W.</p>
280.0	Left bank, Crook Canyon Creek, 20 ft. wide, course South.
299.9	Lode line; discovery pt. bears N. $20^{\circ} 19'$ W., 1364.36 ft. dist.
335.0	Unimproved road, bears S. 15° E. and N. 15° W.
400.0	Unimproved road, bears South and North.
599.90	<p>Cor. No. 4</p> <p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly set within the iron post, mkd. M S 4459 S 4 X; from which</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence N. $20^{\circ} - 19'$ W.</p>
1144.36	Cor. No. 1 and place of beginning.

Chains
Feet.

JOE B. III LODE

At cor. No. 1 of the Joe B. III lode identical with Cor. No. 4 of the Marjorie lode, this survey.

Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 J B III 1 M 4 X; from which

U. S. L. M. No. 1, previously described, bears N. 45° 52' W., 1522.76 ft. dist.

A mound of stone constructed adjacent to the iron post.

Thence N. 76° 04' E.

189.64 Cor. No. 3 of the Tomlinson lode, this survey.

300.0 Lode line; discovery pt. bears S. 11° 26' E., 1458.82 ft. dist.

505.0 Unimproved road, bears S. 5° W. and N. 5° E.

540.0 Right bank, Crook Canyon Creek, 20 ft. wide, course South.

597.80 Cor. No. 2 identical with Cor. No. 3 Marjorie lode, Cor. No. 4, Nancie lode, & Cor. No. 1, Maytie lode, all of this survey.

Set a galvanized iron post, 24 ins. long 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap 2 ins. diam., firmly set within the iron post, mkd. M S 4459 J B III 2 M 3 N 4 M I X; from which

U. S. L. M. No. 1, previously described, bears N. 61° 17' W. 1907.26 ft. dist.

A mound of stone constructed adjacent to the iron post.

Thence S. 11° 26' E.

385.0 Left bank, Crook Canyon Creek, 15 ft. wide, course S. 75° E.

Chains Feet		Chains Feet
410.0	Unimproved road bears, S. 75° E. and N. 75° W.	38.88
1230.0	Right bank, Crook Canyon Creek, 10 ft. wide, course S. 11° E., thence down the Creek.	
1318.82	Leave the Creek, course S. 25° E.	
1498.82	Cor. No. 3, identical with Cor. No. 4 of the Maytie lode, this survey.	
	Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap 2 ins. diam., firmly fastened within the iron post mkd. M S 4459 J B III 3 M 4 X.	
	Thence S. 76° 04' W.	
297.80	Lode line; discovery pt. bears N. 11° 26' W. 40.0 ft. dist.	
501.0	Intersect line 1 - 2, Stranger lode, this survey.	
597.80	Cor. No. 4	
	Set a galvanized iron post, 24 ins. long, 3/4 ins. diam. in a 15 pound concrete and rock base, 16 ins. in the ground with a brass cap 2 ins. diam., firmly set within the iron post, mkd. M S 4459 J B III 4 X; from which	
	A yellow pine, 18 ins. diam., bears S. 83° 00' W., 6.67 ft. dist., mkd. 4459 J B III 4 B T.	
	A mound of stone constructed adjacent to the iron post.	
	Cor. No. 1 Stranger lode, this survey, bears N. 79° 45' W., 77.82 ft. dist.	
	Thence N. 11° 26' W.	
.18.26	Intersect Line 1 - 2 Stranger lode, this survey.	

0000 Feet 1498.82	Cor. No. 1, and place of beginning.
	<p style="text-align: center;">MAYTIE LODE</p>
	<p>At Cor. No. 1 of the Maytie lode, identical with Cor. No. 2 Joe B. III lode, Cor. No. 3, Marjorie lode and Cor. No. 4 Nancie lode, all of this survey, previously described.</p> <p style="text-align: center;">Thence N. 76° 04' E.</p>
300.0	Lode line; discovery pt. bears S. 11° 26' E., 45.0 ft dist.
599.90	<p>Cor. No. 2 identical with Cor. No. 3 of the Nancie lode, this survey.</p> <p>Set a galvanized iron post, 24 ins. long, 3/4 ins. diam. in a 15 pound concrete and rock base, 16 ins. in the ground with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 M 2 N 3 X; from which</p> <p style="text-align: center;">A yellow pine, 12 ins. diam. bears N. 41° 00' W., 20.5 ft. dist., mkd. 4459 M 2 N 3 B T.</p> <p style="text-align: center;">A yellow pine, 12 ins. diam., bears N. 61° E., 10.5 ft. dist., mkd. 4459 M 2 N 3 B T.</p> <p style="text-align: center;">A mound of stone constructed adjacent to the iron post.</p> <p style="text-align: center;">Thence S. 11° 26' E.</p>
1498.82	<p>Cor. No. 3</p> <p>Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground with a brass cap 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 M 3 X.</p> <p style="text-align: center;">A mound of stone constructed adjacent to the iron post.</p> <p style="text-align: center;">Thence S. 76° 04' W.</p>

Chain feet	
299.90	Lode line; discovery pt. bears N. $11^{\circ} 26'$ W., 1453.82 ft. dist.
480.0	Unimproved road, bears S. 40° E. and N. 40° W.
520.0	Left bank, Crook Canyon Creek, 18 ft. wide, course S. 40° E.
599.90	Cor. No. 4, identical with Cor. No. 3, Joe B III lode, this survey, previously described. Thence N. $11^{\circ} 26'$ W.
180.0	Right bank, Crook Canyon Creek, 12 ft. wide, course S. 25° E., thence up the creek.
268.82	Leave the creek, course S. 11° E.
1088.82	Unimproved road bears N. 75° W. and S. 75° E.
1098.82	Right bank, Crook Canyon Creek, 15 ft. wide, course S. 75° E.
1498.82	Cor. No. 1, and place of beginning. B. FRANK LODE At cor. No. 1 of the B. Frank lode. Set a galvanized iron post 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron pipe, mkd. M S 4459 B F 1 X; from which Sur No. 4459, U. S. L. M. No. 1, previously described, bears S. 35° $43' 30''$ W., 212.80 ft. dist. A mound of stone constructed adjacent to the iron post. Thence N. $76^{\circ} - 03'$ E.
300.0	Lode line; discovery pt. bears S. $05^{\circ} 16'$ E. 1200.0 ft. dist.
350.0	Unimproved road, bears S. 15° E. and N. 15° W.
400.0	Right bank, Crook Canyon Creek, 20 ft. wide, course S. 15° E.
599.70	Cor No. 2, identical with Cor. No. 1, of the Tomlinson lode, this

CHAINS
Feet

	<p>survey.</p> <p>Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 B F 2 T I X; from which</p> <p style="text-align: center;">U. S. L. M. No. 1, ^{Sur. No. 4459,} previously described, bears S. 65° 48' 30" W., 774.38 ft. dist.</p> <p>Cor. No. 4 of the Patricia lode, this survey, bears S. 44° 04' E., 650.74 ft. dist.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p style="text-align: center;">Thence S. 05° - 16' E.</p>
300.0	Left bank, Crook Canyon Creek, 25 ft. wide, course, S. 60° E.
340.0	Unimproved road, bears S. 60° E. and N. 60° W.
1446.56	<p>Cor. No. 3 identical with Cor. No. 4 of the Tomlinson lode, this survey.</p> <p>Set a galvanized iron post, 24 Ins. long, 3/4 ins diam. in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 B F 3 T 4 X.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p style="text-align: center;">Thence S. 76° 03' W.</p>
299.70	Lode line; discovery pt. bears N. 05° 16' W., 246.56 ft. dist.
599.70	<p>Cor. No. 4</p> <p>Set a galvanized iron post, 24 ins. long, 3/4 ins. diam. in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post mkd. M S 4459 B F 4 X.</p> <p>A mound of stone constructed adjacent to the iron post.</p>

Chains Feet 1446.56	Thence N. 5° 16' W. Cor. No. 1 and place of beginning
	TOMLINSON LODGE
	At Cor. No. 1 of the Tomlinson lode, identical with Cor. No. 2 of the B. Frank lode, this survey, previously described.
225.0	Thence N. 76° 04' E. Lode line; discovery pt. bears S. 5° 16' E., 160.0 ft dist.
440.19	Cor. No. 3, Man-of-War lode, this survey.
453.13	Cor. No. 2, identical with Cor. No. 1, Marjorie lode, this survey. Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap. 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 T 2 M I X; from which U. S. L. M. No. 1, ^{Sur. No. 4459,} previously described, bears S. 69° 35' 30" W., 1222.93 ft. dist. A mound of stone constructed adjacent to the iron post. Thence S. 5° - 11' E.
58.84	Intersect line 4 - 1, Patricia lode, this survey.
590.61	Intersect line 3 - 4, Patricia lode, this survey.
685.0	Unimproved road, bears S. 55° E. and N. 55° W.
740.0	Left bank, Crook Canyon Creek, 20 ft. wide, course S. 55° E.
1446.89	Cor. No. 3, on line 1 - 2 Joe B. III lode, this survey. Set a galvanized iron pipe, 24 ins. long 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass

Chains
Feet

cap, 2 ins. diam., firmly fastened within the iron pipe, mkd..M S
4459 T 3 X.

A mound of stone constructed adjacent to the iron post.

Thence S. $76^{\circ} 04'$ W.

189.64 Cor. No. 1 of the Joe B. III lode identical with Cor. No. 4 Marjorie
lode both of this survey.

226.05 Lode line; discovery pt. bears N. $5^{\circ} 16'$ W., 1286.56 ft. dist.

451.05 Cor. No. 4 identical with Cor. No. 3, B. Frank lode; this survey
previously described.

Thence N. $5^{\circ} 16'$ W.

1106.56 Unimproved road, bears S. 60° E. and N. 60° W.

1121.56 Right bank Crook Canyon Creek, 25 ft. wide, coarse, S. 60° E.

1446.56 Cor. No. 1 and place of beginning:

MARJORIE LODE

At cor. No. 1 of the Marjorie lode, identical with Cor. No. 2 of
the Tomlinson lode, this survey, previously described.

Thence N. $76^{\circ} 04'$ E.

4.60 Intersect line 4 - 1, Patricia lode, this survey.

300.0 Lode line: discovery pt. bears S. $2^{\circ} - 03'$ W., 1327.75 ft. dist.

590.10 Cor. No. 2 identical with Cor. No. 1 of the Nancie lode and Cor.
No. 4, Edward lode, both of this survey.

Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15
pound concrete and rock base, 16 ins. in the ground, with a brass
cap, 2 ins. diam., firmly fastened within the iron post, mkd., M S
4459 M 2 N 1 E 4 X; from which

U. S. L. M. No. 1, ^{Sur. No. 4459} previously described, bears S. 71°

Station Feet	
	42' W. 1810.66 ft. dist. - 3 - 8 and 9
	Cor. No. 3 Patricia lode, this survey, bears S. 1° 16'
	30" E. 874.63 ft. dist. identical
	A mound of stone constructed adjacent to the iron post.
	Thence S. 1° 46' W.
862.46	Intersect line 3 - 4, Patricia lode, this survey.
1485.65	Cor. No. 3 identical with Cor. No. 4 Nancie lode, Cor. No. 1 Maytie lode and Cor. No. 2 Joe B. III lode, all of this survey, previously described.
	Thence S. 76° 04' W.
37.80	Left bank, Crook Canyon Creek, 20 ft. wide, course South.
92.80	Unimproved road, bears S. 5° W. and N. 5° E.
297.80	Lode line; discovery pt. bears N. 2° 03' E., 160.0 ft. dist.
408.16	Cor. No. 3, Tomlinson lode, this survey.
597.80	Cor. No. 4, identical with Cor. No. 1 of the Joe B. III lode, this Survey, previously described.
	Thence N. 2° 03' E.
795.0	Right bank, Crook Canyon Creek 15 ft wide course S. 55° E.
860.0	Unimproved road, bears S. 55° E. and N. 55° W.
1487.75	Cor. No. 1, and place of beginning.
	NANCIE LODGE
	At cor. No. 1 at the Nancie lode, identical with Cor. 2 of the Marjorie lode and Cor. No. 4 of the Edward lode, both of this survey, previously described.
	Thence N. 76° 04' E.

Chains Feet	
7.00	Intersect line 2 - 3, Patricia lode this survey.
300.00	Lode line; discovery pt. bears S. $1^{\circ} 46'$ W. 730.0 ft. dist.
599.90	Cor. No. 2 identical with Cor. No. 3 of the Edward lode, this survey. Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd M S 4459 N. 2 E 3 X. A mound of stone constructed adjacent to the iron post. Thence S. $1^{\circ} 46'$ W.
1485.65	Cor. No. 3 Identical with Cor. No. 2, Maytie lode, this survey, previously described. Thence S. $76^{\circ} 04'$ W.
299.90	Lode line; discovery pt. bears N. $1^{\circ} 46'$ E., 755.65 ft dist.
599.90	Cor. No. 4 identical with Cor. No. 1, Maytie lode, Cor. No. 2 Joe B III lode and Cor. No. 3, Marjorie lode all of this survey, previously described. Thence N. $1^{\circ} 46'$ E.
623.19	Intersect line 3 - 4, Patricia lode, this survey.
1485.65	Cor. No. 1, and place of beginning. MAN-OF-WAR LODE At Cor. No. 1 of the Man-of-War lode, identical with Cor. No. 4 of the Westerner lode, this survey. Set a galvanized iron post, 24ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 M W 1 W 4 X; from which U. S. L. M. No. 1, / ^{Sur. No. 4459} previously described, bears S. $17^{\circ} 44'$ W.,

Feet	
	1851.38 ft. dist.
	Cor No. 1, Patricia lode, this survey, identical with Cor.
	No. 2 survey No. 2588 Franklin No. 2 lode, bears S. 54°
	11' 30" E., 707.27 ft. dist.
	A mound of stone constructed adjacent to the iron post.
	Thence N. 76° 04' E.
	300.0 Lode line; discovery pt. bears S. 0° 27' 30" W. 600.0 ft. dist.
	596.94 Cor. No. 2, identical with Cor. No. 3 of the Westerner lode, this
	survey.
	Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15
	pound concrete and rock base, 16 ins. in the ground, with a brass
	cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S
	4459 M W 2 W 3 X.
	A mound of stone constructed adjacent to the iron post.
	Thence S. 0° 22' 30" W.
	466.48 Intersect line 1 - 2, Sur. 2588, Franklin No. 2 lode from which
	Cor. No. 2, identical with Cor. No. 1 Patricia lode, this survey,
	bears S. 1° - 45' W., 91.25 ft. dist.
	558.15 Intersect line 1 - 2, Patricia lode, this survey.
	558.17 Intersect line 2 - 3, Sur. 2588, Franklin No. 2 lode, from which
	Cor. No. 2 bears N. 74° 30' W. 2.66 ft. dist.
	662.48 Intersect line 4 - 1, Patricia lode, this survey.
	1000.0 Unimproved road, bears East and West.
	1483.86 Cor. No. 3, on line 1 - 2 Tomlinson lode, this survey.
	Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15
	pound concrete and rock base, 16 ins. in the ground, with a brass cap,

Chains
feet

2 ins. diam., firmly fastened within the iron post, mkd. M S 4459
M W 3 X; from which

A mound of stone constructed adjacent to the iron post.

Thence S. $76^{\circ} 04'$ W.

299.22 Lode line; discovery pt. bears N. $0^{\circ} 27' 30''$ E., 884.42 ft. dist.

440.19 Cor. No. 1, Tomlinson lode identical with Cor. No. 2, B. Frank lode
both of this survey.

599.22 Cor. No. 4

Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15
pound concrete and rock base, 16 ins. in the ground, with a brass
cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S
4459 M W 4 X; from which

A mound of stone constructed adjacent to the iron post.

Thence N. $0^{\circ} 27' 30''$ E.

720.0 Unimproved road bears S. 55° E. and N. 55° W.

1484.42 Cor No. 1, and place of beginning.

WESTERNER LODE

At Cor. No. 1 of the Westerner lode, identical with Cor. No. 4,
Survey 1588, Harrison lode. The old rock corner monument was found
loose down the slope and obviously out of position. The Cor. was
re-established using the Bearing Tree.

Set a galvanized iron post, 24 ins. long., $3/4$ ins. diam., in a 15
pound concrete and rock base, 16 ins. in the ground, with a brass
cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S
4459 M S 15 88 W 1 H 4 X; from which

Chain Feet	
	<p style="text-align: center;">Sur. No. 4459,</p> <p>U. S. L. M. No. 1/ previously described bears S. $10^{\circ} 30'$ W., 2653.57 ft. dist.</p> <p>A yellow pine, 24 ins. diam. bears N. $81^{\circ} 15'$ E., 32.7 ft. to blaze, mkd. 1588 H 4. This tree used to re-establish corner.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p style="text-align: center;">Thence N. $76^{\circ} 04'$ E.</p>
300.0	Lode line; discovery pt. bears S. $5^{\circ} 25' 30''$ E., 570.0 ft. dist.
584.11	<p>Cor. No. 2</p> <p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd M S 4459 W 2 X; from which</p> <p style="text-align: center;">Cor. No. 3, Sur. 1588, Harrison lode bears S. $39^{\circ} 50' 30''$ E., 27.26 ft. dist.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p style="text-align: center;">Thence S. $6^{\circ} 17'$ E.</p>
24.11	Intersect line 3 - 4, Harrison lode, Sur. 1588, from which Cor. No. 3 bears N. $78^{\circ} - 25' 30''$ E., 15.13 ft. dist.
847.75	Cor. No. 3, identical with Cor. No. 2, Man-of-War lode, this survey previously described.
	Thence S. $76^{\circ} 04'$ W.
296.94	Lode line; discovery pt. bears N. $5^{\circ} 25' 30''$ W., 279.50 ft. Dist.
596.94	Cor. No. 4, identical with Cor. No. 1, Man-of-War lode, this

	<p>survey, previously described.</p> <p>Thence N. $5^{\circ} 25' 30''$ W.</p>
849.50	<p>Cor. No. 1, and place of beginning.</p> <p>PATRICIA LODE</p> <p>At Cor. No. 1 of the Patricia lode, identical with Cor. No. 2, Sur. 2588, Franklin No. 2 lode.</p> <p>A granite stone monument, 4 ins. x 8 ins., 6 ins. above ground, mkd. 2588 F2 2, add mks. 4459 P I X; from which</p> <p>U. S. L. M. No. 1, ^{Sur. No. 4459,} previously described, bears S. $40^{\circ} 07' 30''$ W., 1765.02 ft. dist.</p> <p>Cor. No. 1 Man-of-War lode, this survey, bears North $54^{\circ} 11' 30''$ West, 707.27 ft. dist.</p> <p>Cor. No. 3 Sur. 2588, Franklin No. 2 lode, bears S. $74^{\circ} 30'$ E. 600.0 ft. dist.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence S. $74^{\circ} 58' 30''$ E.</p>
2.66	Intersect line 2 - 3, Man-of-war lode, this survey.
265.0	Unimproved road, bears South and North.
300.0	Lode line; discovery pt. bears S. $0^{\circ} 49'$ E., 80.0 ft. dist.
500.0	Witness for Cor. No. 2
	<p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron pipe, mkd. M S 4459 P 2 W C X; from which</p> <p>A mound of stone constructed adjacent to the iron post.</p>
598.80	Intersect line 3 - 4, Sur. 2588, Franklin No. 2 lode, from which Cor. No. 3 bears S. $1^{\circ} 45'$ W., 5.11 ft. dist.

Corner Feet	
600.0	<p>Cor. No. 2</p> <p>Cor. No. 3, Sur. No. 2588, Franklin No. 2 lode, bears S. 15° 23' W., 5.37' ft dist.</p> <p>This corner falls in center of open cut with sides caved.</p> <p>Thence S. 0° 49' E.</p>
538.75	Intersect line 4 - 1, Edward lode, this survey.
623.81	Intersect line 1 - 2, Nancie lode and line 4-3, Edward lode, both of this survey.
1500.0	<p>Cor. No. 3</p> <p>Set a galvanized iron post, 24 ins. long 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron pipe, mkd M S 4459 P 3 X; from which</p> <p>Cor. No. 1, Nancie lode, identical with Cor. No. 2,</p> <p>Marjorie lode, both of this survey, bears N. 1° 16' 30" W., 874.63 ft. dist.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence N. 74° 58' 30" W.</p>
47.69	Intersect line 4 - 1, Nancie lode and line 2-3, Marjorie lode, both of this survey.
300.0	Lode line; discovery pt. bears N. 0° 49' W., 1420.0' ft. dist.
557.91	Intersect line 2 - 3, Tomlinson lode, this survey.
600.0	<p>Cor. No. 4</p> <p>Set a galvanized iron post, 24 ins. long, 3/4 ins. diam, in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 P 4 X; from which</p> <p>Cor. No. 1, Tomlinson lode, identical with Cor. No. 2</p>

Chain Feet	
	B. Frank lode, both of this survey, bears N. $44^{\circ} 04'$ W., 650.74 ft. dist.
	Thence N. $0^{\circ} 49'$ W.
518.73	Intersect line 2 - 3, Tomlinson lode, this survey.
577.49	Intersect line 1 - 2, Marjorie lode, this survey.
1050.0	Unimproved road, bears East and West.
1394.71	Intersect line 2 - 3 Man-of-War lode, this survey.
1500.0	Cor. No. 1 and place of beginning.
	EDWARD LODE
	At Cor. No. 1 of the Edward lode.
	Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 E I X; from which
	U. S. L. M. No. 1, ^{Sur. No. 4459,} previously described, bears S. 41° $19' 30''$ W. 2749.0 ft. dist.
	A juniper tree, 8 ins. diam., bears N. $56^{\circ} 00'$ W., 27.5 ft. dist., mkd. 4459 E. 1 B T.
	A mound of stone constructed adjacent to the iron post.
	Cor. No. 4, Starlight No. 1 lode, this survey, bears N. $77^{\circ} 24'$ E., 348.54 ft. dist.
	Thence N. $76^{\circ} 04'$ E.
300.0	Lode line; discovery pt. bears S. $3^{\circ} 41'$ W., 875.0 ft. dist.
371.53	Intersect line 4 - 1, Starlight No. 1 lode this survey.
515.98	Intersect line 4 - 1 Ronald lode, this survey.
599.90	Cor. No. 2.

Chains Feet	Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 E 2 X; from which
	A yellow pine, 8 ins. diam. bears S. 83° 00' E., 26.0ft. dist. Measurement is from brass cap to center of tree at blaze, inclined distance. Mkd. 4459 E 2 B T.
	A mound of stone constructed adjacent to the iron post. Cor. No. 1 of the Ronald lode, this survey, bears N. 61° 36' 30" W., 95.37 ft. dist.
	Cor. No. 1, of the Starlight No. 1 lode, this survey, bears N. 53° 13' 30" E., 1198.75ft. dist. Thence S. 3° 41' W.
414.39	Intersect line 3 - 4 of the Starlight No. 1 lode, this survey.
810.56	Intersect line 4 - 1 of the Ronald lode this survey.
1499.0	Cor. No. 3, identical with Cor. No. 2 of the Nancie lode, this survey, previously described.
	Thence S. 76° 04' W.
299.90	Lode line; discovery pt. bears N. 3° 41' E., 624.0 ft. dist.
592.90	Intersect line 2 - 3 of the Patricia lode, this survey.
599.90	Cor No. 4, identical with Cor. No. 1 of the Nancie lode and Cor. No. 2, Marjorie lode, both of this survey, previously described.
	Thence N. 3° 41' E.
86.92	Intersect line 2 - 3, Patricia lode, this survey.

Chains Feet		Chains Feet
1499.0	Cor. No. 1 and place of beginning.	
	CHARLES LODE	
	At Cor. No. 1 of the Charles lode.	
	Set a galvanized iron post, 24 ins. long, 3/4 ins. in diam., in a	
	15 pound concrete and rock base, 16 ins. in the ground with a brass	
	cap, 2 ins. diam. firmly fastened within the iron post, mkd. M S	
	4459 C 1 X; from which	
	U. S. L. M. No. 1, ^{Sur. No. 4459} previously described. bears S. 71°	
	29' W., 2552.70 ft dist.	
	Cor. No. 4 of the Ronald lode, this survey, bears S. 85°	
	31' W., 53.66 ft. dist.	
	A yellow pine, 12 ins. diam., bears S. 47° 00' E. 39.0 ft.	
	dist., mkd. 4459 C 1 B T.	
	A mound of stone constructed adjacent to the iron post.	
	Thence S. 82° 28' 30" E.	
	Lode line; discovery pt. bears S. 10° 52' E., 800.0 ft. dist.	
	Intersect line 2 - 3 of the Ronald lode, this survey.	
	Cor. No. 2	
	Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15	
	pound concrete and rock base, 16 ins. in the ground with a brass	
	cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S	
	4459 C 2 X; from which	
	Cor. No. 3 of the Ronald lode, this survey, bears N. 82°	
	53' 30" W., 82.85 ft. dist.	
	A mound of stone constructed adjacent to the iron post.	

Chains Feet	
1499.0	<p>Thence S. $11^{\circ} 59' 30''$ E.</p> <p>Cor No. 3</p> <p>This Cor. falls on inaccessible bluff, 15 ft. high, facing East. A Cor. of the location bears S. 12° E., 30.0 ft. dist.</p> <p>Thence N. $82^{\circ} 28' 30''$ W.</p>
5.0	<p>Witness for Cor. No. 3</p> <p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 C 3 W C X; from which</p> <p>A mound of stone constructed adjacent to the iron post.</p>
299.90	<p>Lode line; discovery monument bears N. $10^{\circ} 52'$ W., 688.91 ft. dist.</p>
599.90	<p>Cor. No. 4</p> <p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd., M S 4459 C 4 X; from which</p> <p>A corner of the location bears S. 20° W. 40.0 ft. dist.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence N. $10^{\circ} 52'$ W.</p>
1478.30	<p>Intersect line 3 - 4 of the Ronald lode, this survey.</p>
1488.91	<p>Cor. No. 1 and place of beginning.</p> <p>RONALD LODGE</p> <p>At Cor. No. 1 of the Ronald lode</p> <p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15</p>

24

Feet
Corners

pound concrete and rock base, 16 ins. in the ground, with a brass cap., 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 R 1 X; from which

U. S. L. M. No. 1, ^{Sur. No. 4459.} previously described, bears S. 45° $44' 30''$ W., 3230.06 ft. dist.

Cor. No. 2, of the Edward lode, this survey, bears S. $61^{\circ} 36' 30''$ E. 95.37 ft. dist.

Cor. No. 3 of the Starlight No. 1 lode, this survey, bears S. $14^{\circ} 22'$ E., 642.37 ft. dist.

A mound of stone constructed adjacent to the iron post.

Thence S. $83^{\circ} 36'$ E.

13.56 Intersect line 4 - 1 Starlight No. 1 lode, this survey.

300.0 Lode line; discovery pt. bears S. $2^{\circ} 08'$ E. 475.0 ft. dist.

538.59 Cor. No. 2

Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap. 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 R 2 X; from which

Cor. No. 1, Starlight No. 1 lode, this survey, bears N. $34^{\circ} 48'$ E. 891.80 ft. dist.

A mound of stone constructed adjacent to the iron post.

Thence S. $2^{\circ} 08'$ E.

309.28 Intersect line 2 - 3, Starlight No. 1 lode, this survey.

1448.21 Intersect line 1 - 2, Charles lode, this survey.

1448.82 Cor. No. 3

XXXX
Chains
Feet

Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 R 3 X; from which

Cor. No. 2 of the Charles lode, this survey, bears S. 82° 53' 30" E., 82.85 ft. dist.

A mound of stone constructed adjacent to the iron post.

Thence N. 83° 36' W.

238.59 Lode line; discovery pt. bears N. 2° 08' W., 973.82 ft. dist.

482.74 Intersect line 4 - 1 of the Charles lode, this survey.

538.59 Cor. No. 4

Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 R 4 X; from which

Cor. No. 1 of the Charles lode, this survey, bears N. 85° 31' E., 53.66 ft. dist.

A mound of stone constructed adjacent to the iron post.

Thence N. 2° 08' W.

593.96 Intersect line 2 - 3 of the Edward lode, this survey.

1058.18 Intersect line 3 - 4, Starlight No. 1 lode, this survey.

1383.21 Intersect line 1 - 2 of the Edward lode, this survey.

1438.74 Intersect line 4 - 1, Starlight No. 1 lode, this survey.

1448.82 Cor. No. 1 and place of beginning.

CROSS Feet	SOUTH Feet
	<p>STARLIGHT NO. 1 LODE</p> <p>At Cor. No. 1 of the Starlight No. 1 lode, identical with Cor. No. 4 of the Starlight lode, this survey.</p> <p>Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 S 11 S 4 X; from which</p> <p>U. S. L. M. No. 1/^{Sur. No. 4459,} previously described, bears S. 48° 55' 30" W., 4454.10 ft. dist.</p> <p>Cor. No. 3, Sur. 2588, Summit lode, bears S. 31° 30' 30" W., 716.02 ft. dist.</p> <p>Cor. No. 2, Ronald lode, this survey, bears S. 34° 48' W., 891.80 ft. dist.</p> <p>Cor. No. 2, Edward lode, this survey, bears S. 53° 13' 30" W., 1198.75 ft. dist.</p> <p>A yellow pine, 14 ins. diam., bears North, 27.0 ft. dist. Mkd. 4459 S. 1 1 S 4 B T</p> <p>A mound of stone constructed adjacent to iron post.</p> <p>Thence S. 31° 59' 30" E.</p>
300.0	Lode line; discovery pt. bears S. 56° 49' 30" W., 20.0 ft. dist.
599.57	<p>Cor. No. 2, identical with Cor. No. 3, Starlight lode, this survey.</p> <p>Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 S 1 2 S 3 X; from which</p> <p>A yellow pine, 12" diam., bears S. 46° 00' E., 15.0 ft. dist., mkd. 4459 S 1 2 S 3 B T.</p>

Chains
Feet

100 05 . A yellow pine, 12 ins. diam., bears N. 20° 00' E., 30.5 ft. dist., mkd. 4459 S 1.2 S 3.B T

A mound of stone constructed adjacent to the iron post.

Thence S! 56° 49' 30" W.

973.80 Intersect line 2 - 3, Ronald lode, this survey.

1436.57 Cor. No. 3

Set a galvanized iron post 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 S 1 3 X; from which

Cor. No. 1, Ronald lode, this survey, bears N. 14° 22' W., 642.37 ft. dist.

A mound of stone constructed adjacent to the iron post.

Thence N. 31° 59' 30" W.

192.67 Intersect line 2 - 3, Edward lode, this survey.

273.45 Intersect line 4 - 1, Ronald Lode, this survey.

299.57 Lode line; discovery pt. bears N. 56° 49' 30" E., 1416.57 ft. dist.

599.57 Cor. No. 4

Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 S 1 4 X; from which

Cor. No. 1, Edward lode, this survey, bears S. 77° 24' W., 348.54 ft. dist.

CHECK Feet	
	A juniper tree, 8 ins. diam., bears S. $26^{\circ} 00'$ W., 4.5 ft. dist., mkd. 4459 S 1.4 B T.
	A mound of stone constructed adjacent to the iron post. Thence N. $56^{\circ} 49'$ 30" E.
24.55	Intersect line 1 - 2, Edward lode, this survey.
189.50	Intersect line 4 - 1, Ronald lode, this survey.
205.15	Intersect line 1 - 2, Ronald lode, this survey.
381. 90	Intersect line 2 - 3 Sur. No. 2588, Summit lode, from which Cor. No. 3 bears S. $86^{\circ} 15'$ E., 509.64 ft. dist.
1019.42	Intersect line 3 - 4, Sur. No. 2588, Summit lode, from which Cor. No. 3 bears S. $3^{\circ} 45'$ W., 383.0 ft. dist.
1436.57	Cor. No. 1 and place of beginning.
	<p style="text-align: center;">STARLIGHT LODE</p> <p>At Cor. No. 1 of the Starlight lode, identical with Cor. No. 4 of the Starlight No. 2 lode, this survey.</p> <p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam. firmly fastened within the iron post, mkd. M S 4459 S 1 S 2 4 X; from which</p>
	U. S. L. M. No. 1, ^{Sur. No. 4459,} previously described, bears S. $49^{\circ} 41'$ 30" W., 4875.85 ft. dist.
	A yellow pine, 24 ins. diam., bears S. $52^{\circ} 00'$ W., 101.0 ft. dist., mkd. 4459 S 1 S 2 4 B T.
	A yellow pine, 18 ins. diam., bears N. $17^{\circ} 00'$ E., 16.0'

CHAINS
Feet

	<p>mkd. 4459 S. 1 S. 2 4 B T.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence S. $31^{\circ} 59' 30''$ E.</p>
300.0	Lode line; discovery pt. bears S. $57^{\circ} 44' 30''$ W., 406.48 ft. dist.
599.57	Cor. No. 2, identical with Cor. No. 3, Starlight No. 2 lode, this survey.
	<p>Set a galvanized iron post, 24 ins. long, $3/4$ ins. diam., in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S 4459 S. 2 S 2 3 X; from which</p> <p>A yellow pine, 12 ins. diam., bears S. $30^{\circ} 00'$ E., 16.5 ft. dist. mkd. 4459 S 2 S 2 3 B T.</p> <p>A mound of stone constructed adjacent to the iron post.</p> <p>Thence S. $57^{\circ} 44' 30''$ W.</p>
426.48	Cor. No. 3, identical with Cor. No. 2, Starlight No. 1 lode, this survey, previously described.
	Thence N. $31^{\circ} 59' 30''$ W.
299.57	Lode line; discovery pt. bears N. $57^{\circ} 44' 30''$ E., 20.0 ft. dist.
599.57	Cor. No. 4, identical with Cor. No. 1, Starlight No. 1 lode, this survey, previously described.
	Thence N. $57^{\circ} 44' 30''$ E.
426.48	Cor. No. 1 and place of beginning.
	<p>STARLIGHT NO. 2 LODE</p> <p>At Cor. No. 1 of the Starlight No. 2 lode.</p>

30
 Check
 Feet

On granite bedrock outcrop, even with general surface, point for
 Cor. No. 1, mkd 4459 S 2 1 X; from which

U. S. L. M. No. 1, ^{Sur. No. 4459} previously described, bears S. 51°
 55' W., 6355.97 ft. dist.

A stone monument constructed adjacent to the point.

Thence S. 31° 59' 30" E.

300.0 Lode line; discovery pt. bears S. 59° 11' W., 1435.65 ft. dist.

599.57 Cor. No. 2

Set a galvanized iron post, 24 ins. long, 3/4 ins. diam., in a 15
 pound concrete and rock base, 16 ins. in the ground, with a brass
 cap, 2 ins. diam., firmly fastened within the iron post, mkd. M S
 4459 S 2 2 X.

A mound of stones constructed adjacent to the iron post.

Thence S. 59° 11' W.

1495.65 Cor. No. 3, identical with Cor. No. 2 of the Starlight lode, this
 survey, previously described.

Thence N. 31° 59' 30" W.

299.57 Lode line: discovery pt. bears N. 59° 11' E., 60.0 ft. dist.

599.57 Cor. No. 4, identical with Cor. No. 1 of the Starlight lode, this
 survey, previously described.

Thence N. 59° 11' E.

1495.65 Cor. No. 1 and place of beginning.

Chains
feet

A R E A S

Acres

Total area Stranger lode 19.008

Area in conflict with -

Joe B. III lode of this survey 0.020

Total area Joe B. III lode 20.550

Total area Maytie lode 20.622

Total area B. Frank lode 19.687

Total area Tomlinson lode 14.842

Area in conflict with -

Marjorie lode of this survey 3.113

Marjorie lode of this survey, exclusive of its
conflict with the Patricia lode of this survey 2.872

Patricia lode of this survey 0.241

Total area Marjorie lode 19.502

Area in conflict with -

Patricia lode of this survey 9.108

Total area Nancie lode 19.697

Area in conflict with -

Patricia lode of this survey 0.528

Total area Charles lode 18.952

Area in conflict with -

Ronald lode of this survey 0.059

Total area Man-of-War lode 19.742

Area in conflict with -

Sur. No. 2588 Franklin No. 2 lode 0.003

Patricia lode of (this survey) 0.003

Patricia lode of this survey exclusive of its conflict
with Sur. No. 2588, Franklin No. 2 lode 0.003

32

Chains
Feet

Acres

Total area Westerner lode 11.390

Area in conflict with -

Sur. No. 1588, Harrison lode 0.160

Total area Edward lode 19.676

Area in conflict with -

Patricia lode of this survey 0.007

Starlight No. 1 lode of this survey, 1.150

Ronald lode of this survey 0.745

Ronald lode of this survey exclusive of its conflict
with the Starlight No. 1 lode 0.214

Total area Ronald lode 17.715

Area in conflict with -

Starlight No. 1 lode of this survey 5.730

Total area Starlight No. 1 lode 19.769

Area in conflict with -

Sur. No. 2588, Summit lode 2.241

Total area Patricia lode 19.877

Area in conflict with -

Sur. No. 2588, Franklin No. 2 lode 0.034

Total area Starlight lode 5.870

Total area Starlight No. 2 lode 20.582

LOCATION

This survey is located approximately in sec. 12; T. 12 N.,
R. 2 W., G & S. R. B. & M. (Unsurveyed.)

The survey of these lodes is wholly within the locations as
marked on the ground. Present corners are identical with corners
of the location except where previously shown.

XXXX
Chains
Feet

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows;

- No. 1 The discovery cut of the Westerner lode, the face of which being the discovery point, is on the lode line, 570.0 ft., S. 5° 25' 30" E., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1; 6 ft. wide, 4 ft. deep, runs N. 6° E., 120.0 ft.
Value, \$200.00
- No. 2 A trench, the South end of which bears S. 49° E. 430 ft. from Cor. No. 1 of the Westerner lode; 4 ft. wide, 4 ft. deep, running N. 5° W., 300 ft.
Value, \$75.00
- No. 3 A trench, the South end of which bears S. 29° E., 740 ft. from Cor. No. 1 of the Westerner lode; 8 ft. wide, 15 ft. deep, and running North, 15 ft.
Value, \$200.00
- No. 1 The discovery shaft of the Man-of-War lode, being the discovery point, is on the lode line, the S. E. Cor. being 600.00 ft., S. 0° 27' 30" W., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1; 6x6 ft., 30 ft. deep.
Value, \$600.00
- No. 2 A shaft, the center of which bears S. 52° E., 350 ft. from Cor. No. 1 of the Man-of-War lode; 6 x 6 ft., 100 ft. deep.
Value \$2,000.00
- No. 1 The discovery point of the Tomlinson lode is on the lode line 160.0 ft., S. 5° 16' E., from a pt. on line 1 - 2, 225.0 ft. from Cor. No. 1.
Value - None
- An interest in two common improvements for the Tomlinson, Man-of-War and Westerner lodes., described as follows;

~~CHECK~~
Feet

An adit, 5 x 6 ft. in size, the portal of which bears S. 78° E., 220.0 ft. from Cor. No. 1, of the Tomlinson lode; running N. 10° E. 200.0 ft (Minimum)

An adit, 5 x 6 ft. in size, the portal of which bears S. 50° E., 470.0 ft. from Cor. No. 1 of the Tomlinson lode; running N. 4° W. 100.0 ft. (Minimum). This adit is presently being used for water storage as a concrete dam has been constructed to within 2 ft. of the back of the adit of a pt. 35 ft. from the portal.

Value of the adits \$4500.00

Value of one-third interest \$1500.00

These improvements will be used for the eventual development of the Tomlinson, Man-of-War and Westerner lodes which are contiguous claims along the strike of a productive vein.

The surface rises rapidly to the North from the Portal of the adits and the extension in its present course, with necessary lateral crosscuts, affords the most practical and economical means of developing each of the stated lodes at depth.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each of the three stated lodes, subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-third interest in their value is hereby credited to each of said lodes.

No portion of or interest in these improvements has been credited heretofore as patent expenditure to any lode claim.

No. 1 The discovery cut of the Maytie lode, which is the discovery point, is on the lode line 45.0 ft., S. 11° 26' E., from a pt. on line 1 - 2,300.0 ft. from Cor. No. 1; 4 x 4 ft., 6 ft. deep.

Value, \$50.00

No. 2 An adit, 4 x 6 ft. in size, the portal of which bears S. 14° 30' E., 395.0 ft. from Cor. No. 1 of the Maytie lode and runs N. 5° W., 30.0 ft.

SHAFTS

- Value, \$450.00
- No. 3 An adit, 4 x 6 ft. in size, the portal of which bears S. 15° 30' E., 1175 ft. from Cor. No. 1 of the Maytie lode and running S. 55° E. 50 ft. (Minimum) Portal partially caved.
Value, \$750.00
- No. 1 The discovery point of the Joe B. III lode is on the lode line 40.0 ft., N. 11° 26' W. from a pt. on line 3 - 4, 297.80 ft. from Cor. No. 3.
Value, None
- No. 2 A shaft, 5 x 6 ft., 6 ft. deep, the center of which bears S. 81° 30' W., 270 ft. from Cor. No. 3 of the Joe B. III lode.
Value, \$100.00
- No. 3 An open cut, the South end of which bears West, 255 ft. from Cor. No. 3 of the Joe B. III lode, 7 ft. wide, 3 ft. deep, and running N. 10° E., 12 ft.
Value, \$125.00
- No. 1 The discovery point of the Stranger lode is on the lode line, 80.0 ft., S. 20° 19' E., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1.
Value, None
- No. 2 An open cut, the South end of which bears S. 86° 30' E. 342 ft. from Cor. No. 1 of the Stranger lode; 10 ft. wide, 5 ft. deep and running N. 10° E., 30 ft.
Value, \$300.00
- An interest in a common improvement for the Joe B. III and Stranger lodes, described as follows:
- An adit, 4 x 6 ft. in size, the portal of which bears N. 58° 30' W., 225.0 ft. from Cor. No. 3 of the Joe B. III lode; running S. 35° W. 150.0 ft. At 140.0 ft. a crosscut bears N. 55° W., 65 ft.
Value, \$4,300.00
Value of one-half interest, \$2,150.00

Chas
feet

This improvement will be used for the eventual development of the Joe B. III and Stranger lodes which are adjoining claims.

The surface rises rapidly to the Southwest from the portal of the adit and the extension is its present course, with necessary lateral crosscuts, affords the most practical and economical means of developing each of the stated lodes at depth.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each of the two stated lodes, subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-half interest in their value is hereby credited to each of said lodes.

No portion of or interest in these improvements has been credited heretofore as patent expenditure to any lode claim.

No. 1 The discovery cut and adit of the B. Frank lode, being the discovery point, is on the lode line 246.56 ft., N. $5^{\circ} 16'$ W., from a pt. on line 3 - 4, 299.70 ft. from Cor. No. 3; the cut is 4 ft. wide, 4 ft. deep running N. 44° W., 25 ft.; thence entering adit 4 x 6 ft. in size running N. 44° W., 10 ft.; thence open cut, 4 ft. wide, 15 ft. deep and running N. 46° E., 15 ft.

Value, \$500.00

No. 1 The discovery point of the Marjorie lode is on the lode line, 160.0 ft., N. $2^{\circ} 03'$ E., from a pt. on line 3 - 4, 297.80 ft. from Cor.

No. 3

Value, None

No. 2 An open cut, the South end of which bears N. 68° W., 355.0 ft. from Cor. No. 3 of the Marjorie lode; 4 ft. wide, 10 ft. deep and running N. 20° W., 30 ft.

Value, \$400.00

No. 3 An open cut, the North end of which bears N. $44^{\circ} 30'$ W., 625 ft. from Cor. No. 3 of the Marjorie lode; 4 ft. wide, 6 ft. deep and

Check feet	running S. 10° W. 10 ft. Value, \$100.00
No. 4	An adit-stope, the South end of which bears S. 15° E. 170.0 ft. from Cor. No. 1 of the Marjorie lode; 4 ft. wide, 15 ft. high running N. 35° W. 10 ft. thence North 10 ft. Value, \$500.00
No. 1	The discovery shaft of the Nancie lode, which is the discovery point, is on the lode line 730.0 ft., S. 1° 46' W., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1; 4 x 4 ft., 6 ft. deep. Value, \$100.00
No. 2	An open cut, and adit, the South end of which bears N. 11° 30' W., 560. ft from Cor. No. 3 of the Nancie lode; 5 ft. wide, 6 ft. deep and running N. 2° E., 12 ft. thence an adit 4 x 6 ft. in size running 6 ft. Value, \$250.00
No. 1	The discovery cut of the Edward lode, which is the discovery point, is on the lode line 875.0 ft. S. 3° 41' W., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1; 4 ft. wide, 6 ft. deep and running N° 15° W. 8 ft. Value, \$175.00
No. 1	The discovery cut of the Patricia lode, which is the discovery point, is on the lode line 80.0 ft., S. 0° 49' W., from a pt. on line 1-2, 300.0 ft. from Cor. No. 1; 4 ft. wide, 6 ft. deep and running N. 10° E., 6 ft. Value, \$135.00
No. 2	An open cut and adit the South end of which bears N. 7° 30' E., 550 ft. from Cor. No. 4 of the Patricia lode; 5 ft. wide, 6 ft. deep and running North, 10 ft.; thence an adit 5 x 5 ft. in size running 10 ft. Value, \$250.00

Chains Feet	An interest in a common improvement for the Edward and Patricia lodes, described as follows:
.11 0.	<p>An open cut and adit, the S. E. end of which bears N. 9° 30' E., 590. ft. from Cor. No. 4 of the Edward lode; 8 ft. wide, 8 ft. deep and running N. 55° W., 30 ft.; thence an adit 4 x 6 ft. in size running 40 ft.; thence S. 45° W., 50 ft.</p>
	Value, \$1500. 00
	Value of one half interest \$750.00
	<p>This improvement will be used for the development of the Edward and Patricia lodes which are contiguous claims covering a vein striking across both lodes.</p>
	<p>The surface rises rapidly to the N. W. from the portal of the adit and the extension in its present course with necessary lateral crosscuts, affords the most practical and economical means of developing each of the stated lodes at depth.</p>
	<p>Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each of the two stated lodes. Subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-half interest in its value is hereby credited to each of said lodes.</p>
	<p>No portion of or interest in these improvements has been credited heretofore as patent expenditure to any lode claim.</p>
No. 1	<p>The discovery point of the Charles lode is on the lode line 800.0 ft., S. 10° 52' E., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1.</p>
	Value, None.
No. 2	<p>An adit, raise and shaft; the portal of the adit bears S. 29° E., 900 ft. from Cor. No. 1 of the Charles lode; the adit, 4 x 6 ft. in size, runs South, 65 ft., at a pt. 10 ft. from the portal. A</p>

Chains Feet	
	<p>stope, 5 ft. wide, 10 ft. long breaks through to the surface 25 ft. high. The shaft, 5 x 6 ft. is located at the portal of the adit. Depth unknown as it is water-filled.</p> <p>Value, \$1,500.00</p>
No. 1	<p>The discovery point of the Ronald lode is 475.0 ft., S. 2° 08' E., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1</p> <p>Value, None.</p>
No. 2	<p>An open cut, the North end of which bears S. 27° E., 580. ft. from Cor. No. 1 of the Ronald lode; 4 ft. wide, 6 ft. deep and running S. 55° W., 6 ft.</p> <p>Value, \$135.00</p>
No. 3	<p>An adit, 4 x 6 ft. in size, the portal of which bears S. 46° 30' E., 640 ft. from Cor. No. 1 of the Ronald lode; and runs S. 17° W., 60 ft.</p> <p>Value, \$900.00</p>
No. 1	<p>The discovery point of the Starlight No. 1 lode is on the lode line 20.0 ft., S. 56° 49' 30" W., from a pt. on line 1 - 2, 300.0 ft. from Cor. No. 1.</p> <p>Value, none.</p>
No. 2	<p>An open cut and adit, the West end of which bears S. 25° E., 300.0 ft. from Cor. No. 1 of the Starlight No. 1 lode; 6 ft. wide, 6 ft. deep and running N. 63° E. 10 ft.; thence an adit 5 x 5 ft. in size running 25 ft.</p> <p>Value, \$600.00</p>
No. 3	<p>An open cut, the North end of which bears S. 38° W., 880 ft. from Cor. No. 1 of the Starlight No. 1 lode; 3 ft. wide, 4 ft. deep running S. 56° W., 25 ft.</p> <p>Value, \$150.00</p>
No. 1	<p>The discovery point of the Starlight lode is on the lode line,</p>

Chains
Feet

20.0 ft., N. $57^{\circ} 44' 30''$ E., from a pt. on line 3 - 4, 299.57 ft. from Cor. No. 3.

Value, None

No. 2 An adit, 4 x 6 ft. in size, the portal of which bears S. 29° E., 320 ft. from Cor. No. 4 of the Starlight lode and runs East, 35 ft.

Value, \$525.00

No. 3 An adit, 4 x 5 ft. in size, the portal of which bears S. 2° W., 360 ft. from Cor. No. 1 of the Starlight lode, and running N. 35° E., 20.0 ft., thence N. 50° E., 100 ft.

Value, \$1,800.00

No. 1 The discovery point of the Starlight No. 2 lode is on the lode line 60.0 ft. N. $59^{\circ} 11'$ E., from a pt. on line 3 - 4, 299.57 ft. from Cor. No. 3.

Value, None.

No. 2 An adit-stope, the portal of which bears S. 32° E., 300.0 ft. from Cor. No. 4 of the Starlight No. 2 lode; 7 ft. wide, 20 ft. high and running N. 57° E., 50 ft.

Value, \$700.00

No. 3 A stope with raise to the surface and bears S. $61^{\circ} 30'$ E., 465.0 ft. from Cor. No. 4 of the Starlight No. 2 lode; 4 x 5 ft. in size at the surface entering a stope 7 ft. wide, 10 ft. high and running N. 65° E., 30 ft.

Value, \$500.00

OTHER IMPROVEMENTS

A mill building, frame with corrugated sheet steel sides and roof, complete with necessary equipment for treating 25 tons of ore per day. Equipment includes;

Ore bin

Crusher

Feet

Conveyors

Tables

Floatation Cells

Water Tanks, 18 ft. diam., 2 each

Power plant

The Northwest corner bears S. 49° E., 290.0 ft. dist. from Cor. No. 1 of the Tomlinson lode, claimant herein.

A frame bunk house, the S. E. Corner of which bears S. 75° E., 28.0 ft. dist. from Cor. No. 4, Patricia lode, 15 x 30 ft. in size; the long sides bear N. 45° W, claimant herein.

A frame bunk house, the S. W. Corner of which bears S. 75° E., 90.0 ft. dist. from Cor. No. 4 of the Patricia lode, 20 x 30 ft. in size; the long sides bear N. 15° E. A similar structure adjoins at the N. E. Corner, the long sides bear S. 75° E, claimant herein.

Four frame cabins, 10 x 12 ft., bear S. 5° E., 350.0 ft. from Cor. No. 1 of the Tomlinson lode, claimant herein.

OTHER CORNER DESCRIPTIONS
and SUPPLEMENTAL DATA

U. S. L. M. No. 1/ *Sur. No. 4459,* A galvanized iron post, 24 ins. long, 3/4 ins. diam., set in a 15 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. U. S. L. M. 1 M. S. 4 4 5 9 X; from which

A yellow pine, 12 ins. diam., bears N. 29° 13' 30" E., 16.05 ft. dist. to center, mkd. U. S. L. M. I. 4 4 5 9 X.

A yellow pine, 10 ins. diam., bears N. 72° 36' 30" W., 7.37 ft. dist. to center, mkd. U. S. L. M. I. 4 4 5 9 X.

The S. W. Corner of the mill building bears N. 88° 13' E. 925.0 ft. dist.

The monument is located atop a small knob on top of ridge

~~CHAINS~~
Feet

which ends in the first small ravine West of the four small cabins on the South side of the road. This knob and monument are visible from two higher ridges, one to the North and one to the East.

Sur. No. 1588, Harrison lode: Cor. No. 3, a stone monument, 6 x 8 ins., 12 ins. above ground, mkd. 1588 H 3 X. The pine bearing tree had been cut down but the juniper, with no markings appeared to be still standing. Cor. No. 4, a rock 4 x 12 ins., 24 ins. long, mkd. 1588 H 4 X, found approximately 15 ft. down the slope from its proper position. The pine bearing tree found and the corner re-established from it. A second bearing tree not positively identified. The line 3 - 4, was found to bear S. 78° 25' 30" W. and its length to be 596.66 ft. instead of S. 78° 32' W. and 600.0 ft.

Sur. No. 2588, Franklin No. 2 lode, Cor. No. 2, a stone monument, 4 x 8 ins., 6 ins. above ground, mkd. 2588 F 2 2. Cor No. 3, not found as pt. occurs over caved open cut and underground workings. Lines shown as approved.

Sur. No. 2588, Summit lode, Cor. No. 3, an angular granite rock with apex at top and 6 in. base at surface of ground. 6 ins. above ground. Mkd 2588 S. 3. Cor. No. 2, ... Unable to locate monument, probably knocked out of position by one of numerous rock movements. Lines shown as approved.

FIELD ASSISTANTS

Name	Capacity
Russell Hart	Chainman
Richard Cleveland	Chainman
Richard Mc Atee	Axeman

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

43

CERTIFICATE OF SURVEYOR

May 10, 1959

I, Harvey W. Smith
 Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the Bur. Land
Management, Cadastral Engineer, at Phoenix, Arizona
 dated August 4, 1958, I have faithfully and correctly executed the survey of
 the mining claim of Decker Enterprises, Inc.
 known as the Starlight and 15 others (see reverse side)
(Lode, placer, or mill site)
 situate in Hassayampa Mining Dist., Yavapai County Sect. 12
 T. 12 N, R. 2 W-Unsurveyed-G&SRB&M Meridian, Arizona, and
(State)
 designated as Survey No. 4459, which is represented in the foregoing field notes as having been
 executed by me and under my direction, and that said survey has been made in strict conformity with said order,
 the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
 described in the foregoing field notes, and I do further certify that the labor expended and improvements made
 upon or for the benefit of the Lode location(s) embraced in the said mining claim by
(Lode or placer)
 claimant(s) or its grantors are fully stated in my report therein, and that the character,
 extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
 portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
 of expenditures upon any other claim.

Prescott, Arizona
(Place)

H. W. Smith
H. W. Smith
(Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management--Survey Office
(Office)
Phoenix, Arizona September 4, 1959
(Place) (Date)

The foregoing field notes of mineral survey No. 4459, in approximately Section 12
unsurveyed, T. 12 North, R. 2 West, Gila & Salt River Meridian,
Arizona, executed by Harvey W. Smith, Mineral Surveyor,
(State)
 under order dated August 4, 1958, having been critically examined and the necessary
 corrections made prior to their certification by the surveyor, the field notes and the survey therein described
 are hereby approved.

Lester S. Mann
Lester S. Mann

Office Cadastral Engineer
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

Office Cadastral Engineer
(Title)

NAME OF CLAIM	DATE OF LOCATION	DATE OF RECORD	AMENDED LOG. DATE	AMENDED LOG. RECORD. DATE
STARLIGHT	July 1, 1945	July 16, 1945	June 28, 1952	July 31, 1952
STARLIGHT NO. 1	July 1, 1945	July 16, 1945	June 28, 1952	July 31, 1952
STARLIGHT NO. 2	July 1, 1945	July 16, 1945	June 28, 1952	July 31, 1952
RONALD	July 7, 1952	July 31, 1952	none	
EDWARD	July 7, 1952	July 31, 1952	none	
CHARLES	July 12, 1952	July 31, 1952	none	
NANCIE	July 7, 1952	July 31, 1952	none	
WESTERNER	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
MAN OF WAR	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
B. FRANK	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
TOMLINSON	June 28, 1952	July 31, 1952	none	
PATRICIA	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952
MARJORIE	June 3, 1936	June 3, 1936	July 12, 1952	July 31, 1952
JOE B. III	June 3, 1936	June 3, 1936	July 12, 1952	July 31, 1952
MAYTIE	July 7, 1952	July 31, 1952	none	
STRANGER	June 3, 1936	June 3, 1936	July 5, 1952	July 31, 1952