

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 4553

ARIZONA Land District.

FIELD NOTES

Of The Survey Of The Mining Claim Of

Frank Melluzzo

Known As The

El rame #S 27, 28 & 44 lodes

Winifred Mining District,

Maricopa County, Arizona

Section 3, Township 4N., Range 3E., G.&S.R.B.&M.

Surveyed under order dated Feb. 7, 19 61

by Harvey W. Smith
Mineral Surveyor.

El rame #27 3/18/57
El rame #28 3/18/57
Claim located El rame #44 3/17/57, 19

Survey commenced June 10, 19 61

Survey completed June 16, 19 61

Address of claimant 1009 E. Hatcher Rd.
Sunnyslope, Arizona

DATES OF AMENDED LOCATIONS

THE UNIVERSITY OF CHICAGO
LIBRARY

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO
LIBRARY

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

SURVEY NO. 4553

1

CHAINS
Feet

This survey was made with a K. & E. transit, No. 51591, with horizontal limb 5.5 ins. diam., having two double opposite verniers and full vertical circle 4.5 ins. diam., having one double vernier, the verniers read to one minute of arc; the instrument is equipped with a colored eye-shade to be attached for making direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian established by direct observation on the sun. At 08:53:30 A. M. on June 15, 1961 at cor. No. 4 of the El rame #27 lode, latitude $33^{\circ}42'51''$ North, longitude, $112^{\circ}02'22''$ West, turning from a reference pt. about 600 ft. east clockwise to the sun in an east direction.

True bearing of reference pt.

N. $89^{\circ}54'30''$ E.

The lines were measured with a Lufkin steel tape, 300 ft. in length, graduated every ft. for 299 ft. and the remaining ft. graduated to tenths and hundredths. The tape was compared to a standard at the beginning of the survey and found to be correct. All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $13^{\circ}40'$ East.

SURVEY NO. 4553

El rame #27 Lode

At cor. No. 1 of the El rame #27 lode; identical with cor. No. 2 of the El rame #28 lode of this survey and on the sec. line between secs. 3 & 10, T.4N., R.3E., G.&S.R.B.&M.

Set a galvanized iron post, $\frac{3}{4}$ in. diam., 30 ins. long, in a 15 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4553 ER 27 1 ER 28 2 X; from which

The $\frac{1}{4}$ cor. of secs. 3 & 10, T.4N.,

R.3E., G.&S.R.B.&M., bears N. 89°

$54'30''$ E., 729.09 ft. dist.; a stone,

6x8 ins., 6 ins. above ground, firmly set marked and witnessed as described in the official record.

A mound of stones constructed adjacent to the iron post.

Thence S. $89^{\circ}54'30''$ W.

300.0 Lode line; discovery pt. bears N. $0^{\circ}06'30''$ E., 500.0 ft. dist.

579.16 Cor. No. 2 identical with the W. $1/16$ cor. on the south boundary of sec. 3, T.4N., R.3E., G.&S.R.B.&M.

Chains	Feet	
		Set a galvanized iron post, 3/4 in. diam., 30 ins. long in a 15 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4553 ER 27 2 X; from which The cor. of secs. 3, 4, 9 & 10 bears S. 89°54'30" W., 1308.25 ft. dist. A mound of stones constructed adjacent to the iron post. Thence N. 0°45'30" W.
	195.0	Unimproved dirt road bears N. 58° E. and S. 58° W.
	1320.09	Cor. No. 3 Set a galvanized iron post, 3/4 in. diam., 30 ins. long in a 15 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4553 ER 27 3 X; from which The NE cor. of the SW $\frac{1}{4}$ SW $\frac{1}{4}$ bears N. 15°48'20" E., 30.62 ft. dist.; a mound of stones, the center of which I accept as the pt. for the corner. A mound of stones constructed adjacent to the iron post. Thence N. 89°54'30" E.
	8.54	Intersect the line between the SW $\frac{1}{4}$ SW $\frac{1}{4}$ and the SE $\frac{1}{4}$ SW $\frac{1}{4}$ at a pt. from which the W. 1/16 cor. of the south boundary of Sec. 3 bears S. 0°23'10" E., 1320.01 ft. dist., previously described.
	294.11	Lode line; discovery pt. bears S. 0°06'30" E., 820.0 ft. dist.
	594.11	Cor. No. 4 identical with cor. No. 3 of the El rame #28 lode of this survey.
		Set a galvanized iron post 3/4 in. diam., 30 ins. long, set in a 15 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4553 ER 27 4 ER28 3 X; from which A mound of stones constructed adjacent to the iron post. Thence S. 0°06'30" E.
	430.0	Unimproved dirt road bears S. 70° E. and N. 70° W.
	1320.0	Cor. No. 1 and the place of beginning. El rame #28 Lode At cor. No. 1 of the El rame #28 lode identical with cor. No. 2 of the El rame #44 lode of this survey and on the line bet. secs. 3 & 10, T.4N., R.3E., G.&S.R.B.&M.

xChains Feet	
	<p>Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 15 pound concrete and rock base, 18 ins. in ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4553 ER 28 1 ER 44 2 X; from which</p> <p>The 1/4 cor. of secs. 3 & 10, T.4N., R.3E., G.&S.R.B.&M.; bears N. 89°54'30" E., 129.75 ft. dist.; previously described.</p> <p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence S. 89°54'30" W.</p>
300.0	Lode line; discovery pt. bears N. 0°04'50" E., 500.0 ft. dist.
599.34	Cor. No. 2 identical with cor. No. 1 of the El rame #27 lode of this survey; previously described.
	Thence N. 0°06'30" W.
890.0	Unimproved dirt road bears N. 70° W. and S. 70° E.
1320.0	Cor. No. 3 identical with cor. No. 4 of the El rame #27 lode of this survey; previously described.
	Thence N. 89°54'30" E.
300.0	Lode line; discovery pt. bears S. 0°04'50" E., 820.0 ft. dist.
600.0	Cor. No. 4 identical with cor. No. 3 of the El rame #44 lode of this survey.
	<p>Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 15 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4553 ER 28 4 ER44 3 X; from which</p> <p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence S. 0°04'50" E.</p>
1320.0	Cor. No. 1 and the place of beginning.
	El rame #44 Lode
	Beginning at cor. No. 1 of the El rame #44 lode, identical with the 1/4 cor. of secs. 3 & 10, T.4N., R.3E., G.&S.R.B.&M.; previously described.
	<p>Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 15 pound concrete and rock base, 18 ins. in the ground in an angular position so that the brass cap, 2 ins. diam., sets immediately above the stone 1/4 cor. marker, mkd. MS 4553 ER44 1 X; from which</p> <p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence S. 89°54'30" W.</p>
68.0	Lode line; discovery pt. bears N. 0°06'10" E., 500.0 ft. dist.

Feet	CHAINS	DESCRIPTION
129.75		Cor. No. 2 identical with cor. No. 1 of the El rame #28 lode of this survey; previously described. Thence N. $0^{\circ}04'50''$ W.
1320.0		Cor. No. 3 identical with cor. No. 4 of El rame #28 lode of this survey; previously described. Thence N. $89^{\circ}54'30''$ E.
65.96		Lode line; discovery pt. bears S. $0^{\circ}06'10''$ W., 820.01 ft. dist.
132.48		Intersect the line between the $SE\frac{1}{4}SW\frac{1}{4}$ and the $SE\frac{1}{4}$, Sec. 3, at a pt. from which the $\frac{1}{4}$ cor. of secs. 3 & 10, T.4N., R.3E., G.&S.R.B.&M. bears S. $0^{\circ}02'20''$ W., 1320.0 ft. dist.; previously described.
133.96		Cor. No. 4 Set a galvanized iron post, $\frac{3}{4}$ in. diam., 30 ins. long in a 15 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4553 ER44 4 X; from which A mound of stones constructed adjacent to the iron post. Thence S. $0^{\circ}06'10''$ W.
1320.01		Cor. No. 1 and the place of beginning.

AREAS		Acres
Total area El rame #27 lode		17.777
Area in conflict with $SW\frac{1}{4}SW\frac{1}{4}$, Sec. 3, T.4N., R.3E.		0.130
Total area El rame #28 lode		18.172
Total area El rame #44 lode		3.995
Area in conflict with $SE\frac{1}{4}$ Sec. 3, T.4N., R.3E., G.&S.R.B.&M.		0.022

LOCATION
This survey is located in the $SW\frac{1}{4}$ and $SE\frac{1}{4}$ Sec. 3, T.4N., R.3E., G.&S.R.B.&M.

The survey of the El rame #s 27, 28 & 44 lodes is identical with the respective location or amended location as marked on the ground.

SURVEY NO. 4553

~~CHAIN~~
Feet

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or his grantors are as follows:

- No. 1 The discovery pt. of the El rame #27 lode is on the lode line 500.0 ft. from a pt. on line 1-2, 300.0 ft. from cor. No. 1.
Value, None
- No. 2 An open cut, the SE Cor. of which bears N. 5°45'W., 870 ft. dist. from cor. No. 1 of the El rame #27 lode; 30x40 ft. in size, 6 ft. average depth. On the west edge is a cut 8 ft. wide, 4 ft. deep and running N. 10°E., 30 ft.
Value, \$600.
- No. 1 The discovery pt. of the El rame #28 lode is on the lode line 500.0 ft. from a pt. on line 1-2, 300.0 ft. from cor. No. 1
Value, None
- No. 2 An untimbered shaft, the SE cor. of which bears N. 31°30'W., 975 ft. dist from cor. No. 1 of the El rame #28 lode; 6x8 ft. in size, 35 ft. deep, inclined at 60°, N.45°W.
Value, \$1000.
- No. 3 An open cut, the SE cor. of which bears N.29°W., 1010 ft. dist., from cor. No. 1 of the El rame #28 lode; 2 ft. wide, 2 ft. deep and running N.60°E., 15 ft.
Value, \$40.
- No. 4 A pit, the SE cor. of which bears N. 29°W., 1030 ft. dist. from cor. No. 1 of the El rame #28 lode; 6x5 ft. in size, 11 ft. deep.
Value, \$225.
- No. 5 An untimbered shaft, the SE cor. of which bears N.31°W., 1070 ft. dist. from cor. No. 1 of the El rame #28 lode; 6x8 ft. in size, 30 ft. deep.
Value, \$900.
- No. 1 The discovery pt. of the El rame #44 lode is on the lode line, 500.0 ft. from a pt. on line 1-2, 68.0 ft. from cor. No. 1.
Value, None

OTHER IMPROVEMENTS

NONE

OTHER CORNER DESCRIPTIONS
AND SUPPLEMENTAL DATA

The cor. of secs. 3, 4, 9 & 10, T.4N., R3E., G.&S.R. B. & M. is a stone, 8 x 10 ins., 1 ft. above ground, firmly set, marked and witnessed as described in the official record.

The N. $\frac{1}{2}$ cor. of sec. 3, T.4N., R.3E., G.&S.R.B.&M. is obliterated, therefore, the N-S midsection line was calculated from the official plat records.

FIELD ASSISTANTS

Name
Bill Donahue

Capacity
Chainman-Axeman

Serial No. 4553

Chains

Quantity
feet

EXHIBITS

The improvements and the value of the land and improvements made upon or for the benefit of said land together embraced in said mining claim by the claimant of the grantors are as follows:

No. 1 The discovery pt. of the claim is on the line 1-2, 500 ft. from cor. No. 1. Value, none.

No. 2 An open cut, the 25 cor. of which bears N. 30° E. 100 ft. dist. from cor. No. 1 of the claim; the 25 cor. in size, 25 ft. deep and containing 100 cu. ft. of stone. Value, \$100.

No. 3 The discovery pt. of the claim is on the line 1-2, 500 ft. from cor. No. 1. Value, none.

No. 4 An open cut, the 25 cor. of which bears N. 30° E. 100 ft. dist. from cor. No. 1 of the claim; the 25 cor. in size, 25 ft. deep and containing 100 cu. ft. of stone. Value, \$100.

No. 5 An open cut, the 25 cor. of which bears N. 30° E. 100 ft. dist. from cor. No. 1 of the claim; the 25 cor. in size, 25 ft. deep and containing 100 cu. ft. of stone. Value, \$100.

No. 6 An open cut, the 25 cor. of which bears N. 30° E. 100 ft. dist. from cor. No. 1 of the claim; the 25 cor. in size, 25 ft. deep and containing 100 cu. ft. of stone. Value, \$100.

No. 7 An open cut, the 25 cor. of which bears N. 30° E. 100 ft. dist. from cor. No. 1 of the claim; the 25 cor. in size, 25 ft. deep and containing 100 cu. ft. of stone. Value, \$100.

No. 8 The discovery pt. of the claim is on the line 1-2, 500 ft. from cor. No. 1. Value, none.

OTHER IMPROVEMENTS

None

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

The cor. of sec. 3, T. 2 N., R. 10 E., is a stone, 3 ft. high, 1 ft. above ground. It is a witness and is located as described in the official record.

The cor. of sec. 3, T. 2 N., R. 10 E., is a stone, 3 ft. high, 1 ft. above ground. It is a witness and is located as described in the official record.

FIELD NOTES

W. J. Fox

W. J. Fox

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

June 25, 1961

I, Harvey W. Smith,
 Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____
 _____ Cadastral Engineer, at Phoenix, Arizona
 dated Feb. 7, 1961, I have faithfully and correctly executed the survey of
 the mining claim of Frank Melluzzo,
 known as the El rame #s 27, 28 & 44 Lodes
(Lode, placer, or mill site)
 situated in Winifred Mining District, Maricopa County, Sec. 3,
 T. 4N., R. 3E., G. & S. R. B. & Meridian, Arizona, and
(State)
 designated as Survey No. 4553, which is represented in the foregoing field notes as having been
 executed by me and under my direction, and that said survey has been made in strict conformity with said order,
 the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
 described in the foregoing field notes, and I do further certify that the labor expended and improvements made
 upon or for the benefit of the Lode location(s) embraced in the said mining claim by
(Lode or placer)
 claimant(s) or his grantors are fully stated in my report therein, and that the character,
 extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
 portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
 of expenditures upon any other claim.

Scottsdale, Arizona
(Place)

Harvey W. Smith
(Mineral Surveyor)
 Harvey W. Smith

CERTIFICATE OF APPROVAL

Bureau of Land Management, Survey Office
(Office)

Phoenix, Arizona September 20, 19 61
(Place) (Date)

The foregoing field notes of mineral survey No. 4553, in Winifred Mining District
Section 3, T. 4 N., R. 3 E., G. & S. R. Meridian,
Arizona, executed by Harvey W. Smith, Mineral Surveyor,
(State)
 under order dated February 7, 1961, having been critically examined and the necessary
 corrections made prior to their certification by the surveyor, the field notes and the survey therein described
 are hereby approved.

Fred J. Weiler
 Fred J. Weiler
 State Director
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

(Title)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
OFFICE OF THE SURVEYOR

June 15, 1911

Survey of 1891

Section 1, Township 10N, Range 10E, T10N, R10E

Section 1

Section 1

Section 1

Section 1

Section 1

Section 1

Section 1

Section 1

OFFICE OF THE SURVEYOR

Section 1

Section 1

Section 1

OFFICE OF THE SURVEYOR

Section 1

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (942)
BUREAU OF LAND MANAGEMENT M.S. 4553
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The El rame #s 27, 28 & 44 lodes, Mineral Survey No. 4553, located in Township 4 North, Range 3 East, Gila and Salt River Meridian, Arizona, are hereby canceled. As of this date, this notice of cancellation will become part of the field notes for Mineral Survey No. 4553, page 11.


This claim has not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"El rame #s 27, 28 & 44 lodes, M.S. 4553 were canceled April 29, 1996, by memo 9605 (942) M.S. 4553 which is now a part of the original field notes."

April 29, 1996
Date


Acting Chief Cadastral Surveyor of Arizona

1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025

[Handwritten signature]