4--688

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 457.0

ARIZONA	Land District.
FIELD NOTE	ES
Of The Survey Of The Minin	g Claim Of
EMANUEL B. WILLIS	
Known As The	
TRAILS END MINE LODE	
4	
Goldfield Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 eyed under order dated Aug.8, 1	Arizona , Range 7E., G.&S.
Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 Teyed under order dated Aug.8, 1	Arizona , Range 7E., G.&S. 961 961 Amd., 19
Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 Teyed under order dated Aug.8, 1	Arizona , Range 7E, G.&S. 961 961 Amd., 19
Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 Peyed under order dated Aug.8, 1	Arizona , Range 7E, G.&S. 961 961 Amd., 19
Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 Peyed under order dated Aug.8, 1	Arizona Range 7E, G.&S. 961 961 Amd., 19 Harvey W. Smith Mineral Surveyor , 19 51
Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 eyed under order dated Aug.8, 1 by Claim located Jan. 22,	Arizona , Range 7E., G.&S. 961 961 Amd., 19 Harvey W. Smith Mineral Surveyor , 19 51
Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 eyed under order dated Aug.8, 1 by Claim located Jan. 22, Survey commenced June 27,	Arizona , Range 7E, G.&S. 961 961 Amd., 19 Harvey W. Smith Mineral Surveyor , 19 51 , 19 61
Maricopa County, 3 & 34 , Township 1 & 2 N May 8, 1 eyed under order dated Aug.8, 1 by Claim located Jan. 22, Survey commenced June 27, Survey completed Aug. 10, Address of claimant Rt. 2, Box 24	Arizona , Range 7E, G.&S. 961 961 Amd., 19 Harvey M. Smith Mineral Surveyor , 19 51 , 19 61 76

ACTIVATE SPOTS (M.) Provincia (m.) 1864 - St. Marcha (m.) (m.) 1862-4864 - St. Chinal (m.) 1864-1864

MET HOW THE LOSS STREETS AND ASSESSED.

PATON ALAN

and providing and the Manager and the

\$60° 28 (80-2

Jurian gradic fat it.

The state of the s

and the second of the second o

SECTION SERVING SECTION

7

Chainsx Feet

4-678 b

This survey was made with a K. & E. transit, No. 51591, with horizontal limb 5.5 ins. diam., having two double opposite verniers and full vertical circle 4.5 ins. diam., having one double vernier, the verniers read to one minute of arc; the instrument is equipped with a colored eye-shade to be attached for making direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments

were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian established by direct observation on the sun. At 08:04 A. M. on June 27, 1961 at cor. No. 1 of the Trails End Mine lode, latitude 53°27'51" North, longitude 111°37'54" West, turning from a reference pt. about 300 ft. southwest clockwise to the sun in an east direction.

> True bearing of reference pt. S. 7°23'W.

The lines were measured with a Lufkin steel tape, 300 ft. in length graduated every ft. for 299 ft. and the remaining foot graduated to tenths and hundredths. The tape was compared to a standard at the beginning of the survey and found to be correct. All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 14015' East.

SURVEY NO. 4570

TRAILS END MINE LODE

At cor. No. 1 of the Trails End Mine Lode.

Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4570 TEM 1 X; from which

> The cor. of secs. 33, 34, 3 & 4, Ts. 1 & 2
> N., R.7E., G.&S.R.B.&M., bears N.40
> 47'20"W., 552.65 ft. dist.; an iron post, firmly set, marked and witnessed as described in the official record.

A mound of stones constructed adjacent to the iron post.

Thence N. 7º23'E.

472.0 Dirt road bears N.800W. and S.80°E.

632.0 Dirt road bears N.30° W. and S.30° E.

720.0 Dirt road bears N. 30°E. and S. 30°W. I.

1430.0 Dirt road bears N.25°E. and S.25°W.

1500:0 Cor. No. 2

Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly

GPO 896619

-		
		fastened within the iron post, mkd. MS 4570 TEM
	rejetov	legifrov in the section of stones constructed adjacent to the iron post.
	tio gain	Thence \$. 82037 E.
	12.50	Dirt road bears N. 30°E. and S. 25°W.
	The second secon	Dirt road bears N. 25°E. and S. 12° W.
	300.0	Lode line; discovery pt. bears S. 7°23'W., 440 ft. dist.
	588.0	Point for witness cor. No. 3
	8.82 156	Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 15 pound concrete and rock base, 12 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4570 TEM 3 W C X; from which
	l tape, b. and redons.	A mound of stones constructed adjacent to the iron post.
	600.0	Cor. No. 3 parces as of heardings and a state of
	etada. Tarios . **	This pt. falls at the west edge of an improved dirt
		Thence S. 7° 23' W.
	192.0	Improved dirt road bears N. 16° E. and S. 16° W.
	1500.0	Cor. No. 4
		This pt. falls at the edge of a local drainage. A mon- ument here would soon be obliterated.
	I MIT O	Thence N. 82037'W.
	43.33	Point for witness Cor. No. 4.100
		fastened within the iron post, mkd. MS 4570 TEM 4 W C X; from which
		A mound of stones constructed adjacent to the iron post.
	104.33	Improved dirt road bears N. 8°E. and S.9°T.
	300.0	Lode line; discovery pt. bears N. 7°23'E., 1060 ft. dist.
	600.0	Cor. No. 1 and the place of beginning.
		AREAS Cas beer s. 25° 1. and 8.25° 1.
	A PARTY OF	Total area Trails End Mine 20.661

4-678 b

Chains-LOCATION This survey is located in the SW4 Sec. 34 and NW4 Sec. 3, Ts. 1 & 2 N., R.7E., G.&S.R.B.&M. The survey of the Trails End Mine lode is identical with its location or amended location as marked on the ground. EXPENDITURES The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or his grantors are as follows; The discovery pt. of the Trails End Mine lode is on the lode line 440 ft. from a pt. on line 2-3, 300.0 No. 1 ft. from cor. No. 2. Value, None An open cut and pit, the SW edge of the pit bears N. 19° E., 980 ft. dist from cor. No. 1 of the Trails End Mine lode; the cut is 50 ft. in diam. No. 2 with a leg 10 ft. wide on the NE edge bearing N. 70° E., 50 ft.; average depth $l^{\frac{1}{2}}$ ft. At the NW cor. of the leg is a right-angle pit, llx17 ft., 7 ft. wide. The south leg is 7 ft. deep and the west leg averages 3 ft. deep. Value, \$300. A cut, the SE cor. of which bears N. 18°30' E., 1230 ft. dist from cor. No. 1 of the Trails End Mine lode; ll ft. wide, 3 ft. average depth and running N. 60° E., 40 ft. No. 3 Value, \$125. An open cut, the SE cor. of which bears N. 19030'E., 1338 ft. dist. from cor. No. 1 of the Trails End Mine lode; 38 ft. wide, 2½ ft. average depth and running N. 350 E., 65 ft. No. 4 Value, \$440. An open cut, the SW cor. of which bears N. 7°30' E., 1340 ft. from cor. No. 1 of the Trails End Mine lode; 7 ft. wide, 1 ft. average depth and running N. 7° E., 20 ft. Value, \$25. OTHER IMPROVEMENTS NONE OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA NONE

FIELD ASSISTANTS

Name Bill Donahue Capacity Chainman-Axeman

Chains	* CIRADO?	Sales D
	.cof 570 and hi beampefuni wavmra 5772	
	3.600 (1.10 1.20 1.70)	
	les angvo, of the trails find time late with its logsalon of knowed location as a the ground.	
	GENUTICE S. L.	
10-40-20	in the introvence of the value of the recoverable of the controverse o	
ode .s ca as 2 3, 500. k	ine discovery jt. of the india End Eine L Lie lote lige 140 ft. Iron a pt. on li	
onpl.	1. 1265 cor. 6. 2. Ular	
l ol the	As oben hat and hit, the of ears of the il by 190 B., 980 fs. wist from cor. No. rails and him loce; the suc is to is when a local of the on the As ears f. 700 b., 50 fs.; average outto lift I'll cor. of the leg is a right-angle of it. When the souts leg is 7 fs. As	. aa.
	west let avereren 71 f. doep. Colon	
and the	n odt, the s. com. of witch bears b. 18 ⁰ 30 ft. 110: from com. 10. 1 of the frails ledo: 11 is. wide, 3 is. average nepth a. 50° f., av is. Valu	€ .04
ngo lo s., mail land maps and me, s. 10.	in obel cit, the Si cor. of which oters A. 1535 ft. dist. from corres. I of the fine loce; 70 ft. dide, 2) ft. average running s. 75° i., of ft.	
pelatu bra	ad open eqs, the S. our. of which beers S. d. of the Trails S. d. o. l. of the Trails S. d. o. l. of the Trails S. d. o. l. o. the Trails of t	6 .01
. 3 S . au		
	STEEL VORTAL STEELO	
	alon Glottatiotal Lings faiths	
	AND LA TEMETITUS CVA	
	ENOS.	
	FIEDD ASSISTANCE	
Impecity Mainnan-Ireman	lers. a.cancu 111t	

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

-
24
V
_

CERTIFICATE OF SURVEYOR

45.1		<u>Aug. 19, , 19 61</u>
I,	Harvey W. Smith	
		······································
Minera		at in pursuance of an order received from the
	Cadastral Engineer May 8, 1961	, at Phoenix, Arizona
dated _	Aug. 8, 1961	, I have faithfully and correctly executed the survey of
the mir	ning claim of <u>Emanuel B. Wi</u>	illis
known	as the Trails End Mi	ine Lode (Lode, placer, or mill site)
situate	inGoldfield Mining Distr	rict, Secs. 3 & 34
Т	1 & 2 N, R. 7E,	G.&S.R.B.& Meridian, Arizona, and (State)
designa execute the Ma	ated as Survey No. <u>4570</u> , when when the description, and that half of Instructions for the Survey of the P	hich is represented in the foregoing field notes as having been said survey has been made in strict conformity with said order, Public Lands of the United States, and in the specific manner rther certify that the labor expended and improvements made
upon o	r for the benefit of thelode (Lode or placer	location(s) embraced in the said mining claim by
extent, portion	location, and itemized value thereof are sp	are fully stated in my report therein, and that the character, specified therein with particularity and full detail, and that no nents so credited to this claim has been included in the estimate
		21 Jehl- +
Scot	tsdale, Arizona (Place)	(Mineral Surveyor) Harvey W. Smith
	CERTIFICA	ATE OF APPROVAL
		Bureau of Land Management, Survey Office (Office)
		Phoenix, Arizona October 13 , 1961 (Place) (Date)
Th	e foregoing field notes of mineral survey N	No. <u>4570</u> , in
Secti	ons 3 & 34 , T. 1 & 2 N.	, R,
Ari	zona , executed by Harve (State) May 8, 1961	y W. Smith , Mineral Surveyor,
correct	order dated August 8, 1961 Amd.	he surveyor, the field notes and the survey therein described
		Raymond C. Cleghorn
-		Acting State Director
		(Title)
	CERTIFICA	ATE OF TRANSCRIPT
I d is a tru	CERTIFY that the foregoing transcript of field copy of the original field notes.	eld notes of the above described mineral survey No.


(Title)

UNITED STATES... DEPARTMENT OF THE INTERSOFT BUREAU OF LARD MANAGEMENT

9

CERTIFICATE OF SHRVEYEN

Moses Survived, hereby dealify upon boner that in parameter of an early averaged from the
The state of the s
to yourse and between glassical and fall Multiple and elements executed the mirvey of
and the second s
The first in which which is the control of the cont
The state of the s
ton and the second seco
designation as Survey No. 1857.2. which is represented in the integration find notes as larging bean exceeded by me and under my directions and the Land curvey has been against and contents with adduction and the Lands of the
upon or for the condition that the condition of the condi
distinguities of the control of the
AVOSTA TO BEAUTIFO
Turneds of Library and Advisor Committee Street Miller
The transfer of the state of th
The transfer of the second property of the second property and the second property of T
publish to the second of the s
accepted to material and the second s
properties to the state of the
accepted to material and the second s
As some the control of the first of the firs
And the state of t
An acres of the control of the contr
And some state of the first of
An acres of the control of the contr
And the state of t
An acres of the control of the contr
Allowed Shrivers of Shrivers o
And the state of t





United States Department of the Interior

BUREAU OF LAND MANAGEMENT State Office

3022 Federal Building Phoenix, Arizona 85025

B.L. M. LAND OFFICE

MAR 1 9 1971

10:00 A.M. PHOENIX, ARIZONA

March 18, 1971

Memorandum

To :

Land Office Manager, Arizona

From

State Director, Arizona

Subject:

Mineral Survey No. 4570

This memorandum cancels the survey of the Trails End Mine lode claim of Mineral Survey No. 4570. The following notation should be made on the plat of Mineral Survey No. 4570:

Survey of Trails End Mine lode claim cancelled by State Director's memorandum dated March 18, 1971.

The plat and field notes should remain in the files. This memorandum should be made a part of the original field notes.

Adverse proceedings were initiated against the claim on June 22, 1962, under Contest Number 10513. By Land Office Manager's Decision dated August 14, 1962, the Trails End Mine lode claim was declared null and void. No appeal from the Decision was filed during the time allowed, and Contest Number 10513 was closed August 14, 1962.

Mineral Survey No. 4570 does not appear on any subsisting plats. Application AR 021661 for purchase for Recreation and Public Purposes has been filed for a portion of the lands formerly embraced by the Trails End Mine lode claim of Mineral Survey No. 4570.

Le T. Tollini

cc: Director

Etnic of the Department of the Interio

B.L.M. LAND OFFICE

TERL S 1971

10:00 A.M. HOENIX, ARE

war is the market or a visit of the

single and the same

and the same of the same of the

The second section of the second seco

parente de la companya del companya del companya de la companya del companya de la companya del companya de la companya del co

The collection of the company of the collection of the collection

so inteller

de sito has