

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey Number

4571

State

Arizona

Land District

FIELD NOTES

Of the Survey of the Mining Claim of (Name & address of Claimant)

Cyprus Mines Corp.
1200 Pacific Mutual Bldg. c/o Victor H. Verity, Attorney
523 W. 6th St. 2207 E. Waverly St.
Los Angeles 14, California Tucson, Arizona

Known as the (Name of group, if any)

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Coronado	8-12-44	
Coronado No. 1	9-9-44	
Coronado No. 2	9-9-44	
Burro	9-8-27	
Burro No. 3	8-17-35	9-9-44 7-3-61
Mary Hope	7-9-41	9-9-44 7-3-61
Mason No. 1	8-21-26	7-3-61
Afterthought	11-11-58	7-3-61

Mining District Cochise		County Cochise	Section 25-26-35-36
Township 15S.	Range 22 E.	Meridian G.&S.R.B.&M.	Surveyed under order dated July 17, 1961
Survey commenced July 25, 1961	Survey completed Sept. 21, 1961	Name of Mineral Surveyor John H. Stitzer	

FIELD NOTES

Field Number

Date

Location

CONTENTS OF LOCATION DRAWN AND LOCATED IN POLYMER

DATE

SECTION

SECTION

COUNTY

SHOWED WITH LAND DRAW

SECTION

Name of Mineral Survey or

Survey or District

Survey or District

Chains-

1.

This survey was made with a Berger transit No. 32066, with horizontal limb $5 \frac{3}{8}$ ins. diam., having two double opposite verniers and a full vertical circle $4 \frac{3}{4}$ ins. diam.; having one double vernier; the verniers read to one minute of arc. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:

August 11, 1961, at Cor. No. 1 of the Burro lode, in latitude $32^{\circ}06'$ N., and longitude $110^{\circ}04'$ W., I make a series of six altitude observations upon the sun for azimuth at equal time intervals, three each with the telescope in direct and reversed positions, observing opposite limbs of the sun and reading the horizontal angle from U.S. Mineral Monument No. 1, which is 1723.6 ft. distant.

Mean time of observation 105th meridian standard time $7^{\text{h}} 54^{\text{m}}$ a.m.

Declination of sun at mean time of observation $15^{\circ}13'37''$

Mean observed vertical angle to sun's center $26^{\circ}50'15''$

Mean horizontal angle from reference point to sun's center $141^{\circ}01'40''$

True bearing to reference point N. $52^{\circ}45'$ W.

The lines were measured with a Lufkin steel tape 200 ft. in length, graduated every ft. All measurements were made with a spring balance keeping a uniform tension on the tape and all measurements made with the tape fully suspended; the tape was compared with a 100 ft. and 200 ft. standard at the time of beginning the survey and the necessary tension to measure exactly these distances were determined at that time.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $13^{\circ}30'$ E.

Feet

MASON NO. 1 LODE

At Cor. No. 1 of the Mason No. 1 lode, identical with Cor. No. 1 of the Coronado No. 1 lode of this survey.

Set a galvanized iron post 3 ft. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stones, with leaden cap mkd. MASON NO. 1 - COR. 1 - 4571 - CORONADO NO. 1 - COR. 1; from which

U. S. Mineral Monument No. 1 bears N. $11^{\circ}12'$ W., 151.7 ft. dist.; a redwood post 4 ins. sq., 7 ft. above the ground, surrounded by a mound of stones 3 ft. high.

Triangulation station F bears N. $19^{\circ}10'$ W., 199.6 ft. dist.; a $\frac{5}{8}$ ins. steel pin in concrete.

Thence N. $57^{\circ}20'$ E.

287.5 Lode line; discovery point bears S. $35^{\circ}28'30''$ E., 745 ft. dist.

Set a galvanized iron post 3 ft. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. MASON - NEC - 4571.

Chains Feet		2.
575.0	<p>Cor. No. 2, identical with NW Cor. Sur. No. 325 Golden Shield lode, an iron capped pipe, 2 ins. diam., 2 ft. above the ground mkd. NW COR-325-GOLDEN SHIELD</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S. 35°28'30" E.</p>	
563	Center of road, bears N. 55° E. and S. 55° W.	
810	Center of road, bears N. 45° E. and S. 45° W.	
1023	Junction of three small washes.	
1235	A fence, bears N. 88°30' E. and S. 88°30' W.	
1479.6	<p>Cor. No. 3, identical with Cor. No. 1 of the Burro lode and Cor. No. 1 of the Coronado lode, both of this survey.</p> <p>Set a galvanized iron post, 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. MASON NO. 1-COR. NO. 3-4571-BURRO-COR. NO.1-4571-CORONADO-COR. NO. 1-4571; from which</p> <p>SW Cor. Sur. No. 325 Golden Shield lode bears S. 20°19' W., 28.2 ft. dist.</p> <p>Thence S. 57°20' W.</p>	
23.1	Intersect West side line Sur. No. 325 Golden Shield lode at a point from which the SW. Cor. bears S. 34°35' E., 17.0 ft. dist.	
287.5	<p>Lode line; discovery point bears N. 35°28'30" W., 734.6 ft. dist.</p> <p>Set a galvanized post, 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. MASON NO. 1-SEC-4571-CORONADO-NEC-4571.</p>	
575.0	<p>Cor. No. 4, identical with Cor. No. 4 of the Coronado lode, Cor. No. 4 of the Mary Hope lode and Cor. No. 4 of the Coronado No. 1 lode, all of this survey.</p> <p>Set a galvanized post, 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with a leaden cap mkd. MASON NO. 1-COR. NO. 4-4571-CORONADO-COR. 4-4571-MARY HOPE-COR. 4-4571-CORONADO NO.1-COR. 4-4571; from which</p> <p>A corner of the location bears S. 43°45' E., 19.3 ft. dist.</p> <p>Thence N. 35°28'30" W.</p>	
640	Center of road, bears N. 70° E. and S. 70° W.	
1479.6	Cor. No. 1 and the place of beginning.	

Chains Feet	3.
	CORONADO NO. 1 LODE
	At Cor. No. 1 of the Coronado No. 1 lode, identical with Cor. No. 1 of the Mason No. 1 lode of this survey.
	Thence S. 57°20' W.
287.5	Lode line; discovery point bears S. 35°28'30" E., 1254.6 ft. dist.
	Set a galvanized iron post 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO NO. 1-NEC-4571.
472	A wash, 8 ft. wide, course SE.
575.0	Cor. No. 2
	Set a galvanized iron post 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO NO. 1-COR. NO. 2-4571.
	No local bearing objects or trees available.
	Thence S. 35°28'30" E.
936	A wash, 6 ft. wide, course NE.
1479.6	Cor. No. 3, identical with Cor. No. 1 of the Mary Hope lode of this survey.
	Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO NO. 1-COR. NO. 3-4571-MARY HOPE-COR. 1-4571; from which
	A corner of the location bears S. 11°18' E., 24.7 ft. dist.
	Thence N. 57°20' E.
174	A wash, 6 ft. wide, course southeasterly.
287.5	Lode line; discovery point bears N. 35°28'30" W., 225 ft. dist.
	Set a galvanized iron post 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO NO. 1-SEC-4571-MARY HOPE-NEC-4571.
478	A wash, 10 ft. wide, course southeasterly.
575.0	Cor. No. 4, identical with Cor. No. 4 of Mason No. 1 lode, Cor. No. 4 of the Mary Hope lode, Cor. No. 4 of Coronado lode, all of this survey.
	Thence N. 35°28'30" W.
640	Center of road, bears N. 70° E. and S. 70° W.
1479.6	Cor. No. 1 and the place of beginning.

Chains
Feet

BURRO LODE

At Cor. No. 1 of the Burro lode, identical with Cor. No. 1 of Coronado lode and Cor. No. 3 of Mason No. 1 lode, both of this survey; from which

U. S. Mineral Monument No. 1 bears N. $52^{\circ}45'$ W., 1723.6 ft. dist.; previously described.

SW. Cor. of Sur. No. 325 Golden Shield lode bears S. $20^{\circ}19'$ W., 28.2 ft. dist.

Thence S. $35^{\circ}28'30''$ E.

- 16.3 Intersect south end line of Sur. No. 325 Golden Shield lode from which the SE. Cor. bears N. $55^{\circ}42'$ E., 574.4 ft. dist.
- 1499.2 Cor. No. 2, identical with Cor. No. 2 of the Coronado lode, Cor. No. 1 of the Coronado No. 2 lode and Cor. No. 1 of the Burro No. 3 lode, all of this survey
- Set a galvanized iron post, 3 ft. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stones with a leaden cap mkd. BURRO-COR.2-4571-CORONADO NO. 2-COR.1-4571-BURRO NO. 3-COR. 1-4571-CORONADO-COR.2-4571; from which
- A corner of the location bears N. $35^{\circ}20'$ E., 11.0 ft. dist.
- Thence N. $57^{\circ}20'$ E.
- 287.5 Lode line; discovery point bears N. $35^{\circ}28'30''$ W., 1449.2 ft. dist.
- Set a galvanized iron post 3 ft. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. BURRO-SEC-4571-CORONADO NO. 2-NEC-4571.
- 569.3 Intersect west side line Sur. No. 326 Chicora lode, from which the NW. Cor. bears N. $39^{\circ}22'40''$ W., 1030.5 ft. dist.
- 580.4 Cor. No. 3, identical with Cor. No. 2 of Coronado No. 2 lode of this survey.
- This corner falls on a bank of loose earth where a permanent monument can not be established. Set a temporary stake; from which
- A witness corner bears N. $57^{\circ}20'$ E., 15.0 ft. dist., a galvanized iron post 3 ft. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stones mkd. WC-BURRO-COR. 3-4571-CORONADO NO. 2-COR.2-4571
- Thence N. $35^{\circ}41'$ W.
- 450 Center of road, bears S. 65° E. and N. 65° W.
- 668.6 Intersect line 4-1 of Afterthought lode of this survey.

Survey No. 4571

Chains Feet	
955	Center of road, bears N. 5° W. and S. 5° E.
1023.4	Intersect north line of Sur. No. 326 Chicora lode, identical with line 1-2 of Sur. No. 4314 Tenderfoot lode at a point from which the NW. Cor. of Sur. No. 326 Chicora lode bears S. 58°24'30" W., 77.7 ft. dist. and Cor. No. 2 Sur. No. 4314 Tenderfoot lode bears S. 58°24'30" W., 43.7 ft. dist.
1074.1	Intersect line 1-2 of Afterthought lode of this survey.
1499.5	Cor. No. 4, identical with SE. Cor. Sur. No. 325 Golden Shield lode, an iron capped pipe, 2 ins. diam., 2 ft. above ground, mkd. G.S.-S.E.-325; from which <p style="margin-left: 40px;">Cor. No. 1 Afterthought lode of this survey bears S. 21°16' E., 456.3 ft. dist.</p> <p style="margin-left: 40px;">Cor. No. 2 Sur. No. 4314 Tenderfoot lode bears S. 30°25' E., 474.9 ft. dist.</p> <p style="margin-left: 40px;">NW. Cor. Sur. No. 326 Chicora lode bears S. 26°19'30" E., 476.8 ft. dist.</p> <p style="margin-left: 80px;">Thence S. 57°20' W.</p>
200.0	Intersect line 2-3 Sur. No. 4314 Tenderfoot lode at a point from which Cor. No. 2 bears S. 53°35' E., 508.1 ft. dist.
287.5	Lode line; discovery point bears S. 35°28'30" E., 50.0 ft. dist. <p style="margin-left: 40px;">Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. BURRO-NEC-4571.</p>
575.0	Cor. No. 1 and place of beginning.

CORONADO LODE

	At Cor. No. 1 of the Coronado lode, identical with Cor. No. 1 of the Burro lode and Cor. No. 3 of the Mason No. 1 lode, both of this survey. <p style="margin-left: 40px;">Thence S. 35°28'30" E.</p>
16.3	Intersect south end line of Sur. No. 325 Golden Shield lode at a point from which the SW. Cor. bears S. 55°42' W., 23.4 ft. dist.
1499.2	Cor. No. 2, identical with Cor. No. 2 of the Burro lode, Cor. No. 1 of the Coronado No. 2 lode and Cor. No. 1 of the Burro No. 3 lode, all of this survey. <p style="margin-left: 40px;">Thence S. 57°20' W.</p>
287.5	Lode line; discovery point bears N. 35°28'30" W., 1359.2 ft. dist. <p style="margin-left: 40px;">Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO-SEC-4571-BURRO NO. 3-NEC-4571.</p>

7
Survey No. 4571

Chains- Feet 320	A wash, 18 ft. wide, course southeasterly	6.
575.0	Cor. No. 3, identical with Cor. No. 2 of the Burro No. 3 lode and Cor. No. 3 of the Mary Hope lode, both of this survey. Set a galvanized iron post 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO-COR: 3-4571-BURRO NO. 3-COR. 2-4571-MARY HOPE-COR. 3-4571; from which A corner of the location bears N. 57°20'E., 2.5 ft. dist. Cor. No. 3, Sur: No. 1800 Wolfram Queen lode bears S. 24°27' E., 383.0 ft. dist. Thence N. 35°28'30" W.	
58	A wash, 4 ft. wide, course northeasterly.	
411	A wash, 11 ft. wide, course southeasterly.	
1499.2	Cor. No. 4, identical with Cor. No. 4 of the Mary Hope lode, Cor. No. 4 of the Coronado No. 1 lode and Cor. No. 4 of the Mason No. 1 lode, all of this survey. Thence N. 57°20' E.	
287.5	Lode line; discovery point bears S. 35°28'30" E., 140.0 ft. dist. A galvanized iron pipe previously described.	
551.9	Intersect west side line of Sur. No. 325 Golden Shield lode at a point from which the SW. Cor. bears S. 34°35'E., 17.0 ft. dist.	
575.0	Cor. No. 1 and place of beginning.	

MARY HOPE LODE

	At Cor. No. 1 of the Mary Hope lode, identical with Cor. No. 3 of the Coronado No. 1 lode of this survey; from which U. S. Mineral Monument No. 1 bears N. 13°39'W., 1712.5 ft. dist. Thence S. 35°28'30" E.	
1499.2	Cor. No. 2 Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. MARY HOPE-COR. 2-4571; from which A corner of the location bears S. 6°31'E., 4.4 ft. dist. Cor. No. 4 Sur. No. 1800 Wolfram Queen lode bears S. 76°13'E., 200.4 ft. dist. Cor. No. 2 Sur. No. 1800 King lode bears S. 65°42'E., 200.9 ft. dist. Cor. No. 3 Sur. No. 1800 King lode bears S. 70°09'W., 273.6 ft. dist. Thence N. 57°20' E.	

Survey No. 4571

287.5	<p>Lode line; discovery point bears N. $35^{\circ}28'30''$ W., 883.2 ft. dist.</p> <p>Set a galvanized iron post 3 ft. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground and in a mound of stones, with leaden cap mkd. MARY HOPE-SEC-4571.</p>	7.
386	A wash, 1 ft. wide, course northerly.	
575.0	<p>Cor. No. 3, identical with Cor. No. 3 of Coronado lode and Cor. No. 2 of Burro No. 3 lode, both of this survey.</p> <p>Thence N. $35^{\circ}28'30''$ W.</p>	
58	A wash, 4 ft. wide, course northeasterly	
411	A wash, 11 ft. wide, course southeasterly	
1499.2	<p>Cor. No. 4, identical with Cor. No. 4 of the Coronado lode, Cor. No. 4 of the Coronado No. 1 lode and Cor. No. 4 of the Mason No. 1 lode, all of this survey.</p> <p>Thence S. $57^{\circ}20'$ W.</p>	
97	A wash, 10 ft. wide, course southeasterly	
287.5	<p>Lode line; discovery point bears S. $35^{\circ}28'30''$ E., 616 ft. dist.</p> <p>A galvanized iron post previously described.</p>	
401	A wash, 6 ft. wide, course southeasterly	
575.0	Cor. No. 1 and place of beginning.	
CORONADO NO. 2 LODE		
<p>At Cor. No. 1 of the Coronado No. 2 lode, identical with Cor. No. 1 of the Burro No. 3 lode, Cor. No. 2 of the Coronado lode and Cor. No. 2 of the Burro lode, all of this survey; from which</p> <p>U. S. Mineral Monument No. 1 bears N: $44^{\circ}43'10''$ W., 3186.7 ft. dist., previously described.</p> <p>Thence N. $57^{\circ}20'$ E.</p>		
287.5	<p>Lode Line; discovery point bears S. $35^{\circ}51'$ E., 225 ft. dist.</p> <p>A galvanized iron pipe, previously described.</p>	
569.3	Intersect the west side line Sur. No. 326 Chicora lode at a point from which the SW. Cor. bears S. $39^{\circ}22'40''$ E., 196.3 ft. dist.	
580.4	<p>Cor. No. 2, identical with Cor. No. 3 of Burro lode of this survey.</p> <p>Thence S. $36^{\circ}07'15''$ E.</p>	

Survey No. 4571

Chains Feet	
195.3	The SW. Cor. of Sur. No. 326 Chicora lode which is identical with the NW. Cor. Sur. No. 327 Southern lode.
520	A wash, 4 ft. wide, course southeasterly.
1098	A wash, 16 ft. wide, course northeasterly.
1274.4	Intersect north line of Section 36, T. 15 S., R. 22 E., State land at a point from which the NW. Cor. of Section 36 bears S. 89°56' W., 553.1 ft. dist.
1473.1	<p>Cor. No. 3</p> <p>Set a galvanized iron pipe 3 ft. long, 1½ ins. in diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO NO. 2-COR. 3-4571; from which</p> <p>The SW. Cor. of Sur. No. 327 Southern lode bears S. 7°56'30" W., 163.2 ft. dist.</p> <p>Cor. No. 2 Sur. No. 1966 St. George lode bears S. 48°54' W., 247.8 ft. dist.</p> <p>The 1/4 Sec. Cor. common to Secs. 25 and 36 bears N. 85°16' E., 1985.24 ft. dist.</p> <p>Thence S. 57°20' W.</p>
103.3	Intersect the west side line of Sur. No. 327 Southern lode at a point from which the NW. Cor. bears N. 31°29' W. 1275.7 ft. dist.
300.0	<p>Lode line; discovery point bears N. 35°51' W., 1247.7 ft. dist.</p> <p>Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO NO. 2-SEC-4571.</p>
597.1	<p>Cor. No. 4, identical with Cor. No. 4 Burro No. 3 lode of this survey.</p> <p>Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. CORONADO NO. 2-COR. 4-4571-BURRO NO. 3-COR. 4-4571; from which</p> <p>A corner of the location bears N. 69°30' E., 19.0 ft. dist.</p> <p>The NW. Cor. of Sec. 36 bears N. 19°10' W., 510.5 ft. dist.</p> <p>The SW. Cor. of Sec. 36 bears S. 1°46' W., 4812.4 ft. dist.</p> <p>Thence N. 35°28'30" W.</p>
287.3	Intersect west line of Section 36, T. 15 S., R. 22 E., State land at a point from which the NW. Cor. of Section 36 bears N. 0°12' W., 248.2 ft. dist.
1093	A wash, 12 ft. wide, course easterly.
1472.2	Cor. No. 1 and place of beginning.

Survey No. 4571

Chains Feet	
	9.
	BURRO NO. 3 LODE
	At Cor. No. 1 of the Burro No. 3 lode, identical with Cor. No. 1 of Coronado No. 2 lode, Cor. No. 2 of Burro lode and Cor. No. 2 of Coronado lode, all of this survey.
	Thence S. 57°20'W.
287.5	Lode line; discovery point bears S. 35°28'30" E. 280 ft. dist.
	A galvanized iron pipe previously described.
320	A wash, 18 ft. wide, course southeasterly.
575.0	Cor. No. 2, identical with Cor. No. 3 of the Mary Hope lode and Cor. No. 3 of the Coronado lode, both of this survey.
	Thence S. 35°28'30"E.
1472.2	Cor. No. 3
	Set a galvanized iron post 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. BURRO NO. 3-COR. 3-4571; from which
	A corner of the location bears S. 89°28'E., 13.4 ft. dist.
	Cor. No. 1 Sur. No. 4197 Calumet lode bears N. 37°46'E., 128.7 ft. dist.
	Thence N. 57°20'E.
63.07	Intersect line 1-2 of Sur. No. 4197 Calumet lode at a point from which Cor. No. 1 bears N. 20°50'E., 72.4 ft. dist.
153.1	Intersect line 4-1 of Sur. No. 4197 Calumet lode at a point from which Cor. No. 1 bears N. 69°10'W., 53.6 ft. dist.
287.5	Lode line; discovery point bears N. 35°28'30" W., 1192.2 ft. dist.
	Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. BURRO NO. 3-SEC-4571.
378.4	Intersect west line of Section 36, T. 15 S., R. 22 E., State land at a point from which the NW. Cor. of Section 36 bears N. 0°12'W., 588.3 ft. dist.
398	A wash, 3 ft. wide, course southeasterly.
575.0	Cor. No. 4, identical with Cor. No. 4 of Coronado No. 2 lode of this survey.
	Thence N. 35°28'30"E.

Chains Feet	
287.3	Intersect west line of Section 36, T. 15 S., R. 22 E., State land at a point from which the NW. Cor. of Section 36 bears N. 0°12'W., 248.2 ft. dist.
1093	A wash, 12 ft. wide, course easterly.
1472.2	Cor. No. 1 and place of beginning.
AFTERTHOUGHT LODGE	
At Cor. No. 1 of the Afterthought lode	
Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. AFTERTHOUGHT-COR. 1-4571; from which	
U. S. Mineral Monument No. 1 bears N. 60°11'38" W., 2330.1 ft. dist., previously described.	
A corner of the location bears S. 24°00'W., 12.8 ft. dist.	
The NW. Cor. of Sur. No. 326 Chicora lode bears S. 87°18'E., 46.0 ft. dist.	
Cor. No. 2 Sur. No. 4314 Tenderfoot lode bears N. 78°14'E., 76.6 ft. dist.	
Cor. No. 4 of the Burro lode of this survey bears N. 21°16'W., 456.3 ft. dist.	
Thence N. 46°01'E.	
57.9	Intersect line 2-3 Sur. No. 4314 Tenderfoot lode at a point from which Cor. No. 2 bears S. 53°35'E., 41.4 ft. dist.
114.8	Intersect line 3-4 Burro lode of this survey.
180	Center of road, bears N. 10°W. and S. 10°E.
302.95	Lode line; discovery point bears S. 51°58'E., 1362.5 ft. dist.
Set a galvanized iron post 3 ft. long, 1½ ins. diam. 12 ins. in the ground and in a mound of stones with leaden cap mkd. AFTERTHOUGHT-NEC-4571.	
383.1	Intersect south side line of Sur. No. 324 Republic lode at a point from which the SE. Cor. bears S. 53°33'E., 125.2 ft. dist.
456	Edge of tailing pond bears easterly and westerly.
587.8	Intersect line 4-1 Sur. No. 4314 Tenderfoot lode at a point from which Cor. No. 1 bears S. 53°35'E., 164.1 ft. dist.
605.9	Cor. No. 2
Set a galvanized iron post 3 ft. long, 1½ ins. diam. over a 6 ft. long drill steel rod driven into the mill	

Survey No. 4571

Chains Feet	<p>tailings upon which this corner is set with leaden cap mkd. AFTERTHOUGHT-COR. 2-4571; from which</p> <p>Cor. No. 1 Sur. No. 4314 Tenderfoot lode bears S. 47°16'E., 162.1 ft. dist.</p> <p>The NE. Cor. Sur. No. 326 Chicora lode bears S. 32°08'E., 155.9 ft. dist.</p>	11.
	<p>Cor. No. 5 Sur. No. 2764 Mayflower lode bears S. 27°25'E., 98.5 ft. dist.</p> <p>SE. Cor. Sur. No. 324 Republic lode bears S. 14°35'W., 236.73 ft. dist.</p>	
	<p>A corner of the location bears N. 5°E., 7.0 ft. dist.</p> <p>Thence S. 51°58'E.</p>	
88.5	<p>Intersect line 5-1 Sur. No. 2764 Mayflower lode at a point from which Cor. No. 5 bears S. 36°31'W., 40.9 ft. dist.</p>	
88.5	<p>Also intersect east end line of Sur. No. 324 Republic lode at a point from which the SE. Cor. bears S. 36°31'W., 217.2 ft. dist.</p>	
422	<p>Edge of tailings pond, bears northerly and southerly.</p>	
1493.1	<p>Intersect line 2-3 Sur. No. 2764 Mayflower lode at a point from which Cor. 3 bears S. 37°07'W., 28.0 ft. dist.</p>	
1497.5	<p>Cor. No. 3</p> <p>Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. AFTERTHOUGHT-COR. 3-4571; from which</p> <p>A corner of the location bears S. 14°E., 63.2 ft. dist.</p>	
	<p>Thence S. 46°01'W.</p>	
28.30	<p>Cor. No. 3 of Sur. No. 2764 Mayflower lode.</p>	
302.95	<p>Lode line; discovery point bears N. 51°58'W., 135 ft. dist.</p>	
	<p>Set a galvanized iron pipe 3 ft. long, 1½ ins. in diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. AFTERTHOUGHT-SEC-4571.</p>	
328.3	<p>Cor. No. 4 of Sur. No. 2764 Mayflower lode.</p>	
345.9	<p>Intersect east side line of Sur. No. 327 Southern lode at a point from which the NE. Cor. bears N. 32°45' W., 103.2 ft. dist.</p>	
605.9	<p>Cor. No. 4.</p>	

Chains Feet		12
	Set a galvanized iron pipe 3 ft. long, 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap mkd. AFTERTHOUGHT-COR. 4-4571; from which The NE. Cor. of Sur. No. 327 Southern lode bears N. 26°08'30" E., 297.8 ft. dist. Thence N. 51°58'W.	
171.6	Intersect the north end line of Sur. No. 327 Southern lode at a point from which the NE. Cor. bears N. 58°46'E., 311.6 ft. dist.	
1092.3	Intersect line 3-4 Burro lode of this survey.	
1218	Center of road bears southeasterly and northwesterly.	
1340.8	Intersect the west side line of Sur. No. 326 Chicora lode at a point from which the NW. Cor. bears N. 39°22'40" W., 122.1 ft. dist.	
1497.5	Cor. No. 1 and place of beginning.	

AREAS

	Acres
Total area, Mason No. 1 lode	19.508
Area in conflict with Sur. No. 325 Golden Shield lode	0.392
Total area, Coronado No. 1 lode	19.508
Total area, Burro lode	19.858
Area in conflict with Sur. No. 325 Golden Shield lode	0.108
Sur. No. 326 Chicora lode	1.041
Sur. No. 4314 Tenderfoot lode	1.328
Sur. No. 4314 Tenderfoot lode exclusive of its conflict with Sur. No. 325 Golden Shield lode	1.315
Afterthought lode of this survey	0.529
Afterthought lode of this survey exclusive of its conflict with	
(1) Sur. No. 326 Chicora lode	0.137
(2) Sur. No. 4314 Tenderfoot lode	0.477
(3) Sur. Nos. 326 and 4314 Chicora and Tenderfoot lodes	0.085
Total area, Coronado lode	19.766
Area in conflict with Sur. No. 325 Golden Shield lode	0.009
Total area, Mary Hope lode	19.766
Total area, Coronado No. 2 lode	19.874
Area in conflict with Sur. No. 326 Chicora lode	0.025
Sur. No. 327 Southern lode	1.512
State Land, Section 36, T. 15 S., R. 22 E.,	4.894
State Land, Section 36, T. 15 S., R. 22 E., exclusive of its conflict with Sur. No. 327 Southern lode	4.405
Total area, Burro No. 3 lode	19.410
Area in conflict with State Land, Section 36, T. 15 S., R. 22 E.,	0.648
Sur. No. 4197 Calumet lode	0.045

Survey No. 4571

Chains
Feet

13.

Total Area, Afterthought lode	20.628 -
Area in conflict with	
Sur. No. 324 Republic lode	0.536 -
Sur. No. 326 Chicora lode	12.469 -
Sur. No. 326 Chicora lode exclusive of its conflict with	
Sur. No. 324 Republic lode	12.467 -
Sur. No. 327 Southern lode	0.876 -
Sur. No. 2764 Mayflower lode	5.891 -
Sur. No. 4314 Tenderfoot lode	1.233 -
Sur. No. 4314 Tenderfoot lode exclusive of its conflict with	
(1) Sur. No. 324 Republic lode	0.733 -
(2) Sur. No. 2764 Mayflower lode	1.184 -
(3) Sur. No. 324 Republic lode and Sur. No. 2764 Mayflower lode	.684 -

LOCATION

This survey is located in the SW 1/4 Sec. 25, Sec. 26, NE 1/4 Sec. 35 and NW 1/4 Sec. 36 of T. 15 S., R. 22 E. G. & S. R. B. & M., Cochise County, Arizona.

The survey of all of these claims falls within the location as marked on the ground. Cor. Nos. 2 and 3 of Mason No. 1 lode are identical with corners of the location. Cor. No. 4 of Burro lode is identical with the corner of the location and Cor. No. 3 of the Coronado No. 2 lode is identical with the corner of the location.

EXPENDITURES

The improvements and the value of labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows:

- No. 1 The discovery point of the Mason No. 1 lode is on the lode line 745 ft. from a point on line 1-2, 287.5 ft. from Cor. No. 1
No value.
- No. 2 A shaft, the center of which bears N. 70°30'E., 70 ft. from Cor. No. 1 Mason No. 1 lode; 4 x 5 ft., 10 ft. deep.
Value, \$200.
- No. 3 A cut, 4 ft. wide, the face of which bears S. 66° E., 40 ft. from Cor. No. 1 Mason No. 1 lode; runs N. 31°E., 25 ft. to a 5 ft. face.
Value, \$180.
- No. 4 A cut 6 ft. wide, the face of which bears S. 24°E., 780 ft. from Cor. No. 2 Mason No. 1 lode; runs N. 39°W., 25 ft. to a 5 ft. face.
Value, \$280.
- No. 5 The discovery shaft of the Mason No. 1 lode, the center of which bears S. 20°35'E., 762 ft. from Cor. No. 2 Mason No. 1 lode; 8x8 ft., 10 ft. deep.
Value, \$475.

Chains

14.

- ✓ No. 1 The discovery point of the Coronado No. 1 lode is on the lode line 1254.6 ft. from a point on line 1-2, 287.5 ft. from Cor. No. 1.
No value.
- ✓ No. 2 The discovery shaft of the Coronado No. 1 lode, the center of which bears N. 17°05'E., 345 ft. from Cor. No. 3 Coronado No. 1 lode; 6x6 ft., 5 ft. deep.
Value, \$150.
- ✓ No. 3 A shaft, the center of which bears S 72°55'E., 242 ft. from Cor. No. 2 Coronado No. 1 lode; 4x6 ft., 4 ft. deep.
Value, \$120.
- ✓ No. 4 A shaft, the center of which bears S. 67°45'E., 261 ft. from Cor. No. 2 Coronado No. 1 lode; 4x8 ft., 5 ft. deep.
Value, \$130.
- ✓ No. 5 A shaft, the center of which bears S. 62°40'E., 255 ft. from Cor. No. 2 Coronado No. 1 lode; 4x8 ft., 5 ft. deep.
Value, \$130.
- ✓ No. 1 The discovery point of the Burro lode is on the lode line 50 ft. from a point on line 4-1, 287.5 ft. from Cor. No. 1.
No value.
- ✓ No. 2 The discovery shaft of the Burro lode, the center of which bears N. 20°25'W., 193 ft. from Cor. No. 2 Burro lode; 4x5 ft., 4 ft. deep.
Value, \$130.
- ✓ No. 3 A drill hole, bears S. 7°50'E., 468 ft. from Cor. No. 4 Burro lode; depth 203 ft.
Value, \$2030.
- ✓ No. 4 A drill hole, bears S. 14°15'E., 678 ft. from Cor. No. 4 Burro lode; depth 343 ft.
Value, \$3430.
- ✓ No. 5 A drill hole, bears S. 23°30'E., 840 ft. from Cor. No. 4 Burro lode; depth 373 ft.
Value, \$3730.
- ✓ No. 6 A drill hole, bears S. 27°00'E., 1032 ft. from Cor. No. 4 Burro lode; depth 312 ft.
Value, \$3120.
- ✓ No. 7 A drill hole, bears S. 29°45'E., 1221 ft. from Cor. No. 4 Burro lode; depth 264 ft.
Value, \$2640.
- No. 8 A drill hole, bears S. 30°35'E., 710 ft. from Cor. No. 4 Burro lode; depth 258 ft.
Value, \$2580.
- No. 9 A drill hole, bears S. 33°20'E., 910 ft. from Cor. No. 4 Burro lode; depth 384 ft.
Value, \$3840.

Survey No. 4571

Chains	15.
No. 10	An open pit mine, the approximate center of which bears N. 70°W., 400 ft. from Cor. No. 3 Burro lode. Value, \$15,000.
No. 1	The discovery point of the Coronado lode is on the lode line 140 ft. from a point on line 4-1, 287.5 ft. from Cor. No. 1. No value.
No. 2	The discovery shaft of the Coronado lode, the center of which bears S. 16°55'W., 252 ft. from Cor. No. 1 Coronado lode; 6x6 ft., 8 ft. deep. Value, \$210.
No. 3	A shaft, the center of which bears S. 10°15'W., 275 ft. from Cor. No. 1 Coronado lode; 4x6 ft., 8 ft. deep. Value, \$140.
No. 4	A shaft, the center of which bears S. 16°35'W., 318 ft. from Cor. No. 1 Coronado lode; 4x8 ft., 40 ft. deep. Value, \$1400.
No. 5	A shaft, the center of which bears S. 13°25'W., 388 ft. from Cor. No. 1 Coronado lode; 6x6 ft., 5 ft. deep. Value, \$130.
No. 6	An inclined shaft, the center of which bears N. 45°15'W., 742 ft. from Cor. No. 2 Coronado lode; 8x10 ft., 100 ft. deep. Value, \$9,000.
No. 7	A shaft, the center of which bears N. 46°20'W., 695 ft. from Cor. No. 2 Coronado lode; 4x6 ft., 5 ft. deep. Value, \$120.
No. 8	A shaft, the center of which bears N. 47°15'W., 636 ft. from Cor. No. 2 Coronado lode; 4x6 ft., 8 ft. deep. Value, \$150.
No. 9	An inclined shaft, the center of which bears N. 47°25'W., 612 ft. from Cor. No. 2 Coronado lode; 8x10 ft., 100 ft. deep. Value, \$9,000.
No. 10	A cut 6 ft. wide, the face of which bears N. 53°15'W., 450 ft. from Cor. No. 2 Coronado lode; runs N. 45°E., 20 ft. to a 6 ft. face. Value, \$250.
No. 11	A shaft, the center of which bears N. 61°W., 37 ft. from Cor. No. 2 Coronado lode; 4x6 ft., 5 ft. deep. Value, \$120.
No. 1	The discovery point of the Mary Hope lode is on the lode line 616 ft. from a point on line 4-1, 287.5 ft. from Cor. No. 1. No value.

17

Survey No. 4571

Chains	16.
No. 2	The discovery cut 10 ft. wide of the Mary Hope lode, the face of which bears S. $14^{\circ}05'$ E., 660 ft. from Cor. No. 4 Mary Hope lode; runs S. 45° E., 10 ft. to a 10 ft. face. Value, \$500.
No. 1	The discovery point of the Coronado No. 2 lode is on the lode line 225 ft. from a point on line 1-2, 287.5 ft. from Cor. No. 1. No. value.
No. 2	The discovery shaft for the Coronado No. 2 lode, the center of which bears S. 85° E., 360 ft. from Cor. No. 1 Coronado No. 2 lode; 5x5 ft., 5 ft. deep. Value, \$100.
No. 3	A cut 12 ft. wide and adit, the face of which bears N. $57^{\circ}35'$ W., 755 ft. from Cor. No. 3 Coronado No. 2 lode; runs south 25 ft. to a 15 ft. face from which an adit 4x5 ft. runs 15 ft. to breast. Value, \$710.
No. 4	A shaft, the center of which bears N. $69^{\circ}45'$ W., 595 ft. from Cor. No. 3 Coronado No. 2 lode; 6x8 ft., 50 ft. deep. Value, \$4,500.
No. 5	A cut 12 ft. wide and inclined shaft, the face of which bears S. $45^{\circ}45'$ E., 145 ft. from Cor. No. 1 Coronado No. 2 lode; runs N. 20° E., 40 ft. to a 20 ft. face at which point an inclined shaft 4x6 ft., 15 ft. deep. Value, \$2,000.
No. 6	A cut 8 ft. wide, the face of which bears S. $74^{\circ}15'$ E., 133 ft. from Cor. No. 1 Coronado No. 2 lode; runs N. 20° E., 20 ft. to a 10 ft. face. Value, \$300.
No. 1	The discovery cut of the Burro No. 3 lode, the center of which is the discovery point, is on the lode line 280 ft. from a point on line 1-2, 287.5 ft. from Cor. No. 1; 6 ft. wide runs South 20 ft. to 8 ft. face. Value, \$350.
No. 2	A shaft, the center of which bears S. $43^{\circ}05'$ E., 776 ft. from Cor. No. 2 Burro No. 3 lode; 6x6 ft., 5 ft. deep. Value, \$150.
No. 3	A shaft, the center of which bears S. $41^{\circ}35'$ E., 835 ft. from Cor. No. 2 Burro No. 3 lode; 6x6 ft., 5 ft. deep. Value, \$150.
No. 1	The discovery shaft of the Afterthought lode, the center of which is the discovery point is on the lode line 1362.5 ft. from a point on line 1-2, 302.95 ft. from Cor. No. 1; 5x5 ft., 5 ft. deep. Value, \$120.
No. 2	A drill hole bears N. $64^{\circ}00'$ E., 232 ft. from Cor. No. 1 Afterthought lode; depth 361 ft. Value, \$3,610.
No. 3	A drill hole bears S. $68^{\circ}00'$ E., 66 ft. from Cor. No. 1 Afterthought lode; depth 241 ft. Value, \$2,410.

Survey No. 4571

Chains

17.

OTHER IMPROVEMENTS

A concrete powder magazine, the North Cor. of which bears S. 21°15'E., 495 ft. from Cor. No. 1 Coronado lode; 21x11 ft. in size; the long side bears N. 57°E. Claimant herein.

A water tank, the center of which bears N. 79°20'E., 200 ft. from Cor. No. 1 Mason No. 1; 25 ft. diam. Claimant herein.

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

Sur. No. 324 Republic lode; the SW. and SE. Cors. have been replaced by 2" iron capped pipes, 2 ft. above the ground and properly mkd. The south side line was found to bear N. 53°33'W., instead of N. 53°27'W. as approved. The NE. Cor. is covered by tailings. Direction of this line determined by south end center of Sur. No. 4314 Rough Rider lode, a 2" iron capped pipe in the tailings pond. The east end line as determined above was found to bear S. 36°31'W., instead of S. 36°33'W., as approved.

Sur. No. 325 Golden Shield lode; the SE. and NW. Cors. have been replaced by iron capped pipes, 2 ft. above the ground and properly mkd. The SW. Cor. is the original 4x4 in. post set in a mound of stones, properly mkd. The West side line was found to be N. 34°35'W., 1495.7 ft. instead of N. 34°27'W., 1500 ft. as approved. The south end line was found to be S. 55°42'W., 597.8 ft. instead of S. 55°33'W., 600 ft. as approved. Tie from Cor. No. 1 to U. S. Mineral Monument No. 1 was found to be S. 72°31'W., 538.3 ft. instead of S. 72°18'W., 548 ft. as approved.

Sur. No. 326 Chicora lode; the NW. and NE. Cors. have been replaced with 2 in. iron capped pipes properly mkd., the SE. Cor. is the original 4x4 in. post in a mound of stones, markings have been eroded. The SW. Cor. was missing and reset by me at the record distance of Sur. No. 327 Southern lode. The west side line was found to be N. 39°22'40"W., 1226.8 ft., instead of N. 39°27'W., 1230 ft. as approved. The north end line was found to be N. 58°24'30" E., 555.2 ft. instead of N. 58°30' E., 557.5 ft. as approved. The east side line was found to be S. 39°59'30"E., 1232.2 ft., instead of S. 40°04'E., 1233 ft. as approved. The south end line was found to be S. 58°46'W., 579.5 ft. instead of S. 58°30'W., 579.5 ft. as approved.

Sur. No. 327 Southern lode; the NE. and SW. Cors. are 4x4 in. posts set in mounds of stone, markings are eroded but barely readable. SE. Cor. has been replaced by a 2 in. diam. lead capped pipe, 2 ft. above the ground. The NW. Cor. was missing and I reestablished by record distance from the NE. Cor. and SW. Cor. The east side line bears S. 32°45'E., instead of S. 32°38'E., as approved. The west side line bears N. 31°29'W., instead of N. 31°30'W., as approved. The north end line bears N. 58°46'E., instead of N. 58°30'E., as approved.

Sur. No. 1800 Wolfram Queen lode; Cor. No. 3 and 4 are granite stones, firmly set and properly marked.

Sur. No. 1800 King lode; Cors. No. 2 and 3 are granite stones, firmly set and properly marked.

Sur. No. 1966 St. George lode; Cor. No. 2 was temporarily reset by record dist. and bearing as given on plat of Sur. No. 4197, this line being witnessed by line 1-5 Hagerman lode.

Chains

Sur. No. 2764 Mayflower lode; Cor. No. 1 is missing. Cor. No. 2 is partially destroyed, a 4x4 in. post was found laying alongside a mound of stones; bearings were taken to the center of the mound. Cor. No. 3 is a 4x4 in. post in a mound of stones. The W.C. to Cor. No. 4 is partially preserved by one half of the concrete base which was poured around the original 4x4 in. post. Cor. No. 5 has been replaced by an iron capped 2 ins. diam. pipe. Line 2-3 bears S. 37°07'W., instead of S. 36°37'W., as approved. Line 3-4 is found to be approximately correct as approved. Line 4-5 was found to be N.40°10'45"W., 1391.7 ft., instead of N. 40°18'W., 1394.7 ft. as approved.

Sur. No. 4197 Calumet lode; Cors. No. 1, 2 and 4 are 2 ins. diam. leaden capped pipes set in mound of stones. Bearings of lines 1-2 and 1-4 were found to be correct as approved.

Sur. No. 4314 Tenderfoot lode; Cors. No. 1, 2 and 3 are 2 ins. diam. iron capped pipes firmly set and properly mkd. Line 1-2 was found to be S. 58°24'30" W., 563.3 ft., instead of S. 58°30'W., 563.3 ft. as approved. Line 2-3 was found to bear N. 53°33'W., instead of N. 53°24'W., as approved.

The NW. Cor. of Section 36, T. 15 S., R. 22 E., was missing and was re-established by me using the ties to Sur. No. 327 Southern lode as given in the field notes of the survey of T. 15 S., R. 22 E., as collateral evidence of its location. I set a galvanized iron pipe, 3 ft. long 1½ ins. diam., 12 ins. in the ground and in a mound of stones with leaden cap appropriately mkd.

The north 1/4 Cor. of Section 36, T. 15 S., R. 22 E., is a limestone in place and plainly mkd. 1/4 on the north face as per the field notes.

The SW. Cor. of Section 36, T. 15 S., R. 22 E., is a granite stone mkd. C.C. on the north face as per the field notes.

The 1/4 Section Cor. common to Sections 25 and 26 is buried under the mill tailings pond and presumably lost.

FIELD ASSISTANTS

Name

Capacity

Martin Cole

Chainman

Fernando Pacheco

Chainman and rodman

Harold McKernan

Chainman

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

October 17, 1961

I, John H. Stitzer,
Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____
Cadastral Engineer, at Phoenix, Arizona

dated July 17, 1961, I have faithfully and correctly executed the survey of

the mining claim of Cyprus Mines Corp, known as the Coronado lode, Coronado No. 1
lode, Coronado No. 2 lode, Burro lode, Burro No. 3 lode, Mary Hope lode,
known as the Mason No. 1 lode and Afterthought lode
(Lode, placer, or mill site)

situate in Sections 25, 26, 35 and 36

T. 15 S., R. 22 E., G. & S. R. P. & _____ Meridian, Arizona, and
(State)

designated as Survey No. 4571, which is represented in the foregoing field notes as having been
executed by me and under my direction, and that said survey has been made in strict conformity with said order,
the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
described in the foregoing field notes, and I do further certify that the labor expended and improvements made
upon or for the benefit of the lode location(s) embraced in the said mining claim by
(Lode or placer)

claimant(s) or its grantors are fully stated in my report therein, and that the character,
extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
of expenditures upon any other claim.

Tucson, Arizona
(Place)

John H. Stitzer
(Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management, Survey Office
(Office)

Phoenix, Arizona February 2, 1962
(Place) (Date)

The foregoing field notes of mineral survey No. 4571, in Cochise Mining District

Secs. 25, 26, 35 & 36, T. 15 S., R. 22 E., G. & S. R. Meridian,

Arizona, executed by John H. Stitzer, Mineral Surveyor,
(State)

under order dated July 17, 1961, having been critically examined and the necessary
corrections made prior to their certification by the surveyor, the field notes and the survey therein described
are hereby approved.

Fred J. Weiler
Fred J. Weiler

State Director
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

I, the undersigned, being duly sworn, hereby certify upon honor that in pursuance of an order received from the
Department of the Interior at _____
dated _____ I have faithfully and correctly executed the survey of
the mining claim of _____ known as the _____
situated in _____
T. _____ S. _____ R. _____
and _____
designated as Survey No. _____ which is represented in the foregoing field notes as having been
executed by me and under my direction and that said survey has been made in accordance with said order
the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
specified in the foregoing field notes, and I do further certify that the labor expended and improvements made
upon the land for the benefit of the _____
location(s) embraced in the said mining claim by
_____ grants are fully stated in my report therein, and that the character,
extent, location and estimated value thereof are specified therein with particularity and full detail, and that no
portion of or interest in said labor and improvements so specified in the aforesaid report has been included in the estimate
of expenses upon the said claim.

[Handwritten Signature]

CERTIFICATE OF APPROVAL

The foregoing field notes of mineral survey No. _____
situated in _____
T. _____ S. _____ R. _____
and _____
executed by _____
Mineral Surveyor _____
under date dated _____, having been critically examined and the necessary
corrections made prior to their certification by the surveyor, the field notes and the survey therein described
are hereby approved.

[Handwritten Signature]

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
Arizona State Office
3022 Federal Building
Phoenix, Arizona 85025

IN REPLY REFER TO

9183.1 (942)
M.S. #4571

*MS Plat ✓
Index Card ✓
Status Plat ✓*
April 24, 1974

Memorandum

To : Chief, Branch of Records & Data Management (952) *155 YVE*
From : State Director, Arizona
Subject: Mineral Survey No. 4571

This memorandum cancels the survey of the following lode claims of Mineral Survey No. 4571:

Coronado No. 1
Mary Hope

The following notation should be made on the plat of Mineral Survey No. 4571:

"Survey of the Coronado No. 1 and Mary Hope lode claims cancelled by State Director's memorandum dated April 24, 1974."

The plat and field notes should remain in the files. This memorandum should be made a part of the original field notes.

By letter dated March 23, 1973, W. J. Rundle, Vice President of Cyprus Mines Corporation, P. O. Box 4368, Tucson, Arizona, requested that we cancel that portion of Mineral Survey No. 4571 under which the Coronado No. 1 and Mary Hope lode claims were surveyed.

The above mining claims are scheduled for disposal under PX Application A 7840.

Shirley H. Ramboches
ACTING

cc: Director (420)



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
Arizona State Office
5001 National Building
Phoenix, Arizona 85004

April 2, 1975

To : Chief, South of Records & Data Management (S-10)
From : State Director, Arizona
Subject : Mineral Survey No. 4111

This document contains the survey of the following lands of
Mineral Survey No. 4111:

Section 10, T. 1 N., R. 1 E.,
County of Coconino, Arizona

The following reservation should be made on the title of Mineral Survey
No. 4111:

Survey of the Coconino Co., Arizona, by the late
Mineral Survey No. 4111, as amended, dated April 22,
1975.

The title and other notes should remain in the title. The reservation
should be made a part of the original title notes.

By letter dated April 22, 1975, W. J. Lusk, the Director of Coconino
County, Arizona, advised that he
has the position of Mineral Survey No. 4111 under title the Coconino
Co., Arizona, and that the same is correct.

The reservation of title is requested for the title of Mineral Survey
No. 4111.

State Director (S-10)