

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey Number

4593

State

ARIZONA

Land District

ARIZONA

FIELD NOTES

Of the Survey of the Mining Claim of (Name & address of Claimant)

Frank Melluzzo and G. H. Seebold
1009 E. Hatcher Rd.
Sunnyslope, Arizona

Known as the (Name of group, if any)

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
New Strike Nos. 1, 2 & 3	7/16/35	
New Strike No. 4	8/20/35	
New Strike No. 5	8/21/35	
New Strike No. 6	9/28/35	
New Strike No. 7	10/8/37	

Mining District Walker		County Yavapai		Section 17 & 20
Township 13 N.	Range 1 W.	Meridian G. & S. R. B. & M.		Surveyed under order dated 4/17/62
Survey commenced 4/17/62	Survey completed 5/15/62	Name of Mineral Surveyor Harvey W. Smith		

FIELD NOTES

1

Section Name

Date

Field Number

Location

Notes

Notes

Date	Location	Notes
10/15/80
10/16/80
10/17/80
10/18/80
10/19/80

Prepared by

Checked by

Date

SURVEY NO. 4593

CHAINS

Feet

This survey was made with a K. & E. transit No. 51591, with horizontal limb 5.5 ins. diam., having two double opposite verniers, and full vertical circle 4.5 ins. diam., having one double vernier; the verniers read to one minute of arc; the instrument is equipped with a colored-eye-shade to be attached for making direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian established by direct observation on the sun. At 8:40 A. M. on April 18, 1962 at Cor. No. 1 of the New Strike No. 1 lode; latitude $34^{\circ}30'10''$ North, longitude $112^{\circ}23'28''$ West, turning from a reference pt. about 300 ft. in a west direction clockwise to the sun in an east direction.

True bearing of reference pt:

N. $81^{\circ}28'30''$ W.

The lines were measured with a Lufkin steel tape, 300 ft. in length, graduated every ft. for 299 ft. and the remaining foot graduated to tenths and hundredths. The tape was compared to a standard at the beginning of the survey and found to be correct. All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $13^{\circ}45'$ East.

NEW STRIKE NO. 1 LODE

At Cor. No. 1 of the New Strike-No. 1 lode; on line 3-4, New Strike No. 4 lode of this survey.

Set a galvanized iron post, $\frac{3}{4}$ in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS1 1 X; from which

The Cor. of secs. 17, 18, 19 & 20, T.13N.

R.1W., G. & S. R. B. & M., bears

S. $57^{\circ}10'10''$ W., 1896.37 ft. dist.;

an iron post, 2 ins. diam., set,

marked and witnessed as described in the official record.

A mound of stones constructed adjacent to the iron post.

Thence N. $14^{\circ}28'45''$ W.

- 685.0 Right bank local drainage, 20 ft. wide, course N. 26° E.
 715.0 Unimproved dirt road bears N. 26° E. and S. 26° W.
 1390.0 Unimproved dirt road bears S. 85° E. and N. 85° W.
 1430.0 Cor. No. 3, New Strike No. 4 lode of this survey.
 1500.0 Cor. No. 2, identical with Cor. No. 1 of the New Strike No. 3 lode of this survey.

Chain	Feet	
		Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly set within the iron post, mkd. MS. 4593 NS1 2 NS3 1 X; from which The cor. of Secs. 17, 18, 19 & 20, T. 13N., R. 1W., G. & S. R. B. & M. bears S. 26° 09' 35" W., 2,763.57 ft. dist.; previously described. A mound of stones constructed adjacent to the iron post. Thence N. 75° 31' 15" E.
	300.0	Lode line; discovery pt. bears S. 14° 28' 45" E., 600 ft. dist.
	600.0	Cor. No. 3 identical with Cor. No. 4 of the New Strike No. 3 lode and on line 1-2 of the New Strike No. 6 lode, both of this survey. Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS1 3 NS3 4 X; from which A mound of stones constructed adjacent to the iron post. Thence S. 14° 28' 45" E.
	285.0	Unimproved dirt road bears N. 56° E. and S. 56° W.
	295.0	Left bank local drainage, 20 ft. wide, course N. 56° E.
	650.0	Cor. No. 1 of the New Strike No. 6 lode identical with Cor. No. 2 of the New Strike No. 7 lode, both of this survey.
	1500.0	Cor. No. 4 identical with Cor. No. 3 of the New Strike No. 2 lode and on line 1-2 of the New Strike No. 7 lode; both of this survey. Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS1 4 NS2 3 X; from which A mound of stones constructed adjacent to the iron post. Thence S. 75° 31' 15" W.
	300.0	Lode line, discovery pt. bears N. 14° 28' 45" W., 900.0 ft. dist.
	600.0	Cor. No. 1 and the place of beginning.
NEW STRIKE No. 2 LODE		
		At Cor. No. 1 of the New Strike No. 2 lode, on line 3-4 of the New Strike No. 5 lode of this survey.

Chains Feet	
	Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS2 1 X; from which
	The Cor. of secs. 17, 18, 19 & 20, T.13N., R. 1W., G. & S. R. B. & M. bears N. 77° 50' 20" W., 2013.71 ft. dist.; previously described.
	A mound of stones constructed adjacent to the iron post.
	Thence N. 14° 28' 45" W.
740.0	Right bank Benjamin Gulch, 20 ft. wide, course N. 62° E.
1430.0	Cor. No. 3 of the New Strike No. 5 lode identical with Cor. No. 4 of the New Strike No. 4 lode; both of this survey.
1500.0	Cor. No. 2, identical with Cor. No. 1 of the New Strike No. 1 lode, on line 3-4 of the New Strike No. 4 lode; both of this survey; previously described.
	Thence N. 75° 31' 15" E.
300.0	Lode line; discovery pt. bears S. 14° 28' 45" E., 300.0 ft. dist.
600.0	Cor. No. 3 identical with Cor. No. 4 of the New Strike No. 1 lode, on line 1-2 of the New Strike No. 7 lode; both of this survey; previously described.
	Thence S. 14° 28' 45" E.
450.0	Left bank Benjamin Gulch, 20 ft. wide, course N. 70° E.
650.0	Cor. No. 1 of the New Strike No. 7 lode of this survey.
1500.0	Cor. No. 4
	Set a galvanized iron post, 3/4 ins. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS2 4 X; from which
	A mound of stones constructed adjacent to the iron post.
	Thence S. 75° 31' 15" W.
300.0	Lode line; discovery pt. bears N. 14° 28' 45" W., 1200.0 ft. dist.
600.0	Cor. No. 1 and the place of beginning.
	<hr/>
	NEW STRIKE NO. 3 LODE
	Beginning at Cor. No. 1 of the New Strike No. 3 lode, identical with Cor. No. 2 of the New Strike No. 1 lode of this survey; previously described.
	Thence N. 14° 28' 45" W.

Chains Feet	
770.0	Right bank local drainage, 10 ft. wide, course N. 75°E.
1500.0	Cor. No. 2 Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS3 2 X; from which A mound of stones constructed adjacent to the iron post. Thence N. 75°31'15" E.
300.0	Lode line; discovery pt. bears S. 14°28'45" E., 1300.0 ft. dist.
600.0	Cor. No. 3 Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened, within the iron post, mkd MS 4593 NS3 3 X; from which A mound of stones constructed adjacent to the iron post. Thence S. 14°28'45" E.
650.0	Cor. No. 2 of the New Strike No. 6 lode of this survey.
690.0	Left bank local drainage, 10 ft. wide, course N. 60°E.
1500.0	Cor. No. 4 identical with Cor. No. 3 of the New Strike No. 1 lode and on line 1-2 of the New Strike No. 6 lode, both of this survey; previously described. Thence S. 75°31'15" W.
300.0	Lode line; discovery pt. bears N. 14°28'45" W., 200.0 ft. dist.
600.0	Cor. No. 1 and the place of beginning.
	NEW STRIKE NO. 4 LODE
	At Cor. No. 1 of the New Strike No. 4 lode, identical with Cor. No. 2 of the New Strike No. 5 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS4 1 NS5 2 X; from which The Cor. of secs. 17, 18, 19 & 20, T.13N. R.1W., G. & S. R. B. & M. bears S. 51°48'20" W., 1,310.57 ft. dist.; previously described. A wooden post, 4 ins. diam., 4 ft. above ground set adjacent to the iron post. Thence N. 14°28'45" W.

SURVEY NO. 4593

6

5

Chain Feet	Description
1010.0	Unimproved dirt road bears N. 15° E. and S. 15° W.
1500.0	Cor. No. 2 Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS4 2 X; from which A mound of stones constructed adjacent to the iron post. Thence N. 75° 31' 15" E.
300.0	Lode line; discovery pt. bears S. 14° 28' 45" E., 1300 ft. dist.
600.0	Cor. No. 3 on line 1-2 of the New Strike No. 1 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS4 3 X; from which A mound of stones constructed adjacent to the iron post. Thence S. 14° 28' 45" E.
840.0	Unimproved dirt road bears S. 85° E. and N. 85° W.
715.0	Unimproved dirt road bears N. 26° E. and S. 26° W.
725.0	Left bank local drainage, 20 ft. wide, course N. 26° E.
1430.0	Cor. No. 1 of the New Strike No. 1 lode identical with Cor. No. 2 of the New Strike No. 2 lode; both of this survey.
1500.0	Cor. No. 4 identical with Cor. No. 3 of the New Strike No. 5 lode and on line 1-2 of the New Strike No. 2 lode; both of this survey. Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS4 4 NS5 3 X; from which A mound of stones constructed adjacent to the iron post. Thence S. 75° 31' 15" W.
300.0	Lode line; discovery pt. bears N. 14° 28' 45" W., 200.0 ft. dist.
425.0	Right bank local drainage, 20 ft. wide; course N. 5° W.
435.0	Unimproved dirt road bears N. 5° W. and S. 5° E.
600.0	Cor. No. 1 and the place of beginning.
	NEW STRIKE NO. 5 LODE
	At Cor. No. 1 of the New Strike No. 5 lode.

3 7

SURVEY NO. 4593

6

Chains Feet	
	Set a galvanized iron post $\frac{3}{4}$ in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd MS 4593 NS5 1 X; from which
	The Cor. of secs. 17, 18, 19 & 20, T.13N., R.1W., G. & S. R. B. & M., bears N. $65^{\circ}26'35''$ W., 1,544.79 ft. dist.; previously described.
	A mound of stones constructed adjacent to the iron post.
	Thence N. $14^{\circ}28'45''$ W.
290.0	Unimproved dirt road bears N. 55° E. and S. 60° W.
305.0	Right bank Benjamin Gulch, 20 ft. wide; course N. 75° E.
1500.0	Cor. No. 2 identical with Cor. No. 1 of the New Strike No. 4 lode of this survey; previously described.
	Thence N. $75^{\circ}31'15''$ E.
155.0	Left bank local drainage, 20 ft. wide; course N. 5° W.
165.0	Unimproved dirt road bears N. 5° W. and S. 5° E.
300.0	Lode line; discovery pt. bears S. $14^{\circ}28'45''$ E., 200.0 ft. dist.
600.0	Cor. No. 3 identical with Cor. No. 4 of the New Strike No. 4 lode and on line 1-2 of the New Strike No. 2 lode, both of this survey; previously described.
	Thence S. $14^{\circ}28'45''$ E.
670.0	Left bank Benjamin Gulch, 20 ft. wide; course N. 62° E.
1430.0	Cor. No. 1 of the New Strike No. 2 lode of this survey.
1500.0	Cor. No. 4
	Set a galvanized iron post, $\frac{3}{4}$ in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS5 4 X; from which
	A mound of stones constructed adjacent to the iron post.
	Thence S. $75^{\circ}31'15''$ W.
300.0	Lode line; discovery pt. bears N. $14^{\circ}28'45''$ W., 1300.0 ft. dist.
400.0	Right bank local drainage, 15 ft. wide; course N. 17° W.
600.0	Cor. No. 1 and the place of beginning.
	NEW STRIKE NO. 6 LODGE
	At Cor. No. 1 of the New Strike No. 6 lode, identical with Cor. No. 2 of the New Strike No. 7 lode and on line 3-4 of the New Strike No. 1 lode, both of this survey.

xChains Feet	<p>Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground with a brass cap, 2 ins. diam. firmly fastened within the iron post, mkd. MS 4593 NS6 1 NS7 2 X; from which</p> <p>The cor. of secs. 17, 18, 19 & 20, T.13N., R.1W., G. & S. R. B. & M., bears S.44° 25'55" W., 2,802.43 ft. dist.; previously described.</p> <p>A mound of stones constructed adjacent to the iron post.</p>
	<p>Thence N. 14°28'45" W.</p>
335.0	Right bank local drainage, 20 ft. wide; course N. 56°E.
365.0	Unimproved dirt road bears N.56°E. and S. 56° W.
650.0	Cor. No. 3 of the New Strike No. 1 lode identical with Cor. No. 4 of the New Strike No. 3 lode; both of this survey.
1450.0	Right bank local drainage, 10 ft. wide; course N. 60°E.
1500.0	Cor. No. 2 on line 3-4 of the New Strike No. 3 lode of this survey.
	<p>Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS6 2 X; from which</p> <p>A mound of stones constructed adjacent to the iron post.</p>
	<p>Thence N. 75°31'15" E.</p>
135.0	Left bank local drainage, 10 ft. wide; course N.50°E.
300.0	Lode line; discovery pt. bears S.14°28'45".E., 1050 ft. dist.
470.0	Improved dirt road bears N. 40°W. and S.45° E.
600.0	Cor. No. 3
	<p>Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS6 3 X; from which</p> <p>A mound of stones constructed adjacent to the iron post.</p>
	<p>Thence S. 14°28'45" E.</p>
230.0	Improved dirt road bears S.45°E. and N. 45°W.
450.0	Left bank local drainage, 15 ft. wide; course N. 45° E.
1500.0	Cor. No. 4 identical with Cor. No. 3 of the New Strike No. 7 lode of this survey.
	<p>Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins.</p>

Chains	Feet	in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS6 4 NS7 3 X; from which
		A mound of stones constructed adjacent to the iron post.
		Thence S. $75^{\circ}31'15''$ W.
	300.0	Lode line; discovery pt. bears N. $14^{\circ}28'45''$ W., 450 ft. dist.
	600.0	Cor. No. 1 and the place of beginning.
NEW STRIKE NO. 7 LODE		
		At Cor. No. 1 of the New Strike No. 7 lode, on line 3-4 of New Strike No. 2 lode of this survey.
		Set a galvanized iron post, $3/4$ in. diam., 24 ins. long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. NS7 1 X; from which
		The Cor. of secs. 17, 18, 19 & 20, T.13N., R.1W., G. & S. R. B. & M., bears S. $76^{\circ}47'$ W., 2,400.52 ft. dist.; previously described.
		A mound of stones constructed adjacent to the iron post.
		Thence N. $14^{\circ}28'45''$ W.
	180.0	Right bank Benjamin Gulch, 20 ft. wide; course N. 70° E.
	650.0	Cor. No. 3 of the New Strike No. 2 lode identical with Cor. No. 4 of the New Strike No. 1 lode; both of this survey.
	1500.0	Cor. No. 2 identical with Cor. No. 1 of the New Strike No. 6 lode and on line 3-4 of the New Strike No. 1 lode; previously described.
		Thence N. $75^{\circ}31'15''$ E.
	300.0	Lode line; discovery pt. bears S. $14^{\circ}28'45''$ E., 225.0 ft. dist.
	600.0	Cor. No. 3 identical with Cor. No. 4 of the New Strike No. 6 lode of this survey; previously described.
		Thence S. $14^{\circ}28'45''$ E.
	1285.0	Left bank Benjamin Gulch, 20 ft. wide; course N. 85° E.
	1500.0	Cor. No. 4
		Set a galvanized iron post, $3/4$ in. diam., 24 ins long, in a 25 pound concrete and rock base, 16 ins. in the ground, with a brass cap, 2 ins. diam., firmly fastened within the iron post, mkd. MS 4593 NS7 4 X; from which
		A mound of stones constructed adjacent to the iron post.

SURVEY NO. 4593

Chains
Feet

Thence S. 75°31'15" W.

300.0 Lode line; discovery pt. bears N. 14°28'45" W., 1,275
ft. dist.

600.0 Cor. No. and the place of beginning.

AREAS

	Acres
Total area, New Strike No. 1 lode	20.661
Total area, New Strike No. 2 lode	20.661
Total area, New Strike No. 3 lode	20.661
Total area, New Strike No. 4 lode	20.661
Total area, New Strike No. 5 lode	20.661
Total area, New Strike No. 6 lode	20.661
Total area, New Strike No. 7 lode	20.661

LOCATION

This survey is located in the NW $\frac{1}{4}$, SW $\frac{1}{4}$, SE $\frac{1}{4}$ of
Sec. 17 and NW $\frac{1}{4}$ of Sec. 20; T.13N.; R.1W., G.&S.R.B.&M.

The survey of the New Strike Nos. 1-7 lodes is
identical with the respective location or amended
location as marked on the ground.

EXPENDITURES

The improvements and the value of the labor and
improvements made upon or for the benefit of each of
the lode locations embraced in said mining claim by
the claimant or his grantors are as follows:

- No. 1 The discovery pt. of the New Strike No. 1 lode is on
the lode line, 600 ft. from a pt. on line 2-3,
300.0 ft. from Cor. No. 2. Value, None
- No. 2 A shaft, the SW Cor. of which bears N. 2°E., 1050 ft.
dist from Cor. No. 1 of the New Strike No. 1
lode; 8x8 ft. in size, total depth unknown, 25 ft.
allotted to claimant. Value, \$1250.
- No. 3 A pit, the NW Cor. of which bears S.55°E., 280 ft.
dist. from Cor. No. 2 of the New Strike No. 1
lode; 200 ft. long, 100 ft. average width, 4 ft.
average depth. Value, \$5,000.
- No. 4 A pit, the SW Cor. of which bears N.24°E., 450 ft.
from Cor. No. 1 of the New Strike No. 1 lode;
6x6 ft. in size, 3 $\frac{1}{2}$ ft. deep. Value, \$75.
- No. 5 A cut, the SW Cor. of which bears N.18°E., 540 ft.
dist. from Cor. No. 1 of the New Strike No. 1
lode; 10 ft. wide, 3 ft. average depth and running
S.70°E., 60 ft. Value, \$350.
- No. 6 A cut, the SW Cor. of which bears N.25°30'E., 570 ft.
dist. from Cor. No. 1 of the New Strike No. 1
lode; 10 ft. wide, 3 $\frac{1}{2}$ ft. average depth and
running N.15°W.; 60 ft. Value, \$350.
- No. 7 A pit, the SW Cor. of which bears N.49°E., 305 ft. dist.
from Cor. No. 1 of the New Strike No. 1 lode;
7x10 ft. in size, 2 $\frac{1}{2}$ ft. average depth.
Value, \$60.

11

SURVEY NO. 4593

10

CHAIN Feet		
No. 8	A pit, the SW Cor. of which bears N.41° E., 310 ft. dist. from Cor. No. 1 of the New Strike No. 1 lode; 11 ft. wide, 2½ ft. average depth and running east, 25 ft.	Value, \$100.
No. 1	The discovery pt. of the New Strike No. 2 lode is on the lode line, 300 ft. from a pt. on line 2-3, 300.0 ft. from Cor. No. 2.	Value, None
No. 2	A pit, the NW Cor. of which bears S.73° E., 310 ft. dist. from Cor. No. 2 of the New Strike No. 2 lode; 8x8 ft. in size, 7 ft. deep.	Value, \$200.
No. 3	A cut, the SW Cor. of which bears N.86°30' E., 295 ft. dist. from Cor. No. 2 of the New Strike No. 2 lode; 10 ft. wide, 2 ft. average depth and running S.80° E., 35 ft.	Value, \$175.
No. 4	A cut, the NW Cor. of which bears S.46°30' E., 655 ft. dist. from Cor. No. 2 of New Strike No. 2 lode; 10 ft. wide, 3 ft. average depth and running N.40° E., 25 ft.	Value, \$175.
No. 5	A pit, the NW Cor. of which bears S.44° E., 680 ft. dist. from Cor. No. 2 of the New Strike No. 2 lode; 5x6 ft. in size, 6 ft. deep.	Value, \$150.
No. 1	The discovery pt. of the New Strike No. 3 lode is on the lode line, 200 ft. from a pt. on line 4-1, 300.0 ft. from Cor. No. 4.	Value, None
No. 2	A pit, the SW edge of which bears N.35° E., 370 ft. dist. from Cor. No. 1 of the New Strike No. 3 lode; 7 ft. diam., 2 ft. average depth.	Value, \$50.
No. 3	A pit, the SW Cor. of which bears N.11° W., 530 ft. dist. from Cor. No. 1 of the New Strike No. 3 lode; 5x12 ft. in size, 4 ft. deep.	Value, \$150.
No. 4	A pit, the SW Cor. of which bears N.6° E., 990 ft. dist. from Cor. No. 1 of the New Strike No. 3 lode; 5x5 ft. in size, 4 ft. deep.	Value, \$90.
No. 5	A cut, the SW Cor. of which bears N.5°30' E., 950 ft. dist. from Cor. No. 1 of the New Strike No. 3 lode; 6 ft. wide, 4 ft. deep and running east, 20 ft.	Value, \$225.
No. 1	The discovery pt. of the New Strike No. 4 lode is on the lode line, 200 ft. from a pt. on line 4-1, 300.0 ft. from Cor. No. 4.	Value, None
No. 2	A pit, the SW Cor. of which bears N.15°30' E., 700 ft. dist. from Cor. No. 1 of the New Strike No. 4 lode; 4x6 ft. in size, 2 ft. deep.	Value, \$50.

Chains Feet		
No. 3	A pit, the SW Cor. of which bears N.8°30'E., 1,035 ft. dist. from Cor. No. 1 of the New Strike No. 4 lode; 4x6 ft. in size, 2 ft. deep.	Value, \$50.
No. 4	A pit, the SW Cor. of which bears N.63°E., 325 ft. dist. from Cor. No. 1 of the New Strike No. 4 lode; 6x8 ft. in size, 3 ft. deep.	Value, \$75.
No. 1	The discovery pt. of the New Strike No. 5 lode is on the lode line, 200 ft. from a pt. on line 2-3, 300 ft. from Cor. No. 2.	Value, None
No. 2	A cut, the SW Cor. of which bears N.17°E., 390 ft. dist. from Cor. No. 1 of the New Strike No. 5 lode, 5 ft. wide, running east 8 ft. to a 4 ft. face.	Value, \$150.
No. 3	A cut, the SW Cor. of which bears N.30°E., 250 ft. dist. from Cor. No. 1 of the New Strike No. 5 lode; 8 ft. wide, a 10 ft. face on the east side, and running north, 30 ft.	Value, \$1000.
No. 1	The discovery cut of the New Strike No. 6 lode is on the lode line, 450 ft. from a pt. on line 4-1, 300.0 ft. from Cor. No. 4; 5 ft. wide, running south 8 ft. to a 6 ft. face.	Value, \$200.
No. 1	The discovery pt. of the New Strike No. 7 lode is on the lode line 225 ft. from a pt. on line 2-3, 300.0 ft. from Cor. No. 2.	Value, None
No. 2	A pit, the NW Cor. of which bears S.69°E., 470 ft. dist. from Cor. No. 2 of the New Strike No. 7 lode; 6x8 ft. in size, 3 ft. deep.	Value, \$80.
No. 3	A pit, the NW Cor. of which bears S.81°E., 470 ft. dist. from Cor. No. 2 of the New Strike No. 7 lode; 6x8 ft. in size, 4½ ft. deep.	Value, \$110.

An interest in a common improvement described as follows:

An adit, 4x6 ft. in size, the portal of which bears S.43°E., 630 ft. dist. from Cor. No. 2 of the New Strike No. 1 lode; running S.59°E. a minimum of 100 ft. There are no maps available on the complete underground workings therefore a complete description can not be made.

Value, \$2,400. minimum.

Value of one-third interest, \$800.

This improvement was made to develop an ore body on the New Strike No. 1 lode but it would be the most economic development of the south end of New Strike No. 6 lode and north end of the New Strike No. 7 lode which are contiguous lode claims owned in common within the range of benefit of said adit.

Chains
Feet

The surface rises rapidly to the southeast from the portal of the adit and the extension in its present course, with necessary laterals, affords the most practical and economical means of developing each of the stated lodes at depth.

Five-hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each of the stated lodes subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-third interest in its value is hereby credited to each of the following listed lodes; New Strike No. 1, New Strike No. 6 and New Strike No. 7.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode claim.

OTHER IMPROVEMENTS

A frame bunkhouse, the NW Cor. of which bears S. 43° E., 450 ft. dist. from Cor. No. 2 of the New Strike No. 1 lode; 10x10 ft. in size, one side bears N. 75° E. Claimant herein.

OTHER CORNER DESCRIPTIONS
AND SUPPLEMENTAL DATA

NONE

FIELD ASSISTANTS

Name	Capacity
Richard Cleveland	Chainman-Axeman

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

5/15/62, 19

I, Harvey W. Smith
Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the Cadastral
Engineer, at Phoenix, Arizona
dated April 17, 1962, I have faithfully and correctly executed the survey of
the mining claim of Frank Melluzzo and G. H. Seebold
known as the New Strike Nos. 1, 2, 3, 4, 5, 6 & 7 Lodes
(Lode, placer, or mill site)
situate in Walker Mining District, Yavapai County
T. 13 N., R. 1 W., G. & S. R. B. & Meridian, Arizona, and
(State)
designated as Survey No. 4593, which is represented in the foregoing field notes as having been
executed by me and under my direction, and that said survey has been made in strict conformity with said order,
the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
described in the foregoing field notes, and I do further certify that the labor expended and improvements made
upon or for the benefit of the lode location(s) embraced in the said mining claim by
(Lode or placer)
claimant(s) or his grantors are fully stated in my report therein, and that the character,
extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
of expenditures upon any other claim.

Scottsdale, Arizona
(Place)

Harvey W. Smith
(Mineral Surveyor)
Harvey W. Smith

CERTIFICATE OF APPROVAL

Bureau of Land Management, State Director
(Office)
Phoenix, Arizona August 16, 19 62
(Place) (Date)

The foregoing field notes of mineral survey No. 4593, in Walker Mining District
Secs. 17 & 20, T. 13 N., R. 1 W., G. & S. R. Meridian,
Arizona, executed by Harvey W. Smith, Mineral Surveyor,
(State)
under order dated April 17, 1962, having been critically examined and the necessary
corrections made prior to their certification by the surveyor, the field notes and the survey therein described
are hereby approved.

Fred J. Weiler
Fred J. Weiler
State Director
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

(Title)

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S.4593
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The New Strike No.1, New Strike No.2, New Strike No.3, New Strike No.4, New Strike No.5, New Strike No.6, and New Strike No.7 lodes, Mineral Survey No. 4593, located in sections 17 and 20, Township 13 North, Range 1 West, Gila and Salt River Meridian, Arizona, are hereby canceled.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"New Strike No.1, New Strike No.2, New Strike No.3, New Strike No.4, New Strike No.5, New Strike No.6, and New Strike No.7 lodes, M.S. 4593, were canceled October 16, 2008, by memo 9605 (956) M.S. 4593, which is now a part of the original field notes."

October 16, 2008
Date



Chief Cadastral Surveyor of Arizona

