

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey Number

4598

1

State

Arizona

Land District

Arizona

FIELD NOTES

Of the Survey of the Mining Claim of (Name & address of Claimant)

Carrie and Alice Boyle
4215 No. Mitchell St.
Phoenix, Arizona

Known as the (Name of group, if any)

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Enterprise #1	10/9/39	
Enterprise #2	10/9/39	
Bull Dog #1	10/9/39	
Bull Dog #2	10/9/39	

Mining District Superstition		County Pinal	Section 2 & 3
Township 1 N.	Range 8 E.	Meridian G. & S. R. B. &M.	Surveyed under order dated 7/24/62
Survey commenced 8/8/62	Survey completed 8/16/62	Name of Mineral Surveyor Harvey W. Smith	

FIELD NOTES

SECTION NUMBER

DATE

LOCALITY

STATE

PROPERTY OR OTHER INTEREST

NAME OF PARTY

DESCRIPTION OF LAND

ACRES

SECTION

TOWNSHIP

RANGE

COUNTY

STATE

ADDITIONAL NOTES

SECTION	TOWNSHIP	RANGE	COUNTY	STATE
ACRES	SECTION		TOWNSHIP	RANGE
ADDITIONAL NOTES	COUNTY	STATE	DATE	BY

SURVEY NO. 4598

1

Chains
Feet

This survey was made with a K. & E. transit, No. 51591, with horizontal limb 5.5 ins. diam., having two double opposite verniers and full vertical circle 4.5 ins. diam., having one double vernier. The verniers read to one minute of arc. The instrument is equipped with a colored eye-shade to be attached for making direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian established by direct observation on the sun. At 8:27 A. M. on August 11, 1962 at Cor. No. 1 of the Enterprise #1 lode identical with Cor. No. 4 of the Bull Dog #1 lode, latitude $33^{\circ}27'45''$ North, longitude $111^{\circ}30'33''$ West, turning from a reference pt. about 2000 ft. southeast clockwise to the sun in an east direction.

True bearing of reference pt.

S. $6^{\circ}50'40''$ E.

The lines were measured with a Lufkin steel tape, 300 ft. in length graduated every ft. for 299 ft. and the remaining foot graduated to tenths and hundredths. The tape was compared to a standard at the beginning of the survey and found to be correct. All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $15^{\circ}40'$ East.

SURVEY NO. 4598

ENTERPRISE #1 LODE

At Cor. No. 1 of the Enterprise #1 lode identical with Cor. No. 4 of the Bull Dog #1 lode of this survey.

Set an iron post, $\frac{3}{4}$ in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, $2\frac{1}{2}$ ins. diam., firmly secured to the iron post, mkd. MS 4598 E1 1 BDI 4 X; from which

The Cor. of Secs. 2, 3, 34 & 35, Ts. 1 & 2 N., R. 18 E., G. & S. R. B. & M., bears N. $44^{\circ}10'10''$ E., 524.63 ft. dist.; an iron post, 2 ins. diam., 12 ins. above ground, leaning at a 30° angle, southward, with a brass cap marked as described in the official record.

A mound of stones constructed adjacent to the iron post.

Thence S. $6^{\circ}50'40''$ E.

1307.0 Unimproved dirt road bears N. 15° E. and S. 15° W.

1500.0 Cor. No. 2 identical with Cor. No. 3 of the Bull Dog #1, Cor. No. 2 of the Bull Dog #2 and Cor. No. 4 of Enterprise #2 lodes; all of this survey.

Chains	
Feet	Set a galvanized iron post, 3/4 in. diam., 30 ins. long,
	in a 25 pound concrete and rock base, 18 ins. in
	the ground, with a brass cap, 2 1/2 ins. diam., firmly
	secured to the iron post, mkd. MS 4598 E1 2 E2 4
	BD1 3 BD2 2 X; from which
	A mound of stones constructed adjacent
	to the iron post.
	Thence S. 83°10'20" W.
69.0	Unimproved dirt road bears south and N. 13° E.
300.0	Lode line; discovery pt. bears N. 6°50'40" W., 500 ft.
	dist.
600.0	Cor. No. 3 identical with Cor. No. 3 of the Enterprise
	#2 lode, of this survey.
	Set a galvanized iron post, 3/4 in. diam., 30 ins. long,
	in a 25 pound concrete and rock base, 18 ins. in
	the ground, with a brass cap, 2 1/2 ins. diam., firmly
	secured to the iron post, mkd. MS 4598 E1 3 E2 3 X;
	from which
	A mound of stones constructed adjacent to
	the iron post.
	Thence N. 6°50'40" W.
1495.0	South bank of local ravine; course S. 50° E.
1500.0	Cor. No. 4.
	This pt. falls in a local ravine and a monument here
	would soon be obliterated.
	Thence N. 83°10'20" E.
63.01	Witness pt. for Cor. No. 4
	Set a galvanized iron post, 3/4 in. diam., 30 ins. long,
	in a 25 pound concrete and rock base, 18 ins. in
	the ground, with a brass cap, 2 1/2 ins. diam., firmly
	secured to the iron post, mkd. MS 4598 E1 4 WC X;
	from which
	A wooden post 4x4 ins., 3 ft. long set
	in a mound of stones adjacent to
	the iron post.
300.0	Lode line; discovery pt. bears S. 6°50'40" E., 1,000 ft.
	dist.
600.0	Cor. No. 1 and the place of beginning.
ENTERPRISE #2 LODE	
	At Cor. No. 1 of the Enterprise #2 lode, identical with
	Cor. No. 1 of the Bull Dog #2 lode of this survey.
	Set a galvanized iron post; 3/4 in. diam., 30 ins. long,
	in a 25 pound concrete and rock base, 18 ins. in
	the ground, with a brass cap, 2 1/2 ins. diam.,
	securely fastened to the iron post, mkd. MS 4598
	E2 1 BD2 1 X; from which

Chains Feet	<p>The $\frac{1}{4}$ Cor. of Secs. 2 & 3, T. 1 N., R. 8 E., G. & S. R. B. & M., bears N. $0^{\circ}50'$ E., 710.59 ft. dist.; an iron post, 1 in. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the official record.</p> <p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence S. $83^{\circ}10'20''$ W.</p>
190.0	Left bank of local drainage, 15 ft. wide; course S. 5° E.
300.0	Lode line; discovery pt. bears N. $6^{\circ}50'40''$ W., 1,400 ft. dist.
600.0	<p>Cor. No. 2</p> <p>Set a galvanized iron post, $\frac{3}{4}$ in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, $2\frac{1}{2}$ ins. diam., firmly secured to the iron post, mkd. MS 4598 E2 2 X; from which</p> <p>An iron post, 3 ins. diam., 3 ft. long, set in a mound of stones adjacent to the iron post.</p> <p>Thence N. $6^{\circ}50'40''$ W.</p>
490.0	Unimproved dirt road bears N. 55° E. and S. 55° W.
1500.0	<p>Cor. No. 3 identical with Cor. No. 3 of the Enterprise #1 lode of this survey; previously described.</p> <p>Thence N. $83^{\circ}10'20''$ E.</p>
300.0	Lode line; discovery pt. bears S. $6^{\circ}50'40''$ E., 100 ft. dist.
531.0	Unimproved dirt road bears south and N. 13° E.
600.0	<p>Cor. No. 4 identical with Cor. No. 2 of the Enterprise #1, Cor. No. 3 of the Bull Dog #1 and Cor. No. 2 of the Bull Dog #2 lodes, all of this survey; previously described.</p> <p>Thence S. $6^{\circ}50'40''$ E.</p>
200.0	Right bank of local drainage, 40 ft. wide; course, south.
1500.0	Cor. No. 1 and the place of beginning.

BULL DOG #1 LODE

At Cor. No. 1, of the Bull Dog #1 lode.

Set a galvanized iron post, $\frac{3}{4}$ in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, $2\frac{1}{2}$ ins. diam., firmly secured to the iron post, mkd. MS 4598 BD1 1 X; from which

45

SURVEY NO. 4598

4

Chain Feet	
	<p>The Cor. of secs. 2, 3, 34 & 35, Ts. 1 & 2 N., R. 8 E., G. & S. R. B. & M., bears N. 37°02'45" W., 382.11 ft. dist.; previously described</p> <p>A wooden post, 4 ins. diam., 4 ft. long set adjacent to the iron post.</p> <p>Thence S. 6°50'40" E.</p>
1150.0	Right bank of local drainage, 30 ft. wide; course S. 30° W.
1500.0	<p>Cor. No. 2 identical with Cor. No. 3 of the Bull Dog #2 lode of this survey.</p> <p>Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 1/2 ins. diam., firmly secured to the iron post, mkd. MS 4598 BD1 2 BD2 3 X; from which</p> <p>A mound of stones constructed adjacent to the iron post.</p> <p>Thence S. 83°10'20" W.</p>
300.0	Lode line; discovery pt. bears N. 6°50'40" W., 500 ft. dist.
400.0	Left bank of local drainage, 30 ft. wide; course S. 40° W.
600.0	<p>Cor. No. 3 identical with Cor. No. 2 of the Bull Dog #2, Cor. No. 2 of the Enterprise #1 and Cor. No. 4 of the Enterprise #2 lodes, all of this survey; previously described.</p> <p>Thence N. 6°50'40" W.</p>
193.0	Unimproved dirt road bears N. 15° E. and S. 15° W.
1500.0	<p>Cor. No. 4 identical with Cor. No. 1 of the Enterprise #1 lode of this survey; previously described.</p> <p>Thence N. 83°10'20" E.</p>
300.0	Lode line; discovery pt. bears S. 6°50'40" E., 1,000 ft. dist.
600.0	Cor. No. 1 and the place of beginning.
BULL DOG #2 LODE	
	<p>Beginning at Cor. No. 1 of the Bull Dog #2 lode, identical with Cor. No. 1 of the Enterprise #2 lode of this survey; previously described.</p> <p>Thence N. 6°50'40" W.</p>
1260.0	Left bank of local drainage, 40 ft. wide; course, south.
1500.0	Cor. No. 2 identical with Cor. No. 4 of the Enterprise #2, Cor. No. 2 of the Enterprise #1 and Cor. No. 3 of the Bull Dog #1 lodes, all of this survey; previously described.

x Chains
Feet

Thence N. 83°10'20" E.

170.0 Right bank of local drainage; 30 ft. wide; course, S. 40° W.

300.0 Lode line; discovery pt. bears S. 6°50'40" E., 50 ft. dist.

600.0 Cor. No. 3 identical with Cor. No. 2 of the Bull Dog #1 lode of this survey; previously described.

Thence S. 6°50'40" E.

1500.0 Cor. No. 4

Set a galvanized iron post, 3/4 in. diam., 30 ins. long, in a 25 pound concrete and rock base, 18 ins. in the ground, with a brass cap, 2 1/2 ins. diam., securely fastened to the iron post, mkd. MS 4598 BD2 4 X; from which

A wooden post, 4x4 ins., 4 ft. long set adjacent to the iron post:

Thence S. 83°10'20" W.

300.0 Lode line; discovery pt. bears N. 6°50'40" W., 1,450 ft. dist.

600.0 Cor. No. 1 and the place of beginning.

SURVEY NO. 4598

AREAS

	Acres
Total area Bull Dog #1 lode	20.661
Total area Bull Dog #2 lode	20.661
Total area Enterprise #1 lode	20.661
Total area Enterprise #2 lode	20.661

LOCATION

This survey is located in the NW 1/4 and SW 1/4 of Sec. 2 and the NE 1/4 and SE 1/4 of sec. 3, T.1N., R.8E., G. & S. R.B.&M.

The survey of the Bull Dog #s 1 & 2 and the Enterprise #s 1 & 2 lodes is identical with the respective location or amended location as marked on the ground.

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows:

No. 1 The discovery pt. of the Bull Dog #1 lode is on the lode line 500 ft. from a pt. on line 2-3, 300.0 ft. from Cor. No. 2.

Value, None

7

SURVEY NO. 4598

6

xChains Feet	
No. 2	A cut, the SW Cor. of which bears N. 33°30' E., 595 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 5 ft. wide, 50 ft. deep and running north 50 ft. Value, \$1,500.
No. 3	A cut, the SW Cor. of which bears N. 30° 45' E., 635 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 6 ft. wide, 7 ft. deep and running north, 15 ft. Value, \$150.
No. 4	A shaft, the SW Cor. of which bears N. 25° E., 690 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 8x7 ft. in size, 75+ deep. Value, \$3,750.
No. 5	A cut, the SW Cor. of which bears N. 26° E., 695 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 5 ft. wide, 25 ft. deep and running north, 20 ft. Value, \$250.
No. 6	A pit, the SW Cor. of which bears N. 24° E., 740 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 7x8 ft. in size, 10 ft. deep. Value, \$250.
No. 7	A cut, the SW Cor. of which bears N. 21° E., 800 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 5 ft. wide, 7 ft. deep and running east; 15 ft. Value, \$250.
No. 8	A cut, the SW Cor. of which bears N. 20° E., 875 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 5 ft. wide, 4 ft. deep and running east 12 ft. Value, \$175.
No. 9	A pit, the SW edge of which bears N. 7° E., 725 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; an irregular shaped pit approximately 450 ft. wide x 700 ft. long and averaging 3½ ft. deep. Value, \$15,000.
No. 10	A pit, the SW Cor. of which bears north, 675 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 12x12 ft. in size, 4 ft. deep. Value, \$200.
No. 11	A pit, the SW Cor. of which bears N. 1°30' E., 675 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 8x8 ft. in size, 5 ft. deep. Value, \$175.
No. 12	A pit, the SE edge of which bears N. 3° E., 555 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; approximately 30x75 ft. in size, 2½ ft. average depth. Value, \$150.
No. 13	A timbered shaft, the SW Cor. of which bears N. 38°30' E., 505 ft. dist., from Cor. No. 3 of the Bull Dog #1 lode; 4x4 ft. in size, 50+ ft. deep. Value, \$1,500.

x Chains	Feet	
No. 14	A pit, the SW Cor. of which bears N.31°30' E., 415 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 5 ft. wide, 18 ft. deep and running N.40°E., 15 ft. Value, \$300.	
No. 15	A shaft, the SW Cor. of which bears N.35°E., 405 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 6x6 ft. in size, 75 + ft. deep. Value, \$2,000	
No. 16	A cut, the SW Cor. of which bears N.9° E., 345 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 4 ft. wide, 20 ft. deep and running north, 25 ft. Value, \$400.	
No. 17	A cut, the SW Cor. of which bears N. 21°30' E., 185 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 8 ft. wide, 4 ft. deep and running north, 25 ft. Value, \$150.	
No. 18	A shaft with timbered collar, the SW Cor. of which bears N.46°E., 385 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 5x6 ft. in size, 50+ ft. deep. Value, \$2,000.	
No. 19	A shaft, the SW Cor. of which bears N.67°30'E., 190 ft. dist. from Cor. No. 3 of the Bull Dog #1 lode; 6x6 ft. in size, 30+ ft. deep. Value, \$1,200.	
No. 1	The discovery pt. of the Bull Dog #2 lode is on the lode line, 50 ft. from a pt. on line 2-3, 300 ft. from Cor. No. 2. Value, None	
No. 2	A shaft, the NW Cor. of which bears S.77°E., 290 ft. from Cor. No. 2 of the Bull Dog #2 lode; 4x6 ft. in size, 50+ ft. deep. Value, \$2,000.	
No. 3	A pit, the NW Cor. of which bears S.69°30' E., 310 ft. dist. from Cor. No. 2 of the Bull Dog #2 lode; 4x4 ft. in size, 4 ft. deep. Value, \$40.	
No. 4	A pit, the NW Cor. of which bears S.75°E., 320 ft. dist. from Cor. No. 2 of the Bull Dog #2 lode; 4x4 ft. in size, 4 ft. deep. Value, \$40.	
No. 5	A pit, the NW Cor. of which bears S.69°E., 355 ft. dist. from Cor. No. 2 of the Bull Dog #2 lode; 5x6 ft. in size, 8 ft. deep. Value, \$200.	
No. 6	A pit, the NW Cor. of which bears S.75°E., 385 ft. dist. from Cor. No. 2 of the Bull Dog #2 lode; 6x6 ft. in size, 6 ft. deep. Value, \$150.	
No. 7	A pit, the NW Cor. of which bears S. 78°E., 375 ft. dist. from Cor. No. 2 of the Bull Dog #2 lode; 6x4 ft. in size, 8 ft. deep. Value, \$150.	

XChange Feet	
No. 8	A pit, the NW Cor. of which bears S. 81° E., 400 ft. dist. from Cor. No. 2 of the Bull Dog #2 lode; 5x5 ft. in size, 6 ft. deep. Value, \$100.
No. 1	The discovery pt. of the Enterprise #1 lode is on the lode line, 500 ft. from a pt. on line 2-3, 300 ft. from Cor. No. 2. Value, None
No. 2	A cut, the SW Cor. of which bears N. 36° 30' E., 655 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 6 ft. wide, 30 ft. deep and running N. 45° E., 25 ft. Value, \$400.
No. 3	An inclined adit, the portal of which bears N. 35° 30' E., 620 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 6x6 ft. in size, running N. 35° W., 50+ ft. at an inclination of 25°. Value, \$1,000.
No. 4	A shaft, the SW Cor. of which bears N. 35° 30' E., 745 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 5x5 ft. in size, 20 ft. deep. Value, \$600.
No. 5	A pit, the SW Cor. of which bears N. 11° E., 625 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 8x10 ft. in size, 10 ft. deep. Value, \$500.
No. 6	An inclined shaft, the SW Cor. of which bears N. 10° E., 715 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 10x8 ft. in size, 30+ ft. deep inclined at 60°. Value, \$1,000.
No. 7	A pit, the SW Cor. of which bears N. 20° 30' E., 210 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 4x6 ft. in size, 15 ft. deep. Value, \$350.
No. 8	An adit, the portal of which bears N. 18° E., 410 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 4x5 ft. in size and running north, 20 ft. Value, \$400.
No. 9	A cut, the SW Cor. of which bears N. 8° 30' E., 1,445 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 4 ft. wide, 4 ft. face at the east end and running east, 10 ft. Value, \$50.
No. 10	A pit, the SW Cor. of which bears N. 9° E., 1,435 ft. dist., from Cor. No. 3 of the Enterprise #1 lode; 4x6 ft. in size, 6 ft. deep. Value, \$125.00
No. 11	A cut, the SW Cor. of which bears N. 9° 30' E., 1,420 ft. dist. from Cor. No. 3 of the Enterprise #1 lode; 4 ft. wide, 2 ft. deep and running east, 10 ft. Value, \$50.

SURVEY NO. 4598

9

XChains
Feet

- No. 1 The discovery pt. of the Enterprise #2 lode is on the lode line, 100 ft. from a pt. on line 3-4, 300 ft. from Cor. No. 3.
Value, None
- No. 2 A pit, the NW edge of which bears S.46°E., 105 ft. dist. from Cor. No. 3 of the Enterprise #2 lode; an irregular shaped area, approximately 75 x 100 ft. in area, averaging 3 ft. deep.
Value, \$500.
- No. 3 A pit, the NW Cor. of which bears S.69°E., 410 ft. dist. from Cor. No. 3 of the Enterprise #2 lode; 6x4 ft. in size, 6 ft. deep.
Value, \$125.
- No. 4 A pit, the NW Cor. of which bears S.55°30' E., 400 ft. dist. from Cor. No. 3 of the Enterprise #2 lode; 6x4 ft. in size, 10 ft. deep.
Value, \$200.
- No. 5 A pit, the NW Cor. of which bears S.79°E., 470 ft. dist. from Cor. No. 3 of the Enterprise #2 lode; 6x5 ft. in size, 12 ft. deep.
Value, \$300.
- No. 6 A pit, the NW Cor. of which bears S.80°30' E., 490 ft. dist. from Cor. No. 3 of the Enterprise #2 lode; 4x8 ft. in size, 4 ft. deep.
Value, \$125.
- No. 7 A pit, the NW Cor. of which bears S.83°E., 460 ft. dist., from Cor. No. 3 of the Enterprise #2 lode, 4x6 ft. in size, 7 ft. deep.
Value, \$125.
- No. 8 A pit, the NW Cor. of which bears S.81°30' E., 545 ft. dist. from Cor. No. 3 of the Enterprise #2 lode; 4x6 ft. in size, 5 ft. deep.
Value, \$100.
- No. 9 A pit, the NW Cor. of which bears S.77°E., 560 ft. dist. from Cor. No. 3 of the Enterprise #2 lode; 3x10 ft. in size, 4 ft. deep.
Value, \$150.

OTHER IMPROVEMENTS

A windmill water pump situated on the shaft of improvement No. 18 on the Bull Dog #1 lode
Claimant unknown.

OTHER CORNER DESCRIPTIONS
AND SUPPLEMENTAL DATA

The Sec. line between the Cor. of secs. 2, 3, 34 & 35, Ts. 1 & 2 N., R.8E., G.&S.R.B.&M. and the $\frac{1}{4}$ cor. of Secs. 2 & 3 was found to be S.0°03' E., 2,644.61 ft. The bearing is correct as approved.

FIELD ASSISTANTS

Name
Richard Cleveland

Capacity
Chainman-Axeman

Chains

The discovery pt. of the Intergrated #2 lode is on the lode line, 100 ft. from a pt. on line 2-100-100 ft. from Cor. No. 3.

A pit, the NW Cor. of which bears S. 40° E., 100 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; an irregular shaped area, approximately 10 x 100 ft. in area, averaging 5 ft. deep.

A pit, the NW Cor. of which bears S. 30° E., 410 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; in area, 5 ft. deep.

A pit, the NW Cor. of which bears S. 55° E., 400 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; in area, 10 ft. deep.

A pit, the NW Cor. of which bears S. 70° E., 410 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; in area, 12 ft. deep.

A pit, the NW Cor. of which bears S. 60° E., 400 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; in area, 4 ft. deep.

A pit, the NW Cor. of which bears S. 80° E., 400 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; in area, 7 ft. deep.

A pit, the NW Cor. of which bears S. 70° E., 410 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; in area, 5 ft. deep.

A pit, the NW Cor. of which bears S. 70° E., 410 ft. dist. from Cor. No. 3 of the Intergrated #2 lode; in area, 4 ft. deep.

COMMON INTEREST

A shallow water pump situated on the surface of the land owned by the Intergrated #2 lode.

THE COMMON INTEREST

The fee line between the Cor. of No. 3 and the Cor. of No. 4 is a line, S. 80° E., 600 ft. and the Cor. of No. 4 is a line, S. 80° E., 600 ft. and the bearing is correct as shown.

FIELD ASSAYS

Assays were made at various points on the lode line.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Aug. 17, 1962

I, Harvey W. Smith,
 Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____
Cadastral Engineer, at Phoenix, Arizona
 dated July 24, 1962, I have faithfully and correctly executed the survey of
 the mining claim of Carrie and Alice Boyle,
 known as the Enterprise #s 1 & 2 and Bull Dog #s 1 & 2 Lodes
(Lode, placer, or mill site)
 situate in Superstition Mining District, Pinal County, Secs. 2 & 3,
 T. 1 N., R. 8 E., G. & S. R. B. & Meridian, Arizona, and
(State)
 designated as Survey No. 4598, which is represented in the foregoing field notes as having been
 executed by me and under my direction, and that said survey has been made in strict conformity with said order,
 the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
 described in the foregoing field notes, and I do further certify that the labor expended and improvements made
 upon or for the benefit of the lode location(s) embraced in the said mining claim by
(Lode or placer)
 claimant(s) or his grantors are fully stated in my report therein, and that the character,
 extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
 portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
 of expenditures upon any other claim.

Scottsdale, Arizona
(Place)

Harvey W. Smith
(Mineral Surveyor)
 Harvey W. Smith

CERTIFICATE OF APPROVAL

Bureau of Land Management, State Office
(Office)
Phoenix, Arizona September 18, 1962
(Place) (Date)

The foregoing field notes of mineral survey No. 4598, in Superstition Mining District
Secs. 2 and 3, T. 1 N., R. 8 E., G. & S. R. Meridian,
Arizona, executed by Harvey W. Smith, Mineral Surveyor,
(State)
 under order dated July 24, 1962, having been critically examined and the necessary
 corrections made prior to their certification by the surveyor, the field notes and the survey therein described
 are hereby approved.

Fred J. Weiler
 Fred J. Weiler
 State Director
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

(Title)

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (952)
BUREAU OF LAND MANAGEMENT M.S. 4598
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Bull Dog #1 and 2, Enterprise #1 and 2 lodes, Mineral Survey No. 4598, located in sections 2 and 3, Township 1 North, Range 8 East, Gila and Salt River Meridian, Arizona, are hereby canceled.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Bull Dog #1 and 2, Enterprise #1 and 2 lodes, M.S. 4598 were canceled February 3, 1999, by memo 9605 (952) M.S. 4598, which is now a part of the original field notes."

February 3, 1999
Date



Chief Cadastral Surveyor of Arizona

