

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey Number

4601

State

ARIZONA

Land District

ARIZONA

FIELD NOTES

Of the Survey of the Mining Claim of (Name & address of Claimant)

HOMER L. WRIGHT
P.O. BOX 173
MAYER ARIZONA

Known as the (Name of group, if any)

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
STONEWALL	7/1/1947	9/30/1962
MISSING LINK	7/1/1947	9/30/1962
LONE STAR	7/1/1947	9/30/1962

Mining District AGUA FRIA		County YAVAPAI	Section 7-8-17-18
Township 12 N.	Range 2 E.	Meridian G.&.S.R. Meridian	Surveyed under order dated SEPT. 24, 1962 Oct. 2, 1962 Amd.
Survey commenced Sept. 24, 1962	Survey completed Oct. 11, 1962	Name of Mineral Surveyor J.WILLIAM WAARA	

FIELD NOTES

On the basis of the above, I am of the opinion that the following

is a correct description of the above

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

DATE	NAME OF LOCATION
1-1-58	...
1-1-58	...
1-1-58	...

Section	County	Range	Township	Name of Mineral Interest	Survey Contained	Survey Contained
1-0-17-18

Surveyed under order dated

MINERAL SURVEY No. 4601

1.

~~CHECKS~~
Feet

This survey was made with a Lietz Light Mountain transit No. 9303, with horizontal limb five inches in diameter, having two double opposite verniers reading to thirty seconds of arc, and full vertical circle five inches in diameter, having double opposite verniers reading to one minute of arc; the eye-piece is equipped to receive a prismatic eye-piece with colored shade for direct observations upon the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian established by direct observations on the sun.

October 2, 1962, at Improvement No. 1 of the Lone Star lode, Latitude $34^{\circ}26'08''$ N. and Longitude $112^{\circ}09'47''$ W., turning from reference point northwest, clockwise to the sun in the southeast.

True bearing of the reference point, S. $15^{\circ}10'$ E.

The lines were measured with a 1/8 inch wide 500 foot steel tape, graduated every foot. This tape was compared with a standard 100 foot steel tape at the time of beginning the survey, and found correct.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $14^{\circ}30'$ E.

SURVEY No. 4601

Stonewall lode

At Cor. No. 1 of the Stonewall lode, identical with Cor. No. 1 of the Missing Link lode of this survey.

Set a $\frac{1}{2}$ inch iron pipe, 30 inches long, 18 inches in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked S 1-M L 1-4601 with its center for exact corner point, from which

The corner of sections 7, 8, 17 and 18, T. 12 N., R. 2 E., Gila and Salt River Meridian, Arizona, bears S. $21^{\circ}13'$ E., 266.6 ft. dist.

No other bearings available.

Thence S. $24^{\circ}35'$ W.

560.9 Wash, course easterly.

600.9 Mine road, bears E. to W.

1500.9 Cor. No. 2, identical with Cor. No. 4 of the Missing Link lode of this survey.

Set a $\frac{1}{2}$ inch iron pipe, 30 inches long, 18 inches in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked S 2-M L 4-4601 with its center for exact corner point.

No bearings available.

Chains Feet	
	Thence N. 78°32' W.
303.2	Lode line, built a substantial mound of stone; discovery shaft bears N. 24°26' E., 810 ft. dist.
610.6	Cor. No. 3. Set a ½ inch iron pipe, 30 inches long, 18 inches in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked S 3-4601 with its center for exact corner point. No bearings available. Thence N. 24°28' E.
845.0	Road to Mayer, Arizona, bears SW. and NE.
870.0	Wash, course easterly.
1500.0	Cor. No. 4. Set a ½ inch iron pipe, 30 inches long, 18 inches in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked S 4-4601 with its center for exact corner point. No bearings available. Thence S. 78°32' E.
306.8	Lode line, built a substantial mound of stone; discovery shaft bears S. 24°26' W., 690 ft. dist.
614.0	Cor. No. 1, and the place of beginning.
MISSING LINK LODE	
	Beginning at Cor. No. 1 of the Missing Link lode, identical with Cor. No. 1 of the Stonewall lode of this survey. Thence S. 78°32' E.
181.9	Lode line, built a substantial mound of stone; discovery cut bears S. 24°26' W., 730 ft. dist.
476.3	Cor. No. 2, identical with Cor. No. 1 of the Lone Star lode of this survey. Set a ½ inch iron pipe, 30 inches long, 18 inches in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked M L 2-L S 1-4601, with its center for exact corner point. No bearings available. Thence S. 24°36' W.
740.0	Wash, course southeasterly.

MINERAL SURVEY No. 4601

3.

xChains Feet 815.0	Mine road, bears SE. and NW.
1500.9	Cor. No. 3, identical with Cor. No. 4 of the Lone Star lode of this survey. Set a $\frac{1}{2}$ inch iron pipe, 30 inches long, 18 inches in the ground surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked M L 3-L S 4-4601 with its center for exact corner point. No bearings available. Thence N. $78^{\circ}32'$ W.
289.8	Lode line, built a substantial mound of stone; discovery cut bears N. $24^{\circ}26'$ E., 770 ft. dist.
476.0	Cor. No. 4, identical with Cor. No. 2 of the Stonewall lode of this survey. Thence N. $24^{\circ}35'$ E.
900.0	Mine road, bears east to west.
940.0	Wash, course east.
1500.9	Cor. No. 1, and the place of beginning.
LONE STAR LODE	
Beginning at Cor. No. 1 of the Lone Star lode, identical with Cor. No. 2 of the Missing Link lode of this survey, from which The corner to sections 7, 8, 17 and 18, T. 12 N., R. 2 E., G. & S.R. Meridian, Arizona, bears S. $67^{\circ}26'$ W., 401.0 ft. dist. No other bearings available. Thence S. $78^{\circ}32'$ E.	
295.0	Lode line, built a substantial mound of stone; discovery cut bears S. $24^{\circ}26'$ W., 1210 ft. dist.
595.6	Cor. No. 2. Set a $\frac{1}{2}$ inch iron pipe, 30 inches long, 18 inches in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked L S 2 4601 with its center for exact corner point. No bearings available. Thence S. $24^{\circ}26'$ W.
980.0	Wash, course easterly.
1495.47	Intersect line 1-2 Survey No. 2307 Copper Bottom lode at a point from which Cor. No. 2 identical with Cor. No. 1 Survey No. 2307 Copper Kettle lode bears S. $83^{\circ}30'$ W., 10.05 ft. dist.
1500.0	Cor. No. 3. Set a $\frac{1}{2}$ inch iron pipe, 30 inches long, 18 inches in the ground, surrounded by a substantial mound of stone, fitted with a three

Chains
Feet

inch floor flange with copper plate bolted thereon, marked LS 3-4601 with its center for exact corner point, from which

Cor. No. 1 of the Copper Kettle lode, identical with Cor. No. 2 of the Copper Bottom lode, both of Survey No. 2307, bears N. 69°51' W., 8.65 ft. dist.

No other bearings available.

Thence N. 78°32' W.

8.13 Intersect line 4-1 of the Copper Kettle lode, identical with line 2-3 of the Copper Bottom lode, both Survey No. 2307, at a point from which Corners No. 1 and 2 respectively, bears N. 6°30' W., 1.36 ft. dist.

12.58 Intersect line 1-2 of the Survey No. 2307 Copper Kettle lode at a point from which Cor. No. 1 bears N. 83°30' E., 4.23 ft. dist.

300.6 Lode line, built a substantial mound of stone; discovery cut bears N. 24°26' E., 290 ft. dist.

600.0 Cor. No. 4, identical with Cor. No. 3 of the Missing Link lode of this survey.

Thence N. 24°36' E.

685.0 Mine road, bears SE. and NW.

760.0 Wash, course southeasterly.

1500.9 Cor. No. 1, and the place of beginning.

SURVEY No. 4601

AREAS

	Acres
Total area, Stonewall lode	20.546
Total area, Missing Link lode	15.978
Total area, Lone Star lode	20.060
Area in conflict with	
Survey No. 2307, Copper Bottom lode000
Survey No. 2307, Copper Kettle lode000

LOCATION

This survey is located in the SE. ¼, Sec. 7; SW. ¼, Sec. 8; NW. ¼, Sec. 17; and NE. ¼, Sec. 18, T. 12 N., R. 2 E., Gila and Salt River Meridian, Arizona.

The survey of these lodes is identical with the respective locations or amended locations of the lodes as marked upon the ground.

Chains

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of each of the lodes locations embraced in said mining claim by the claimant or his grantors are as follows:

- | | | | |
|-------|--|------------------------|---------------------|
| No. 1 | The discovery shaft of the Stonewall lode, the center of which being the discovery, is on the lode line S. 24°26' W., 690 feet from a point on line 4-1, 306.8 feet from Cor. No. 4; shaft 5x6x35 feet deep with tunnel 4x6x45 feet bearing southwest. | Value, shaft
Tunnel | \$ 700.00
600.00 |
| No. 2 | A trench, the southerly end of which bears N. 24°26' E. 715 feet from the southerly lode line monument of the Stonewall lode; trench 4x6x37 feet long in wash and now filled, bears Southwest. | Value | 370.00 |
| No. 3 | A cut, the mouth of which bears S. 29°45' W., 830 feet from Cor. No. 1 of the Stonewall lode, cut 5x18x10 foot face, tunnel 4x6x8 foot, running southwesterly under a shaft 6x8x10 feet deep. | Value, cut
Shaft | 150.00
150.00 |
| No. 4 | A cut and tunnel, the mouth of cut bears S. 31°30' W., 655 feet from Cor. No. 1 of the Stonewall lode; cut 4x4x12 foot face bears S. 9° W., 41 feet to mouth of tunnel, thence S. 15° W., at 38 feet north edge of winze 4x10x10 feet deep, 75 feet; thence west 15 feet to drift, running northerly 4 feet to face, also running S. 5° W., 20.0 feet, thence S. 20° E., 15 feet to face of tunnel, having a total length 133.0 feet | Value, cut
Tunnel | 400.00
1295.00 |
| No. 5 | A cut and tunnel, the mouth of cut bears S. 29°15' W., 715 feet from Cor. No. 1 of the Stonewall lode; cut 4x24x12 foot face bears S. 4°30' W., 24 feet to mouth of tunnel, thence S. 30° W. at 36 feet north edge of winze 4x6x10 feet deep, 56 feet to turn, thence S. 40° W., 34 feet to turn, thence S. 40° W. 3.5 feet to face, also south, 15.0 feet to face, having a total length of 108.5 feet. | Value, cut
Tunnel | 240.00
1085.00 |
| No. 1 | The discovery cut and tunnel of the Missing Link lode, the center face of cut being the discovery point, is on the lode line S. 24°26' W., 730 feet from a point on line 1-2, 181.9 feet from Cor. No. 1; cut 4x17x16 foot face, bears S. 58° W. at 17 feet to mouth of tunnel, 38 feet to face of tunnel, 4x6x21 feet long. | Value, cut
Tunnel | 150.00
210.00 |
| No. 2 | A shaft, the center of which bears S. 5°45' W., 510 feet from Cor. No. 1 of the Missing Link lode; 5x8x20 feet deep, with tunnel in bottom 4x6x10 feet bears northerly. | Value, shaft
Tunnel | 200.00
150.00 |

XXXX		
No. 3	A cut and shaft, the mouth of cut bears N. 62°20' E., 460 feet from Cor. No. 4 of the Missing Link lode; cut 4x15x6 foot face with shaft in bottom of cut 4x6x15 feet deep, cut bears westerly.	
	Value, cut	\$ 100.00
	Shaft	150.00
No. 4	A cut, the mouth of which bears N. 74°40' E., 450 feet from Cor. No. 4 of the Missing Link lode; cut 6x30x12 foot face bears westerly.	
	Value, cut	200.00
No. 5	A shaft, the center of which bears N. 81°15' E., 465 feet from Cor. No. 4 of the Missing Link lode; shaft 6x8x35 feet deep.	
	Value, shaft	500.00
No. 6	A shaft, the center of which bears N. 13° E., 265 feet from Cor. No. 3 of the Missing Link lode; shaft 8x12x35 feet deep, stoped.	
	Value, shaft	700.00
No. 1	The discovery cut of the Lone Star lode, the center face of cut being the discovery point, is on the lode line, N. 24°26' E., 290 feet from a point on line 3-4, 300.6 ft. from Cor. No. 3; cut 4x16x10 foot face, bears southerly.	
	Value, cut	125.00
No. 2	A cut and tunnel, the mouth of cut bears N. 34°15' E., 645 feet from Cor. No. 4 of the Lone Star lode; cut 4x22x12 foot face bears S. 75° W., 22 feet to mouth of tunnel, thence west at 25 feet, winze 4x6x2 feet deep, 48 feet face of tunnel, total 4x6x48 feet.	
	Value, cut	150.00
	Tunnel	480.00
	Winze	25.00
No. 3	A shaft, the center of which bears S. 73°30' E., 190 feet from Cor. No. 1 of the Lone Star lode; shaft 4x6x8 feet deep.	
	Value, shaft	100.00
No. 4	A cut, the face of which bears N. 20°15' E., 430 feet from Cor. No. 3 of the Lone Star lode; cut 4x15x12 foot face bears southwesterly.	
	Value, cut	200.00
No. 5	A cut, the mouth of which bears N. 23° E., 560 feet from Cor. No. 3 of the Lone Star lode; cut 4x15x10 foot face, bears northeasterly.	
	Value, cut	175.00

Chains

arbitrarily

OTHER IMPROVEMENTS

Hoist and small gallows frame.

OTHER CORNER DESCRIPTIONS

Survey No. 2307; the corners of this survey are stones, scribed with number of the corner and survey, and are in good condition and as described in the official field notes of said survey. Lines are as shown as approved in the official record.

FIELD ASSISTANTS

Raymond W. White

Logan Culp

8

FIELD ASSISTANTS

Chains

Chains

OTHER IMPROVEMENTS

Don't say what follows (year)

OTHER OTHER DECISION

Survey No. 107: The corners of this survey are shown, situated
 1/4th corner of the corner and survey, and are 1/4th of 1/4th
 will be described in the official field notes of said survey.
 This and as shown as approved in the official record.

FIELD ASSISTANTS

George M. White

Robert G. ...

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Prescott Arizona.
OCTOBER 22, 1962

I, J. WILLIAM WAARA

Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____

office Cadastral Engineer _____, at Phoenix Arizona.

dated Sept. 24, 1962
Oct. 2, 1962, Amd., I have faithfully and correctly executed the survey of

the mining claim of HOMER L. WRIGHT

known as the Stonewall, Missing Link and Lone Star lodes.

(Lode, placer, or mill site)

situate in Sections 7-8-17-18 T. 12 N. R. 2 E. G & S.R.M

T. 12 N., R. 2 E. G. & S.R. Meridian, ARIZONA, and

(State)

designated as Survey No. 4601, which is represented in the foregoing field notes as having been executed by me and under my direction, and that said survey has been made in strict conformity with said order, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes, and I do further certify that the labor expended and improvements made

upon or for the benefit of the lodes location(s) embraced in the said mining claim by

(Lode or placer)

claimant(s) or his grantors are fully stated in my report therein, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Prescott Arizona.

Oct. 22, 1962

(Place)

J. William Waara

(Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management, State Office

(Office)

Phoenix, Arizona November 8, 1962

(Place)

(Date)

The foregoing field notes of mineral survey No. 4601, in Agua Fria Mining District,

Secs. 7, 8, 17, 18, T. 12 N., R. 2 E., G. & S. R. Meridian,

Arizona, executed by J. William Waara, Mineral Surveyor,

(State)

Sept. 24, 1962 and

under order dated Oct. 2, 1962, Amd., having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

Raymond C. Cleghorn

Raymond C. Cleghorn

Acting State Director

(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____ is a true copy of the original field notes.

(Title)

