

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey Number

4608

State

Arizona

Land District

Arizona

FIELD NOTES

Of the Survey of the Mining Claim of (Name & address of Claimant)

Banner Mining Company
c/o Twitty, Sievwright & Mills
Attorneys at Law
Title & Trust Building
Phoenix, 3, Arizona

Known as the (Name of group, if any)

Parrot Group

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

| NAME OF LOCATION | DATE | |
|---------------------------|---------|---------------------------------|
| | LOCATED | AMENDED |
| Parrot Nos. 1 & 2 | 2/6/16 | 7/2/63 |
| Parrot Nos. 3 & 4 | 2/6/16 | 7/2/63 Second Amended 8/1/63 |
| Parrot No. 5 | 2/6/16 | 7/3/63 |
| Parrot Numbers 10 thru 12 | 2/5/16 | 7/2/63 |
| Parrot No. 13 | 2/5/16 | 7/2/63 |
| Parrot Numbers 15 thru 19 | 2/5/16 | 7/2/63 |
| Parrot Numbers 22 & 23 | 2/5/16 | 7/2/63 |
| Parrot Nos. 24 thru 28 | 2/5/16 | 7/2/63 |

| | | | |
|------------------|------------------|--------------------------|--------------------------------|
| Mining District | | County | Section |
| Greenlee | | Greenlee | 25, 26, 35, 36 30, 31. |
| Township | Range | Meridian | Surveyed under order dated |
| 3 S. 3 S. | 29 E. 30 E. | Gila and Salt River | Mar. 25, 1963 Aug. 20, 1963 |
| Survey commenced | Survey completed | Name of Mineral Surveyor | |
| Mar. 25, 1963 | Aug. 24, 1963 | Harvey W. Smith | |

SURVEY NO. 4608

(1)

Chain
Feet

This survey was made with a Swiss Kern theodolite transit, model DKMI, No. 77769, having horizontal and vertical circles, 50 mm. in diam. The circles are graduated in degrees and twenty-minute increments. An optical micrometer, adjustable to the vertical and horizontal circles, permits the reading of angles direct to 10 seconds accuracy and estimating to one-second accuracy. The instrument is equipped with a colored eye-shade to be attached for making direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian established by direct observation on the sun. At 10:00 AM on March 28, 1963 at cor. No.1 of the Parrot No.1 lode, latitude $33^{\circ}07'59''$ North, longitude $109^{\circ}17'33.2''$ West, turning from a reference pt. about 800 ft. southeast clockwise to the sun in a southeast direction.

True reference of bearing pt.
S. $35^{\circ}07'25''$ E.

The lines were measured with a Lufkin "Highway" steel tape, 300 ft. in length graduated every ft. for 299 ft. and the remaining ft. graduated to tenths and hundredths. One additional ft. at the "0" end of the tape is also graduated in tenths and hundredths. The tape was compared to a standard and found to be correct. All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 13° East.

SURVEY NO. 4608

PARROT NO. 1 LODE

At cor. No.1 of the Parrot No.1 lode, identical with cor. No.1 of the Parrot No.2 lode of this survey.

Set a galvanized iron post, $3/4$ in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P1.1 P2.1 X; from which

The cor. of secs. 25, 30, 31 & 36, T. 3 S., Rs. 29 & 30 E., G. & S. R. B. & M., bears S. $22^{\circ}44'10''$ E. 39.92 ft. dist.; an iron post 2 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the official record.

A mound of stones constructed and painted yellow adjacent to the iron post.

Thence S. $50^{\circ}05'50''$ W.

- 450.0 Left bank of creek, 20 ft. wide, course S. 50° E.
 583.10 Unimproved road bears S. 35° E. and N. 35° W.
 1098.10 Unimproved road bears N. 5° W. and S. 20° E.
 1268.10 Unimproved road bears N. 67° W. and S. 60° E.
 1498.10 Cor. No.2 identical with cor. No.2 of the Parrot No.4 lode, cor. No.1 of the Parrot No.5 lode and cor. No.4 of the Parrot No.2 lode, all of this survey.

| -Chains Feet | |
|-----------------|--|
| | <p>Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P1 2 P2 4 P4 2 P5 1 X; from which</p> |
| | <p>The cor. of secs. 25,30,31&36, T.3S., Rs. 29&30E., G.&S.R.B.&M., bears N.51°34'E. E., 1486.82 ft. dist.; previously described.</p> |
| | <p>A mound of stones constructed and painted yellow adjacent to the iron post.</p> |
| | <p>Thence N.35°24'35"W.</p> |
| 293.06 | <p>Lode line; discovery cut bears N.49°49'55"E., 1323.67 ft. dist.</p> |
| 553.23 | <p>Intersect line 2-3 of the Parrot Number 15 lode of this survey.</p> |
| 593.06 | <p>Cor. No.3 identical with cor. No.1 of the Parrot No.4 lode of this survey.</p> |
| | <p>Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P1 3 P4 1 X; from which</p> |
| | <p>The cor. of secs. 25,30,31&36, T.3S., Rs. 29&30E., G.&S.R.B.&M., bears N.73°42'25"E., 1,571.41 ft. dist.; previously described.</p> |
| | <p>A mound of stones constructed and painted yellow adjacent to the iron post.</p> |
| | <p>Thence N.49°49'55"E.</p> |
| 160.0 | <p>Unimproved road bears N.87°W. and S.80°E.</p> |
| 232.33 | <p>Intersect line 1-2 of the Parrot Number 15 lode, identical with line 3-4 of the Parrot No.13 lode, both of this survey.</p> |
| 685.0 | <p>Unimproved dirt road bears N.55°W. and S.35°E.</p> |
| 910.0 | <p>Unimproved dirt road bears N.30°W. and S.30°E.</p> |
| 950.0 | <p>Right bank of drainage, 20 ft. wide, course S.30°E.</p> |
| 1498.67 | <p>Cor. No.4</p> |
| | <p>Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P1 4 X; from which</p> |
| | <p>A mound of stones constructed and painted yellow adjacent to the iron post.</p> |
| | <p>Thence S.35°24'35"E.</p> |

| Chains Feet | |
|-------------------|---|
| .194.08 | Intersect line 2-3 of the Parrot No.13 lode of this survey. |
| 300.0 | Lode line; discovery cut bears S.49°49'55"W. 175.0 ft. dist. |
| 600.0 | Cor. No.1 and the place of beginning. |
| PARROT NO. 2 LODE | |
| | Beginning at cor. No.1 of the Parrot No.2 lode, identical with cor. No.1 of the Parrot No.1 lode of this survey; previously described. Thence S.35°07'25"E. |
| 300.0 | Lode line; discovery cut bears S.50°05'50"W., 58 ft. dist. |
| 581.99 | Left bank of drainage, 20 ft. wide, course S.60°E. |
| 596.99 | Cor. No.2 This cor. falls in drainage where a monument would be obliterated. Thence S.50°37'45"W. |
| 336.95 | Pt. for witness cor. to cor. No.2 identical with cor. No.1 of the Parrot No.3 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P2 2WC P3 1 X; from which The cor. of secs. 25,30,31&36, T.3S., Rs. 29&30E., G&S.R.B.&M., bears N.32°14'10"W., 561.44 ft. dist.; previously described. A mound of stones constructed and painted yellow, adjacent to the iron post. |
| 308.0 | Unimproved road bears north and south. |
| 1497.0 | Cor. No.3 identical with cor. No.2 of the Parrot No.5 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P2 3 P5 2 X; from which A mound of stones constructed and painted yellow, adjacent to the iron post. Thence N.35°07'25"W. |
| 1.87 | Intersect line 4-1 of the Parrot No.3 lode of this survey. |
| 283.03 | Lode line; discovery cut bears N.50°05'50"E., 1440.10 ft. dist. |

| Chains Feet | |
|-------------------|--|
| 583.03 | Cor. No.4 identical with cor. No.1 of the Parrot No.5 lode, cor. No.2 of the Parrot No.4 lode, and cor. No.2 of the Parrot No.1 lode, all of this survey; previously described. Thence N.50°05'50"E. |
| 230.0 | Unimproved road bears N.67°W. and S.60°E. |
| 400.0 | Unimproved road bears N.5°W., and S.20°E. |
| 015.0 | Unimproved road bears S.35°E. and N.35°W. |
| 1028.10 | Right bank of creek, 20 ft. wide, course S.50°E. |
| 1498.10 | Cor. No.1 and the place of beginning. |
| PARROT NO. 3 LODE | |
| | Beginning at cor. No.1 of the Parrot No.3 lode, identical with the witness cor. for cor. No.2 of the Parrot No.2 lode of this survey and on line 2-3 of the Parrot No.2 lode of this survey; previously described. Thence S.35°07'25"E. |
| 245.0 | Lode line; discovery pt. bears S.50°42'10"W., 720 ft. dist. |
| 489.80 | Cor. No.2 Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P3 2 X; from which A mound of stones constructed and painted yellow, adjacent to the iron post. Thence S.50°42'10"W. |
| 440.0 | Unimproved road bears N.85°E. and S.85°W. |
| 1069.60 | Intersect line 4-1, Sur. No.4224A, Belfast lode, at a pt. from which cor. No.4 bears N.38°50'W., 15.45 ft. dist. |
| 1320.0 | Left bank of drainage, 20 ft. wide, course S.65°E. |
| 1500.0 | Cor. No.3 Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P3 3 X; from which Cor. No.4, Sur. No. 4224A, Belfast lode, bears N.48°38'50"E., 430.81 ft. dist. Cor. No.1, Sur. No. 4224A, Governor No.2 lode, bears N.27°26'20"E., 47.74 ft. dist. A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.35°07'25"W. |

SURVEY NO. 4608

(5)

| Chain Feet | |
|--------------------|--|
| 19.19 | Intersect line 1-2, Sur. No. 4224A, Governor No. 2 lode, in part common with line 3-4, Sur. No. 4224A, Belfast lode at a pt. from which cor. No. 1 of the Governor No. 2 lode bears N. 51° 05' E. 42.46 ft. dist. and cor. No. 4 of the Belfast lode bears N. 51° 05' E. 42.26 ft. thence N. 51° 12' 20" E., 386.69 ft. dist. |
| 244.80 | Lode line; discovery pt. bears N. 50° 42' 10" E., 780 ft. dist. |
| 305.0 | Right bank of drainage, 20 ft. wide, course S. 72° E. |
| 489.80 | Cor. No. 4 on line 2-3 of the Parrot No. 5 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P3 4 X; from which A mound of stoned constructed and painted yellow adjacent to the iron post. Thence N. 50° 42' 10" E. |
| 12.01 | Intersect line 4-1, Sur. No. 4224A, Governor No. 2 lode, at a pt. from which cor. No. 1 bears S. 38° 50' E., 469.67 ft. dist. |
| 40.10 | Intersect line 1-2 of the Parrot No. 5 lode, common with line 3-4 of the Parrot No. 2 lode, both of this survey. |
| 1225.0 | Unimproved dirt road bears north and south. |
| 1500.0 | Cor. No. 1 and the place of beginning. |
| PARROT NO. 4 LODGE | |
| | Beggining at cor. No. 1 of the Parrot No. 4 lode, identical with cor. No. 3 of the Parrot No. 1 lode of this survey; previously described. Thence S. 35° 24' 35" E. |
| 39.83 | Intersect line 2-3 of the Parrot Number 15 lode of this survey. |
| 300.0 | Lode line; discovery cut bears S. 54° 17' 15" W., 165.0 ft. dist. |
| 593.06 | Cor. No. 2 identical with cor. No. 2 of the Parrot No. 1 lode, cor. No. 4 of the Parrot No. 2 lode and cor. No. 1 of the Parrot No. 5 lode, all of this survey; previously described. Thence S. 54° 01' 20" W. |
| 1030.0 | Left bank of drainage, 10 ft. wide, course S. 60° E. |
| 1143.85 | Intersect line 1-2, Sur. No. 4245A, Gold Standard No. 14 lode at a pt. from which cor. No. 1 bears N. 40° 12' 35" W., 36.02 ft. dist. |

| Chains | |
|---------|---|
| Feet | |
| 1179.65 | Left bank of drainage, 20 ft. wide, course, N.82°E. |
| 1499.65 | Cor. No.3 identical with cor. No.4 of the Parrot No.5 lode of this survey. This cor. falls on a loose talus slope where a permanent monument would be obliterated; from this pt. cor. No.1, Sur. No. 4245A, Gold Standard No. 14 lode, bears N.48° 12'45"E., 354.97 ft. dist.; cor. No.2, Sur. No. 4245A, Gold Standard No.18 lode, bears N.6°02'20"W., 105.24 ft. dist.; Cor. No.4, Sur. No. 4224A, Governor lode, identical with cor. No.3, Governor No.2 lode of the same survey, bears S.89°18'15"E., 820.29 ft. dist. and cor. No.2, Sur. No.4245A, Gold Standard No.14 lode, bears S.76°21'30"E., 601.53 ft. dist. Thence N.35°24'35"W. |
| 66.45 | Pt. for witness cor. for cor. No.3 identical with cor. No.4 of the Parrot No.5 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P4 3WC P5 4WC X; from which A mound of stones constructed and painted yellow adjacent to the iron post. |
| 88.55 | Intersect line 2-3, Sur. No.4245A, Gold Standard No.18 lode, in part common with line 4-1, Sur. No.4245A, Gold Standard No.14 lode at a pt. from which cor. No. 2 of the Gold Standard No.18 lode bears N.51°05'E., 51.71 ft. dist. and cor. No.1 of the Gold Standard No. 14 lode bears N.51°05'E., 51.71 ft.; thence N.64°26' 20"E., 305.65 ft. |
| 190.0 | Right bank of drainage, 15 ft. wide, course N.85°E. |
| 300.0 | Lode line; discovery pt. bears N.54°17'15"E., 1334.56 ft. dist. |
| 495.73 | Intersect line 2-3 of the Parrot Number 10 lode of this survey. |
| 497.82 | Intersect line 1-2, Sur. No. 4245A, Gold Standard No.18 lode, at a pt. from which cor. No.2 bears S.42°39'10"E., 409.36 ft. dist. |
| 500.0 | Pt. for witness cor. for cor. No.4. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P4 4WC x; from which A mound of stones constructed and painted yellow adjacent to the iron post. |
| 592.0 | Right bank of drainage, 10 ft. wide, course S.45°E. |

SURVEY NO. 4608

(7)

| Chains | |
|-------------------|--|
| Feet | |
| 600.0 | Cor. No.4 This cor. falls in drainage and a monument would soon be obliterated. Thence N.54°17'15"E. |
| 282.33 | Intersect line 3-4 of the Parrot Number 15 lode of this survey. |
| 317.32 | Intersect line 1-2 of the Parrot Number 10 lode of this survey. |
| 355.0 | Right bank of drainage, 10 ft. wide, course S.35°E. |
| 1499.56 | Cor. No.1 and the place of beginning. |
| PARROT NO. 5 LODE | |
| | Beginning at cor. No.1 of the Parrot No.5 lode identical with cor. No.2 of the Parrot No.4 lode, cor. No.2 of the Parrot No.1 lode and cor. No.4 of the Parrot No.2 lode, all of this survey; previously described. Thence S.35°07'25"E. |
| 300.0 | Lode line; discovery pt. bears S.54°01'20"W., 25.0 ft. dist. |
| 581.16 | Intersect line 4-1 of the Parrot No.3 lode of this survey. |
| 583.03 | Cor. No.2 identical with cor. No.3 of the Parrot No.2 lode of this survey; previously described. Thence S.53°22'25"W. |
| 27.98 | Intersect line 4-1, Sur. No. 4224A, Governor No.2 lode at a pt. from which cor. No. 4 bears N.38°50'W., 130.89 ft. dist. |
| 40.0 | Cor. No.4 of the Parrot No.3 lode of this survey. |
| 175.0 | Left bank of drainage, 20 ft. wide, course S.68°E. |
| 827.59 | Intersect line 2-3, Sur. No. 4224A, Governor No.2 lode, common with line 4-1, Governor lode of the same survey at a pt. from which cor. No.3 of the Governor No.2 lode, identical with cor. No.4 of the Governor lode bears N.38°50'W., 102.83 ft. dist. |
| 1500.0 | Cor. No.3 Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P5 3 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.35°07'25"W. |

| Chains | |
|---------|--|
| Feet | |
| 121.65 | Intersect line 2-3, Sur. No. 4245A, Gold Standard No.14 lode, in part common with line 3-4, Sur. No. 4224A, Governor lode at a pt. from which cor. No.2 of the Gold Standard No.14 lode bears N.51°05'E., 397.75 ft. dist. and cor. No.4 of the Governor lode bears N.51°05'E., 397.75 ft. dist.; thence N.60°45'50"E., 270.07 ft. dist. |
| 300.0 | Lode line; discovery pt. bears N.54°01'20"E., 1474.65 ft. dist. |
| 600.0 | Cor. No.4 identical with cor. No.3 of the Parrot No.4 lode of this survey; previously described. Thence N.54°01'20"E. |
| 300.0 | Right bank of drainage, 20 ft. wide, course N.82°E. |
| 355.80 | Intersect line 1-2, Sur. No. 4245A, Gold Standard No.14 lode, at a pt. from which cor. No.2 bears S.40°12'35"E., 459.48 ft. dist. |
| 459.65 | Right bank of drainage, 10 ft. wide, course, S.60°E. |
| 1499.65 | Cor. No.1 and the place of beginning. |
| | PARROT NO. 13 LODE |
| | At cor. No.1 of the Parrot No. 13 lode, Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P13 1 X; from which The cor. of secs. 25,30,31&36, T.3S., Rs. 29&30E., bears S.29°02'45"E., 1,032.61 ft. dist.; previously described. A mound of stones constructed and painted yellow adjacent to the iron post. Thence S.47°51'55"E. |
| 300.0 | Lode line; discovery cut bears S.55°41'15"W., 1382.96 ft. dist. |
| 600.0 | Cor. No.2 Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P13 2 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence S.55°41'15"W. |
| 235.13 | Intersect line 4-1 of the Parrot No.1 lode of this survey. |

SURVEY NO. 4608

(9)

| Chains- Feet | |
|-----------------|--|
| 770.0 | Left bank of drainage, 20 ft. wide, course S. 35°E. |
| 820.0 | Unimproved dirt road bears S.38°E. and N.38°W. |
| 1075.0 | Unimproved dirt road bears S.20°E, and N.20°W. |
| 1482.96 | Cor. No.3 identical with cor. No.2 of the Parrot Number 15 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P13 3 P15 2 X; from which A mound of stones constructed and painted yellow, adjacent to the iron post. Thence N.47°51'55"W. |
| 66.72 | Intersect line 3-4 of the Parrot No.1 lode of this survey. |
| 300.0 | Lode line; discovery cut bears N.55°41'15"E., 100 ft. dist. |
| 600.0 | Cor. No.4 identical with cor. No. 1 of the Parrot Number 15 lode and cor. No.2 of the Parrot Number 16 lode, both of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete, rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P13 4 P15 1 P16 2 X; from which The cor. of secs. 25,30,31&36, T.3S., R.29 &30E., bears S.87°47'05"E., 1,727.52 ft. dist.; previously described A mound of stones constructed and painted yellow, adjacent to the iron post. Thence N.55°41'15"E. |
| 930.0 | Right bank of drainage, 20 ft. wide, course, S.40°E. |
| 1482.96 | Cor. No.1 and the place of beginning. |

PARROT NUMBER 15 LODE

Beginning at cor. No.1 of the Parrot Number 15 lode, identical with cor. No.4 of the Parrot No.13 lode and cor. No.2 of the Parrot Number 16 lode, both of this survey; previously described.

Thence S.47°51'55"E.

| | |
|--------|---|
| 300.0 | Lode line; discovery pt. bears S.55°58'45"W., 1082.69 ft. dist. |
| 533.28 | Intersect line 3-4 of the Parrot No.1 lode of this survey. |

| Chains- Feet | |
|---|---|
| 600.0 | Cor No.2 identical with cor. No.3 of the Parrot No.13 lode of this survey; previously described. Thence S.56°00'00"W. |
| 246.01 | Intersect line 2-3 of the Parrot No.1 lode, common with line 1-2 of the Parrot No.4 lode, both of this survey. |
| 1390.0 | Left bank of drainage, 10' wide, course, S.35°E. |
| 1427.82 | Intersect line 1-2 of the Parrot no. 10 lode of this survey. |
| 1462.82 | Cor. No.3 Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P15 3 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.47°51'55"W. |
| 3.54 | Intersect line 4-1 of the Parrot No. 4 lode of this survey. |
| 299.43 | Lode line; discovery pt. bears N.55°58'45"E., 380.0 ft. dist. |
| 497.35 | Intersect line 4-1 of the Parrot Number 10 lode, common with line 2-3 of the Parrot Number 11 lode, both of this survey. |
| 599.43 | Cor. No.4 identical with cor. No.3 of the Parrot Number 16 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P15 4 P16 3 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.55°58'45"E. |
| 65.53 | Intersect line 1-2 of the Parrot Number 11 lode of this survey. |
| 1225.0 | Unimproved road bears N.35°W. and S.35°E. |
| 1462.69 | Cor. No.1 and the Place of beginning. |
| PARROT NUMBER 16 LODE | |
| At cor. No.1 of the Parrot Number 16 lode. | |
| Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P16 1 X; from which The cor. of secs. 25, 30 31&36, T.3S., | |

SURVEY NO. 4608

(11)

| Feet Chains | |
|----------------|---|
| | Rs. 29 & 30 E.; G.&S.R.B.&M., bears S.77° 48'10"E., 2,221.29 ft. dist.; previously described. Cor. No. 6, Sur. No. 947, Merrimac lode, bears S.16° 07'20"W., 7.13 ft. dist. A mound of stones constructed and painted yellow adjacent to the iron post. Thence S.47° 51'55"E. |
| 300.0 | Lode line; discovery cut bears S.55° 55'10"W., 200 ft. dist. |
| 600.0 | Cor. No. 2 identical with cor. No. 1 of the Parrot Number 15 lode and cor. No. 4 of the Parrot No. 13 lode, both of this survey; previously described. Thence S.55° 58'45"W. |
| 237.69 | Unimproved road bears N.35° W. and S.35° E. |
| 1397.16 | Intersect line 1-2 of the Parrot Number 11 lode of this survey. |
| 1462.69 | Cor. No. 3 identical with cor. No. 4 of the Parrot Number 15 lode of this survey; previously described. Thence N.47° 51'55"W. |
| 298.41 | Lode line; discovery cut bears N.55° 55'10"E., 1262.29 ft. dist. |
| 447.75 | Intersect line 4-1 of the Parrot Number 11 lode common with line 2-3 of the Parrot Number 12 lode, both of this survey. |
| 498.41 | Pt. for witness cor. for cor. No. 4 identical with cor. No. 3 of the Parrot Number 22 lode and cor. No. 2 of the Parrot Number 23 lode, both of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P16 4WC P22 3WC P23 2WC X; from which A mound of stones constructed and painted yellow adjacent to the iron post. |
| 598.41 | Cor. No. 4 identical with cor. No. 3 of the Parrot Number 22 lode and cor. No. 2 of Parrot Number 23 lode, both of this survey. This cor. falls on a loose talus slope where a permanent monument would soon be obliterated. Thence N.55° 55'10"E. |
| 75.0 | Unimproved road bears N.55° W. and S.40° E. |
| 101.68 | Intersect line 1-2 of the Parrot Number 12 lode of this survey. |
| 185.0 | Unimproved road bears North and S.3° W. |
| 1015.0 | Unimproved road bears N.55° W. and S.55° E. |
| 1298.13 | Cor. No. 2 of the Parrot Number 22 lode of this survey. |
| 1377.63 | Intersect line 5-6, Sur. No, 947, Merrimac lode, at a pt. |

| Feet Chains | |
|-----------------------|--|
| | from which cor. No. 6 bears N.59°13'E., 79.31 ft. dist. |
| 1455.38 | Intersect line 6-1, Sur. No. 947, Merrimac lode, at a pt. from which cor. No. 6 bears S.51°30'E., 4.78 ft. dist. |
| 1462.29 | Cor. No. 1 and the place of beginning. |
| PARROT NUMBER 22 LODE | |
| | At cor. No. 1 of the Parrot Number 22 lode. |
| | This pt. falls on an inaccessible sheer bluff where a permanent monument cannot be placed. From this pt. |
| | The cor. of secs. 25, 26, 35 & 36, T.3S., R.29E., G.&S.R.B.&M., bears S.74°49'20"W., 2,533.13 ft. dist., an iron post, 2 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the official record. |
| | Cor. No. 5, Sur. No. 947, Merrimac lode, bears S.20°38'50"W., 812.25 ft. dist. |
| | Thence S.62°23'55"E. |
| 35.33 | Pt. for witness cor. for cor. No. 1 |
| | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P22 LWC X; from which |
| | A mound of stones constructed and painted yellow adjacent to the iron post. |
| 140.0 | Left bank of drainage, 20 ft. wide, course, east. |
| 300.0 | Lode line; discovery pt. bears S.55°55'10"W., 1173.13 ft. dist. |
| 594.67 | Intersect line 5-6, Sur. No. 947, Merrimac lode, at a pt. from which cor. No. 5 bears S.59°13'W., 946.80 ft. dist. |
| 600.0 | Cor. No. 2 on line 4-1 of the Parrot Number 16 lode of this survey. |
| | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P22 2 X; from which |
| | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | Thence S.55°55'10"W. |
| 283.13 | Unimproved road bears N.55°W. and S.55°E. |
| 1113.13 | Unimproved road bears North and S.3°W. |
| 1196.45 | Intersect line 1-2 of the Parrot Number 12 lode of this survey. |
| 1223.13 | Unimproved road bears N.55°W. and S.40°E. |

SURVEY NO. 4608

14
(13)

| Feet | |
|-----------------------|---|
| 1298.13 | Cor. No. 3 identical with cor. No. 4 of the Parrot Number 16 lode and cor. No. 2 of the Parrot Number 23 lode, both of this survey; previously described. |
| | Thence N.62°23'55"W. |
| 86.28 | Intersect line 4-1 of the Parrot Number 12 lode of this survey. |
| 300.0 | Lode line; discovery pt. bears N.55°55'10"E., 125 ft. dist. |
| 300.0 | Unimproved road bears S.70°W. and N.70°E. |
| 583.20 | Cor. No. 4 identical with cor. No. 1 of the Parrot Number 23 lode of this survey. |
| | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P22 4 P23 1 X; from which |
| | The cor. of secs. 25, 26, 35 & 36, T.3S., R.29E., G.&S.R.B.&M., bears N.87°01'25"W., 1386.31 ft. dist.; previously described. |
| | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | Thence N.55°15'45"E. |
| 482.82 | Intersect line 3-4, Sur. No. 947, Merrimac lode, at a pt. from which cor. No. 4 bears S.51°30'E., 181.89 ft. dist. |
| 1120.0 | Right bank of drainage, 20 ft. wide, course, east. |
| 1290.26 | Cor. No. 1 and the place of beginning. |
| PARROT NUMBER 23 LODE | |
| | Beginning at cor. No. 1 of the Parrot Number 23 lode, identical with cor. No. 4 of the Parrot Number 22 lode of this survey; previously described. |
| | Thence S.62°23'55"E. |
| 283.20 | Lode line; discovery pt. bears S.56°54'30"W., 450 ft. dist. |
| 283.20 | Unimproved road bears S.70°W. and N.70°E. |
| 496.92 | Intersect line 4-1 of the Parrot Number 12 lode of this survey. |
| 583.20 | Cor. No. 2 identical with cor. No. 3 of the Parrot Number 22 lode and cor. No. 4 of the Parrot Number 16 lode, both of this survey; previously described. |
| | Thence S.56°54'30"W. |
| 593.98 | Intersect line 3-4 of the Parrot Number 12 lode, in part common with line 1-2 of the Parrot Number 19 lode, both of this survey. |
| 1162.48 | Right bank of drainage, 10 ft. wide, course N.30°E. |
| 1170.48 | Cor. No. 3 |
| | This pt. falls in drainage where a permanent monument would soon be obliterated |

15

SURVEY NO. 4608

(14)

Feet
Chains

| | |
|---------|--|
| | Thence N.62°23'55"W. |
| 95.70 | Pt. for witness cor. for cor. No. 3 identical with cor. No. 3 of the Parrot No. 26 lode and cor. No. 2 of the Parrot No. 24 lode, both of this survey. Set a galvanized iron post, 3/4 in diam., 14 ins. long in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS.4608 P23 3WC P26 3 P24 2 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. |
| 300.0 | Lode line; discovery pt. bears N.56°54'30"E., 720.48 ft. dist. |
| 341.03 | Intersect line 4-1 of the Parrot Number 19 lode of this survey. |
| 600.0 | Cor. No. 4 on line 3-4 of the Parrot No. 26 lode, common with line 1-2 of the Parrot No. 24 lode, both of this survey. Set a galvanized iron post, 3/4 in diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P23 4 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. |
| | Thence N.57°37'10"E. |
| 976.90 | Intersect line 1-2 of the Parrot No. 26 lode, common with line 4-1 of the Parrot No. 28 lode, both of this survey. |
| 976.90 | Unimproved road bears N.60°W. and S.60°E. |
| 1015.0 | Left bank of drainage, 10 ft. wide, course N.30°E. |
| 1106.53 | Intersect line 3-4 of the Parrot No. 28 lode of this survey. |
| 1178.79 | Cor. No. 1 and the place of beginning. |

PARROT NUMBER 12 LODE

At cor. No. 1 of the Parrot Number 12 lode.

Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 Pl2 1 X; from which

The cor. of secs. 25,26,35 & 36, T.3S., R.29E., G.&S.R.B.&M., bears N.83°13'30"W., 1,944.82 ft. dist.; previously described.

A mound of stones constructed and painted yellow adjacent to the iron post.

Thence S. 44°13'E.

| Chains | Feet | |
|--------|------|---|
| 77.81 | | Intersect line 2-3 of the Parrot Number 22 lode, in part common with line 4-1 of the Parrot Number 16 lode, both of this survey. |
| 113.20 | | Lode line; discovery cut bears S.55°38'10"W., 593.14 ft. dist. |
| 165.0 | | Unimproved road bears N.5°E. and S.10°W. |
| 225.98 | | Cor. No.2 identical with cor. No.1 of the Parrot Number 11 lode of this survey. |
| | | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P12 2 P11 1 X; from which |
| | | The cor. of secs. 25,26,35&36, T.3S., R.29 E., G.&S.R.B.&M., bears N.79°23'15"W., 2125.18 ft. dist.; previously described. |
| | | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | | Thence S.55°38'10"W. |
| 91.86 | | Intersect line 3-4 of the Parrot Number 16 lode of this survey. |
| 693.14 | | Cor. No.3 identical with cor. No.4 of the Parrot Number 11, cor. No.1 of the Parrot Number 18 and cor. No.2 of the Parrot Number 19 lode all of this survey. |
| | | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P12 3 P11 4 P18 1 P19 2 X; from which |
| | | The cor. of secs. 25, 26,35&36, T.3S., R.29 E., G.&S.R.B.&M., bears N.62°42'15"W., 1706.68 ft. dist.; previously described. |
| | | A mound of stones constructed and painted yellow adjacent to iron post. |
| | | Thence N.44°13'W. |
| 112.78 | | Lode line; discovery cut bears N.55°38'10"E., 100 ft. dist. |
| 112.78 | | Pt. for witness cor. for cor. No.4 on line 1-2 of the Parrot Number 19 lode of this survey. |
| | | Set a galvanized iron post, 3/4 in. diam., 14 ins. long in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P12 4WC X; from which |
| | | A mound of stones constructed and painted yellow adjacent to the iron post. |

17

SURVEY NO. 4608

(16)

| Chains | |
|-----------------------|--|
| Feet | |
| 162.07 | Intersect line 2-3 of the Parrot Number 23 lode of this survey. |
| 225.98 | Cor. No.4 on line 1-2 of the Parrot Number 19 lode of this survey. This cor. falls in an inaccessible precipitous area. Thence N.55°38'10"E. |
| 564.21 | Intersect line 1-2 of the Parrot Number 23 lode common with line 3-4 of the Parrot Number 22 lode, both of this survey. |
| 645.0 | Unimproved road bears N.60°W. and S.60°E. |
| 693.14 | Cor. No.1 and the place of beginning. |
| PARROT NUMBER 11 LODE | |
| | Beginning at cor. No. 1 of the Parrot Number 11 lode, identical with cor. 2 of the Parrot Number 12 lode of this survey; previously described. Thence S.44°32'15"E. |
| 270.0 | Lode line; discovery pt. bears S.53°10'40"W., 688.48 ft. dist. |
| 340.21 | Pt. for witness cor. for cor. No.2, identical with pt. for witness cor. for cor. No.1 of the Parrot Number 10 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P11 2WC P10 1WC X; from which A mound of stones constructed and painted yellow adjacent to the iron post. |
| 370.0 | Left bank of drainage, 10 ft. wide, course, S.48°E. |
| 442.73 | Intersect line 2-3 of the Parrot Number 16, common with line 4-1 of the Parrot Number 15 lode, both of this survey. |
| 540.0 | Cor. No.2 identical with cor. No.1 of the Parrot Number 10 lode of this survey. This cor. falls in drainage where a permanent monument would be obliterated. From this pt., The cor. of secs. 25,26,35&36, T.3S., R.29 E., G.&S.R.B.&M. bears N.72°32'10"W., 2586.78 ft. dist.; previously described. Thence S.52°36'W. |

SURVEY NO. 4608

18
(17)

Chains

Feet

- 58.95 Intersect line 3-4 of the Parrot Number 15 lode of this survey.
- 687.58 Cor. No.3 identical with cor. No.4 of the Parrot Number 10 lode, cor. No.1 of the Parrot Number 17 lode and cor. No.2 of the Parrot Number 18 lode, all of this survey.
- Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P11 3 P10 4 P17.1 P18 2 X; from which
- The cor. of secs. 25,26,35&36, T.3S., R. 29E., G.&S.R.B.&M., bears N.58°08'35"W., 2,262.08 ft. dist.; previously described.
- A mound of stones constructed and painted yellow adjacent to the iron post.
- Thence N.44°32'15"W.
- 277.0 Lode line and discovery pt.
- 577.0 Cor. No.4 identical with cor. No.1 of the Parrot Number 18 lode, cor. No.2; of the Parrot Number 19 lode and cor. No.3 of the Parrot Number 12 lode, all of this survey; previously described.
- Thence N.55°38'10"E.
- 601.28 Intersect line 3-4 of the Parrot Number 16 lode of this survey.
- 693.14 Cor. No.1 and the place of beginning.

PARROT NUMBER 10 LODE

- Beginning at cor. No.1 of the Parrot Number 10 lode identical with cor. No.2 of the Parrot Number 11 lode of this survey; previously described.
- Thence S.45°05'30"E.
- 274.30 Lode line and discovery pt.
- 491.05 Intersect line 4-1 of the Parrot No.4 lode of this survey.
- 495.61 Intersect line 2-3 of the Parrot Number 15 lode of this survey.
- 574.30 Cor. No.2
- Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P10 2 X; from which

8119

SURVEY NO. 4608

(18)

| Chains | Feet | |
|--------|------|---|
| | | Cor. No.1, Sur. No.4245A, Gold Standard No. 18 lode, bears S.80°20'25"W., 395.13 ft. dist. |
| | | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | | Thence S.50°28'05"W. |
| 290.0 | | Left bank of drainage, 10 ft. wide, course, S.42°E. |
| 331.91 | | Intersect line 1-2, Sur. No. 4245A, Gold Standard No. 18 lode, at a pt. from which cor. No.1 bears N.42°39'10" W., 197.10 ft. dist. |
| 332.17 | | Intersect line 3-4 of the Parrot No.4 lode of this survey. |
| 684.61 | | Cor. No.3 identical with cor. No.2 of the Parrot Number 17 lode of this survey. |
| | | This cor. falls on an inaccessible precipitous area. From this pt. |
| | | Cor. No.4, Sur. No. 4245A, Gold Standard No.18 lode, identical with cor. No.2 of the Greenlee No. 8 lode of the same survey; bears S.71°45'15"W., 580.64 ft. dist. |
| | | Thence N. 45°05'30"W. |
| 203.49 | | Intersect line 4-1, Sur. No.4245A, Gold Standard No.18 lode, at a pt. from which cor. No.1 bears N.51°22'30"E., 361.73 ft. dist. |
| 300.0 | | Lode line; discovery pt. bears N.50°28'05"E., 684.61 ft. dist. |
| 336.97 | | Pt. for witness cor. for. cor. No.3 identical with cor. No.2 of the Parrot Number 17 lode of this survey. |
| | | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P10 3WC P17 2WC X; from which |
| | | A mound of stones constructed and painted yellow adjacent to the iron post. |
| 600.0 | | Cor. No.4 identical with cor. No.1 of the Parrot Number 17 lode, cor. No. 2 of the Parrot Number 18 lode and cor. No.3 of the Parrot Number 11 lode, all of this survey; previously described. |
| | | Thence N.52°36'E. |
| 628.63 | | Intersect line 3-4 of the Parrot Number 15 lode of this survey. |
| 682.0 | | Right bank of drainage, 10 ft. wide, course S.48°E. |

| Chains- Feet | |
|---|---|
| 687.58 | Cor. No.1 and the place of beginning. |
| PARROT NUMBER 17 LODE | |
| Beginning at cor. No.1 of the Parrot Number 17 lode identical with cor. No.2 of the Parrot Number 18 lode, cor. No.3 of the Parrot Number 11 lode and cor. No.4 of the Parrot Number 10 lode, all of this survey; previously described. | |
| Thence S.45°05'30"E. | |
| 263.03 | Witness cor. for cor. No.2 identical with cor. No.3 of the Parrot Number 10 lode of this survey; previously described. |
| 300.0 | Lode line; discovery pt. bears S.44°49'55"W., 1276.44 ft. dist. |
| 396.51 | Intersect line 4-1, Sur. No. 4245A, Gold Standard No.18 lode, at a pt. from which cor. No.4, identical with cor. No.2 of the Greenlee No.8 lode, of the same survey, bears S.51°22'30"W., 521.38 ft. dist. |
| 600.0 | Point for Cor. No.2 identical with cor. No.3 of the Parrot Number 10 lode of this survey; previously described. Thence S.44°49'55"W. |
| 120.0 | Left bank of drainage, 15 ft. wide, course, N.85°E. |
| 546.90 | Intersect line 3-4, Sur. No.4245A, Gold Standard No.18 lode, common with line 2-3 of the Greenlee No.8 lode of the same survey, at a pt. from which cor. No.4 of the Gold Standard No.18 lode, identical with cor. No.2 of the Greenlee No.8 lode, bears N.38°50'W., 264.52 ft. dist. |
| 1401.44 | Cor. No.3 Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P17 3 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.45°05'30"W. |
| 213.05 | Intersect line 1-2, Sur. No.4245A, Greenlee No.8 lode, at a pt. from which cor. No.2, identical with cor. No.4 of the Gold Standard No.18 lode of the same survey, bears N.41°36'10"E. 884.85 ft. dist. |
| 300.0 | Lode line; discovery pt. bears N.44°49'55"E., 125 ft. dist. |
| 600.0 | Cor. No.4 identical with cor. No.3 of the Parrot Number 18 lode of this survey. |

| Chains | Feet | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 14 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P17 4 P18 3 X; from which |
|-----------------------|------|---|
| | | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | | Thence N.44°49'55"E. |
| 1401.44 | | Cor. No.1 and the place of beginning. |
| PARROT NUMBER 18 LODE | | |
| | | Beginning at cor. No.1 of the Parrot Number 18 lode identical with cor. No.2 of the Parrot Number 19 lode, cor. No.3 of the Parrot Number 12 lode and cor. No.4 ... of the Parrot Number 11 lode, all of this survey; previously described. |
| | | Thence S.44°32'15"E. |
| 300.0 | | Lode line; discovery pt. bears S.45°46'20"W., 90.0 ft. dist. |
| 577.0 | | Cor. No.2 identical with cor. No.1 of the Parrot Number 17 lode, cor. No.3 of the Parrot Number 11 lode and cor. No.4 of the Parrot Number 10 lode, all of this survey; previously described. |
| | | Thence S.44°49'55"W. |
| 1401.44 | | Cor. No.3 identical with cor. No.4 of the Parrot Number 17 lode of this survey; previously described. |
| | | Thence N.44°32'15"W. |
| 300.0 | | Lode line; discovery pt. bears N.45°46'20"E., 1311.38 ft. dist. |
| 600.0 | | Cor. No.4 identical with cor. No.3 of the Parrot Number 19 lode of this survey. |
| | | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P18 4 P19 3 X; from which |
| | | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | | Thence N.45°46'20"E. |
| 1401.38 | | Cor. No.1 and the place of beginning. |

SURVEY NO. 4608

(21)

Feet
Chains

PARROT NUMBER 19 LODE

At cor. No. 1 of the Parrot Number 19 lode.

Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd MS 4608 P19 1 X; from which

The cor. of secs. 25, 26, 35 & 36, T.3S., R.29E., G.&S.R.B.&M., bears N.72°11'40"W., 1153.64 ft. dist.; previously described.

A mound of stones constructed and painted yellow adjacent to the iron post.

Thence S.44°13'E.

- 73.47 Intersect line 2-3 of the Parrot No. 26 lode of this survey.
- 125.0 Left bank of drainage, 10 ft. wide, course N.20°E.
- 300.0 Lode line; discovery pt. bears S.45°34'20"W., 200 ft. dist.
- 373.80 True pt. for cor. No. 4 of the Parrot Number 12 lode of this survey.
- 437.71 Intersect line 2-3 of the Parrot Number 23 lode of this survey.
- 487.0 Witness cor. for cor. No. 4 of the Parrot Number 12 lode.
- 599.78 Cor. No. 2 identical with cor. No. 1 of the Parrot Number 18 lode, cor. No. 3 of the Parrot Number 12 lode and cor. No. 4 of the Parrot Number 11 lode, all of this survey; previously described.
- Thence S.45°46'20"W.
- 1401.38 Cor. No. 3 identical with cor. No. 4 of the Parrot Number 18 lode of this survey; previously described.
- Thence N.44°13'W.
- 196.62 Intersect line 2-3 of the Parrot No. 24 lode of this survey.
- 294.87 Lode line; discovery pt. bears N.45°34'20"E., 1201.38 ft. dist.
- 594.87 Cor. No. 4
- Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P19 4 X; from which
- A mound of stones constructed and painted yellow adjacent to the iron post.
- Thence N.45°34'20"E.
- 729.29 Intersect line 3-4 of the Parrot Number 23 lode, in part common with line 3-4 of the Parrot No. 26 lode identical with line 1-2 of the Parrot No. 24 lode, all of this survey.

| Feet | |
|---------|---|
| 1401.38 | Cor. No. 1 and the place of beginning. |
| | PARROT NO. 28 LODE |
| | At cor. No. 1 of the Parrot No. 28 lode identical with cor. No. 1 of the Parrot No. 26 lode and on line 2-3 of the Parrot No. 27 lode, both of this survey. |
| | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P28 1 P26 1 X; from which |
| | The cor. of secs. 25, 26, 35 & 36, T.3S., R.29E., G.&S.R.B.&M., bears S.84°31'30"W., 738.12 ft. dist.; previously described. |
| | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | Thence N.30°26'30"E. |
| 15.0 | Unimproved road bears S.50°E. and N.62°W. |
| 110.0 | Right bank of drainage, 10 ft. wide, course S.62°E. |
| 300.00 | Cor. No. 2 of the Parrot No. 27 lode of this survey. |
| 1259.84 | Cor. No. 2 |
| | Set a galvanized iron post 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P28 2 X; from which |
| | No.1 U. S. Mineral Monument/bears N.55°18'40"E., 832.75 ft. dist. |
| | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | Thence S.62°23'55"E |
| 300.0 | Lode line; discovery pt. bears S.30°26'30"W., 699.84 ft. dist. |
| 600.0 | Cor. No. 3 |
| | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P28 3 X; from which |
| | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | Thence S.30°26'30"W. |

| Chains | Feet | |
|---------|------|---|
| 1060.0 | | Left bank of drainage, 10 ft. wide, course; N.80°E. |
| 1147.46 | | Intersect line 4-1 of the Parrot Number 23 lode of this survey. |
| 1240.0 | | Unimproved road bears N.65°E. and S.65°W. |
| 1259.84 | | Cor. No.4 identical with cor. No. 2 of the Parrot No.26 lode of this survey. |
| | | Set a galvanized iron post, 3/4 in. diam., 24 ins. long, in a 25 pound concrete and rock base 14 ins. in the ground with a brass cap 2 1/2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P28 4 P26 2 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.62°23'55"W. |
| 10.0 | | Unimproved road bears N.65°E. and S.80°W. |
| 30.0 | | Right bank of drainage, 10 ft. wide, course N.30°E. |
| 59.28 | | Intersect line 4-1 of the Parrot Number 23 lode of this survey. |
| 59.28 | | Unimproved road bears N.50°W. and S.50°E. |
| 300.0 | | Lode line; discovery pt. bears N.30°26'30"E., 560 ft. dist. |
| 300.0 | | Unimproved road bears S.65°E. and N.65°W. |
| 580.0 | | Unimproved road bears N.20°W. and S.20°E. |
| 600.0 | | Cor. No.1 and the place of beginning. |
| | | PARROT NO. 26 LODE |
| | | Beginning at cor. No.1 of the Parrot No.26 lode identical with cor. No.1 of the Parrot No.28 lode and on line 2-3 of the Parrot No.27 lode, both of this survey; previously described. |
| | | Thence S.62°23'55"E. |
| 20.0 | | Unimproved road bears N.20°W. and S.20°E. |
| 300.0 | | Lode line and discovery pt. |
| 300.0 | | Unimproved road bears S.65°E. and N.65°W. |
| 540.72 | | Intersect line 4-1 of Parrot Number 23 lode of this survey. |
| 540.72 | | Unimproved road bears N.50°W. and S.50°E. |
| 560.0 | | Left bank of drainage, 10 ft. wide, course, N.30°E. |
| 590.0 | | Unimproved road bears N.65°E. and S.80°W. |

23

SURVEY NO. 4608

(24)

| Chains Feet | |
|----------------|---|
| 600.0 | Cor. No.2 identical with cor. No.4 of the Parrot No.28 lode of this survey; previously described. Thence S.30°33'30"W. |
| 100.0 | Right bank of drainage, 10 ft. wide, course, North. |
| 229.80 | Intersect line 1-2 of the Parrot Number 19 lode of this survey. |
| 846.99 | Cor. No.3 identical with cor. No.2 of the Parrot No.24 lode, identical with the witness cor. for cor. No.3 of the Parrot Number 23 lode and on line 3-4 of the Parrot Number 23 lode, both of this survey; previously described. Thence N.62°23'55"W. |
| 245.33 | Intersect line 4-1 of the Parrot Number 19 lode of this survey. |
| 298.27 | Lode line; discovery pt. bears N.30°26'30"E., 846.89 ft. dist. |
| 504.30 | Cor. No.4 of the Parrot Number 23 lode of this survey. |
| 598.27 | Cor. No.4 identical with cor. No.1 of the Parrot No.24 lode, cor. No.2 of the Parrot No.25 lode and cor. No.3 of the Parrot No.27 lode, all of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P26 4 P24 1 P25 2 P27 3 X; from which The cor. of secs. 25,26,35&36, T.3S., R.29 E., G.&S.R.B.&M., bears N.24°51'30"W., 727.10 ft. dist. A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.30°26'30"E. |
| 846.89 | Cor. No.1 and the place of beginning. |

PARROT NO. 27 LODE

At cor. No.1 of the Parrot No. 27 lode.

Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P27 1 X; from which

The cor. of secs. 25,26,35&36, T3S., R.29 E., G.&S.R.B.&M., bears S.30°16'40"W., 743.45 ft. dist.; previously described.

SURVEY 4608

(25)

| Chains | Feet | |
|---------|------|---|
| | | A mound of stones constructed and painted yellow adjacent to the iron post. Thence S.58°33'30"E. |
| 115.0 | | Unimproved road bears East and West. |
| 300.0 | | Lode line; discovery pt. bears S.30°26'30"W., 1146.89 ft. dist. |
| 600.0 | | Cor. No.2 on line 1-2 of the Parrot No. 28 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P27 2 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence S.30°26'30"W. |
| 180.0 | | Left bank of drainage, 10 ft. wide, course, S.62°E. |
| 285.0 | | Unimproved road bears S.50°E. and N.62°W. |
| 300.0 | | Cor. No.1 of the Parrot No.28 lode identical with cor. No. 1 of the Parrot No.26 lode, both of this survey. |
| 1146.89 | | Cor. No.3 identical with cor. No.4 of the Parrot No.26 lode, cor. No.1 of the Parrot No.24 lode and cor. No.2 of the Parrot No.25 lode, all of this survey; previously described. Thence N.58°33'30"W. |
| 300.0 | | Lode line and discovery pt. |
| 600.0 | | Cor. No.4 identical with cor. No.1 of the Parrot No.25 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P27 4 P25 1 X; from which The cor. of secs. 25,26 35&36, T.3S., R. 29E., G.&S.R.B.&M., bears N.30°44'35" E., 403.45 ft. dist.; previously described. A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.30°26'30"E. |
| 585.0 | | Unimproved road bears N.30°W. and S.30°E. |
| 1075.0 | | Unimproved road bears east and west. |
| 1146.89 | | Cor. No.1 and the place of beginning |

25

27

SURVEY NO. 4608

(26)

| Chains Feet | |
|----------------|---|
| | <p>PARROT NO. 24 LODGE</p> <p>Beginning at cor. No.1 of the Parrot No. 24 lode, identical with cor. No.2 of the Parrot No.25 lode, cor. No.3 of the Parrot No.27 lode and cor. No.4 of the Parrot No.26 lode, all of this survey; previously described.</p> <p>Thence S.62°23'55"E.</p> |
| 93.97 | Cor. No.4 of the Parrot Number 23 lode of this survey. |
| 300.0 | Lode line; discovery pt. bears S.34°05'30"W., 1125.46 ft. dist. |
| 352.94 | Intersect line 4-1 of the Parrot Number 19 lode of this survey. |
| 598.27 | Cor. No.2 identical with cor. No.3 of the Parrot No.26 lode, the witness cor. for cor. No.3 of the Parrot Number 23 lode and on line 3-4 of the Parrot Number 23 lode, all of this survey; previously described. |
| | Thence S.34°01'W. |
| 823.13 | Intersect line 3-4 of the Parrot Number 19 lode of this survey. |
| 1049.80 | Intersect line 2-3, Sur. No.4245A, Gold Standard No.7 lode at a pt. from which cor. No.2 bears N.53°52'40"W., 247.98 ft. dist. |
| 1325.28 | Cor. No.3 |
| | Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P24 3 X; from which |
| | Cor. No.2, Sur. No.4245A, Gold Standard No.7 lode, bears N.7°01'55"W., 377.36 ft. dist. |
| | Cor. No.4, Sur. No.4245A, Gold Standard No.8 lode, identical with cor. No.1 of the Gold Standard No.16 lode of the same survey, bears N.47°33'10"W., 145.90 ft. dist. |
| | A mound of stones constructed and painted yellow adjacent to the iron post. |
| | Thence N.62°23'55"W. |
| 55.34 | Intersect line 4-1, Sur. No.4245A, Gold Standard No.8 lode, at a pt. from which cor. No.4 identical with cor. No.1 of the Gold Standard No.16 lode of the same survey, bears N.38°50'W., 93.49 ft. dist. |
| 151.45 | Intersect line 3-4, Sur. No.4245A, Gold Standard No.8 lode, common with line 1-2 of the Gold Standard No.16 lode of the same survey at a pt. from which cor. No.4 of the Gold Standard No.8 lode, identical with cor. No.1 of the Gold Standard No.16 lode, bears N.43°10'E., 38.80 ft. dist. |

| CHAINS Feet | |
|--------------------|--|
| 300.0 | Lode line; discovery pt. bears N.34°05'30"E., 200 ft. dist. |
| 309.08 | Intersect line 1-2, Sur. No.4245A, Gold Standard No.7 lode, at a pt. from which cor. No.2 bears N.44°33'E., 324.59 ft. dist. |
| 600.0 | Cor. No.4 identical with cor. No.3 of the Parrot No.25 lode of this survey. Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post mkd. MS 4608 P24 4 P25 3 X; from which Cor. No.4, Sur. No.4245A, Gold Standard No.16 lode, bears N.9°25'55"E., 291.80 ft. dist. Cor. No.4, Sur. No.4482, Expectation No.15 lode, bears, N.7°52'10"E., 278.46 ft. dist. A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.34°05'30"E. |
| 227.80 | Intersect line 4-1, Sur. No.4245A, Gold Standard No.16 lode, at a pt. from which cor. No.1, identical with cor. No.4 of the Gold Standard No.8 lode of the same survey, bears S.38°50'E. 472.64 ft. dist. |
| 380.0 | Left bank of drainage, 20 ft. wide, course, N.62°W. |
| 1325.46 | Cor. No.1 and the place of beginning. |
| PARROT NO. 25 LODE | |
| | Beginning at cor. No.1 of the Parrot No.25 lode, identical with cor. No.4 of the Parrot No.27 lode of this survey; previously described. Thence S.58°33'30"E. |
| 300.0 | Lode line; discovery pt. bears S.34°05'30"W., 200 ft. dist. |
| 600.0 | Cor. No.2 identical with cor. No.1 of the Parrot No.24 lode, cor. No.3 of the Parrot No.27 lode, and cor. No.4 of the Parrot No.26 lode, all of this survey; previously described. Thence S.34°05'30"W. |
| 925.46 | Right bank of drainage, 20 ft. wide, course, N.62°W. |
| 1097.66 | Intersect line 4-1, Sur. No.4245A, Gold Standard No.16 lode, at a pt. from which cor. No.4 bears N.38°50'W., 127.36 ft. dist. |

| Chains Feet | |
|----------------|---|
| 1325.46 | Cor. No.3 identical with cor. No.4 of the Parrot No.24 lode of this survey; previously described. Thence N.58°33'30"W. |
| 162.01 | Intersect line 4-1, Sur. No. 4482, Expectation No.15 lode, at a pt. from which cor. No.4 bears N.42°40'E.; 260.20 ft. dist. |
| 164.03 | Intersect line 3-4, Sur. No.4245A, Gold Standard No.16 lode, at a pt. from which cor. No.4 bears N.42°52'E., 276.00 ft. dist. |
| 300.0 | Lode line; discovery pt. bears N.34°05'30"E., 1125.46 ft. dist. |
| 600.0 | Cor. No.4 Set a galvanized iron post, 3/4 in. diam., 14 ins. long, in a 15 pound concrete and rock base, 10 ins. in the ground, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. MS 4608 P25 4 X; from which A mound of stones constructed and painted yellow adjacent to the iron post. Thence N.34°05'30"E. |
| 220.0 | Left bank of drainage, 20 ft. wide, course, N.80°W. |
| 276.08 | Intersect line 3-4, Sur. No.4482, Expectation No. 15 lode, at a pt. from which cor. No.4 bears S.56°05'E., 476.32 ft. dist. |
| 1325.46 | Cor. No.1 and the place of beginning. |

SURVEY NO. 4608

| AREAS | Acres |
|--|----------|
| Total area Parrot No.1 lode | 20.453 ✓ |
| Area in conflict with | |
| Parrot No.13 lode of this survey | 3.740 ✓ |
| Parrot No.15 lode of this survey | 0.289 ✓ |
| Total area Parrot No.2 lode | 20.221 ✓ |
| Total area Parrot No.3 lode | 16.822 ✓ |
| Area in conflict with | |
| Parrot No.2 lode of this survey | 0.031 ✓ |
| Sur. No.4224A, Belfast lode | 0.171 ✓ |
| Sur. No.4224A, Governor No.2 lode | 0.294 ✓ |
| Parrot No.5 lode of this survey | 0.001 ✓ |
| Parrot No.5 lode of this survey exclusive of its conflict with Sur. No.4224A, Governor No.2 lode | 0.001 ✓ |
| Total area Parrot No.4 lode | 20.535 ✓ |
| Area in conflict with | |
| Parrot Number 15 lode of this survey | 0.604 ✓ |

SURVEY NO. 4608

(29)

| Chains Feet | | Acres |
|----------------|---|--------|
| | Parrot Number 15 lode exclusive of its conflict with Parrot Number 10 lode, both of this survey. | 0.601 |
| | Sur. No. 4245A, Gold Standard No. 14 lode | 0.547 |
| | Sur. No. 4245A, Gold Standard No. 18 lode | 0.242 |
| | Parrot Number 10 lode of this survey. | 0.696 |
| | Parrot Number 10 lode of this survey exclusive of its conflict with Sur. No. 4245A, Gold Standard No. 18 lode | 0.696 |
| | Total area Parrot No. 5 lode | 20.362 |
| | Area in conflict with | |
| | Sur. No. 4224A, Governor lode | 1.930 |
| | Sur. No. 4224A, Governor No. 2 lode | 2.144 |
| | Sur. No. 4245A, Gold Standard No. 14 lode | 4.051 |
| | Total area Parrot No. 13 lode | 19.858 |
| | Total area Parrot Number 15 lode | 19.553 |
| | Area in conflict with | |
| | Parrot Number 10 lode of this survey | 0.526 |
| | Parrot Number 11 lode of this survey | 0.140 |
| | Total area Parrot Number 16 lode | 19.536 |
| | Area in conflict with | |
| | Sur. No. 947, Merrimac lode | 0.004 |
| | Parrot Number 11 lode of this survey | 0.786 |
| | Parrot Number 12 lode of this survey | 0.325 |
| | Total area Parrot Number 10 lode | 9.184 |
| | Area in conflict with | |
| | Sur. No. 4245A, Gold Standard No. 18 lode | 1.636 |
| | Total area Parrot Number 11 lode | 8.747 |
| | Total area Parrot Number 12 lode | 3.543 |
| | Total area Parrot Number 17 lode | 19.303 |
| | Area in conflict with | |
| | Sur. No. 4245A, Gold Standard No. 18 lode | 2.860 |
| | Sur. No. 4245A, Greenlee No. 8 lode | 4.739 |
| | Total area Parrot Number 18 lode | 18.933 |
| | Total area Parrot Number 19 lode | 19.217 |
| | Total area Parrot Number 22 lode | 15.520 |
| | Area in conflict with | |
| | Sur. No. 947, Merrimac lode | 9.780 |
| | Parrot Number 12 lode of this survey | 0.202 |
| | Total area Parrot Number 23 lode | 13.862 |
| | Area in conflict with | |
| | Parrot Number 12 lode of this survey | 0.921 |
| | Parrot Number 19 lode of this survey | 5.345 |
| | Parrot Number 28 lode of this survey | 0.076 |
| | Total area Parrot No. 26 lode | 11.634 |
| | Area in conflict with | |
| | Parrot Number 19 lode of this survey | 2.303 |
| | Parrot No. 23 lode of this survey | 5.472 |
| | Parrot No. 23 lode exclusive of its conflict with Parrot Number 19 lode, both of this survey. | 3.169 |
| | Total area Parrot No. 27 lode | 15.795 |

| Chains Feet | a | Acres |
|----------------|---|--------|
| | Total are/Parrot No. 28 lode | 17.332 |
| | Total area Parrot No. 24 lode | 18.114 |
| | Area in conflict with | |
| | Parrot Number 19 lode of this survey | 5.637 |
| | Sur. No. 4245A, Gold Standard No. 16 lode | 1.374 |
| | Sur. No. 4245A, Gold Standard No. 8 lode | 0.041 |
| | Sur. No. 4245A, Gold Standard No. 7 lode | 1.885 |
| | Sur. No. 4245A, Gold Standard No. 7 lode exclusive of its conflict with Gold Standard No. 8 lode | 1.844 |
| | Sur. No. 4245A, Gold Standard No. 7 lode exclusive of its conflict with the Gold Standard No. 16 lode of the same survey. | 0.243 |
| | Survey No. 4245A, Gold Standard No. 7 lode exclusive of its conflict with the Gold Standard No. 8 lode and Gold Standard No. 16 lode, both of the same survey. | 1.601 |
| | Total area Parrot No. 25 lode | 18.238 |
| | Area in conflict with | |
| | Sur. No. 4245A, Gold Standard No. 16 lode | 0.828 |
| | Sur, No. 4482, Expectation No. 15 lode | 2.793 |
| | Sur. No. 4482, Expectation No. 15 lode ex- clusive of its conflict with Sur. No. 4245A, Gold Standard No. 16 lode | 2.784 |

LOCATION

This survey is located in the SE. 1/4 & SW. 1/4 of sec. 25, SE. 1/4 of sec. 26, NE. 1/4 of sec. 35, NW. 1/4 & NE. 1/4 of sec 36, T.3S., R.29E. and the SW. 1/4 of sec. 30 and NW. 1/4 of sec. 31, T.3S., R.30E., G.&S.R.B.&M.

The survey of the Parrot Nos. 1 through 5, Numbers 10 through 12, No. 13, Numbers 15 through 19, Numbers 22 & 23 and Nos. 24 through 28 lodes is identical with the respective location or amended location as marked on the ground.

| -Chains | Feet | EXPENDITURES |
|---------|------|--|
| | | The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or their grantors are as follows: |
| No.1 | | The discovery pt. of the Parrot No.3 lode is on the lode line 720 ft. from a pt. on line 1-2, 245.0 ft. from cor. No.1. Value, None. |
| No.2 | | A cut, the SE. cor. of which bears S.26°W., 605 ft. dist. from cor. No.1 of the Parrot No.3 lode; 5 ft. wide, running N.60°W.; 7ft. to a 12 ft. face. Value, \$125.00 |
| No.3 | | A cut, the NE. cor. of which bears S.39°W., 915 ft. from cor. No.1 of the Parrot No.3 lode; 3 ft. wide, running west, 12 ft. to a 7 ft. face. Value, \$125.00 |
| No.1 | | The discovery cut of the Parrot No.2 lode is on the lode line 58 ft. from a pt. on line 1-2, 300 ft. from cor. No.1; 5 ft. wide running north, 10 ft. to a 10 ft. face. Value, \$150.00 |
| No.2 | | A pit, the NE. cor. of which bears S.42°E., 295 ft. from cor. No.4 of the Parrot No.2 lode; 6x6 ft. in size, 6 ft. deep. Value, \$150.00 |
| No.3 | | A cut, the NW. cor. of which bears S.40°E., 220 ft. from cor. No.4 of the Parrot No.2 lode; 5 ft. wide, running N.45°E., 10 ft. to a 4 ft. face. Value, \$80.00 |
| No.1 | | The discovery cut of the Parrot No.1 lode is on the lode line 175 ft. from a pt. on line 4-1, 300 ft. from cor. No.4; 4x6 ft. in size, 8 ft deep. Value, \$150.00 |
| No.2 | | A pit, the NE. cor. of which bears S.35°E., 365 ft. from cor. No.4 of the Parrot No.1 lode; 6x7 ft. in size, 5 ft. deep. Value, \$125.00 |
| No.3 | | An adit, the portal of which bears S.72°W., 740 ft. dist. from cor. No.1 of the Parrot No.1 lode; 4x5 ft. in size, running S.50°W, 50+ft. Value, \$1,000.00 |
| No.4 | | An adit, the portal of which bears S.72°W., 800 ft. dist. from cor. No.1 of the Parrot No.1 lode; 4x5 ft. in size, running S.40°W., 30 ft. at which pt. it intersects improvement No.5, a vertical shaft. Value, \$600.00 |

33

SURVEY NO. 4608

(32)

Chains
Feet

- | | |
|------|--|
| No.5 | A vertical shaft, untimbered, the NE. cor. of which bears S.71°30'W., 825 ft. dist. from cor. No.1 of the Parrot No.1 lode; 5x6 ft. in size, 75+ft. deep. Value, \$4,000.00 |
| No.1 | The discovery cut of the Parrot No.4 lode is on the lode line 165 ft. from a pt. on line 1-2, 300 ft. from cor. No.1; 5 ft. wide, running N.30°W., 10 ft. to a 10 ft. face. Value, \$150.00 |
| No.1 | The discovery pt. of the Parrot No.5 lode is on the lode line, 25 ft. from a pt. on line 1-2, 300 ft. from cor. No.1. Value, None |
| No.2 | A pit, the NE. cor. of which bears S. 28° E., 295 ft. dist., from cor. No. 1 of the Parrot No. 5 lode; 4 x 6 ft. in size, 8 ft. deep. Value, \$225.00 |
| No.1 | The discovery pt. of the Parrot Number 10 lode is on the NE. end of the lode line, 274.30 ft. from cor. No.1. Value, None |
| No.2 | A cut, the SE. cor. of which bears S.45°E., 90.0ft. from cor. No.1 of the Parrot Number 10 lode; 4 ft. wide, running N.30°W., 8 ft. to a 10 ft. face. Value, \$100.00 |
| No.3 | A cut, the SE. cor. of which bears S.64°E., 1150ft. dist. from cor. No.4 of the Parrot Number 10 lode; 4 ft. wide, running N.60°W., 12 ft. to a 7 ft. face. Value, \$125.00 |
| No.1 | The discovery pt. of the Parrot Number 11 lode is on the SW. end of the lode line, 277 ft. from cor. No.3. Value, None |
| No.2 | A cut, the NE. cor. of which bears S.12°W., 350 ft. dist. from cor. No.1 of the Parrot Number 11 lode; 5 ft. wide, running S.45°E., 13 ft. to a 3 ft. face. Value, \$80.00 |
| No.3 | A cut, the NE. cor. of which bears S.6°30'W., 315 ft. dist. from cor. No.1 of the Parrot Number 11 lode; 4 ft. wide, running S.65°E., 6 ft. to a 5 ft. face. Value, \$80.00 |

SURVEY NO. 4608

34
(33)

Chains

Feet

- | | |
|------|---|
| No.1 | The discovery cut of the Parrot Number 12 lode is on the lode line, 100 ft. from a pt. on line 3-4, 112.78 ft. from cor. No.3; 4 ft. wide, running S.55°W., 10 ft. to an 8 ft. face. Value, \$125.00 |
| No.1 | The discovery cut of the Parrot No.13 lode is on the lode line, 100 ft. from a pt. on line 3-4, 300 ft. from cor. No.3; 5 ft. wide, running N.60°W., 7 ft. to an 8 ft. face. Value, \$115.00 |
| No.1 | The discovery pt. of the Parrot Number 15 lode is on the lode line, 380 ft. from a pt. on line 3-4, 299.43 ft. from cor. No.3. Value, None |
| No.2 | A cut, the NW. cor. of which bears N.80°E., 450 ft. from cor. No.4 of the Parrot Number 15 lode; 4 ft. wide, running N.56°E., 8 ft. to an 8 ft. face. Value, \$125.00 |
| No.1 | The discovery cut of the Parrot Number 16 lode is on the lode line, 200 ft. from a pt. on line 1-2, 300 ft. from cor. No.1; 5x7 ft. in size, 5 ft. deep. Value, \$125.00 |
| No.1 | The discovery pt. of the Parrot Number 17 lode is on the lode line, 125 ft. from a pt. on line 3-4, 300 ft. from cor. No.3. Value, None. |
| No.2 | A cut, the SE. cor. of which bears N.29°W., 290 ft. dist. from cor. No.3 of the Parrot Number 17 lode; 5 ft. wide running N.20°E., 8 ft. to a 12 ft. face. Value \$175.00 |
| No.1 | The discovery pt. of the Parrot Number 18 lode is on the lode line 90 ft. from a pt. on line 1-2, 300 ft. from cor. No.1. Value, None |
| No.2 | A cut, the NE. cor. of which bears S.27°30'E., 290 ft. dist. from cor. No.1 of the Parrot Number 18 lode; 6 ft. wide, running S.25°E., 10 ft. to a 10 ft. face. Value, \$175.00 |
| No.3 | A cut, the NE. cor. of which bears S.42°E., 275 ft. dist. from cor. No.1 of the Parrot Number 18 lode; 5 ft. wide, running S.8°W., 12 ft. to a 10 ft. face. Value, \$175.00 |

| Chains Feet | |
|----------------|---|
| No.4 | A pit, the NE. cor. of which bears S.38°30'E., 465 ft. dist. from cor. No.1 of the Parrot Number 18 lode; 5x7 ft. in size, 2 ft. deep. Value, \$50.00 |
| No.1 | The discovery pt. of the Parrot Number 19 lode is on the lode line 200 ft. from a pt. on line 1-2, 300 ft. from cor. No.1. Value, None |
| No.2 | A cut, the NE. cor. of which bears S.2°W., 170 ft. dist. from cor. No.1 of the Parrot Number 19 lode; 4 ft. wide running west, 10 ft. to a 9 ft. face. Value, \$150.00 |
| No.1 | The discovery pt. of the Parrot Number 22 lode is on the lode line, 125 ft. from a pt. on line 3-4, 300 ft. from cor. No.3. Value, None |
| No.2 | A cut, the NE. cor. of which bears S.69°30'E., 405 ft. dist. from cor. No.4 of the Parrot Number 22 lode; 4 ft. wide, running S.25°W., 7 ft. to a 10 ft. face. Value, \$125.00 |
| No.3 | A cut, the NE. cor. of which bears S.61°E., 325 ft. from cor. No.1 of the Parrot Number 22 lode; 8 ft. wide, running west, 10 ft. to a 12 ft. face. Value, \$175.00 |
| No.1 | The discovery pt. of the Parrot Number 23 lode is on the lode line, 450 ft. from a pt. on line 1-2, 283.20 ft. from cor. No.1 Value, None |
| No.2 | A cut, the NE. cor. of which bears S.48°W., 620 ft. dist. from cor. No.1 of the Parrot Number 23 lode; 6 ft. wide, running west, 8 ft. to a 9 ft. face. Value, \$150.00 |
| No.1 | The discovery pt. of the Parrot No.24 lode is on the lode line 200 ft. from a pt. on line 3-4, 300 ft. from cor. No.3. Value, None |
| No.2 | A cut, the NW. cor. of which bears N. 89° 30' E., 365 ft. dist. from cor. No.4 of the Parrot No. 24 lode; 4 ft. wide, running S. 30° E., 8 ft. to a 10 ft. face. Value, \$200.00 |
| No.1 | The discovery pt. of the Parrot No.25 lode is on the lode line, 200 ft. from a pt. on line 1-2, 300 ft. from cor. No.1. Value, None |

SURVEY NO. 4608

(35)

Claims

Feet

| | |
|------|---|
| No.2 | A cut, the SE. cor. of which bears N.72°W, 120 ft. dist. from cor. No.2 of the Parrot No.25 lode; 5 ft. wide running N.60°W., 12 ft. to a 10 ft. face. Value, \$175.00 |
| No.3 | A pit, the NE. cor. of which bears S.75°30'W., 275 ft. dist. from cor. No.2 of the Parrot No.25 lode; 4x7 ft. in size, 4 ft. average depth. Value, \$100.00 |
| No.4 | A cut, the NE. cor. Of which bears S.62°W., 420 ft. dist. from cor. No.2 of the Parrot No. 25 lode; 6 ft. wide, running west, 18 ft. to an 8 ft. face. Value, \$200.00 |
| No.5 | A cut, the NE. cor. of which bears S.48°W., 880 ft. dist. from cor. No.2 of the Parrot No. 25 lode; 4 ft. wide, running S.60°E., 10 ft. to a 3 ft. face. Value, \$100.00 |
| No.1 | The discovery pt. of the Parrot No.26 lode is on the NE end line, 300 ft. from cor. No.1. Value, None |
| No.2 | A cut, the NE. cor. of which bears S.29°W., 170 ft. from cor. No.1 of the Parrot No.26 lode; 4 ft. wide, running N.80°W., 8 ft. to a 6 ft. face. Value, \$100.00 |
| No.1 | The discovery pt. of the Parrot No.27 lode is on the SW. end of the lode line, 300 ft. from cor. No.3. Value, None. |
| No.2 | A cut, the SW. cor. of which bears S. 62°E., 320 ft. from cor. No.4 of the Parrot No.27 lode; 5 ft. wide, running S.20°E., 20 ft. to a 10 ft. face. Value, \$200.00 |
| No.3 | An adit, the portal of which bears N.84°30'E., 340 ft. dist. from cor. No.4 of the Parrot No.27 lode; 6 ft. high, 5 ft. wide at the portal, running S.18°E., 15 ft. to a 12 ft. width. Value, \$350.00 |
| No.4 | A cut, the NE. cor. of which bears S.73°W., 230 ft. from cor. No.2 of the Parrot No.27 lode; 5 ft. wide, running N.60°W., 10 ft. to a 5 ft. face. Value, \$150.00 |
| No.1 | The discovery pt. of the Parrot No.28 lode is on the lode line 560 ft. from a pt. on line 4-1, 300 ft. from cor. No.4. Value, None |

Chains

Feet

No.2 A cut, the SW. cor. of which bears N.63°30'E., 350 ft. dist. from cor. No.1 of the Parrot No.28 lode; 4 ft. wide, running North, 8 ft. to an 8 ft. face.

Value, \$150.00

An interest in a common improvement described as follows:

An adit, the portal of which bears S.24°30'W., 505 ft. dist. from cor. No.1 of the Parrot No.2 lode; 4x6 ft. in size, running S.35°W., 50+ft.

Value, \$1,500.00

Value of one-third interest, \$500.00

This improvement may be used to assist in the eventual development of the Parrot Nos. 1,2&3 lodes of this survey, which are all contiguous lode claims owned in common within the range of benefit of said adit.

The surface rises rapidly to the southwest from the portal of the adit and the extension in its present course, with necessary laterals and cross-cuts affords the most practical and economical means of developing each of the stated lodes at depth.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each of the stated lodes subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-third interest in its value is hereby credited to the Parrot Nos. 1,2&3 lodes.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode claim.

An interest in a common improvement described as follows:

An adit, the portal of which bears S.84°30'W., 515 ft. dist. from cor. No.1 of the Parrot No.1 lode; 5x6 ft. in size, running N.35°E., 25 ft. to a winze, 6x7 ft. in size, 50+ft. deep.

Value of adit and winze, \$3,500.00

Value of one-fourth interest, \$875.00

This improvement may be used to assist in the eventual development of the parrot Nos. 1&13 of this survey and Parrot Nos. 6&8, unsurveyed, which are all contiguous lodes owned in common within the range of benefit of said adit and winze.

The surface rises rapidly to the northeast from the portal of the adit and the extension in its present course, with necessary laterals and cross-cuts affords the most practical and economical means of developing each of the stated lodes at depth.

Chains
Feet

Five hundred dollars or over has been expended in such a manner as tends to the development of each of the stated lodes subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore an undivided one-fourth interest in its value is hereby credited to the Parrot Nos. 1, 6, 8 & 13 lodes.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode claim.

An interest in a common improvement described as follows;

An adit, the portal of which bears S. 57° 30' W., 590 ft. dist. from cor. No. 1 of the Parrot No. 1 lode; 4x6 ft. in size running approximately N. 75° W., 500 ft.

Value of Adit, \$10,000.00

Value of one-sixth interest, \$1,666.66

This improvement may be used to assist in the eventual development of the Parrot Nos. 1, 4 & 13 and Parrot Numbers 15 and 16 lodes of this survey and Parrot No. 14, unsurveyed, which are all contiguous lodes owned in common within the range of benefit of said adit.

The surface rises rapidly to the southwest from the portal of the adit and the extension in its present course with necessary laterals and cross-cuts affords the most practical and economical means of developing each of the stated lodes at depth.

Five hundred dollars or over has been expended in such a manner as tends to the development of each of the stated lodes subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore an undivided one-sixth interest in its value is hereby credited to the Parrot Nos. 1, 4, 13 & 14 lodes and the Parrot Numbers 15 & 16 lodes.

No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode location.

An interest in a common improvement described as follows:

An unimproved dirt road traversing nearly all claims of this survey and providing vehicular access to an extremely rugged terrain.

Value of roads constructed, \$16,000.00

Value apportioned to each claim of this survey, \$500.00 each.

OTHER IMPROVEMENTS.

A frame cabin, the SE. cor. of which bears S. 89° 30' W., 675 ft. dist. from cor. No. 1 of the Parrot No. 1 lode; 13x34 ft. in size; the long sides bear N. 45° W.

Claimant herein.

Chains
Feet

OTHER CORNER DESCRIPTIONS
AND SUPPLEMENTAL DATA

Sur. No. 4224A Belfast lode: Cor. No.4 is a granite stone 10x12 ins. in size, 18 ins above ground mkd. B4 4224A. No "X". Line 4-1 is shown as approved. Line 3-4 is shown as approved from Cor. No.3 to cor. No.1 of the Governor No.2 lode of the same survey. From cor. No.1 of the Governor No.2 lode to cor. No.4 of the Belfast lode was found to be N.51°12'20"E., 386.69 ft. instead of N. 51°05'E., 360.0 ft. as approved.

Sur. No. 4224A Governor No.2 lode: Cor. No.1 is a stone 6x8 ins. in size, 8 ins. above ground and a mound of stones. All markings undiscernible except "X" mark on top. Cor. No.3 identical with cor. No.4 of the Governor lode of the same survey is a dacite rock, 5x8 ins. in size, 10 ins. above ground, mkd. G2 2 4224A and a mound of stones. No marking for G4. Cor. No.4 was not found. Line 4-1 is shown as approved. Line 2-3, common with line 4-1 of the Governor lode of the same survey is shown as approved. Line 3-4 was found to be N.51°21'50"E., 799.02 instead of N.51°05'E., 819.2 ft. as approved.

Sur. No. 4224A Governor lode: Cor. No.4 identical with cor. No.3 of the Governor No.2 lode of the same survey described above. Line 4-1 common with line 2-3 of the Governor No.2 lode of the same survey described above. Line 3-4, in part common with line 2-3, Sur. No. 4245A, Gold Standard No.14 lode, is shown as approved from cor. No.3 to cor. No.2 of the Gold Standard No.14 lode. From cor. No.2 of the Gold Standard No.14 to cor. No.4 was found to be N.60°45'50"E., 270.07 ft. instead of N.51°05'E., 237.7 ft. as approved.

Sur. No.4245A Gold Standard No.14 lode: Cor. No.1 was not found. However a mound of stones and a bearing rock, 48x77 ins. in size, 34 ins. above ground was found mkd. BR4. Cor. No.2 is a gabbro ledge, 23x48 ins. in size, 63 ins. above ground mkd. with an "X". No other markings discernible. Line 1-2 was found to be S.40°12'35"E., 495.50 ft. instead of S.38°50'E., 600 ft. as approved. Line 2-3, common with line 3-4, Sur. No. 4224A, Governor lode, is shown as approved. Line 4-1, in part common with line 2-3, Sur. No. 4245A, Gold Standard No.18 lode, is shown as approved from cor. No.4 to cor. No.2 of the Gold Standard No.18 lode. From Cor. No.2 of the Gold Standard 18 lode to cor. No.1 of the Gold Standard No.14 lode was found to be N.64°26'20"E., 305.65 ft. instead of N.51°05'E., 360.10 ft. as approved.

Sur. No.4245A Gold Standard No. 18 lode: Cor. No.1 was not found. However a mound of stones and a bearing rock, 41x54 ins. in size, 38 ins. above ground, mkd. BR X was found. Cor. No.2 is a 20x30 in. ledge on a rock outcrop mkd. "X" and a mound of stones. No other marks discernible. Cor. No.4 identical with cor. No.2 of the Greenlee No.8 lode of the same survey was not found. However, a bearing rock was found, 25x70 ins. in size, 38 ins. above ground, mkd. BR X and a mound of stones. Line 1-2 was found to be S.42°39'10"E., 604.38 ft. instead of S.38°50'E., 600 ft. as approved. Line 2-3, common with line 4-1 of the Gold Standard No.14 lode of the same survey is shown as approved. Line 3-4, common with line 2-3 of the Greenlee No.8 lode of the same survey, is shown as approved. Line 4-1 was found to be N.51°22'30"E., 883.11 ft. instead of N.51°05'E., 912.20 ft. as approved.

~~Chains~~

Feet

Sur. No.4245A Greenlee No.8 lode: Cor. No.2, identical with cor. No.4 of the Gold Standard No.18 lode of the same survey described above. Line 2-3, common with line 3-4 of the Gold Standard No.18 lode, is shown as approved. Line 1-2, in part common with line 3-4 of the Gold Standard No.7 lode of the same survey, from cor. No.3 of the Gold Standard No.7 lode to cor. No.2 was found to be N.41°36'10"E., 915.56 ft. instead of N.44°33'E., 903.50 ft. as approved.

Sur. No.4245A Gold Standard No.7 lode: Cor. No.2 is a stone, 8x12 ins. in size, 14 ins. above ground, mkd. GS 7 X. No other markings discernible. Cor. No.3 is a rock 6x14 ft. in size 4 ft. above ground, mkd. GS 7 3 X. No other markings discernible. Line 1-2 is shown as approved. Line 2-3 was found to be S.53°52'40"E., 1423.99 ft. instead of S.55°06'E., 1334.0 ft. as approved.

Sur. No.4245A Gold Standard No.16 lode: Cor. No.4 was not found. However its position was established in relation to cor. No.4, Sur. No.4482, Expectation No.15 lode. Cor. No.1, identical with cor. No.4 of the Gold Standard No.8 lode of the same survey was not found. Line 3-4 is shown as approved for Sur. No.4482. Line 4-1 is shown as approved. Line 1-2, common with line 3-4 of the Gold Standard No.8 lode, is shown as approved.

Sur. No.4245A Gold Standard No.8 lode: Cor. No.4, identical with cor. No.1 of the Gold Standard No.16 lode of the same survey described above. Line 3-4, common with line 1-2 of the Gold Standard No.16 lode, is shown as approved. Line 4-1 is shown as approved.

Survey No.4482 Expectation No.15 lode: Cor. No.4 is a copper coated pin, firmly set flush with the ground level, properly mkd. as described in the official record. Lines 3-4 and 4-1 are shown as approved.

Survey No. 947 Merrimac lode: No evidence of the corners of this survey were found. All lines shown as approved.

U.S. Mineral Monument No.1 is a wood post, 4x4 ins. in size, 3 ft. above ground set in a large mound of stones. No visible marking.

FIELD ASSISTANTS

| Name | Capacity |
|-------------------|-----------------|
| Richard Cleveland | Chainman-Axeman |

Chains

1897

Mr. No. 2575 Greenlee No. 3 lode, Cor. No. 1
 with cor. No. 4 of the Gold Standard No. 13 lode of the
 same survey described above. Line 1-3, common to the
 2-A of the Gold Standard No. 13 lode, is shown as approved
 line 1-3, in part common with line 1-4 of the Gold
 Standard No. 7 lode of the same survey. The cor.
 the Gold Standard No. 7 lode to cor. No. 2 was found to be
 21.00 ft. instead of 21.25 ft. as approved.
 The No. 2575 Gold Standard No. 7 lode, Cor. No. 1
 a stone, 21 ft. in size, 14 in. above ground, and
 No. 7, the other markings described. The cor.
 was found 17 ft. in size, 1 ft. above ground, and
 other markings described. Line 1-1 is shown as
 approved. Line 1-2 was found to be 21.25 ft. instead of
 21.00 ft. instead of 21.25 ft. as approved.
 Mr. No. 2575 Gold Standard No. 13 lode, Cor.
 was found. However the position was established
 relation to cor. No. 4. Mr. No. 2575, Greenlee No. 13
 lode, Cor. No. 1, identical with cor. No. 1 of the Gold
 Standard No. 3 lode of the same survey was not
 found. Line 1-1 is shown as approved for cor. No. 13.
 Line 1-2 is shown as approved. Line 1-3, common with line
 the Gold Standard No. 3 lode, is shown as approved.
 Mr. No. 2575 Gold Standard No. 13 lode, Cor.
 identical with cor. No. 1 of the Gold Standard No. 13 lode
 of the same survey described above. Line 1-1, common
 with line 1-2 of the Gold Standard No. 13 lode, is shown
 as approved. Line 1-1 is shown as approved.
 Survey No. 2575, Greenlee No. 13 lode, Cor. No. 1
 a corner, located on a firm surface with the ground
 level, properly marked, as described in the official record
 lines 1-1 and 1-2, one shown as approved.
 Survey No. 2575, Greenlee lode; no evidence of the
 corners of this survey were found. All lines shown
 as approved.
 Mr. No. 2575 Mineral Monument No. 1 is a wood post, 4 ft.
 in size, 3 ft. above ground set in a large mound
 of stones. No visible marking.

FIELD ASSISTANTS

Richard Cleveland
 Captain-Alexander

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

41

CERTIFICATE OF SURVEYOR

Aug. 22, 19 63

I, Harvey W. Smith

Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the _____
State Director _____, at Phoenix, Arizona

dated Mar. 25, 1963 & Aug. 20, 1963, I have faithfully and correctly executed the survey of
the mining claim of Banner Mining Company
known as the (see reverse side)

(Lode, placer, or mill site)

situate in Greenlee Mining District, Greenlee County, Secs. 25, 26, 30, 31, 35 & 36,
T. 3S., R.s. 29 & 30E., G & SR Meridian, Arizona, and
(State)

designated as Survey No. 4608, which is represented in the foregoing field notes as having been
executed by me and under my direction, and that said survey has been made in strict conformity with said order,
the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner
described in the foregoing field notes, and I do further certify that the labor expended and improvements made

upon or for the benefit of the Lode location(s) embraced in the said mining claim by
(Lode or placer)

claimant(s) or their grantors are fully stated in my report therein, and that the character,
extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no
portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate
of expenditures upon any other claim.

Scottsdale, Arizona
(Place)

Harvey W. Smith
Harvey W. Smith
(Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management, State Office
(Office)
Phoenix, Arizona November 12, 1963
(Place) (Date)

The foregoing field notes of mineral survey No. 4608, in Greenlee Mining District,
Secs. 25, 26, 35 & 36 3 S. 29 E.
Secs. 30 & 31 T. 3 S. R. 30 E. G. & S. R. Meridian,

Arizona, executed by Harvey W. Smith, Mineral Surveyor,
(State) March 25, 1963 and
under order dated Amended August 20, 1963, having been critically examined and the necessary
corrections made prior to their certification by the surveyor, the field notes and the survey therein described
are hereby approved.

Fred J. Weiler
Fred J. Weiler
State Director
(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No. _____
is a true copy of the original field notes.

(Title)

42

Lodes

Parrot Nos. 1 & 2

Parrot Nos. 3 & 4

Parrot No. 5

Parrot Numbers 10 thru 12

Parrot No. 13

Parrot Numbers 15 thru 19

Parrot Numbers 22 & 23

Parrot Nos. 24 thru 28

CERTIFICATE OF APPROVAL

CERTIFICATE OF TRANSCRIPT

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (942)
BUREAU OF LAND MANAGEMENT M.S. 4608
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The PARROT NO. 3, PARROT NO. 13, PARROT NUMBER 22, PARROT NO. 24, PARROT NO. 25, PARROT NO. 26, PARROT NO. 27, and PARROT NO. 28 lodes, Mineral Survey No. 4608, located in Township 3 South, Range 29 East, Gila and Salt River Meridian, Arizona, are hereby canceled.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"PARROT NO. 3, PARROT NO. 13, PARROT NUMBER 22, PARROT NO. 24, PARROT NO. 25, PARROT NO. 26, PARROT NO. 27, and PARROT NO. 28 lodes, M.S. 4608 were canceled November 10, 1993, by memo 9605 (942) M.S. 4608, which is now a part of the original field notes."

November 10, 1993
Date



Chief Cadastral Surveyor of Arizona

