

Form 3400-11  
(September 1967)  
(formerly 4-683)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Mineral Survey number  
4630 Amd.

State  
Arizona

Land District  
Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*

BS&K Mining Company, an Arizona Corporation  
c/o Albert H. Mackenzie, Attorney-at-Law  
711 Arizona Title Bldg.,  
Phoenix, Arizona 85004

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
BS&K No. 1	5-20-65	
BS&K No. 3	5-20-65	
BS&K No. 4	5-20-65	
BS&K No. 5	6-14-65	
BS&K No. 13	7-14-65	
Nevada No. 2	7-27-54	7-17-70
New York	5-1-49	7-17-70

Mining district Silver Bell			County Pima	
Section 28 & 33	Township 11 South	Range 8 East	Meridian Gila & Salt River	Survey under order dated Sept 13, 1965
Survey commenced Oct 6, 1965		Survey completed Nov 10, 1965	Name of Mineral Surveyor Robert L. Frazer	
			Am. Oct 1 & 28, 1965 & Aug. 3, 1970	

Amd Sept 15 1970 to Oct 2 1970

Department of the Interior  
Bureau of Land Management  
Washington, D.C. 20250

OFFICE OF THE ASSISTANT SECRETARY  
FOR PUBLIC LANDS

FOR THE RECORD  
The enclosed report was prepared for the Assistant Secretary for Public Lands by the Bureau of Land Management, Department of the Interior, Washington, D.C. 20250. The report is being submitted to you for your information.

REPORT NUMBER	DATE	REPORT TITLE	AUTHOR
BLM-74-101	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-102	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-103	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-104	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-105	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-106	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-107	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-108	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-109	10-1-74	Inventory of Public Lands	J. H. ...
BLM-74-110	10-1-74	Inventory of Public Lands	J. H. ...

No. in District: 1000  
Section: 36  
Range: 20N  
Township: 20N  
County: ...

FEET	
	Thence N 67° 02' 45" E
180	Center of road, bears N 88° E, S 88° W
268.62	Intersect lode line at a point from which the disc. mon. a 4 x 4 post and 5/8 in. steel pin bears S 22° 56' 31" E, 299.21 ft. dist.
292.52	Intersect line 4-1, New York, of this survey; at a point from which Cor. No. 4 bears S 78° 04' 10" E, 491.66 ft. dist.
515	Center of road bears N 55° W, S 55° E
566.41	Cor. No. 2  Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, Stamped USMS 4630 - BSK 4-2, from which the corresponding loc. mon. for this claim, a 5/8 in. steel bar and 4 x 4 post bears N 9° 58' 25" W, 1.25 ft. dist.
	Thence S 22° 56' 31" E
125	Center of road bears S 80° E, N 40° W
190.93	Intersect line 4-1, New York of this survey; at a point from which Cor. No. 4 bears S 78° 04' 10" E, 157.82 ft. dist.
321.07	Intersect line 4-1, BS&K No. 5, of this survey, at a point from which Cor. No. 4 bears N 70° 01' 52" E, 614.24 ft. dist.
1480	Center of road, Junction bears East and N 70° W
1497.21	Cor. No. 3, identical with loc. mon. Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630-BSK 4-3  Thence S 67° 02' 45" W
297.79	Intersect lode line at a point from which the disc. mon. bears N 22° 56' 31" W, 1198.00 ft. dist.
460	Center of Arroyo 30' wide drains N 40° W.
504.05	Intersect the record line of line 2-3, survey 2791, King, from which existing Cor. No. 3 bears S 50° 40' E, 1042.21 ft. dist.
566.41	Cor. 4, identical with Cor. No. 3, BS&K No. 3, of this survey, a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 BSK 4-4, 3-3. Corresponding loc. mon., a 5/8 in. steel bar and 4 x 4 post bears S 45° 03' 35" E, 2.72 ft. dist.

(This form bound on left side)

FEET	
	Thence N 22° 56' 31" W
118.66	Intersect line 2-3, sur. 2791, King, at a point from which existing Cor. No. 3 bears S 50° 40' E, 1176.25 ft. dist.
122.21	Center of Arroyo 25' wide drains N 65° W.
237.21	Center of road bears S 70° W, N 70° E.
1205.68	Intersect line 4-1, BS&K No. 5, of this survey at a point from which Cor. No. 1 bears S 70° 01' 52" W, 318.48 ft. dist.
1332.21	Center of road bears N 70° E, S 70° W.
1497.21	Cor. No. 1 and place of beginning.
	-----
	BS&K NO. 5 LODE
	At Cor. No. 1, identical with location set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 BSK 5-1, from which the Cor. of Secs. 28, 29, 32, 33, as previously described, bears N 52° 21' 10" W, 2102.89 ft. dist.
	Common Cor. No. 2, BS&K No. 3 and Cor. No. 1 BS&K No. 4 bears N 26° 12' 34" E, 420.46 ft. dist.
	Thence N 19° 56' 48" W
15.0	Center of road bears N 30° E, S 30° W.
275.32	Intersect line 1-2, BS&K No. 3, of this survey at a point from which Cor. No. 2 bears N 67° 02' 45" E, 303.67 ft. dist.
300.00	Intersect lode line at a point from which disc. mon. bears N 70° 02' 17" E, 99.95 ft. dist.
360.0	Center of road, bears N 60° E, S 60° W.
450.0	Enter wash 20 ft. wide drains N 20° W from S 30° W.
500.0	Leave wash 20 ft. wide drains N 50° W from N 20° W.
600.00	Cor. No. 2 identical with loc. mon. Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 - BSK 5-2 from which Cor. No. 1, New York of this survey bears N 67° 26' 28" W, 353.89 ft. dist. Cor. falls on side of wash.
	Thence N 70° 02' 29" E

FEET	
15.0	Set witness Cor. 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630, BS&K 5, W-C 15'
123.55	Intersect line 4-1, New York lode of this survey at a point from which Cor. No. 1 bears N 78° 04' 10" W, 452.72 ft. dist.
187.0	Center of wash 10 ft. wide, drains N 25° W.
555.0	Center of road bears N 70° W, S 70° E.
582.20	Intersect line 4-1, BS&K No. 13, of this survey at a point from which Cor. No. 4 bears S 22° 50' 25" E, 287.04 ft. dist.
970.0	Junction of washes, drains N 37° W, from S 37° E, and South.
1176.40	Intersect line 2-3, BS&K No. 13, of this survey at a point from which Cor. No. 3 bears S 22° 47' 07" E, 257.32 ft. dist.
1209.55	Intersect line 2-3, New York, of this survey at a point from which Cor. No. 3 bears S 78° 04' 10" E, 156.62 ft. dist.
1489.90	Set witness Cor. 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630, W.C. BSK 5-3 10'
1499.90	<p>Cor. 3 falls in wash, drains N 35° W, identical with location.</p> <p>Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630-BSK 5-3.</p> <p>The 1/4 cor. common to Secs. 28 and 33 bears N 47° 50' 30" W, 307.89 ft. dist. A GLO brass-capped pipe, 1 in. in dia., 8 in. above ground, firmly set, stamped as in the official record.</p> <p>Thence S 19° 56' 48" E</p>
299.91	Intersect lode line at a point from which the disc. Mon. bears S 70° 02' 17" W, 1399.95 ft. dist.
535.0	Center of arroyo 30 ft. wide, drains West.
599.73	Cor. No. 4, identical with location. Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630-BSK 5-4

FEET	
	Thence S 70° 01' 52" W
290.0	Center of road bears N 80° W, S 80° E.
614.24	Intersect line 2-3, BS&K No. 4, of this survey at a point from which Cor. No. 2 bears N 22° 56' 31" W, 321.07 ft. dist.
1181.42	Intersect common line 2-3 BS&K No. 3 and 4-1 BS&K No. 4 of this survey at a point from which common cor. No. 2 and 1 bears N 22° 56' 31" W, 291.53 ft. dist.
1499.90	Cor. No. 1 and place of beginning
	- - - - -
	NEW YORK LODGE
	At Cor. No. 1
	Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM.N.Y.-1, from which the location Mon., a 4 x 4 post in a mound of stones bears N 77° 52' 57" W, 150.44 ft. dist.
	The cor. of Secs. 28, 29, 32, 33, as previously described bears N 62° 42' 56" W, 1275.44 ft. dist.
	Cor. No. 1 of New York as located prior to the judgement in Civil Cause No. 98311 bears S 20° 45' 05" E, 154.89 ft. dist.
	Cor. No. 2 BS&K No. 5, of this survey, bears S 67° 26' 28" E, 353.89 ft. dist.
	Thence N 15° 04' 02" E
300.45	Intersect lode line at a point from which Disc. Mon. bears S 78° 04' 10" E, 750.00 ft. dist.
403.0	Center of road bears N 25° E, S 25° W.
574.57	Cor. No. 2
	Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM.N.Y.-2, from which the location Mon., a 4 x 4 post in a mound of stones bears N 78° 05' 11" W, 150.64 ft. dist.
	Cor. No. 4, Nevada No. 2 of this survey, bears N 83° 42' 39" W, 56.82 ft. dist.

FEET	
	<p>Cor. No. 2 of New York as located prior to the judgement in Civil Cause No. 98311 bears S 35° 57' 36" W, 144.32 ft. dist.</p> <p style="text-align: center;">Thence S 78° 04' 10" E</p>
45.0	Center of road bears N 25° E, S 25° W.
130.0	Center of arroyo, 20 ft. wide, drains North.
580.61	Intersect line 4-1, BS&K No. 13, of this survey at a point from which Cor. No. 4 bears S 22° 50' 25" E, 690.50 ft. dist.
1020.0	Center of arroyo, 30 ft. wide, drains N 19° W.
1303.14	Intersect line 2-3, BS&K No. 13, of this survey at a point from which Cor. No. 3 bears S 22° 47' 07" E, 278.61 ft. dist.
1343.38	Intersect line 2-3, BS&K No. 5 of this survey at a point from which Cor. No. 3 bears N 70° 02' 29" E, 290.35 ft. dist.
1500.00	<p>Cor. No. 3</p> <p>Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM. N.Y.-3.</p> <p>No location monument found.</p> <p>The 1/2 cor. common to Secs. 28 and 33, as previously described bears N 17° 48' 01" W, 355.12 ft. dist.</p> <p>Cor. No. 3 of New York as located prior to the judgement in Civil Cause No. 98311 bears N 18° 10' 51" W, 175.31 ft. dist.</p> <p style="text-align: center;">Thence S 15° 04' 02" W</p>
274.12	Intersect lode line at a point from which Disc. Mon. bears N 78° 04' 10" W, 750.00 ft. dist.
390.0	Center of arroyo 50 ft. wide, drains N 60° W.
485.0	Center of arroyo 30 ft. wide, drains N 85° W.
530.0	Center of road, bears N 82° W, S 82° E.
574.57	<p>Cor. No. 4</p> <p>Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM. N.Y.-4, from which the loc. Mon., a 4 x 4 post in a mound of stones, bears S 75° 21' 50" E, 155.66 ft. dist.</p>

(This form bound on left side)

FEET	
	Cor. No. 3, BS&K No. 13, of this survey, bears N 10° 48' 27" E, 344.77 ft. dist.
	Cor. No. 2, BS&K No. 4, of this survey, bears N 47° 42' 01" W, 310.16 ft. dist.
	Cor. No. 4 of New York as located prior to the judgement in Civil Cause No. 98311 bears N 34° 39' 26" E, 148.87 ft. dist.
	Thence N 78° 04' 10" W
157.82	Intersect line 2-3, BS&K No. 4, of this survey, at point from which Cor. No. 2 bears N 22° 56' 31" W, 190.93 ft. dist.
360.0	Center of road bears S 82° W, N 82° E.
491.66	Intersect line 1-2, BS&K No. 4 of this survey at a point from which Cor. No. 2 bears N 67° 02' 45" E, 273.89 ft. dist.
600.0	Enter arroyo 10 ft. wide, meanders along line.
750.0	Leave arroyo, which drains N 70° W.
960.0	Center of arroyo 10 ft. wide, drains N 45° W.
1047.28	Intersect line 2-3, BS&K No. 5, of this survey at a point from which Cor. No. 2 bears S 70° 02' 29" W, 123.55 ft. dist.
1195.0	Center of arroyo 5 ft. wide, drains N 50° W.
1430.0	Center of arroyo 5 ft. wide, drains North.
1500.00	Cor. No. 1 and place of beginning.
	- - - - -
	BS&K NO. 13 LODE
	At cor. No. 1, identical with loc. Mon., set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630-BSK 13-1 from which the cor. of secs. 28, 29, 32, 33, as previously described bears S 68° 55' 43" W, 1648.45 ft. dist.
	Cor. No. 1, BS&K No. 1, of this survey bears S 56° 19' 16" E, 78.07 ft. dist.
	Cor. No. 2, Nevada No. 2, of this survey bears N 5° 25' 15" E, 379.10 ft. dist.
	Thence N 67° 10' 30" E
40.0	Center of road, bears N 50° W, S 65° E.



FEET	
42.92	Intersect line 4-1, BS&K No. 1, of this survey at a point from which Cor. No. 1 bears S 22° 58' 27" E, 65.11 ft. dist.
294.64	Intersect lode line at a point from which Disc. Mon. bears S 22° 47' 12" E, 283.6 ft. dist. Corresponding Loc. Mon., a 4 x 4 post bears N 52° 34' 09" E, 5.25 ft. dist.
345.0	Center of arroyo 40 ft. wide drains N 55° W.
377.31	Intersect line 2-3, Nevada No. 2, of this survey at a point from which Cor. No. 3 bears S 53° 28' 30" E, 118.96 ft. dist.
594.64	<p>Cor. No. 2</p> <p>Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 - BSK 13-2 corresponding Loc. Mon., a 4 x 4 post, bears N 52° 42' 30" E, 5.30 ft. dist.</p> <p style="text-align: center;">Thence S 22° 47' 07" E</p>
585.0	Center of road bears N 60° E, S 60° W.
1217.60	Intersect line 2-3, New York, of this survey at a point from which Cor. No. 3 bears S 78° 04' 10" E, 196.86 ft. dist.
1238.89	Intersect line 2-3, BS&K No. 5, of this survey at a point from which true point for Cor. No. 3 bears N 70° 02' 29" E, 323.49 ft. dist.
1496.21	<p>Cor. No. 3</p> <p>Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 - BSK 13-3 from which corresponding Loc. Mon., a 4 x 4 post, bears S 67° 10' 19" E, 5.06 ft. dist.</p> <p>Cor. 3, New York, bears N 21° 23' 56" E, 232.17 ft. dist.</p> <p>Cor. 3, BS&amp;K No. 5, bears N 30° 27' 01" E, 403.28 ft. dist.</p> <p style="text-align: center;">Thence S 67° 10' 30" W</p>
125.0	Center of arroyo 40 ft. wide, drains North.
225.0	Center of arroyo drains N 10° W.
300.00	<p>Intersect lode line at a point from which Disc. Mon. bears N 22° 47' 12" W, 1212.62 ft. dist.</p> <p>Corresponding Loc. Mon., a 4 x 4 post, bears N 83° 24' 40" E, 6.23 ft. dist.</p>

(This form bound on left side)

FEET	
380.0	Center of road bears N 60° W, S 60° E.
593.24	Cor. No. 4
	Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630, BSK 13-4 corresponding Loc. Mon., a 4 x 4 post, bears S 21° 37' 34" W, 2.49 ft. dist.
	Thence N 22° 50' 25" W
275.0	Center of road bears N 70° W, S 70° E.
287.04	Intersect line 2-3, BS&K No. 5, of this survey at a point from which Cor. No. 2 bears S 70° 02' 29" W, 582.20 ft. dist.
690.50	Intersect line 2-3, New York, of this survey at a point from which Cor. No. 2 bears N 78° 04' 10" W, 580.61 ft. dist.
825.0	Center of road bears N 45° E, S 45° W.
1237.35	Intersect line 3-4, Nevada No. 2 of this survey at a point from which Cor. No. 3 bears N 47° 30' 18" E, 465.03 ft. dist.
1315.0	Center of road bears N 80° E, S 80° W
1431.02	Intersect line 1-2, BS&K No. 1, of this survey at a point from which Cor. No. 1 bears N 67° 02' 57" E, 43.07 ft. dist.
1496.23	Cor. 1 and place of beginning.
	-----
	NEVADA NO. 2 LODGE
	At Cor. No. 1, identical with Loc. Mon., a 4 x 4 post in a mound of stones, set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM. NEV 2-1, from which: The cor. of secs. 28, 29, 32, 33, as previously described, bears S 71° 14' 03" W, 864.85 ft. dist.
	Cor. No. 1 of Nevada No. 2 as located prior to the judgement in Civil Cause No. 98311, a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 NEV 2-1, bears N 15° 51' 42" E, 621.37 ft. dist.
	Cor. No. 2 of BS&K No. 1, bears N 80° 52' 24" E, 235.01 ft. dist.

FEET	
	Thence N. 47°30'18" E.
242.09	Intersect line 2-3, BS&K No. 1, of this survey at a point from which Cor. No. 2 bears S 22° 58' 27" E, 137.14 ft. dist.
460.0	Center of arroyo, 30 ft. wide, drains N 53° W
715.0	Center of road bears N 47° W, S 58° E
878.43	Intersect line 4-1, BS&K No. 1, of this survey at a point from which Cor. No. 1 bears S 22° 58' 27" E, 350.02 ft. dist.
950.0	Center of arroyo, 50 ft. wide drains N 70° W
1024.17	Cor. No. 2, identical with a 4 x 4 post in a mound of rock, dimly scribed "NEV." Set a 5/8" in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM. NEV 2-2, from which Cor. No. 1 of BS&K No. 13 bears S 5° 25' 15" W, 379.10 ft. dist.  Cor. No. 2 of Nevada No. 2 as located prior to the judgement in Civil Cause No. 98311 bears N 67° 10' 03" W, 45.00 ft. dist.  Thence S 53° 28' 30" E
180.0	Enter arroyo, 50 ft. wide drains N 80° W
263.18	Intersect lode line at a point from which Disc. point bears S 47° 30' 18" W, 600.91 ft. dist. Leave arroyo, drains N 20° W
388.20	Intersect line 1-2, BS&K No. 13, of this survey at a point from which Cor. No. 1 bears S 67° 10' 30" W, 377.31 ft. dist.
507.16	Cor. No. 3  This corner falls on the Easterly bank of a side wash which drains North, in unstable ground.  Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM. NEV 2-3  Cor. No. 3 of Nevada No. 2 as located prior to the judgement in Civil Cause No. 98311 bears S 2° 35' 39" W, 1094.52 ft. dist.  Thence S 47° 30' 18" W
20.0	Thread of wash, drains N 54° W
30.0	Set a witness cor. 5/8 in. steel bar 30 in. long with cast aluminum cap affixed thereon, driven 15 in. in the ground. Stamped USMS 4630 AM. WC NEV 2-3. 30'
50.0	Side wash, drains North

(This form bound on left side)

FEET		
310.0	Center of road forks, bears N 45° W, S 78° W, and S 65° E.	
465.03	Intersect line 4-1, BS&K No. 13, of this survey at a point from which Cor. No. 1 bears N 22° 50' 25" W, 258.88 ft. dist.	
710.0	Center of arroyo, 20 ft. wide, drains N 15° W.	
815.0	Center of road bears N 24° E, S 24° W	
1024.17	<p>Cor. No. 4, identical with Loc. Mon., a 4 x 4 post in a mound of stones. Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630 AM. NEV 2-4</p> <p>Cor. No. 2, New York, bears S 83° 42' 39" E, 56.82 ft. dist.</p> <p>Cor. No. 4 of Nevada No. 2 as located prior to the judgement in Civil Cause No. 98311 bears S 12° 43' 15" E, 535.29 ft. dist.</p> <p style="text-align: center;">Thence N 53° 28' 30" W</p>	
243.98	<p>Intersect lode line at a point from which Disc. point bears N 47° 30' 18" E, 423.26 ft. dist.</p> <p>A 4 x 4 post in a mound of stones bears S 47° 30' 14" W, 7.54 ft. dist.</p>	
507.16	<p>Cor. No. 1 and place of beginning.</p> <p style="text-align: center;">-----</p> <p style="text-align: center;">BS&amp;K NO. 1 LODE</p> <p>At Cor. No. 1, identical with location set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. in the ground and surrounded by stones, stamped USMS 4630-BSK 1-1, from which the Cor. of Secs. 28,29,32,33 as previously described bears S 71° 05' 05" W, 1694.71 ft. dist.</p> <p>Cor. No. 1, BS&amp;K No. 13 bears N 56° 19' 16" W, 78.07 ft. dist.</p> <p style="text-align: center;">Thence S 67° 02' 57" W</p>	
43.07	Intersect line 4-1, BS&K No. 13, of this survey at a point from which Cor. No. 1 bears N 22° 50' 25" W, 65.21 ft. dist.	
299.76	Intersect lode line at a point from which Disc. Mon. bears N 22° 58' 27" W, 650.08 ft. dist.	
350.0	Center of arroyo, 50 ft. wide, drains N 30° W	
599.76	Cor. No. 2. Identical with location. Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. into the ground and surrounded by stones, stamped USMS 4630-BSK 1-2	

FEET	
	Thence N 22° 58' 27" W
137.14	Intersect line 1-2, Nevada No. 2, of this survey at a point from which Cor. No. 1 bears S 47° 30' 18" W, 242.09 ft. dist.
645.0	Center of arroyo 50 ft. wide drains N 70° W
745.0	Center of road bears N 60° W and East
1499.57	Cor. No. 3. Identical with location. Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. into the ground and surrounded by stones, stamped USMS 4630 BSK 1-3
	Thence N 67° 02' 57" E
235.0	Center of arroyo 50 ft. wide drains N 40° W
300.00	Intersect lode line at a point from which Disc. Mon. bears S 22° 58' 27" E, 849.49 ft. dist.
599.76	Cor. No. 4, identical with location. Set a 5/8 in. steel bar, 30 in. long with a cast aluminum cap affixed thereon, driven 15 in. into the ground and surrounded by stones, stamped USMS 4630 BSK 1-4
	Thence S 22° 58' 27" E
935.0	Center of road bears N 80° W, N 80° E
1065.0	Center of arroyo, 50 ft. wide, drains N 70° W
1149.55	Intersect line 1-2, Nevada No. 2, of this survey at a point from which Cor. No. 2 bears N 47° 30' 18" E, 145.74 ft. dist.
1434.46	Intersect line 1-2, BS&K No. 13, of this survey at a point from which Cor. No. 1 bears S 67° 10' 30" W, 42.92 ft. dist.
1440.0	Center of road bears N 52° W, S 60° E
1499.57	Cor. No. 1 and place of beginning.
	- - - - -
	<u>AREAS</u>
	<u>Acres</u>
	Total Area, BS&K No. 1 Lode 20.647
	Area in conflict with:
	Nevada No. 2, Lode 3.354
	BS&K No. 13, Lode 0.064
	Nevada No. 2 exclusive of its conflict with BS&K No. 13 3.290
	Total Area, BS&K No. 3 Lode 20.569
	Area in conflict with:

(This form bound on left side)

FEET	<u>AREAS</u>	<u>Acres</u>
	Sur. No. 2791, King, Lode	4.330
	Sur. No. 2790, Rex, Lode	3.449
	BS&K No. 5, Lode	2.023
	Total Area, BS&K No. 4 Lode	19.468
	Area in conflict with:	
	Sur. No. 2791, King, Lode	0.085
	BS&K No. 5, Lode	3.983
	New York, Lode	0.600
	BS&K No. 5, exclusive of its conflict with New York	3.383
	Total Area, BS&K No. 5 lode	20.655
	Area in conflict with:	
	New York Lode	7.928
	BS&K No. 13 Lode	3.707
	BS&K No. 4, Lode	3.983
	BS&K No. 4, Lode exclusive of its conflict with New York	3.383
	BS&K No. 3, Lode	2.023
	Total Area, BS&K No. 13	20.401
	Area in conflict with:	
	Nevada No. 2 Lode	1.744
	BS&K No. 1 Lode	0.064
	Nevada No. 2, exclusive of its conflict with BS&K No. 1	1.680
	BS&K No. 5 Lode	3.707
	New York, Lode	6.601
	New York, exclusive of its conflict with BS&K No. 5	2.894
	Total Area, New York, Lode	19.756
	Area in conflict with:	
	BS&K No. 13, Lode	6.601
	BS&K No. 5, Lode	7.928
	BS&K No. 13, exclusive of its conflict with BS&K No. 5	2.894
	BS&K No. 4, Lode	0.600
	BS&K No. 5, exclusive of its conflict with BS&K No. 13	4.221
	BS&K No. 5, exclusive of its conflict with BS&K No. 13 and BS&K No. 4	3.620
	Total Area, Nevada No. 2 Lode	11.706
	Area in conflict with:	
	BS&K No. 13 Lode	1.744
	BS&K No. 1 Lode	3.354
	BS&K No. 1, exclusive of its conflict with BS&K No. 13	3.290
	BS&K No. 13 exclusive of its conflict with BS&K No. 1	1.680

FEET	LOCATION
	<p>This survey is located in Secs. 28 and 33, T-11S, R-8E Gila &amp; Salt River Base and Meridian.</p> <p>Survey of all lodes are identical with, or wholly within the location or amended location cors. as found on the ground, as shown in notes.</p> <p style="text-align: center;"><b>EXPENDITURES</b></p> <p>The improvements and value of labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors is as follows:</p> <p><u>BS&amp;K NO. 3 LODE</u></p>
No. 1	<p>The discovery Mon. is on the lode line, 98.3 ft. from a pt. on line 1-2, 298.45 ft. from Cor. No. 1; a 4 x 4 post</p> <p style="text-align: center;">Value - None</p>
No. 2	<p>A discovery shaft, the center of which bears S 22° 04' 09" E, 110.00 ft. dist. from a pt. on line 1-2, 298.45 ft. from Cor. No. 1, 6' x 10' in size, 8' deep, blasted in rock</p> <p style="text-align: center;">Value - \$125.00</p>
No. 3	<p>A core drill hole, the center of which bears S 43° 01' 29" E, 75.37 ft. dist. from a point on line 1-2, 298.45 ft. from Cor. No. 1, 2 in. core, 182 ft. deep at \$6.50 per ft.</p> <p style="text-align: center;">Value - \$1183.00</p> <p style="text-align: center;">. Total Expenditure \$1308.00</p>
	<p><u>BS&amp;K NO. 4 LODE</u></p>
No. 1	<p>The discovery Mon. is on the lode line, 299.21 ft., from a pt. on Line 1-2, 268.62 ft. from Cor. No. 1, a 4 x 4 post and 5/8 in. steel bar.</p> <p style="text-align: center;">Value - None</p>
No. 2	<p>A disc. shaft, the center of which bears S 22° 35' 14" E, 290.92 ft. dist. from a pt. on Line 1-2, 268.62 ft. dist. from Cor. No. 1; 6' x 7' in size, 8' deep, blasted in rock.</p> <p style="text-align: center;">Value - \$100.00</p>
No. 3	<p>A core drill hole, the center of which bears S 3° 47' 40" E, 190.68 ft. Dist. from a pt. on Line 1-2, 268.62 ft. from Cor. No. 1, 2 in. core, 170 ft. deep at \$6.50 per ft.</p> <p style="text-align: center;">Value - \$1105.00</p> <p style="text-align: center;">Total Expenditure \$1205.00</p>

(This form bound on left side)



FEET	
	<u>BS&amp;K NO. 1 LODE</u>
No. 1	The discovery Mon. is on the Lode line 650.08 ft. from a pt. on Line 1-2, 299.76 ft. from Cor. No. 1, a 4 x 4 post and 5/8 in. steel bar.  Value - None
No. 2	A discovery shaft, the center of which bears N 23° 06' 55" W, 639.0 ft. from a point on Line 1-2, 299.76 ft. from Cor. No. 1; 12' x 12' in size, 8' deep, blasted in rock  Value - \$125.00
No. 3	A core drill hole, the center of which bears N 20° 50' 40" W, 590.68 ft. dist. from a pt. on Line 1-2, 299.76 ft. from Cor. No. 1, 2 in. core, 100 ft. deep, at \$6.50 per ft.  Value - \$650.00  Total Expenditure \$775.00
	<u>NEW YORK LODE</u>
No. 1	The discovery Mon. is on the lode line 750.00 ft. dist. from a point on Line 1-2, 300.00 ft. from Cor. No. 1, a 4 x 4 post set after judgement in Civil Cause No. 98311.  Value - None
No. 2	A discovery shaft, 4' x 6' in size, 8' deep, blasted in rock, the center of which bears N 80° 37' 59" E, 819.50 ft. dist. from Cor. No. 1, in place prior to judgement in Civil Cause No. 98311.  Value - \$100.00
No. 3	Disc. Mon. bears N 81° 27' 49" E, 820.60 ft. Dist. from a point on Line 1-2; 300.0 ft. from Cor. No. 1, a 4 x 4 post  Value - None
No. 4	A core drill hole, the center of which bears N 87° 31' 03" E, 935.94 ft. dist. from Cor. No. 1, 2 in. core, 206 ft. deep at \$6.50 per ft.  Value - \$1339.00  Total Expenditure \$1439.00
	<u>BS&amp;K NO. 13 LODE</u>
No. 1	The discovery Mon. is on the lode line, 283.60 ft. from a pt. on line 1-2, 294.64 ft. from Cor. No. 1; a 4 x 4 post.  Value - None



FEET	
No. 2	<p>A discovery shaft, the center of which bears S 25° 02' 57" E, 285.0 ft. dist. from a point on Line 1-2, 294.64 ft. from Cor. No. 1; 6' x 8' in size, 8' deep, blasted in rock.</p> <p>Value - \$100.00</p>
No. 3	<p>A core drill hole, the center of which bears S 9° 31' 47" E, 546.26 ft. dist. from a point on line 1-2, 294.64 ft. from Cor. No. 1; 2 in. core, 167 ft. deep, at \$6.50 per foot.</p> <p>Value - \$1085.00</p> <p>Total Expenditure \$1185.00</p> <p><u>BS&amp;K NO. 5 LODE</u></p>
No. 1	<p>The disc. mon. is on the Lode line 99.95 ft. dist. from a point on Line 1-2, 300.00 ft. from Cor. No. 1, a 4 x 4 post and 5/8 in. steel bar.</p> <p>Value - None</p>
No. 2	<p>A discovery shaft bears N 70° 43' 58" E, 106.75 ft. dist. from a point on line 1-2, 300.00 ft. from Cor. No. 1, 6' x 8' in size, 8' deep, blasted in rock.</p> <p>Value - \$125.00</p> <p>Claimant will file supplemental proof of expenditure of at least \$500.00 prior to expiration of period of publication.</p> <p><u>NEVADA NO. 2 LODE</u></p>
No. 1	<p>A disc. pt. is on the lode line 423.26 ft. dist. from a point on Line 4-1, 243.98 ft. from Cor. No. 4, a 4 x 4 post set after judgement in Civil Cause No. 98311.</p> <p>Value - None</p>
No. 2	<p>A disc. Mon bears N 83° 13' 16" E, 593.0 ft. dist. from Cor. No. 1, A 4 x 4 post in place prior to judgement in Civil Cause No. 98311.</p> <p>Value - None</p>
No. 3	<p>A discovery cut, 8' x 12' in size, 7' deep, blasted in rock in the bank of an arroyo, the center of which bears N 84° 42' 06" E, 588.24 ft. from Cor. No. 1.</p> <p>Value - \$100.00</p>
No. 4	<p>A core drill hole, the center of which bears N 85° 39' 38" E, 673.48 ft. dist. from Cor. No. 1, 2 in. core, 151 ft. deep, at \$6.50 per ft.</p> <p>Value - \$1081.50</p> <p>Total Expenditure \$1181.50</p>

FEET

OTHER CORNER DESCRIPTIONS AND  
SUPPLEMENTAL DATA

BS&K LODES 1, 3, 4, 5

All location and discovery corners are 5/8 in. deformed bars, 15 in. long, driven 12 in. or more deep. A 4 x 4 post in a stone mound is placed immediately beside the bar.

BS&K 13

Location and discovery cors. are 4 x 4 posts in stone mounds.

NEW YORK

Location and discovery mons. are 4 x 4 posts in stone mounds. The Northeast corner falls in an arroyo. Loc. Mon. probably destroyed by water.

NEVADA NO. 2

Location and discovery mons. are 4 x 4 posts in stone mounds. The Southeast corner falls on edge of an arroyo. Loc. Mon. probably destroyed by water.

Surv 2790, Rex; Cors No. 1 and 2 are 2 in. pipes with 2- $\frac{1}{2}$  in. lead caps firmly set in stone mounds. Line 1-2 was found to be N 43° 40' 54" W, 1500.3 ft. instead of N 43° 40' W, 1500 ft. as approved. Line 3-4 was found to be S 43° 37' 59" E, 1499.803 ft. instead of S 43° 40' E, 1500 ft. as approved.

Line 4-1 was found to be S 39° 54' 32" W, 592.9 ft. instead of S 39° 50' W, 593.3 ft. as approved. Cors No. 3 and 4 are well-built stone monuments of the same size and character as Cors. 1 and 2. Pipes not in place. Set a 5/8 in. bar in center of same for definite point. Line 2-3 was found to be N 39° 58' 52" E, 594.1 ft. instead of N 39° 50' E, 593.3 ft. as approved.

Surv 2791, King; Cor. No. 1 is a 2 in. lead-capped pipe firmly set in a stone mound. Cor. No. 4 is a well-built stone monument; as for Cor. No. 1, pipe not in place. Set a 5/8 in. bar in center of same for definite point.

Lines 1-2 and 2-3 were projected to a calculated intersection for missing point No. 2, using the record bearings of each line. Thus, line 1-2 was calculated to be N 49° 27' E, 609.546 ft. instead of N 49° 27' E, 609.0 ft. as approved. Line 2-3 was calculated to be S 50° 40' E, 1498.812 ft., instead of S 50° 40' E, 1500.0 ft. as approved.

FEET	
	<p>Cor. No. 3 is a firmly set stone, scribed 3K-2791 on West face. Position for Cor. No. 2 falls in a wash, not found, no witness cor. Called in survey notes.</p> <p>Line 3-4 found to be S 49° 23' 14" W, 609.7 ft. instead of S 49° 27' W, 609 ft.</p> <p>Line 4-1 found to be N 50° 39' 27" W, 1499.5 ft. instead of N 50° 40' W 1500 ft.</p> <p>Sur. 2791, Columbia, Cor. No. 2 is a 2" pipe and lead cap firmly set in a stone mon.</p> <p>Cor. No. 3 is a stone mon. Same size and character Cor. No. 2, pipe not in place.</p> <p>Other cors. not found.</p>

F E E T



# United States Department of the Interior

1

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
3022 Federal Building  
Phoenix, Arizona 85025

*Survey plat & index card noted  
10-14-71*

October 13, 1971 *EB*

## Memorandum

To : Chief, Division of Management Services, ASO  
(Att'n. Branch of Records & Data Management)

From : State Director, Arizona

Subject: Mineral Survey No. 4630 AMD.

This memorandum cancels the survey of the BS&K No. 5 lode claim of Mineral Survey No. 4630 AMD.

The following notation should be made on the plat of Mineral Survey No. 4630 AMD.:

"Survey of BS&K No. 5 lode claim canceled by State Director's memorandum dated October 13, 1971."

The plat and field notes should remain in the files. This memorandum should be made a part of the original field notes of Mineral Survey No. 4630 AMD.

By letter dated October 11, 1971, the claimant, BS&K Mining Company, requested cancellation of the survey of BS&K No. 5 lode claim under Mineral Survey No. 4630 AMD. The BS&K No. 5 lode claim, as surveyed under Mineral Survey No. 4630 AMD., was the subject of court action by an adjoining locator. Pursuant to judgment in this court action, the location point and discovery shaft for the BS&K No. 5 lode were held to be on invalid ground, specifically on NSB No. 19, an unsurveyed senior lode location. Claimant has relocated the BS&K No. 5 lode as the Gap No. 1 lode and made application for survey of the Gap No. 1 lode under a new survey designated as Mineral Survey No. 4682.

Mineral Survey No. 4630 AMD. does not appear on any subsisting plats.

cc: Director

*Riley E. Freeman*









# United States Department of the Interior

IN REPLY REFER TO  
3000 (945)

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
3022 Federal Building  
Phoenix, Arizona 85025

3

July 29, 1974

413

ARIZONA STATE OFFICE	
B.J. LAND MANAGEMENT	
AUG 7 '74	
CO	_____
ASSOC. SD	_____
PCS	_____
RESOURCES	_____
TECH SER	_____
MGMT SER	_____
PJB. AFF	_____
CF	_____
ACTION	
INFO.	
13 lode missing	

Memorandum

To: Chief, Division of Management Services, ASO  
(Att'n. Branch of Records & Data Management)

From: State Director, Arizona

Subject: Mineral Survey No. 4630 AMD.

This memorandum cancels the survey of the BS&K No's 1 and 13 lode claims of Mineral Survey No. 4630 AMD.

The following notation should be made on the plat of Mineral Survey No. 4630 AMD.:

"Survey of BS&K No's 1 and 13 lode claims canceled by State Director's memorandum dated July 29, 1974."

The plat and field notes should remain in the files. This memorandum should be made a part of the original field notes of Mineral Survey No. 4630 AMD.

The BS&K No's 1 and 13 lode claims as surveyed under M.S. 4630 AMD were the subject of court action by an adjoining locator. The final judgement in this case (American Smelting & Refining Co. - Ariz. Civ #98311) decreed that possessory title to the BS&K No's 1 and 13 lode claims vested in American Smelting & Refining Co.

Claimant BS&K Mining Company has not appealed the decision and the judgement is final.

*Joe T. Fallini*

RECEIVED  
BUREAU OF LAND MANAGEMENT  
COMMUNICATIONS UNIT

AUG 2 1974

AM 7,8,9,10,11,12,1,2,3,4,5,6 PM

ENTERED - 8-8-74 D.D.T.

