

Form 4-683
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey number

4636

State
Arizona

Land District
Phoenix

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*

R. W. and Philip R. Hull
Post Office Box 461
Payson, Arizona 85541

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Royal Flush	8/27/34	
Royal Flush No. 1	8/27/34	
Royal Flush #4	5/19/62	
Royal Flush No. 5	6/27/42	
Royal Flush #6	9/5/63	
Royal Flush #7	5/19/62	12/8/65
Royal Flush #8	9/5/63	
Royal Flush No. 9	6/27/42	4/15/66
Royal Flush #11	5/24/62	
Grubstake	11/10/42	

Mining district Green Valley			County Gila	
Section 36 30 & 31	Township 10N 10N	Range 10E 11E	Meridian Gila & Salt River	Survey under order dated Nov. 22, 65 Amended
Survey commenced 12/12/65		Survey completed 5/6/66	Name of Mineral Surveyor Robert E. Adams	2/24/66 5/3/66

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Project Number	
Date	
Field Station	

On the survey of the Mining Claim of [Name] and [Name] of [County] [State]

Section 33
T10N R10E S12E
[County] [State]

Survey of the [Name] of [Name] of [County] [State]

COMPARISON OF LOCATIONS MARKED AND LOCATED AS FOLLOWS

DATE	NAME OF LOCATION	
	LOCATED	MARKED
1911		
1912		
1913		
1914		
1915		
1916		
1917		
1918		
1919		
1920		
1921		
1922		
1923		
1924		
1925		
1926		
1927		
1928		
1929		
1930		
1931		
1932		
1933		
1934		
1935		
1936		
1937		
1938		
1939		
1940		
1941		
1942		
1943		
1944		
1945		
1946		
1947		
1948		
1949		
1950		

Surveyed by	
Checked by	
Date of Survey	
Scale	
Notes	

FEET	SURVEY NO. 4636
	<p>This survey was made with a Universal Wild T-2 Theodolite No. T2-68064, reading by optical micrometer to one second of arc. The instrument was in good condition at the time of the survey and all adjustments were in good order.</p> <p>All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:</p> <p>March 29, 1966 at cor. No. 3 of the royal Flush #7 lode this survey, in latitude 34° 10.1' N., and longitude 111° 16' W., I made a series of six altitude observations upon the sun three each with the telescope in the direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angle from a point along the south bdry. of the Royal Flush #7 lode extended, about 3500 ft. south west, to the sun. The true bearing of this line, which forms the south east bdrys. of the Royal Flush, Royal Flush #4, and the Royal Flush #7 lodes this survey, is S. 69° 08'42" W.</p> <p>The lines were measured with a Lufkin steel tape 300 feet in length graduated every foot thruout its length except the 1st., 99th., 199th., and 299th feet which are graduated to tenths and hundredths of a foot. The tape was compared with a standard tape at the time of the survey and found to be correct.</p> <p>All lines and connections of this survey were run by direct methods.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of 14° 30' E.</p>
	<p><u>ROYAL FLUSH LODGE</u></p>
	<p>Beginning at cor. No. 1 of the Royal Flush lode, identical with Cor. No. 1 of the Royal Flush No. 1 lode of this survey.</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 ins. in the ground, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, in a small mound of stones, mkd. Rf-1, RF1-1, 4636 from which</p> <p style="padding-left: 40px;">The cor. to secs. 25,36, T.10 N., R. 10 E. and secs. 30,31, T.10 N., R. 11 E., G. & S. R. Mer., bears N. 11° 00' 05" E., 1320.13 ft. dist., a stone 12 ins. by 8 ins. projecting 1 ft. above ground, marked and witnessed as described in the official record.</p> <p style="padding-left: 40px;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="padding-left: 80px;">Thence N. 69° 88' 42" E.</p>
20.00	Ridge, bears S. 40° E. and N. 40° W.
465.00	Road, 10 ft. wide, bears N. 75° W. and S. 75° E.
505.00	Road, 8 ft. wide, bears N. 75° W. and S. 75° E.
1,450.00	Gibson Creek, 50 ft. wide, course S: 25° E.
1,500.00	Cor. No. 2, identical with Cor. No. 2 of the Royal Flush #4 lode of this survey.
	<p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 ins. metal cross piece welded to its base,</p>

FEET		
	<p>20 ins. in the ground, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, in a small mound of stones, mkd. RF-2, RF4-2, 4636 from which</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 20° 51' 18" E.</p>	
300.00	Lode line; discovery point bears S. 69° 08' 42" W., 800 ft. dist.	
383.00	Center Gibson Creek, 50 ft. wide, course S. 25° E.	
600.00	<p>Cor. No. 3, identical with Cor. No. 3 of the Royal Flush #4 lode and on Line 1-2 of the Royal Flush No. 5 Lode, both of this survey.</p> <p>Set a wood stake as this corner is in the center of Gibson Creek, 50 ft. wide, course South from which</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 17 ins. in the ground, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, in a small mound of stones, for witness Cor. No. 3, mkd. WC-RF3, RF4-3, 4636, bears N. 69° 08' 42" E., 39.60 ft. dist.</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 69° 08' 42" W.</p>	
177.00	Road, 8 ft. wide, bears N. and S.	
752.00	Top of hill.	
789.00	Road, 8 ft. wide bears N. 40° W. and S. 40° E.	
840.44	Cor. No. 2 of the Royal Flush No. 5 lode of this survey.	
1,500.00	<p>Cor. No. 4, on Line 4-1 Royal Flush No. 1 lode of this survey, and falls on south edge of road.</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, in a small mound of stones, mkd. RF-4, 4636 from which</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence N. 20° 51' 18" W.</p>	
4.00	Road, 10 ft. wide, bears N. 50° E. and S. 50° W.	
300.00	Lode line; discovery point bears N. 69° 08' 42" E., 700 ft. dist.	
600.00	Cor. No. 1 and place of beginning.	
	<u>ROYAL FLUSH NO. 1 LODE</u>	
	Beginning at Cor. No. 1 of the Royal Flush No. 1 lode,	

FEET	
	<p>identical with cor. No. 1 of the Royal Flush lode of this survey, previously described.</p> <p style="text-align: center;">Thence S. 52° 08' 42" W.</p>
199.38	Cor. No. 1 of the Royal Flush #11 lode of this survey.
407.00	Road, 10 ft. wide, bears N. 40° W. and S. 40° E.
627.00	Road, 10 ft. wide, bears N. 65° W. and S. 65° E.
695.00	Wash, 5 ft. wide, course S. 60° E.
878.92	Cor. No. 2 of the Royal Flush #11 lode of this survey.
1,500.00	<p>Cor. No. 2</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF1-2, 4636 from which</p> <p style="text-align: center;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="text-align: center;">Thence S. 20° 51' 18" E.</p>
313.71	Lode line; discovery point bears N. 52° 08' 42" E., 1150 ft. dist.
365.00	Top of hill.
627.42	<p>Cor. No. 3</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 17 ins. in the ground, in a small mound of stones with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF1-3, 4636 from which</p> <p style="text-align: center;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="text-align: center;">Thence N. 52° 08' 42" E.</p>
969.69	Intersect line 1-2 Royal Flush No. 9 lode of this survey.
1,031.00	Wash, 5 ft. wide, course S. 40° E.
1,113.00	Road, 10 ft. wide, bears N. 40° W. and S. 40° E.
1,236.00	Road, 10 ft. wide, bears N. and S. 10° W.
1,249.00	Road, 10 ft. wide, bears N. 40° E. and S. 10° W.
1,371.34	Intersect line 4-1 Royal Flush No. 9 lode of this survey.
1,500.00	<p>Cor. No. 4</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 19 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF1-4, 4636 from which</p> <p style="text-align: center;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="text-align: center;">Thence N. 20° 51' 18" W.</p>
27.42	Cor. No. 4 of the Royal Flush lode of this survey.

31.42	Road, 10 ft. wide, bears N. 50° E. and S. 50° W.
313.71	Lode line; discovery point bears S. 52° 08' 42" W., 350 ft. dist.
627.42	Cor. No. 1 and place of beginning.
<u>ROYAL FLUSH NO. 4 LODE</u>	
Beginning at Cor. No. 1 of the Royal Flush #4 lode, identical with Cor. No. 1 of the Royal Flush #7 lode of this survey.	
Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 19 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF4-1, RF7-1, 4636 from which	
The cor. of secs. 25, 30, 31, and 36, T. 10 N., R's. 10 & 11 E., G. & S.R.M., bears N. 84° 53' 49" W., 2561.68 ft. dist.; previously described.	
A mound of stones constructed adjacent to the iron pipe.	
Thence S. 69° 08' 42" W.	
369.00	Wash, 9 ft. wide, course S. 20° E.
1,257.00	Top of ridge.
1,500.00	Cor. No. 2, identical with Cor. No. 2 of the Royal Flush lode of this survey, previously described.
Thence S. 20° 51' 18" E.	
300.00	Lode line; discovery point bears N. 69° 08' 42" E., 750 ft. dist.
383.00	Center Gibson Creek, 50 ft. wide, course S. 25° E.
600.00	Cor. No. 3, identical with Cor. No. 3 of the Royal Flush lode of this survey, previously described.
Thence N. 69° 08' 42" E.	
39.60	Witness cor. for Cor. No. 3, previously described.
258.00	Ridge, bears N. and S.
490.00	Road, 8 ft. wide, bears N. 10° W. and S. 10° E.
659.56	Cor. No. 1 of the Grubstake lode, identical with Cor. No. 1 of the Royal Flush No. 5 lode both of this survey.
871.00	Wash, 9 ft. wide, course S. 20° E.
941.00	Small ridge, bears N. 20° W. and S. 20° E.
1,006.00	Wash, 5 ft. wide, course S. 20° E.
1,188.00	Road, 10 ft. wide, bears N. 25° W. and S. 20° E.

FEET	
1,200.00	Wash, 3 ft. wide, course S. 50° W.
1,259.56	Cor. No. 2 of the Grubstake lode, identical with Cor. No. 1 of the Royal Flush #6 lode both of this survey.
1,500.00	Cor. No. 4, identical with Cor. No. 4 of the Royal Flush #7 lode, and on line 4-1 of the Royal Flush #6 lode, both of this survey. Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 17 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF4-4, RF7-4, 4636 from which A mound of stones constructed adjacent to the iron pipe. Thence N. 20° 51' 18" W.
50.00	Wash, 4 ft. wide, course S. 70° W.
127.00	Road, 12 ft. wide, bears S. 65° W. and N. 65° E.
300.00	Lode line; discovery point bears S. 69° 08' 42" W., 750 ft. dist.
600.00	Cor. No. 1 and place of beginning.
<u>ROYAL FLUSH NO. 5 LODE</u>	
	Beginning at Cor. No. 1 of the Royal Flush No. 5 lode, identical with Cor. No. 1 of the Grubstake lode, and on line 3-4 Royal Flush #4 lode, both of this survey. Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 16 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF5-1, G-1, 4636 from which The cor. of secs. 25, 30, 31 and 36, T. 10 N., R's. 10 & 11 E., G. & S.R.M., bears N. 61° 12' 51" W., 2258.89 ft. dist., previously described. A mound of stones constructed adjacent to the iron pipe. Thence S. 69° 08' 42" W.
169.56	Road, 8 ft. wide, bears N. 10° W. and S. 10° E.
401.56	Ridge, bears N. and S.
619.96	Witness cor. for Cor. No. 3 of the Royal Flush Lode and Cor. No. 3 of the Royal Flush #4 lode, previously described.
659.56	Cor. No. 3 of the Royal Flush Lode, identical with Cor. No. 3 of the Royal Flush #4 lode, both of this survey, and center of Gibson Creek, 50 ft. wide, course south.
836.56	Road, 8 ft. wide, bears N. and S.
1,411.56	Top of hill.
1,448.56	Road, 8 ft. wide, bears N. 40° W. and S. 40° E.

FEET	
1,500.00	<p>Cor. No. 2, on Line 3-4 of the Royal Flush Lode of this survey.</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. cross piece welded to its base, 20 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF5-2, 4636 from which</p> <p style="padding-left: 40px;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="padding-left: 80px;">Thence S. 20° 51' 18" E.</p>
300.00	Lode line; discovery point bears N. 69° 08' 42" E., 750 ft. dist.
505.00	Wash, 10 ft. wide, course S. 80° E.
600.00	<p>Cor. No. 3</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF5-3, 4636 from which</p> <p style="padding-left: 40px;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="padding-left: 80px;">Thence N. 69° 08' 42" E.</p>
122.00	Wash, 10 ft. wide; course S. 80° E.
475.00	Gibson Creek, 60 ft. wide, course S.
1,500.00	<p>Cor. No. 4, on line 4-1 of the Grubstake lode of this survey.</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 19 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF5-4, 4636 from which</p> <p style="padding-left: 40px;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="padding-left: 80px;">Thence N. 20° 51' 18" W.</p>
264.00	Road, 8 ft. wide, bears N. 70° E. and S. 70° W.
300.00	Lode line; discovery point bears S. 69° 08' 42" W., 750 ft. dist.
600.00	Cor. No. 1 and place of beginning.
<p><u>ROYAL FLUSH #6 LODE</u></p> <p>Beginning at Cor. No. 1 of the Royal Flush #6 lode, identical with Cor. No. 2 of the Grubstake lode, and on Line 3-4 of the Royal Flush #4 lode, both of this survey.</p>	

FEET	
	<p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. cross piece welded to its base, 18 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF6-1, G-2, 4636 from which</p> <p>The cor. of secs. 25, 30, 31, and 36, T. 10 N., R's, 10 & 11 E., G. & S.R.M., bears N. 71° 00' 44" W., 2686.63 ft. dist., previously described.</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 20° 51' 18" E.</p>
73.00	Road, 8 ft. wide, bears N. 70° W. and S. 70° E. N.
120.00	Trench, 10 ft. wide, bears 85° W. and S. 85° E.
211.00	Road, 8 ft. wide, bears N. 25° E. and S. 25° W.
300.00	Lode line; discovery point bears N. 69° 08' 42" E., 700 ft. dist.
600.00	<p>Cor. No. 2, on line 2-3 of the Grubstake lode of this survey.</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF6-2, 4636 from which</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence N. 69° 08' 42" E.</p>
242.00	Road, 10 ft. wide, bears S. 10° E. and N. 10° W.
365.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
536.00	Wash, 6 ft. wide, course S. 50° W.
550.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
766.00	Wash, 2 ft. wide, course S. 25° W.
857.00	Wash, 2 ft. wide, course N. 80° W.
965.00	Wash, 2 ft. wide, course S. 40° W.
1,500.00	<p>Cor. No. 3</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 in. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF6-3, 4636 from which</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence N. 20° 51' 18" W.</p>

FEET	
300.00	Lode line; discovery point bears S. $69^{\circ} 08' 42''$ W., 800 ft. dist.
562.00	Wash, 3 ft. wide, course S. 70° W.
600.00	Cor. No. 4, on line 3-4 of the Royal Flush #7 lode of this survey.
	Set a galvanized iron pipe $3/4$ ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF6-4, 4636 from which
	A mound of stones constructed adjacent to the iron pipe.
	Thence S. $69^{\circ} 08' 42''$ W.
127.00	Wash, 3 ft. wide, course N. 30° W.
208.00	Road, 8 ft. wide, bears S. 15° E. and N. 25° W.
262.00	Center line of Arizona Public Service transmission line, bears N. $27^{\circ} 40'$ E. and S. $27^{\circ} 40'$ W.
293.00	Wash, 4 ft. wide, course S. 5° E.
453.00	Center line of Arizona Public Service transmission line, bears N. $27^{\circ} 40'$ E. and S. $27^{\circ} 40'$ W.
1,259.56	Cor. No. 4 of the Royal Flush #4 lode, identical with Cor. No. 4 of the Royal Flush #7 lode both of this survey.
1,500.00	Cor. No. 1 and place of beginning.
	<u>ROYAL FLUSH #7 LODE</u>
	Beginning at Cor. No. 1 of the Royal Flush #7 lode, identical with Cor. No. 1 of the Royal Flush #4 lode, both of this survey, previously described.
	Thence N. $69^{\circ} 08' 42''$ E.
248.01	Cor. No. 1 of the Royal Flush #8 lode of this survey.
1,135.00	Road, 10 ft. wide, bears S. 10° W. and N. 10° E.
1,272.00	Wash, 8 ft. wide, course S. 5° E.
1,500.00	Cor. No. 2, on Line 1-2 of the Royal Flush #8 lode, of this survey.
	Set a galvanized iron pipe $3/4$ ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 21 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF7-2, 4636 from which
	The center line of Arizona Public Service transmission line passes directly overhead, bears N. $27^{\circ} 40'$ E. and S. $27^{\circ} 40'$ W.

SURVEY NO. 4636

9.

FEET	
	<p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 20° 51' 18" E.</p>
160.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
300.00	Lode line; discovery point bears S. 69° 08' 42" W., 300 ft. dist.
600.00	Cor. No. 3
	<p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF7-3, 4636 from which</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 69° 08' 42" W.</p>
240.44	Cor. No. 4 of the Royal Flush #6 lode of this survey.
367.44	Wash, 3 ft. wide, course N. 30° W.
448.44	Road, 8 ft. wide, bears S. 15° E. and N. 25° W.
502.44	Center line of Arizona Public Service transmission line, bears, N. 27° 40' E. and S. 27° 40' W.
533.44	Wash, 4 ft. wide, course S. 5° E.
693.44	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
1,500.00	Cor. No. 4, identical with Cor. No. 4 of the Royal Flush #4 lode, and on Line 4-1 of the Royal Flush #6 lode, both of this survey, previously described.
	Thence N. 20° 51' 18" W.
50.00	Wash, 4 ft. wide, course S. 70° W.
127.00	Road, 12 ft. wide, bears S. 65° W. and N. 65° E.
300.00	Lode line; discovery point bears N. 69° 08' 42" E., 1200 ft. dist.
600.00	Cor. No. 1 and place of beginning.
	<u>ROYAL FLUSH NO. 8 LODE</u>
	<p>Beginning at Cor. No. 1 of the Royal Flush #8 lode, on Line 1-2 of the Royal Flush #7 lode of this survey.</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF8-1, 4636 from which</p> <p>The cor. secs. 25, 30, 31 and 36, T.10N., R's, 10 & 11 E.G. & S.R.M., bears N. 87° 07' 46" W., 2786.78 ft. dist., previously described.</p> <p>A mound of stones constructed adjacent to the iron pipe.</p>

FEET		
	Thence N. 69° 08' 42" E.	
886.99	Road, 10 ft. wide, bears S. 10° W. and N. 10° E.	
1,023.99	Wash, 8 ft. wide, course S. 5° E.	
1,251.99	Cor. No. 2 of the Royal Flush #7 lode of this survey, and center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.	
1,342.00	Road, 10 ft. wide, bears N. 35° W. and S. 35° E.	
1,430.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.	
1,500.00	Cor. No. 2	
	Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 22 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF8-2, 4636 from which	
	A mound of stones constructed adjacent to the iron pipe.	
	Thence N. 20° 51' 18" W.	
57.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.	
217.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.	
300.00	Lode line; discovery point bears S. 69° 08' 42" W., 750 ft. dist.	
600.00	Cor. No. 3	
	Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 24 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF8-3, 4636 from which	
	A mound of stones constructed adjacent to the iron pipe.	
	Thence S. 69° 08' 42" W.	
430.00	Wash, 8 ft. wide, course S. 20° E.	
1,000.00	Top of hill.	
1,500.00	Cor. No. 4	
	Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 17 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF8-4, 4636, from which	

FEET	
	<p>A Juniper, 10 ins. diam. bears S. 14° W., 8.45 ft. dist., mkd. RF8-4-4636-BT.</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 20° 51' 18" E.</p>
300.00	Lode line; discovery point bears N. 69° 08' 42" E., 750 ft. dist.
600.00	Cor. No. 1 and place of beginning.
	<u>ROYAL FLUSH NO. 9 LODE</u>
	<p>Beginning at Cor. No. 1 of the Royal Flush No. 9 lode,</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF9-1, 4636 from which</p> <p>The cor. of secs. 25, 30, 31 and 36, T. 10N., R's. 10 & 11 E., G. & S.R.M., bears N. 10° 16' 01" E., 1,921.66 ft. dist., previously described.</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 18° 18' 16" W.</p>
177.00	Road, 10 ft. wide, bears N. 60° W. and S. 60° E.
270.00	Wash, 5 ft. wide, course N. 74° E.
300.00	Lode line; discovery point bears S. 71° 41' 44" E., 200 ft. dist.
333.60	Intersect line 3-4 of the Royal Flush No. 1 lode of this survey.
600.00	Cor. No. 2
	<p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF9-2, 4636 from which</p> <p>A mound of stones constructed adjacent to the iron pipe.</p> <p>Thence S. 71° 41' 44" E.</p>
550.00	Wash, 5 ft. wide, course S. 40° E.
1,252.00	Road, 10 ft. wide, bears S. 40° E. and N. 40° W.
1,500.00	Cor. No. 3
	<p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF9-3, 4636 from which</p> <p>A mound of stones constructed adjacent to the iron pipe.</p>

FEET	
	Thence N. 18° 18' 16" E.
300.00	Lode line; discovery point bears N. 71° 41' 44" W., 1300 ft. dist.
356.00	Top of hill.
600.00	Cor. No. 4
	Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, in small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF9-4, 4636 from which
	A mound of stones constructed adjacent to the iron pipe.
	Thence N. 71° 41' 44" W.
1,055.00	South edge of wash, 4 ft. wide, course E.
1,170.00	Wash, 4 ft. wide, course N. 85° E.
1,276.33	Intersect line 3-4 of the Royal Flush No. 1 lode of this survey.
1,304.00	Road, 10 ft. wide, bears N. 33° E. and S. 33° W.
1,402.00	Road, 10 ft. wide, bears N. 15° W. and S. 15° E.
1,500.00	Cor. No. 1 and place of beginning.
	<u>ROYAL FLUSH #11 LODGE</u>
	Beginning at Cor. No. 1 of the Royal Flush #11 lode, on line 1-2 of the Royal Flush No. 1 lode of this survey.
	Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 17 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF11-1, 4636 from which
	The cor. of secs. 25, 30, 31 and 36, T. 10N., R's. 10 & 11 E., G. & S.R.M., bears N. 16° 06' 00" E., 1476.11 ft. dist., previously described.
	A mound of stones constructed adjacent to the iron pipe.
	Thence S. 52° 08' 42" W.
207.62	Road, 10 ft. wide, bears N. 40° W. and S. 40° E.
339.77	Lode line; discovery point bears N. 65° 51' 18" W., 800 ft. dist.
427.62	Road, 10 ft. wide, bears N. 65° W. and S. 65° E.
495.62	Wash, 5 ft. wide, course S. 60° E.
679.54	Cor. No. 2, on line 1-2 of the Royal Flush No. 1 lode of this survey.

FEET	
	<p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 17 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF11-2, 4636 from which</p> <p style="text-align: center;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="text-align: center;">Thence N. 65° 51' 18" W.</p>
1,330.00	Wash, 6 ft. wide, course N. 85° E.
1,500.00	<p>Cor. No. 3</p> <p>This corner falls on the vertical face of a large boulder 5 ft. high where a monument cannot be established.</p> <p style="text-align: center;">Thence N. 52° 08' 42" E.</p>
5.31	<p>Witness corner for Cor. No. 3</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. WC-RF11-3, 4636 from which</p> <p style="text-align: center;">A mound of stones constructed adjacent to the iron pipe.</p>
104.00	Wash, 2 ft. wide, course S. 50° E.
339.77	Lode line; discovery point bears S. 65° 51' 18" E., 700 ft. dist.
366.00	Ridge, bears S. 85° E. and N. 85° W.
496.00	Road, 8 ft. wide, bears S. 60° E. and N. 60° W.
651.00	Road, 10 ft. wide, bears S. 40° E. and N. 40° W.
679.54	<p>Cor. No. 4</p> <p>Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 19 ins. in the ground in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. RF11-4, 4636 from which</p> <p style="text-align: center;">A mound of stones constructed adjacent to the iron pipe.</p> <p style="text-align: center;">Thence S. 65° 51' 18" E.</p>
391.00	Road, 10 ft. wide, bears S. 85° E. and N. 85° W.
717.00	Ridge, bears S. 85° E. and N. 85° W.
974.00	Road, 10 ft. wide, bears N. 65° E., and S. 65° W.
994.00	Road, 8 ft. wide, bears N. 45° E. and S. 45° W.
1,054.00	Wash, 3 ft. wide, course S. 5° E.
1,138.00	Road, 10 ft. wide, bears N. 35° W. and S. 35° E.
1,500.00	Cor. No. 1 and place of beginning.

FEET	<u>GRUBSTAKE LODE</u>
	Beginning at Cor. No. 1 of the Grubstake lode, identical with Cor. No. 1 of the Royal Flush No. 5 lode, and on Line 3-4 of the Royal Flush #4 lode, both of this survey, previously described.
	Thence N. 69° 08' 42" E.
211.44	Wash, 9 ft. wide, course S. 20° E.
281.44	Small ridge, bears N. 20° W. and S. 20° E.
300.00	Lode line; discovery point bears S. 20° 51' 18" E., 750 ft. dist.
346.44	Wash, 5 ft. wide, course S. 20° E.
528.44	Road, 10 ft. wide, bears N. 25° W. and S. 20° E.
540.44	Wash, 3 ft. wide, course S. 50° W.
600.00	Cor. No. 2, identical with Cor. No. 1 of the Royal Flush #6 lode, and on line 3-4 of the Royal Flush #4 lode, both of this survey, previously described.
	Thence S. 20° 51' 18" E.
73.00	Road, 8 ft. wide, bears N. 70° W. and S. 70° E.
120.00	Trench, 10 ft. wide, bears N. 85° W. and S. 85° E.
211.00	Road, 8 ft. wide, bears N. 25° E. and S. 25° E.
600.00	Cor. No. 2 of the Royal Flush #6 lode of this survey.
926.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
1,021.00	Road, 8 ft. wide, bears S. 20° W. and N. 20° E.
1,083.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
1,175.00	Wash, 5 ft. wide, course S. 40° W.
1,500.00	Cor. No. 3
	Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 18 ins. in the ground, in a small mound of stones, with a brass pipe, 3 ins. diam., firmly secured to the iron pipe, mkd. G-3, 4636 from which
	A Juniper, 9 ins. diam., bears N. 83° 52' E., 21.5 ft. dist., mkd. X-G-3-4636-BT.
	A mound of stones constructed adjacent to the iron pipe.
	Thence S. 69° 08' 42" W.
191.00	Wash, 6 ft. wide, course S. 15° E.

SURVEY NO. 4636

FEET	
274.00	Road, 10 ft. wide, bears S. 45° W. and N. 45° E.
300.00	Lode line; discovery point bears N. 20° 51' 18" W., 750 ft. dist.
384.00	Road, 8 ft. side, bears S. 35° W. and N. 35° E.
476.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
600.00	Cor. No. 4 Set a galvanized iron pipe 3/4 ins. diam., 30 ins. long, with a 6 in. metal cross piece welded to its base, 20 ins. in the ground, in a small mound of stones, with a brass cap, 3 ins. diam., firmly secured to the iron pipe, mkd. G-4, 4636 from which A mound of stones constructed adjacent to the iron pipe. Thence N. 20° 51' 18" W.
54.00	Center line of Arizona Public Service transmission line, bears N. 27° 40' E. and S. 27° 40' W.
262.00	Top of hill.
834.00	Wash, 12 ft. wide, course S. 65° W.
900.00	Cor. No. 4 of the Royal Flush No. 5 lode of this survey.
1,164.00	Road, 8 ft. wide, bears S. 70° W. and N. 70° E.
1,500.00	Cor. No. 1 and place of beginning.

AREAS

	Acres
Total area, Royal Flush lode	20.661
Total area, Royal Flush No. 1 lode	20.661
Area in conflict with -	
Royal Flush No. 9 lode	0.856
Total area, Royal Flush #4 lode	20.661
Total area, Royal flush No. 5 lode	20.661
Total area, Royal Flush #6 lode	20.661
Total area, Royal Flush #7 lode	20.661
Total area, Royal Flush #8 lode	20.661
Total area, Royal Flush No. 9 lode	20.661
Area in conflict with -	
Royal Flush No. 1 lode	0.856
Total area, Royal Flush #11 lode	20.661
Total area, Grubstake lode	20.661

LOCATION

This survey is located in the NE 1/4 and SE 1/4 sec. 36 of T. 10 N., R. 10 E., and in sec. 31 and the SE 1/4 and SW 1/4 of sec. 30 of T. 10 N., R. 11 E., Gila and Salt River Base and Meridian, Arizona, the major portion of which lies in sec. 31.

The survey of the Royal Flush Group of lode claims are identical with the respective locations or admended locations as marked on the ground.

FEET	EXPENDITURES
	<p>The improvements and the value of the labor and improvements make upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows:</p>
No. 1	<p>The discovery point of the Royal Flush lode is on the lode line 800 ft. from the center of line 2-3. No. value</p>
No. 2	<p>A shaft, the center of which bears N. 86° 02' W., 736 ft. from cor. No. 3 Royal Flush lode; 5x5 ft., inclined 20° from the vertical, bears N. 65° W., 72 ft. deep, thence a drift 4x4 ft. bears S. 25° W. 11 ft. Improvements to shaft: top 8 ft. timbered, steel headframe, steel ladder full depth of shaft, 3 hp hoist complete with bucket and cable, compressor and drilling equipment with water and air hoses to bottom of shaft, blower and air line to bottom shaft. Various pits located around shaft. Value of complete improvement, \$3,200.</p>
No. 3	<p>Pit, the center of which bears S. 78° 45' W., 865 ft. from cor. No. 3 of the Royal Flush lode; 6x8 ft., 6.5 ft. deep. Value, \$75</p>
No. 4	<p>Drill hole, bears S. 78° 10' W., 868 ft. from cor. No. 3 of the Royal Flush lode; 2 in. diam., 42 ft. deep. Value, \$100</p>
No. 5	<p>Shaft, the center of which bears N. 73° 34' W., 515 ft. from cor. No. 3 of the Royal Flush lode; partially caved, 10x10 ft., 25 ft. deep, inclined 30° from the vertical in a Westerly direction. Value, \$700</p>
No. 1	<p>The discovery point of the Royal Flush No. 1 lode is on the lode line 350 ft. from the center of line 4-1. Value, None</p>
No. 2	<p>Trench, the west end of which bears S. 13° 09' W., 648 ft. from cor. No. 1 of the Royal Flush No. 1 lode; 8 ft. wide by 15 ft. long, average 5 ft. deep, running N. 68° E. Value, \$100</p>
No. 3	<p>Tunnel, the west end of which bears S. 14° 34' W., 722 ft. from cor. No. 1 of the Royal Flush No. 1 lode; partially caved, 5x4 ft., long, running S. 76° E. Value, \$500 43 ft.</p>
No. 1	<p>The discovery point of the Royal Flush #4 lode is on the lode line 750 ft. from the center of line 4-1. Value, None</p>
No. 2	<p>Trench, the west end of which bears S. 83° 50' W., 1047 ft. from cor. No. 4 of the Royal Flush #4 lode; 10 ft. wide by 85 ft. long, average 2 ft. deep, running N. 43° E. Value, \$75</p>

SURVEY NO. 4636

17.

FEET		
No. 3	Trench, the east end of which bears S. 82° 00' W., 1085 ft. from cor. No. 4 of the Royal Flush #4 lode; 10 ft. wide by 80 ft. long, average 1 ft. deep, running S. 57° W. Value, \$60	
No. 4	Trench, the south end of which bears N. 68° 56' W., 593 ft. from cor. No. 4 of the Royal Flush #4 lode; 12 ft. wide by 30 ft. long, average 2 ft. deep, running N. 24° W. Value, \$50	
No. 1	The discovery point of the Royal Flush No. 5 lode is on the lode line 750 ft. from the center of line 4-1. Value, None	
No. 2	Pit, the center of which bears S. 41° 14' W., 552 ft. from cor. No. 1 of the Royal Flush No. 5 lode; 7x7 ft., 4 ft. deep. Value, \$50	
No. 3	Pit, the center of which bears S. 31° 22' W., 532 ft. from cor. No. 1 of the Royal Flush No. 5 lode; 8x8 ft., 8.5 ft. deep. Value, \$75	
No. 1	The discovery point of the Royal Flush #6 lode is on the lode line 700 ft. from the center of line 1-2. Value, None	
No. 2	Trench, the west end of which bears S. 71° 44' E., 419 ft. from cor. No. 1 of the Royal Flush #6 lode; 10 ft. wide by 60 ft. long, average 3 ft. deep, running S. 87° E. Value, \$75	
No. 1	The discovery point of the Royal Flush #7 lode is on the lode line 300 ft. from the center of line 2-3. Value, None	
No. 2	Trench, the south end of which bears S. 69° 09' W., 367 ft. from the cor. No. 3 of the Royal Flush #7 lode; 15 ft. wide by 51 ft. long, average 2.5 ft. deep, running N. 50° W. Value, \$100	
No. 1	The discovery point of the Royal Flush #8 lode is in the lode line 750 ft. from the center of line 2-3. Value, None	
No. 2	Shaft, the center of which bears N. 45° 49' E., 1120 ft. from cor. No. 1 of the Royal Flush #8 lode; 6x4 ft. 45 ft. deep, partially timbered, inclined 15° from the vertical in a westerly direction. Value, \$900	
No. 1	The discovery point of the Royal Flush No. 9 lode is on the lode line 200 ft. from the center of line 1-2. Value, None	

FEET	
No. 2	<p>Shaft, the center of which bears S. 52° 12' E., 278 ft. from cor. No. 1 of the Royal Flush No. 9 lode; 5x5 ft. 25 ft. deep, the top 6 ft. of which is timbered, the bottom of this shaft branches into two inclined shafts; the first -- 8x8 ft., 33 ft. long, inclined 35° from the vertical, running N. 47° E., the second -- 7x5 ft., 35 ft. long, inclined 40° from the vertical running N. 18° W. Also part of this improvement is a trench which bears from the above described shaft S. 47° W., 30 ft., 6 ft. wide by 5 ft. deep; and N. 47° E., 21 ft., thence N. 7° E., 14 ft., thence N. 77° E., 23 ft., thence N. 10° W., 32 ft., thence S. 60° W., 7 ft. to center of pit 7x7 ft. by 5 ft. deep. The trench averages 6 ft. wide by 5 ft. deep.</p> <p>Value of shaft and trench, \$2,300</p>
No. 3	<p>Drill hole, bears S. 56° 28' E., 198 ft. from cor. No. 1 of the Royal Flush No. 9 lode; 2 ins. diam., 110 ft. deep.</p> <p>Value, \$275</p>
No. 1	<p>The discovery point of the Royal Flush #11 lode is on the lode line 800 ft. from the center of line 1-2.</p> <p>Value, None</p>
No. 2	<p>Trench, the north end of which bears N. 74° 18' W., 1350 ft. from cor. No. 1 of the Royal Flush #11 lode; 16 ft. wide by 35 ft. long, average 2 ft. deep, running S. 5° E.</p> <p>Value, \$50</p>
No. 3	<p>Trench, the west end of which bears N. 78° 49' W., 1337 ft. from cor. No. 1 of the Royal Flush #11 lode; 10 ft. wide by 17 ft. long, average 3 ft. deep, running S. 64° E.</p> <p>Value, \$50</p>
No. 4	<p>Trench, the east end of which bears S. 76° 59' W., 656 ft. from cor. No. 1 of the Royal Flush #11 lode; 10 ft. wide by 50 ft. long, average 5 ft. deep, running S. 66° W.</p> <p>Value, \$100</p>
No. 1	<p>The discovery point of the Grubstake lode is on the lode line 750 ft. from the center of line 1-2.</p> <p>Value, None</p>
No. 2	<p>Trench, the center of which bears S. 1° 28' E., 208 ft. from cor. No. 2 of the Grubstake lode; 10 ft. wide by 79 ft. long, average 3 ft. deep, running N. 80° W. and S. 80° E.</p> <p>Value, \$100</p>
No. 3	<p>Trench, the center of which bears S. 5° 25' E., 153 ft. from cor. No. 2 of the Grubstake lode; 10 ft. wide by 85 ft. long, average 1 ft. deep, running N. 80° W. and S. 80° E.</p> <p>Value, \$50</p>
No. 4	<p>Trench, the center of which bears S. 5° 20' E., 109 ft. from cor. No. 2 of the Grubstake lode; 10 ft. wide by 100 ft. long, average 1 ft. deep, running N. 85° W. and S. 85° E.</p>

FEET	Value, \$60
No. 5	<p>Trench, the center of which bears S. 15° 13' W., 172 ft. from cor. No. 2 of the Grubstake lode; 10 ft. wide by 42 ft. long, average 3 ft. deep, running S. 25° W. and N. 25° E. Value, \$60</p>
No. 6	<p>Trench, the center of which bears S. 7° 52' E., 607 ft. from cor. No. 2 of the Grubstake lode; 12 ft. wide, 41 ft. long, average 2.5 ft. deep, running N. 47° E. and S. 47° W. Value, \$50</p>
No. 7	<p>Pit, the center of which bears S. 14° 28' E., 1107 ft. from the cor. no. 2 of the Grubstake lode; 13x13 ft. 4 ft. deep. Value, \$100</p> <p>An interest in a common improvement described as follows:</p> <p>A tunnel 5x6 ft. in size, the portal of which bears N. 72° 57' W., 566 ft. from cor. No. 3 of the Royal Flush lode; running S. 67° W., 86 ft. to pt. A; thence S. 52° W., 50 ft.; thence S. 37° W., 37 ft., thence S. 52° W., 80 ft.; thence S. 87° W., 100 ft., thence S. 77° W., 30 ft.; thence westerly, 31 ft. to breast. At pt. A a drift 5x6 ft. in size runs S. 13° E., 50 ft. to breast. 200 ft. of track are in place at the end of the tunnel. Value of tunnel, drift and track, \$5500 Value of one-tenth interest, \$550</p> <p>The general strike of the major veins in this area is north-easterly and south-westerly with numerous secondary veins running perpendicular to the main veins. The location of the 10 lode claims of this survey take advantage of this fact as do the locations of the improvements. Therefore this improvement is for the development of the 10 lode claims of this survey and a discovery would be to the benefit of all the lodes.</p> <p>The surface rises rapidly on each side of Gibson Creek and a tunnel affords a practical and economical means of developing the lodes at depth.</p> <p>An interest in a common improvement described as follows:</p> <p>Access roads amounting to 10,000 ft. in length have been constructed for the purpose of providing access to and for removal of ore and rock from the various improvements of this survey. The roads pass thru the various lodes to their improvements and therefore it is not practical to assign the value of each road to specific lodes as they may benefit several or all the other lodes. Therefore an undivided one-tenth interest of the value of all roads constructed to improvements is hereby credited to each of said lodes.</p> <p>Value of all roads, \$2,000 Value of one-tenth interest, \$200</p> <p>Five hundred dollars or over has been expended on these improvements in such a manner as tends to the development of each lode of this survey subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore an undivided one-tenth interest in its value is hereby credited to each of said lodes.</p>

<p>FEET</p>	<p>No portion of or interest in these improvements has been credited heretofore as patent expenditure to any lode claim.</p> <p style="text-align: center;">OTHER IMPROVEMENTS</p> <p>Four Arizona Public Service steel transmission towers located as follows:</p> <p>No. 1 bears N. 85° 20' W., 472 ft. from cor. No. 3 of the Grubstake lode.</p> <p>No. 2 bears N. 31° 20' W., 362 ft. from cor. No. 3 of the Grubstake lode.</p> <p>No. 3 bears S. 52° 10' W., 728 ft. from cor. No. 4 of the Royal Flush #6 lode.</p> <p>No. 4 bears S. 44° 10' W., 620 ft. from cor. No. 4 of the Royal Flush #6 lode.</p>									
	<p style="text-align: center;">FIELD ASSISTANTS</p> <table border="0"> <tr> <td>Ray Gavette</td> <td>Instrumentman</td> </tr> <tr> <td>Al Clough</td> <td>Instrumentman</td> </tr> <tr> <td>Jim Brittenham</td> <td>Chainman</td> </tr> <tr> <td>Bill Troutman</td> <td>Chainman</td> </tr> </table>	Ray Gavette	Instrumentman	Al Clough	Instrumentman	Jim Brittenham	Chainman	Bill Troutman	Chainman	
Ray Gavette	Instrumentman									
Al Clough	Instrumentman									
Jim Brittenham	Chainman									
Bill Troutman	Chainman									

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

22


CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor	Date
Robert E. Adams	May 11, 1966

I HEREBY CERTIFY That in pursuance of an order received from the Bureau of Land Management, at Phoenix, Arizona, dated Nov. 22, 1965; amended 2/24/66, 19 & I have carefully executed the survey of the claim of R. W. and Philip R. Hull (5/3/66), known as the (lode, placer, or mill site) Royal Flush Group, situated in Sec. 36, 30, & 31 Township 10 N., Range 10 E., G. & S.R. Meridian, in the State of Arizona 11 E.

This survey, designated as number 4636, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in the specific manner described in the foregoing field notes.


I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) Lode location(s) embraced in the said mining claim by claimant(s) or His grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Phoenix, Arizona (Location)	 (Signature of Mineral Surveyor)
--------------------------------	---

CERTIFICATE OF APPROVAL

Office Arizona State Office Bureau of Land Management
Location Phoenix, Arizona
Date June 13, 1966

The foregoing field notes of mineral survey number 4636, in Section 36, Township 10 North, Range 10 East, and Sections 30 and 31, surveyed unsurveyed, Township 10 N., Range 11 E., Gila and Salt River Meridian, in the State of Arizona, executed by Robert E. Adams, Mineral Surveyor, under order dated November 22, 1965, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

 Fred J. Weller (Authorized Signature)	State Director (Title)
---	---------------------------

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of field notes of the above described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U. S. C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
STATEMENT OF WORK

1. Project Title: [Illegible]

2. Project Description: [Illegible]

3. Objectives: [Illegible]

4. Deliverables: [Illegible]

5. Timeline: [Illegible]

6. Budget: [Illegible]

7. Risks: [Illegible]

8. Stakeholders: [Illegible]

9. Conclusion: [Illegible]

[Illegible signature]

[Illegible text]

10. Appendix: [Illegible]

11. References: [Illegible]

12. Notes: [Illegible]

[Illegible signature]

CERTIFICATE OF WORK

13. Project Completion: [Illegible]

14. Final Report: [Illegible]

15. Final Review: [Illegible]

16. Final Approval: [Illegible]

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S. 4636
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The Royal Flush, Royal Flush No.1, Royal Flush #4, Royal Flush No.5, Royal Flush #6, Royal Flush #7, Royal Flush #8, Royal Flush No.9, Royal Flush #11 and Grubstake lodes, Mineral Survey No. 4636, located in sections 36, 30 and 31, Township 10 North, Ranges 10 and 11 East, Gila and Salt River Meridian, Arizona, are hereby canceled.

These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"Royal Flush, Royal Flush No.1, Royal Flush #4, Royal Flush No.5, Royal Flush #6, Royal Flush #7, Royal Flush #8, Royal Flush No.9, Royal Flush #11 and Grubstake lodes, M.S. No. 4636, were canceled July 11, 2011, by memo 9605 (956) M.S. 4636, which is now a part of the original field notes."

July 11, 2011
Date

Daniel L. Mayby
Acting Chief Cadastral Surveyor of Arizona

