

Form 4-683
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey number	4658
State	Arizona
Land District	Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*
Steven C. Chilson, Daniel G. Chilson, Jr., Richard E. Chilson, Marian C. Chilson, Donna Gail Chilson, Laurita Yarter, Robert C. & Rebecca Fordham, c/o Evans, Kitchel & Jenckes, Attorneys at Law, 363 North 1st Avenue, Phoenix, Arizona 85003

Known as the, *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
ARIZONA NO. 33	11/5/55	3/4/66
ARIZONA NO. 34	11/5/55	3/4/66
ARIZONA NO. 35	11/5/55	3/4/66
ARIZONA NO. 36	11/5/55	3/4/66
ARIZONA NO. 37	11/5/55	3/4/66
ARIZONA NO. 38	11/5/55	3/4/66
ARIZONA NO. 39	11/5/55	3/4/66
ARIZONA NO. 40	11/5/55	3/4/66
ARIZONA NO. 41	11/5/55	3/4/66
ARIZONA NO. 42	11/5/55	3/4/66
ARIZONA NO. 43	11/5/55	3/4/66
MIDLAND NO. 18	2/3/56	3/4/66
MIDLAND NO. 19	2/3/56	3/4/66
MIDLAND NO. 20	2/3/56	3/4/66
MIDLAND NO. 21	2/3/56	3/4/66
MIDLAND NO. 22	2/3/56	3/4/66
MIDLAND NO. 23	2/3/56	3/4/66
PIMA #1	1/21/63	3/4/66
PIMA #2	1/21/63	3/4/66
CWT NO. 1	3/11/65	3/4/66

Mining district			PIMA		County	PIMA	
Section	Township	Range	Meridian	Survey under order dated			
23, 24 & 25	17 South	12 East	Gila & Salt River	1/24/67			
Survey commenced		Survey completed		Name of Mineral Surveyor			
Feb. 10, 1967		Feb. 20, 1967		Robert L. Frazer			

1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100

FEET

This survey was made concurrently with Surveys Nos. 4648, 4657, and 4656.

A control traverse, including all four corners of Section 23, T 17 S, R 12 E, G&SRB&M, was made by use of Electronic Distance-measuring Equipment. Angular error was $0^{\circ} 00' 01''$; Latitude error $-0.230'$. Departure $-0.007'$; Ratio of closure $1':107,152'$.

The attached sketch shows the entire traverse in its relationship to Section 23, and to surveys 4648, 4656, 4657, and 4658. Traverse points controlling survey No. 4658 are shown on the survey map.

This survey was made with the following equipment:

Wilde T-2 Theodolites, Nos. 55949 and 92997.

Cubic Electrotape Units 205 and 206.

Lufkin 200 Ft. Steel Tape.

All equipment was in good condition and adjustment.

Angular values are the mean of angles in direct and inverse attitude from distant foresight.

Electrotape measurements are reciprocal, and values are the mean of measurement by both units. Taped traverses were checked at the ends by measured angle to a visible control point.

Position of final corners of this survey was checked in field by comparison of a field angle turned at the corner between two control points, with the difference in calculated bearing from these control points to the corner.

Due to the concurrency and contiguity of the above-noted surveys, and precision of the control traverse, determination of meridian was made only at the corner common to Sections 23, 24, 25, 26, T 17 S, R 12 E, G&SRB&M, as follows:

On February 17, 1967, and February 20, 1967, at Lat. $31^{\circ} - 55.5' N$, Long. $111^{\circ} - 04.8' W$, (from U.S.G.S. Quadrangle Map "Twin Buttes"), at the corner common to Sections 23, 24, 25, 26, T 17 S, R 12 E, G&SRB&M, I observed Polaris at the hours noted below. Angles were turned clock-wise from traverse pt. No. 4, a $5/8$ in. reinforcing rod which bears North-westerly a distance of 1068.64 ft. from the above-recited section corner. Computation of local hour angle and bearing of Polaris by "Procedure B" in Keuffel & Esser Ephemeris for 1967.

FEET

DATE:

Feb. 17, 1967

TIME: (AVE)

8^h: 41^m: 48^s P.M., MST

Horiz. Angle (Ave)-Pt. No. 4 to Star

33°-23'37"

Calc. Bearing of
Polaris

+

0°-54'-46"BEARING - Sec. Cor.
to Pt. No. 4

N34°-18'-23"W

DATE:

Feb. 20, 1967

TIME: (AVE)

8^h: 58^m: 51^s P.M., MST.

Horiz. Angle (Ave)-Pt. No. 4 to Star

33°-20'-26"

Calc. Bearing of
Polaris

+

0°-58'-06"

BEARING - Sec. Cor. to Pt. No. 4 -N34°-18'-32"W

AVERAGE BEARING, SEC. COR. TO TRAV. PT. NO. 4
N34° 18' 28"W

The above average bearing was used as basis of bearing for this survey, as well as Surveys Nos. 4648, 4657, 4656.

An aerial photograph, with control points paneled in field to show thereon, was enlarged to scale of 1" = 200'. Road and drainage intersections were scaled from photograph. Approximate bearings protracted.

MEAN MAGNETIC DECLINATION IS 14° 30' E.

FEET	
	MIDLAND NO. 18 LODGE
	At Cor. No. 1 of the MIDLAND NO. 18 lode.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 18-1-4658; from which
	The cor. of secs. 23, 24, 25 and 26, T.17S., R.12E., G&SR.B&M. bears S. 89° 47' 36" W., 488.45 ft. dist. Monumented with a 2 in. diam. post, projecting 10 ins. above ground. Topped with a brass cap. Firmly set at a fence corner and marked as described in official 1941 Record by Raymond F. Moss.
	Thence S. 89° 47' 36" W.
300.00	Lode line; discovery point bears N. 3° 43' 28" E., 100 ft. dist.
488.45	The cor. of secs. 23, 24, 25, 26, T.17S., R.12E., previously described.
600.00	Cor. No. 2, identical with Cor. No. 1 of the MIDLAND NO. 19 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 18-2-MD 19-1-4658.
	Thence N. 3° 43' 28" E.
25	Road bears East and West.
560	Arroyo drains S. 60° E.
1274.19	Intersect line 1-2 PIMA #2 lode of this survey.
1441.21	Intersect the line between secs. 23 and 24 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 0° 42' 52" E., 1437.88 ft. dist.
1500.00	Cor. No. 3 identical with Cor. No. 4 of the MIDLAND NO. 19 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD-18-3-MD 19-4-4658.
	Thence N. 89° 47' 36" E.
50	Swale 50 ft. wide drains S. 80° E.
300.00	Lode line, discovery point bears S. 3° 43' 28" W., 1400 ft. dist.
350	Swale 50 ft. wide drains N. 45° E.
600.00	Cor. No. 4.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD-18-4-4658, from which

FEET	
	Cor. No. 1 of the PIMA #2 lode of this survey bears S. 23° 43' 50" E., 285.78 ft. dist.
	Thence S. 3° 43' 28" W.
256.00	Intersect. line 1-2 PIMA #2 lode of this survey.
950	Arroyo 30 ft. wide drains East.
1450	Road bears East and West.
1498.57	Intersect line between secs. 24 and 25 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 89° 37' 32" W., 488.55 ft. dist.
1500.00	Cor. No. 1, and place of beginning.
MIDLAND NO. 19 LODE	
	Beginning at Cor. No. 1 of the MIDLAND NO. 19 lode, identical with Cor. No. 2 of the MIDLAND NO. 18 lode of this survey; from which
	The cor. of secs. 23, 24, 25, 26, bears N. 89° 47' 36" E., 111.55 ft. dist., previously described.
	Thence S. 89° 47' 36" W.
300.00	Lode line, discovery point bears N. 3° 43' 28" E., 100 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 1 of the MIDLAND NO. 20 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. MD 19-2-MD 20-1-4658.
	Thence N. 3° 43' 28" E.
20.00	Road bears East and West.
520	Arroyo, 30 ft. wide drains East.
910	Power line bears N. 77° E., S. 77° W.
1060	Fence bears N. 77° E., S. 77° W.
1304.37	Intersect line 1-2, PIMA #2 lode of this survey.
1430	Swale 100 ft. wide drains N. 50° E.
1500.00	Cor. No. 3, identical with Cor. No. 4 of the MIDLAND NO. 20 lode of this survey.

FEET	
	Set 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 19-3-MD 20-4-4658. Thence N. 89° 47' 36" E.
75	Swale 100 ft. wide, drains N. 60° E.
178	Fence bears N. 0° 10' E., S. 0° 10' W.
250	Power line bears N. 1° W., S. 1° E.
300.00	Lode line, discovery point bears S. 3° 43' 28" W., 1400 ft. dist.
595.45	Intersect the line between secs. 23 and 24 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 0° 42' 52" E., 1496.53 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 3 of the MIDLAND NO. 18 lode of this survey. Thence S. 3° 43' 28" W.
58.79	Intersect the line between secs. 23 and 24 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 0° 42' 52" E., 1437.88 ft. dist.
225.81	Intersect line 1-2 PIMA #2 lode of this survey.
940	Arroyo, 30 ft. wide drains S. 60° E.
1475	Road bears East and West.
1500.00	Cor. No. 1, and place of beginning.
MIDLAND NO. 20 LODE	
	Beginning at Cor. No. 1 of the MIDLAND NO. 20 lode, identical with Cor. No. 2 of the MIDLAND NO. 19 lode of this survey; from which. The cor. of secs. 23, 24, 25, 26 bears N. 89° 47' 36" E., 711.55 ft. dist., previously described. Thence S. 89° 47' 36" W.
300.00	Lode line, discovery point bears N. 3° 43' 28" E., 100 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 1 of the MIDLAND NO. 21 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 20-2-MD 21-1-4658. Thence N. 3° 43' 28" E.
20	Road bears East and West.
455	Arroyo, 25 ft. wide drains S. 50° E.

FEET	
780	Power line bears N. 77° E., S. 77° W.
930	Fence bears N. 77° E., S. 77° W.
985	Arroyo, 25 ft. wide drains East.
1075	Arroyo, 30 ft. wide drains N. 50° E.
1240	Toe of tailings pond dike.
1280	Center top of tailings pond dike bears N. 72° E., S. 72° W.
1334.56	Intersect line 1-2 PIMA #1 lode of this survey.
1350	Toe of tailings pond dike.
1500.00	Cor. No. 3, identical with Cor. No. 4 of the MIDLAND NO. 21 lode of this survey.
	Set a 5/8 in. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 20-3-MD 21-4-4658.
	Thence N. 89° 47' 36" E.
300.00	Lode line, discovery point bears S. 3° 43' 28" W., 1400 ft. dist.
390	Toe of tailings pond dike.
425.35	Intersect common line 4-1 PIMA #1 lode and 2-3 PIMA #2 lode, of this survey.
460	Center top of tailings pond dike bears N. 8° W., S. 8° E.
500	Toe of tailings pond dike.
600.00	Cor. No. 4, identical with Cor. No. 3 of the MIDLAND NO. 19 lode of this survey,
	Thence S. 3° 43' 28" W.
70.	Drainage swale, 100 ft. wide drains N. 50° E.
195.63	Intersect line 1-2 PIMA #2 lode of this survey.
440	Fence bears N. 77° E., S. 77° W.
590	Power line bears N. 77° E., S. 77° W.
980	Arroyo, 30 ft. wide drains East.
1480	Road bears East and West.
1500.00	Cor. No. 1, and place of beginning.

FEET	
	MIDLAND NO. 21 LODE
	Beginning at Cor. No. 1 of the MIDLAND NO. 21 lode, identical with Cor. No. 2 of the MIDLAND NO. 20 lode of this survey; from which
	The cor. of secs. 23, 24, 25, 26 bears N. 89° 47' 36" E., 1311.55 ft. dist., previously described.
	Thence S. 89° 47' 36" W.
300.00	Lode line, discovery point bears N. 3° 43' 28" E., 100 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 1 of the MIDLAND NO. 22 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 21-2-MD 22-1-4658.
	Thence N. 3° 43' 28" E.
35	Road bears East and West.
320	Arroyo, 25 ft. wide drains N. 80° E.
645	Power line bears N. 77° E., S. 77° W.
690	Arroyo, 20 ft. wide drains N. 45° E.
790	Fence bears N. 77° E., S. 77° W.
1050	Arroyo, 50 ft. wide drains East.
1364.75	Intersect line 1-2 PIMA #1 lode of this survey.
1500.00	Cor. No. 3, identical with Cor. No. 4 of the MIDLAND NO. 22 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 21-3-MD 22-4-4658.
	Thence N. 89° 47' 36" E.
300.00	Lode line, discovery point bears S. 3° 43' 28" W., 1400 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 3 of the MIDLAND NO. 20 lode of this survey.
	Thence S. 3° 43' 28" W.
150	Toe of tailings pond dike.
165.44	Intersect line 1-2 PIMA #1 lode of this survey.
220	Center top of tailings pond dike bears N. 72° E., S. 72° W.
260	Toe of tailings pond dike.
425	Arroyo, 50 ft. wide drains N. 50° E.

FEET	
515	Arroyo, 20 ft. wide drains East.
570	Fence bears N. 77° E., S. 77° W.
720	Power line bears N. 77° E., S. 77° W.
1045	Arroyo, 25 ft. wide drains S. 50° E.
1480	Road bears East and West.
1500.00	Cor. No. 1, and place of beginning.
MIDLAND NO. 22 LODE	
Beginning at Cor. No. 1 of the MIDLAND No. 22 lode, identical with Cor. No. 2 of the MIDLAND NO. 21 lode of this survey; from which	
The cor. of secs. 23, 24, 25, 26, bears N. 89° 47' 36" E., 1911.55 ft. dist., previously described.	
Thence S. 89° 47' 36" W.	
On the common line of secs. 23, 26.	
300.00	Lode line, discovery point bears N. 3° 43' 28" E., 100 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 1 of the MIDLAND NO. 23 lode of this survey.
Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 22-2-MD 23-1-4658.	
Thence N. 3° 43' 28" E.	
40	Road bears from West to S. 80° E.
370	Arroyo, 25 ft. wide drains East.
510	Power line bears N. 77° E., S. 77° W.
655	Fence bears N. 77° E., S. 77° W.
1010	Arroyo, 50 ft. wide drains East.
1094.19	Intersect line 3-4 CWT NO. 1. lode of this survey.
1247.11	Intersect the Southerly side of an "L"-shaped sheet steel mill building at a point from which the Southerly cor. bears S. 53° 31' 40" E., 6.64 ft. dist. The Westerly building cor. bears N. 53° 31' 40" W., 95.26 ft. dist.

FEET	
1329.75	Intersect the Northerly side of the aforesaid mill building at a point from which the interior angle of the "L" bears S. 36° 28' 20" W., 6.91 ft. dist. The adjacent cor. of the building bears N. 36° 28' 20" E., 42.43 ft. dist.
1500.00	Cor. No. 3, identical with Cor. No. 4 of the MIDLAND NO. 23 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MD 22-3-MD 23-4-4658; from which Cor. No. 2, PIMA #1 lode of this survey bears S. 47° 00' 16" E., 162.34 ft. dist. Cor. No. 3, CWT NO. 1 lode of this survey bears N. 86° 32' 05" E., 394.37 ft. dist. Thence N. 89° 47' 36" E.
123.79	Intersect line 2-3 PIMA #1 lode of this survey.
300.00	Lode line, discovery point bears S. 3° 43' 28" W., 1400 ft. dist.
371.61	Intersect line 3-4 CWT NO. 1 lode of this survey.
600.00	Cor. No. 4, identical with Cor. No. 3 of the MIDLAND NO. 21 lode of this survey. Thence S. 3° 43' 28" W.
135.25	Intersect line 1-2 PIMA #1 lode of this survey.
450	Arroyo, 50 ft. wide drains East.
710	Fence bears N. 77° E., S. 77° W.
810	Arroyo, 20 ft. wide drains N. 45° E.
855	Power line bears N. 77° E., S. 77° W.
1180	Arroyo, 25 ft. wide drains N. 80° E.
1465	Road bears East and West.
1500.00	Cor. No. 1, and place of beginning.
MIDLAND NO. 23 LODE	
Beginning at Cor. No. 1 of the MIDLAND NO. 23 lode, identical with Cor. No. 2 of the MIDLAND NO. 22 lode of this survey; from which	
The cor. of secs. 23, 24, 25, 26, bears N. 89° 47' 36" E., 2511.55 ft. dist., previously described.	

FEET	
	Thence S. 89° 47' 36" W.
	On the common line of secs. 23, 26.
300.00	Lode line, discovery point bears N. 3° 43' 28" E., 100 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 1, Sur. No. 4656, ELLA #1 lode. A 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MID 23-2-4658-EL1-1-4656; from which Cor. No. 4, CWT NO. 1 lode of this survey bears N. 5° 24' 51" E., 454.77 ft. dist. Thence N. 3° 43' 28" E.
230	Road bears N. 70° W., S. 70° E.
330	Arroyo, 10 ft. wide drains from S. 60° W., to S. 45° E.
466.13	Intersect line 4-1 CWT NO. 1 lode of this survey.
523	Fence bears N. 77° E., S. 77° W.
790	Arroyo, 50 ft. wide drains N. 80° E.
1101	Power line bears N. 82° E., S. 82° W.
1358.84	Intersect common line 1-2 CWT NO. 1 lode of this survey and line 4-1 sur. 4648 NEVADA NO. 8 lode at a point from which Cor. No. 1 NEVADA NO. 8 lode, identical with Cor. No. 1 CWT NO. 1 lode bears S. 44° 22' 55" W., 676.07 ft. dist.
1500.00	Cor. No. 3, identical with Cor. No. 4, Sur. 4656, ELLA #1 lode. A 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. MID 23-3-4658 - EL1-4-4656; from which Cor. No. 1 Sur. 4648 NEVADA NO. 8 lode bears S. 37° 41' 03" W., 788.54 ft. dist. The Southwesterly corner of a steel building, 28 ft. x 96 ft. dimension bears N. 88° 10' 46" E., 18.26 ft. dist. The Northwesterly corner of said building bears N. 27° 12' 10" E., 31.91 ft. dist. Thence N. 89° 47' 36" E.

FEET	
129.14	Intersect common line 1-2 CWT NO. 1 lode of this survey and line 4-1 Sur. 4648, NEVADA NO. 8 lode at a point from which Cor. No. 1 of the NEVADA N. 8 lode bears S. $44^{\circ} 22' 55''$ W., 873.81 ft. dist.
300.00	Lode line, discovery point bears S. $3^{\circ} 43' 28''$ W., 1400 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 3 of the MIDLAND NO. 22 lode of this survey; from which The NE. cor. of a sheet steel warehouse building of 32 ft. x 48 ft. dimension, bears S. $60^{\circ} 50' 45''$ W., 133 ft. dist. The SE. cor. of said warehouse building bears S. $40^{\circ} 30' 37''$ W., 119 ft. dist. Thence S. $3^{\circ} 43' 28''$ W.
170.25	Intersect Northerly side of mill building, previously described.
252.89	Intersect Southerly side of mill building, previously described.
405.81	Intersect line 3-4 CWT NO. 1 lode of this survey.
490	Arroyo, 50 ft. wide drains East.
845	Fence bears S. 77° W., N. 77° E.
980	Power line bears S. 77° W., N. 77° E.
1130	Arroyo, 25 ft. wide drains East.
1460	Road bears from West to S. 80° E.
1500.00	Cor. No. 1, and place of beginning.

CWT NO. 1 LODE

Beginning at Cor. No. 1 of the CWT NO. 1 lode, identical with Cor. No. 1 Sur. 4648 NEVADA NO. 8 lode.

A $5/8$ in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. CWT 1-1-4658-NV 8-1-4648; from which

The cor. of secs. 22, 23, 26 and 27 bears S. $63^{\circ} 55' 20''$ W., 2003.37 ft. dist. Monumented with a 2 in. diam. iron post projecting 10 ins. above ground topped with a lead cap. Firmly set in an E.-W. fence and properly marked by a surveyor whose name is unknown. Accepted as best evidence of the wooden post set in 1872 by T.F. White.

Cor. No. 4 Sur. 4656 ELLA #1 lode bears N. $37^{\circ} 41' 03''$ E., 788.54 ft. dist.

FEET		
	Thence N. 44° 22' 55" E.	
245	Power line bears N. 82° E., S. 82° W.	
530	Road bears N. 20° W., S. 20° E.	
676.07	Intersect line 4-1, Sur. 4656 ELLA #1 lode at a point from which Cor. No. 4 bears N. 3° 43' 28" E., 141.16 ft. dist.	
873.81	Intersect line 3-4, MIDLAND NO. 23 lode of this survey.	
1072.49	Intersect line 1-2 ARIZONA NO. 43 lode of this survey.	
1497.93	Cor. No. 2, identical with Cor. No. 4 Sur. No. 4648 NEVADA NO. 8 lode. A 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 24 ins. in the ground, mkd. CWT 1-2-4658-NV 8-4-4648	
	Thence S. 45° 30' 15" E.	
239.26	Intersect line 2-3 PIMA #1 lode of this survey.	
262.64	Intersect line 4-1 ARIZONA NO. 43 lode of this survey.	
300.00	Lode line, discovery point bears S. 44° 23' 40" W., 150.00 ft. dist.	
436.59	Intersect line 1-2 ARIZONA NO. 41 lode of this survey.	
600.00	Cor. No. 3. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. CWT 1-3-4658; from which Cor. No. 2 of the PIMA #1 lode of this survey bears S. 63° 55' 22" W., 306.07 ft. dist.	
	Thence S. 44° 24' 25" W.	
31.49	Intersect line 3-4 MIDLAND NO. 22 lode of this survey.	
197.29	Intersect line 1-2 PIMA #1 lode of this survey.	
600.22	Intersect common line 2-3 MIDLAND NO. 22 lode, 4-1 MIDLAND NO. 23 lode, of this survey.	
650	NE. Cor. of a sheet steel power plan building, of 64 ft. x 102 ft. dimension, bears N. 45° 35' 35" W., 212 ft. dist.	
730	Arroyo, 50 ft. wide drains N. 60° E.	

FEET	
736	SW. Cor. of power plant building bears N. 45° 35' 35" W., 268 ft. dist.
1320	Power line bears N. 2° 30' W., S. 2° 30" E.
1385	Fence bears N. 77° E., S. 77° W.
1497.92	Cor. No. 4. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. CWT 1-4-4658. Thence N. 45° 30' 15" W.
17.71	Intersect common line 2-3 MIDLAND NO. 23 lode of this ^{and line} survey/ 4-1 sur. No. 4656 ELLA #1 lode at a point from which cor. No. 4 of the ELLA #1 lode bears N. 3° 43' 28" E., 1033.87 ft. dist.
80	Fence bears N. 77° E., S. 77° W.
299.67	Lode line, discovery point bears N. 44° 23' 40" E., 1347.92 ft. dist.
440	Arroyo, 40 ft. wide drains N. 80° E.
510	Road bears North, South.
599.34	Cor. No. 1, and place of beginning.
PIMA #2 LODE	
At Cor. No. 1 of the PIMA #2 lode.	
Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. PM 2-1-4658; from which	
The cor. of secs. 23, 24, 25, 26 bears S. 29° 32' 12" W., 1421.75 ft. dist., previously described.	
Thence N. 87° 19' 23" W.	
131.78	Intersect line 4-1 MIDLAND NO. 18 lode of this survey.
717.52	Intersect line between secs. 23 and 24 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 0° 42' 52" E., 1270.59 ft. dist.
730.47	Intersect common line 2-3 MIDLAND NO. 18 lode, 4-1 MIDLAND NO. 19 lode, of this survey.
1055	Power line bears N. 1° W., S. 1° E.
1140	Fence bears N. 0° 10' W., S. 0° 10' E.
1329.16	Intersect common line 2-3 MIDLAND NO. 19 lode, 4-1 MIDLAND NO. 20 lode of this survey.

FEET		
1499.76	<p>Cor. No. 2, identical with Cor. No. 1 of the PIMA #1 lode of this survey.</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. PM 2-2-PM 1-1-4658.</p> <p>Thence N. 2° 36' 01" E.</p>	
20	Swale drains N. 45° E.	
70	Toe of tailings pond dike.	
110	<p>Top center of tailings pond dike bears from S. 72° W., to an angle point dist. 40 ft., thence N. 8° W.</p>	
186.81	Intersect line 3-4 MIDLAND NO. 20 lode of this survey.	
300.00	Lode line, discovery point bears S. 87° 19' 23" E., 1399.76 ft. dist.	
365.70	Intersect line 1-2 ARIZONA NO. 37 lode of this survey.	
400	Top center of tailings pond dike bears N. 8° W., S. 8° E.	
599.08	<p>Cor. No. 3 and Easterly toe tailings pond dike, identical with Cor. No. 4 of the PIMA #1 lode of this survey.</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. PM 2-3-PM 1-4-4658.</p>	
265	Fence bears N. 54° W., S. 54° E.	
293.75	Intersect common line 4-1 ARIZONA NO. 37 lode, 2-3 ARIZONA NO. 35 lode, of this survey.	
410	Power line bears N. 1° W., S. 1° E.	
595	Arroyo, 10 ft. wide drains N. 40° E.	
747.53	<p>Intersect line between secs. 23 and 24 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 0° 42' 52" E., 1870.72 ft. dist.</p>	
897.17	Intersect common line 4-1 ARIZONA NO. 35 lode, 2-3 ARIZONA NO. 33 lode, of this survey.	
1499.76	<p>Cor. No. 4.</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. PM 2-4-4658; from which</p>	

FEET	
	Cor. No. 1 of the ARIZONA NO. 33 lode of this survey bears S. 6° 14' 01" E., 168.45 ft. dist. Thence S. 2° 36' 01" W.
167.56	Intersect line 1-2 ARIZONA NO. 33 lode of this survey.
220	Swale, drains East.
299.08	Lode line, discovery point bears N. 87° 19' 23" W., 100.00 ft. dist.
599.08	Cor. No. 1, and place of beginning.
PIMA #1 LODE	
	Beginning at Cor. No. 1 of the PIMA #1 lode, identical with Cor. No. 2 of the PIMA # 2 lode of this survey; from which The cor. of secs. 23, 24, 25, 26, bears S. 31° 22' 53" E., 1530.98 ft. dist., previously described. Thence N. 87° 19' 23" W.
30	Swale drains N. 45° E.
180	Toe of tailings pond dike.
280	Top center of tailings pond dike bears N. 72° E., S. 72° W.
428.08	Intersect common line 2-3 MIDLAND NO. 20 lode 4-1 MIDLAND NO. 21 lode of this survey.
460	Toe of tailings pond dike.
1026.77	Intersect common line 2-3 MIDLAND NO. 21 lode, 4-1 MIDLAND NO. 22 lode of this survey.
1362.75	Intersect line 3-4 CWT NO. 1 lode of this survey.
1405.45	The Easterly wall of a steel tailings thickener tank, 37 ft., 2 in. diam., calculated center bears S. 85° 15' 39" W., 37.59 ft. dist.
1480.00	Westerly wall of said tailing thickener tank, calculated center bears S. 79° 54' 25" E., 37.59 ft. dist.
1499.76	Cor. No. 2. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground mkd. PM 1-2-4658. Thence N. 2° 36' 01" E.
111.27	Intersect line 3-4 MIDLAND NO. 22 lode of this survey.

FEET	
249.75	Intersect line 1-2 ARIZONA NO. 43 lode of this survey.
300.00	Lode line, discovery point bears S. 87° 19' 23" E., 1399.76 ft. dist.
387.77	Intersect line 2-3 CWT NO. 1 lode of this survey.
487.85	Intersect common line 4-1 ARIZONA NO. 43 lode, 2-3 ARIZONA NO. 41 lode of this survey.
599.08	Cor. No. 3. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. PM 1-3-4658.
	Thence S. 87° 19' 23" E.
500	Westerly end of tailings pond dike.
586.69	Intersect common line 4-1 ARIZONA NO. 41 lode, 2-3 ARIZONA NO. 39 lode of this survey.
590	Top center of tailings pond dike bears N. 83° E., S. 83° W.
1000	Toe of tailings pond dike.
1190.11	Intersect common line 4-1 Arizona NO. 39 lode, 2-3 ARIZONA NO. 37 lode, of this survey.
1390	Toe of tailings pond dike.
1460	Top center of tailings pond dike bears N. 8° W., S. 8° E.
1499.76	Cor. No. 4, identical with Cor. No. 3 of the PIMA #2 lode of this survey.
	Thence S. 2° 36' 01" W.
199	Top center of tailings pond dike bears N. 8° W., S. 8° E.
233.38	Intersect line 1-2 ARIZONA NO. 37 lode of this survey.
299.08	Lode line, discovery point bears N. 87° 19' 23" W., 100.00 ft. dist.
412.27	Intersect line 3-4, MIDLAND NO. 20 lode of this survey.
489	Top center of tailings pond dike bears S. 72° W., N. 72° E.
529	Toe of tailings pond dike.

FEET	
579	Swale drains N. 45° E.
599.08	Cor. No. 1, and place of beginning.
ARIZONA NO. 33 LODE	
	At Cor. No. 1 of the ARIZONA NO. 33 lode.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 33-1-4658; from which
	The cor. of secs. 23, 24, 25, 26 bears S. 24° 06' 25" W., 1827.36 ft. dist., previously described.
	Thence N. 89° 50' 11" W.
25.89	Intersect line 4-1 PIMA #2 lode of this survey.
300.00	Lode line, discovery point bears N. 5° 57' 14" W., 1449.50 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 1 of the ARIZONA NO. 35 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 33-2-AZ 35-1-4658
	Thence N. 5° 57' 14" W.
194.94	Intersect line 3-4 PIMA #2 lode of this survey.
390	Swale drains East.
615	Power line bears N. 79° 30' E., S. 79° 30' W.
690	Road, 20 ft. wide bears N. 50° W., S. 50° E.
1220	Arroyo 10 ft. wide drains N. 45° E.
1499.50	Cor. No. 3, identical with; Cor. 4 ARIZONA NO. 35, Cor. No. 2 ARIZONA NO. 36, Cor. No. 4 ARIZONA NO. 34 lodes, of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 33-3- AZ 35-4- AZ 36-2 - AZ 34-4-4658.
	Thence S. 89° 50' 11" E.
300.00	Lode line, discovery point bears S. 5° 57' 14" E., 50.00 ft. dist.
360	Arroyo, 10 ft. wide drains N. 45° E.
600.00	Cor. No. 4, identical with Cor. No. 3 ARIZONA NO. 34 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 33-4 - AZ 34-3-4658.

FEET	
	Thence S. 5° 57' 14" E.
725	Road, 20 ft. wide bears N. 75° E., S. 75° W.
770	Power line bears N. 79° 30' E., S. 79° 30' W.
1130	Swale drains East.
1499.50	Cor. No. 1, and place of beginning.
ARIZONA NO. 35 LODGE	
	Beginning at Cor. No. 1 of the ARIZONA NO. 35 lode, identical with Cor. No. 2 of the ARIZONA NO. 33 lode of this survey, previously described.
	The cor. of secs. 23, 24, 25, 26, bears S. 5° 00' 35" W., 1676.10 ft. dist., previously described.
	Thence N. 89° 50' 11" W.
167.20	Intersect line between secs. 23 and 24 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 0° 42' 52" E., 1670.30 ft. dist.
300.00	Lode line, discovery point bears N. 5° 57' 14" W., 1449.50 ft. dist.
510	Power line bears N. 1° W., S. 1° E.
580	Fence bears N. 0° 10' W., S. 0° 10' E.
600.00	Cor. No. 2, identical with Cor. No. 1 of the ARIZONA NO. 37 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 35-2- AZ 37-1-4658.
	Thence N. 5° 57' 14" W.
15	Swale drains N. 40° E.
175	Fence bears N. 41° W., S. 41° E.
221.55	Intersect line 3-4 PIMA #2 lode of this survey.
710	Road, 20 ft. wide, bears N. 45° E., S. 45° W.
920	Arroyo, 10 ft. wide drains S. 80° E.
1499.50	Cor. No. 3, identical with; Cor. No. 4 ARIZONA NO. 37, Cor. No. 2 ARIZONA NO. 38, Cor. No. 3 ARIZONA NO. 36 lodes of this survey

FEET	
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 35-3 AZ 37-4 - AZ 38-2 - AZ 36-3-4658.
	Thence S. 89° 50' 11" E.
300.00	Lode line, discovery point bears S. 5° 57' 14" E., 50.00 ft. dist.
569.75	Intersect line between Secs. 23 and 24 at a point from which the cor. of secs. 23, 24, 25 and 26 bears S. 0° 42' 52" E., 3161.44 ft. dist.
600.00	Cor. No. 4, identical with cor. No. 3 ARIZONA NO. 33 lode of this survey, previously described.
	Thence S. 5° 57' 14" E.
280	Arroyo, 10 ft. wide drains N. 45° E.
810	Road, 20 ft. wide, bears N. 50° W., S. 50° E.
885	Power line bears N. 79° 30' E., S. 79° 30' W.
1110	Swale drains East.
1304.56	Intersect line 3-4 PIMA #2 lode of this survey.
1499.50	Cor. No. 1, and place of beginning.
ARIZONA NO. 37 LODE	
	Beginning at Cor. No. 1 of the ARIZONA NO. 37 lode, identical with Cor. No. 2 of the ARIZONA NO. 35 lode of this survey, previously described; from which
	The cor. of secs. 23, 24, 25, 26, bears S. 15° 11' 05" E., 1731.87 ft. dist., previously described.
	Thence N. 89° 50' 11" W.
15	Swale drains N. 40° E.
290	Toe of tailings pond dike.
300.00	Lode line, discovery point bears N. 5° 57' 14" W., 1449.50 ft. dist.
325	Top center of tailings pond dike bears N. 8° W., S. 8° E.
327.01	Intersect common line 2-3 PIMA #2 lode, 4-1 PIMA #1 lode of this survey.
395	Toe of tailings pond dike.
600.00	Cor. No. 2, identical with Cor. No. 1 of the ARIZONA NO. 39 lode of this survey.

FEET	
	<p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 37-2 - AZ 39-1-4658.</p> <p>Thence N. 5° 57' 14" W.</p>
248.17	Intersect line 3-4 PIMA #1 lode of this survey.
280	Toe of tailings pond dike.
355.	Top center of tailings pond dike bears N. 83° E., S. 83° W.
385	Toe of tailings pond dike.
480	Road, 20 ft. wide bears West to East.
800	Fence bears N. 54° W., S. 54° E.
860	Arroyo, 10 ft. wide drains from S. 40° W., to N. 20° E.
1499.50	<p>Cor. No. 3 identical with;</p> <p>Cor. No. 4 ARIZONA NO. 39, Cor. No. 2 ARIZONA NO. 40, Cor. No. 3 ARIZONA NO. 38 lodes of this survey.</p> <p>Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 37-3 - AZ 39-4-AZ 40-2 - AZ 38-3-4658.</p> <p>Thence S. 89° 50' 11" E.</p>
300.00	Lode line, discovery point bears S. 5° 57' 14" E., 50.00 ft. dist.
600.00	<p>Cor. No. 4, identical with Cor. No. 3 of the ARIZONA NO. 35 lode of this survey, previously described.</p> <p>Thence S. 5° 57' 14" E.</p>
580	Arroyo, 10 ft. wide drains S. 80° E.
790	Road, 20 ft. wide, bears N. 45° E., S. 45° W.
1277.95	Intersect line 3-4 PIMA #2 lode of this survey.
1325	Fence bears N. 41° W., S. 41° E.
1485	Swale drains N. 40° E.
1499.50	Cor. No. 1, and place of beginning.
<p>ARIZONA NO. 39 LODE</p> <p>Beginning at Cor. No. 1 of the ARIZONA NO. 39 lode, identical with Cor. No. 2 of the ARIZONA NO. 37 lode of this survey from which</p>	

FEET	
	The cor. of secs. 23, 24, 25, 26, bears S. 32° 12' 01" E., 1977.24 ft. dist. previously described.
	Thence N. 89° 50' 11" W.
300.00	Lode line, discovery point bears N. 5° 57' 14" W., 1449.50 ft. dist.
600.00	Cor. No. 2.
	On line 4-1 of the ARIZONA NO. 41 lode of this survey; at a point from which
	Cor. No. 1 ARIZONA NO. 41 lode bears S. 5° 57' 14" E., 50.33 ft. dist., hereinafter described.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 39-2-4658.
	Thence N. 5° 57' 14" W.
210	Toe of tailings pond dike.
274.78	Intersect line 3-4 PIMA #1 lode of this survey.
280	Top center of tailings pond dike bears N. 83° E., S. 83° W.
310	Toe of tailings pond dike.
420	Road, 20 ft. wide bears West, East.
1070	Arroyo, 10 ft. wide drains from West to S. 45° E.
1260	Fence bears N. 54° W., S. 54° E.
1370	Road bears N. 80° E., S. 80° W.
1449.67	Cor. No. 4 ARIZONA NO. 41 lode, identical with Cor. No. 3 ARIZONA NO. 42 lode of this survey, hereinafter described.
1499.50	Cor. No. 3, identical with Cor. No. 2 of the ARIZONA NO. 42 lode, and Cor. No. 3 of the ARIZONA NO. 40 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 39-3- AZ 42-2- AZ 40-3-4658.
	Thence S. 89° 50' 11" E.
300.00	Lode line, discovery point bears S. 5° 57' 14" E., 50.00 ft. dist.
450	Road bears N. 80° E., S. 70° W.
600.00	Cor. No. 4, identical with Cor. No. 3 ARIZONA NO. 37 of this survey, previously described.

FEET		
	Thence S. 5° 57' 14" E.	
640	Arroyo 10 ft. wide drains from S. 40° W., to N. 20° E.	
700	Fence bears N. 54° W., S. 54° E.	
1020	Road, 20. ft. wide bears East and West.	
1115	Toe of tailings pond dike..	
1145	Top center of tailings pond dike bears N. 83° E., S. 83° W.	
1220	Toe of tailings pond dike..	
1251.33	Intersect line 3-4 PIMA #1 lode of this survey.	
1499.50	Cor. No. 1, and place of beginning.	
<hr/>		
ARIZONA NO. 41 LODE		
At Cor. No. 1 of the ARIZONA NO. 41 lode.		
Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 ins. in the ground, mkd. AZ 41-1-4658; from which		
The cor. of secs. 23, 24, 25, 26, bears S. 45° 24' 49" E., 2314.55 ft. dist., previously described.		
Thence N. 89° 50' 23" W.		
300.00	Lode line, discovery point bears N. 5° 57' 14" W., 1450 ft. dist.	
488.60	Intersect line 2-3 CWT NO. 1 lode of this survey.	
600.00	Cor. No. 2, identical with Cor. No. 1 ARIZONA NO. 43 lode of this survey.	
Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 41-2- AZ 43-1-4658.		
Thence N. 5° 57' 14" W.		
122.26	Intersect line 2-3 CWT NO. 1 lode of this survey.	
239.25	Intersect line 2-3 PIMA #1 lode of this survey.	
380	Road, 20 ft. wide bears N. 85° E., S. 85° W.	
740	Road bears N. 70° N., S. 70° W.	

FEET	
1160	Road bears N. 65° E., S. 65° W.
1239.42	Intersect line 3-4 Sur. 4648 NEVADA NO. 5 lode at a point from which cor. No. 3 bears N. 44° 26' 29" E., 188.49 ft. dist.
1310	Fence bears N. 85° E., S. 85° W.
1500.00	Cor. No. 3, identical with; Cor. No. 4 ARIZONA NO. 43 lode and Cor. No. 4 ARIZONA NO. 42 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 41-3 - AZ 43-4 - AZ 42-4-4658; from which Cor. No. 3 Sur. 4648 NEVADA NO. 5 lode, identical with Cor. No. 4, Sur. 4648 NEVADA NO. 6 lode bears S. 51° 54' 55" E., 202.01 ft. dist. Thence S. 89° 50' 23" E.
32.04	Intersect line 2-3 Sur. 4648 NEVADA NO. 5 lode at a point from which Cor. No. 3 bears S. 45° 33' 31" E., 177.84 ft. dist.
280.44	Intersect line 3-4 Sur. 4648 NEVADA NO. 6 lode at a point from which Cor. No. 4 bears S. 44° 26' 29" W., 173.43 ft. dist.
300.00	Lode line, discovery point bears S. 5° 57' 14" E., 50 ft. dist.
600.00	Cor. No. 4, on line 2-3 of the ARIZONA NO. 39 lode of this survey, identical with Cor. No. 3 of the ARIZONA NO. 42 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 41-4 - AZ 42-3-4658. Thence S. 5° 57' 14" E.
80.	Road bears N. 80° E., S. 80° W.
190.	Fence bears N. 54° W., S. 54° E.
380	Arroyo, 10 ft. wide drains from West to S. 45° E.
500	NE. cor. of a concrete explosive magazine, of 15 ft. x 40 ft. dimension, bears S. 84° 02' 46" W., 201 ft. dist.
532	SE. cor. of said explosive magazine bears S. 84° 02' 46" W., 180 ft. dist.
1030	Road, 20 ft. wide bears East and West.
1140	Toe of tailings pond dike.
1170	Top center of tailings pond dike bears N. 83° E., S. 83° W.

FEET	
1174.89	Intersect line 3-4 PIMA #1 lode of this survey.
1240	Toe of tailings pond dike.
1449.67	Cor. No. 2 ARIZONA NO. 39 lode of this survey, previously described.
1500.00	Cor. No. 1, and place of beginning.
ARIZONA NO. 43 LODE	
At Cor. No. 1 of the ARIZONA NO. 43 lode, identical with Cor. No. 2 of the ARIZONA NO. 41 lode of this survey; from which	
The cor. of sees. 23, 24, 25, 26 bears S. 54° 07' 07" E., 2775.01 ft. dist., previously described.	
Thence N. 89° 48' 50" W.	
35.62	Intersect line 2-3 PIMA #1 lode of this survey.
300.00	Lode line, discovery point bears N. 5° 57' 14" W., 750 ft. dist.
497.58	Intersect line 4-1 Sur. 4648 NEVADA NO. 8 lode, common to line 1-2, CWT NO. 1 lode of this survey at a point from which Cor. No. 4 bears N. 44° 22' 55" E., 425.44 ft. dist.
600.00	Cor. No. 2 Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 43-2-4658; from which Cor. No. 4 Sur. 4648 NEVADA NO. 8 lode, identical with Cor. No. 2 of the CWT NO. 1 lode of this survey bears N. 52° 47' 18" E., 502.22 ft. dist.
Thence N. 5° 57' 14" W.	
330	Road, 20 ft. wide bears East and West.
681.64	Intersect common line 2-3 Sur. 4648 NEVADA NO. 8 lode and 3-4 Sur. 4648 NEVADA NO. 4 lode at a point from which Cor. No. 3, NEVADA NO. 8 bears N. 44° 26' 29" E., 61.65 ft. dist. Cor. No. 3 NEVADA NO. 4 bears N. 44° 26' 29" E., 362.78 ft. dist.
810	Road, bears N. 80° E., S. 80° W.

FEET	
1250	Fence bears N. 85° E., S. 85° W.
1250.71	Intersect common line 2-3 Sur. 4648 NEVADA NO. 4 lode and line 4-1 Sur. 4648 NEVADA NO. 5 lode at a point from which Cor. No. 3, NEVADA NO. 4 lode, identical with Cor. No. 4, NEVADA NO. 5 lode bears S. 45° 33' 31" E., 438.45 ft. dist.
1310	Wash, 50 ft. wide drains N. 30° E.
1500.00	Cor. No. 3 Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd AZ 43-3-4658; from which Cor. No. 3 Sur. 4648 NEVADA NO. 4 lode, identical with Cor. No. 4 Sur. 4648 NEVADA NO. 5 lode bears S. 31° 24' 43" E., 650.23 ft. dist. Thence S. 89° 48' 50" E.
260	Wash, 50 ft. wide drains N. 45° E.
300.00	Lode line, discovery point bears S. 5° 57' 14" E., 750 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 3 ARIZONA NO. 41, lode of this survey, previously described. Thence S. 5° 57' 14" E.
190	Fence bears N. 85° E., S. 85° W.
260.58	Intersect line 3-4 Sur. 4648 NEVADA NO. 5 lode at a point from which Cor. No. 4 bears S. 44° 26' 29" W., 411.52 ft. dist.
340	Road bears N. 65° E., S. 65° W.
760	Road bears N. 70° E., S. 70° W.
1120	Road, 20 ft. wide bears N. 85° E., S. 85° W.
1260.75	Intersect line 2-3 PIMA #1 lode of this survey.
1377.74	Intersect line 2-3 CWT NO. 1 lode of this survey at a point from which Cor. No. 2, identical to Cor. No. 4 Surv. 4648 NEVADA NO. 8 lode bears N. 45° 30' 15" W., 262.64 ft. dist.
1500.00	Cor. No. 1, and place of beginning. ARIZONA NO. 34 LODE At Cor. No. 1 of the ARIZONA NO. 34 lode, identical with Cor. No. 1 of the ARIZONA NO. 36 lode of this survey. Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 34-1 - AZ 36-1-4658; from which

FEET	
	<p>The cor. of secs. 13, 14, 23 and 24, T.17S., R.12E., bears N. 8° 59' 17" E., 635.31 ft. dist. Monumented by a 5/8 in. steel bar projecting 6 ins. above ground, topped by an aluminum cap, firmly set and properly marked. Set by double-proportional measurements by R. L. Frazer L.S. 1144 in 1964 as the best evidence of the wooden post set in 1872 by T.F. White.</p> <p>Thence S. 89° 50' 11" E.</p>
107.14	Intersect the line between Secs. 23 and 24 at a point from which the Cor. of Secs. 13, 14, 23 and 24 bears N. 0° 42' 52" W. 628.15 ft. dist.
300.00	Lode line, discovery point bears S. 5° 58' 40" E., 1447.50 ft. dist.
600.00	Cor. No. 2.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 34-2-4658.
	Thence S. 5° 58' 40" E.
550	Wash, 50 ft. wide drains N. 50° E.
610	Road bears S. 80° E., N. 80° W.
760	Road bears N. 75° E., S. 75° W.
1450	Arroyo, 10 ft. wide drains East.
1497.50	Cor. No. 3, identical with Cor. No. 4 of the ARIZONA NO. 33 lode of this survey, previously described.
	Thence N. 89° 50' 11" W.
240	Arroyo, 10 ft. wide drains N. 45° E.
300.00	Lode line, discovery point bears N. 5° 58' 40" W., 50.00 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 3 of the ARIZONA NO. 33 lode of this survey, previously described.
	Thence N. 5° 58' 40" W.
329.68	Intersect the line between secs. 23 and 24 at a point from which the Cor. of Secs. 13, 14, 23 and 24 bears N. 0° 42' 52" W., 1789.40 ft. dist.
570	Road bears N. 65° E., S. 65° W.

FEET	
700	Wash, 50 ft. wide drains from West to N. 80° E.
940	Road bears N. 30° W., East.
1497.50	Cor. No. 1, and place of beginning.
ARIZONA NO. 36 LODE	
Beginning at Cor. No. 1 of the ARIZONA NO. 36 lode, identical with Cor. No. 1 of the ARIZONA NO. 34 lode of this survey.	
Thence S. 5° 58' 40" E.	
560	Road bears N. 30° W., and East.
800	Wash, 50 ft. wide drains from West to N. 80° E.
930	Road bears N. 65° E., and S. 65° W.
1167.82	Intersect line between secs. 23 and 24 at a point from which the cor. of secs. 13, 14, 23 and 24 bears N. 0° 42' 52" W., 1789.40 ft. dist.
1497.50	Cor. No. 2, identical with Cor. No. 4 of the ARIZONA NO. 34 lode of this survey, previously described.
Thence N. 89° 50' 11" W.	
30.25	Intersect the line between secs. 23 and 24 at a point from which the cor. of secs. 13, 14, 23 and 24 bears N. 0° 42' 52" W., 2117.23 ft. dist.
300.00	Lode line, discovery point bears N. 5° 58' 40" W., 50.00 ft. dist.
600.00	Cor. No. 3, identical with Cor. No. 3 of the ARIZONA NO. 35 lode of this survey, previously described.
Thence N. 5° 58' 40" W.	
150	Road bears N. 60° E., and S. 60° W.
520	Arroyo, 10 ft. wide drains N. 85° E.
810	Wash, 50 ft. wide drains East.
1280	Road bears N. 60° W., and S. 60° E.
1497.50	Cor. No. 4, identical with Cor. No. 1 of the ARIZONA NO. 38 lode of this survey.
Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 36-4 - AZ 38-1-4658.	
Thence S. 89° 50' 11" E.	
300.00	Lode line, discovery point bears S. 5° 58' 40" E., 1447.50 ft. dist.
600.00	Cor. No. 1, and place of beginning.

FEET	
	ARIZONA NO. 38 LODE
	Beginning at Cor. No. 1 of the ARIZONA NO. 38 lode, identical with Cor. No. 4 of the ARIZONA NO. 36 lode of this survey, previously described; from which
	The cor. of secs. 13, 14, 23, 24 bears N. 48° 09' 41" E., 938.62 ft. dist., previously described.
	Thence S. 5° 58' 40" E.
220	Road bears S. 60° E., and N. 60° W.
690	Wash 50 ft. wide drains East.
980	Arroyo 10 ft. wide drains N. 85° E.
1350	Road bears N. 60° E., and S. 60° W.
1497.50	Cor. No. 2, identical with Cor. No. 3 of the ARIZONA NO. 36 lode of this survey, previously described.
	Thence N. 89° 50' 11" W.
300.00	Lode line, discovery point bears N. 5° 58' 40" W., 50.00 ft. dist.
600.00	Cor. No. 3, identical with Cor. No. 3 of the ARIZONA NO. 37 lode of this survey, previously described.
	Thence N. 5° 58' 40" W.
40.00	Road bears N. 80° E., and S. 80° W.
450	Wash 50 ft. wide drains from N. 60° W., to N. 45° E.
1180	Arroyo 6 ft. wide drains N. 60° E.
1497.50	Cor. No. 4, identical with Cor. No. 1 of the ARIZONA NO. 40 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, driven in the ground, mkd. AZ 38-4 - AZ 40-1-4658.
	Thence S. 89° 50' 11" E.
290	Arroyo, 10 ft. wide drains N. 60° E.
300.00	Lode line, discovery point bears S. 5° 58' 40" E., 1447.50 ft. dist.
600.00	Cor. No. 1, and place of beginning.

FEET	
	ARIZONA NO. 40 LODE
	Beginning at Cor. No. 1 of the ARIZONA NO. 40 lode, identical with Cor. No. 4 of the ARIZONA NO. 38 lode of this survey, previously described, from which
	The cor. of secs. 13, 14, 23, 24 bears N. 64° 20' 02" E., 1441.53 ft. dist., previously described.
	Thence S. 5° 58' 40" E.
320	Arroyo drains N. 60° E.
1050	Wash 50 ft. wide, drains from N. 60° W., to N. 45° E.
1460	Road bears N. 80° E., and S. 80° W.
1497.50	Cor. No. 2, identical with Cor. No. 3 of the ARIZONA NO. 38 lode of this survey, previously described.
	Thence N. 89° 50' 11" W.
150	Road bears N. 80° E., and S. 70° W.
300.00	Lode line, discovery point bears N. 5° 58' 40" W., 50.00 ft. dist.
600.00	Cor. No. 3, identical with Cor. No. 3 of the ARIZONA NO. 39 lode, and Cor. No. 2 of the ARIZONA NO. 42 lode of this survey.
	Cor. No. 1 Surv. 4648 NEVADA NO. 7 lode bears N. 30° 34' 42" E., 794.61 ft. dist.
	Thence N. 5° 58' 40" W.
247.03	Intersect line 3-4 Sur. 4648 NEVADA NO. 6 lode, at a point from which Cor. No. 3 identical with Cor. No. 2 Sur. 4648 NEVADA NO. 7 lode, bears N. 44° 26' 29" E., 14.06 ft. dist.
	Cor. No. 1, Surv. 4648 NEVADA NO. 7 lode bears N. 44° 26' 29" E., 614.06 ft. dist.
269.10	Intersect line 2-3 Sur. 4648 NEVADA NO. 6 lode at a point from which cor. No. 3 bears S. 45° 33' 31" E., 17.01 ft. dist. Identical with cor. No. 2 Sur. 4648 NEVADA NO. 7 lode.
680	Wash 50 ft. wide drains East.
1210.77	Intersect line 4-1 Sur. 4648 NEVADA NO. 7 lode at a point from which Cor. No. 1 bears S. 45° 33' 31" E., 742.78 ft. dist.
1449.97	Cor. No. 1, of the ARIZONA NO. 42 lode of this survey, hereinafter described.
1497.50	Cor. No. 4.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 40-4-4658.

FEET	
	Thence S. 89° 50' 11" E.
300.00	Lode line, discovery point bears S. 5° 58' 40" E., 1447.50 ft. dist.
600.00	Cor. No. 1, and place of beginning.
ARIZONA NO. 42 LODE	
	At Cor. No. 1 of the ARIZONA NO. 42 lode, on line 3-4 ARIZONA NO. 40 lode of this survey.
	Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 42-1-4658; from which
	The cor. of secs. 13, 14, 23, 24, bears N. 70° 31' 26" E., 2009.32 ft. dist., previously described.
	Cor. No. 4 of the ARIZONA NO. 40 lode of this survey bears N. 5° 58' 40" W., 47.53 ft. dist.
	Thence S. 5° 58' 40" E.
239.20	Intersect line 4-1 Sur. 4648 NEVADA NO. 7 lode at a point from which Cor. No. 1 bears S. 45° 33' 31" E., 742.48 ft. dist.
770	Wash, 50 ft. wide drains East.
1180.87	Intersect line 2-3 Sur. 4648 NEVADA NO. 7 lode at a point from which Cor. No. 2 bears S. 45° 33' 31" E., 17.01 ft. dist. Identical with Cor. No. 3 Sur. 4648 NEVADA NO. 6 lode.
1202.94	Intersect line 3-4 Sur. 4648 NEVADA NO. 6 lode at a point from which Cor. No. 3 bears N. 44° 26' 29" E., 14.06 ft. dist. Identical with Cor. No. 2 Sur. 4648 NEVADA NO. 7 lode.
1449.97	Cor. No. 2, identical with Cor. No. 3 of the ARIZONA NO. 40 lode, and Cor. No. 3 of the ARIZONA NO. 39 lode, of this survey, previously described.
	Thence S. 5° 57' 14" E.
49.83	Cor. No. 3, identical with Cor. No. 4 of the ARIZONA NO. 41 lode of this survey, previously described.

FEET	
	Thence N. 89° 50' 23" W.
300.00	Lode line, discovery point bears N. 5° 58' 37" W., 5.00 ft. dist.
319.56	Intersect line 3-4 Sur. 4648 NEVADA NO. 6 lode at a point from which Cor. No. 4 bears S. 44° 26' 29" W., 173.43 ft. dist. identical with Cor. No. 3 Sur. 4648 NEVADA NO. 5 lode.
567.96	Intersect line 4-1 Sur. 4648 NEVADA NO. 6 lode at a point from which Cor. No. 4 bears S. 45° 33' 31" E., 177.84 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 3 of the ARIZONA NO. 41 lode of this survey, previously described.
	Thence N. 5° 58' 37" W.
35.10	Intersect line 4-1 Sur. 4648 NEVADA NO. 6 lode at a point from which Cor. No. 4 bears S. 45° 33' 31" E., 227.83 ft. dist.
470	Wash 50 ft. wide drains N. 85° E.
976.39	Intersect line 2-3 Sur. 4648 NEVADA NO. 7 lode at a point from which Cor. No. 2 bears S. 45° 33' 31" E., 953.29 ft. dist. Identical with Cor. No. 3 Sur. 4648 NEVADA NO. 6 lode.
1499.79	Cor. No. 5 Set a 5/8 in. diam. steel bar, 24 in. long, with aluminum cap affixed thereon, 16 in. in the ground, mkd. AZ 42-5-4658.
	Thence S. 89° 50' 23" E.
300.00	Lode line, discovery point bears S. 5° 58' 37" E., 1494.98 ft. dist.
381.70	Intersect line 4-1 Sur. 4648 NEVADA NO. 7 lode at a point from which Cor. No. 1 bears S. 45° 33' 31" E., 1083.13 ft. dist.
600.00	Cor. No. 1, and place of beginning.

FEET	<u>Areas</u>	<u>Acres</u>
	Total area MIDLAND NO. 18 lode	20.613
	Area in conflict with -	
	PIMA #2 lode	3.311
	NW.1/4 Sec. 25	0.008
	Total area MIDLAND NO. 19 lode	20.613
	Area in conflict with -	
	PIMA #2 lode	2.896
	Total area MIDLAND NO. 20 lode	20.613
	Area in conflict with -	
	PIMA #2 lode	0.757
	PIMA #1 lode	1.724
	Total area MIDLAND NO. 21 lode	20.613
	Area in conflict with -	
	PIMA #1 lode	2.066
	Total area MIDLAND NO. 22 lode	20.613
	Area in conflict with -	
	PIMA #1 lode	1.342
	PIMA #1 lode exclusive of its	
	conflict with CWT NO. 1 lode	0.831
	CWT NO. 1 lode	1.727
	CWT NO. 1 lode exclusive of its	
	conflict with PIMA #1 lode	1.216
	Total area MIDLAND NO. 23 lode	20.613
	Area in conflict with -	
	CWT NO. 1 lode	9.866
	Sur. 4648 NEVADA No. 8 lode	0.209
	Total area PIMA #2 lode	20.626
	Area in conflict with -	
	MIDLAND NO. 18 lode	3.311
	ARIZONA NO. 33 lode	2.436
	ARIZONA NO. 35 lode	2.852
	ARIZONA NO. 37 lode	1.614
	MIDLAND NO. 19 lode	2.896
	MIDLAND NO. 20 lode	0.757
	Total area PIMA #1 lode	20.626
	Area in conflict with -	
	MIDLAND NO. 20 lode	1.724
	MIDLAND NO. 21 lode	2.066
	MIDLAND NO. 22 lode	1.342
	CWT NO. 1 lode	1.427
	MIDLAND NO. 22 lode exclusive of	
	its conflict with CWT NO. 1 lode	0.831
	CWT NO. 1 lode exclusive of its	
	conflict with MIDLAND NO. 22 lode	0.916
	ARIZONA NO. 43 lode	0.097
	ARIZONA NO. 43 lode exclusive of its	
	conflict with CWT NO. 1 lode	0.020
	ARIZONA NO. 41 lode	4.614
	ARIZONA NO. 41 lode exclusive of its	
	conflict with CWT NO. 1 lode	4.459
	ARIZONA NO. 39 lode	3.581
	ARIZONA NO. 37 lode	1.603
	Total area ARIZONA NO. 33 lode	20.537
	Area in conflict with -	
	PIMA #2 lode	2.436
	Total area ARIZONA NO. 35 lode	20.537
	Area in conflict with -	
	PIMA #2 lode	2.852

FEEET	<u>Areas</u>	<u>Acres</u>
	Total area ARIZONA NO. 37 lode	20.537
	Area in conflict with -	
	PIMA #2 lode	1.614
	PIMA #1 lode	1.603
	Total area ARIZONA NO. 39 lode	20.537
	Area in conflict with -	
	PIMA #1 lode	3.581
	Total area ARIZONA NO. 41 lode	20.544
	Area in conflict with -	
	PIMA #1 lode	4.614
	CWT NO. 1 lode	0.155
	PIMA #1 lode exclusive of its conflict with CWT NO. 1 lode	4.459
	Surv. 4648 NEVADA NO. 5 lode	0.480
	Surv. 4648 NEVADA NO. 6 lode	0.354
	Total area ARIZONA NO. 43 lode	20.543
	Area in conflict with -	
	PIMA #1 lode	0.097
	CWT NO. 1 lode	1.977
	PIMA #1 lode exclusive of its conflict with CWT NO. 1 lode	0.020
	CWT NO. 1 lode exclusive of its conflict with PIMA #1 lode	1.900
	Sur. 4648 NEVADA NO. 8 lode	4.141
	Sur. 4648 NEVADA No. 4 lode	1.826
	Sur. 4648 NEVADA No. 5 lode	5.562
	Total area CWT NO. 1 lode	20.621
	Area in conflict with -	
	MIDLAND NO. 23 lode	9.866
	MIDLAND NO. 22 lode	1.727
	PIMA #1 lode	1.427
	PIMA #1 lode exclusive of its conflict with MIDLAND NO. 22 lode	0.916
	MIDLAND NO. 22 lode exclusive of its conflict with PIMA #1 lode	1.216
	ARIZONA NO. 43 lode	1.977
	ARIZONA NO. 41 lode	0.155
	ARIZONA NO. 43 lode exclusive of its conflict with PIMA #1 lode	1.900
	PIMA #1 lode exclusive of its conflict with ARIZONA NO. 41 lode	1.272
	PIMA #1 lode exclusive of its conflict with ARIZONA NO. 43 lode	1.350
	Sur. 4656 ELLA No. 1 lode	4.514
	Total area ARIZONA NO. 34 lode	20.508
	Total area ARIZONA NO. 36 lode	20.508
	Total area ARIZONA NO. 38 lode	20.508
	Total area ARIZONA NO. 40 lode	20.508
	Area in conflict with -	
	Sur. 4648 NEVADA No. 7 lode	5.233
	Sur. 4648 NEVADA No. 6 lode	0.003
	Total area ARIZONA NO. 42 lode	20.540
	Area in conflict with -	
	Sur. 4648 NEVADA No. 7 lode	11.074
	Sur. 4648 NEVADA No. 6 lode	7.775
	Sur. 4648 NEVADA No. 5 lode	0.013

LOCATION

This survey is located in secs. 23, 24 and 25, T.17S., R.12E., G.&SR.B&M.

The survey is identical with the respective location or amended locations as marked on the ground with 4 x 4 posts except as noted herein in Memoranda.

FEET

EXPENDITURES

The improvements and the value of the labor and improvements made upon or for the benefit of the lode locations embraced in said mining claims by the claimants or its grantor is as follows:

- | | |
|-------|---|
| No. 1 | The discovery point of the MIDLAND NO. 19 lode is on the lode line, 100 ft., N. 3° 43' 28" E. from the center of line 1-2.
Value, None. |
| No. 2 | A trench, the center of which bears N. 69° 42' E., 260 ft. from Cor. No. 2 MIDLAND NO. 19 lode; 6 x 20 ft., 8 ft. deep.
Value, \$25.00. |
| No. 1 | The discovery point of the MIDLAND NO. 18 lode is on the lode line, 100 ft. N. 3° 43' 28" E., from the center of line 1-2.
Value, None. |
| No. 2 | A trench, the center of which bears N. 70° 55' W., 310 ft. from Cor. No. 1 MIDLAND NO. 18 lode; 5 x 10 ft., 8 ft. deep.
Value, \$25.00. |
| No. 1 | The discovery point of the MIDLAND NO. 20 lode is on the lode line, 100 ft. N. 3° 43' 28" E. from the center of line 1-2.
Value, None |
| No. 2 | A trench, the center of which bears N. 64° 14' W., 324 ft. from Cor. No. 1, MIDLAND NO. 20 lode; 6 x 20 ft., 8 ft. deep.
Value, \$25.00. |
| No. 1 | The discovery point of the MIDLAND NO. 21 lode is on the lode line, 100 ft., N. 3° 43' 28" E. from the center of line 1-2
Value, None. |
| No. 2 | A trench, the center of which bears N. 64° 57' W., 321 ft. from Cor. No. 1 MIDLAND NO. 21 lode; 6 x 8 ft., 8 ft. deep.
Value, \$25.00. |
| No. 1 | The discovery point of the PIMA #1 lode is on the lode line 100 ft., N. 89° 19' 23" W. from the center of line 4-1

The location trench of the PIMA #1 lode was not found, and was allegedly obliterated in construction of the tailings pond and dike. |

FEET	
No. 1	<p>The discovery point of the PIMA #2 lode is on the lode line 100 ft., N. 87° 19' 23" W. from the center of line 4-1. Value, None</p>
No. 2	<p>A trench, the center of which bears N. 16° 38' W., 302 ft. from Cor. No. 1 PIMA #2 lode; 8 x 8 ft., 8 ft. deep. Value, \$25.00</p> <p>An interest in a common improvement, described as follows:</p> <p>A core drill hole, designated in mine records as "T-39", the center of which bears N. 71° 03' 05" E., 240.98 ft. dist. from Cor. No. 2 of the MIDLAND NO. 19 lode. 4-1/2 ins. diam., 2 in. core, 1232 ft. deep. Value of 1232 ft. at \$4.37 per ft. \$5,383.84 Value of 1/6 interest 897.31</p> <p>This improvement is for the development of the MIDLAND NO. 18, MIDLAND NO. 19, MIDLAND NO. 20, MIDLAND NO. 21, PIMA #1, and PIMA #2 lodes of this survey, which are contiguous lodes owned in common within the range of benefit of said improvement.</p> <p>Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of the aforesaid six lodes of this survey subsequent to their location and to the time since common ownership and contiguity have prevailed; therefore an undivided one-sixth interest is hereby credited to each of said claims.</p> <p>Except as above-stated, no portion of, or interest in this improvement has been credited heretofore as patent expenditures to any lode claim.</p>
No. 1	<p>The discovery point of the MIDLAND NO. 22 lode is on the lode line, 100 ft., N. 3° 43' 28" E., from the center of line 1-2. Value, None.</p>
No. 2	<p>A trench, the center of which bears N. 59° 02' W., 314 ft. from Cor. No. 1 MIDLAND NO. 22 lode; 6 x 20 ft., 8 ft. deep. Value, \$25.00.</p>
No. 1	<p>The discovery point of the MIDLAND NO. 23 lode is on the lode line, 100 ft., N. 3° 43' 23" E., from the center of line 1-2. Value, None.</p>
No. 2	<p>A trench, the center of which bears N. 78° 08' W., 303 ft. from Cor. No. 1 MIDLAND NO. 23 lode; 10 x 20 ft., 8 ft. deep. Value, \$25.00.</p>

FEET	
No. 1	<p>The discovery point of the CWT NO. 1 lode is on the lode line 150 ft., S. 44° 23' 40" W., from the center of line 2-3. Value, None.</p>
No. 2	<p>A trench, the center of which bears N. 73° 49' W., 334 ft. from Cor. No. 3 CWT NO. 1 lode; 10 x 20 ft., 8 ft. deep. Value, \$25.00</p> <p>An interest in a common improvement described as follows:</p> <p>A core drill hole, designated in mine records as "C-26", the center of which bears N. 60° 19' 38" W., 307.08 ft. from Cor. No. 3 of the CWT NO. 1 lode, 4-1/2 ins. diam., 4 in. core, 890 ft. deep. Value of 890 ft. at \$4.37 per ft. \$3,889.30 Value of 1/3 interest 1,296.43</p> <p>This improvement is for the development of the MIDLAND NO. 22, MIDLAND NO. 23, and the CWT NO. 1 lodes of this survey, which are contiguous lodes owned in common within the range of benefit of said improvement.</p> <p>Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of the aforesaid three lodes of this survey subsequent to their location and to the time since common ownership and contiguity have prevailed; therefore an undivided one-third interest is hereby credited to each of said claims.</p> <p>Except as above-stated, no portion of, or interest in this improvement has been credited heretofore as patent expenditures to any lode claim.</p>
No. 1	<p>The discovery point of the ARIZONA NO. 33 lode is on the lode line, 50 ft., S. 5° 57' 14" E. from the center of line 3-4. Value, None.</p>
No. 2	<p>A trench, the center of which bears S. 68° 38' W., 234 ft. from Cor. No. 4 ARIZONA NO. 33 lode; 8 x 8 ft., 8 ft. deep. Value, \$25.00.</p>

FEET	
No. 1	The discovery point of the ARIZONA NO. 34 lode is on the lode line 50 ft., N. 5° 58' 40" W. from the center of line 3-4. Value, None.
No. 2	A trench, the center of which bears N. 72° 04' W., 310 ft. from Cor. No. 3 ARIZONA NO. 34 lode; 8 x 20 ft., 8 ft. deep. Value, \$25.00.
No. 1	The discovery point of the ARIZONA NO. 35 lode is on the lode line 50 ft., S. 5° 57' 41" E. from the center of line 3-4. Value, None.
No. 2	A trench, the center of which bears S. 61° 19' W., 266 ft. from Cor. No. 4 ARIZONA NO. 35 lode; 8 x 8 ft., 8 ft. deep. Value, \$25.00
No. 1	The discovery point of the ARIZONA NO. 36 lode is on the lode line, 50 ft. N. 5° 58' 40" W. from the center of line 2-3. Value, None.
No. 2	A trench, the center of which bears N. 74° 05' W., 240 ft. from Cor. No. 2 ARIZONA NO. 36 lode; 8 x 10 ft., 8 ft. deep. Value, \$25.00.
No. 1	The discovery point of the ARIZONA NO. 37 lode is on the lode line, 50 ft., S. 5° 57' 14" E. from the center of line 3-4. Value, None.
No. 2	A trench, the center of which bears S. 68° 58' W., 262 ft. from Cor. No. 4 ARIZONA NO. 37 lode; 8 x 20 ft., 8 ft. deep. Value, \$25.00.
No. 1	The discovery point of the ARIZONA NO. 38 lode is on the lode line, 50 ft., N. 5° 58' 40" W. from the center of line 2-3. Value, None.
No. 2	A trench, the center of which bears N. 72° 0' W., 255 ft. from Cor. No. 2 ARIZONA NO. 38 lode; 7 x 20 ft., 8 ft. deep. Value, \$25.00.
	An interest in a common improvement, described as follows:
	A core drill hole, designated in mine records as "T-9", the center of which bears S. 18° 04' 50" E., 661.36 ft. dist. from Cor. No. 3 of the ARIZONA NO. 35 lode; 4-1/2 ins. diam., 2 in. core, 1540 ft. deep. Value of 1540 ft. at \$4.37 per ft. \$6729.80 Value of 1/6 interest 1121.63

FEET

This improvement is for the development of the ARIZONA NO. 33, ARIZONA NO. 34, ARIZONA NO. 35, ARIZONA NO. 36, ARIZONA NO. 37 and ARIZONA NO. 38 lodes of this survey, which are contiguous lodes owned in common within the range of benefit of said improvement.

Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of the aforesaid six lodes of this survey subsequent to their location and to the time since common ownership and contiguity have prevailed; therefore an undivided one-sixth interest is hereby credited to each of said claims.

Except as above-stated, no portion of, or interest in this improvement has been credited heretofore as patent expenditures to any lode claim.

- No. 1 The discovery point of the ARIZONA NO. 39 lode is on the lode line, 50 ft., S. 5° 57' 14" E., from the center of line 3-4.
Value, None
- No. 2 A trench, the center of which bears S. 59° 10' W., 291 ft. from Cor. No. 4 ARIZONA NO. 39 lode; 8 x 20 ft., 8 ft. deep.
Value, \$25.00.
- No. 1 The discovery point of the ARIZONA NO. 40 lode is on the lode line, 50 ft., N. 5° 53' 40" W. from the center of line 2-3.
Value, None.
- No. 2 A trench, the center of which bears N. 73° 05' W., 260 ft. from Cor. No. 2 ARIZONA NO. 40 lode; 8 x 18 ft., 8 ft. deep.
Value, \$25.00.
- No. 1 The discovery point of the ARIZONA NO. 41 lode is on the lode line, 50 ft., S. 5° 57' 14" E., from the center of line 3-4.
Value, None.
- No. 2 A trench, the center of which bears S. 67° 07' W., 293 ft. from Cor. No. 4 ARIZONA NO. 41 lode; 7 x 20 ft., 8 ft. deep.
Value, \$25.00.

FEET		
No. 1	<p>The discovery point of the ARIZONA NO. 42 lode is on the lode line, 5 ft., N. 5° 58' 37" W. from the center of line 3-4. Value, None.</p>	
No. 2	<p>A trench, the center of which bears N. 79° 48' W., 295 ft. from Cor. No. 3 ARIZONA NO. 42 lode; 8 x 15 ft., 8 ft. deep. Value, \$25.00.</p> <p>An interest in a common improvement, described as follows:</p> <p>A core drill hole, designated in mine records as "T-57", the center of which bears S. 23° 11' 50" W., 582.95 ft. from Cor. No. 4 of the ARIZONA NO. 41 lode; 4-1/2 ins. diam., 2 in. core, 1144 ft. deep. Value of 1144 ft. at \$4.37 per ft. \$4,999.28 Value of 1/4 interest 1,249.82</p> <p>This improvement is for the development of the ARIZONA NO. 39, ARIZONA NO. 40, ARIZONA NO. 41, ARIZONA NO. 42 lodes of this survey, which are contiguous lodes owned in common within the range of benefit of said improvement.</p> <p>Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of the aforesaid four lodes of this survey subsequent to their location and to the time since common ownership and contiguity have prevailed; therefore an undivided one-fourth interest is hereby credited to each of said claims.</p> <p>Except as above-stated, no portion of, or interest in this improvement has been credited heretofore as patent expenditures to any lode claim.</p>	
No. 1	<p>The discovery point of the ARIZONA NO. 43 lode is on the lode line, 750 ft., N. 5° 57' 14" W. from the center of line 1-2. Value, None.</p>	
No. 2	<p>A trench, the center of which bears N. 26° 16' W., 855 ft. from Cor. No. 1 ARIZONA NO. 43 lode; 7 x 15 ft., 8 ft. deep. Value, \$25.00.</p>	
No. 3	<p>A core drill hole, designated in mine records as "C-18", the center of which bears S. 19° 08' 53" E., 646.36 ft. dist. from Cor. No. 3 of the ARIZONA NO. 43 lode; 4-1/2 ins. diam. 2 in. core, 800 ft. deep. Value of 800 ft. at \$4.37 per ft. \$3,496.00</p>	

FEET

OTHER IMPROVEMENTS

Core drill holes, 4-1/2 ins. diam., 2 in. core, of depths and mine record designations as follows:

Designations	Lode Claim	Depth Ft.
T-38	MIDLAND NO. 21	1234
C-1	ARIZONA NO. 43	965
C-2	" " "	843
C-4	" " "	793
C-5	" " "	830
C-6	" " "	851
C-16	" " "	780
C-18	" " "	800
C-25	MIDLAND NO. 23	980

Claimants herein.

Portions of an operating mine lying within the limits of claims of this survey, as shown on the plat. Taken from the mine record maps furnished by claimants.

Main tunnel headings at 800 and 900 ft. below the collar of the before-described shaft, averaging 12 ft. wide and 8 ft. to 12 ft. high. Various drifts, raises and stopes. Extent of development shown is as of Feb. 1, 1967.

Claimants herein.

Power house, warehouse, mill building and tailings thickener tank, as described in field notes, are all appurtenant to the ore-processing plant, and are of no value in development of lode claims of this survey.

An electrical power line, as described in field notes and shown on plat.

Claimant unknown.

A four-wire, steel post fence, as described in field notes and shown on plat.

Claimants herein.

A bladed mine access road, approximately 20 ft. wide, as described in field notes and shown on plat.

Claimants herein.

A concrete explosive magazine, as described in field notes and shown on plat.

Claimants herein.

FEET	OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA	
	<p>The cor. of secs. 24 and 25, T. 17S., R.12E., and secs. 19 and 30, T.17S., R.13E., is monumented with a 2 ins. diam., iron post, projecting 10 ins. above ground, topped by a brass cap. Firmly set and properly marked as in Record of 1941 Survey by Raymond Moss.</p> <p>The line between secs. 24 and 25 was found to be S. 89° 37' 32" W., for 5321.2 ft. instead of the 1941 Record of S. 89° 35' W., for 5323.56 ft.</p> <p>The line between secs. 23 and 24 was found to be N. 0° 42' 52" W., for 5278.67 ft., instead of North for 5280 ft. in Record of 1872.</p>	

(This form bound on left side)

FEET

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor	Date
Robert L. Frazer	July 26, 1967

I HEREBY CERTIFY That in pursuance of an order received from the Division of Engineering, Bureau of Land Management, at Phoenix, Arizona, dated January 24, 1967, I have carefully executed the survey of the claim of Steven G. Chilson and others as listed on reverse side hereof, known as the (lode, placer, or mill site) 20 lode claims listed on reverse side hereof, situated in secs. 23, 24 and 25 Township 17.S, Range 12E., Gila and Salt River Base and Meridian, in the State of Arizona.

This survey, designated as number 4658, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in the specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) lode location(s) embraced in the said mining claim by claimant(s) or their grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

P.O.Box 1711, Tucson, Arizona

(Location)

Robert L. Frazer

(Signature of Mineral Surveyor)

CERTIFICATE OF APPROVAL

Bureau of Land Management
Office

Arizona State Office

Location

Phoenix, Arizona

Date

December 19, 1968

The foregoing field notes of mineral survey number 4658, in Sections 23, 24 and 25, Township 17 S., Range 12 E., Gila and Salt River Meridian, in the State of Arizona, executed by Robert L. Frazer Mineral Surveyor, under order dated January 24, 1967, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

Gregg Weiler
(Authorized Signature)

State Director

(Title)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of field notes of the above described mineral survey number is a true copy of the original field notes

(Authorized Signature)

(Title)

18, U. S. C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within jurisdiction.

CLAIMS OF: Steven C. Chilson
 Daniel G. Chilson, Jr.
 Richard E. Chilson
 Marian C. Chilson
 Donna Gail Chilson
 Laurita Yarter
 Robert C. & Rebecca Fordham
 c/o Evans, Kitchel & Jenckes, Attorneys at Law
 363 North 1st Avenue, Phoenix, Arizona

LODE CLAIMS KNOWN AS:

ARIZONA NO. 33
 ARIZONA NO. 34
 ARIZONA NO. 35
 ARIZONA NO. 36
 ARIZONA NO. 37
 ARIZONA NO. 38
 ARIZONA NO. 39
 ARIZONA NO. 40
 ARIZONA NO. 41
 ARIZONA NO. 42
 ARIZONA NO. 43
 MIDLAND NO. 18
 MIDLAND NO. 19
 MIDLAND NO. 20
 MIDLAND NO. 21
 MIDLAND NO. 22
 MIDLAND NO. 23
 PIMA #1
 PIMA #2
~~PIMA #3~~
 CWT NO. 1