Form 3400-11 (September 1967) (formerly 4-683)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

Mineral Survey number 4683
State Arizona
Land District

Of the Survey of the Mining Claim of (name and address of Claimant)

Duval Sierrita Corporation

c/o Bilby, Thompson, Shoenhair & Warnock, Attorneys at Law 9th Floor Valley Mational Building
Tucson, Arizona 85701

Known as the (name of group, if any)

D. S. Mill Site Group

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DAT	
	LOCATED 7/11/70	AMENDED
O. S. Mill Site 1	7/14/70	
O. S. Mill Site 2	7/14/70	
O. S. Mill Site 3	7/14/70	
O. S. Mill Site 4	7/14/70	
O. S. Mill Site 5	7/14/70	
S. Mill Site 8	7/14/70	
. S. Mill Site 9	7/14/70	
o. S. Mill Site 10	7/14/70	
. S. Mill Site 11	7/14/70	
. S. Mill Site 12	7/14/70	
O. S. Mill Site 13	7/14/70	
. S. Mill Site 14	7/14/70	
. S. Mill Site 15	7/14/70	
. S. Mill Site 16	7/14/70	
. S. Mill Site 17	7/14/70	
. S. Mill Site 18	7/14/70	
O. S. Mill Site 19	7/14/70	
O. S. Mill Site 20	7/14/70	
. S. Mill Site 21	7/14/70	

Mining district			County		
Pima				Pima.	
Sections 9, 10 & 16	Townshi 18 Sc	p outh	Range 12 East	Meridian Gila and Salt River Sept. 9, 1970	i
Survey commence Sept. 18, 19			y completed 23, 1971	Name of Mineral Surveyor Robert Lenon, P. E.	_

And the control of th D. S. MEID LEE - TORGE THE PERSON AS Continue to the continue of THEF Franciscom in .e. the telephone and The Contract of the Contract o i rube (164 an a 5018 115 . . or day E Will I Div . . . 7 11-10 g with the . . THE STATE OF THE T 4 III 70 A DEF CIM ere rimal. . PT 经第二级 . . . 17-417 THERE SAYS IT .

438 main of

-

The court of all Williams for the name of the page.

F. F. . T. . T. . T. . Toler's Land. F. E.

FEET

This survey was made with a Bausch & Lomb Precise Transit, No. 9259, with horizontal limb 5-1/2 ins diam., having two single opposite verniers, and full vertical circle 4-1/4 ins. diam., having two double opposite verniers, all verniers reading to one minute of arc. The eyepiece is equipped with a colored glass set in the dust shutter, for making direct observations on the sun. The instrument was in good condition at the time of the survey, and all adjustments were in good order.

All azimuths in this record were determined by the method of double horizontal angles referred to the meridian determined by the following observations:

September 18, 1970, at Cor. No. 3 of the D. S. Mill Site 8, in latitude 31°52'30" N., and longitude 111°07' W., I make a series of four altitude observations (in two sets of two each) upon the sun for azimuth, at approximately equal time intervals, two each with the telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angles clockwise, from Cor. No. 2, Surv. No. 4428, New Years Eve Extension #23, 1,200 feet NW'ly, SE to the sun:

1st set 2nd set Mean time of observation, 105th merid-10^h14^ma.m. 10^h07^ma.m. ian standard time: Declination of sun at mean time of observation: 1°55' N. Mean observed vertical angles to sun's 47°46'30" center: 48°18'00" Mean horizontal angles from reference point to sun's center: 162°32'30" 163°26'30" True bearing to ref-N. 33°35' W. erence point:

The lines were measured with a Lufkin steel tape, 500 feet in length, graduated every foot, with the end feet graduated to tenths and hundredths; and a Chicago steel tape, 300 feet in length, graduated every foot, with the end feet graduated to tenths; both tapes were compared with a Lufkin standard steel tape at the time of beginning the survey, and found correct.

All lines were run by direct methods. The magnetic declination observed at each corner of the survey gave a uniform value of 13°00' E.

SURVEY No. 4683

D. S. MILL SITE 5

At Cor. No. 1 of the D. S. Mill Site 5 of this survey.

On line 2-3, Sur. No. 4428 Copper John Extension #44 lode.

Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS5-1-4683; from which

	SURVEY No. 4683
FEET	The 1/4 sec. cor. of secs. 9 and 10, T. 18 S., R. 12 E., G. & S. R. M., bears N. 89°52'10"E, 2,391.76 ft. dist., a 5/8 in. iron pin with aluminum cap, 12 ins. above the ground, firmly set and properly marked, stone mound alongside.
	Cor. No. 2 Sur. No. 4428 Copper John Extension #44 lode bears N. 36°12'30" W., 68.70 ft. dist.
W. I	Thence N. 89°52'10" E.
393.14	Cor. No. 2, identical with Cor. No. 5 of the D. S. Mill Site 3 of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS5-2-DS3-5-4683.
3 -	Thence S. 2°22' E.
432.	Gulch, 2 ft. wide, course S. 70° W.
586.40	Cor. No. 3, identical with Cor. No. 4 of the D.S. Mill Site 3 of this survey and on line 2-3 Sur. No. 4428 New Years Eve Extension #24 lode.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS5-3-DS3-4-4683, from which
	Cor. No. 3 Sur. No. 4428 New Years Eve Extension #24 lode bears S. 33°35' E., 401.44 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #23 lode.
	Thence N. 33°35' W.
133.	Gulch, 2 ft. wide, course S. 70° W.
192.70	Cor. No. 4, identical with Cor. Nos. 2 and 3 Sur. No. 4428 New Years Eve Extension #24 and Copper John Extension #44 lodes, respectively.
	Found a 5/8 in. iron pin with copper cap, 3 ins. above the ground, firmly set, and with mound of stone alongside, mkd. X-NEX24-2-CJX44-3-4428, to which I added DS5-4-4683.
*	Thence N. 36°12'30" W.
45.	Road, 10 ft. wide, bears S. 50° W.
105.	Road, 10 ft. wide, bears S. 40° W.
526.06	Cor. No. 1, and place of beginning.
	D. S. MILL SITE 3
	At Cor. No. 1 of the D. S. Mill Site 3, identical with Cor. No. 1 of the D. S. Mill Site 1 of this survey.
8 - 2	

	BOTT HOT TOOS
FEET	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS3-1-DS1-1-4683; from which
	The 1/4 sec. cor. of secs. 9 and 10 bears N. 89°52'10" E., 1,668.62 ft. dist.; pre- viously described.
	Thence S. 2°22' E.
652.21	Cor. No. 2, identical with Cor. Nos. 4, 4, and 1 of the D. S. Mill Site 1, D. S. Mill Site 2 and D. S. Mill Site 4, respectively, of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS3-2-DS1-4-DS2-4-DS4-1-4683.
	Thence S. 89°52'10" W.
289.10	Cor. No. 3, identical with Cor. No. 3 of the D.S. Mill Site 4 of this survey, and on line 2-3, Sur. No. 4428 New Years Eve Extension #24 lode.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS3-3-DS4-3-4683; from which
	Cor. No. 3 Sur. No. 4428 New Years Eve Extension #24 lode bears S. 33°35' E., 322.64 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #23 lode.
	Thence N. 33°35' W.
78.80	Cor. No. 4, identical with Cor. No. 3 of the D.S. Mill Site 5 of this survey, and on line 2-3, Sur. No. 4428 New Years Eve Extension #24 lode.
	Thence N. 2°22' W.
154.40	Gulch, 2 ft. wide, course S. 70° W.
586.40	Cor. No. 5, identical with Cor. No. 2 of the D.S. Mill Site 5 of this survey.
	Thence N. 89°52'10" E.
330.00	Cor. No. 1, and place of beginning.
(e) E	D. S. MILL SITE 1
	Beginning at Cor. No. 1 of the D. S. Mill Site 1, identical with Cor. No. 1 of the D. S. Mill Site 3 of this survey, from which
	The 1/4 sec. cor. of secs. 9 and 10 bears N. 89°52'10" E., 1,668.62 ft. dist., previously described.
	Thence N. 89°52'10" E.

	0011121 1100 1009	_
335°.00	Cor. No. 2.	
A Maria and a	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS1-2-4683.	
e el justilia	Thence S. 2°22' E.	
652.21	Cor. No. 3, identical with Cor. No. 5 of the D.S. Mill Site 2 of this survey.	
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS1-3-DS2-5-4683.	
	Thence S. 89°52'10" W.	
330.00	Cor. No. 4, identical with Cor. Nos. 4, 1, and 2 of the D. S. Mill Site 2, D. S. Mill Site 4, and D. S. Mill Site 3, respectively, of this survey.	
	Thence N. 2°22' W.	
652.21	Cor. No. 1, and place of beginning.	
	D. S. MILL SITE 4	
1 - 1 - 1 - 1	Beginning at Cor. No. 1 of the D. S. Mill Site 4, identical with Cor. Nos. 2, 4, and 4 of the D. S. Mill Site 3, D. S. Mill Site 1, and D. S. Mill Site 2, respectively, of this survey, from which	
	The 1/4 sec. cor. of secs. 9 and 10 bears N. 68°14' E., 1,767.73 ft. dist.; previously described.	
100	Thence S. 2°22' E.	
465.42	Cor. No. 2, identical with Cor. No. 3 of the D.S. Mill Site 2 of this survey, and on line 2-3 New Years Eve Extension #23 lode, Sur. No. 4428	
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS4-2-DS2-3-4683; from which	
	Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 359.39 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #22 lode.	
	Thence N. 33°35' W.	
234.75	Intersect Cor. No. 2 Sur. No. 4428 New Years Eve Extension #23 lode, identical with Cor. No. 3 Sur. No. 4428 New Years Eve Extension #24 lode.	
557•39	Cor. No. 3, identical with Cor. No. 3 of the D.S. Mill Site 3 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #24 lode.	
	Thence N. 89°52'10" E.	

At Cor. No. 1 and place of beginning. D. S. MILL SITE 2 At Cor. No. 1 of the D. S. Mill Site 2, on lide 1 of the D. S. Mill Site 8 of this survey. Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-1-4 from which The ½ sec. cor. of secs. 9 and 10 bears N. 44°31'20" E., 1832.33 ft. dist.; previously described. Thence S. 88°25'20" W. Cor. No. 2, identical with Cor. No. 4 of the Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 1 Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this surhence N. 89°52'10" E. Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey. Thence S. 2°22' E.	
At Cor. No. 1 of the D. S. Mill Site 2, on li 4-1 of the D. S. Mill Site 8 of this survey. Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-1-4 from which The ½ sec. cor. of secs. 9 and 10 bears N. 44°31'20" E., 1832.33 ft. dist.; previously described. Thence S. 88°25'20" W. 210.53 Cor. No. 2, identical with Cor. No. 4 of the Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 1 Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this su Thence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	
4-1 of the D. S. Mill Site 8 of this survey. Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-1-4 from which The ½ sec. cor. of secs. 9 and 10 bears N. 44°31'20" E., 1832.33 ft. dist.; previously described. Thence S. 88°25'20" W. 210.53 Cor. No. 2, identical with Cor. No. 4 of the Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 1 Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this survey. Thence N. 89°52'10" E.	
Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-1-4 from which The \$ sec. cor. of secs. 9 and 10 bears N. 44°31'20" E., 1832.33 ft. dist.; previously described. Thence S. 88°25'20" W. 210.53 Cor. No. 2, identical with Cor. No. 4 of the Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 1 Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this sur Thence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	ne
24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-1-4 from which The ½ sec. cor. of secs. 9 and 10 bears N. 44°31'20" E., 1832.33 ft. dist.; previously described. Thence S. 88°25'20" W. 210.53 Cor. No. 2, identical with Cor. No. 4 of the Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 1 Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. 465.42 Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this survey. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	ong.
N. 44°31'20" E., 1832.33 ft. dist.; previously described. Thence S. 88°25'20" W. 210.53 Cor. No. 2, identical with Cor. No. 4 of the Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 l Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. 465.42 Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this survey. Thence N. 89°52'10" E.	one
Cor. No. 2, identical with Cor. No. 4 of the Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 1 Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-Ds2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. 465.42 Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this surhence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	
Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #23 1 Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. 465.42 Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this survey. Thence N. 89°52'l0" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	
24 ins. in the ground, and with mound of st alongside, with aluminum cap mkd. X-DS2-2-D 4-4683; from which Cor. No. 3 Sur. No. 4428 New Years Eve Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. 465.42 Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this su Thence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	
Extension #23 lode bears S. 33°35' E., 129.31 ft. dist.; identical with Cor. No 2 Sur. No. 4428 New Years Eve Extension #22 lode. Thence N. 33°35' W. 230.08 Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. 465.42 Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this su Thence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	one
Cor. No. 3, identical with Cor. No. 2 of the Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this su Thence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	•
Mill Site 4 of this survey, and on line 2-3 No. 4428 New Years Eve Extension #23 lode. Thence N. 2°22' W. Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this su Thence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	
Cor. No. 4, identical with Cor. Nos. 1, 2, an of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this su Thence N. 89°52'10" E. Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	
of the D. S. Mill Site 4, D. S. Mill Site 3 D. S. Mill Site 1, respectively, of this su Thence N. 89°52'10" E. 330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	
330.00 Cor. No. 5, identical with Cor. No. 3 of the Mill Site 1 of this survey.	and
Mill Site 1 of this survey.	
Thence S. 2°22' E.	D.S.
652.21 Cor. No. 1, and place of beginning.	
D. S. MILL SITE 8	
At Cor. No. 1 of the D. S. Mill Site 8, ident with Cor. No. 4 of the D. S. Mill Site 9 of this survey.	
Set an iron pin, 5/8ths ins. diam., 30 ins. 1 24 ins. in the ground, and mound of stone alongside, with aluminum cap mkd. X-DS8-1-D 4-4683; from which	
The ½ sec. cor. of secs. 9 and 10 bears N. 36°25'40" E., 1612.43 ft. dist.; previously described.	

FEET	Thence S. 1°05'50" E.
280.00	Gulch, 1 ft. wide, course S. 80° W.
635.28	Cor. No. 2, identical with Cor. No. 3 of the D. S. Mill Site 9, on line 4-1 of the D. S.
	Mill Site 14 of this survey.
6 0 1 50 H. E 6 0 1 50 H. E 7 1 2 2 2 2 3 3 4 4 4 4 4 4 4 4 4 4 4 4 4 4	Set an iron pin, 5/8ths ins. diam., 30 ins. long 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS8-2-DS9-3-4683.
- May 1.7-8	Thence S. 88°25'20" W.
135.56	<pre>Cor. No. 3, identical with Cor. No. 4 of the D. S. Mill Site 14 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #1 lode.</pre>
.P.U 500 33 1.	Set an iron pin, 5/8ths ins. diam., 30 ins. long
	24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS8-3-DS14-4-4683; from which
	Cor. No. 3 Sur. No. 4428 New Years Eve Extension #1 lode bears S. 33°35' E., 568.46 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 New Years Eve Extension #8 lode.
. 10 100 1	Thence N. 33°35' W.
25.68	Intersect Cor. Nos. 2 and 3 Sur. No. 4428 New Years Eve Extension #1 and New Years Eve Extension #22 lodes, respectively.
345.	Gulch, 2 ft. wide, course S. 60° W.
365.	Gulch, 2 ft. wide, course S. 15° W.
619.82	Intersect Cor. Nos. 2 and 3 Sur. No. 4428 New
	Years Eve Extension #22 lode, and New Years Eve Extension #23 lode, respectively.
749.13	Cor. No. 4, identical with Cor. No. 2 of the D. S. Mill Site 2 of this survey.
u : 20 I .	Thence N. 88°25'20" E.
210.53	Cor. No. 1 of the D. S. Mill Site 2 of this survey.
537.93	Cor. No. 1, and place of beginning.
	D. S. MILL SITE 9
0 2 1	At Cor. No. 1 of the D. S. Mill Site 9, identically with Cor. No. 1 of the D. S. Mill Site 10 of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. lon 24 ins. in the ground, and with mound of ston alongside, with aluminum cap mkd. X-DS9-1-DS1

	SURVEY No. 4683
FEET	The 1/4 sec. cor. of secs. 9 and 10 bears N. 26°04' E., 1434.22 ft. dist.; previously described.
	Thence S. 1°05°50" E.
635.28	Cor. No. 2, identical with Cor. Nos. 4, 4, and 1 of the D. S. Mill Site 10, D. S. Mill Site 12, and D. S. Mill Site 14, respectively, of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS9-2-DS10-4-DS12-4-DS14-1-4683.
	Thence S. 88°25'20" W.
327.40	Cor. No. 3, identical with Cor. No. 2 of the D.S. Mill Site 8, and on line 4-1 of the D. S. Mill Site 14 of this survey.
	Thence N. 1°05'50" W.
355.28	Gulch, 1 ft. wide, course S. 80° W.
635.28	Cor. No. 4, identical with Cor. No. 1 of the D.S. Mill Site 8 of this survey.
a =0	Thence N. 88°25'20" E.
327.40	Cor. No. 1, and place of beginning.
* 27	D. S. MILL SITE 10
W 2 3	J. J. MILL 3111 10
.d	Beginning at Cor. No. 1 of the D. S. Mill Site 10, identical with Cor. No. 1 of the D. S. Mill Site 9 of this survey.
V 11 25	Thence N. 88°25'20" E.
327.40	Cor. No. 2, identical with Cor. No. 4 of the D.S. Mill Site 11 of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS10-2-DS11-4-4683.
X	Thence S. 1°05'50" E.
635.28	Cor. No. 3, identical with Cor. No. 3 of the D. S. Mill Site 11, and on line 4-1 of the D. S. Mill Site 12 of this survey.
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS10-3-DS11-3-4683.
200	Thence S. 88°25'20" W.
100	

FEET	
327.40	Cor. No. 4, identical with Cor. Nos. 4, 1, and 2 of the D. S. Mill Site 12, D. S. Mill Site 14, and D. S. Mill Site 9, respectively, of this survey.
2	Thence N. 1°05'50" W.
635.28	Cor. No. 1, and place of beginning.
	D. S. MILL SITE 11
	At Cor. No. 1 of the D. S. Mill Site 11, identical with Cor. No. 1 of the D. S. Mill Site 15 of this survey.
ine).	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DSll-1-DSl5-1-4683; from which
	The 1/4 sec. cor. of secs. 9 and 10 bears N. 1°05'50" W., 1270.56 ft. dist.; previously described.
	Thence S. 1°05'50" E.
635.28	Cor. No. 2, identical with Cor. Nos. 4, 2, and 1, of the D. S. Mill Site 15, D. S. Mill Site 19, and D. S. Mill Site 12, respectively, of this survey.
2 112 .0	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS11-2-DS15-4-DS19-2-DS12-1-4683.
2525 V 25 25"	Thence S. 88°25'20" W.
327.40	Cor. No. 3, identical with Cor. No. 3 of the D. S. Mill Site 10, and on line 4-1 of the D. S. Mill Site 12 of this survey.
	Thence N. 1°05'50" W.
635.28	Cor. No. 4, identical with Cor. No. 2 of the D. S. Mill Site 10 of this survey.
	Thence N. 88°25'20" E.
327.40	Cor. No. 1, and place of beginning.
20 .	3 Cor. Mr. C. idersigal viol Cor. W
	D. S. MILL SITE 15
- 10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Beginning at Cor. No. 1 of the D. S. Mill Site 15, identical with Cor. No. 1 of the D. S. Mill Site 11 of this survey.
	Thence N. 89°33' E.
330.00	Cor. No. 2, identical with Cor. No. 3 of the D. S. Mill Site 16 of this survey.

4683

 	2011/21 1.01
FEET	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS15-2-DS16-3-4683.
	Thence S. 1°05'50" E.
635,28	Cor. No. 3, identical with Cor. No. 2 of the D. S. Mill Site 16, and on line 2-3 of the D. S. Mill Site 19 of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS15-3-
540	DS16-2-4683.
	Thence S. 89°33° W.
330.00	Cor. No. 4, identical with Cor. Nos. 2, 1 and 2, of the D. S. Mill Site 19, D. S. Mill Site 12, and D. S. Mill Site 11, respectively, of this survey.
	Thence N. 1°05'50" W.
635.28	Cor. No. 1, and place of beginning.
	D. S. MILL SITE 16
	At Cor. No. 1 of the D. S. Mill Site 16, identical with Cor. Nos. 1, 1 and 3 of the D. S. Mill Site 17, D. S. Mill Site 20, and D. S. Mill Site 19, respectively, of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS16-1-DS17-1-DS20-1-DS19-3-4683; from which
10 (10 (10 (10 (10 (10 (10 (10 (10 (10 (The cor. of secs. 9, 10, 15 and 16 bears S. 45°19'20" W., 910.93 ft. dist., an iron pin, 5/8 ins. diam., with copper cap, 6 ins. above the ground, firmly set and properly marked.
	Thence S. 89°33' W.
330.00	Cor. No. 2, identical with Cor. No. 3 of the D.S. Mill Site 15, and on line 2-3 of the D. S. Mill Site 19 of this survey.
	Thence N. 1°05'50" W.
635,28	Cor. No. 3, identical with Cor. No. 2 of the D.S. Mill Site 15 of this survey.
	Thence N. 89°33' E.
330.00	Cor. No. 4, identical with Cor. No. 2 of the D.S. Mill Site 17 of this survey.

FEET	1	
	Set an iron pin, 5/8ths ins. diam., 30 ins. long 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS16-4-DS17-2-4683.	
	Thence S. 1°05'50" E.	
635.28	Cor. No. 1, and place of beginning.	
	D. S. MILL SITE 17	
	Beginning at Cor. No. 1 of the D. S. Mill Site 17, identical with Cor. Nos. 1, 3, and 1 of the D. S. Mill Site 20, D. S. Mill Site 19 and D. S. Mill Site 16, respectively, of this survey.	
	Thence N. 1°05'50" W.	
635.28	Cor. No. 2, identical with Cor. No. 4 of the D. S. Mill Site 16 of this survey.	
1.	Thence N. 89°33° E.	
330.00	Cor. No. 3, identical with Cor. No. 4 of the D. S. Mill Site 18 of this survey.	
	Set an iron pin, 5/8ths ins. diam., 30 ins. long 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS17-3-DS18-4-4683.	
	Thence S. 1°05'50" E.	
635.28	Cor. No. 4, identical with Cor. Nos. 3, 4 and 2, of the D. S. Mill Site 18, D. S. Mill Site 21, and D. S. Mill Site 20, respectively, of this survey.	
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS17-4-DS18-3-DS21-4-DS20-2-4683.	
	Thence S. 89°33' W.	
330.00	Cor. No. 1, and place of beginning.	
	and a training gas and the effective teachers are also as a conservation of the conser	
	D. S. MILL SITE 18	
	At Cor. No. 1 of the D. S. Mill Site 18.	
Set an iron pin, 5/8ths ins. diam., 30 ins. 24 ins. in the ground, with mound of stone alongside, with aluminum cap mkd. X-DS18-1-4683; from which		
	The 1/4 sec. cor. of secs. 9 and 10 bears N. 46°59°40" W., 1847.23 ft. dist.; previously described. Thence S. 0°47°20" E.	

		SURVEY No. 4683
	ғеет 58.	Gulch, 5 ft. wide, course S. 35° E.
	597•	Gulch, 1 ft. wide, course N. 70° E.
	635.28	Cor. No. 2, identical with Cor. No. 5 of the D.S. Mill Site 21 of this survey.
	× 1 1	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS18-2-DS21-5-4683.
		Thence S. 89°33' W.
	57•	Gulch, 1 ft. wide, course N. 10° E.
	333.14	Cor. No. 3, identical with Cor. Nos. 4, 2 and 4, of the D. S. Mill Site 21, D. S. Mill Site 20, and D. S. Mill Site 17, respectively, of this survey.
		Thence N. 1°05'50" W.
	635.28	Cor. No. 4, identical with Cor. No. 3 of the D.S. Mill Site 17 of this survey.
1.00	0 400	Thence N. 89°33' E.
9	298.	Gulch, 5 ft. wide, course S. 35° E.
58. 597. 635.2 635.2 298. 336.5	336.57	Cor. No. 1, and place of beginning.
	eş.	D. S. MILL SITE 14
	* - *	Beginning at Cor. No. 1 of the D. S. Mill Site 14 identical with Cor. Nos. 2, 4 and 4 of the D. S. Mill Site 9, D. S. Mill Site 10, and D. S. Mill Site 12, respectively, of this survey, from which
		The cor. of secs. 9, 10, 15, and 16, bears S. 47°12'40" E., 908.52 ft. dist., prevously described.
		Thence S. 1°05'50" E.
	317.64	Cor. No. 2, identical with Cor. Nos. 3 and 3, of the D. S. Mill Site 12, and D. S. Mill Site 13, respectively, of this survey.
	3	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS14-2-DS12-3-DS13-3-4683.
		Thence S. 1°21'45" E.
	416.34	Cor. No. 3, identical with Cor. No. 2 of the D.S. Mill Site 13, of this survey, and with Cor. No. 1 Sur. No. 4428 Anticipation #5 lode, and on line 2-3 Sur. No. 4428 New Years Eve Extension #8 lode.
/*		Found an iron pin, 5/8ths ins. diam., with copper cap, 3 ins. above the ground, firmly set with
TT 1 1 1 1		

FEET	stone mound alongside, with copper cap mkd. X-A5-1-4428, to which I added DS14-3-DS13-2-4683.
	Thence N. 33°35' W.
297.07	Intersect Cor. Nos. 2 and 3 Sur. No. 4428 New Years Eve Extension #8 lode, and New Years Eve Extension #1 lode, respectively.
865.53	Cor. No. 4, identical with Cor. No. 3 of the D.S. Mill Site 8 of this survey, and on line 2-3 Sur. No. 4428 New Years Eve Extension #1 lode.
	Thence N. 88°25'20" E.
135.56	Cor. Nos. 2 and 3 of the D. S. Mill Site 8 and D. S. Mill Site 9, respectively, of this survey.
462.96	Cor. No. 1 and place of beginning.
6	
	D. S. MILL SITE 12
	Beginning at Cor. No. 1 of the D. S. Mill Site 12, identical with Cor. Nos. 2, 4, and 2 of the D. S. Mill Site 11, D. S. Mill Site 15, and D. S. Mill Site 19, respectively, of this survey; from which
	The cor. of secs. 9, 10, 15 and 16 bears S. 1°05'50" E., 635.28 ft. dist., previously described.
	Thence S. 1°05'50" E.
317.64	Cor. No. 2, identical with Cor. No. 4 of the D. S. Mill Site 13, and on line 1-2 of the D. S. Mill Site 19 of this survey.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS12-2-DS13-4-4683.
	Thence S. 88°25'20" W.
175.	Gulch, 1 ft. wide, course S. 10° W.
550.	Gulch, 2 ft. wide, course S. 5° E.
654.80	Cor. No. 3, identical with Cor. Nos. 3 and 2 of the D. S. Mill Site 13 and D. S. Mill Site 14, respectively, of this survey.
	Thence N. 1°05'50" W.
317.64	Cor. No. 4, identical with Cor. Nos. 1, 2 and 4, of the D. S. Mill Site 14, D. S. Mill Site 9, and D. S. Mill Site 10, respectively, of this survey.
	Thence N. 88°25'20" E.

	SURVEY NO. 4003
327.40	Cor. Nos. 3 and 3, of the D. S. Mill Site 10 and D. S. Mill Site 11, respectively, of this
survey.	
654.80	Cor. No. 1, and place of beginning.
0 ¥	D. S. MILL SITE 13
F	At Cor. No. 1 of the D. S. Mill Site 13, identical with Cor. No. 1 of the D. S. Mill Site 19 of this survey, and on line 1-2, Sur. No. 4428, Anticipation #5 lode.
1.	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DSl3-1-DSl9-1-4683, from which
	The cor. of secs. 9, 10, 15 and 16 bears S. 1°05'50" E., 184.02 ft. dist., previously described.
	Cor. No. 1 Sur. No. 4428 Anticipation #5 lode bears S. 65°05° W., 713.63 ft. dist.
	Thence S. 65°05' W.
290.	Gulch, 2 ft. wide, course S. 15° W.
585.	Gulch, 3 ft. wide, course from S. 20° W. to S. 40° W.
713.63	Cor. No. 2, identical with Cor. No. 3 of the D. S. Mill Site 14 of this survey, and with Cor. No. 1 Sur. No. 4428 Anticipation #5 lode and on line 2-3, Sur. No. 4428, New Years Eve Extension #8 lode.
	Thence N. 1°21'45" W.
416.34	Cor. No. 3, identical with Cor. Nos. 2 and 3, of the D. S. Mill Site 14 and D. S. Mill Site 12, respectively, of this survey.
	Thence N. 88°25'20" E.
104.80	Gulch, 2 ft. wide, course S. 5° E.
479.80	Gulch, 1 ft. wide, course S. 10° W.
654.80	Cor. No. 4, identical with Cor. No. 2 of the D. S. Mill Site 12, and on line 1-2 of the D. S. Mill Site 19 of this survey.
E 10 WH	Thence S. 1°05'50" E.
133.62	Cor. No. 1, and place of beginning.
ig	

	20KAFI MO. 4002	
FEET	D. S. MILL SITE 19	
,	Beginning at Cor. No. 1 of the D. S. Mill Site 19, identical with Cor. No. 1 of the D. S. Mill Site 13, of this survey, previously described, and on line 1-2 Sur. No. 4428, Anticipation #5 lode.	
	Thence N. 1°05'50" W.	
133.62	Cor. Nos. 4 and 2 of the D. S. Mill Site 13 and D. S. Mill Site 12, respectively, of this survey.	
451.26	Cor. No. 2, identical with Cor. Nos. 1, 2 and 4, of the D. S. Mill Site 12, D. S. Mill Site 11, and D. S. Mill Site 15, respectively, of this survey.	
4	Thence N. 89°33' E.	
330.00	Cor. Nos. 3 and 2 of the D. S. Mill Site 15 and D. S. Mill Site 16, respectively, of this survey.	
660.00		
	Thence S. 1°05'50" E.	
152.46	Cor. No. 4, identical with Cor. No. 5 of the D. S. Mill Site 20 of this survey, and on line 1-2, Sur. No. 4428, Anticipation #5 lode.	
9-9 -w	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS19-4-DS20-5-4683, from which	
, in	Cor. No. 2 Sur. No. 4428 Anticipation #5 lode bears N. 65°05' E., 65.00 ft. dist.	
la Pa	Thence S. 65°05' W.	
145.	Gulch, 4 ft. wide, course S. 75° E.	
721.40	Cor. No. 1, and place of beginning.	
	D. S. MILL SITE 20	
	Beginning at Cor. No. 1 of the D. S. Mill Site 20, identical with Cor. Nos. 3, 1, and 1 of the D. S. Mill Site 19, D. S. Mill Site 16, and D. S. Mill Site 17, respectively, of this survey.	
	Thence N. 89°33' E.	
330.00	Cor. No. 2, identical with Cor. Nos. 4, 3 and 4, of the D. S. Mill Site 17, D. S. Mill Site 18, and D. S. Mill Site 21, respectively, of this survey.	

FEET	
PECI	Thence S. 1°05'50" E.
548.43	Cor. No. 3, identical with Cor. No. 3 of the D. S. Mill Site 21 of this survey, and on line 2-3 Sur. No. 4428 Anticipation #5 lode.
50 S	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS20-3-DS21-3-4683; from which
	Cor. No. 3 Sur. No. 4428 Anticipation #5 lode bears S. 33°31' E., 89.55 ft. dist.; identical with Cor. No. 2 Sur. No. 4428 Anticipation #12 lode.
	Thence N. 33°31' W.
325.	Gulch, 2 ft. wide, course S. 75° E.
504.59	Cor. No. 4, identical with Cor. No. 2 Sur. No. 4428 Anticipation #5 lode.
	Found an iron pin, 5/8ths ins. diam., with copper cap, 3 ins. above the ground, firmly set with stone mound alongside, with copper cap mkd. X-A5-2-4428, to which I added DS20-4-4683.
	Thence S. 65°05' W.
65.00	Cor. No. 5, identical with Cor. No. 4, of the D. S. Mill Site 19, of this survey, and on line 1-2 Sur. No. 4428 Anticipation #5 lode.
· 18-m	Thence N. 1°05'50" W.
152.46	Cor. No. 1, and place of beginning.
	D. S. MILL SITE 21
	At Cor. No. 1 of the D. S. Mill Site 21 lode of this survey.
	Found an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, mound of stone alongside, with aluminum cap mkd. X-W16-S10-S15, to which I added DS21-1-4683; from which
	The cor. of secs. 9, 10, 15 and 16 bears N. 89°53'35" W., 1319.85 ft. dist.; previously described.
	Thence N. 89°53'35" W.
267.60	Cor. No. 2, on line 2-3 Sur. No. 4428 Anticipation #12 lode.
	Set an iron pin, 5/8ths ins. diam., 30 ins. long, 24 ins. in the ground, and with mound of stone alongside, with aluminum cap mkd. X-DS21-2-4683.
Ħ	Thence N. 33°31' W.

	FEET		
	26.28	Intersect Cor. Nos. 2 and 3, Sur. No. 4428,	
	20.20	Anticipation #12 and Anticipation #5 lodes,	
	the but g	respectively.	
	• § 1 mg		
	115.83	Cor. No. 3, identical with Cor. No. 3 of the	-
5		D. S. Mill Site 20 of this survey, and on line	
		2-3 Sur. No. 4428 Anticipation #5 lode.	
		Thence N. 1°05'50" W.	
5 6	Language Con-		
	548.43	Cor. No. 4, identical with Cor. Nos. 2, 4 and 3,	
		of the D. S. Mill Site 20, D. S. Mill Site 17,	
		and D. S. Mill Site 18, respectively, of this	ļ
		survey.	
		Thence N. 89°33' E.	
		Thence N. 69 33 E.	
	276.14	Gulch, 1 ft. wide, course N. 10° E.	
1000	2/0.14	Guich, 1 It. wide, course N. 10 H.	
	333.14	Cor. No. 5, identical with Cor. No. 2 of the	
	333.14	D. S. Mill Site 18 of this survey.	
	a .	B. B. Hill blee to of this survey.	
	1 As 5	Thence S. 0°47'20" E.	1
	648.04	Cor. No. 1, and place of beginning.	
	0.0.0.	502. 110. 2, and part 1	ļ
	4 5.	AREAS	
		· · · · · · · · Acres	1
		D. S. Mill Site 5 2.591	
•		D. S. Mill Site 3 4.906	
		D. S. Mill Site 1 4.937	ļ
		D. S. Mill Site 4 1.543	
		D. S. Mill Site 2 4.702	İ
		D. S. Mill Site 8 4.911	
		D. S. Mill Site 9 4.775	ļ
		D. S. Mill Site 10 4.775	
700 7772		D. S. Mill Site 11 4.775	
		D. S. Mill Site 15 4.812 D. S. Mill Site 16 4.812	
	1800 50	D. S. Mill Site 16 4.812 D. S. Mill Site 17 4.812	
		D. S. Mill Site 17 4.883	
		D. S. Mill Site 16 3.893	
	1 2 1 20 1	D. S. Mill Site 12 4.775	
		D. S. Mill Site 13 4.131	
	0.10	D. S. Mill Site 19 4.573	
		D. S. Mill Site 20 2.282	
	Ambie - Inc.	D. S. Mill Site 21 4.849	
	TE 10 8 10		
		LOCATION	ì
		0.4-0	
		This survey is located in the SEZ of Sec. 9,	
(4)		the SW\2SW\2 of Sec. 10, and the NE\2NE\2 of Sec.	Ì
		16, of T. 18 S., R. 12 E.; G. & S. R. M.	
		1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
. 3		The survey of all of the Mill Sites are iden-	
	0	tical with the locations as marked on the ground	1
		EXPENDITURES OR IMPROVEMENTS	
		I P on-	
		None.	
			1

FEET

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

Sur. No. 4428 Copper John Extension #44 lode: Cors. No. 2 & 3 are 5/8ths in. iron pins with copper caps, firmly set and properly marked. Line 2-3 was found to be S. 36°12'30" E., 594.76 ft., instead of S. 36°08'30" E., 594.76 ft., as approved. Lines 1-2 and 3-4 are shown as approved.

Sur. No. 4428 New Years Eve Extension #24 lode: Cors. No. 2 & 3 are 5/8ths in. iron pins with copper caps, firmly set and properly marked. Line 2-3 was found to be S. 33°35' E., 594.14 ft., instead of S. 33°31' E., 594.14 ft., as approved. Lines 1-2 and 3-4 are shown as approved.

Sur. No. 4428 New Years Eve Extension #23 lode: Cors. No. 2 & 3 are 5/8ths in. iron pins with copper caps, firmly set and properly marked. Line 2-3 was found to be S. 33°35' E., 594.14 ft., instead of S. 33°31' E., 594.14 ft., as approved. Lines 1-2 and 3-4 are shown as approved.

Sur. No. 4428 New Years Eve Extension #22 lode: Cor. No. 2 is a 5/8ths in. iron pin with copper cap, and Cor. No. 3 is a siliceous outcrop 36" x 48" x 48", both firmly set and properly marked. Line 2-3 was found to be S. 33°35' E., 594.14 ft., instead of S. 33°31' E., 594.14 ft., as approved. Lines 1-2 and 3-4 are shown as approved.

Sur. No. 4428 New Years Eve Extension #1 lode: Cor. No. 2 is a siliceous outcrop 36" x 48" x 48", and Cor. No. 3 is a 5/8ths in. iron pin with copper cap, both firmly set and properly marked. Line 2-3 was found to be S. 33°35' E., 594.14 ft., instead of S. 33°31' E., 594.14 ft., as approved. Lines 1-2 and 3-4 are shown as approved.

Sur. No. 4428 New Years Eve Extension #8 lode: Cor. No. 2 & Witness Cor. No. 3 are 5/8ths in. iron pins with copper caps, firmly set and properly marked. Line 2-3 was found to be S. 33°35' E., instead of S. 33°31' E., as approved. Line 1-2 shown as approved.

Sur. No. 4428 Anticipation #5 lode: Cors. No. 1, 2 & 3 are 5/8ths in. iron pins with copper caps, firmly set and properly marked. Line 1-2 was found to be N. 65°05' E., 1500.03 ft., instead of N. 65°05' E., 1500.00 ft., as approved. Line 2-3 is correct as approved. Line 3-4 is shown as approved.

Sur. No. 4428 Anticipation #12 lode: Cor. No. 2 is a 5/8ths in. iron pin with copper cap, firmly set and properly marked. Lines 1-2 and 2-3 are shown as approved.

The S'ly half of the line common to Secs. 9 and 10 was found to be N. 1°05'50" W., 2541.12 ft. instead of North 2640.0 ft., as approved.

The W'ly half of the line common to Secs. 10 and 15 was found to be N. 89°53'35" W., 2639.70 ft. instead of S. 89°54' W., 2637.36 ft., as approved.

FEET

The E'ly half of the line common to Secs. 9 and 16 was found to be S. 86°54'42" W., 2562.94 ft. instead of S. 89°52' W., 2634.72 ft., as approved.

FIELD ASSISTANTS

Name

P. B. Newlin, P. E.;
Jack Kesler;
John Stebbings;
David Newlin;
Jim Smith;
Douglas Smith;

Capacity

Transitman
Head Chainman
Chainman
Chainman
Chainman
Chainman
Chainman

GPO 839 - 785

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor		Date
Robert Lenon, P. E.		October 28, 1971
I HEREBY CERTIFY That in pursuance of an or	der received from the Bure	
of Duval Sierrita Corporation known as the Madaxplacaxxx mill site) D. S situated in Secs. 9, 10, and 16	19 70 , I have carefully e	gh. 5 and 8 through 21 , , Township 18 S. ,
This survey, designated as number 4683 been made in strict conformity with said order, the United States, and in specific manner describ	he Manual of Instructions fo	
I FURTHER CERTIFY That the labor expended Madax Kabaranax embraced in the said mining claim by claimant(s) grantors are fully stated in my report. The chara	or setent, location, and	location(s) itemized value are specified in
full detail. No portion of, or interest in, said lab cluded in the estimate of expenditures upon any		edited to this claim has been in-
	An a	
Patagonia, Arizona	7	Anon
(Location)	(Signatur	e of Mineral Surveyor)
		Arizona State Office Location Phoenix, Arizona Date
		April 27, 1972
executed by Robert Lenon	, X surveyed un un Meridian, in the State of	tions 9, 10 and 16 surveyed Township 18 S., Arizona, , Mineral Surveyor, ally examined and the necessary and the survey therein described
De T. Tallini	State Directo	r
Joe T. Fall (Authorized Signature)		(Title)
CERTIFICA	TE OF TRANSCRIPT	
I HEREBY CERTIFY That the foregoing transcr number is a true copy of the origin		above described mineral survey
(Authorized Signature)		(Title)
Title 18, U.S.C. section 1001, makes it a crime for an agency of the United States any false, fictitious, or frits jurisdiction.	y person knowingly and willfu audulent statements or repres	illy to make to any department or