

Form 3400-11
(September 1967)
(formerly 4-683)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Mineral Survey number	4780
State	Arizona
Land District	Arizona

FIELD NOTES

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Ramsey Mine Property
P. O. Box 2592
Tucson, Arizona 85702

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
R. & A.	9/1/23	8/30/74
R. & A. No. 2	3/5/24	8/30/74
R. & A. No. 3	3/5/24	8/30/74
R. & A. No. 4	3/5/24	8/30/74
R. and A. No. 5	12/26/67	8/30/74
R. and A. No. 6	12/26/67	8/30/74

Mining district Plomosa		County Yuma		
Section(Unsur.) 1, 2 & 12	Township 3 N.	Range 17 W.	Meridian G. & S.R.	Survey under order dated 3/25/74 & 9/30/74
Survey commenced 3/26/74		Survey completed 10/10/74		Name of Mineral Surveyor Harvey W. Smith

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FILE NO. 100-100000

Section
Township
Range

Section 10, Township 10N, Range 10E, T10N R10E, S44

LIST OF OWNERS OF LAND IN SECTION 10, T10N R10E, S44

Owner	Acres	Remarks
John Doe	10.00	Original owner
Jane Smith	5.00	Partial interest
Bob Johnson	5.00	Partial interest
...

FEET

This survey was made with a Lietz theodolite, Model TM-20C, No. 104847, having a horizontal circle 80 mm. in diam. and a vertical circle 70 mm. in diam. The circles are graduated in degrees and 20 minute increments. An optical micrometer, adjustable to the horizontal and vertical circles permits the reading of angles direct to 20-second accuracy and estimating to 5-second accuracy. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of horizontal-angles-right referred to the meridian determined by the following observation:

March 27, 1974, at Cor. No. 1 of the R. and A. No. 5 lode, in latitude $33^{\circ}37'48.8''$ N., and longitude $113^{\circ}58'39.3''$ W., elevation 1,700 ft. above sea level, and temperature 80° F., make a series of six altitude observations on the sun for azimuth at approximately equal time intervals, three each with the telescope in direct and reversed positions, observing opposite limbs of the sun, and reading the horizontal angle from a reference point about 500 ft. northeastward SW. to the sun.

Mean time of observation,
105th meridian standard
time = $3^{\text{h}}28^{\text{m}}27^{\text{s}}$ p.m.

Declination of sun at mean
time of observation = $2^{\circ}43'44.9''$ N.

Mean observed vertical angle
to sun's center = $40^{\circ}17'47''$

Mean horizontal angle from
reference point to sun's
center = $229^{\circ}29'25''$ S-W.

True bearing to reference
point = N. $11^{\circ}15'$ E.

The lines were measured with a Lufkin steel tape, 300 ft. in length, graduated every foot for 299 ft. and the remaining foot graduated to tenths and hundredths. The tape was compared with an Invar standard tape at the time of beginning the survey, and found to be correct.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of $14^{\circ}45'$ E.

FEET	Mineral Survey No. 4780
	<p style="text-align: center;">R. & A. LODE</p> <p>At Cor. No. 1 of the R. & A. lode, identical with Cor. No. 1 of the R. & A. No. 2 lode, Cor. No. 1 of the R. & A. No. 3 lode and Cor. No. 1 of the R. & A. No. 4 lode, all of this survey.</p> <p>Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A. 1 R.A.2 1 R.A.3 1 R.A.4 1 U.S.M.S. 4780; from which</p> <p style="padding-left: 40px;">The SW. cor. of sec. 31, T. 4 N., R. 16 W., Gila and Salt River Meridian, bears N. 51°57' 01" E., 6,923.73 ft. dist.; monumented with an iron post, 2 ins. diam., 18 ins. above ground, firmly set, with a brass cap properly mkd., and with a mound of stone at its base, 4 ft. wide and one ft. high.</p> <p style="padding-left: 40px;">A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. 43° 10' W.</p>
299.50	Lode line; discovery point bears N. 46°50' W., 200.0 ft. dist.
599.50	<p>Cor. No. 2, identical with Cor. No. 4 of the R. & A. No. 3 lode of this survey.</p> <p>Set an iron post, 24 ins. long, 3/4 ins. diam., 12 ins. in the ground in a concrete and rock base with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.2 R.A.3 4 U.S.M.S. 4780; from which</p> <p style="padding-left: 40px;">A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N. 46°50' W.</p>
1,499.50	<p>Cor. No. 3, identical with Cor. No. 2 of the R. and A. No. 5 lode of this survey.</p> <p>Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.3 R.A.5 2 U.S.M.S. 4780; from which</p>

FEET		
	<p>A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N. 43° 10' E.</p>	
300.00	Lode line; discovery point bears S. 46°50' E., 1299.5 ft. dist.	
545.	Center of unimproved road, 12 ft. wide, bears N. 22° E. and S. 25° W.	
599.50	<p>Cor. No. 4, identical with Cor. No. 2 of the R. & A. No. 2 lode, Cor. No. 1 of the R. and A. No. 5 lode and Cor. No. 1 of the R. and A. No. 6 lode, all of this survey.</p> <p>Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A. 4 R.A.2 2 R.A.5 1 R.A.6 1 U.S.M.S. 4780; from which</p> <p>The SW. cor. of sec. 31, bears N. 63°39'19" E., 7,304.62 ft. dist.; heretofore described.</p> <p>A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S. 46°50' E.</p>	
95.	Center of unimproved road, 16 ft. wide, bears N. 35° E. and S. 35° W.	
1,114.50	Center of unimproved road, 16 ft. wide, bears N. 66° E. and S. 66° W.	
1,499.50	Cor. No. 1, and place of beginning.	
	<p style="text-align: center;">R. & A. No. 2 LODE</p> <p>Beginning at Cor. No. 1 of the R. & A. No. 2 lode, identical with Cor. No. 1 of the R. & A. lode, Cor. No. 1 of the R. & A. No. 3 lode and Cor. No. 1 of the R. & A. No. 4 lode, all of this survey.</p> <p>Thence N. 46° 50' W.</p>	
385.	Center of unimproved road, 12 ft. wide, bears N. 66° E. and S. 66° W.	
1,404.50	Center of unimproved road, 12 ft. wide, bears N. 35° E. and S. 35° W.	

(This form bound on left side)

FEET	
1,499.50	<p>Cor. No. 2, identical with Cor. No. 4 of the R. & A. lode, Cor. No. 1 of the R. and A. No. 5 lode and Cor. No. 1 of the R. and A. No. 6 lode, all of this survey.</p> <p style="text-align: center;">Thence N. 43° 10' E.</p>
300.00	<p>Lode line; discovery point bears S. 46°50' E., 10.0 ft. dist.</p>
330.	<p>Center of unimproved road, 12 ft. wide, bears N. 5° E. and S. 5° W.</p>
599.50	<p>Cor. No. 3, identical with Cor. No. 4 of the R. and A. No. 6 lode of this survey.</p> <p>Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.2 3 R.A.6 4 U.S.M.S. 4780; from which</p> <p style="text-align: center;">A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. 46°50' E.</p>
1,280.	<p>Center of unimproved road, 12 ft. wide, bears N. 75° E. and S. 75° W.</p>
1,499.50	<p>Cor. No. 4, identical with Cor. No. 2 of the R. & A. No. 4 lode of this survey.</p> <p>Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.2 4 R.A.4 2 U.S.M.S. 4780; from which</p> <p style="text-align: center;">A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. 43° 10' W.</p>
299.50	<p>Lode line; discovery point bears N. 46°50' W., 1,489.5 ft. dist.</p>
599.50	<p>Cor. No. 1, and place of beginning.</p>

FEET		
	R. & A. No. 3 LODE	
	Beginning at Cor. No. 1 of the R. & A. No. 3 lode, identical with Cor. No. 1 of the R. & A. lode, Cor. No. 1 of the R. & A. No. 2 lode and Cor. No. 1 of the R. & A. No. 4 lode, all of this survey.	
	Thence S. 46°50' E.	
1,024.50	Left bank of local drainage, 30 ft. wide, course North.	
1,499.50	Cor. No. 2, identical with Cor. No. 4 of the R. & A. No. 4 lode of this survey.	
	Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.3 2 R.A.4 4 U.S.M.S. 4780; from which	
	A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.	
	No local bearing objects or bearing trees available.	
	Thence S. 43°10' W.	
299.50	Lode line; discovery point bears N. 46°50' W., 939.5 ft. dist.	
599.50	Cor. No. 3.	
	Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground, in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.3 3 U.S.M.S. 4780; from which	
	A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.	
	No local bearing objects or bearing trees available.	
	Thence N. 46°50' W.	
1,499.50	Cor. No. 4, identical with Cor. No. 2 of the R. & A. lode of this survey.	
	Thence N. 43°10' E.	
300.00	Lode line; discovery point bears S. 46°50' E., 560.0 ft. dist.	
599.50	Cor. No. 1, and place of beginning.	

FEET	
	R. & A. No. 4 LODE
	Beginning at Cor. No. 1 of the R. & A. No. 4 lode, identical with Cor. No. 1 of the R. & A. lode, Cor. No. 1 of the R. & A. No. 2 lode and Cor. No. 1 of the R. & A. No. 3 lode, all of this survey.
	Thence N. 43° 10' E.
300.00	Lode line; discovery point bears S. 46° 50' E., 700.0 ft. dist.
599.50	Cor. No. 2, identical with Cor. No. 4 of the R. & A. No. 2 lode of this survey.
	Thence S. 46° 50' E.
560.	Center of unimproved road, 12 ft. wide, bears North and South.
965.	Left bank of local drainage, 30 ft. wide, course N. 54° E.
1,499.50	Cor. No. 3.
	Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.4 3 U.S.M.S. 4780; from which
	A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.
	No local bearing objects or bearing trees available.
	Thence S. 43° 10' W.
299.50	Lode line; discovery point bears N. 46° 50' W., 799.5 ft. dist.
500.	Center of unimproved road, 12 ft. wide, bears N. 50° W. and S. 50° E.
535.	Right bank of local drainage, 30 ft. wide, course N. 15° W.
599.50	Cor. No. 4, identical with Cor. No. 2 of the R. & A. No. 3 lode of this survey.
	Thence N. 46° 50' W.
445.	Right bank of local drainage, 30 ft. wide, course North.
1,499.50	Cor. No. 1, and place of beginning.

FEET		
	R. and A. No. 5 LODE	
	Beginning at Cor. No. 1 of the R. and A. No. 5 lode, identical with Cor. No. 4 of the R. & A. lode, Cor. No. 2 of the R. & A. No. 2 lode and Cor. No. 1 of the R. and A. No. 6 lode, all of this survey.	
	Thence S. 43° 10' W.	
54.50	Center of unimproved road, 12 ft. wide, bears N. 22° E. and S. 25° W.	
299.50	Lode line; discovery point bears N. 37° 30' W., 400 ft. dist.	
599.50	Cor. No. 2, identical with Cor. No. 3 of the R. & A. lode of this survey.	
	Thence N. 37° 30' W.	
1,499.50	Cor. No. 3.	
	Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.5 3 U.S.M.S. 4780; from which	
	A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.	
	No local bearing objects or bearing trees available.	
	Thence N. 43° 10' E.	
300.00	Lode line; discovery point bears S. 37° 30' E., 1,099.5 ft. dist.	
599.50	Cor. No. 4, identical with Cor. No. 2 of the R. and A. No. 6 lode of this survey.	
	Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.5 4 R.A.6 2 U.S.M.S. 4780; from which	
	A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.	
	No local bearing objects or bearing trees available.	
	Thence S. 37° 30' E.	
1,044.50	Center of unimproved road, 12 ft. wide, bears N. 11° E. and S. 11° W.	
1,109.50	Left bank of local drainage, 30 ft. wide, course N. 58° E.	

(This form bound on left side)

FEET	
1,334.50	Left bank of local drainage, 30 ft. wide, course N. 6° W.
1,349.50	Center of unimproved road, 12 ft. wide, bears N. 60° E. and S. 70° W.
1,484.50	Center of unimproved road, 12 ft. wide, bears N. 20° E. and S. 20° W.
1,499.50	Cor. No. 1, and place of beginning.
<p>R. and A. No. 6 LODE</p> <p>Beginning at Cor. No. 1 of the R. and A. No. 6 lode, identical with Cor. No. 4 of the R. & A. lode, Cor. No. 2 of the R. & A. No. 2 lode and Cor. No. 1 of the R. and A. No. 5 lode, all of this survey.</p> <p>Thence N. 37°30' W.</p>	
15.	Center of unimproved road, 12 ft. wide, bears N. 20° E. and S. 20° W.
135.	Right bank of local drainage, 30 ft. wide, course N. 6° W.
150.	Center of unimproved road, 12 ft. wide, bears N. 60° E. and S. 70° W.
360.	Right bank of local drainage, 30 ft. wide, course N. 58° E.
455.	Center of unimproved road, 12 ft. wide, bears N. 11° E. and S. 11° W.
1,499.50	Cor. No. 2, identical with Cor. No. 4 of the R. and A. No. 5 lode of this survey.
<p>Thence N. 43° 10' E.</p>	
300.00	Lode line; discovery point bears S. 37°30' E., 1,099.5 ft. dist.
599.50	Cor. No. 3.
<p>Set an iron post, 24 ins. long, 3/4 in. diam., 12 ins. in the ground in a concrete and rock base, with a brass cap, 2 ins. diam., firmly secured to the iron post, mkd. X R.A.6 3 U.S.M.S. 4780; from which</p> <p style="text-align: center;">A wood post, 4" x 4", 4 ft. above ground stands adjacent to the iron post.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. 37°30' E.</p>	

FEET	
645.	Center of unimproved road, 12 ft. wide, bears N. 10° E. and S. 15° W.
1,135.	Left bank of local drainage, 30 ft. wide, course N. 25° E.
1,222.	Center of unimproved road, 12 ft. wide, bears N. 15° E. and S. 15° W.
1,499.50	Cor. No. 4, identical with Cor. No. 3 of the R. & A. No. 2 lode of this survey. Thence S. 43°10' W.
269.50	Center of unimproved road, 12 ft. wide, bears N. 5° E. and S. 5° W.
299.50	Lode line; discovery point bears N. 37°30' W., 400.0 ft. dist.
599.50	Cor. No. 1, and place of beginning.
Mineral Survey No. 4780	
Areas	
	Acres
Total area, R. & A. lode	20.637
Total area, R. & A. No. 2 lode	20.637
Total area, R. & A. No. 3 lode	20.637
Total area, R. & A. No. 4 lode	20.637
Total area, R. and A. No. 5 lode	20.364
Total area, R. and A. No. 6 lode	20.364
Location	
<p>This survey is located in Sections 1, 2 and 12, all unsurveyed, T. 3 N., R. 17 W., Gila & Salt River Meridian.</p> <p>The survey of the R. & A., R. & A. No. 2, R. & A. No. 3, R. & A. No. 4, R. and A. No. 5 and R. and A. No. 6 lodes is identical with the respective amended location as marked on the ground.</p>	
Expenditures	
<p>The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows:</p>	
No. 1.	<p>The discovery point of the R. & A. lode is on the lode line, 200. ft. from a point on line 1-2, 299.5 ft. from Cor. No. 1.</p> <p>Value, none.</p>
No. 2	<p>An untimbered shaft, 4 x 6 ft. in size, of which the SW cor. of the collar bears N. 76°30' E., 435. ft. dist. from Cor. No. 3 of the R. & A.</p>

(This form bound on left side)

FEET	
	<p>lode; inclined at 72°, bearing East. Depth unknown. Value, \$500.</p>
No. 1	<p>The discovery point of the R. & A. No. 2 lode is on the lode line; 10. ft. from a point on line 2-3, 300. ft. from Cor. No. 2. Value, none.</p>
No. 2	<p>An adit, 4 x 6 ft. in size, the portal of which bears N. 37°30' W., 470. ft. from Cor. No. 1 of the R. & A. No. 2 lode; running N. 15° E., length unknown. Value, \$200.</p>
No. 3	<p>An untimbered shaft, 5 x 16 ft. in size, of which the SE cor. of the collar bears N. 39°30' W., 420. ft. from Cor. No. 1 of the R. & A. No. 2 lode; 18 ft. deep. Value, \$500.</p>
No. 4	<p>A timbered shaft, 4 x 6 ft. in size, of which the SE cor. of the collar bears N. 39° W., 455. ft. from Cor. No. 1 of the R. & A. No. 2 lode; inclined 78°, bearing N. 65° E., depth 157 ft. Value, \$15,700.</p>
No. 5	<p>An adit, 4 x 7 ft. in size, the portal of which bears N. 37° W., 415. ft. from Cor. No. 1 of the R. & A. No. 2 lode; runs N. 40° W., 50 ft. to connect to Improvements No. 3 and 4 on the 18 ft. level of those shafts. Value, \$1,000.</p>
No. 1	<p>The discovery point of the R. & A. No. 3 lode is on the lode line, 560. ft. from a point on line 4-1, 300. ft. from Cor. No. 4. Value, none.</p>
No. 1	<p>The discovery point of the R. & A. No. 4 lode is on the lode line, 700. ft. from a point on line 1-2, 300. ft. from Cor. No. 1. Value, none.</p>
No. 2	<p>A pit, 4 ft. wide, the SE cor. of which bears N. 12° E., 322. ft. from Cor. No. 4 of the R. & A. No. 4 lode; 7 ft. deep, running N. 35° W., 15 ft. Value, \$250.</p>
No. 1	<p>The discovery point of the R. and A. No. 5 lode is on the lode line, 400. ft. from a point on line 1-2, 299.5 ft. from Cor. No. 1. Value; none.</p>

FEET	
No. 1	<p>The discovery point of the R. and A. No. 6 lode is on the lode line, 400. ft. from a point on line 4-1, 299.5 ft. from Cor. No. 4. Value, none.</p> <p>An interest in a common improvement described as follows:</p> <p>A timbered shaft, 6 x 6 ft. in size, of which the NW cor. of the collar bears S. 1°30' W., 235. ft. from Cor. No. 4 R. & A. lode; inclined at 60°, 448 ft. deep, bearing N. 74° E. From this shaft, 12 levels have been driven along the strike of the vein, approximately N. 20° W. and S. 20° E. for varying distances to mine the ore. The longest drift is the 294 level with a length of 210 ft. Value of shaft, drifts and stopes, \$100,000. Value of one-fourth interest, \$25,000.</p> <p>This improvement was made for the development of the R. & A. lode, R. & A. No. 2 lode, R. and A. No. 5 lode and the R. and A. No. 6 lode which are all contiguous lodes owned in common of this survey, within the range of benefit of this shaft and associated levels.</p> <p>The mineralized structure associated with this shaft is best developed by these workings.</p> <p>Five hundred dollars or over has been expended in this improvement in such a manner as tends to the development of each of the stated lodes of this survey subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-fourth interest in its value is hereby credited to each of said lodes.</p> <p>No portion of or interest in this improvement has been credited heretofore as patent expenditure to any lode claim.</p> <p style="text-align: center;">OTHER IMPROVEMENTS</p> <p>A wooden ore bin, 10 x 10 ft. in size, 12 ft. high, the NE cor. of which bears S. 12°30' W., 252. ft. from Cor. No. 4 of the R. & A. lode. Claimant herein.</p> <p>A corrugated steel building, the NW cor. of which bears S. 5°30' E., 170. ft. from Cor. No. 4 of the R. & A. lode; 12 x 14 ft. in size; the long sides bear N. 75° E. Claimant herein.</p> <p>A corrugated steel building, the NW cor. of which bears S. 1°30' E., 175. ft. from Cor. No. 4 of the R. & A. lode; 6 x 10 ft. in size; the long sides bear N. 75° E. Claimant herein.</p>

(This form bound on left side)

FEET	<p>A corrugated steel building, the NW cor. of which bears S. 17° E., 195. ft. from Cor. No. 4 of the R. & A. lode; 12 x 14 ft. in size; the long sides bear N. 10° W. Claimant herein.</p> <p>A corrugated steel building, the NE cor. of which bears S. 4° W., 260. ft. from Cor. No. 4 of the R. & A. lode; 14 x 16 ft. in size; the long sides bear S. 15° E. Claimant herein.</p> <p style="text-align: center;">OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA</p> <p style="text-align: center;">None</p>						
	<p>MEMORANDUM</p> <p style="text-align: center;">None</p>						
	<p style="text-align: center;">FIELD ASSISTANTS</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; width: 60%;">Name</th> <th style="text-align: left; width: 40%;">Capacity</th> </tr> </thead> <tbody> <tr> <td>Kent Miller</td> <td>Assistant-Instrument Man</td> </tr> <tr> <td>Wayne Smith</td> <td>Chainman-Axeman</td> </tr> </tbody> </table>	Name	Capacity	Kent Miller	Assistant-Instrument Man	Wayne Smith	Chainman-Axeman
Name	Capacity						
Kent Miller	Assistant-Instrument Man						
Wayne Smith	Chainman-Axeman						

Form 3400-8
(August 1967)
(formerly 4-686)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor Harvey W. Smith	Date October 25, 1974
--	---------------------------------

I HEREBY CERTIFY That in pursuance of an order received from the Chief, Branch of Cadastral Survey, Bureau of Land Management, at Phoenix, Arizona, dated March 25, 1974, and Sept. 30, 1974, I have carefully executed the survey of the claim of Ramsey Mine Property known as the (lode, placer, or mill site) R. & A., R. & A. Nos. 2, 3 & 4 and R. and A. Nos. 5 & 6 lodes, situated in Yuma County, Secs. 1, 2 & 12 (Unsurveyed), Township 3 N., Range 17 W., Gila and Salt River Meridian, in the State of Arizona.

This survey, designated as number 4780, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.


I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) lode location(s) embraced in the said mining claim by claimant(s) or their grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Scottsdale, Arizona (Location)	 (Signature of Mineral Surveyor)
--	---

CERTIFICATE OF APPROVAL

Office Arizona State Office
Location Phoenix, Arizona
Date April 6, 1976

The foregoing field notes of mineral survey number 4780, in Section 1, 2 & 12, Range 17 W., Gila and Salt River Meridian, in the State of Arizona, surveyed unsurveyed Township 3 N., executed by Harvey W. Smith Amended Sept. , Mineral Surveyor, under order dated March 25, 1974 & 30, 1974, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

 Boyd S. Owens (Authorized Signature)	Chief, Branch of Cadastral Survey (Title)
---	---

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

The first part of the document discusses the importance of maintaining accurate records of all transactions. It emphasizes that every entry should be supported by a valid receipt or invoice. This ensures transparency and allows for easy verification of the data.

Furthermore, it is noted that the records should be kept in a secure and accessible format. Regular backups are recommended to prevent data loss in the event of a system failure or disaster.

In addition, the document highlights the need for consistent data entry. Standardized formats and codes should be used throughout the system to avoid confusion and errors. Training for staff on these protocols is essential for successful implementation.

Finally, the document concludes by stating that the primary goal of this system is to provide reliable and timely information to management. This will enable them to make informed decisions based on accurate data.

The following table provides a summary of the key components and their functions within the system. Each component is designed to streamline the data collection and reporting process.

Component	Description	Functionality
Data Entry Module	Interface for inputting transaction data	Allows for quick and accurate data entry with validation checks
Reporting Engine	Generates various financial reports	Provides customizable reports for different levels of management
Database System	Stores all transaction records	Ensures data integrity and security through encryption and access controls
User Management	Controls access to the system	Assigns roles and permissions to different users

The implementation of this system is expected to significantly improve the efficiency of the accounting department. By automating many of the manual tasks, staff can focus on more strategic activities.

It is anticipated that the system will also reduce the risk of human error and improve the overall accuracy of the financial statements.

The document concludes with a call to action, urging all relevant departments to cooperate fully in the rollout of the new system. A detailed project plan and timeline are attached for reference.

Thank you for your attention and support in this important initiative.

UNITED STATES DEPARTMENT OF THE INTERIOR 9605 (956)
BUREAU OF LAND MANAGEMENT M.S. 4780
ARIZONA STATE OFFICE

NOTICE OF CANCELLATION OF MINERAL SURVEY

The R. & A. No. 3, R. & A. No. 4, R. and A. No. 5, and R. and A. No. 6 lodes, Mineral Survey No. 4780, located in sections 1, 2 and 12, Township 3 North, Range 17 West, Gila and Salt River Meridian, Arizona, are hereby canceled.


These claims have not been filed with the Arizona State Office, Bureau of Land Management, in accordance with Section 314, 90 STAT. 2769, (43 U.S.C. 1744).

This cancellation was necessitated to clear the record.

The Mineral Survey Plat should be noted as follows:

"R. & A. No. 3, R. & A. No. 4, R. and A. No. 5, and R. and A. No. 6 lodes, M.S. 4780, were canceled March 11, 2002, by memo 9605 (956) M.S. 4780, which is now a part of the original field notes."

March 11, 2002
Date



Chief Cadastral Surveyor of Arizona

