

Form 3400-11
(September 1967)
(formerly 4-683)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Mineral Survey number
4802

State
Arizona

Land District

Of the Survey of the Mining Claim of *(name and address of Claimant)*

Jerry Glazier & Leon Glazier
P. O. Box 752
Hurricane, Utah 84737

Known as the *(name of group, if any)*

CONSISTING OF LOCATIONS NAMED AND LOCATED AS FOLLOWS

NAME OF LOCATION	DATE	
	LOCATED	AMENDED
Vanderbilt #17	11/25/69	
Wall Street #1	7/1/58	

Mining district Bentley			County Mohave	
Section 16	Township 33 N.	Range 14 W.	Meridian G & SR.	Survey under order dated Sept. 21, 1979
Survey commenced Nov. 25, 1979		Survey completed Dec. 5, 1979	Name of Mineral Surveyor William P. Smith	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

WATER RIGHTS

Section
Township
Range

Section 10, Township 10N, Range 10E, T10N R10E S10E

Section 10, Township 10N, Range 10E, T10N R10E S10E

Section	Acres	Water Right	Priority	Other
10	360			
11	360			
12	360			
13	360			
14	360			
15	360			
16	360			
17	360			
18	360			
19	360			
20	360			
21	360			
22	360			
23	360			
24	360			
25	360			
26	360			
27	360			
28	360			
29	360			
30	360			
31	360			
32	360			
33	360			
34	360			
35	360			
36	360			
37	360			
38	360			
39	360			
40	360			
41	360			
42	360			
43	360			
44	360			
45	360			
46	360			
47	360			
48	360			
49	360			
50	360			
51	360			
52	360			
53	360			
54	360			
55	360			
56	360			
57	360			
58	360			
59	360			
60	360			
61	360			
62	360			
63	360			
64	360			
65	360			
66	360			
67	360			
68	360			
69	360			
70	360			
71	360			
72	360			
73	360			
74	360			
75	360			
76	360			
77	360			
78	360			
79	360			
80	360			
81	360			
82	360			
83	360			
84	360			
85	360			
86	360			
87	360			
88	360			
89	360			
90	360			
91	360			
92	360			
93	360			
94	360			
95	360			
96	360			
97	360			
98	360			
99	360			
100	360			

Section 10, Township 10N, Range 10E, T10N R10E S10E

FEET

This survey was made with a Geotec TH-20 theodolite No. 723055, having 90 mm horizontal glass and a vertical glass of 74 mm with a micro reading each of 20 seconds of arc; the eyepiece is equipped with colored shade for making direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian determined by the following observation:

November 25, 1979, at Cor. No. 2 of the Wall Street #1 lode, in latitude $36^{\circ}15'38''$ N., and longitude $113^{\circ}47'52''$ W., elevation 4,560 ft. above sea level, and temperature 70° F., make a series of eight altitude observations on the sun for azimuth at approximately equal time intervals, four each with the telescope in direct and reversed positions observing opposite limbs of the sun and reading the horizontal angle from Cor. No. 1 of Wall Street #1 lode, westward (SW) to the sun.

Mean time of observation 10⁵th
meridian standard time - 2^h 52^m p. m.
Declination of sun at mean time
of observation - $20^{\circ}46'05''$ S.
Mean observed vertical angle
to sun's center - $22^{\circ}56'$
Mean horizontal angle from
Cor. No. 1 of Wall Street #1
lode to sun's center - $96^{\circ}35'$ W-S
True bearing of line 1-2
Wall Street #1 lode - N. $45^{\circ}20'$ W.

The lines were measured with a Tellurometer CD6 Electro-Optic System of Distance Measurement. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of 15° E.

VANDERBILT #17 LODE

At Cor. No. 1 of the Vanderbilt #17 lode.

A steel pipe, 2 ins. diam., 24 ins. above ground, firmly set in a mound of stone; in top of pipe, set an aluminum cap, mkd. V17-1-4802; from which

FEET	
	<p>The $\frac{1}{4}$ cor. of secs. 9 and 16, T. 33 N., R. 14 W., G. and SRM., bears N. $20^{\circ}23'$ E., 1573.7 ft. dist.; monumented with an iron post, firmly set, with brass cap properly marked as per official record.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. $45^{\circ}20'$ E.</p>
300.0	Point for center line not monumented; from this point, the point of discovery bears S. $44^{\circ}40'$ W., 765.0 ft. dist., which point of discovery is an open cut.
402.0	Center of road, 8 ft. wide, bears N. 67° W. and S. 67° E.
600.0	<p>Cor. No. 2, identical with Cor. No. 1 Wall Street #1 lode of this survey.</p> <p>A steel pipe, 2 ins. diam., 24 ins. above ground, firmly set in a mound of stone; in top of pipe, set an aluminum cap, mkd. V17-2 WSl-1-4802.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. $44^{\circ}40'$ W.</p> <p>Along line 1-4 Wall Street #1 lode of this survey.</p>
910.0	Bottom of canyon, drains N. 89° E.
1500.0	<p>Cor. No. 3, identical with Cor. No. 4 Wall Street #1 lode of this survey.</p> <p>A steel pipe, 2 ins. diam., 24 ins. above ground, firmly set in a mound of stone; in top of pipe, set an aluminum cap, mkd. V17-3 WSl-4-4802.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N. $45^{\circ}20'$ W.</p>
600.0	<p>Cor. No. 4.</p> <p>A steel pipe, 2 ins. diam., 24 ins. above ground, firmly set in a mound of stone; in top of pipe, set an aluminum cap, mkd. V17-4-4802.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N. $44^{\circ}40'$ E.</p>

FEET	
305.0	Bottom of canyon, drains S. 52° E.
1368.0	Center of road, 8 ft. wide, bears N. 66° W. and S. 66° E.
1500.0	Cor. No. 1 and place of beginning.
WALL STREET #1 LODE	
Beginning at Cor. No. 1 of the Wall Street #1 lode, identical with Cor. No. 2 Vanderbilt #17 lode of this survey; from which	
The $\frac{1}{4}$ cor. of secs. 9 and 16, T. 33 N., R. 14 W., G. and SRM., bears N. 3°40' E., 1900.8 ft. dist.; previously described.	
Thence S. 45°20' E.	
300.0	Point for center line not monumented; from this point, the point of discovery bears S. 44°40' W., 750.0 ft. dist., monumented by a steel post.
600.0	Cor. No. 2.
A steel pipe, 2 ins. diam., 24 ins. above ground, firmly set in a mound of stone; in top of pipe, set an aluminum cap, mkd. WSl-2-4802.	
No local bearing objects or bearing trees available.	
Thence S. 44°40' W.	
580.0	Bottom of canyon, drains N. 82° E.
1500.0	Cor. No. 3.
A steel pipe, 2 ins. diam., 24 ins. above ground, firmly set in a mound of stone; in top of pipe, set an aluminum cap, mkd. WSl-3-4802.	
No local bearing objects or bearing trees available.	
Thence N. 45°20' W.	
600.0	Cor. No. 4, identical with Cor. No. 3 Vanderbilt #17 lode of this survey.
Thence N. 44°40' E.	
590.0	Bottom of canyon, drains N. 89° E.
1500.0	Cor. No. 1 and place of beginning.

FEET	AREAS
	<p style="text-align: right;">Acres</p> Total area, Vanderbilt #17 lode--20.661 Total area, Wall Street #1 lode--20.661
	LOCATION
	<p>This survey is located in the NW$\frac{1}{4}$, NE$\frac{1}{4}$ and SW$\frac{1}{4}$ of sec. 16, T. 33 N., R. 14 W., Gila and Salt River Meridian.</p>
	<p>The survey of the Vanderbilt #17 and Wall Street #1 lodes are identical with the corners of the location or amended location as marked on the ground.</p>
	EXPENDITURES
	<p>The improvements and the value of the labor and improvements made upon or for the benefit of each of the lode locations embraced in said mining claim by the claimant or its grantors are as follows:</p>
No. 1	<p>The discovery cut of the Vanderbilt #17 lode, the center of which being the discovery point, bears S. 44°40' W., 765 ft. from the center of line 1-2, 20 ft. wide, 4 ft. deep, runs S. 44° W., 20 ft. and N. 44° E., 20 ft. Value, \$100.</p>
No. 1	<p>The discovery point of the Wall Street #1 lode, bears S. 44°40' W., 750 ft. from the center of line 1-2, monumented by a steel pipe in a mound of stone. No value.</p>
No. 2	<p>A shaft, the center of which bears S. 67°15' W., 610 ft. from Cor. No. 2 Wall Street #1 lode, 8 x 8 ft. in size, 10 ft. deep. Value, \$200.</p>
No. 3	<p>A shaft, the center of which bears S. 69°15' W., 585 ft. from Cor. No. 2 Wall Street #1 lode, 6 x 8 ft. in size, 12 ft. deep. Value, \$220.</p>
No. 4	<p>A shaft, the center of which bears S. 73° W., 515 ft. from Cor. No. 2 Wall Street #1 lode, 8 x 8 ft., 10 ft. deep. Value, \$200.</p>
No. 5	<p>A tunnel, 5 x 6 ft. in size, the portal of which bears S. 71°55' W., 458 ft. from Cor. No. 2 Wall Street #1 lode, runs N. 61°30' W., 20 ft., caved. Value, \$400.</p>

FEET									
No. 6	<p>A tunnel, 5 x 6 ft. in size, the portal of which bears S. 53°45' W., 680 ft. from Cor. No. 2 Wall Street #1 lode, runs S. 30° E., 22 ft., thence S. 1¹/₂° E., 44 ft., thence S. 10° E., 21 ft. to breast.</p> <p style="padding-left: 40px;">Value, \$2000.</p>								
No. 7	<p>A cut, 20 ft. wide, the face of which bears N. 31°30' E., 690 ft. from Cor. No. 3 Wall Street #1 lode, runs S. 28°30' W., 40 ft. to 5 ft. face.</p> <p style="padding-left: 40px;">Value, \$300.</p> <p>An interest in common improvements described as follows:</p> <p>A shaft, the center of which bears S. 44°40' W., 685 ft. from the center of line 1-2, Wall Street #1 lode, 7 x 8 ft. in size, 30 ft. deep.</p> <p style="padding-left: 40px;">Value of shaft, \$620. Value of one-half interest, \$310.</p> <p>A drill hole, the center of which bears S. 53°55' W., 648 ft. from Cor. No. 2 Wall Street #1 lode, 4 ins. diam., 200 ft. deep.</p> <p style="padding-left: 40px;">Value of drill hole, \$1200. Value of one-half interest, \$600.</p> <p>These improvements are for the development of the two lodes of this survey which are contiguous lodes owned in common within the range of benefit of said shaft and drill hole.</p> <p>Five hundred dollars or over has been expended in these improvements in such a manner as tends to the development of the two lodes at depth subsequent to their locations and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-half interest in their value is hereby credited to each of said lodes.</p> <p>No portion of or interest in these improvements has been credited heretofore as patent expenditure to any lode claims.</p> <hr/> <p style="text-align: center;">Field Assistants</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Name</th> <th style="text-align: left;">Capacity</th> </tr> </thead> <tbody> <tr> <td>Randall J. Smith</td> <td>Instrumentman</td> </tr> <tr> <td>William G. Smith</td> <td>Chainman</td> </tr> <tr> <td>B. T. Boyd</td> <td>Chainman</td> </tr> </tbody> </table>	Name	Capacity	Randall J. Smith	Instrumentman	William G. Smith	Chainman	B. T. Boyd	Chainman
Name	Capacity								
Randall J. Smith	Instrumentman								
William G. Smith	Chainman								
B. T. Boyd	Chainman								

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Name of Mineral Surveyor William P. Smith	Date February 8, 1980
---	---------------------------------

I HEREBY CERTIFY That in pursuance of an order received from the Bureau of Land Management Division of Technical Services, at Phoenix, Arizona, dated September 21, 1979, I have carefully executed the survey of the claim of Jerry Glazier & Leon Glazier, P.O. Box 752, Hurricane, Utah 84737 known as the (lode, placer, or mill site) Vanderbilt #17 and Wall Street #1 lodes, situated in Mohave County, Section 16, Township 33 N., Range 14 W., Gila & Salt River Meridian, in the State of Arizona.

This survey, designated as number 4802, has been executed by me and under my direction and has been made in strict conformity with said order, the Manual of Instructions for the Survey of Public Lands of the United States, and in specific manner described in the foregoing field notes.

I FURTHER CERTIFY That the labor expended and improvements made upon and for the benefit of the (lode or placer) lode location(s) embraced in the said mining claim by claimant(s) or grantors are fully stated in my report. The character, extent, location, and itemized value are specified in full detail. No portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.

Glendale, California (Location)	<i>William P. Smith</i> (Signature of Mineral Surveyor)
---	--

CERTIFICATE OF APPROVAL

Office Arizona State Office
Location Phoenix, Arizona
Date July 25, 1980

The foregoing field notes of mineral survey number 4802, in Section 16, Range 14 W., Gila and Salt River Meridian, in the State of Arizona, surveyed unsurveyed Township 33 N., executed by William P. Smith, Mineral Surveyor, under order dated September 21, 1979, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.

<i>Boyd S. Owens</i> (Authorized Signature)	Chief, Branch of Cadastral Survey (Title)
--	---

CERTIFICATE OF TRANSCRIPT

I HEREBY CERTIFY That the foregoing transcript of field notes of the above-described mineral survey number is a true copy of the original field notes.

(Authorized Signature)	(Title)
------------------------	---------

Title 18, U.S.C. section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

Division of Technical Services
Department of Agriculture
Washington, D. C.

January 1, 1951

Dear Sir:
Reference is made to your letter of December 15, 1950, regarding the matter of the proposed construction of a new building for the Division of Technical Services, Department of Agriculture, Washington, D. C.

The proposed building is located on the site of the old building which was destroyed by fire in 1945. The site is bounded by the following streets: North on M Street, South on N Street, East on E Street, and West on W Street.

The proposed building is to be a three-story structure with a total area of approximately 100,000 square feet. It is to be constructed of brick and concrete. The building is to be used for the following purposes: (1) as a headquarters for the Division of Technical Services; (2) as a place for the storage of records and files; and (3) as a place for the storage of equipment and supplies.

The proposed building is to be constructed in accordance with the plans and specifications submitted to the Bureau of Reclamation, Department of the Interior, for their approval. The Bureau of Reclamation has approved the plans and specifications and has issued a permit for the construction of the building.

The proposed building is to be constructed in accordance with the plans and specifications submitted to the Bureau of Reclamation, Department of the Interior, for their approval. The Bureau of Reclamation has approved the plans and specifications and has issued a permit for the construction of the building.

The proposed building is to be constructed in accordance with the plans and specifications submitted to the Bureau of Reclamation, Department of the Interior, for their approval. The Bureau of Reclamation has approved the plans and specifications and has issued a permit for the construction of the building.

The proposed building is to be constructed in accordance with the plans and specifications submitted to the Bureau of Reclamation, Department of the Interior, for their approval. The Bureau of Reclamation has approved the plans and specifications and has issued a permit for the construction of the building.

The proposed building is to be constructed in accordance with the plans and specifications submitted to the Bureau of Reclamation, Department of the Interior, for their approval. The Bureau of Reclamation has approved the plans and specifications and has issued a permit for the construction of the building.

The proposed building is to be constructed in accordance with the plans and specifications submitted to the Bureau of Reclamation, Department of the Interior, for their approval. The Bureau of Reclamation has approved the plans and specifications and has issued a permit for the construction of the building.

The proposed building is to be constructed in accordance with the plans and specifications submitted to the Bureau of Reclamation, Department of the Interior, for their approval. The Bureau of Reclamation has approved the plans and specifications and has issued a permit for the construction of the building.