

~~Plotted~~

1588

BOOK 1588

1588  
1

# Exteriors

4-671.

FIELD NOTES

GENERAL LAND OFFICE.

Tp. 9 S. R's. 22 and 23 E.

1588

Book No. 1

1588 <sup>BOOK</sup> 1588

Index.

- Bct T 95 R 22 & 23 E - 3  
North Bdy T 95 R 22 E - 14  
South " T 95 " 23 E - 23  
North " T 95 " 23 E - 26

\Preliminary Oaths of Assistants.

BOOK 1588

We N. H. Callahan BOOK 1588

and Frank L. Lewis

do solemnly swear that we will well and faithfully execute the duties of Chain Carriers; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist

BOOK 1588

in measuring, to the best of our skill and ability and in accordance with instructions given us in the survey of the Extensions

and subdivisions of Townships

7 South R.s. 22 and 24 E. Tps. 8 & R.s. 22 and 25 E. Tps. 9 & R.s. 22 and 23 E. Tps. 16 & R.s. 21 and 22 E. Tps.

R.s. 21 and 22 E. Tps. 18 & R.s. 22 E. Gila and

et River Muriciand Territory of Arizona.

N. H. Callahan ..... Chainman.

Frank L. Lewis ..... Chainman

Subscribed and sworn to before me, this

1 of Sept - 1886

George R. Kline  
Notary Public.

We B. F. Crawford W. E. Cads IA  
and A. B. Ford BOOK 1588

do solemnly swear that we will well and truly perform the  
duties of Cameran and Flagman

in the establishment of corners and other duties according to  
instructions given us, and to the best of our skill and ability,  
in the survey of the Extions and subdivisions

Townships 7 South Range 22 and 24 E.

Tps. 8 S. Rs. 22 and 25 E. Tps. 9 S. Rs 22 and 23 E.

Tps. 16 S. Rs. 21 and 22 E. Tps. 17 S. Rs 21 and 22 E.

Tps. 18 S. Rs. 22 E. Gila and Salt Riv

Meridian and Base Territory of Arizona.

B. F. Crawford Cameran  
W. E. Cads Cameran  
A. B. Ford

Subscribed and sworn to before me this

day of September 1886

9<sup>th</sup>

George R. King  
Notary Public.



\ Prelimin

We John do solemnly swear that

and Fris will well and truly perform the duties of  
do solemnly swear according to instructions given and to the best of  
duties of Chain C skill and ability.

BOOK 1588

Sworn to and subscribed before me this

day of 188

BOOK

in measuring, t

nce with instru

and s

7 Sout

do solemnly swear that

258. Rs. 90 will well and truly perform the duties of  
Rs. 21 and according to instructions given and to the best of  
Rs. 11 R. 11 skill and ability.

Sworn to and subscribed before me this

day of 188

S

of

J

Field Notes

1B

of the Survey of the W. bdy of  
Tps 9S. through Rs 22 and 23 E.  
and the E. Boundary of Tp. 9S. R 22E  
Gila and Salt River Base and  
Meridian

Arizona Territory

BOOK 1588

As Surveyed by

C. S. Wallace

W.S. Deputy Surveyor

Under Contract

No 3

Dated April 26 1886

Survey Commenced September 13, 1884  
Survey Completed " 17, 1886

Names and duties of Assistants

H. H. Callahan	Chairman
Frank L. Lewis	Chairman
W. E. Eads	Axeman
B. F. Crawford	Axeman
A. B. Ford	Flagman

Index

T 6 T 4 T 3 T 2 T 1 T 6 T 5 T 4  
 14 to 16 16 to 17 17 to 18 18 to 19 19 to 20 20 to 21 26 to 27 27 to 28 29

T 6, 12 to 13

T 7 10 to 12 T 9 S.

T 18, 8 to 10 R 23 C

T 19, 6 to 8

T 30, 5 to 6

T 31, 3 to 5

6 23 5 23 4 23 3 23

T 9 S. 22 E

Rang line betw 22 and 23 E. A. S.

Survey commenced September 13, 1886,  
with a Gurley Solar Transit.

I began at corner to Rps 9 and 10 S., R's 22  
and 23 E., which is a mound of earth  
and pits with stake in pit marked  
A. 10 S. R. 22 E. on S. W.

A. 9 S. R. 22 E. on N. W.

A. 9 S. R. 23 E. on N. E.

A. 10 S. R. 23 E. on S. E. faces and a notch  
on each edge.

Hence I run north betw. R's 22 and  
23 E.

Va.  $12\frac{1}{2}$ ° E.

40.00 Set a chain and stake 12 in. in the  
ground, for 1/4 sec. corner, dug pits  
18 x 18 x 12 in., N. and S. of corner 5 1/2 ft  
dist. and raised a mound of  
earth 1 1/2 ft high, 3 1/2 ft base width.

Rangeline CR 22 and 23

In S. pit drove a stake 2 ft long  
2 ins. square 12 ins. in the ground  
marked  $\frac{1}{4}$  S. on W. face.

Ascend over grassy slope.

80.00 Drove a chain and stake 12 ins. in the  
ground for corner to sections 25, 30  
31 and 36, dug pits 18x18x12 ins. in  
each section  $5\frac{1}{2}$  ft dist., and raised  
a mound of earth 2 ft high,  $4\frac{1}{2}$  ft  
base, over it. In S.E. pit drove a  
stake 2 ft long, 2 ins. square, 12 ins. in  
the ground, marked:-

S. 9 S. 30 on N.E.,

R 23 E. S. 31 on S.E.,

R 22 E. S. 36 on S.W., and

S. 25 on N.W. faces, with 1 notch  
on S. and 5 notches on N. edge

Land gently rolling.

Soil 3rd rate.

Good grass. No timber.

E. Pts. 9 & S. Fila of Salt River B. & W.

North line recd. 25 and 30.

Var.  $12\frac{1}{2}^{\circ}$  E.

Ascend gradually

4000 Set a chancd stake 12 ins. in the ground for  $\frac{1}{4}$  sec. cor., dug pits  $18 \times 18 \times 12$  ins. N. and S. of corner  $5\frac{1}{2}$  ft dist., and raised a mound of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft base over it. In N. pit drove a stake 2 ft long 2 ins. square 12 ins. in the ground, marked,  $\frac{1}{4}$  S. on its face.

80.00 Drove a chancd stake 12 ins in the ground for corner to recd. 19, 24, 25 and 30, dug pits  $18 \times 18 \times 12$  ins. in each sec.  $5\frac{1}{2}$  ft dist and raised a mound of earth 2 ft high,  $4\frac{1}{2}$  ft base over it. In S.E. pit drove a stake 2 ft long 2 ins. square 12 ins. in the ground marked:-

Rough line betw 22 and 23 E

T. 9 S. R. 22 E. S. 25 on S.W.,

S. 24 on N. W.,

R. 23 E. S. 19 on N.E.,

S. 30 on S.E., face, with 2 notches  
on the south and 4 on the north edges  
land surface sloping south.

Soil 3rd rate.

Good grass. No timber.

North betw. secs. 24 and 19,

Variation  $12\frac{1}{2}^{\circ}$  E.

- 2.80 Road from Grant to Thomas br. N.W.
- 8.19 Goit Telegraph line from Fort Grant  
to Fort Thomas br. N.W. and S.E. and  
ascend rocky ridge.
- 10.50 Top of ridge 50 ft high betw N.E. and  
S.W., descend.
- 40.00 Set a chain and stake 12 ins. in the  
ground for  $\frac{1}{4}$  sec. corner dug pits

P. 9 S. Gila and Sabi River B. and M.

18 x 18 x 12 ins. A. and S. of corner  $5\frac{1}{2}$  ft. dist.  
and raised a mound of earth  $1\frac{1}{2}$  ft  
high  $3\frac{1}{2}$  ft base over it. In A. pit down  
a stake 2 ft long 2 ins. square 12 ins. in  
the ground, marked  $\frac{1}{4}$  S. on W. face.

Up gradual slope, grassy.

80.00 Set a chain and stake 12 ins. in the ground  
for corner to secs. 13, 18, 19 and 24, dug pits  
18 x 18 x 12 ins., in each sec.  $5\frac{1}{2}$  ft. distant,  
raised a mound of earth 2 ft high,  $4\frac{1}{2}$  ft  
base over it. In S.E. pit down a stake 2 ft.  
long 2 ins. square, 12 ins. in the ground,  
marked:-

P. 9 S. R. 22 E. S. 13 on Th. W.

R. 23 E. S. 18 on Th. E.,

S. 24 on S. W. and

S. 19 on S.E. faces with 3 notches  
on the S. and 3 on the Th. edges.

Land gently sloping

Rangeline L.N. 22 and 23 E

Soil 4th rate, no timber.

Good grass.

Sept. 13. 1886.

North 8<sup>th</sup> section 13<sup>rd</sup> & 18.

Via 12 $\frac{1}{2}$ ° E.

- 36.80 Road from Grant to Cedar Springs  
bears N. W. and S. E.  
40.00 Drove a chand stake 12 ins. in the  
ground for 1/4 sec. cor. dug pits 18x18  
x12 ins. N. and S. of corner 5 1/2 ft. distant  
and raised a mound of earth 1 1/2 ft  
high 3 1/2 ft. base on it. In N. pit I  
drove a stake 2 ft. long 2 ins. square  
12 ins. in the ground marked 1/4 S  
on W. face

On rolling foot hills; good grass.

- 80.00 Set a chand stake 12 ins. in the  
ground for corner to sections 7, 12,

P. 9 S. Gila and Sat River Band M.

13 and 18, dug pits 18x18x12 ins. in each sec. 5½ ft. deep and raised a mound of earth 3 ft. high, 4½ ft. base over it. In S.E. put down a stake 3 ft long 2 ins. square 12 ins. in the ground, marked:-

R 23 E. S. 7 on N.E.,

S 18 on S.E.,

S 13 on S.W. and

P. 9 S. R 22 E. S 12 on N.W. facee with 4 notches on the S. and 3 on the N. edges. Land slightly broken.

Soil 4th rate.

No timber. Good grass.

North lot. secs. 7 and 12

Tan. 12½° E.

15.00 Ravine, 20 links wide, course S.W. and ascend.

4000 Set a charred stake 12 ins. in the

Ranger Line betw 22 and 23 E.

ground for  $\frac{1}{4}$  sec. cor., dug pits  $18 \times 18 \times 12$  in.  
 $5\frac{1}{2}$  ft. dist. N. and S. of corner and raised  
a mound of earth  $1\frac{1}{2}$  ft high,  $3\frac{1}{2}$  ft. base  
over it. In N. pit drove a stake 2 ft.  
long, 2 ins. square, 12 ins. in the ground  
marked  $\frac{1}{4}$  S. on W. face

63.00 Range, 10 links wide course S.W. thence  
along ravine.

63.00 Set a chaind stake 12 ins. in the  
ground for corner to sections 1, 6, 7 and 12  
dug pits  $18 \times 18 \times 12$  ins. in the ground  
in each sec.  $5\frac{1}{2}$  ft. dist. and raised  
a mound of earth 2 ft high  $4\frac{1}{2}$  ft base  
over it. In S.E. pit drove a stake  
2 ft long 2 ins. square 12 ins. in the  
ground marked:-

S. S. S. 6 on N.E.

R. 23 E. S. 7 and S.E.

R. 22 E. S. 1 on N.W. and

Gila and Salt River B.M.

S. W. on S.W. faces, with 5 notches on the S and 1 notch on the N. edge.

Land rolling.

Soil 4 to 6 in.

No timber. Good grass.

## North G.R. sec. 1 and 6.

Variation 12° E.

- 17.00 Ravine 25 miles wide, course S.W.
- 19.80 Ravine 46 miles wide, course S.W.
- 39.00 Ravine 18 miles wide, course S.W.
- 40.00 Set a post 3 ft long 3 in. square, <sup>with chain stakes</sup> 12 in. in the ground for 1/4 sec. corner dug pits 18 x 18 x 12 in. Head S. of corner 3 1/2 ft dirt and raised a mound of earth 1 1/2 ft high 3 1/2 ft base around post. Marked 1/4 sec. on W. face.
- 54.00 Top of hill 150 ft high.
- 74.00 Cross ravine 17 miles wide course S.W.

Ranger line between 22 and 23 E. 1.98.

Set a sand stone 3 ft long 6 x 6 in.,  
18 in. in the ground forearm to town.  
Slips 8 and 9 S. R. 22 and 23 E. marked  
with 6 notches on N.E. and W. edge.  
Raised a movement of stone alongside.  
And oak 12 in. in diameter, marked  
N. 8 S. R. 23 E. S. 31 B. N. br. 7/22:16 E. 31 links.  
And live oak 12 in. in diameter  
marked N. 8 S. R. 22 E. S. 36 B. N. br. 7/82 W. 102 links.  
A willow 5 in. in diameter brare 8.66° W.  
72 links marked N. 9 S. R. 22 E. S. 1 B. N.  
A willow 5 in. in diameter marked N. 8 S. R. 22 E.  
S. 1 B. N. brare 8.18° W. 30 links.

Sept. 14th 1886.

Clarence H. Wallace

U.S. Deputy Surveyor.

Part 14  
22Y. bdy D. 98. R. 22 E.

From the corner to Tps 8 and 9 S. R's 22 and 23 E., which is a stone and iron - of iron properly established I run th over a random line bet. Tps. 8 and 9 S.

Variation  $12\frac{1}{2}$ ° E.

I set temporary half mile and mile corners at each 40 and 80 chains & find the Tp. line to be 5 miles 79 rods 75 links long and falling 72 links N. of the corner to Tps 8 and 9 S. R's 21 and 22 E. The correction for the true line will therefore be 12 links south per mile and its course will be T. 89° 55' E.

From the corner to Tps 8 and 9 S. R's 21 and 22 E. which is a post 5-mw<sup>3</sup> square 3'  $\times$  3' above ground, surrounded by a mound of straw, marked:-

T. 88 S. R. 22 E. 31 on N.E.

A Boundary of 798

N. 9 S. R. 22 E. 6 on S.E.

N. 9 S. R. 21 E. 1 on S.W.

N. 8 S. R. 21 E. 36 on N.W. faces with  
6 notches on each edge.

From N. 89° 55' E. on a trueline between  
6 and 31.

Variation 12 $\frac{1}{2}$ ° E.

17.00 Ravine 60 links wide, course S.W.

27.50 Top of ridge 15' ft high brc S.W. by N.E.

39.75 Set a stone 16 x 7 x 7 in., 12 in. in the  
ground for 1/4 sec corner, marked 1/4  
on N. face and raised a mound of  
stone plaster.

41.75 Small ravine 10 links wide, course S.W.

59.75 Ravine 100 links wide, course S.W.

79.75 Set a stone 16 x 8 x 8 in., 11 in. in the  
ground for corner, to secs. 5, 6, 31  
and 32, marked with 5 notches on  
the E. and 1 on N. edges. Raised a

R 22 E Gila and Salt River Branch.

movement of stone along side.

Land rolling rough hills.

Soil rocky & thin.

Some grass, no timber.

At 89° 55' E. saw a tree line bet. sec. 8 and 32.

Var. 12 1/2 E.

23.30 Rained 78 links wide, course S.W.

40.00 Set a stone 12 x 10 x 6 ins 8 ins in the ground for 1/4 sec. corner marked 1/4 on N. face raised a mound of stone along side.

48.50 Rained 69 links wide, course S.W.

60.00 Top of ridge 150 ft high, loc. S.W. and N.E.

80.00 Set a stone 16 x 10 x 7 ins. 11 ins in the ground for corner to secs. 4, 5, 32 and 33 marked with 4 notches on the E and 2 on the W. edge. Raised a mound of stone along side.

N. Boundary of T. 9 S.

Land hilly and rough -

Soil rocky and 4 th rate -  
some grass. No timber.

St. 89° 55' E on a true line b/w recs. 4 and 33.

Variation  $12\frac{1}{2}^{\circ}$  E.

- 2.50 Ravine 150 ft deep, course S.W.  
26.40 Ravine 36 links wide, course S.W.  
32.00 Ravine 19 links wide, course S.W.  
40.00 Set a stone  $14 \times 10 \times 7$  ins. high in the ground  
for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  on N face and  
raised a mound of stone alongside.  
64.30 Ravine 20 links wide, course S.W.  
70.20 Ravine 100 links wide, course S.W.  
80.00 Set a granite rock  $18 \times 10 \times 7$  ins. 12 ins.  
in the ground forecorner to recs. 3, 4  
and 33, and  $\frac{1}{4}$  marked with 3 notches  
on E and W edges. Raised a mound  
of stone alongside.

R 22 E Gila and Salt River Band M.

Land hilly and rough.

Soil rocky & thin.

No timber, some grass.

At  $89^{\circ} 55' E.$  on a true line betw. sec. 3 and 34.

Variation  $12^{\circ} 2' E.$

35.40 Telegraph line betw. S.E. and N.W.

40.00 Set a granite rock  $14 \times 12 \times 12$  inc. 9 inc.  
in the ground for  $\frac{1}{4}$  sec. corner, marked  
 $\frac{1}{4}$  on N. face and raised a mound of  
stone alongside.

46.20 Camp Grant and Cedar Spring road  
betw. N.W. and S.E.

80.00 Set a stone  $24 \times 12 \times 8$  inc., 18 inc. in  
the ground for corner to sections 23, 34  
and 35. Marked with 2 notches on the  
E and 4 notches on the W edge  
raised a mound of stone alongside  
Land sloping gently to the S.W.

North edge 198

Soil rocky, good grass.  
No timber -

N 89° 55' E on a true line between sec. 2 and 35.

Var. 12½° E.

On surface sloping S.W.

40.00 Set at stone 17 x 7 x 5 ins., 11 ins. into  
ground for 1/4 sec. corner, marked  
1/4 on N. face. Raised a moun-  
tain of stone alongside.

66.00 Ravine 58 links wide, course S.W.

80.00 Set at stone 30 x 10 x 6 ins., 21 ins. into  
ground for corner to secs. 1, 2, 35 and  
36, marked with 1 notch on the  
E. and 5 notches on the W. edges.

Raised a mound of stone alongside.

Land rough. Slope to the south.

Soil 4th rate -

Some grass and a few scrubby trees.

Sept 15th 1886.

Rare Gila and Salt River R. and M.

$789^{\circ} 55' E$  on a true line N.W. sec. 1 and 36.

Variation  $12 \frac{1}{2}' E$ .

- .50 Ramir 60 miles wide, course S.W. and ascend a rough rocky slope -
- 4.00 Set a stone  $18 \times 18 \times 6$  ins., 12 ins. with ground for  $\frac{1}{2}$  sec. corner marked  $\frac{1}{2}$  on N. face. Raised a mound of atom alongside.
- 48.50 Top of rocky ridge 800 ft above surrounding country by N.W. and S. and descend
- 78.00 Foot of slope -
- 80.00 Corner to 1<sup>st</sup> 8 and 9 & R's 22 and 23 E.  
Land rough and hilly.  
Soil rocky & thin.  
Some grass and stunted timber.

General description

The northern portion of this township

is rough and hilly, with deep dry ravines. The southern part is gently sloping high plain, good for pasture - There is no living water in the township, and no settlers but in view of the possibilities of the future it should be subdivided.

Clarence H. Wallace

U. S. Dep't. Survey

Retracing S. bdy T. 9 S. R. 23 E.

Preliminary to the survey of the  
fractional part of T. 9 S. R. 23 E. I com-  
mence at the corner of Pts 9 and 10 S.  
R. 22 and 23 E. and run

S 89° 58' E.

Var. 12  $\frac{1}{4}$  ° E.

Bet Pts 9 and 10 S. R. 23 E.

79.65 Find corner to secce 8, 6, 31 and 32

Hence on same line Var. same

80.06 The old corner to secce 4, 5, 32 and 33

Hence on same line

Var. 12  $\frac{1}{4}$  ° E.

80.00 The old corner to secce 34, 33 and 34

Hence on same course

Var same

39.32 I find the old closing corner on the  
west boundary of Camp Grant

S. 6dy 9.9 S. R. 28 E.

Military Reservation, a post of  
high stone square, set in a mound  
of earth with 3 pits, post mile  
C.C. on E.,

R. XXII E. 111 m. S.W.,

T. IX S. XXXIV on N.W.,

T. X S. on S.E. face

Hence along same line

Var same -

40.05 I find the old 1/4 sec. corner for  
sections 3 and 34.

The chaining and bearings being  
the same as in the old survey I  
return to the closing corner on  
the boundary line

Hence S. 7° 28' E.

Var.  $12\frac{1}{2}$  ° E.

1621 I find a square granite stone  
2 ft  $\times$  1 $\frac{1}{2}$  ft., 1 ft high firmly

West End Camp Grant M.R.

set in the ground for corner to the  
Camp Grant Military Reservation  
From at the flagstaff at camp  
Grant have  $44^{\circ} 49' - 26^{\circ} E.$  318 chains  
thence down  $47^{\circ} 28' W$  along the N.  
boundary of the reservation setting  
flags at the end of each 10 chains  
to be used in closing the section line  
of the township on the boundary -  
In retracing this line of the reservation  
I found other stones set on it, at  
intervals, similar to corner not  
previously described

Sept 16th 1886.

North boundary of 9 S.

To survey the North boundary of  
Spc. 9 S. R. 23 E. I begin at the corner  
to Sps. 8 and 9 S. Rs. 22 and 23 E.  
which is a stone and monument of  
stone properly established.

Then I run C. on a true line C. N. recd.  
and 21.

Var.  $12\frac{1}{2}$  E.

- 4.00 Dry ravine, 27 links wide course S.W.  
and ascend on abrupt rocky hill  
40.00 Set a granite rock 24 x 12 x 9 ins 18  
ins, as the ground for  $\frac{1}{4}$  sec. corner  
marked  $\frac{1}{4}$  on N. face and raise a  
monument of stone alongside.
- 64.50 Top of ridge 700 ft high to S.W.
- 79.00 Bottom of cañon, course S.W.
- 80.00 A granite rock in place 18 ins  
high, 12 x 12 ins, marked as  
exact corner point with a x

R 23 E Gila and Salt River B. & W.

and 1 notch on N end - on E edge

Raised a monument of stone along side  
a white oak 8 in. in diam. tree 7.45' W.  
28 lbs marked R. 23. S. 21 B. N.

A black oak 8 in. in diam. tree 8.54' W.

40 lbs, dark, marked R. 23. S. 21 B. N.

A white oak 20 in. in diameter tree 8.45'

45 lbs, marked R. 23 E. S. 21 B. N.

A black oak 8 in. in diam. tree 8.76' E.

38 lbs, marked S. 21 B. N.

Land rough and mountainous -

Soil rocky and thin -

Some grass and scrubby trees.

East on a true line 6 ft. sec 5 and 32.

Var 12  $\frac{1}{2}$ ° E.

descend slope -

22.5° Bottom of Taylor's corner corner S.

28.5° Wood road up canyon tree N and S.

North Boundary 198

- 40.00 Set a granite stone  $17\frac{1}{2} \times 7$  ins. 11 ins  
in the ground for N. corner, marked  
 $\frac{1}{4}$  on N face. Raised a monument  
of stone alongside -
- 62.5° Bottom of ravine 20 links wide comp S.E.
- 80.00 Set a stone  $18 \times 12 \times 8$  ins 12 ins, in  
the ground for corner to sections 4, 5  
32, and 33 marked with 2 notches  
on the W. and 1 notch on the E.  
edges, raised a monument of  
aliquid.
- An oak 10 ins. in diameter marked  
R. 98. S. 4 B. T. brs.  $852^{\circ}$  E. 39 links.
- An oak 8 ins. in diameter, marked  
R. 23 E. S. 32 B. T. brs.  $725^{\circ}$  W. 52 links
- An oak 8 ins in diameter, marked  
R. 23 E. S. 5 B. T. brs.  $869^{\circ}$  W. 42 links
- An oak 10 ins in diam., marked  
R. 98. S. 33 B. T. brs.  $762^{\circ}$  E. 102 links

R. E. Gila and Salt River R. and M.

Land rough and mountainous.

Soil rocky & th. rats.

Some grass and scrubby trees.

East on a true line bet. secs 4 and 33

Via  $12\frac{1}{2}^{\circ}$  E.

Over rough broken rocky country.

40.00 Set a stone  $15 \times 9 \times 5$  ins. 10 ins. in the ground for  $\frac{1}{4}$  sec. eor., marked  $\frac{1}{4}$  on N. face and raised a monument of stone alongside.

56.40 Intersect W. boundary line of Camp Grant Military Reservation where I mark a stone in place  $7 \times 6 \times 5$  ins. with a X, at exact intersection, and C.G. M.R. on S. face, raised a monument of stone alongside.

Land rough and broken.

Soil rocky & th. rats.

Brush and scattering trees.

T. Boundary N. 9 S. R. 23 E.

All of the N. boundary of T. 9 S.  
R. 23 E. extends over rough broken  
rocky mountains covered with  
stunted growth of trees.

#### General Description

The northern portion of T. 9 S. R. 23 E.  
is high and mountainous and its  
southern part an open plain  
sloping southward, covered  
with a fair growth of grass  
and along the ravines a few  
specimen trees.

There being a number of settlers  
in this Township it should  
be subdivided.

Sept. 17. 1886.

Clarence H. Wallace,  
U.S. Deputy Surveyor

For final oaths see books 6, 7, 9, 10 and 15.

BOOK 1588

31

U. S. Surveyor-General's Office,

TUCSON, A. T., *June 13, 1888*

The foregoing Field Notes of the Surveys of  
the Exterior Lines of  
T. 9 S. - Rgs. 22 & 23 E.

Gila and Salt River Meridian  
in Arizona..... executed by  
Clarence H. Wallace.

U. S. Deputy Surveyor, under his contract dated

April 26<sup>th</sup> 1886.

having been critically examined, the necessary corrections and explanations made, the said Field Notes and the surveys they describe are hereby approved.

*John H. Tissie*  
U. S. Surveyor-General  
for the Territory of Arizona.