

1604

Resurrey
South Boundary

BOOK 1604

T 19 S., R 29 E.

Rockfellow

4-671

FIELD NOTES
GENERAL LAND OFFICE

1604

1604

BOOK 1604 Preliminary Oaths of Assistants.

We, Martin Walsh
and M. H. O'Connor
do solemnly swear that we will well and faithfully
execute the duties of Chain Carriers; that we will
level the chain upon even and uneven ground, and
plumb the tally pins, either by sticking or dropping
the same; that we will report the true distance to
all notable objects, and the true lengths of all lines
that we assist in measuring, to the best of our skill
and ability, and in accordance with instructions
given us, in the survey of the South

Boundary of T.P
195 R. 29 East

of the Gila and Salt River Base and Meridian in
the Territory of Arizona.

Martin Walsh Chainman.

M. H. O'Connor Chainman.

Chainman.

Chainman.

Subscribed and sworn before me, this 19
day of August 1899

John F. Papperton
Notary Public.

[SEAL.]
my com. expires Apr 10 1903

We, R. H. Fowler ^{IA}
BOOK 1604
T F W Heyne

do solemnly swear that we will well and truly per-
form the duties of Flagman &
Axeman

in the establishment of corners and other duties,
according to instructions given us, and to the best
of our skill and ability, in the ^{re-}survey of the

South Boundary of
F.P. 19 S. R. 29 E.

of the Gila and Salt River Base and Meridian, in
the Territory of Arizona.

R. H. Fowler
T. F. W. Heyne

Subscribed and sworn to before me this 19

day of August 1899

J. A. Rockwood
Notary Public.

Field Notes
of the resurvey of the
South Boundary
of
Township No 19 South
Range No 29 East
of the
Gila & Salt River Base
and Meridian
in the Territory of
Arizona
as resurveyed by
John A Rockfellow
U.S. Deputy Surveyor
Under special instruc-
tions dated Oct 26, 1899.

Survey commenced Dec 11/99
Survey completed Dec 13/99

2 Resurvey D Bdy

BOOK 1604

INDEX

31 32 33 34 35 36
L 7 + 9 + 11 + 14 + 16 + 17 L
6 5 4 3 2 1

9/19 O R. 29 E

3

BOOK 1604

4 Resurvey O. Bdy

BOOK

1604

Resurvey commenced
Dec 11 1899 and ex-
ecuted with a Young
& Sons Light Mountain
Transit No. 6855 with
Smith's solar attachment.
The horizontal limb is
provided with two dou-
ble verniers placed oppo-
site to each other and
reading to single min-
utes of arc which is
also the least count of
the latitude and declina-
tion arcs.

The instrument was
examined, tested on
the true meridian
at Tucson A.T. June
13, 1899, found correct

Y. 19 S. R. 29 E.

BOOK 1604

5-

and was approved
by the Surveyor Gen'l.
Examined and
tested the instrument
this morning at 8 A.M.
I.t. on the meridian
established by me
by Polaris & Polar ob-
servations on Augt, 1899
at ^{Camp Rocker Creek} cor to Townships No
19 & 20 S. Ranges No 29 &
30 East, as heretofore
described and found
the same to be correct.

From cor to Sps 19 & 20 S.
Ranges 29 & 30 E. I run
S. 84° 45' W (as by spl in-
structions) on Random
line bet. ^{bcs} 1 & 36, var 2.

6

Resurvey O Bdy

BOOK 1604

clue

40.00 $\frac{1}{4}$ sec cor could not
be found after diligent
search

80.48 Cor of secs 1, 2, 35 & 36, as
described by Surveyor Geil
hrs 11.168 lks.

From cor sees 35 & 36 on
S. Bdy., I run
 $\textcircled{D}.$ $89^{\circ}45'W$ var $12^{\circ}30'$
on random line betw
2 & 35.

40.04 $\frac{1}{4}$ sec cor as described
by Surveyor Geil hrs
 $\textcircled{D}.$ 38 lks.

80.04 No sign of old cor after
2 hours diligent search
Continue same course
 $\textcircled{D}.$ $89^{\circ}45'W$ and find
no other corners on
 \textcircled{D} Bdy.

Y. 19th R. 29^E

BOOK 1604

7

dist
359.04

Intersect W. Bdy 336 like
Width of cor to Yrs 19 & 20
S. Railgs 28 & 29^E,
which I find as de-
scribed by Surveyor Cail.
Hence true

○ 89° 43' E on true
line on S. bdy sec 31,
One mountainous island.

4.80 Wash Devil's cañon, 40kds
wide course S.

39.04 Set cement rock 12x12x7ins
is sunk 3ins to bed rock
for 1/4 sec cor. marked
1/4 on U. face. Build
mound of stones 2 1/2 ft
base 1 1/2 ft high U. of cor.
A low white oak 6 ins in
diam S 30° E 20kds dist.
marked 1/4 P. 6 B. Y.

A juniper 8 ins in diam
marked 1/4 S 31 P. 7 base
N. 2° 15' W 78kds dist.

8 Resurvey O Bdy

- 81.00 Summit of divide
hrs C. S. S.
- BOOK 1604 Descend along N. slope
of divide.
- 74.00 Enter wash Devil's
cañon course W. N. W.
- 76.30 Leave wash.
- 77.80 Re-enter Devil's cañon wash
course W. S. W. 40 ft wide
- 78.04 Cov to secs 5, 6, 31 + 32.
falls in edge of wash
A cement boulder 3×3 ft
2 ft high, 12 lks E of
true cor point for want
ness cov. which I mark
+ W.C. with 1 notch
on W. & 5 on E edges
+ raise end of stones
 $2\frac{1}{2}$ ft base 2 ft high
H. of cov.

Y. 19 S. R. 29 E. 9
BOOK 1604

che

A dry Juniper 2 ft in
diam in wash, brs N.

45° W. 26 lbs dist, mark

Y. 19 S. R. 29 E. 9 3/4 lbs

A Blackoak 11 ins in
diam brs 3 45° E, mark

Y. 20 S. R. 29 E. 9 5/8 lbs

Soil 2nd & 3rd rate

Land mountainous 79.04 acs

Dak 24 ins in diam marked Y. 19 S. R. 29 E. 9 3/4 lbs
N. 35° 30' E 44 lbs dist.
Dak 8 ins diam marked Y. 20 S. R. 29 E. 9 5/8 lbs
S. 51° W. 49 lbs dist.

From cor. to secs 5, 6,
31 + 32. I run
S. 89° 43' E in ^{var. 12° - 25°} line on S. bdy of sec
32, over mts land.
Ascend long wooded
ridge, course E + W.

36.00 Abrupt descent into Geo-
logical canon, riun brs S. + N.

10 Resurvey S. Bdy

cte

40.00

BOOK 1604

1/4 sec cov falls at base
of an almost perpen-
dicular cliff of rocks
25 ft high. mark
+ at exact cov. + 1/4 ft. far
raise monument of stone
2 1/2 ft base 1 1/2 ft high. N.
A white oak 5 ins in
diam bre 1.22 lvs diet.
mark 1/4 S 32, B. Y.

46.20

wash of Devil's Cañon
30 lvs wide course N.W.
Very steep ascent.

63.00

Rim of cañon.

Ascent less steep.

70.00

High divide bre N. & S.

80.00

Col to secs 4, 5-32 & 33
falls in a slide of loose
rocks. Set witness cov
8 lvs W. of true cov. on

Y. 19 D. R. 29 E. 11

BOOK 1604

cement

rock in place $4 \times 3 \frac{1}{4} \times 3$
ft high, just under
a pinnacle of rock 20 ft
high. mark + W.C.
4 notches on E + 2 on
Wedges. build md
of stones 2 ft base 1 $\frac{1}{2}$ ft
high on it.

A white oak 13 in in diam
trs $\odot 30^\circ E$ 48 lks dist
marked Y. 20 D. R. 29. E
 $\odot 4^{\text{we}} B. S.$

Soil 2nd + 3rd rate

Mountainous land 80 chs.

From course ^{line} ft
I run sec 45, 32 + 33

I run var 12 - 25'

$\odot 89^\circ 43' E$ on true line
on Bdy sec 33, over

12

Resurvey S. Bdy

the
BOOK

1604

- mountainous land.
 Descend along slope
 into Devil's Cañon
 Wash of Devil's Cañon
 20 lks wide course S. W.
 Ascend over very rough
 ground, a mass of ce-
 ment boulders & slabs
 10 to 30 ft in diam
 Ridge of cement boulders
 bre S & N.
 Descend.
 Small gulch 15 lks wide
 course N. W.
 Ascend along slope.
 Cement bed rock in
 place 2×2 ft 8 in high
 for $\frac{1}{4}$ sec cor.
 mark + at exact cor
 point + $\frac{1}{4}$ on N. face.

July 19 O. R. 29 E. 13

BOOK 1604

Raise monument of stones
3 ft base 3 ft high N. of cor.

Pits impracticable

45.00 High divide between Devil's
Canyon & Left fork Brunner
canyon pre N. & S.

5-200 Cement reef pre N. & S.

77.10 Wash left Fork Brunner
canyon, 3 folks wide
course S.

8000 Rock in place 15 ft N + S.
2 ft high, on W, (Bed rocks
are all about). for cor
to secs 3, 4, 33 & 34.
mark + at exact cor
point, 3 notches on E
& 3 on W. edges.

Raise monument of stones
3 ft base $1\frac{1}{2}$ ft high on
N. Pits impracticable

14

Resurvey O. Bdy

BOOK 1604

A pine 8 in diam
bre $0 30^{\circ} W.$ 29 lbs dist
mark T. 20 O. R. 29 E. O. 4 B. Y.

Pine 8 ins in diam bre
 $W. 45^{\circ} W.$ 13 lbs dist marked
T. 19 O. R. 29 E. O. 33 B. Y.

Soil 2nd & 3rd rate.
Mountainous land 85 cho.

From cor secs 3, 4, 33 & 34

I run var $12^{\circ} 25'$
O. $89^{\circ} 43' E.$ on true
line on O Bdy sec 34.

Over rough mountainous
Ascend over very broken
& brushy ground.

4 o.oo Set cement rock 18x10x6
ins 1/2 ins in ground
for 1/4 sec cor, mark

7.19 R. 29 E.

15

BOOK 1604

clue

1/4 on N. side.

Build wall of stones 2 ft
base 1 1/2 ft high N of cor.
It's impracticable

A white oak 8 in diameter
brs S 40° W. 22 lks dist-
marked 1/4 S. 3 B.T.

5.3.00 Very high divide bre N. & S.
Deep descent

68.00 Ravine 10 lks wide
course N.

77.40 Main divide of Chincagua
Mountains, course N. & S.

80.00 Cut Porphyry rock 20x6 ft
5 ins / 2 ins in ground
for cor to acc 2, 3, 34 & 35
marked 2 notches on E & 4
on W. edges. Raise md
of stones 3 ft base 1 1/2 ft
high N. of cor.

16

Resurvey D. Bdy.

cls

BOOK 1604

A Juniper tree 13 ins
in diam bre $340^{\circ} W$
36 lks dist - marked
S. 20 D. R. 29 E. S. 3 B. Y.
A Black oak 9 ins in diam
bre N. $4^{\circ} E$ 45 lks dist marked
S. 19 D. R. 29 E. S. 33 B. Y.
Soil 2^{nd} & 3^{rd} rate
Mountainous land 80 cls.

Thence I run
S $89^{\circ} 43' E$ on true line
on D. Bdy sec 35 $\frac{1}{4}$ sec 1230
over mountains.

Descend

37.76 Road from Old camp
Rucker to San Simon
bre N + S.

4000 $\frac{1}{4}$ sec cor as described
by Surveyor General.

Y. 19 O. R. 29 E

BOOK

17
1604

chrs

Thence I run
 $W. 89^{\circ} 03' E$

Ascend point
and along S slope of
main divide.

40.04

Courses 1, 2, 35 + 36

As described by Survey-
or General.

Oril 2nd or 3rd rate
land mountainous 80.04

chrs

Thence I run,

O. $89^{\circ} 03'$ E on true
line O. Bdy sec $36^{\frac{1}{2}-30'}$

Along slope of main divide

27.00

Main divide b/w O. S. E +
U. U. W.

Descend along U. slope

feet from the divide
recrossing it on
the S. boundary of
sec 36.

- The country is
generally well timbered
with pinon juniper
and live oak and in
some places is cov-
ered with dense
brush principally
scrub oak and man-
zanita. Little if
any of the land along
this S. boundary is
agricultural

Tombstone Ariz.

Sec 23 1899

John T. Rockfellow
U.S. Dep. Surveyor

List of Names.

A List of the Names of the Individuals
employed by John H. Rockfellow
U. S. Deputy Surveyor, to assist in running, meas-
uring and marking the lines and corners described
in the foregoing Field Notes of the survey of the
South Boundary
of Tp 19 South
Range 29 East

of the Gila and Salt River Base and Meridian, in
the Territory of Arizona, showing the respective
capacities in which they acted.

M. J. O'Connor Chairman.
Martin Welsh Chairman.

Chairman.

Chairman.

Axeman.

R. H. Fowler Axeman.
F. W. Payne Flagman.

Final Oath of Assistants.

We hereby certify that we assisted John A. Blackfellow U. S. Deputy Surveyor, in re-surveying all those parts or portions of the

South Boundary of
T.P. 19 S. R 29 E.

of the Gila and Salt River Base and Meridian, in the Territory of Arizona, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said Survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States Surveyor General for Arizona.

Martin Walsh, Chainman.
M. H. O'Connor, Chainman.

Chainman.

Chainman.

Axeman.

Axeman.

Flagman.

Sworn to and subscribed before me, this 1st day of December, 1899.

John A. Blackfellow
Notary Public.

[SEAL.]

My Commission expires

Final Oath of U. S. Deputy Surveyor.

I, John A. Pickfleiss

U. S. Deputy Surveyor, do solemnly swear that in
pursuance of ~~instruction~~ received from ~~the~~ ^{the} ~~christ~~ ^{christ}
~~Johnson~~, United States Surveyor-General for Ari-

zona, bearing date of the 26th day of

October 1899, I have well, faithfully,
and truly, in my own proper person, and in
strict conformity with the instructions furnished by
the United States Surveyor-General for Arizona,
the Manual of Surveying Instructions, and the
laws of the United States, surveyed all those parts

or portions of the South Boundary

of the 19th South
Range 29th East

of the Gila and Salt River Base and Meridian, in
the Territory of Arizona, as are represented in the
foregoing Field Notes as having been surveyed by
me and under my direction; and I do further
solemnly swear that all the corners of said surveys
have been established and perpetuated in strict
accordance with the Manual of printed instructions,
the special instructions of the United States Sur-
veyor-General for Arizona, and in the specific

24

manner described in the field notes, and that the foregoing are the true Field Notes of such survey and should any fraud be detected I will suffer the penalty of perjury, under the provisions of an act of Congress approved August 8, 1846.

John A. Peck Fellow
U. S. Deputy Surveyor.

Sworn to and subscribed before me this 23rd day of December, 1899.

A. H. Emmanuel,
Clerk.

BOOK 1604